



US 20240222952A1

(19) **United States**

(12) **Patent Application Publication**
Chambon

(10) **Pub. No.: US 2024/0222952 A1**

(43) **Pub. Date: Jul. 4, 2024**

(54) **ELECTRONIC PROTECTION DEVICE FOR AN ELECTRICAL LOAD, POWER SUPPLY SYSTEM FOR AN ELECTRICAL LOAD AND METHOD FOR CONTROLLING SUCH A DEVICE**

H02H 1/00 (2006.01)

H02H 3/18 (2006.01)

H02H 11/00 (2006.01)

H03K 17/18 (2006.01)

(52) **U.S. Cl.**

CPC *H02H 3/08* (2013.01); *G01R 19/16538*

(2013.01); *H02H 1/0007* (2013.01); *H02H*

3/18 (2013.01); *H02H 11/003* (2013.01);

H03K 17/18 (2013.01)

(71) Applicant: **Schneider Electric Industries SAS**,
Rueil Malmaison (FR)

(72) Inventor: **Patrick Chambon**, Saint Martin
d'Heres (FR)

(73) Assignee: **Schneider Electric Industries SAS**,
Rueil Malmaison (FR)

(21) Appl. No.: **18/539,387**

(22) Filed: **Dec. 14, 2023**

(30) **Foreign Application Priority Data**

Jan. 4, 2023 (FR) 2300079

Publication Classification

(51) **Int. Cl.**

H02H 3/08 (2006.01)

G01R 19/165 (2006.01)

(57)

ABSTRACT

An electronic protection device for a load includes an arrangement of transistors in series with the load, that can be controlled into a state out of on and off states, an off state being from among first and second off states. The electronic protection device further includes: a current sensor; a control module connected to the current sensor and controlling the arrangement of transistors into its second off state if an intensity measured by the current sensor is above a first threshold; and a voltage sensor connected to the control module. The control module controls the arrangement of transistors into its on state if the voltage is above a voltage threshold and into its first off state if the intensity is below a second threshold.

