



US 20240178718A1

(19) **United States**(12) **Patent Application Publication**
MAKIDO et al.(10) **Pub. No.: US 2024/0178718 A1**(43) **Pub. Date: May 30, 2024**(54) **MOTOR****Publication Classification**(71) Applicant: **TOYOTA JIDOSHA KABUSHIKI**
KAISHA, Toyota-shi (JP)(51) **Int. Cl.**
H02K 5/20 (2006.01)
H02K 3/28 (2006.01)
H02K 5/10 (2006.01)(72) Inventors: **Yasuhiro MAKIDO**, Toyota-shi (JP);
Yuichiro Kanada, Toyota-shi (JP);
Shogo Kajimoto, Toyota-shi (JP);
Hideyuki Higashi, Okazaki-shi (JP);
Yukio Tsuchiya, Toyota-shi (JP)(52) **U.S. Cl.**
CPC **H02K 5/20** (2013.01); **H02K 3/28**
(2013.01); **H02K 5/10** (2013.01)(73) Assignee: **TOYOTA JIDOSHA KABUSHIKI**
KAISHA, Toyota-shi (JP)(57) **ABSTRACT**

A motor includes a rotor, a stator including a stator core and a coil, a housing, and a first annular member that provides sealing between a first end surface of the stator core in a direction of an axis of the stator core and an inner wall surface of the housing. The first annular member has first holes configured to be passed through by a refrigerant injected toward a first coil end of the coil, the first coil end protruding from the first end surface. The first annular member includes a first section in which at least two of the first holes are arranged in a circumferential direction of the first annular member at a first interval, and a second section in which at least two of the first holes are arranged in the circumferential direction at a second interval that is larger than the first interval.

(21) Appl. No.: **18/482,210**(22) Filed: **Oct. 6, 2023**(30) **Foreign Application Priority Data**

Nov. 29, 2022 (JP) 2022-190648

