




# Svelte

slides at <https://github.com/mvolkmann/talks>

**R. Mark Volkmann**  
Object Computing, Inc.  
<http://objectcomputing.com>  
Email: [mark@objectcomputing.com](mailto:mark@objectcomputing.com)  
Twitter: @mark\_volkman  
GitHub: mvolkmann



OCI | TRAINING



# What Is It?

- Alternative to web frameworks like React, Vue, and Angular
- A web application **compiler**, not a runtime library
  - implemented in TypeScript
  - compiles `.svelte` files to a single JavaScript file
  - no Svelte runtime **dependencies**, only **devDependencies**
- Doesn't use a virtual DOM
- Developed by **Rich Harris**
  - formerly at "The Guardian"; currently at "The New York Times"
  - previously created **Ractive** web framework - <https://ractive.js.org/>
    - used at "The Guardian"
    - inspired parts of Vue
  - created **Rollup** module bundler - <https://rollupjs.org/>
    - alternative to Webpack and Parcel



# An Example

- Since you are all experienced web developers, let's look at an example app so you can compare the look of the code to your current favorite web framework
- On to the classic ... todo app!

# Todo App ...

code and tests at  
<https://github.com/mvolkmann/svelte-todo>

**To Do List**

1 of 2 remaining Archive Completed

Add

☒ learn Svelte Delete

☐ build a Svelte app Delete

← a Todo component

```
src/main.js
import ToDoList from './ToDoList.svelte';
const app = new ToDoList({target: document.body});
export default app;
```



# ... Todo App ...

```
<script>
  import {createEventDispatcher} from 'svelte';
  const dispatch = createEventDispatcher();
  export let todo; // the only prop
</script>

<style>
  .done-true {
    color: gray;
    text-decoration: line-through;
  }
  li {
    margin-top: 5px;
  }
</style>

<li>
  <input
    type="checkbox"
    checked={todo.done}
    on:change={() => dispatch('toggleDone')}
  />
  <span class={'done-' + todo.done}>{todo.text}</span>
  <button on:click={() => dispatch('delete')}>Delete</button>
</li>
```

src/Todo.svelte

export makes it a prop

What is the name of this component?  
Can't tell.  
Names are assigned when other components import this one.

interpolation

# ... Todo App ...

```
<script>
  import Todo from './Todo.svelte';

  let lastId = 0;
  const createTodo = (text, done = false) => ({id: ++lastId, text, done});

  let todoText = '';
  let todos = [
    createTodo('learn Svelte', true),
    createTodo('build a Svelte app')
  ];

  $: uncompletedCount = todos.filter(t => !t.done).length;
  $: status = `${uncompletedCount} of ${todos.length} remaining`;

  function addTodo() {
    todos = todos.concat(createTodo(todoText));
    todoText = '';
  }

  const archiveCompleted = () => todos = todos.filter(t => !t.done);

  const deleteTodo = todoId => todos = todos.filter(t => t.id !== todoId);

  function toggleDone(todo) {
    const {id} = todo;
    todos = todos.map(t => t.id === id ? {...t, done: !t.done} : t);
  }
</script>
```

src/TodoList.svelte

Top-level variables ARE  
the component state!

reactive  
declarations

No methods,  
just functions.

Not really archiving in this  
simple implementation,  
just deleting.



# ... Todo App ...

```
<style>                                     src/ToDoList.svelte
  button {
    margin-left: 10px;
  }

  /* This removes bullets from a bulleted list. */
  ul.unstyled {
    list-style: none;
    margin-left: 0;
    padding-left: 0;
  }
</style>
```

# ... Todo App

```
<div>
  <h2>To Do List</h2>
  <div>
    {status}
    <button on:click={archiveCompleted}>Archive Completed</button>
  </div>
  <form on:submit|preventDefault>
    <input
      type="text"
      size="30"
      autofocus
      placeholder="enter new todo here"
      bind:value={todoText}
    />
    <button disabled={!todoText} on:click={addTodo}>
      Add
    </button>
  </form>
  <ul class="unstyled">
    {#each todos as todo}
      <Todo
        todo={todo}
        on:delete={() => deleteTodo(todo.id)}
        on:toggleDone={() => toggleDone(todo)}
      />
    {/each}
  </ul>
</div>
```

src/TodoList.svelte

not doing anything on submit

binds value of form element to a variable;  
simulates two-way data binding;  
provides current value and  
event handling for updating variable  
when user changes value

Mustache-style markup



# Logic in Markup

- Three approaches for conditional and iteration logic

- **React**

- uses JSX where logic is implemented by JavaScript code in curly braces

- **Angular and Vue**

- support framework-specific attributes for logic
  - ex. `ngIf`, `ngFor`, `v-if`, `v-for`, ...

- **Svelte**

- supports mustache-like custom syntax that wraps elements
  - ex. `{#if}` and `{#each}`
  - can wrap multiple elements without introducing a new, common parent

Why does it make sense to specify conditional and iteration logic INSIDE elements using attributes?

Imagine if you could do that with JavaScript functions.

```
doSomething(  
  arg1,  
  arg2,  
  if (arg1 > 10),  
  for (arg1 in someCollection));
```

Isn't that weird?

# Top Svelte Features

- Small bundle sizes
- File-based component definitions
- CSS scoped by default
- Clear place to put global CSS
- Easy component state management (reactivity)
- Easy app state management (stores)
- Easy way to pass data from components to descendant components (context)
- Reactive declarations



# Small Bundle Sizes

- Delivered code is much smaller, so loads faster in browsers
- Uses Rollup by default for module bundling, but can also use Webpack or Parcel
- Create production build with `npm run build`
- <https://www.freecodecamp.org/news/a-realworld-comparison-of-front-end-frameworks-with-benchmarks-2019-update-4be0d3c78075/>
  - gzipped app size in KBs

**Angular+ngrx: 134**  
**React+Redux: 193**  
**Vue: 41.8**  
**Svelte: 9.7**

# File-based Component Defs

- **Angular** uses classes
- **React** uses functions or classes
- **Vue** uses object literals
- **Svelte** doesn't use any JavaScript container
  - JavaScript, CSS, and HTML in source files are combined to form the component definition which automatically becomes the default export
  - name is associated when imported and must start uppercase
    - can't tell from looking at source file what names might be used
  - lowercase names are reserved
    - for predefined elements like those in HTML and SVG



# CSS

- Scoped by default
  - CSS specified in a component `style` tag is automatically scoped to the component
  - achieved by adding the same generated CSS class name, `svelte-hash`, to each rendered element of the component affected by these CSS rules
- Clear place for global CSS
  - `public/global.css`

# Easy Component State Mgmt.

("reactivity")

- Changes to top-level variables referenced in interpolations automatically cause those interpolations to be reevaluated
- Example

```
<script>
  let count = 0;
  const increment = () => count++;
</script>

<div>count = {count}</div>
<button on:click={increment}>+</button>
```

- Must assign a new value to trigger
  - pushing new elements onto an array doesn't do this

```
myArr = myArr.concat(newValue);
```

works

```
myArr = [...myArr, newValue];
```

works

```
// Alternative trick
myArr.push(newValue);
myArr = myArr;
```

works



# Easy App State Mgmt.

- “Stores” hold application state outside any component
- Alternative to using props or context to make data available in components
- Where to define?
  - for stores that should be available to any component, define and export them in a file like `src/stores.js` and import them from that file wherever needed
  - for stores that should only be available to descendants of a given component, define them in that component and pass them to descendants using props or context

# Kinds of Stores

- **Writable**
  - only kind that can be modified by components
- **Readable**
  - handle computing their data
  - components cannot modify
- **Derived**
  - derive data from current values of other stores



# Defining Writable Stores

stores.js

```
import {writable} from 'svelte/store';  
export const dogStore = writable([]);
```

initial value

```
export const fancyStore = writable(  
  initialValue,  
  async set => {  
    // Called when subscribe count goes from 0 to 1.  
    // Compute initial value and pass to set function.  
    const res = await fetch('/some/url');  
    const data = await res.json();  
    set(data);  
  
    return () => {  
      // Called when subscriber count goes to 0.  
    }  
  }  
);
```

using optional  
second argument

can calculate new value from current with  
`update(currentValue => newValue)`

# Using Stores

- Option #1 - **subscribe** method - very verbose!
- Option #2 - **\$** auto-subscription shorthand - much better!
  - variables whose names begin with **\$** must be stores
  - automatically subscribes when first used and unsubscribes when removed from DOM

```
<script>
  import {onDestroy} from 'svelte';
  import {dogStore} from './stores.js';
  let dogs;
  const unsubscribe = dogStore.subscribe(value => dogs = value);
  onDestroy(unsubscribe);
</script>
```

uses **subscribe** method

```
<!-- Use dogs in HTML. -->
```

```
<script>
  import {dogStore} from './stores.js';
</script>
```

uses auto-subscription

```
<!-- Use $dogStore in HTML. -->
```



# Easy Passing Data to Descendants

- Use “context”
- Alternative to props and stores for making data available in descendant components

```
import {getContext, setContext} from 'svelte';
```

- Ancestor components set context associated with the component

```
setContext(key, value);
```

- must be called during component initialization
- Descendant components get context from closest ancestor that has context with given key

```
const value = getContext(key);
```

- must be called during component initialization
- Keys can be any kind of value, not just strings
- Values can be any kind of value including functions and objects with methods

# Context Example

A.svelte

```
<script>
  import {setContext} from 'svelte';
  import B from './B.svelte';
  setContext('favorites', {color: 'yellow', number: 19});
</script>

<div>
  This is in A.
  <B />
</div>
```

## Output

```
This is in A.
This is in B.
This is in C.
favorite color is yellow
favorite number is 19
```

B.svelte

```
<script>
  import C from './C.svelte';
</script>

<div>
  This is in B.
  <C />
</div>
```

C.svelte

```
<script>
  import {getContext} from 'svelte';
  const {color, number} = getContext('favorites');
</script>

<div>
  This is in C.
  <div>favorite color is {color}</div>
  <div>favorite number is {number}</div>
</div>
```



# Reactive Declarations

- `$:` is a “labeled statement” with label name “`$`” that Svelte treats as a “reactive declaration”

Labeled statements can be used as targets of `break` and `continue` statements. It is not an error in JavaScript to use same label more than once in same scope.

- Add as a prefix on top-level statements that should be repeated whenever any referenced variables change
- Examples

```
$: average = total / count;  
$: console.log('count =', count);
```

like “computed properties” in Vue

great for debugging

when applied to an assignment to an undeclared variable the `let` keyword is not allowed

- Can apply to a block

```
$: {  
  // statements to repeat go here  
}
```

- Can apply to multiline statements like `if` statements

```
$: if (someCondition) {  
  // body statements  
}
```

executes if any variables referenced in condition or body change, but of course the body only executes when condition is true

# Outstanding Issues

- TypeScript support
  - it's coming, but not ready yet
  - <https://github.com/sveltejs/svelte/issues/1639>
- Popularity
  - perhaps Svelte will soon be considered the #4 most popular approach for building web apps
  - isn't easy to find developers that already know it
  - but it's very easy to learn and there is less to learn than other approaches



# Related Tools

- **Svelte VS Code extension**
- **Sapper** - <https://sapper.svelte.dev/>
  - “application framework powered by Svelte”
  - name may be a contraction of “Svelte” and “Application”
  - similar to Next and Gatsby
  - provides routing, server-side rendering, and code splitting
- **Svelte Native** - <https://svelte-native.technology/>
  - for implementing native mobile apps
  - based on nativescript-vue
  - community-driven project
- **Svelte GL** - <https://github.com/Rich-Harris/svelte-gl>
  - in-work Svelte version of Three.js
- **Svelte Testing Library** - <https://testing-library.com/docs/svelte-testing-library/intro>
- **Storybook** with Svelte - <https://storybook.js.org/docs/guides/guide-svelte/>



# Svelte Resources

- **"Rethinking reactivity"** - <https://www.youtube.com/watch?v=AdNJ3fydeao>
  - talk by **Rich Harris** at "You Gotta Love Frontend (YGLF) Code Camp 2019"
- **Home page** - <https://svelte.dev>
- **Tutorial** - <https://svelte.dev/tutorial>
- **API Docs** - <https://svelte.dev/docs>
- **Examples** - <https://svelte.dev/examples>
- **Online REPL** - <https://svelte.dev/repl>
  - great for trying small amounts of Svelte code; can save for sharing and submitting issues
- **Blog** - <https://svelte.dev/blog>
- **Discord chat room** - <https://discordapp.com/invite/yy75DKs>
- **GitHub** - <https://github.com/sveltejs/svelte>



# Conclusion

- Svelte is a worthy alternative to the current popular options of React, Vue, and Angular
- For more, see my long article
  - <https://objectcomputing.com/resources/publications/sett/july-2019-web-dev-simplified-with-svelte>