

Vuex

Vuex Overview

- Most popular state management library for Vue
- Developed by and maintained by the Vue team
- Somewhat similar to Redux
 - uses a single store to hold application state
- Vue CLI can install and configure Vuex
- To install when not using Vue CLI,
`npm install vuex`

Demo App

- To demonstrate use of Vuex, we'll build the classic Todo app
- Source files to review
 - `store.js`
 - `App.vue`
 - `TodoList.vue`
 - `Todo.vue`

To Do List

1 of 2 remaining Archive Completed

Add

☒ learn Vue Delete

☐ build a Vue app Delete

Store Setup

- Typically done in `src/store.js`
- Vue CLI creates this file
- Store has four parts
 - **state** - stores application data
 - **mutations** - modify state
 - **getters** - compute values based on state
 - **actions** - perform asynchronous actions (like REST calls) and invoke mutations
- Mutations do not need to treat state as immutable
 - except ... to set a specific array element,
rather than using syntax like `state.colors[2] = color`
use Array **splice** method like `state.colors.splice(2, 0, color)`
or Vue-supplied method **\$set** like `state.colors.$set(2, color)`

Mutations

- Only way to modify state
- Set of synchronous methods (no REST calls)
- Invoked in components by calls to `this.$store.commit`, not direct calls
- Within a mutation there are two ways to update a state property
 - for example, to change property `foo.bar` to `'baz'` use `state.foo.bar = 'baz'`
or
`Vue.set(state.foo, 'bar', 'baz')`
 - why would the second form ever be preferred?

store.js ...

```
import Vue from 'vue';
import Vuex from 'vuex';

Vue.use(Vuex);

let lastId = 0;
const createTodo = (text, done = false) => ({id: ++lastId, text, done});

export default new Vuex.Store({
  strict: true, // throws if state is modified outside a mutation
  state: {
    todoText: '',
    todos: [
      createTodo('learn Vue', true),
      createTodo('build a Vue app')
    ]
  },
});
```


... store.js

```
mutations: {  
  addToDo(state) {  
    const todo = createToDo(state.todoText);  
    state.todos.push(todo);  
    state.todoText = '';  
  },  
  archiveCompleted(state) {  
    state.todos = state.todos.filter(t => !t.done);  
  },  
  deleteToDo(state, todoId) {  
    state.todos = state.todos.filter(t => t.id !== todoId);  
  },  
  toggleDone(state, todo) {  
    const todoToToggle = state.todos.find(t => t.id === todo.id);  
    todoToToggle.done = !todoToToggle.done;  
  },  
  updateToDoText(state, todoText) {  
    state.todoText = todoText;  
  }  
},  
getters: {  
  uncompletedCount: state => state.todos.filter(t => !t.done).length  
}  
});
```

just removes completed todos

App.vue

- Registers store which “injects” access to it into all descendant components

```
<template>
  <TodoList/>
</template>

<script>
import TodoList from '../components/TodoList';
import store from '../store';

export default {
  name: 'App',
  components: {TodoList},
  store
};
</script>

<style>
body {
  font-family: sans-serif;
  padding-left: 10px;
}
</style>
```


State

- Any component can access with `this.$store.state`
- When many items are needed from the state, it is convenient to use `mapState` to make them accessible via computed properties
- `mapState` returns an object that should be spread into the `computed` property
- Example

```
computed: {  
  ...mapState({  
    todos: state => state.todos,  
    todoText: state => state.todoText  
  })  
},
```

will appear in
TodoList.vue

Committing Mutations

- To commit mutations from a component, call `this.$store.commit(mutationName, arg)`
- Example `this.$state.commit('toggleDone', todo);`
- Only a single argument can follow the mutation name
- To supply more than one value, pass an array or object containing all the values
- Any components that use the state affected by the mutation will be updated

mapMutations

- Another option is to use **mapMutations** to generate methods that make these calls for you
- Returns an object that should be spread into the **methods** property

- Example

```
methods: {  
  ...mapMutations([  
    'addTodo',  
    'archiveCompleted',  
    'deleteTodo',  
    'toggleDone',  
    'updateTodoText'  
  ])  
}
```

will appear in
TodoList.vue

- Allows `this.$state.commit('toggleDone', todo)` to be replaced by `this.toggleDone(todo)`

Getters

- Set of methods defined in the store that compute derived state from stored state

- Example

```
getters: {  
  uncompletedCount: state => state.todos.filter(t => !t.done).length;  
}
```

in store.js

- To retrieve value of this getter in a component, use `this.$store.getters.uncompletedCount()`

mapGetters

- Computed properties can be created inside a component that map to getters so they can be referred to with just computed property names
- **mapGetters** returns an object that should be spread into the `computed` property

- Example

```
computed: {  
  ...mapGetters ( [ 'uncompletedCount' ] )  
},
```

will appear in
TodoList.vue

TodoList.vue ...

```
<template>
  <div>
    <h2>To Do List</h2>
    <div>
      {{uncompletedCount}} of {{todos.length}} remaining
      <button @click="archiveCompleted">
        Archive Completed
      </button>
    </div>
    <form @submit.prevent>
      <input
        type="text"
        size="30"
        autofocus
        placeholder="enter new todo here"
        :value="todoText"
        @input="updateTodoText($event.target.value)"
      >
      <button
        :disabled="!todoText"
        @click="addTodo"
      >Add</button>
    </form>

    <ul class="unstyled">
      <li :key="todo.id" v-for="todo in todos">
        <Todo
          :todo="todo"
          :onDeleteTodo="() => deleteTodo(todo.id)"
          :onToggleDone="() => toggleDone(todo)"
        />
      </li>
    </ul>
  </div>
</template>
```


... TodoList.vue

```
<script>
import {mapGetters, mapMutations, mapState} from 'vuex';
import Todo from './Todo.vue';

export default {
  name: 'TodoList',
  components: {Todo},
  computed: {
    ...mapGetters(['uncompletedCount']),
    ...mapState({
      todos: state => state.todos,
      todoText: state => state.todoText
    })
  },
  methods: {
    ...mapMutations([
      'addTodo',
      'archiveCompleted',
      'deleteTodo',
      'toggleDone',
      'updateTodoText'
    ])
  }
};
</script>
```

```
<style scoped>
button:disabled {
  background-color: gray;
  color: white;
}

ul.unstyled {
  list-style: none;
  margin-left: 0;
  padding-left: 0;
}
</style>
```

Todo.vue

```
<template>
  <li>
    <input type="checkbox" :checked="todo.done" @change="onToggleDone">
    <span :class="doneClass">{{todo.text}}</span>
    <button @click="onDeleteTodo">Delete</button>
  </li>
</template>
```

```
<script>
export default {
  name: 'Todo',
  props: {
    done: Boolean,
    onDeleteTodo: {
      type: Function,
      required: true
    },
    onToggleDone: {
      type: Function,
      required: true
    },
    todo: {
      type: Object,
      required: true,
      validator(obj) {
        return obj.text &&
          obj.done !== undefined;
      }
    }
  },
}
```

```
  computed: {
    doneClass() {
      return 'done-' + this.todo.done;
    }
  };
</script>

<style scoped>
button {
  margin-left: 10px;
}

li {
  margin-top: 5px;

  .done-true {
    color: gray;
    text-decoration: line-through;
  }
}
</style>
```


Actions ...

- Set of methods that support asynchronous mutations
- Can make any number of REST calls and commit any number of mutations
- Invoked by calls to `this.$store.dispatch` in components, not direct calls
- Suppose we have REST services that support persisting todos in a database
- We can implement actions that make REST calls
- On success, they can commit mutations

... Actions

```
actions: {  
  async addTodo(context) {  
    const todo = createTodo(context.state.todoText);  
    const res = await fetch(SERVER_URL, {  
      method: 'POST',  
      headers: {'Content-Type': 'application/json'},  
      body: JSON.stringify(todo)  
    });  
    if (res.ok) {  
      context.commit('addTodo', todo);  
    } else {  
      alert('Error adding todo');  
    }  
  },  
  async deleteTodo(context, todoId) {  
    const res = await fetch(SERVER_URL + todoId, {method: 'DELETE'});  
    if (res.ok) {  
      context.commit('deleteTodo');  
    } else {  
      alert('Error deleting todo');  
    }  
  }  
}
```

add in
store.js

change addTodo mutation
to use the passed todo
instead of creating a new one

mapActions

- An alternative to calling `this.$state.dispatch` is to use `mapActions` to generate methods that make these calls for you
- Returns an object that should be spread into the `methods` property

- Example

```
methods: {  
  ...mapActions([  
    'addTodo',  
    'deleteTodo'  
  ])  
}
```

- Allows `this.$state.dispatch('addTodo', todo)` to be replaced by `this.addTodo(todo)`

Are Actions Needed?

- Any asynchronous processing, such as calling a REST service, can be done in an event handling method instead of an action
- When the asynchronous part completes, a synchronous Vuex commit can be performed
- If common event handling code is needed across multiple components, it can be implemented as a plain function that is imported into each of the components and invoked from their event handling methods.
- This is **simpler than using Vuex actions**

Modules

- The Vuex store can be split into multiple “modules”
- Each of these have their own state, getters, mutations, and actions.
- Modules can be further divided into sub-modules.
- Using a single store is far easier
- **ADD AN EXAMPLE**

vuex-easy

- Create a separate set of slides that show how the todo app can be implemented more easily with vuex-easy!
- **ADD MORE DETAIL**