Utilities

apachelogs.parse_apache_timestamp(*s*) [source]

Parse an Apache timestamp into a `datetime.datetime` object. The month name in the timestamp is expected to be an abbreviated English name regardless of the current locale.

```
>>> parse_apache_timestamp('[01/Nov/2017:07:28:29 +0000]')
datetime.datetime(2017, 11, 1, 7, 28, 29, tzinfo=datetime.timezone.utc)
```

Parameters: **s** (*str*) – a string of the form `DD/Mon/YYYY:HH:MM:SS +HHMM` (optionally enclosed in square brackets)

Returns: an aware `datetime.datetime`

Raises: ValueError – if `s` is not in the expected format

Log Format Constants

The following standard log formats are available as string constants in this package so that you don't have to keep typing out the full log format strings:

apachelogs.COMBINED = *'%h %l %u %t "%r" %>s %b "%{Referer}i" "%{User-Agent}i"'*

NCSA extended/combined log format

apachelogs.COMBINED_DEBIAN = *'%h %l %u %t "%r" %>s %O "%{Referer}i" "%{User-Agent}i"'*

Like `COMBINED`, but with `%O` (total bytes sent including headers) in place of `%b` (size of response excluding headers)

apachelogs.COMMON = *'%h %l %u %t "%r" %>s %b'*

Common log format (CLF)

apachelogs.COMMON_DEBIAN = *'%h %l %u %t "%r" %>s %O'*

Like `COMMON`, but with `%O` (total bytes sent including headers) in place of `%b` (size of response excluding headers)

stable

apachelogs.VHOST_COMBINED= *'%v:%p %h %l %u %t "%r" %>s %O "%{Referer}i" "%{User-Agent}i"'*

`COMBINED_DEBIAN` with virtual host & port prepended

apachelogs.VHOST_COMMON= *'%v %h %l %u %t "%r" %>s %b'*

`COMMON` with virtual host prepended

stable