

Koray Oksay

Why Securing Kubelet API is Critical for K8S Security?





Koray Oksay

Kubernetes Consultant

koray@kubermatic.com

@korayoksay


koksay

Who am I?

- Consultant / SRE / Instructor @Kubermatic
- Working remotely from Istanbul
- Interested in Linux, Kubernetes, and cloud technologies
- CKA | CKAD | CKS | RHCE
- Linux Foundation Trainer for CK.*



Kubernetes Architecture Recap






Kubelet

- By default runs on port 10250
- <= Getting the PodSpecs From the kubeapi-server
- => Fetching logs for pods
- => Attaching (usually through kubect1) to running pods
- => Providing kubectl port-forward





SHODAN Explore Downloads Pricing & kubernetes

kubernetes port:10250

Q

TOTAL RESULTS

164

TOP COUNTRIES



China	133
United States	6
Japan	5
Germany	4
Korea, Republic of	3
More	

TOP ORGANIZATIONS

TOP ONGANIZATIONS	
CHINANET HUNAN PROVINCE NETWORK	79
China Mobile Communications Corporation	25
Allyun Computing Co., LTD	8
CHINANET Hunan province network	6
Amazon Technologies Inc.	4
More	

₩ View Report Wiew on Map

Product Spotlight: Free, Fast IP Lookups for Open Ports and Vulnerabilities using InternetDB

61.109.216.232

Sejong Telecom

Korea, Republic of, Seoul

devops

SSL Certificate

Issued By:
|- Common Name:
host-172-16-2-219-ca@1679539544

Issued To:

|- Common Name: host-172-16-2-210@1679539545

Supported SSL Versions: TLSv1.2

34.239.165.141

ec2-34-239-165-141.compute-1.am azonaws.com

Amazon Technologies Inc.

United States, Ashburn

cloud de

devops

self-signed

Issued By: |- Common Name: ip-172-20-210-221.ec2.internal@1530610450

Issued To: |- Common Name:

ip-172-20-210-221.ec2.internal@1530610450

Supported SSL Versions: TLSv1.2 HTTP/1.1 404 Not Found Content-Type: text/plai

Content-Type: text/plain; charset=utf-8 X-Content-Type-Options: nosniff Date: Sun, 16 Apr 2023 05:23:03 GMT Content-Length: 19

Kubernetes:

Node #1:

Name: kube-apiserver-host-172-16-2-210 Container #1:

Name: kube-apiserver Image: k8s.gcr.io/kube...

HTTP/1.1 404 Not Found
Content-Type: text/plain; charset=utf-8
X-Content-Type-Options: nosniff

Date: Sun, 16 Apr 2023 02:46:50 GMT Content-Length: 19

Kubernetes:

Node #1:

Name: kube-proxy-ip-172-20-210-221.ec2.internal Container #1: Name: kube-proxy


Image: gcr.io/goo...

API documentation?

- Kubelet API is not documented
- Code can be checked

```
grep "Path(" server.go
       root := getURLRootFath(path)
               Path("/pods").
                ws. Path("/checkpoint"). Produces(restful.MIME_JSON)
                Path("/run")
                Path("/exec")
                  th("/attach")
                Path("/portForward")
                Path("/containerLogs")
                Path("/runningpods/").
                ws.Path(logsPath)
       ws := new(restful.WebService).Path(pprofBasePath)
func getURLRootPath(path string) string {
```









★ koray@kubermatic.com

@korayoksay

(7) koksay