

Bootstrap Assignment

Question 1: Spotify-style Bootstrap Navbar (Collapsible)

Create a Bootstrap Navbar for a music playlist app like Spotify, including links for Home, Playlists, and Profile. Make sure it collapses into a hamburger menu on mobile.

navbar.html

```
<!DOCTYPE html>
<html>
<head>
  <title>Spotify Style Navbar</title>
  <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/css/bootstrap.min.css" rel="stylesheet">
</head>
<body>

  <nav class="navbar navbar-expand-lg navbar-dark" style="background-color:#121212;">
    <div class="container-fluid">
      <a class="navbar-brand" href="#" style="color:#1db954; font-weight:bold;">BeatStream</a>

      <button class="navbar-toggler" type="button"
        data-bs-toggle="collapse" data-bs-target="#navbarNav"
        aria-controls="navbarNav" aria-expanded="false" aria-label="Toggle navigation">
        <span class="navbar-toggler-icon"></span>
      </button>

      <div class="collapse navbar-collapse" id="navbarNav">
        <ul class="navbar-nav ms-auto">
          <li class="nav-item">
            <a class="nav-link active" href="#">Home</a>
          </li>
          <li class="nav-item">
            <a class="nav-link" href="#">Playlists</a>
          </li>
          <li class="nav-item">
            <a class="nav-link" href="#">Profile</a>
          </li>
        </ul>
      </div>
    </div>
  </nav>

  <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/js/bootstrap.bundle.min.js"></script>
</body>
</html>
```

Explanation: `navbar-expand-lg` keeps the links in a row on large screens but automatically collapses them below the `lg` breakpoint. The `navbar-toggler` button (the hamburger icon) becomes visible on small screens and, via `data-bs-toggle="collapse"` and `data-bs-target="#navbarNav"`, toggles the visibility of the `#navbarNav` div containing the Home, Playlists, and Profile links — this collapse behavior is handled entirely by Bootstrap's bundled JavaScript, no custom script needed.

Question 2: Flipkart-style Bootstrap Product Card

Design a Bootstrap Card to display a Flipkart-style product preview with an image, product name, price, and a 'Buy Now' button.

product-card.html

```
<!DOCTYPE html>
<html>
<head>
  <title>Flipkart Style Bootstrap Card</title>
  <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/css/bootstrap.min.css" rel="stylesheet">
</head>
<body>

  <div class="container mt-4">
    <div class="card" style="width: 18rem;">
      
      <div class="card-body">
        <h5 class="card-title">Wireless Bluetooth Headphones</h5>
        <p class="card-text fw-bold text-success">₹1,499</p>
        <a href="#" class="btn btn-primary w-100">Buy Now</a>
      </div>
    </div>
  </div>

</body>
</html>
```

Explanation: Bootstrap's `card`, `card-img-top`, `card-body`, `card-title`, and `card-text` classes structure the product image, name, and price cleanly with built-in spacing and borders. The `btn btn-primary w-100` class on the "Buy Now" link styles it as a full-width blue action button, similar to an e-commerce "Buy Now" call-to-action.

Question 3: BookMyShow-style Bootstrap Carousel (Movie Posters)

Build a Bootstrap Carousel that cycles through 3 movie posters, each with a caption below like BookMyShow's featured movies section.

movie-carousel.html

```
<!DOCTYPE html>
<html>
<head>
  <title>BookMyShow Style Carousel</title>
  <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/css/bootstrap.min.css" rel="stylesheet">
</head>
<body>

  <div id="movieCarousel" class="carousel slide" data-bs-ride="carousel">
    <div class="carousel-indicators">
      <button type="button" data-bs-target="#movieCarousel" data-bs-slide-to="0" class="active"></button>
      <button type="button" data-bs-target="#movieCarousel" data-bs-slide-to="1"></button>
      <button type="button" data-bs-target="#movieCarousel" data-bs-slide-to="2"></button>
    </div>

    <div class="carousel-inner">
      <div class="carousel-item active">
        
        <div class="carousel-caption d-none d-md-block">
          <h5>Pathaan</h5>
          <p>Action, Thriller</p>
        </div>
      </div>
    </div>
  </div>
```

```

</div>

<div class="carousel-item">
  
  <div class="carousel-caption d-none d-md-block">
    <h5>Jawan</h5>
    <p>Action, Drama</p>
  </div>
</div>

<div class="carousel-item">
  
  <div class="carousel-caption d-none d-md-block">
    <h5>Animal</h5>
    <p>Action, Crime</p>
  </div>
</div>
</div>

<button class="carousel-control-prev" type="button" data-bs-target="#movieCarousel" data-bs-
slide="prev">
  <span class="carousel-control-prev-icon"></span>
</button>
<button class="carousel-control-next" type="button" data-bs-target="#movieCarousel" data-bs-
slide="next">
  <span class="carousel-control-next-icon"></span>
</button>
</div>

<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/js/bootstrap.bundle.min.js"></script>
</body>
</html>

```

Explanation: The carousel and carousel-inner wrapper, along with three carousel-item divs (the first marked active), let Bootstrap's JavaScript auto-cycle through the three movie posters because of data-bs-ride="carousel". Each slide has a carousel-caption div containing the movie title and genre, which Bootstrap overlays near the bottom of the poster image — mirroring how BookMyShow shows a title and short caption under/over each featured movie banner.

Question 4: Zomato-style Bootstrap Review Form

Create a Bootstrap Form for a Zomato-style restaurant review: include fields for name, rating (1-5 stars), and a review message, along with a submit button.

review-form.html

```

<!DOCTYPE html>
<html>
<head>
  <title>Zomato Style Review Form</title>
  <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/css/bootstrap.min.css" rel="stylesheet">
</head>
<body>

  <div class="container mt-4" style="max-width: 500px;">
    <h4>Write a Review</h4>
    <form>

      <div class="mb-3">
        <label for="name" class="form-label">Your Name</label>
        <input type="text" class="form-control" id="name" placeholder="Enter your name">
      </div>

```

```

<div class="mb-3">
  <label for="rating" class="form-label">Rating</label>
  <select class="form-select" id="rating">
    <option value="5">★★★★★ (5)</option>
    <option value="4">★★★★☆ (4)</option>
    <option value="3">★★★☆☆ (3)</option>
    <option value="2">★★☆☆☆ (2)</option>
    <option value="1">★☆☆☆☆ (1)</option>
  </select>
</div>

<div class="mb-3">
  <label for="review" class="form-label">Review</label>
  <textarea class="form-control" id="review" rows="4" placeholder="Share your experience...">
</textarea>
</div>

  <button type="submit" class="btn btn-danger">Submit Review</button>
</form>
</div>

</body>
</html>

```

Explanation: The form uses Bootstrap's `form-control` class for the text input and textarea, and `form-select` for the star-rating dropdown, giving all fields consistent styling and spacing automatically via `mb-3`. The submit button uses `btn btn-danger`, a red tone in line with Zomato's brand color, to visually stand out as the primary action.

Question 5: Food Delivery Filter Buttons (Active State)

Use Bootstrap Buttons to create a row of filter buttons (e.g., 'All', 'Veg', 'Non-Veg', 'Desserts') for a food delivery app homepage. Highlight the selected filter using the 'active' class.

filter-buttons.html

```

<!DOCTYPE html>
<html>
<head>
  <title>Food Delivery Filter Buttons</title>
  <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/css/bootstrap.min.css" rel="stylesheet">
</head>
<body>

  <div class="container mt-4">
    <div class="btn-group" role="group" aria-label="Food filters">
      <button type="button" class="btn btn-outline-danger active">All</button>
      <button type="button" class="btn btn-outline-danger">Veg</button>
      <button type="button" class="btn btn-outline-danger">Non-Veg</button>
      <button type="button" class="btn btn-outline-danger">Desserts</button>
    </div>
  </div>

  <script>
    // Simple script to move the 'active' class to whichever filter button is clicked
    const filterButtons = document.querySelectorAll('.btn-group .btn');
    filterButtons.forEach(btn => {
      btn.addEventListener('click', () => {
        filterButtons.forEach(b => b.classList.remove('active'));
        btn.classList.add('active');
      });
    });
  </script>

```

```
</body>  
</html>
```

Explanation: The four filter options are grouped inside a `btn-group` using the `btn btn-outline-danger` style, giving them a consistent red-outlined look matching a food app's theme. The `active` class is what visually highlights the selected filter (filling in the background color); it starts on "All" by default. A short JavaScript snippet listens for clicks on any button in the group, removes `active` from all of them, and adds it back only to the clicked button — so only one filter appears selected at a time.