

SQL Assignment — Group 2: Restaurants

Table - CRUD Operations

Group 2 — Restaurants Table: CRUD Operations

1. CREATE Restaurants + INSERT 5 rows

Create a SQL table called `Restaurants` with columns: `id` (INT, auto-increment), `name` (VARCHAR), `cuisine` (VARCHAR), `rating` (DECIMAL), and `city` (VARCHAR). Insert 5 sample restaurants, each with a different cuisine and rating.

```
CREATE TABLE Restaurants (  
  id      INT AUTO_INCREMENT PRIMARY KEY,  
  name    VARCHAR(100),  
  cuisine VARCHAR(50),  
  rating  DECIMAL(2,1),  
  city    VARCHAR(50)  
);  
  
INSERT INTO Restaurants (name, cuisine, rating, city)  
VALUES  
  ('Spice Villa',      'North Indian', 4.2, 'Ahmedabad'),  
  ('Sushi Central',    'Japanese',    4.6, 'Ahmedabad'),  
  ('Pasta Palace',     'Italian',    3.9, 'Mumbai'),  
  ('Taco Fiesta',      'Mexican',    3.3, 'Delhi'),  
  ('Dragon Wok',       'Chinese',    4.1, 'Ahmedabad');
```

Explanation: Each of the 5 rows uses a different `cuisine` value and a distinct `rating`, spanning both above and below 4.0 and 3.5 so later filtering questions (Q2-Q4) have meaningful results to work with. `id` is left out of the `INSERT` list since it auto-increments.

2. UPDATE rating of 'Spice Villa'

Write a SQL `UPDATE` statement to change the rating of the restaurant named 'Spice Villa' to 4.7.

```
UPDATE Restaurants  
SET rating = 4.7  
WHERE name = 'Spice Villa';
```

Explanation: The `WHERE name = 'Spice Villa'` clause ensures only the row matching that exact restaurant name is updated. Without a `WHERE` clause, `UPDATE` would change the rating for every row in the table.

3. DELETE restaurants with rating < 3.5

Delete all restaurants from the `Restaurants` table where the rating is less than 3.5.

```
DELETE FROM Restaurants  
WHERE rating < 3.5;
```

Explanation: This removes every row where the `rating` column is below 3.5 — in the sample data above, that would delete "Taco Fiesta" (3.3). As with any `DELETE`, it's good practice to first run the equivalent `SELECT * FROM Restaurants WHERE rating < 3.5;` to preview exactly which rows will be removed.

4. SELECT with WHERE + LIMIT

Use a *SELECT* query with *WHERE* and *LIMIT* to fetch the top 2 restaurants in the city 'Ahmedabad' with a rating above 4.0.

```
SELECT *  
FROM Restaurants  
WHERE city = 'Ahmedabad' AND rating > 4.0  
ORDER BY rating DESC  
LIMIT 2;
```

Explanation: The `WHERE` clause combines two conditions with `AND` — city must be Ahmedabad and rating must exceed 4.0. `ORDER BY rating DESC` sorts the matching rows from highest to lowest rating so that "top" restaurants come first, and `LIMIT 2` restricts the result set to just the first two rows after sorting.