

DATA SHEET

PRODUCT DESCRIPTION

Oils are severely refined hydro-cracked / hydro-treated oils with highest degree of purity and are stabilized with suitable additives for oxidation/UV stability. These oils are suitable for Pharmaceutical, Cosmetics and Food Industries, for Direct & Indirect Food Contact. The below oils are also recommended for Polystyrene., Thermoplastic industry.

Quality/Approvals: Oils are fully conforming to the requirements of US FDA 21 CFR 172. 878 for use in or on Food for Human Consumption and USFDA 21 CFR 178.3620 (a) for use as a component of Non-Food Articles intended for use in contact with food for Human Consumption.

Oils surpass the current requirements of NF, Indian Pharmacopoeia (IP), U.S. Pharmacopoeia (USP), British Pharmacopoeia (BP), and European Pharmacopoeia (EP).

Packaging Options: 200 Kg. plastic drum

TYPICAL SPECIFICATIONS OF MINERAL OILS

Sr. NO.	TestDescription	Test Method	WOP70
1	Appearance	Visual	Transparent clear, colorless, odorless liquid freefrom suspended impurities
2	Colour,Saybolt	ASTM D156	+30
3	Density @ 25 °C, gm/ml	ASTM D1298	>0.820
4	Kin. Viscosity@40°C, cSt	ASTM D445	11-14
5	ViscosityinSSU	ASTM D445	70
6	FlashPoint°Cmin	ASTMD92	150
7	Pour Point, °C,max	ASTMD97	-15
8	Carbonisable Substance	USP	Passes
9	Acidity / Alkalinity	USP/BP/IP	Passes
10	Sulphur Compounds	USP/BP/IP	Passes
11	Solid Paraffin's	USP/BP/IP	Passes
12	Poly nuclear compounds	FDA 21CFR 172. 878	Passes
13	ConformstoUSFDA21CFR 172.878&178.3620(a)	USFDA/USP	Passes
14	ConformstoUSP/NF	USP/NF	Passes
15	ConformstoIP/BP	IP/BP	Passes

Customized Mineral Oil as per customer's requirement are also offered.

+58 241 8321517/ +58 412 765 2493

ventas@noumatrading.com.ve

www.noumatrading.com.ve

Zona Industrial Municipal Norte Avda. este oeste

Galpón 67-200, Valencia- Edo. Carabobo.

