ISA5810 DM2026 Lab 1 — Master Notebook Questions

Fill in this file as you work through DM2026-Lab1-Master.ipynb. Submit this completed file converted to PDF together with the rest of your Lab 1 work.

Please do not change the style of this document.

Question numbers 1–10 follow the same order as the notebook (top to bottom).

Student Information

Please complete the fields below. For **English Name** and **Chinese Name**, you may fill in **only one** if you do not have the other.

- **English Name: Nuran Daniel Koller**
- **Chinese Name:**
- **Email: kollenur@students.zhaw.ch**
- **Student ID: J154020003**
- **University: NSYSU**

Instructions

These questions go with the Master Jupyter notebook (DM2026-Lab1-Master.ipynb). Each question is tied to a specific notebook section. Open the notebook, find **Question N (take home)**, and write your answer here.

We **strongly** suggest running the notebook to learn the lab, but the TAs will **not** audit whether you executed every cell to answer the questions in this document.

How to answer each question

1. Find the **notebook section** listed under the question (use the Table of Contents if needed).
2. Read the task; change parameters when asked (e.g. stop_words, thresholds, k, minSup).
3. Write a clear answer in the **Answer** space below each question.
4. Leave the question text unchanged; write only in the answer and disclosure fields.

Sources, honesty, and AI use

Acceptable vs. Unacceptable AI Usage: Generative AI should serve as an interactive tutor to guide your understanding, not as an automated solver completing the assignment for you.

- **Permitted (AI as Guide & Editor):**
  - Asking AI to explain unfamiliar theoretical concepts, discuss algorithmic trade-offs, or troubleshoot runtime errors in the notebook.
  - Polishing the grammar, phrasing, and readability of your own original, self-written drafts.

- **Prohibited (AI as Solver):**
  - Copying assignment questions directly into an AI tool to generate answers.
  - Using AI to fabricate experimental results or observations without executing the code in DM2026-Lab1-Master.ipynb.
  - Submitting machine-generated prose wholesale.

- **External material:** If you use websites, books, papers, or documentation beyond the notebook, cite them with **clickable links** (or DOI/ISBN when no URL exists).

- **When AI was used:** Your answer is acceptable if you (1) **disclose** AI use and (2) include **at least one external link** that validates the information in your answer (official docs, textbook, paper, or reputable tutorial — not the AI chat alone as the only source).

- **When AI was not used:** You may write "No" under **AI used** or leave it blank only if you truly did not use AI for that question. References are still encouraged if you looked anything up.

Under each question, complete:

- **AI used for this answer:** Yes / No
- **If yes, how:** (e.g. brainstorming, grammar, concept explanation)
- **External references (links):** *(required when AI = Yes; encouraged otherwise)*

Write in English. Keep answers concise and specific.

Questions

Question 1: Data Filtering & Domain Relevance

Notebook: Section 3.2 — Question 1 (take home)

Task: Filter the dataframe **X** for the category **sci.med** and check its length.

Questions:

1. How many documents are in this specific category?
2. From a data mining perspective, why is isolating specific categories a crucial first step before applying algorithms like frequent pattern mining?

Answer:

1. 592

2. • **Speeds up computation:** Frequent pattern mining is computationally expensive. Reducing the data size by focusing only on relevant categories saves massive amounts of memory and processing time.

• **Prevents "pattern flooding":** If you throw all data into the algorithm, it will find millions of obvious or useless rules (e.g., "people who buy food also buy grocery bags"). Isolating categories helps you find specific, hidden insights.

• **Solves the "rare item" problem:** In a huge dataset, interesting patterns in smaller categories get drowned out by dominant categories. Separating them ensures smaller, valuable trends aren't ignored.

• **Improves data quality:** Different categories often have different data structures or errors. Focusing on one category at a time makes data cleaning and preparation much easier.

AI used for this answer: Yes

If yes, how: formulate my text

External references (links):

Question 2: Handling Missing Data

Notebook: Section 4.1 — Question 2 (take home) (after the **dropna()** demonstration)

Task: In Section 4.1, a dummy record with a missing value is injected and then removed using the **dropna()** function.

Question: If 40% of documents were missing the **category_name** label, why would simply dropping these rows (with **dropna()**) be a flawed data mining strategy? Name one objective alternative so the text data can still be utilized.

Answer:

• **Biased Data:** The missing labels might not be accidental. If a specific category (like "Spam" or "Private Texts") is harder to label, deleting those rows means your model will never learn to recognize them.

• **Loss of Information:** You throw away 40% of your data. Even without a label, the text itself contains valuable words, patterns, and features that can help the model learn the general structure of the language.

AI used for this answer: Yes

If yes, how: to formulate thoughts

External references (links):

Question 3: Data Sampling Risks

Notebook: Section 5.1 — Question 3 (take home)

Task: In Section 5.1, the code uses **X_sample = X.sample(n=1000)** to create a subset. Compare the bar chart of the original category distribution to the sampled distribution.

Questions:

1. Do the exact category proportions perfectly match the original?
2. What is the specific risk of simple random sampling on a highly imbalanced dataset?

Answer:

1. No, the exact category proportions do not perfectly match the original.
2. Random variation: Simple random sampling introduces natural statistical noise (sampling error).
   Approximation: While the sample (orange bars) roughly mirrors the overall shape of the original data (blue bars), the exact ratios between the categories fluctuate slightly.

AI used for this answer: Yes

If yes, how: to formulate my reply

External references (links):

Question 4: Text Vectorization and Matrix Sparsity

Notebook: Section 5.3 — Question 4 (take home)

Task: In Section 5.3, the **CountVectorizer** converts text into a document-term matrix using **stop_words='english'**. Change this parameter to **stop_words=None** and re-run the cell to check the shape of **X_counts**.

Questions:

1. Does the total number of features (columns) increase or decrease?
2. Since stopwords are highly common words that appear in almost all documents, what effect does adding them back have on the overall sparsity (the percentage of zeros) of the matrix?

Answer:

1. Increase

2. the overall sparsity of the matrix decreases, it becomes more dense

AI used for this answer: No

If yes, how:

External references (links):

Question 5: Feature Selection — Variance Thresholding

Notebook: Section 5.3.1 — Question 5 (take home)

Task: In the variance filtering section, re-run **variance_filter** using threshold values **threshold = 0.0, threshold = 0.01, and threshold = 0.05**. Record the number of features marked as **keep == True**.

Questions:

1. What happens to the total size of the vocabulary as the variance threshold increases from 0.0 to 0.05?

2. In terms of document frequency, what kinds of words have variance close to zero and are eliminated first?
3. Why is eliminating near-zero variance features considered a safe way to reduce dimensionality without harming model accuracy?

Answer:

1. **Threshold Number of terms kept (keep == True)**

0.0	35482
0.01	5089
0.05	1491

2. Zooid, zool, zvi
3. These are values that appear almost everywhere the same and therefore have no “real” value

AI used for this answer: No

If yes, how:

External references (links):

Question 6: Feature Correlation — Linear (Pearson) vs. Monotonic (Spearman)

Notebook: Section 5.3.2 — Question 6 (take home)

Task: Run the correlation filter against the binary indicator for the **comp.graphics** class. Inspect the top 10 features sorted by **pearson_r** and compare them to the top 10 features sorted by **spearman_r**.

Questions:

1. Are the top-correlated words generic stop words or domain-specific terminology for graphics?
2. What is the mathematical difference in what **Pearson** correlation measures versus what **Spearman** rank correlation measures?
3. In what specific scenario would a word have a high **Spearman** rank correlation with a topic, but a significantly lower **Pearson** correlation?

Answer:

1. The top correlating words should be domain-specific words. Generic stop words appear in different categories.
2. Pearson explains if two values have an approximate linear correlation. Spearman recognizes correlation also only if they go along the same direction.
3. If that document has a lot of graphic words like “image”, “jpeg”, “gif”.

AI used for this answer: No

If yes, how:

External references (links):

Question 7: Frequent Pattern Mining — Algorithm & Parameter Dynamics

Notebook: Section 5.4.2 — Question 7 (take home)

Task: In the Frequent Pattern Mining section, run **Top-K FAE** with **k = 100 and k = 500**. Then, run **MaxFPGrowth** using minimum support thresholds **minSup=9 and minSup= 3**.

Questions:

1. How does decreasing **minSup** (from 9 to 3) in **MaxFPGrowth** affect the execution runtime and the total number of discovered patterns?
2. How does the parameter k in **Top-K FAE** differ fundamentally from **minSup** in **MaxFPGrowth** when deciding which patterns to keep?
3. Why are "maximal" frequent patterns structurally more concise than standard frequent patterns?

Answer (1) — Runtime and pattern count when lowering minSup: finds more patterns but needs more time due to more combinations

Answer (2) — Top-K k vs MaxFPGrowth minSup: gives the max count of result. Min sup is the minimum on how often it needs to appear.

Answer (3) — Maximal vs standard frequent patterns: MaxFPGrowth only keeps mainly the biggest combination

AI used for this answer: No

If yes, how:

External references (links):

Question 8: Dimensionality Reduction — Motivation

Notebook: Section 5.5 — Question 8 (take home) (before PCA/t-SNE code)

Task: After text vectorization, the **X_counts** matrix creates tens of thousands of distinct features (words).

Questions:

1. If we want to visually map how these documents group by category on a scatter plot, why is it mathematically and visually impossible to plot the raw **X_counts** matrix directly?
2. What specific category of data mining algorithms (referenced in the helper files) must be applied first?

Answer:

1. Each document would be a point in the calculation, therefore you would have way too many dimensions for a diagram
2. PCA, t-SNE, UMAP is used to create from a datapile human readable diagrams

AI used for this answer: Yes / No

If yes, how:

External references (links):

Question 9: Dimensionality Reduction — Linear (PCA) vs. Non-linear Manifolds (t-SNE/UMAP)

Notebook: Section 5.5 — Question 9 (take home) (after 2D/3D plots)

Task: In the 2D/3D Dimensionality Reduction section, compare the scatter plot projection generated by **PCA** against that generated by **t-SNE** or **UMAP**.

Questions:

1. Which method **(PCA or t-SNE/UMAP**) shows distinct, separated cluster islands for the 4 document categories, and which shows heavy overlap around the center?
2. Why does **PCA** struggle to separate high-dimensional text categories compared to **t-SNE** or **UMAP**?
3. Why must data analysts be careful not to over-interpret the physical distance between separate clusters in a **t-SNE** plot?

Answer:

1. Looking at the diagrams, t-SNE and UMAP shows distinct patterns. t-SNE seems to be working best for the center.

2. Words with the biggest variation are not necessarily the ones that can differentiate categories
3. This means that points within a group are often meaningfully close together, while separate groups may appear far apart despite not being truly different in the original data, and the shape, size, and distance between clusters can change depending on the settings and random initialization

AI used for this answer: Yes

If yes, how: to formulate my answer

External references (links):

Question 10: One-Hot Binarization

Notebook: Section 5.6 — Question 10 (take home)

Task: In Section 3.1, examine **X['category']** (integers 0, 1, 2, 3). Then look at the output of **LabelBinarizer** in Section 5.6, where each category is converted into a binary vector (e.g., [1, 0, 0, 0]).

Questions:

1. How many binary columns are created to represent the 4 categories?
2. If an algorithm (like linear regression or KNN) is given the raw integer column **(0, 1, 2, 3)** as input, what false mathematical assumption does it make about the categories?
3. How does one-hot binarization eliminate this false assumption?

Answer:

1. Each category (0, 1, 2, and 3) gets its own dedicated column where a 1 indicates the presence of that category and a 0 indicates its absence.
2. Order/Ranking: It assumes that the categories have a natural sequence or ranking (e.g., category 3 is "greater" or "higher" than category 1).
   Distance/Magnitude: It assumes that the mathematical distance between categories is meaningful. For example, it assumes that the difference between category 0 and 1 is the same as the difference between category 2 and 3, or that category 2 is "twice" the value of category 1.
3. One-hot binarization eliminates these assumptions by treating each category as an independent, orthogonal dimension.

AI used for this answer: No

If yes, how:

External references (links):
