

Task:5

1. In a MongoDB collection named playlists (think Spotify), use the \$set operator to update the 'genre' field to 'Chill' for the playlist with name 'Evening Vibes'.

Ans:

```
db.playlists.updateOne(
  { name: "Evening Vibes" },
  {
    $set: {
      genre: "Chill"
    }
  }
);
```

2. For a collection called restaurants (Zomato-style), remove the

'temporaryOffer' field from all documents where the offer has expired using the \$unset operator.

Ans:

```
db.restaurants.updateMany(  
  { offerExpired: true },  
  {  
    $unset: {  
      temporaryOffer: ""  
    }  
  }  
);
```

3. Using the \$push operator, add a new song 'Calm Waters' to the 'songs' array of the playlist document with _id: 101 in your playlists collection

Ans:

```
db.playlists.updateOne(  
  { _id: 101 },  
  {  
    $push: {  
      songs: "Calm Waters"  
    }  
  }  
);
```

4. In a Flipkart-like products collection, use the \$addToSet operator to ensure the tag 'trending' is added only once to the 'tags' array for the product with SKU 'F12345', even if you run the update multiple times.

Ans:

```
db.products.updateOne(  
  { SKU: "F12345" },
```

```
{
  $addToSet: {
    tags: "trending"
  }
}
);
```

5. Simulate a flash sale: in your products collection, use the \$inc operator to decrease the 'stock' field by 1 for the product with name 'Wireless Earbuds' every time a purchase is made.

Ans:

```
db.products.updateOne(
{
  name: "Wireless Earbuds",
  stock: { $gt: 0 }
})
```

```
},  
{  
  $inc: {  
    stock: -1  
  }  
}  
);
```