

Node: professional projects

E-commerce Website,

Create an Express Server

```
mkdir shop-backend
```

```
cd shop-backend
```

```
npm init -y
```

```
npm install express
```

```
server.js
```

```
const express = require("express");
```

```
const app = express();
```

```
app.use(express.json());
```

```
const products = [
```

```
  { id: 1, name: "Laptop", price: 50000 },
```

```
{ id: 2, name: "Mobile", price: 20000 },  
{ id: 3, name: "Headphones", price: 2000  
}  
];
```

```
app.get("/products", (req, res) => {  
  res.json(products);  
});
```

```
app.listen(3000, () => {  
  console.log("Server running on port  
3000");  
});
```

Create addToCart Function

```
let cart = [];
```

```
function addToCart(productId, quantity) {  
  const item = cart.find(i => i.productId ===  
productId);  
  
  if (item) {  
    item.quantity += quantity;  
  } else {  
    cart.push({ productId, quantity });  
  }  
}
```

Create /cart/total Endpoint

```
app.get("/cart/total", (req, res) => {  
  let total = 0;  
  
  cart.forEach(item => {
```

```
const product = products.find(p => p.id  
=== item.productId);
```

```
if (product) {  
    total += product.price * item.quantity;  
}  
});
```

```
const deliveryCharge = total * 0.05;
```

```
res.json({  
    subtotal: total,  
    deliveryCharge,  
    finalTotal: total + deliveryCharge  
});  
});
```

Create project search endpoint

```
app.get("/products/search", (req, res) => {  
  const search = req.query.name || "";
```

```
  const result = products.filter(product =>
```

```
    product.name.toLowerCase().includes(search.toLowerCase())  
  );
```

```
  res.json(result);  
});
```

Create logger middleware

```
function logger(req, res, next) {  
  console.log(`${req.method} ${req.url}`);  
  next();
```

```
}
```

```
app.use(logger);
```

```
git init
```

```
git add .
```

```
git commit -m "Node E-commerce  
Assignment"
```

```
git branch -M main
```

```
git remote add origin YOUR_REPO_URL
```

```
git push -u origin main
```

Build social network

Create project

```
mkdir insta-clone
```

```
cd insta-clone
```

```
npm init -y
```

```
npm install express
```

```
server.js
```

```
const express = require("express");
```

```
const app = express();
```

```
app.use(express.json());
```

```
const PORT = 3000;
```

```
// Sample profile
const profile = {
  username: "devika",
  followers: 1200,
  following: 500,
  bio: "MERN Stack Developer"
};
```

```
// In-memory posts array
let posts = [
  {
    postId: 1,
    username: "devika",
    imageUrl:
"https://example.com/post1.jpg",
    caption: "My first post!",
```



```
    likes: 10
  }
];
```

```
// PROFILE ENDPOINT
```

```
app.get("/profile", (req, res) => {
  res.json(profile);
});
```

```
// CREATE POST
```

```
app.post("/post", (req, res) => {
  const { imageUrl, caption } = req.body;
```

```
  const newPost = {
    postId: posts.length + 1,
    username: profile.username,
```

```
    imageUrl,  
    caption,  
    likes: 0  
  }  
};
```

```
posts.push(newPost);
```

```
res.status(201).json(newPost);  
});
```

```
// FEED ENDPOINT (Newest First)
```

```
app.get("/feed", (req, res) => {  
  const feed = [...posts].reverse().map(post  
=> ({  
    username: post.username,  
    caption: post.caption
```

```
}});
```

```
res.json(feed);  
});
```

```
// LIKE ENDPOINT
```

```
app.post("/like", (req, res) => {  
  const { postId } = req.body;
```

```
  const post = posts.find(p => p.postId ===  
  postId);
```

```
  if (!post) {  
    return res.status(404).json({  
      message: "Post not found"  
    });
```

```
}
```

```
post.likes++;
```

```
res.json({
```

```
  postId: post.postId,
```

```
  likes: post.likes
```

```
});
```

```
});
```

```
app.listen(PORT, () => {
```

```
  console.log(`Server running on port  
${PORT}`);
```

```
});
```

Sample json data (5 profile)

```
const users = [  
  {  
    username: "devika",  
    followers: 1200,  
    following: 500,  
    bio: "MERN Developer"  
  },  
  {  
    username: "john",  
    followers: 800,  
    following: 300,  
    bio: "Photographer"  
  },  
  {  
    username: "emma",  
    followers: 1500,  
    following: 100,  
    bio: "Software Engineer"  
  }  
]
```

```
    following: 700,  
    bio: "Traveler"  
  },  
  {  
    username: "alex",  
    followers: 950,  
    following: 400,  
    bio: "Food Blogger"  
  },  
  {  
    username: "sophia",  
    followers: 2100,  
    following: 850,  
    bio: "Fashion Influencer"  
  }  
];
```

Sample json data (10 posts)

```
posts = [  
  {  
    postId: 1,  
    username: "devika",  
    imageUrl: "img1.jpg",  
    caption: "Learning Node.js",  
    likes: 12  
  },  
  {  
    postId: 2,  
    username: "john",  
    imageUrl: "img2.jpg",  
    caption: "Nature Photography",  
    likes: 25  
  },  
]
```

```
{  
  postId: 3,  
  username: "emma",  
  imageUrl: "img3.jpg",  
  caption: "Beach Day",  
  likes: 40  
},  
{  
  postId: 4,  
  username: "alex",  
  imageUrl: "img4.jpg",  
  caption: "Delicious Pizza",  
  likes: 18  
},  
{  
  postId: 5,
```



```
    username: "sophia",  
    imageUrl: "img5.jpg",  
    caption: "New Outfit",  
    likes: 55  
  },  
  {  
    postId: 6,  
    username: "devika",  
    imageUrl: "img6.jpg",  
    caption: "Coding Time",  
    likes: 14  
  },  
  {  
    postId: 7,  
    username: "john",  
    imageUrl: "img7.jpg",
```

```
caption: "Sunset View",
likes: 30
},
{
  postId: 8,
  username: "emma",
  imageUrl: "img8.jpg",
  caption: "Mountain Trip",
  likes: 48
},
{
  postId: 9,
  username: "alex",
  imageUrl: "img9.jpg",
  caption: "Burger Night",
  likes: 22
```

```
},  
{  
  postId: 10,  
  username: "sophia",  
  imageUrl: "img10.jpg",  
  caption: "Weekend Vibes",  
  likes: 60  
}  
];
```

Run the project

node server.js

- GET <http://localhost:3000/profile>
- GET <http://localhost:3000/feed>
- POST <http://localhost:3000/post>

- POST `http://localhost:3000/like`

Blog application

Create project

```
mkdir playlist-app
```

```
cd playlist-app
```

```
npm init -y
```

```
npm install express
```

project structure

```
playlist-app/
```

```
|  
├── server.js  
├── song.js  
└── package.json
```

Create song model

```
class Song {  
  constructor(title, artist, duration) {  
    this.title = title;  
    this.artist = artist;  
    this.duration = duration;  
  }  
}
```

```
const songs = [
```

```
    new Song("Shape of You", "Ed Sheeran",  
240),  
    new Song("Blinding Lights", "The  
Weeknd", 200),  
    new Song("Perfect", "Ed Sheeran", 260)  
];
```

```
module.exports = songs;
```

```
create express server
```

```
server.js
```

```
const express = require("express");
```

```
const app = express();
```

```
const songs = require("./song");
```

```
// Middleware
```

```
app.use(express.json());
```

```
// Root Route
```

```
app.get("/", (req, res) => {  
  res.send("Welcome to Playlist App");  
});
```

```
// GET /songs
```

```
app.get("/songs", (req, res) => {  
  res.json(songs);  
});
```

```
// POST /songs
```

```
app.post("/songs", (req, res) => {  
  const { title, artist, duration } = req.body;
```

```
// Validation
```

```
if (!title || title.trim() === "") {  
  return res.status(400).json({  
    error: "Title cannot be empty"  
  });  
}
```

```
if (!duration || duration <= 0) {  
  return res.status(400).json({  
    error: "Duration must be a positive  
number"  
  });  
}
```

```
const newSong = {  
  title,
```



```
    artist,  
    duration  
  };
```

```
songs.push(newSong);
```

```
res.status(201).json({  
  message: "Song added successfully",  
  songs  
});  
});
```

```
const PORT = 3000;
```

```
app.listen(PORT, () => {
```

```
    console.log(`Server running on port  
${PORT}`);  
});
```

Validation code

```
if (!title || title.trim() === "") {  
    return res.status(400).json({  
        error: "Title cannot be empty"  
    });  
}
```

```
if (!duration || duration <= 0) {  
    return res.status(400).json({  
        error: "Duration must be a positive  
number"  
    });  
}
```

Canva website clone

Create project

mkdir poster-maker

cd poster-maker

npm init -y

npm install express multer

project structure

poster-maker/

|

├── server.js

├── public/

| └── index.html

└─ uploads/
└─ package.json

Create static html

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
  <title>Poster Maker</title>
```

```
</head>
```

```
<body>
```

```
  <h1>Welcome to Poster Maker</h1>
```

```
  <p>Create amazing posters like  
Canva.</p>
```

```
</body>
```

```
</html>
```

Create express server

Server.js

```
const express = require("express");
```

```
const multer = require("multer");
```

```
const path = require("path");
```

```
const app = express();
```

```
app.use(express.json());
```

```
app.use(express.static("public"));
```

```
app.use("/uploads",  
express.static("uploads"));
```

```
const PORT = 3000;
```

```
/* -----
```

Template Data

----- */

```
const templates = [  
  {  
    id: 1,  
    name: "Business Flyer",  
    imageUrl: "/templates/business.jpg"  
  },  
  {  
    id: 2,  
    name: "Birthday Poster",  
    imageUrl: "/templates/birthday.jpg"  
  },  
  {  
    id: 3,
```

```
    name: "Travel Banner",
    imageUrl: "/templates/travel.jpg"
},
{
    id: 4,
    name: "Sale Promotion",
    imageUrl: "/templates/sale.jpg"
},
{
    id: 5,
    name: "Social Media Post",
    imageUrl: "/templates/social.jpg"
}
];
```

```
/* -----
```

Root Route

----- */

```
app.get("/", (req, res) => {  
  res.sendFile(path.join(__dirname,  
    "public", "index.html"));  
});
```

/* -----

GET /templates

----- */

```
app.get("/templates", (req, res) => {  
  res.json(templates);  
});
```



```
/* -----  
  POST /design  
----- */
```

```
app.post("/design", (req, res) => {  
  
  const { text, templateId } = req.body;  
  
  const template = templates.find(  
    t => t.id === Number(templateId)  
  );  
  
  if (!template) {  
    return res.status(404).json({  
      message: "Template not found"  
    });  
  }  
});
```

```
}
```

```
const design = {  
  designId: Date.now(),  
  text,  
  template  
};
```

```
res.status(201).json(design);  
});
```

```
/* -----  
  Multer Configuration  
----- */
```

```
const storage = multer.diskStorage({
```

```
destination: (req, file, cb) => {  
  cb(null, "uploads/");  
},
```

```
filename: (req, file, cb) => {  
  cb(  
    null,  
    Date.now() + "-" + file.originalname  
  );  
}  
});
```

```
const upload = multer({ storage });
```

```
/* -----  
POST /upload
```

----- */

```
app.post(
  "/upload",
  upload.single("logo"),
  (req, res) => {

    res.json({
      message: "File uploaded successfully",
      fileUrl:
        "/uploads/" + req.file.filename
    });
  }
);
```

/* -----

Background Color Feature

----- */

```
app.post("/background-color", (req, res)
=> {
```

```
  const { designId, color } = req.body;
```

```
  const updatedDesign = {
    designId,
    backgroundColor: color
  };
```

```
  res.json({
    message:
      "Background color updated",
```

```
    design: updatedDesign
  });
});

app.listen(PORT, () => {
  console.log(
    `Server running on port ${PORT}`
  );
});
```

Task 2 output

GET <http://localhost:3000/templates>

```
[
  {
    "id": 1,
    "name": "Business Flyer",
    "imageUrl": "/templates/business.jpg"
```

```
},  
{  
  "id": 2,  
  "name": "Birthday Poster",  
  "imageUrl": "/templates/birthday.jpg"  
},  
{  
  "id": 3,  
  "name": "Travel Banner",  
  "imageUrl": "/templates/travel.jpg"  
},  
{  
  "id": 4,  
  "name": "Sale Promotion",  
  "imageUrl": "/templates/sale.jpg"  
},
```

```
{  
  "id": 5,  
  "name": "Social Media Post",  
  "imageUrl": "/templates/social.jpg"  
}  
]
```

```
[  
  {  
    "id": 1,  
    "name": "Business Flyer",  
    "imageUrl": "/templates/business.jpg"  
  },  
  {  
    "id": 2,  
    "name": "Birthday Poster",
```



```
    "imageUrl": "/templates/birthday.jpg"
  },
  {
    "id": 3,
    "name": "Travel Banner",
    "imageUrl": "/templates/travel.jpg"
  },
  {
    "id": 4,
    "name": "Sale Promotion",
    "imageUrl": "/templates/sale.jpg"
  },
  {
    "id": 5,
    "name": "Social Media Post",
    "imageUrl": "/templates/social.jpg"
```

```
}  
]
```

Task 3 example

POST <http://localhost:3000/design>

```
{  
  "text": "Big Summer Sale!",  
  "templateId": 4  
}
```

```
{  
  "designId": 17500000000000,  
  "text": "Big Summer Sale!",  
  "template": {  
    "id": 4,  
    "name": "Sale Promotion",  
    "imageUrl": "/templates/sale.jpg"
```

```
}
```

```
}
```

Task 4

Key	Type	Value
-----	------	-------

logo	File	company-logo.png
------	------	------------------

```
{
```

```
  "message": "File uploaded successfully",
```

```
  "fileUrl": "/uploads/1750000000-  
logo.png"
```

```
}
```

Task 5

```
{
```

```
  "designId": 101,
```

```
  "color": "#FF5733"
```

```
}
```

```
{
```

```
"message": "Background color updated",  
"design": {  
  "designId": 101,  
  "backgroundColor": "#FF5733"  
}  
}
```

Bookmyshow clone

Create project

```
mkdir bookmyshow-clone
```

```
cd bookmyshow-clone
```

```
npm init -y
```

```
npm install express
```

project structure

bookmyshow-clone/

|

└─ server.js

└─ movieRoutes.js

└─ package.json

Create movieRoutes.js

```
const express = require("express");
```

```
const router = express.Router();
```

```
const movies = [
```

```
{
```

```
  id: 1,
```

```
  title: "Avengers Secret Wars",
```

```
    language: "English",
    releaseDate: "2027-05-07"
  },
  {
    id: 2,
    title: "Pushpa 3",
    language: "Hindi",
    releaseDate: "2026-08-15"
  },
  {
    id: 3,
    title: "Kalki 2",
    language: "Telugu",
    releaseDate: "2026-12-25"
  },
  {
```

```
    id: 4,  
    title: "Animal Park",  
    language: "Hindi",  
    releaseDate: "2026-06-20"  
  },  
  {  
    id: 5,  
    title: "Dune Messiah",  
    language: "English",  
    releaseDate: "2026-11-18"  
  }  
];
```

```
// GET /movies
```

```
router.get("/movies", (req, res) => {  
  res.json(movies);  
})
```

```
});const express = require("express");  
const app = express();
```

```
app.use(express.json());
```

```
const { router, movies } =  
require("./movieRoutes");
```

```
app.use("/", router);
```

```
/* -----  
    Booked Seats Array  
----- */
```

```
const bookedSeats = ["A1", "A2", "B3"];
```



```
/* -----
```

Seat Validation Function

```
----- */
```

```
function isSeatBooked(seatNumber) {  
  return bookedSeats.includes(  
    seatNumber.toUpperCase()  
  );  
}
```

```
/* -----
```

POST /book-ticket

```
----- */
```

```
app.post("/book-ticket", (req, res, next) =>  
{
```

```
try {  
  
  const {  
    movieId,  
    seatNumber,  
    userEmail  
  } = req.body;  
  
  if (  
    !movieId ||  
    !seatNumber ||  
    !userEmail  
  ) {  
    throw new Error(  
      "All fields are required"  
    );  
  }  
}
```

```
);  
}
```

```
if (isSeatBooked(seatNumber)) {  
    return res.status(400).json({  
        message:  
            "Seat already booked"  
    });  
}
```

```
bookedSeats.push(  
    seatNumber.toUpperCase()  
);
```

```
res.json({  
    message:
```

```
    "Ticket booked successfully",  
    movieId,  
    seatNumber,  
    userEmail  
  });
```

```
  } catch (error) {  
    next(error);  
  }  
});
```

```
/* -----  
   GET /search-movies  
----- */
```

```
app.get(
```

```
"/search-movies",  
(req, res, next) => {
```

```
  try {
```

```
    const q =  
      req.query.q?.toLowerCase() || "";
```

```
    const results = movies.filter(  
      movie =>  
        movie.title  
          .toLowerCase()  
          .includes(q)  
    );
```

```
    res.json(results);
```

```
    } catch (error) {  
      next(error);  
    }  
  }  
);
```

```
/* -----  
Error Middleware  
----- */
```

```
app.use(  
  (err, req, res, next) => {  
  
    console.error(err.message);
```

```
    res.status(500).json({  
      error: err.message  
    });  
  }  
);
```

```
const PORT = 3000;
```

```
app.listen(PORT, () => {  
  console.log(  
    `Server running on port ${PORT}`  
  );  
});
```

Test apis

GET <http://localhost:3000/movies>

[

```
{  
  "id": 1,  
  "title": "Avengers Secret Wars",  
  "language": "English",  
  "releaseDate": "2027-05-07"  
}  
]
```

Search movies

GET <http://localhost:3000/search-movies?q=pushpa>

```
[  
  {  
    "id": 2,  
    "title": "Pushpa 3",  
    "language": "Hindi",
```



```
    "releaseDate": "2026-08-15"
  }
]
```

Book ticket

POST <http://localhost:3000/book-ticket>

```
{
  "movield": 1,
  "seatNumber": "C5",
  "userEmail": "user@gmail.com"
}

{
  "message": "Ticket booked successfully",
  "movield": 1,
  "seatNumber": "C5",
  "userEmail": "user@gmail.com"
}
```

```
}
```

Already booked seat

```
{
```

```
  "movieId": 1,
```

```
  "seatNumber": "A1",
```

```
  "userEmail": "user@gmail.com"
```

```
}
```

```
{
```

```
  "message": "Seat already booked"
```

```
}
```

Olx clone

Create project

mkdir olx-clone

```
cd olx-clone
```

```
npm init -y
```

```
npm install express
```

project structure

olx-clone/

|

├── server.js

└── package.json

Server.js

```
const express = require("express");
```

```
const app = express();
```

```
app.use(express.json());
```

```
let products = [  
  {  
    id: 1,  
    title: "iPhone 15",  
    price: 75000,  
    imageUrl:  
    "https://example.com/iphone15.jpg"  
  },  
  {  
    id: 2,  
    title: "Honda Activa",  
    price: 55000,  
    imageUrl:  
    "https://example.com/activa.jpg"
```

```
},  
{  
  id: 3,  
  title: "Dell Laptop",  
  price: 45000,  
  imageUrl:  
  "https://example.com/dell.jpg"  
}  
];
```

```
/* -----
```

```
  GET /products
```

```
----- */
```

```
app.get("/products", (req, res) => {  
  res.json(products);  
});
```

```
/* -----
```

```
  POST /add-product
```

```
----- */
```

```
app.post("/add-product", (req, res) => {
```

```
  const { title, price, imageUrl } = req.body;
```

```
  const newProduct = {
```

```
    id: products.length + 1,
```

```
    title,
```

```
    price,
```

```
    imageUrl
```

```
  };
```

```
  products.push(newProduct);
```

```
res.status(201).json(products);  
});
```

```
/* -----  
   GET /products/:id  
----- */
```

```
app.get("/products/:id", (req, res) => {
```

```
  const id = parseInt(req.params.id);
```

```
  const product = products.find(
```

```
    p => p.id === id
```

```
  );
```

```
  if (!product) {
```

```
    return res.status(404).json({  
      message: "Product not found"  
    });  
  }
```

```
    res.json(product);  
  });
```

```
/* -----
```

```
DELETE /products/:id
```

```
----- */
```

```
app.delete("/products/:id", (req, res) => {
```

```
  const id = parseInt(req.params.id);
```

```
  const productExists = products.find(
```



```
    p => p.id === id  
  );
```

```
  if (!productExists) {  
    return res.status(404).json({  
      message: "Product not found"  
    });  
  }
```

```
  products = products.filter(  
    p => p.id !== id  
  );
```

```
  res.json(products);  
});
```

```
const PORT = 3000;
```

```
app.listen(PORT, () => {
```

```
  console.log(`Server running on port  
${PORT}`);
```

```
});
```

Get all products

GET /products

```
[
```

```
{
```

```
  "id": 1,
```

```
  "title": "iPhone 15",
```

```
  "price": 75000,
```

```
  "imageUrl":
```

```
"https://example.com/iphone15.jpg"
```

```
},
```

```
{
```

```
"id": 2,  
"title": "Honda Acura",  
"price": 55000,  
"imageUrl":  
"https://example.com/activa.jpg"  
}  
]
```

Add product

POST /add-product

```
{  
  "title": "Samsung S24",  
  "price": 65000,  
  "imageUrl":  
  "https://example.com/s24.jpg"  
}
```

Response

```
[
```

```
{
  "id": 1,
  "title": "iPhone 15",
  "price": 75000,
  "imageUrl":
"https://example.com/iphone15.jpg"
},
{
  "id": 4,
  "title": "Samsung S24",
  "price": 65000,
  "imageUrl":
"https://example.com/s24.jpg"
}
]
```

Get product by ID

GET /products/2

```
{  
  "id": 2,  
  "title": "Honda Acura",  
  "price": 55000,  
  "imageUrl":  
  "https://example.com/activa.jpg"  
}
```

Product not found

GET /products/10

```
{  
  "message": "Product not found"  
}
```

Delete product

DELETE /products/2

```
[  
  {
```

```
"id": 1,  
"title": "iPhone 15",  
"price": 75000,  
"imageUrl":  
"https://example.com/iphone15.jpg"  
},  
{  
  "id": 3,  
  "title": "Dell Laptop",  
  "price": 45000,  
  "imageUrl":  
  "https://example.com/dell.jpg"  
}  
]
```

Task 5: sample image upload
code(multer)

Install multer

```
npm install multer
```

```
const multer = require("multer");
```

```
const storage = multer.diskStorage({  
  destination: (req, file, cb) => {  
    cb(null, "uploads/");  
  },  
  filename: (req, file, cb) => {  
    cb(null, Date.now() + "-" +  
file.originalname);  
  }  
});
```

```
const upload = multer({ storage });
```

```
app.post(
  "/upload",
  upload.single("image"),
  (req, res) => {
    res.json({
      message: "Image uploaded
successfully",
      file: req.file
    });
  }
);
```

Security improvement

```
const upload = multer({
  storage,
  limits: {
    fileSize: 2 * 1024 * 1024
```



```
},  
fileFilter: (req, file, cb) => {  
  
  const allowedTypes = [  
    "image/jpeg",  
    "image/png",  
    "image/webp"  
  ];  
  
  if  
(allowedTypes.includes(file.mimetype)) {  
    cb(null, true);  
  } else {  
    cb(new Error("Only image files  
allowed"));  
  }  
}
```

```
});
```

Airbnb clone

Create project

```
mkdir StayEZ
```

```
cd StayEZ
```

```
npm init -y
```

```
npm install express
```

project structure

```
StayEZ/
```

```
|
```

```
├── app.js
```

```
├── room.js
```

└─ package.json

Create room model room.js

```
class Room {  
  constructor(title, location, price,  
amenities) {  
    this.title = title;  
    this.location = location;  
    this.price = price;  
    this.amenities = amenities;  
  }  
}
```

module.exports = Room;

app.js

```
const express = require("express");
```

```
const Room = require("./room");
```

```
const app = express();
```

```
/* -----
```

```
    Home Route
```

```
----- */
```

```
app.get("/", (req, res) => {
```

```
    res.send("Welcome to StayEZ");
```

```
});
```

```
/* -----
```

```
    Room Data (5 Rooms)
```

```
----- */
```

```
const rooms = [  
  new Room(  
    "Luxury Beach Villa",  
    "Goa",  
    8000,  
    ["WiFi", "Pool", "Sea View", "Parking"]  
  ),
```

```
  new Room(  
    "Mountain Retreat",  
    "Manali",  
    5500,  
    ["WiFi", "Fireplace", "Breakfast"]  
  ),
```

```
  new Room(  

```

"City Apartment",
"Mumbai",
4500,
["WiFi", "AC", "Kitchen"]
,

new Room(
"Lake View Cottage",
"Udaipur",
6000,
["WiFi", "Lake View", "Garden"]
,

new Room(
"Heritage Haveli",
"Jaipur",

```
7000,  
  ["WiFi", "Breakfast", "Parking", "AC"]  
)  
];
```

```
/* -----  
  GET /rooms  
----- */
```

```
app.get("/rooms", (req, res) => {  
  res.json(rooms);  
});
```

```
/* -----  
  GET /rooms/search  
----- */
```

```
app.get("/rooms/search", (req, res) => {  
  
  const location =  
    req.query.location?.toLowerCase();  
  
  const filteredRooms = rooms.filter(  
    room =>  
      room.location.toLowerCase() ===  
location  
  );  
  
  res.json(filteredRooms);  
});  
  
const PORT = 3000;
```



```
app.listen(PORT, () => {  
  console.log(  
    `Server running on port ${PORT}`  
  );  
});
```

Get all rooms

```
[  
  {  
    "title": "Luxury Beach Villa",  
    "location": "Goa",  
    "price": 8000,  
    "amenities": ["WiFi", "Pool", "Sea  
View", "Parking"]  
  },  
  {
```

```
"title": "Mountain Retreat",
"location": "Manali",
"price": 5500,
"amenities":
["WiFi", "Fireplace", "Breakfast"]
},
{
"title": "City Apartment",
"location": "Mumbai",
"price": 4500,
"amenities": ["WiFi", "AC", "Kitchen"]
},
{
"title": "Lake View Cottage",
"location": "Udaipur",
"price": 6000,
```

```
    "amenities": ["WiFi","Lake  
View","Garden"]  
  },  
  {  
    "title": "Heritage Haveli",  
    "location": "Jaipur",  
    "price": 7000,  
    "amenities":  
    ["WiFi","Breakfast","Parking","AC"]  
  }  
]
```

Search rooms by location

```
[  
  {  
    "title": "Luxury Beach Villa",  
    "location": "Goa",
```

```
"price": 8000,  
"amenities": [  
  "WiFi",  
  "Pool",  
  "Sea View",  
  "Parking"  
]  
}  
]
```

