

```

Enter password: *****
Welcome to the MySQL monitor.  Commands end with ; or \g.
Your MySQL connection id is 50
Server version: 8.0.39 MySQL Community Server - GPL

Copyright (c) 2000, 2024, Oracle and/or its affiliates.

Oracle is a registered trademark of Oracle Corporation and/or its
affiliates. Other names may be trademarks of their respective
owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

mysql> use nit;
Database changed
mysql> create table students(id int,name varchar(20),address varchar(30),marks int);
ERROR 1050 (42S01): Table 'students' already exists
mysql> desc students;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| id     | int  | YES  |     | NULL    |       |
| name   | varchar(20) | YES  |     | NULL    |       |
| address | varchar(30) | YES  |     | NULL    |       |
| marks  | int  | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
rows in set (0.01 sec)

mysql> select * from students;
Empty set (0.00 sec)

mysql> insert into students values(1,'ovi','pune',70),(2,'git','mumbai','87'),(7,'smith','nashik',90),(4,'priya','pune',70),(5,'isha','mumbai',90);
Query OK, 5 rows affected (0.01 sec)
Records: 5 Duplicates: 0 Warnings: 0

mysql> select * from students;
+-----+-----+-----+-----+
| id | name | address | marks |
+-----+-----+-----+-----+
| 1  | ovi  | pune    | 70    |
| 2  | git  | mumbai  | 87    |
+-----+-----+-----+-----+

```

```
mysql> insert into students values(1, 'ovi', 'pune', 70);
Query OK, 1 rows affected (0.01 sec)
Records: 1 Duplicates: 0 Warnings: 0
```

```
mysql> select * from students;
```

id	name	address	marks
1	ovi	pune	70
2	git	mumbai	87
7	smith	nashik	90
4	priya	pune	70
5	isha	mumbai	90

```
5 rows in set (0.00 sec)
```

```
mysql> alter table students modify column name varchar(40);
```

```
Query OK, 0 rows affected (0.05 sec)
Records: 0 Duplicates: 0 Warnings: 0
```

```
mysql> select * from students;
```

id	name	address	marks
1	ovi	pune	70
2	git	mumbai	87
7	smith	nashik	90
4	priya	pune	70
5	isha	mumbai	90

```
5 rows in set (0.00 sec)
```

```
mysql> update students set phoneno=123;
```

```
ERROR 1054 (42S22): Unknown column 'phoneno' in 'field list'
```

```
mysql> alter table students add phoneno int;
```

```
Query OK, 0 rows affected (0.04 sec)
Records: 0 Duplicates: 0 Warnings: 0
```

```
mysql> select * from students;
```

id	name	address	marks	phoneno
1	ovi	pune	70	NULL
2	git	mumbai	87	NULL
7	smith	nashik	90	NULL
4	priya	pune	70	NULL
5	isha	mumbai	90	NULL

```
5 rows in set (0.00 sec)
```

```
mysql> update students set phoneno=123;
Query OK, 5 rows affected (0.01 sec)
Rows matched: 5  Changed: 5  Warnings: 0
```

```
mysql> select * from students;
```

id	name	address	marks	phoneno
1	ovi	pune	70	123
2	git	mumbai	87	123
7	smith	nashik	90	123
4	priya	pune	70	123
5	isha	mumbai	90	123

```
5 rows in set (0.00 sec)
```

```
mysql> update students set phoneno=456 where id=1;
Query OK, 1 row affected (0.01 sec)
Rows matched: 1  Changed: 1  Warnings: 0
```

```
mysql> desc students;
```

Field	Type	Null	Key	Default	Extra
id	int	YES		NULL	
name	varchar(40)	YES		NULL	
address	varchar(30)	YES		NULL	
marks	int	YES		NULL	
phoneno	int	YES		NULL	

```
5 rows in set (0.00 sec)
```

```
mysql> select * from students;
```

id	name	address	marks	phoneno
1	ovi	pune	70	456
2	git	mumbai	87	123
7	smith	nashik	90	123
4	priya	pune	70	123
5	isha	mumbai	90	123

```
5 rows in set (0.00 sec)
```

```
mysql> alter table students drop column phoneno;
Query OK, 0 rows affected (0.03 sec)
Records: 0  Duplicates: 0  Warnings: 0
```

```
mysql> select * from students;
```

id	name	address	marks
1	ovi	pune	70
2	git	mumbai	87
7	smith	nashik	90
4	priya	pune	70
5	isha	mumbai	90

```
5 rows in set (0.00 sec)
```

```
mysql> select sum(marks) from students;
```

sum(marks)
407

```
1 row in set (0.01 sec)
```

```
mysql> select avg(marks) from student;
```

avg(marks)
70.8333

```
1 row in set (0.00 sec)
```

```
mysql> select count(name) from student;
```

count(name)
6

```
1 row in set (0.01 sec)
```

```
mysql> select avg(marks) from students;
```

avg(marks)
81.4000

```
1 row in set (0.00 sec)
```

```
mysql> select count(name) from students;
```

count(name)
5

```
mysql> select max(marks) from students;
```

```
+-----+  
| max(marks) |  
+-----+  
|          90 |  
+-----+
```

```
1 row in set (0.00 sec)
```

```
mysql> select min(marks) from students;
```

```
+-----+  
| min(marks) |  
+-----+  
|          70 |  
+-----+
```

```
1 row in set (0.00 sec)
```

```
mysql> select * from students;
```

```
+-----+-----+-----+-----+  
| id  | name  | address | marks |  
+-----+-----+-----+-----+  
| 1   | ovi   | pune    | 70    |  
| 2   | git   | mumbai  | 87    |  
| 7   | smith | nashik  | 90    |  
| 4   | priya | pune    | 70    |  
| 5   | isha  | mumbai  | 90    |  
+-----+-----+-----+-----+
```

```
5 rows in set (0.00 sec)
```

```
mysql> select * from students order by marks;
```

```
+-----+-----+-----+-----+  
| id  | name  | address | marks |  
+-----+-----+-----+-----+  
| 1   | ovi   | pune    | 70    |  
| 4   | priya | pune    | 70    |  
| 2   | git   | mumbai  | 87    |  
| 7   | smith | nashik  | 90    |  
| 5   | isha  | mumbai  | 90    |  
+-----+-----+-----+-----+
```

```
5 rows in set (0.00 sec)
```

```
mysql> select * from students order by marks desc;
```

```
+-----+-----+-----+-----+  
| id  | name  | address | marks |  
+-----+-----+-----+-----+  
| 7   | smith | nashik  | 90    |  
| 5   | isha  | mumbai  | 90    |  
| 2   | git   | mumbai  | 87    |  
| 1   | ovi   | pune    | 70    |  
| 4   | priya | pune    | 70    |  
+-----+-----+-----+-----+
```

```
+-----+-----+-----+-----+
5 rows in set (0.00 sec)
```

```
mysql> select * from students where name like '%s';
Empty set (0.01 sec)
```

```
mysql> select * from students where name like 's%';
```

```
+-----+-----+-----+-----+
| id  | name  | address | marks |
+-----+-----+-----+-----+
| 7   | smith | nashik  | 90    |
+-----+-----+-----+-----+
1 row in set (0.00 sec)
```

```
mysql> select * from students where name like '%a';
```

```
+-----+-----+-----+-----+
| id  | name  | address | marks |
+-----+-----+-----+-----+
| 4   | priya | pune    | 70    |
| 5   | isha  | mumbai  | 90    |
+-----+-----+-----+-----+
2 rows in set (0.00 sec)
```

```
mysql> select * from students where name like '_v%';
```

```
+-----+-----+-----+-----+
| id  | name  | address | marks |
+-----+-----+-----+-----+
| 1   | ovi   | pune    | 70    |
+-----+-----+-----+-----+
1 row in set (0.00 sec)
```

```
mysql> select * from students where name like '%_t';
```

```
+-----+-----+-----+-----+
| id  | name  | address | marks |
+-----+-----+-----+-----+
| 2   | git   | mumbai  | 87    |
+-----+-----+-----+-----+
1 row in set (0.00 sec)
```

```
mysql> desc emp1;
```

Field	Type	Null	Key	Default	Extra
id	int	NO	PRI	NULL	
salary	int	YES		NULL	
empcode	int	YES		NULL	
name	varchar(20)	YES		NULL	

```
4 rows in set (0.00 sec)
```

```
mysql> select * from emp1;
```

id	salary	empcode	name
1	2000	102	aman
3	90000	106	sam
6	3000	105	max
7	6000	104	arup
8	2500	103	ram

```
5 rows in set (0.00 sec)
```

```
mysql> select * from students inner join emp1 on students.id=emp1.id;
```

id	name	address	marks	id	salary	empcode	name
1	ovi	pune	70	1	2000	102	aman
7	smith	nashik	90	7	6000	104	arup

```
2 rows in set (0.00 sec)
```

```
mysql> select * from students cross join emp1;
```

id	name	address	marks	id	salary	empcode	name
5	isha	mumbai	90	1	2000	102	aman
4	priya	pune	70	1	2000	102	aman
7	smith	nashik	90	1	2000	102	aman
2	git	mumbai	87	1	2000	102	aman
1	ovi	pune	70	1	2000	102	aman
5	isha	mumbai	90	3	90000	106	sam
4	priya	pune	70	3	90000	106	sam
7	smith	nashik	90	3	90000	106	sam
2	git	mumbai	87	3	90000	106	sam
1	ovi	pune	70	3	90000	106	sam
5	isha	mumbai	90	6	3000	105	max
4	priya	pune	70	6	3000	105	max
7	smith	nashik	90	6	3000	105	max
2	git	mumbai	87	6	3000	105	max
1	ovi	pune	70	6	3000	105	max
5	isha	mumbai	90	7	6000	104	arup
4	priya	pune	70	7	6000	104	arup
7	smith	nashik	90	7	6000	104	arup
2	git	mumbai	87	7	6000	104	arup
1	ovi	pune	70	7	6000	104	arup
5	isha	mumbai	90	8	2500	103	ram
4	priya	pune	70	8	2500	103	ram
7	smith	nashik	90	8	2500	103	ram
2	git	mumbai	87	8	2500	103	ram
1	ovi	pune	70	8	2500	103	ram

```
25 rows in set (0.00 sec)
```

id	name	address	marks	id	salary	empcode	name
5	isha	mumbai	90	1	2000	102	aman
4	priya	pune	70	1	2000	102	aman
7	smith	nashik	90	1	2000	102	aman
2	git	mumbai	87	1	2000	102	aman
1	ovi	pune	70	1	2000	102	aman
5	isha	mumbai	90	3	90000	106	sam
4	priya	pune	70	3	90000	106	sam
7	smith	nashik	90	3	90000	106	sam
2	git	mumbai	87	3	90000	106	sam
1	ovi	pune	70	3	90000	106	sam
5	isha	mumbai	90	6	3000	105	max
4	priya	pune	70	6	3000	105	max
7	smith	nashik	90	6	3000	105	max
2	git	mumbai	87	6	3000	105	max
1	ovi	pune	70	6	3000	105	max
5	isha	mumbai	90	7	6000	104	arup
4	priya	pune	70	7	6000	104	arup
7	smith	nashik	90	7	6000	104	arup
2	git	mumbai	87	7	6000	104	arup
1	ovi	pune	70	7	6000	104	arup
5	isha	mumbai	90	8	2500	103	ram
4	priya	pune	70	8	2500	103	ram
7	smith	nashik	90	8	2500	103	ram
2	git	mumbai	87	8	2500	103	ram
1	ovi	pune	70	8	2500	103	ram

25 rows in set (0.00 sec)

```
mysql> select * from students right join emp on students.id=emp.id;
```

ERROR 1146 (42S02): Table 'nit.emp' doesn't exist

```
mysql> select * from students right join emp on students.id=empl.id;
```

ERROR 1146 (42S02): Table 'nit.emp' doesn't exist

```
mysql> select * from students right join empl on students.id=empl.id;
```

id	name	address	marks	id	salary	empcode	name
1	ovi	pune	70	1	2000	102	aman
NULL	NULL	NULL	NULL	3	90000	106	sam
NULL	NULL	NULL	NULL	6	3000	105	max
7	smith	nashik	90	7	6000	104	arup
NULL	NULL	NULL	NULL	8	2500	103	ram

5 rows in set (0.00 sec)

```
mysql> select * from students left join empl on students.id=empl.id;
```

id	name	address	marks	id	salary	empcode	name
1	ovi	pune	70	1	2000	102	aman
2	git	mumbai	87	NULL	NULL	NULL	NULL
7	smith	nashik	90	7	6000	104	arup
4	priya	pune	70	NULL	NULL	NULL	NULL
5	isha	mumbai	90	NULL	NULL	NULL	NULL

5 rows in set (0.00 sec)

```
mysql> |
```