EXP 39

```
#include<stdio.h>
#include<stdlib.h>
int main()
  int RQ[100],i,j,n,TotalHeadMoment=0,initial,size,move;
  printf("Enter the number of Requests\n");
  scanf("%d",&n);
  printf("Enter the Requests sequence\n");
  for(i=0;i<n;i++)
  scanf("%d",&RQ[i]);
  printf("Enter initial head position\n");
  scanf("%d",&initial);
  printf("Enter total disk size\n");
  scanf("%d",&size);
  printf("Enter the head movement direction for high 1 and for low 0\n");
  scanf("%d",&move);
  for(i=0;i<n;i++)
  {
    for( j=0;j<n-i-1;j++)
       if(RQ[j]>RQ[j+1])
         int temp;
         temp=RQ[j];
         RQ[j]=RQ[j+1];
         RQ[j+1]=temp;
      }
    }
  int index;
  for(i=0;i<n;i++)
    if(initial<RQ[i])
      index=i;
       break;
    }
  }
  if(move==1)
    for(i=index;i<n;i++)</pre>
```

```
TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);
    initial=RQ[i];
  }
  TotalHeadMoment=TotalHeadMoment+abs(size-RQ[i-1]-1);
  TotalHeadMoment=TotalHeadMoment+abs(size-1-0);
  initial=0;
  for( i=0;i<index;i++)</pre>
    TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);
    initial=RQ[i];
 }
else
  for(i=index-1;i>=0;i--)
    TotalHeadMoment=TotalHeadMoment+abs(RQ[i]-initial);
    initial=RQ[i];
  TotalHeadMoment=TotalHeadMoment+abs(RQ[i+1]-0);
  TotalHeadMoment=TotalHeadMoment+abs(size-1-0);
  initial =size-1;
  for(i=n-1;i>=index;i--)
    Total Head Moment = Total Head Moment + abs(RQ[i]-initial);\\
    initial=RQ[i];
 }
printf("Total head movement is %d",TotalHeadMoment);
return 0;
```

}