

PUNE, INDIA
SID RWY 28

OPAKA 2A, UBSAB 2A, LUKTI 2A, AVKOR 2A, DOGAP 2A
DEPARTURES RWY 28

Trans Alt : 7000'

1. ATC will specify alternate routings if necessary.
2. If unable to comply advise ATC.
3. Caution for VAD-19 900M/AGL.

DME Required

CAUTION

- AVKOR 2A & LUKTI 2A require a minimum climb gradient of 5.5% until reaching 8000ft and crossing R-225 PPN.
- Avoid flying South of R-271° PPN between D3.0 - D5.0.

GND SPEED KTS		75	100	150	200	250	300
335'/NM (5.5%)		419'/min	558'/min	838'/min	1117'/min	1396'/min	1675'/min

SID	RWY	ROUTING
OPAKA 2A	28	Climb on runway Hdg to D 5.0 PPN at or above 2900', Climbing turn right Hdg 077° to intercept R030.
UBSAB 2A	28	Climb on runway Hdg to D 5.0 PPN at or above 2900', Climbing turn right Hdg 095° to intercept R061.
DOGAP 2A	28	Climb on runway Hdg to D 5.0 PPN at or above 2900', Climbing turn right Hdg 329° to intercept R298.
AVKOR 2A	28	Climb on runway Hdg to 5000' at PDG not below 5.5% , Climbing turn left Hdg 123° to intercept R175.
LUKTI 2A	28	Climb on runway Hdg to 5000' at PDG not below 5.5% , Climbing turn left Hdg 099° to intercept R115.

CHANGES : NEW PROCEDURE
IPDC DTE OF OPS (T & S)