

HRC CYLINDRICAL FUSE

TFL

Application

Protection and control of circuits against overloads and short circuits.

Technical Data

- Standard comply to IEC269, VDE 0636
- Rated Breaking Capacity: 125kA – 500/690V AC
- 3 sizes: 10 x 38, 14 x 51 and 22 x 58
- Rating: 1A to 100A. 2 Application categories at 500/690V AC
- GL (Distribution)
- AM (Motor)

TFL	PRODUCT CODE	RATING / A
<p>1038 10 x 38mm Cylindrical Fuse</p>	TFL1038 - 02 TFL1038 - 04 TFL1038 - 06 TFL1038 - 08 TFL1038 - 10 TFL1038 - 12 TFL1038 - 16 TFL1038 - 20 TFL1038 - 32	2 4 6 8 10 12 16 20 32
<p>1451 14 x 51mm Cylindrical Fuse</p>	TFL1451 - 04 TFL1451 - 06 TFL1451 - 10 TFL1451 - 16 TFL1451 - 25 TFL1451 - 32 TFL1451 - 40 TFL1451 - 50	4 6 10 16 25 32 40 50
<p>2258 22 x 58mm Cylindrical Fuse</p>	TFL2258 - 50 TFL2258 - 63 TFL2258 - 80 TFL2258 - 100 TFL2258 - 125	50 63 80 100 125