

**PROJECT TITLE:** CONSTRUCTION OF 9 BUILDINGS AND A&A WORKS TO 2 BUILDING ALONG SEMBWANG ROAD

**LUMINAIRE CODE:** L3E



\*Above picture for illustration purposes only.



Technical Parameters	
Ex Marking	Ex d e IIC T6 Gb / DIP A20 TA, T6
IP Degree	IP66
Corrosion Resistant	WF1
Rated Voltage	220-240VAC/50-60HZ
Conduit Entries	M20
Battery Back-up	Optional: Emergency time up to 3hours; Charging time: 24h; Starting time: 0.3s
Mounting Styles	Pendant; Ceiling; Chain; Embedded; Wall; Stanchion

**Luminaire Brand**

Lumenex

**Model**

BYS-K SERIES

**Country of Origin**

China

**Description**

LUMENEX BYS-K SERIES, 2x14W LED explosion-proof linear light fitting suitable for zone 1,21 2& 22, c/w 2x14W LED tube, daylight total 4200lm, GRP housing & PC diffuser, IP66, ATEX certified

**Compliance**

IP66

**Control Gear**

Integrated Driver

**LED Lamp**

2 x 14w LED Lamps

lumen: 2100lm Per Lamp

Colour Temperature : 6500K

Lifespan: 50k hours (L70@25deg)

**Mounting Method**

Surface / Suspended Mounting

**Dimension**

L=1300mm, W=208mm, H=120mm

