

PROJECT TITLE: CONSTRUCTION OF 9 BUILDINGS AND A&A WORKS TO 2 BUILDING ALONG SEMBWANG ROAD

LOCATION: BLOCK 3 MESS / BLK 2, 03-08 CONFERENCE ROOM **SYMBOL:** L9-1



Luminaire Brand
Lite Unite

Model
PS-DL12C18

Country of Origin
China

Description

Round low glare downlight from Lite Unite setting an advanced and innovative thermal balance system through passive dissipation with stable colour temperature optimised to be used as general indoor lighting for offices, hospitals commercial areas or residential & contract spaces. Designed for ceiling recessed installation. Luminaire body built in die-cast aluminium with aluminium reflector.

DRIVER PARTNERS

TRIDONIC PHILIPS OSRAM E&E

CHIP PARTNERS

PHILIPS OSRAM SAMSUNG



Compliance

IP40, ENEC, TUV, CE, RoHS, SELV, EN55015, EN61000, EN61347, EN61547

Materials

Luminaire body built in die-cast aluminium with low glare dark light reflector

Finish

White powder coated finish

LED Module

Power (W): 12W LED

Lumen (Lm): 1,100lm

Beam Angle: 60°

Colour Temperature: 4000K

CRI: 83

Average Life Span

50,000hrs@L70

Mounting Method

Recessed Mounted

Dimension

140mm (Dia) x 73mm (Ht)

Drilling hole (mm) Ø125

Optional

Colour Temperature : 3000K / 5000K

Beam Angle: 24° / 38°

