Extron

Specifications

WPD 100 AV Series Wallplates

Cable - Digital

TRUE 4K specification

Max. 4K Capabilities		
Resolution and Refresh Rate	**Chroma Sampling**	**Max. Bit Depth per Color**
4096 x 2160 at 30 Hz	4:4:4	8 bit
3840 x 2160 at 30 Hz		
4096 x 2160 at 60 Hz	4:2:0	
3840 x 2160 at 60 Hz		

Frame rate[1] .... 24, 25, 30, 50, or 60 fps
Chroma sampling[1] .... 4:4:4, 4:2:2, or 4:2:0
Color bit depth[1] .... 8 bits per color
Signal type .... HDMI 1.4, DisplayPort 1.1a
Max. video data rate
    HDMI.................................. 10.2 Gbps (3.4 Gbps per color)
    DisplayPort......................... 10.8 Gbps (2.7 Gbps per lane)

NOTE: [1]Subject to the maximum data rate limit. Use our calculator at **www.extron.com/8Kdatarate** to determine video parameters supported by this data rate.

General

Mounting.................................. Extron AAP 314 or AAP 424
    Furniture or wall mount .... Yes, with standard decorator-style wallplate
Enclosure type .... Plastic
Connector type .... HDMI female to HDMI female
    VGA female to VGA female
    RJ-45 CAT 5e barrel
    DisplayPort female to DisplayPort female
    3.5 mm stereo audio jack to captive screw
    USB 2.0 Type A female to Type A female
    3.5 mm Captive screw connector, 3-pole to 3.5 mm captive screw connector, 3-pole

Connectivity - WPD 100 AV Series						
	110 A	120 A	140 A	150 A	160	170
HDMI	1			1	1	2
VGA			1	1		
3.5 mm Audio	1	1	1	1		
DisplayPort		1				
USB 2.0					1	
RJ-45 Barrel					1	1
3.5 mm captive screw	1	1	1			

Cable Dimensions		
	Length*	Outer Diameter
HDMI	12.75" (324 mm)	0.24" (6.0 mm)
VGA	9.00" (228 mm)	0.24" (6.0 mm)
DisplayPort	10.25" (260 mm)	0.17" (4.3 mm)
USB 2.0	13.30" (338 mm)	0.22" (5.7 mm)

*Length includes connector.

Enclosure dimensions............... All models
Module .... 4.10" H x 1.60" W x 0.26" D (104 mm H x 41 mm W x 6.6 mm D)
(Depth excludes connectors. Fits into standard one-gang decorator-style frame.)
Mounting holes are 3.80" (97 mm) apart.
Face is 2.61" H x 1.29" W (66 mm H x 33 mm W).

D **Depths, Including Bend Radius:**
WPD 110 A: 2.0" (50 mm)
WPD 120 A: 2.4" (60 mm)
WPD 140 A: 2.4" (60 mm)
WPD 150 A: 2.4" (60 mm)
WPD 160: 2.4" (60 mm)
WPD 170: 2.4" (60 mm)

WPD 110 A

ATTENTION: Do not bend cable beyond the recommended depth.

Product weight.......................... 0.1 lb (<0.1 kg)
Regulatory compliance............. RoHS, WEEE
Product warranty...................... 3 years parts and labor

NOTE: Specifications are subject to change without notice.

NOTE: Shipping weights and dimensions are available at **www.extron.com**.

5102-D7