

### IR remote control

- to adjust : time delay, sensitivity, brightness, detection of angles (220°- 360° version), keypad lock, ON / OFF, test mode.

Description

IR remote control for EE85x, EE86x and EE87x

Cat. ref.

**EE806**



EE806

### Presence and motion detectors IP21

- automatic switching of electric loads depending on heat motion and ambient brightness
- combination of presence and motion detector with enhanced detection sensitivity in the central

- presence-detection area
- response brightness and delay time adjustable

Description

360° surface mounting, white

360° flush mounting, white

Cat. ref.

**EE804A**

**EE805A**



EE804A

### Motion detector for corridor IP54

- 1 way, 10 A AC1
- 4 m x 20 m
- for surface mounting on wall or ceiling

- sensitive to infrared radiation emitted as heat from a moving body
- specially designed to meet the needs of corridors

Description

360° surface mounting, white

Cat. ref.

**EE880**



EE880

### HF motion detector (hyper frequency) IP54

- 1 way, 10 A AC1
- detection distance from 1 to 8 m
- for surface mounting on wall or ceiling
- employs Hyper Frequency technology and reacts to movements regardless of the temperature

- can detect movements through doors, windows and even non-metallic low-thickness partitions

Description

surface mounting, white

Cat. ref.

**EE883**



EE883

### Protection basket

- Ø 178 mm

Description

compatible with EE804, EE805, EE883, white

Cat. ref.

**EEK006**



EEK006