

```
(program) → [(metas)] ⟨object⟩ EOF
(metas) → (meta) {EOL (meta)} EOP
(comment) → (commentary) EOL
(commentoptional) → {(comment)}
(object) → ((commentoptional) ⟨masterbody⟩)
| (bound)
⟨bound⟩ → commentoptional ((application) | (((method) | ⟨just⟩) ⟨onameortname⟩ EOL))
⟨tbound⟩ → commentoptional ((tapplication) | (((method) | ⟨just⟩) ⟨tname⟩ EOL))
⟨tsubmaster⟩ → commentoptional ⟨tmasterbody⟩
⟨submaster⟩ → commentoptional ⟨masterbody⟩
⟨masterbody⟩ → (formation) | (atom) | ((hanonym) ⟨onameortname⟩ EOL)
⟨tmasterbody⟩ → tformation | (atom) | ((hanonym) ⟨tname⟩ EOL)
(just) → (beginner) | (finisher)
(atom) → (voids) ⟨suffix⟩ "␣" "?" ⟨testsoreol⟩
(formation) → (voids) ⟨onameortname⟩ ⟨innersoreol⟩
(tformation) → (voids) ⟨tname⟩ ⟨innersoreol⟩
⟨testsoreol⟩ → ⟨tests⟩ | EOL
⟨innersoreol⟩ → ⟨inners⟩ | EOL
⟨inners⟩ → EOL TAB ((bound) | (submaster)) {(((bound) | (EOL ⟨submaster⟩) )) UNTAB
⟨tests⟩ → EOL TAB ((tbound) | (tsubmaster)) {(((tbound) | (EOL ⟨tsubmaster⟩) )) UNTAB
⟨voids⟩ → "[" [(void) {"␣" (void)}] "]"
⟨void⟩ → ⟨name⟩ | "@"
(application) → ((happlicationextended) ⟨onameortname⟩ EOL)
| (vapplication)
⟨tapplication⟩ → ((happlicationextended) ⟨tname⟩ EOL)
| (tvapplication)
⟨happlication⟩ → ((happlicationhead) ⟨happlicationtail⟩)
| (happlicationreversed)
⟨happlicationreversedhead⟩ → (reversed) "␣" (happlicationreversedfirst)
⟨happlicationextended⟩ → ((happlicationheadextended) ⟨happlicationtail⟩)
| (happlicationreversed)
⟨happlicationreversed⟩ → (happlicationreversedhead) [(happlicationtail)]
⟨happlicationhead⟩ → ⟨hmethod⟩ | ⟨applicable⟩
(happlicationheadextended) → ⟨vmethod⟩ | ⟨happlicationhead⟩
⟨applicable⟩ → "*" | ⟨name⟩ | "@"
(happlicationargunbound) → "␣" ⟨happlicationarg⟩
⟨happlicationtailscoped⟩ → {(happlicationargunbound)} "␣" (happlicationargscoped)
⟨happlicationtail⟩ → {(happlicationargunbound) ⟨as⟩}+ | {(happlicationargunbound)}+
(happlicationreversedfirst) → ⟨happlicationarg⟩
⟨happlicationarg⟩ → (just) | ⟨hmethod⟩ | ⟨scope⟩
⟨happlicationargscoped⟩ → (voids) ⟨aname⟩ ⟨innersoreol⟩
⟨vapplication⟩ → ((vapplicationhead) ⟨onameortname⟩ ⟨vapplicationargs⟩) | ((reversed) ⟨onameortname⟩ ⟨vapplicationargsreversed⟩)
⟨tvapplication⟩ → ((vapplicationhead) ⟨tname⟩ ⟨vapplicationargs⟩) | ((reversed) ⟨tname⟩ ⟨vapplicationargsreversed⟩)
⟨vapplicationhead⟩ → ⟨applicable⟩ | ⟨hmethod⟩ | ⟨vmethod⟩ | ⟨compacttuple⟩
⟨compacttuple⟩ → ((hmethod) | ⟨applicable⟩ | ⟨reversed⟩ "␣" "*" [⟨int⟩])
⟨vapplicationargs⟩ → EOL TAB ⟨vapplicationargsspecific⟩ UNTAB
⟨vapplicationargsreversed⟩ → EOL TAB ⟨vapplicationargunbound⟩ [(vapplicationargsspecific)] UNTAB
⟨vapplicationargsspecific⟩ → {(vapplicationargbound)}+ | {(vapplicationargunbound)}+
⟨vapplicationargbound⟩ → ((vapplicationargboundcurrent) EOL)
| (vapplicationargboundnext)
⟨vapplicationargboundcurrent⟩ → (( " (" ⟨happlicationextended⟩ ")" ) | ⟨just⟩ | ⟨method⟩ ⟨as⟩ [(⟨oname⟩)] | ((commentoptional) "(" ⟨hanonym⟩ ")" ⟨as⟩ [(⟨fname⟩)])
⟨vapplicationargboundnext⟩ → ((commentoptional) ⟨voids⟩ ⟨as⟩ [(⟨fname⟩) ⟨innersoreol⟩] | ((vapplicationhead) ⟨as⟩ [(⟨oname⟩) ⟨vapplicationargs⟩] | ((reversed) ⟨as⟩ [(⟨oname⟩) ⟨vapplicationargsreversed⟩])
⟨vapplicationargunbound⟩ → ((vapplicationargunboundcurrent) EOL)
| (vapplicationargunboundnext)
(vapplicationargunboundcurrent) → ((happlicationextended) | ⟨just⟩ | ⟨method⟩ [(⟨oname⟩)] | ((commentoptional) ⟨hanonym⟩ [(⟨fname⟩)])
⟨vapplicationargunboundnext⟩ → (formationnamed) | ((vapplicationhead) [(⟨oname⟩) ⟨vapplicationargs⟩] | ((reversed) [(⟨oname⟩) ⟨vapplicationargsreversed⟩] | ((happlicationhead) | ⟨happlicationreversedhead⟩ ⟨happlicationtailscoped⟩)
⟨formationnamed⟩ → (commentoptional) ⟨voids⟩ [(⟨fname⟩) ⟨innersoreol⟩]
⟨hformation⟩ → (voids) {(hanonyminner)}+
⟨hanonym⟩ → (hformation) | ((hmethod) | ⟨happlication⟩ | (hformation) | ⟨just⟩ {(onlyphitail)}+)
⟨onlyphitail⟩ → (arrow) ⟨voids⟩
⟨hanonyminner⟩ → "␣" "(" ((hmethod) | ⟨happlication⟩ | ⟨hanonym⟩ | ⟨just⟩) ⟨oname⟩ ")"
⟨method⟩ → (hmethod) | ⟨vmethod⟩
⟨hmethod⟩ → ((just) | ⟨scope⟩) {(methodtail)}+
⟨vmethod⟩ → ((vmethodheadvapplication) | ((⟨just⟩ | ⟨hanonym⟩) [(⟨oname⟩) EOL] | ⟨formationnamed⟩) ⟨methodtail⟩ {(vmethodheadapplicationtail) ⟨methodtail⟩})
(vmethodheadapplicationtail) → ((⟨oname⟩) ⟨vapplicationargs⟩ EOL) | ((happlicationtail) [(⟨oname⟩) EOL]
⟨vmethodheadvapplication⟩ → ((applicable) | (hmethod) [(⟨oname⟩) ⟨vapplicationargs⟩] | ((reversed) [(⟨oname⟩) ⟨vapplicationargsreversed⟩])
⟨methodtail⟩ → ". " ⟨finisher⟩
⟨beginner⟩ → "*" | "Q" | "QQ" | "$" | (data)
⟨finisher⟩ → ⟨name⟩ | "@" | "^"
⟨reversed⟩ → (finisher) ". "
⟨aname⟩ → ">" ">" ["!" ]
⟨fname⟩ → ⟨oname⟩ | ("␣" ⟨aname⟩)
⟨onameortname⟩ → ⟨oname⟩ | ⟨tname⟩
⟨oname⟩ → (suffix) ["!" ]
⟨tname⟩ → (tarrow) ("@" | ⟨name⟩)
⟨tarrow⟩ → "␣" "+" ">" "␣"
⟨suffix⟩ → (arrow) ("@" | ⟨name⟩) ["!" ]
⟨arrow⟩ → "␣" ">" "␣"
⟨scope⟩ → "(" ((happlication) | ⟨hanonym⟩) ")"
⟨as⟩ → ":" ⟨(name) | ⟨int⟩)
⟨data⟩ → ⟨bytes⟩ | ⟨text⟩ | ⟨string⟩ | ⟨int⟩ | ⟨float⟩ | ⟨hex⟩
(commentary) → "#" [{ [^\\r\\n] } [^␣\\r\\n\\t]]
⟨meta⟩ → "+" ⟨name⟩ {"␣" [^␣\\t\\r\\n] }+
⟨indent⟩ → "␣" "␣"
⟨linebreak⟩ → ["\\r" "\\n"
⟨byte⟩ → [0-9A-F] [0-9A-F]
⟨empty_bytes⟩ → "-" "-"
⟨line_bytes⟩ → (byte) {"-" ⟨byte⟩}+
⟨bytes⟩ → (empty_bytes) | ((byte) "-" | ((line_bytes) {"-" EOL ⟨line_bytes⟩}))
(escape_sequence) → "\\{" ( [btfnr"'\{} ] | ([ [0-3] [0-7] [0-7] ] | ({ "u" }+ ⟨byte⟩ ⟨byte⟩))
⟨string⟩ → DQ {[^"\\{}\\r\\n] | (escape_sequence)} DQ
⟨int⟩ → [{"+" | "-"}] ("0" | ([ "0" [1-9] { [0-9] })))
⟨exponent⟩ → ("e" | "E") [{"+" | "-"}] { [0-9] }+
⟨float⟩ → [{"+" | "-"}] { [0-9] }+ "." { [0-9] }+ [(exponent)]
⟨hex⟩ → "0x" { [0-9a-fA-F] }+
⟨name⟩ → [a-z] { [^␣, . ! ' : ; ! ?] []-{} (\\r\\n\\t\\xF335) }
⟨text⟩ → DQ DQ DQ ["\\x" "\\n" {( [^\\{} ] | (escape_sequence))} DQ DQ DQ
```