

Contents

1 Init (Linux)	1
1.1 vimrc	1
1.2 template.cpp	1
1.3 run.sh	1
2 Reminder	1
2.1 Observations and Tricks	1
2.2 Bug List	1
3 Basic	1
3.1 template (optional)	1
3.2 Stress	2
3.3 PBDS	2
3.4 Random	3
4 Python	2
4.1 I/O	2
4.2 Decimal	2
5 Data Structure	2
5.1 Segment Tree	2
5.2 Heavy Light Decomposition (Benson)	2
5.3 Heavy Light Decomposition (lan)	3
5.4 Skew Heap	3
5.5 Leftist Heap	4
5.6 Persistent Treap	4
5.7 Li Chao Tree	4
5.8 Time Segment Tree	5
6 DP	5
6.1 Aliens	5
6.2 SOS DP	5
7 Graph	6
7.1 Tree Centroid	6
7.2 Bellman-Ford + SPFA	6
7.3 BCC - AP	7
7.4 BCC - Bridge	7
7.5 SCC - Tarjan	8
7.6 Eulerian Path - Undir	8
7.7 Eulerian Path - Dir	8
7.8 Hamilton Path	9
7.9 Kth Shortest Path	9
7.10 System of Difference Constraints	10
8 String	10
8.1 Rolling Hash	10
8.2 Trie	10
8.3 KMP	10
8.4 Z Value	11
8.5 Manacher	11
8.6 Suffix Array	11
8.7 SA-IS	11
8.8 Minimum Rotation	12
8.9 Aho Corasick	12
9 Geometry	12
9.1 Basic Operations	12
9.2 InPoly	12
9.3 Sort by Angle	12
9.4 Line Intersect Check	12
9.5 Line Intersection	12
9.6 Convex Hull	13
9.7 Lower Concave Hull	13
9.8 Polygon Area	13
9.9 Pick's Theorem	13
9.10 Minimum Enclosing Circle	13
9.11 PolyUnion	13
9.12 Minkowski Sum	14
10 Number Theory	14
10.1 Basic	14
10.2 Prime Sieve and Defactor	15
10.3 Harmonic Series	15
10.4 Count Number of Divisors	15
10.5 數論分塊	15
10.6 Pollard's rho	15
10.7 Miller Rabin	16
10.8 Fast Power	16
10.9 Extend GCD	16
10.10 Mu + Phi	16
10.11 Other Formulas	16
10.12 Polynomial	17
11 Linear Algebra	18
11.1 Gaussian-Jordan Elimination	18
11.2 Determinant	18
12 Flow / Matching	18
12.1 Dinic	18
12.2 ISAP	19
12.3 MCMF	19
12.4 Hopcroft-Karp	19
12.5 Cover / Independent Set	20
12.6 KM	20

13 Combinatorics	21
13.1 Catalan Number	21
13.2 Burnside's Lemma	21
14 Special Numbers	21
14.1 Fibonacci Series	21
14.2 Prime Numbers	21

1 Init (Linux)

開場流程：

```
vim ~/.vimrc
mkdir contest && cd contest

vim template.cpp
for c in {A..P}; do
    cp template.cpp $c.cpp
done

vim run.sh && chmod 777 run.sh
```

1.1 vimrc

```
syn on
set nu rnu ru cul mouse=a
set cin et ts=4 sw=4 sts=4
set autochdir
set clipboard=unnamedplus

colo koehler

no <C-h> ^
no <C-l> $
no ; :

inoremap {<CR> {<CR><Esc>kO
```

1.2 template.cpp

```
#include <bits/stdc++.h>
using namespace std;

void solve() {
}

int main() {
    ios_base::sync_with_stdio(false); cin.tie(0);
    int TEST = 1;
    //cin >> TEST;
    while (TEST--) solve();
    return 0;
}
```

1.3 run.sh

```
#!/bin/bash

g++ -std=c++17 -O2 -g -fsanitize=undefined,address $1
&& echo DONE COMPILE || exit 1
./a.out
```

2 Reminder

2.1 Observations and Tricks

- Contribution Technique
- 二分圖/Spanning Tree/DFS Tree
- 行、列操作互相獨立
- 奇偶性
- 當 s, t 遞增並且 $t = f(s)$ ，對 s 二分搜不好做，可以改成對 t 二分搜，再算 $f(t)$
- 啟發式合併
- Permutation Normalization (做一些平移對齊兩個 permutation)

- 枚舉 $a_1 \sim a_n$ 再枚舉 $a_n \sim a_1$ 可以包在一個迴圈
- 兩個凸型函數相加還是凸型函數，相減不一定

2.2 Bug List

- 沒開 long long
- 陣列戳出界／陣列開不夠大
- 寫好的函式忘記呼叫
- 0-base / 1-base
- 忘記初始化
- == 打成 =
- <= 打成 <+
- dp[i] 從 dp[i-1] 轉移時忘記特判 i > 0
- std::sort 比較運算子寫成 < 或是讓 = 的情況為 true
- 漏 case
- 線段樹改值懶標初始值不能設為 0
- DFS 的時候不小心覆寫到全域變數
- 浮點數誤差
- unsigned int128
- 多筆測資不能沒讀完直接 return
- 記得刪 cerr
- vector 超級肥，小 vector 請用 array，例如矩陣快速幂

3 Basic

3.1 template (optional)

```

1 #define F first
2 #define S second
3 #define ep emplace
4 #define eb emplace_back
5 #define endl '\n'
6
7 template<class T> using V=vector<T>;
8 typedef long long ll;
9 typedef pair<int, int> pii;
10 typedef pair<ll, ll> pll;
11 typedef pair<int, ll> pil;
12 typedef pair<ll, int> pli;
13
14 /* ===== */
15 // STL and I/O
16 // pair
17 template<typename T1, typename T2>
18 ostream& operator<<(ostream& os, pair<T1, T2> p) {
19     return os << "(" << p.first << ", " << p.second <<
20         ")";
21 }
22 template<typename T1, typename T2>
23 istream& operator>>(istream& is, pair<T1, T2>& p) {
24     return is >> p.first >> p.second;
25 }
26
27 // vector
28 template<typename T>
29 istream& operator>>(istream& is, vector<T>& v) {
30     for (auto& x : v) is >> x;
31     return is;
32 }
33
34 template<typename T>
35 ostream& operator<<(ostream& os, const vector<T>& v) {
36     for (const auto& x : v) os << x << ' ';
37     return os;
38 }
39
40 /* ===== */
41 // debug(), output()
42 #define RED "\x1b[31m"
43 #define GREEN "\x1b[32m"
44 #define YELLOW "\x1b[33m"
45 #define GRAY "\x1b[90m"
46 #define COLOREND "\x1b[0m"
47
48 void _debug() {}
49 template<typename A, typename... B> void _debug(A a, B...
50     b) { cerr << a << ' ', _debug(b...); }
51 #define debug(...) cerr<<GRAY<<#__VA_ARGS__<<": "<<
52     COLOREND, _debug(__VA_ARGS__), cerr<<endl

```

```

46
47 void _output() {}
48 template<typename A, typename... B> void _output(A a, B
49     ... b) { cout << a << ' ', _output(b...); }
50 #define output(...) _output(__VA_ARGS__), cout<<endl
51 /* ===== */
52 // BASIC ALGORITHM
53 string binary(ll x, int b = -1) {
54     if (b == -1) b = __lg(x) + 1;
55     string s = "";
56     for (int k = b - 1; k >= 0; k--) {
57         s.push_back((x & (1LL<<k)) ? '1' : '0');
58     }
59     return s;
60 }
61 /* ===== */
62 // CONSTANT
63 const int INF = 1.05e9;
64 const ll LINF = 4e18;
65 const int MOD = 1e9 + 7;
66 //const int MOD = 998244353;
67 const int maxn = 2e5 + 3;

```

3.2 Stress

```

1 g++ gen.cpp -o gen.out
2 g++ ac.cpp -o ac.out
3 g++ wa.cpp -o wa.out
4 for ((i=0;;i++))
5 do
6     echo "$i"
7     ./gen.out > in.txt
8     ./ac.out < in.txt > ac.txt
9     ./wa.out < in.txt > wa.txt
10    diff ac.txt wa.txt || break
11 done

```

3.3 PBDS

```

1 #include <bits/extc++.h>
2 using namespace __gnu_pbds;
3
4 // map
5 tree<int, int, less<>, rb_tree_tag,
6     tree_order_statistics_node_update> tr;
7 tr.order_of_key(element);
8 tr.find_by_order(rank);
9
10 // set
11 tree<int, null_type, less<>, rb_tree_tag,
12     tree_order_statistics_node_update> tr;
13 tr.order_of_key(element);
14 tr.find_by_order(rank);
15
16 // priority queue
17 __gnu_pbds::priority_queue<int, less<int> > big_q; //
18     Big First
19 __gnu_pbds::priority_queue<int, greater<int> > small_q;
20     // Small First
21 q1.join(q2); // join

```

3.4 Random

```

1 mt19937 gen(chrono::steady_clock::now().
2     time_since_epoch().count());
3 #define RANDINT(a, b) uniform_int_distribution<int> (a,
4     b)(rng) // inclusive
5 #define RANDLL(a, b) uniform_int_distribution<long long>
6     >(a, b)(rng) // inclusive
7 #define RANDFLOAT(a, b) uniform_real_distribution<float>
8     >(a, b)(rng) // exclusive
9 #define RANDDOUBLE(a, b) uniform_real_distribution<
10     double>(a, b)(rng) // exclusive
11 shuffle(v.begin(), v.end(), gen);

```

4 Python

4.1 I/O

```

1 import sys
2 input = sys.stdin.readline
3
4 # Input
5 def readInt():
6     return int(input())
7 def readList():
8     return list(map(int, input().split()))
9 def readStr():
10    s = input()
11    return list(s[:len(s) - 1])
12 def readVars():
13    return map(int, input().split())
14
15 # Output
16 sys.stdout.write(string)
17
18 # faster
19 def main():
20     pass
21 main()

```

4.2 Decimal

```

1 from decimal import *
2 getcontext().prec = 2500000
3 getcontext().Emax = 2500000
4 a,b = Decimal(input()),Decimal(input())
5 a*=b
6 print(a)

```

5 Data Structure

5.1 Segment Tree

```

1 // Author: Gino
2 struct node {
3     ll sum, add, mod; int ln;
4     node(): sum(0), add(0), mod(0), ln(0) {}
5 };
6
7 struct segT {
8     int n;
9     vector<ll> ar;
10    vector<node> st;
11
12    void init(int _n) {
13        n = _n;
14        reset(ar, n, 0LL);
15        reset(st, n*4);
16    }
17    void pull(int cl, int cr, int i) {
18        st[i].sum = st[cl].sum + st[cr].sum;
19    }
20    void push(int cl, int cr, int i) {
21        ll md = st[i].mod, ad = st[i].add;
22        if (md) {
23            st[cl].sum = md * st[cl].ln, st[cr].sum =
24                md * st[cr].ln;
25            st[cl].mod = md, st[cr].mod = md;
26            st[i].mod = 0;
27        }
28        if (ad) {
29            st[cl].sum += ad * st[cl].ln, st[cr].sum +=
30                ad * st[cr].ln;
31            st[cl].add += ad, st[cr].add += ad;
32            st[i].add = 0;
33        }
34    }
35    void build(int l, int r, int i) {
36        if (l == r) {
37            st[i].sum = ar[l];
38            st[i].ln = 1;
39            return;
40        }
41        int mid = (l+r)>>1, cl = i<<1, cr = i<<1|1;
42        build(l, mid, cl);
43        build(mid + 1, r, cr);
44        pull(cl, cr, i);

```

```

43    }
44    void addval(int ql, int qr, ll val, int l, int r,
45        int i) {
46        if (qr < l || r < ql) return;
47        if (ql <= l && r <= qr) {
48            st[i].sum += val * st[i].ln;
49            st[i].add += val;
50            return;
51        }
52        int mid = (l+r)>>1, cl = i<<1, cr = i<<1|1;
53        push(cl, cr, i);
54        addval(ql, qr, val, l, mid, cl);
55        addval(ql, qr, val, mid + 1, r, cr);
56        pull(cl, cr, i);
57    }
58    void modify(int ql, int qr, ll val, int l, int r,
59        int i) {
60        if (qr < l || r < ql) return;
61        if (ql <= l && r <= qr) {
62            st[i].sum = val * st[i].ln;
63            st[i].add = 0;
64            st[i].mod = val;
65            return;
66        }
67        int mid = (l+r)>>1, cl = i<<1, cr = i<<1|1;
68        push(cl, cr, i);
69        modify(ql, qr, val, l, mid, cl);
70        modify(ql, qr, val, mid+1, r, cr);
71        pull(cl, cr, i);
72    }
73    ll query(int ql, int qr, int l, int r, int i) {
74        if (qr < l || r < ql) return 0;
75        if (ql <= l && r <= qr) return st[i].sum;
76        int mid = (l+r)>>1, cl = i<<1, cr = i<<1|1;
77        push(cl, cr, i);
78        return (query(ql, qr, l, mid, cl) +
79            query(ql, qr, mid+1, r, cr));
80    }
81 };

```

5.2 Heavy Light Decomposition (Benson)

```

1 // Author: Benson
2 const int N = 2e5+5;
3 vector<int> adj[N];
4
5 int dsu[N], sz[N], head[N], heavy[N], arr[N], num[N],
6     dep[N], par[N], visited[N], val[N], t;
7
8 int tr[N<<2], tag[N<<2];
9
10 int combine(int a, int b){
11     return max(a,b);
12 }
13
14 void push(int idx){
15     if(tag[idx]){
16         tr[idx<<1] = tag[idx];
17         tr[idx<<1|1] = tag[idx];
18         tag[idx<<1] = tag[idx];
19         tag[idx<<1|1] = tag[idx];
20         tag[idx] = 0;
21     }
22 }
23
24 void modify(int ml, int mr, int val, int idx, int l,
25     int r){
26     if(ml > mr) swap(ml,mr);
27     if(l!=r) push(idx);
28     if(ml <= l && r <= mr){
29         tr[idx] = val;
30         tag[idx] = val;
31         return;
32     }
33     int mid = l+r>>1;
34     if(ml <= mid) modify(ml,mr,val,idx<<1,l,mid);
35     if(mr > mid) modify(ml,mr,val,idx<<1|1,mid+1,r);
36     tr[idx] = combine(tr[idx<<1],tr[idx<<1|1]);
37 }
38
39 int query(int ml, int mr, int idx, int l, int r){

```

```

38     if(ml > mr) swap(ml,mr);
39     if(l!=r) push(idx);
40     if(ml <= l && r <= mr){
41         return tr[idx];
42     }
43     int mid = l+r>>1;
44     if(mr <= mid) return query(ml,mr,idx<<1,l,mid);
45     if(ml > mid) return query(ml,mr,idx<<1|1,mid+1,r);
46     return combine(query(ml,mr,idx<<1,l,mid),query(ml,
47         mr,idx<<1|1,mid+1,r));
48 }
49 void dfs(int u, int p){
50     int mxsz = 0, idx = 0;
51     sz[u] = 1;
52     visited[u] = 1;
53     for(auto v : adj[u]){
54         if(v==p) continue;
55         dep[v] = dep[u]+1;
56         par[v] = u;
57         dfs(v,u);
58         if(sz[v] > mxsz) mxsz = sz[v], idx = v;
59         sz[u] += sz[v];
60     }
61     heavy[u] = idx;
62 }
63
64 void decompose(int u, int h){
65     head[u] = h;
66     arr[u] = ++t;
67     visited[u] = 1;
68     if(heavy[u]) decompose(heavy[u],h);
69
70     for(auto v : adj[u]){
71         if(v==par[u]||v==heavy[u]) continue;
72         decompose(v,v);
73     }
74 }
75
76 int hld_query(int u, int v){
77     int res = 0;
78     while(head[u]!=head[v]){
79         if(dep[head[u]] < dep[head[v]]) swap(u,v);
80         res = max(res,query(arr[head[u]],arr[u],1,1,t));
81         u = par[head[u]];
82     }
83     if(dep[u] > dep[v]) swap(u,v);
84     res = max(res,query(arr[u],arr[v],1,1,t));
85     return res;
86 }
87
88 void hld_modify(int u, int v, int val){
89     if(dep[u] > dep[v]) swap(u,v);
90     while(head[u]!=head[v]){
91         if(dep[head[u]] < dep[head[v]]) swap(u,v);
92         modify(arr[head[u]],arr[u],val,1,1,t);
93         u = par[head[u]];
94     }
95     if(dep[u] > dep[v]) swap(u,v);
96     modify(arr[u],arr[v],val,1,1,t);
97 }
98 }

```

```

16     else modify(p,k,i<<1|1,m,r);
17     arr[i]=max(arr[i<<1],arr[i<<1|1]);
18 }
19 int query(int ql,int qr,int i=1,int l=0,int r=maxn){
20     if(qr<=l||r<=ql) return 0;
21     if(ql<=l&&r<=qr) return arr[i];
22     if(qr<=m) return query(ql,qr,i<<1,l,m);
23     if(m<=ql) return query(ql,qr,i<<1|1,m,r);
24     return max(query(ql,qr,i<<1,l,m),query(ql,qr,i
25         <<1|1,m,r));
26 }
27 #undef m
28 inline void solve(){
29     int n,q;cin>>n>>q;
30     V<int> v(n);
31     for(auto& i:v)
32         cin>>i;
33     V<V<int>> e(n);
34     for(int i=1;i<n;i++){
35         int a,b;cin>>a>>b,a--,b--;
36         e[a].emplace_back(b);
37         e[b].emplace_back(a);
38     }
39     V<int> d(n,0),f(n,0),sz(n,1),son(n,-1);
40     F<void(int,int)> dfs1=
41     [&](int x,int pre){
42         for(auto i:e[x]) if(i!=pre){
43             d[i]=d[x]+1,f[i]=x;
44             dfs1(i,x),sz[x]+=sz[i];
45             if(!~son[x]||sz[son[x]]<sz[i])
46                 son[x]=i;
47         }
48     };dfs1(0,0);
49     V<int> top(n,0),dfn(n,-1),rnk(n,0);
50     F<void(int,int)> dfs2=
51     [&](int x,int t){
52         static int cnt=0;
53         dfn[x]=cnt++,rnk[dfn[x]]=x,top[x]=t;
54         if(!~son[x]) return;
55         dfs2(son[x],t);
56         for(auto i:e[x])
57             if(!~dfn[i]) dfs2(i,i);
58     };dfs2(0,0);
59     V<int> dfnv(n);
60     for(int i=0;i<n;i++)
61         dfnv[dfn[i]]=v[i];
62     build(dfnv);
63     while(q--){
64         int op,a,b;cin>>op>>a>>b;
65         switch(op){
66             case 1:{
67                 modify(dfn[a-1],b);
68             }break;
69             case 2:{
70                 a--,b--;
71                 int ans=0;
72                 while(top[a]!=top[b]){
73                     if(d[top[a]]>d[top[b]]) swap(a,b);
74                     ans=max(ans,query(dfn[top[b]],dfn[b]+1)
75                         );
76                     b=f[top[b]];
77                 }
78                 if(dfn[a]>dfn[b]) swap(a,b);
79                 ans=max(ans,query(dfn[a],dfn[b]+1));
80                 cout<<ans<<endl;
81             }break;
82         }
83     }
84 }

```

5.3 Heavy Light Decomposition (Ian)

```

1 // Author: Ian
2 // TODO: (2025/08/26) Debug Lazy Segment Tree
3 constexpr int maxn=2e5+5;
4 int arr[(maxn+1)<<2];
5 #define m ((l+r)>>1)
6 void build(V<int>& v,int i=1,int l=0,int r=maxn){
7     if((int)v.size()<=l) return;
8     if(r-l==1){arr[i]=v[l];return;}
9     build(v,i<<1,l,m),build(v,i<<1|1,m,r);
10    arr[i]=max(arr[i<<1],arr[i<<1|1]);
11 }
12 void modify(int p,int k,int i=1,int l=0,int r=maxn){
13     if(p<l||r<=p) return;
14     if(r-l==1){arr[i]=k;return;}
15     if(p<m) modify(p,k,i<<1,l,m);

```

5.4 Skew Heap

```

1 // Author: Ian
2 // Function: 插入、删除最小值、合併兩個左偏樹都能 O(Log
3 //            n)
4 struct node{
5     node *l,*r;
6     int v;
7     node(int x):v(x){
8         l=r=nullptr;
9     }

```

```

9 };
10 node* merge(node* a, node* b){
11     if(!a||!b) return a?:b;
12     // min heap
13     if(a->v>b->v) swap(a,b);
14     a->r=merge(a->r,b);
15     swap(a->l,a->r);
16     return a;
17 }

```

5.5 Leftist Heap

```

1 // Author: Unknown
2 // Function: 插入、删除最小值、合併兩個左偏樹都能  $O(\log n)$ 
3 struct node{
4     node *l,*r;
5     int d, v;
6     node(int x):d(1),v(x){
7         l=r=nullptr;
8     }
9 };
10 static inline int d(node* x){return x?x->d:0;}
11 node* merge(node* a,node* b){
12     if(!a||!b) return a?:b;
13     // min heap
14     if(a->v>b->v) swap(a,b);
15     a->r=merge(a->r,b);
16     if(d(a->l)<d(a->r))
17         swap(a->l,a->r);
18     a->d=d(a->r)+1;
19     return a;
20 }

```

5.6 Persistent Treap

```

1 // Author: Ian
2 struct node {
3     node *l, *r;
4     char c; int v, sz;
5     node(char x = '$'): c(x), v(mt()), sz(1) {
6         l = r = nullptr;
7     }
8     node(node* p) { *this = *p; }
9     void pull() {
10         sz = 1;
11         for (auto i : {l, r})
12             if (i) sz += i->sz;
13     }
14 } arr[maxn], *ptr = arr;
15 inline int size(node* p) {return p ? p->sz : 0;}
16 node* merge(node* a, node* b) {
17     if (!a || !b) return a ? : b;
18     if (a->v < b->v) {
19         node* ret = new(ptr++) node(a);
20         ret->r = merge(ret->r, b); ret->pull();
21         return ret;
22     }
23     else {
24         node* ret = new(ptr++) node(b);
25         ret->l = merge(a, ret->l); ret->pull();
26         return ret;
27     }
28 }
29 P<node*> split(node* p, int k) {
30     if (!p) return {nullptr, nullptr};
31     if (k >= size(p->l) + 1) {
32         auto [a, b] = split(p->r, k - size(p->l) - 1);
33         node* ret = new(ptr++) node(p);
34         ret->r = a; ret->pull();
35         return {ret, b};
36     }
37     else {
38         auto [a, b] = split(p->l, k);
39         node* ret = new(ptr++) node(p);
40         ret->l = b; ret->pull();
41         return {a, ret};
42     }
43 }

```

5.7 Li Chao Tree

```

1 // Author: Unknown
2 // Function: Query maximum value of  $L_i(x)$ ,  $L_i$  is the  $i$ -th line.
3 typedef long double ld;
4 constexpr int maxn = 5e4 + 5;
5 struct line {
6     ld a, b;
7     ld operator()(ld x) {return a * x + b;}
8 } arr[(maxn + 1) << 2];
9 bool operator<(line a, line b) {return a.a < b.a;}
10 #define m ((l+r)>>1)
11 void insert(line x, int i = 1, int l = 0, int r = maxn)
12 {
13     if (r - l == 1) {
14         if (x(l) > arr[i](l))
15             arr[i] = x;
16         return;
17     }
18     line a = max(arr[i], x), b = min(arr[i], x);
19     if (a(m) > b(m))
20         arr[i] = a, insert(b, i << 1, l, m);
21     else
22         arr[i] = b, insert(a, i << 1 | 1, m, r);
23 }
24 ld query(int x, int i = 1, int l = 0, int r = maxn) {
25     if (x < l || r <= x) return -numeric_limits<ld>::max();
26     if (r - l == 1) return arr[i](x);
27     return max({arr[i](x), query(x, i << 1, l, m), query(
28         x, i << 1 | 1, m, r)});
29 }
30 #undef m

```

5.8 Time Segment Tree

```

1 // Author: Ian
2 constexpr int maxn = 1e5 + 5;
3 V<P<int>> arr[(maxn + 1) << 2];
4 V<int> dsu, sz;
5 V<tuple<int, int, int>> his;
6 int cnt, q;
7 int find(int x) {
8     return x == dsu[x] ? x : find(dsu[x]);
9 }
10 inline bool merge(int x, int y) {
11     int a = find(x), b = find(y);
12     if (a == b) return false;
13     if (sz[a] > sz[b]) swap(a, b);
14     his.emplace_back(a, b, sz[b]), dsu[a] = b, sz[b] +=
15         sz[a];
16     return true;
17 }
18 inline void undo() {
19     auto [a, b, s] = his.back(); his.pop_back();
20     dsu[a] = a, sz[b] = s;
21 }
22 #define m ((l + r) >> 1)
23 void insert(int ql, int qr, P<int> x, int i = 1, int l
24     = 0, int r = q) {
25     // debug(ql, qr, x); return;
26     if (qr <= l || r <= ql) return;
27     if (ql <= l && r <= qr) {arr[i].push_back(x);
28         return;}
29     if (qr <= m)
30         insert(ql, qr, x, i << 1, l, m);
31     else if (m <= ql)
32         insert(ql, qr, x, i << 1 | 1, m, r);
33     else {
34         insert(ql, qr, x, i << 1, l, m);
35         insert(ql, qr, x, i << 1 | 1, m, r);
36     }
37 }
38 void traversal(V<int>& ans, int i = 1, int l = 0, int r
39     = q) {
40     int opcnt = 0;
41     // debug(i, l, r);
42     for (auto [a, b] : arr[i])
43         if (merge(a, b))
44             opcnt++, cnt--;
45 }

```

```

41     if (r - l == 1) ans[l] = cnt;
42     else {
43         traversal(ans, i << 1, l, m);
44         traversal(ans, i << 1 | 1, m, r);
45     }
46     while (opcnt--)
47         undo(), cnt++;
48     arr[i].clear();
49 }
50 #undef m
51 inline void solve() {
52     int n, m; cin >> n >> m >> q, q++;
53     dsu.resize(cnt = n), sz.assign(n, 1);
54     iota(dsu.begin(), dsu.end(), 0);
55     // a, b, time, operation
56     unordered_map<ll, V<int>> s;
57     for (int i = 0; i < m; i++) {
58         int a, b; cin >> a >> b;
59         if (a > b) swap(a, b);
60         s[((ll)a << 32) | b].emplace_back(0);
61     }
62     for (int i = 1; i < q; i++) {
63         int op, a, b;
64         cin >> op >> a >> b;
65         if (a > b) swap(a, b);
66         switch (op) {
67             case 1:
68                 s[((ll)a << 32) | b].push_back(i);
69                 break;
70             case 2:
71                 auto tmp = s[((ll)a << 32) | b].back();
72                 s[((ll)a << 32) | b].pop_back();
73                 insert(tmp, i, P<int> {a, b});
74             }
75     }
76     for (auto [p, v] : s) {
77         int a = p >> 32, b = p & -1;
78         while (v.size()) {
79             insert(v.back(), q, P<int> {a, b});
80             v.pop_back();
81         }
82     }
83     V<int> ans(q);
84     traversal(ans);
85     for (auto i : ans)
86         cout << i << ' ';
87     cout << endl;
88 }

```

6 DP

6.1 Aliens

```

1 // Author: Gino
2 // Function: TODO
3 int n; ll k;
4 vector<ll> a;
5 vector<pll> dp[2];
6 void init() {
7     cin >> n >> k;
8     for (auto& d : dp) d.clear(), d.resize(n);
9     a.clear(); a.resize(n);
10    for (auto& i : a) cin >> i;
11 }
12 pll calc(ll p) {
13     dp[0][0] = make_pair(0, 0);
14     dp[1][0] = make_pair(-a[0], 0);
15     for (int i = 1; i < n; i++) {
16         if (dp[0][i-1].first > dp[1][i-1].first + a[i] - p) {
17             dp[0][i] = dp[0][i-1];
18         } else if (dp[0][i-1].first < dp[1][i-1].first + a[i] - p) {
19             dp[0][i] = make_pair(dp[1][i-1].first + a[i] - p,
20                                 dp[1][i-1].second + 1);
21         } else {
22             dp[0][i] = make_pair(dp[0][i-1].first, min(dp[0][i-1].second, dp[1][i-1].second + 1));
23         }
24     }
25     if (dp[0][i-1].first - a[i] > dp[1][i-1].first) {

```

```

24         dp[1][i] = make_pair(dp[0][i-1].first - a[i], dp
25                               [0][i-1].second);
26     } else if (dp[0][i-1].first - a[i] < dp[1][i-1].
27               first) {
28         dp[1][i] = dp[1][i-1];
29     } else {
30         dp[1][i] = make_pair(dp[1][i-1].first, min(dp[0][i-1].second, dp[1][i-1].second));
31     }
32 }
33 return dp[0][n-1];
34 }
35 void solve() {
36     ll l = 0, r = 1e7;
37     pll res = calc(0);
38     if (res.second <= k) return cout << res.first << endl
39                                     , void();
40     while (l < r) {
41         ll mid = (l+r)>>1;
42         res = calc(mid);
43         if (res.second <= k) r = mid;
44         else l = mid+1;
45     }
46     res = calc(l);
47     cout << res.first + k*l << endl;
48 }

```

6.2 SOS DP

```

1 // Author: Gino
2 // Function: Solve problems that enumerates subsets of
3 //           subsets (3^n => n*2^n)
4 for (int msk = 0; msk < (1<<n); msk++) {
5     for (int i = 1; i <= n; i++) {
6         if (msk & (1<<(i-1))) {
7             // dp[msk][i] = dp[msk][i-1] + dp[msk ^
8             //           (1<<(i-1))][i-1];
9         } else {
10            // dp[msk][i] = dp[msk][i-1];
11        }
12    }
13 }

```

7 Graph

7.1 Tree Centroid

```

1 int n;
2 vector<vector<int>> G;
3
4 pii centroid;
5 vector<int> sz, mxcc; // mxcc[u]: max component size
6 // after removing u
7 void dfs(int u, int p) {
8     sz[u] = 1;
9     for (auto& v : G[u]) {
10         if (v == p) continue;
11         dfs(v, u);
12         sz[u] += sz[v];
13         mxcc[u] = max(mxcc[u], sz[v]);
14     }
15     mxcc[u] = max(mxcc[u], n - sz[u]);
16 }
17
18 void find_centroid() {
19     centroid = pii{-1, -1};
20     reset(sz, n + 1, 0);
21     reset(mxcc, n + 1, 0);
22     dfs(1, 1);
23     for (int u = 1; u <= n; u++) {
24         if (mxcc[u] <= n / 2) {
25             if (centroid.first != -1) centroid.second = u;
26             else centroid.first = u;
27         }
28     }
29 }

```


7.2 Bellman-Ford + SPFA

```

1 int n, m;
2
3 // Graph
4 vector<vector<pair<int, ll>>> g;
5 vector<ll> dis;
6 vector<bool> negCycle;
7
8 // SPFA
9 vector<int> rlx;
10 queue<int> q;
11 vector<bool> inq;
12 vector<int> pa;
13 void SPFA(vector<int>& src) {
14     dis.assign(n+1, LINF);
15     negCycle.assign(n+1, false);
16     rlx.assign(n+1, 0);
17     while (!q.empty()) q.pop();
18     inq.assign(n+1, false);
19     pa.assign(n+1, -1);
20
21     for (auto& s : src) {
22         dis[s] = 0;
23         q.push(s); inq[s] = true;
24     }
25
26     while (!q.empty()) {
27         int u = q.front();
28         q.pop(); inq[u] = false;
29         if (rlx[u] >= n) {
30             negCycle[u] = true;
31         }
32         else for (auto& e : g[u]) {
33             int v = e.first;
34             ll w = e.second;
35             if (dis[v] > dis[u] + w) {
36                 dis[v] = dis[u] + w;
37                 rlx[v] = rlx[u] + 1;
38                 pa[v] = u;
39                 if (!inq[v]) {
40                     q.push(v);
41                     inq[v] = true;
42                 }
43             }
44         }
45     }
46
47 // Bellman-Ford
48 queue<int> q;
49 vector<int> pa;
50 void BellmanFord(vector<int>& src) {
51     dis.assign(n+1, LINF);
52     negCycle.assign(n+1, false);
53     pa.assign(n+1, -1);
54
55     for (auto& s : src) dis[s] = 0;
56
57     for (int rlx = 1; rlx <= n; rlx++) {
58         for (int u = 1; u <= n; u++) {
59             if (dis[u] == LINF) continue; // Important
60             !!
61             for (auto& e : g[u]) {
62                 int v = e.first; ll w = e.second;
63                 if (dis[v] > dis[u] + w) {
64                     dis[v] = dis[u] + w;
65                     pa[v] = u;
66                     if (rlx == n) negCycle[v] = true;
67                 }
68             }
69         }
70     }
71
72 // Negative Cycle Detection
73 void NegCycleDetect() {
74     /* No Neg Cycle: NO
75     Exist Any Neg Cycle:
76     YES
77     v0 v1 v2 ... vk v0 */
78
79     vector<int> src;
80     for (int i = 1; i <= n; i++)
81         src.emplace_back(i);
82
83     SPFA(src);
84     // BellmanFord(src);

```

```

80
81     int ptr = -1;
82     for (int i = 1; i <= n; i++) if (negCycle[i])
83         { ptr = i; break; }
84
85     if (ptr == -1) { return cout << "NO" << endl, void
86         (); }
87
88     cout << "YES\n";
89     vector<int> ans;
90     vector<bool> vis(n+1, false);
91
92     while (true) {
93         ans.emplace_back(ptr);
94         if (vis[ptr]) break;
95         vis[ptr] = true;
96         ptr = pa[ptr];
97     }
98     reverse(ans.begin(), ans.end());
99
100     vis.assign(n+1, false);
101     for (auto& x : ans) {
102         cout << x << ' ';
103         if (vis[x]) break;
104         vis[x] = true;
105     }
106     cout << endl;
107 }
108
109 // Distance Calculation
110 void calcDis(int s) {
111     vector<int> src;
112     src.emplace_back(s);
113     SPFA(src);
114     // BellmanFord(src);
115
116     while (!q.empty()) q.pop();
117     for (int i = 1; i <= n; i++)
118         if (negCycle[i]) q.push(i);
119
120     while (!q.empty()) {
121         int u = q.front(); q.pop();
122         for (auto& e : g[u]) {
123             int v = e.first;
124             if (!negCycle[v]) {
125                 q.push(v);
126                 negCycle[v] = true;
127             }
128         }
129     }

```

7.3 BCC - AP

```

1 int n, m;
2 int low[maxn], dfn[maxn], instp;
3 vector<int> E, g[maxn];
4 bitset<maxn> isap;
5 bitset<maxn> vis;
6 stack<int> stk;
7 int bccnt;
8 vector<int> bcc[maxn];
9 inline void popout(int u) {
10     bccnt++;
11     bcc[bccnt].emplace_back(u);
12     while (!stk.empty()) {
13         int v = stk.top();
14         if (u == v) break;
15         stk.pop();
16         bcc[bccnt].emplace_back(v);
17     }
18 }
19
20 void dfs(int u, bool rt = 0) {
21     stk.push(u);
22     low[u] = dfn[u] = ++instp;
23     int kid = 0;
24     Each(e, g[u]) {
25         if (vis[e]) continue;
26         vis[e] = true;
27         int v = E[e]^u;
28         if (!dfn[v]) {
29             // tree edge
30             kid++; dfs(v);
31             low[u] = min(low[u], low[v]);

```

```

31     if (!rt && low[v] >= dfn[u]) {
32         // bcc found: u is ap
33         isap[u] = true;
34         popout(u);
35     }
36     } else {
37         // back edge
38         low[u] = min(low[u], dfn[v]);
39     }
40 }
41 // special case: root
42 if (rt) {
43     if (kid > 1) isap[u] = true;
44     popout(u);
45 }
46 }
47 void init() {
48     cin >> n >> m;
49     fill(low, low+maxn, INF);
50     REP(i, m) {
51         int u, v;
52         cin >> u >> v;
53         g[u].emplace_back(i);
54         g[v].emplace_back(i);
55         E.emplace_back(u^v);
56     }
57 }
58 void solve() {
59     FOR(i, 1, n+1, 1) {
60         if (!dfn[i]) dfs(i, true);
61     }
62     vector<int> ans;
63     int cnt = 0;
64     FOR(i, 1, n+1, 1) {
65         if (isap[i]) cnt++, ans.emplace_back(i);
66     }
67     cout << cnt << endl;
68     Each(i, ans) cout << i << ' ';
69     cout << endl;
70 }

```

7.4 BCC - Bridge

```

1  int n, m;
2  vector<int> g[maxn], E;
3  int low[maxn], dfn[maxn], instp;
4  int bccnt, bccid[maxn];
5  stack<int> stk;
6  bitset<maxm> vis, isbrg;
7  void init() {
8      cin >> n >> m;
9      REP(i, m) {
10         int u, v;
11         cin >> u >> v;
12         E.emplace_back(u^v);
13         g[u].emplace_back(i);
14         g[v].emplace_back(i);
15     }
16     fill(low, low+maxn, INF);
17 }
18 void popout(int u) {
19     bccnt++;
20     while (!stk.empty()) {
21         int v = stk.top();
22         if (v == u) break;
23         stk.pop();
24         bccid[v] = bccnt;
25     }
26 }
27 void dfs(int u) {
28     stk.push(u);
29     low[u] = dfn[u] = ++instp;
30
31     Each(e, g[u]) {
32         if (vis[e]) continue;
33         vis[e] = true;
34
35         int v = E[e]^u;
36         if (dfn[v]) {
37             // back edge
38             low[u] = min(low[u], dfn[v]);

```

```

39     } else {
40         // tree edge
41         dfs(v);
42         low[u] = min(low[u], low[v]);
43         if (low[v] == dfn[v]) {
44             isbrg[e] = true;
45             popout(u);
46         }
47     }
48 }
49 }
50 void solve() {
51     FOR(i, 1, n+1, 1) {
52         if (!dfn[i]) dfs(i);
53     }
54     vector<pii> ans;
55     vis.reset();
56     FOR(u, 1, n+1, 1) {
57         Each(e, g[u]) {
58             if (!isbrg[e] || vis[e]) continue;
59             vis[e] = true;
60             int v = E[e]^u;
61             ans.emplace_back(mp(u, v));
62         }
63     }
64     cout << (int)ans.size() << endl;
65     Each(e, ans) cout << e.F << ' ' << e.S << endl;
66 }

```

7.5 SCC - Tarjan

```

1  // 2-SAT
2  vector<int> E, g[maxn]; // 1~n, n+1~2n
3  int low[maxn], in[maxn], instp;
4  int sccnt, sccid[maxn];
5
6  stack<int> stk;
7  bitset<maxn> ins, vis;
8
9  int n, m;
10
11 void init() {
12     cin >> m >> n;
13     E.clear();
14     fill(g, g+maxn, vector<int>());
15     fill(low, low+maxn, INF);
16     memset(in, 0, sizeof(in));
17     instp = 1;
18     sccnt = 0;
19     memset(sccid, 0, sizeof(sccid));
20     ins.reset();
21     vis.reset();
22 }
23
24 inline int no(int u) {
25     return (u > n ? u-n : u+n);
26 }
27
28 int ecnt = 0;
29 inline void clause(int u, int v) {
30     E.eb(no(u)^v);
31     g[no(u)].eb(ecnt++);
32     E.eb(no(v)^u);
33     g[no(v)].eb(ecnt++);
34 }
35
36 void dfs(int u) {
37     in[u] = instp++;
38     low[u] = in[u];
39     stk.push(u);
40     ins[u] = true;
41
42     Each(e, g[u]) {
43         if (vis[e]) continue;
44         vis[e] = true;
45
46         int v = E[e]^u;
47         if (ins[v]) low[u] = min(low[u], in[v]);
48         else if (!in[v]) {
49             dfs(v);
50             low[u] = min(low[u], low[v]);

```



```

51     }
52 }
53
54 if (low[u] == in[u]) {
55     sccnt++;
56     while (!stk.empty()) {
57         int v = stk.top();
58         stk.pop();
59         ins[v] = false;
60         sccid[v] = sccnt;
61         if (u == v) break;
62     }
63 }
64 }
65
66 int main() {
67     WiWiHorz
68     init();
69
70     REP(i, m) {
71         char su, sv;
72         int u, v;
73         cin >> su >> u >> sv >> v;
74         if (su == '-') u = no(u);
75         if (sv == '-') v = no(v);
76         clause(u, v);
77     }
78
79     FOR(i, 1, 2*n+1, 1) {
80         if (!in[i]) dfs(i);
81     }
82
83     FOR(u, 1, n+1, 1) {
84         int du = no(u);
85         if (sccid[u] == sccid[du]) {
86             return cout << "IMPOSSIBLE\n", 0;
87         }
88     }
89
90     FOR(u, 1, n+1, 1) {
91         int du = no(u);
92         cout << (sccid[u] < sccid[du] ? '+' : '-') << ' ';
93     }
94     cout << endl;
95
96     return 0;
97 }

```

7.6 Eulerian Path - Undir

```

1 // from 1 to n
2 #define gg return cout << "IMPOSSIBLE\n", void();
3
4 int n, m;
5 vector<int> g[maxn];
6 bitset<maxn> inodd;
7
8 void init() {
9     cin >> n >> m;
10    inodd.reset();
11    for (int i = 0; i < m; i++) {
12        int u, v; cin >> u >> v;
13        inodd[u] = inodd[u] ^ true;
14        inodd[v] = inodd[v] ^ true;
15        g[u].emplace_back(v);
16        g[v].emplace_back(u);
17    }
18    stack<int> stk;
19    void dfs(int u) {
20        while (!g[u].empty()) {
21            int v = g[u].back();
22            g[u].pop_back();
23            dfs(v);
24        }
25        stk.push(u);

```

7.7 Eulerian Path - Dir

```

1 // from node 1 to node n
2 #define gg return cout << "IMPOSSIBLE\n", 0
3
4 int n, m;
5 vector<int> g[maxn];
6 stack<int> stk;
7 int in[maxn], out[maxn];
8
9 void init() {
10    cin >> n >> m;
11    for (int i = 0; i < m; i++) {
12        int u, v; cin >> u >> v;
13        g[u].emplace_back(v);
14        out[u]++, in[v]++;
15    }
16    for (int i = 1; i <= n; i++) {
17        if (i == 1 && out[i]-in[i] != 1) gg;
18        if (i == n && in[i]-out[i] != 1) gg;
19        if (i != 1 && i != n && in[i] != out[i]) gg;
20    }
21    void dfs(int u) {
22        while (!g[u].empty()) {
23            int v = g[u].back();
24            g[u].pop_back();
25            dfs(v);
26        }
27        stk.push(u);
28    }
29    void solve() {
30        dfs(1)
31        for (int i = 1; i <= n; i++)
32            if ((int)g[i].size()) gg;
33        while (!stk.empty()) {
34            int u = stk.top();
35            stk.pop();
36            cout << u << ' ';
37    }

```

7.8 Hamilton Path

```

1 // top down DP
2 // Be Aware Of Multiple Edges
3 int n, m;
4 ll dp[maxn][1<<maxn];
5 int adj[maxn][maxn];
6
7 void init() {
8     cin >> n >> m;
9     fill(dp[0], dp[maxn-1]+(1<<maxn), -1);
10 }
11
12 void DP(int i, int msk) {
13     if (dp[i][msk] != -1) return;
14     dp[i][msk] = 0;
15     REP(j, n) if (j != i && (msk & (1<<j)) && adj[j][i]) {
16         int sub = msk ^ (1<<i);
17         if (dp[j][sub] == -1) DP(j, sub);
18         dp[i][msk] += dp[j][sub] * adj[j][i];
19         if (dp[i][msk] >= MOD) dp[i][msk] %= MOD;
20     }
21 }
22
23 int main() {
24     WiWiHorz
25     init();
26
27     REP(i, m) {
28         int u, v;
29         cin >> u >> v;
30         if (u == v) continue;
31         adj[--u][--v]++;
32     }
33
34     dp[0][1] = 1;
35     FOR(i, 1, n, 1) {
36         dp[i][1] = 0;
37         dp[i][1|(1<<i)] = adj[0][i];
38     }
39     FOR(msk, 1, (1<<n), 1) {

```

```

41     if (msk == 1) continue;
42     dp[0][msk] = 0;
43 }
44
45 DP(n-1, (1<<n)-1);
46 cout << dp[n-1][(1<<n)-1] << endl;
47
48 return 0;
49 }
50 }

```

7.9 Kth Shortest Path

```

1 // time: O(|E| \lg |E| + |V| \lg |V| + K)
2 // memory: O(|E| \lg |E| + |V|)
3 struct KSP{ // 1-base
4     struct nd{
5         int u,v; ll d;
6         nd(int ui=0,int vi=0,ll di=INF){ u=ui; v=vi; d=di; }
7     };
8     struct heap{ nd* edge; int dep; heap* chd[4]; };
9     static int cmp(heap* a,heap* b)
10     { return a->edge->d > b->edge->d; }
11     struct node{
12         int v; ll d; heap* H; nd* E;
13         node(){
14             node(ll _d,int _v,nd* _E){ d=_d; v=_v; E=_E; }
15             node(heap* _H,ll _d){ H=_H; d=_d; }
16             friend bool operator<(node a,node b)
17             { return a.d>b.d; }
18         };
19     int n,k,s,t,dst[N]; nd *nxt[N];
20     vector<nd*> g[N],rg[N]; heap *nullNd,*head[N];
21     void init(int _n,int _k,int _s,int _t){
22         n=_n; k=_k; s=_s; t=_t;
23         for(int i=1;i<=n;i++){
24             g[i].clear(); rg[i].clear();
25             nxt[i]=NULL; head[i]=NULL; dst[i]=-1;
26         }
27     }
28     void addEdge(int ui,int vi,ll di){
29         nd* e=new nd(ui,vi,di);
30         g[ui].push_back(e); rg[vi].push_back(e);
31     }
32     queue<int> dfsQ;
33     void dijkstra(){
34         while(dfsQ.size()) dfsQ.pop();
35         priority_queue<node> Q; Q.push(node(0,t,NULL));
36         while (!Q.empty()){
37             node p=Q.top(); Q.pop(); if(dst[p.v]!=-1)continue;
38             dst[p.v]=p.d; nxt[p.v]=p.E; dfsQ.push(p.v);
39             for(auto e:rg[p.v]) Q.push(node(p.d+e->d,e->u,e));
40         }
41     }
42     heap* merge(heap* curNd,heap* newNd){
43         if(curNd==nullNd) return newNd;
44         heap* root=new heap; memcpy(root,curNd,sizeof(heap));
45         if(newNd->edge->d<curNd->edge->d){
46             root->edge=newNd->edge;
47             root->chd[2]=newNd->chd[2];
48             root->chd[3]=newNd->chd[3];
49             newNd->edge=curNd->edge;
50             newNd->chd[2]=curNd->chd[2];
51             newNd->chd[3]=curNd->chd[3];
52         }
53         if(root->chd[0]->dep<root->chd[1]->dep)
54             root->chd[0]=merge(root->chd[0],newNd);
55         else root->chd[1]=merge(root->chd[1],newNd);
56         root->dep=max(root->chd[0]->dep,
57                     root->chd[1]->dep)+1;
58         return root;
59     }
60     vector<heap*> V;
61     void build(){
62         nullNd=new heap; nullNd->dep=0; nullNd->edge=new nd
63         ;
64         fill(nullNd->chd,nullNd->chd+4,nullNd);

```

```

64     while(not dfsQ.empty()){
65         int u=dfsQ.front(); dfsQ.pop();
66         if(!nxt[u]) head[u]=nullNd;
67         else head[u]=head[nxt[u]->v];
68         V.clear();
69         for(auto&& e:g[u]){
70             int v=e->v;
71             if(dst[v]==-1) continue;
72             e->d+=dst[v]-dst[u];
73             if(nxt[u]!=e){
74                 heap* p=new heap; fill(p->chd,p->chd+4,nullNd)
75                 ;
76                 p->dep=1; p->edge=e; V.push_back(p);
77             }
78             if(V.empty()) continue;
79             make_heap(V.begin(),V.end(),cmp);
80             #define L(X) ((X<<1)+1)
81             #define R(X) ((X<<1)+2)
82             for(size_t i=0;i<V.size();i++){
83                 if(L(i)<V.size()) V[i]->chd[2]=V[L(i)];
84                 else V[i]->chd[2]=nullNd;
85                 if(R(i)<V.size()) V[i]->chd[3]=V[R(i)];
86                 else V[i]->chd[3]=nullNd;
87             }
88             head[u]=merge(head[u],V.front());
89         }
90     }
91     vector<ll> ans;
92     void first_K(){
93         ans.clear(); priority_queue<node> Q;
94         if(dst[s]==-1) return;
95         ans.push_back(dst[s]);
96         if(head[s]!=nullNd)
97             Q.push(node(head[s],dst[s]+head[s]->edge->d));
98         for(int _=1;_<=k and not Q.empty();_++){
99             node p=Q.top(); q=Q.pop(); ans.push_back(p.d);
100             if(head[p.H->edge->v]!=nullNd){
101                 q.H=head[p.H->edge->v]; q.d=p.d+q.H->edge->d;
102                 Q.push(q);
103             }
104             for(int i=0;i<4;i++){
105                 if(p.H->chd[i]!=nullNd){
106                     q.H=p.H->chd[i];
107                     q.d=p.d-p.H->edge->d+p.H->chd[i]->edge->d;
108                     Q.push(q);
109                 }
110             }
111         }
112         void solve(){ // ans[i] stores the i-th shortest path
113             dijkstra(); build();
114             first_K(); // ans.size() might less than k
115         }
116     } solver;

```

7.10 System of Difference Constraints

```

1 vector<vector<pair<int, ll>>> G;
2 void add(int u, int v, ll w) {
3     G[u].emplace_back(make_pair(v, w));
4 }

```

- $x_u - x_v \leq c \Rightarrow \text{add}(v, u, c)$
- $x_u - x_v \geq c \Rightarrow \text{add}(u, v, -c)$
- $x_u - x_v = c \Rightarrow \text{add}(v, u, c), \text{add}(u, v, -c)$
- $x_u \geq c \Rightarrow$ add super vertex $x_0 = 0$, then $x_u - x_0 \geq c \Rightarrow \text{add}(u, 0, -c)$
- Don't forget non-negative constraints for every variable if specified implicitly.
- Interval sum \Rightarrow Use prefix sum to transform into differential constraints. Don't forget $S_{i+1} - S_i \geq 0$ if x_i needs to be non-negative.
- $\frac{x_u}{x_v} \leq c \Rightarrow \log x_u - \log x_v \leq \log c$

8 String

8.1 Rolling Hash

```

1 const ll C = 27;
2 inline int id(char c) {return c-'a'+1;}
3 struct RollingHash {
4     string s; int n; ll mod;
5     vector<ll> Cexp, hs;
6     RollingHash(string& _s, ll _mod):
7         s(_s), n((int)_s.size()), mod(_mod)
8     {
9         Cexp.assign(n, 0);
10        hs.assign(n, 0);
11        Cexp[0] = 1;
12        for (int i = 1; i < n; i++) {
13            Cexp[i] = Cexp[i-1] * C;
14            if (Cexp[i] >= mod) Cexp[i] %= mod;
15        }
16        hs[0] = id(s[0]);
17        for (int i = 1; i < n; i++) {
18            hs[i] = hs[i-1] * C + id(s[i]);
19            if (hs[i] >= mod) hs[i] %= mod;
20        }
21        inline ll query(int l, int r) {
22            ll res = hs[r] - (l ? hs[l-1] * Cexp[r-l+1] : 0);
23            res = (res % mod + mod) % mod;
24            return res;
25        };
26    };

```

8.2 Trie

```

1 struct node {
2     int c[26]; ll cnt;
3     node(): cnt(0) {memset(c, 0, sizeof(c));}
4     node(ll x): cnt(x) {memset(c, 0, sizeof(c));}
5 };
6 struct Trie {
7     vector<node> t;
8     void init() {
9         t.clear();
10        t.emplace_back(node());
11    }
12    void insert(string s) { int ptr = 0;
13        for (auto& i : s) {
14            if (!t[ptr].c[i-'a']) {
15                t.emplace_back(node());
16                t[ptr].c[i-'a'] = (int)t.size()-1;
17                ptr = t[ptr].c[i-'a'];
18            }
19        }
20    };
21    } trie;

```

8.3 KMP

```

1 int n, m;
2 string s, p;
3 vector<int> f;
4 void build() {
5     f.clear(); f.resize(m, 0);
6     int ptr = 0; for (int i = 1; i < m; i++) {
7         while (ptr && p[i] != p[ptr]) ptr = f[ptr-1];
8         if (p[i] == p[ptr]) ptr++;
9         f[i] = ptr;
10    }
11    void init() {
12        cin >> s >> p;
13        n = (int)s.size();
14        m = (int)p.size();
15        build();
16    }
17    void solve() {
18        int ans = 0, pi = 0;
19        for (int si = 0; si < n; si++) {
20            while (pi && s[si] != p[pi]) pi = f[pi-1];
21            if (s[si] == p[pi]) pi++;
22            if (pi == m) ans++, pi = f[pi-1];
23        }
24        cout << ans << endl;
25    }

```

8.4 Z Value

```

1 string is, it, s;
2 int n; vector<int> z;
3 void init() {
4     cin >> is >> it;
5     s = it+'0'+is;
6     n = (int)s.size();
7     z.resize(n, 0);
8 }
9 void solve() {
10    int ans = 0; z[0] = n;
11    for (int i = 1, l = 0, r = 0; i < n; i++) {
12        if (i <= r) z[i] = min(z[i-l], r-i+1);
13        while (i+z[i] < n && s[z[i]] == s[i+z[i]]) z[i]++;
14        if (i+z[i]-1 > r) l = i, r = i+z[i]-1;
15        if (z[i] == (int)it.size()) ans++;
16    }
17    cout << ans << endl;
18 }

```

8.5 Manacher

```

1 int n; string S, s;
2 vector<int> m;
3 void manacher() {
4     s.clear(); s.resize(2*n+1, '.');
5     for (int i = 0, j = 1; i < n; i++, j += 2) s[j] = S[i];
6     m.clear(); m.resize(2*n+1, 0);
7     // m[i] := max k such that s[i-k, i+k] is palindrome
8     int mx = 0, mxk = 0;
9     for (int i = 1; i < 2*n+1; i++) {
10        if (mx-(i-mx) >= 0) m[i] = min(m[mx-(i-mx)], mx+mxk-i);
11        while (0 <= i-m[i]-1 && i+m[i]+1 < 2*n+1 &&
12            s[i-m[i]-1] == s[i+m[i]+1]) m[i]++;
13        if (i+m[i] > mx+mxk) mx = i, mxk = m[i];
14    }
15    void init() { cin >> S; n = (int)S.size(); }
16    void solve() {
17        manacher();
18        int mx = 0, ptr = 0;
19        for (int i = 0; i < 2*n+1; i++) if (mx < m[i]) {
20            mx = m[i]; ptr = i;
21        }
22        for (int i = ptr-mx; i <= ptr+mx; i++)
23            if (s[i] != '.') cout << s[i];
24        cout << endl;
25    }

```

8.6 Suffix Array

```

1 #define F first
2 #define S second
3 struct SuffixArray { // don't forget s += "$";
4     int n; string s;
5     vector<int> suf, lcp, rk;
6     vector<int> cnt, pos;
7     vector<pair<pii, int>> buc[2];
8     void init(string _s) {
9         s = _s; n = (int)s.size();
10        // resize(n): suf, rk, cnt, pos, lcp, buc[0~1]
11    }
12    void radix_sort() {
13        for (int t : {0, 1}) {
14            fill(cnt.begin(), cnt.end(), 0);
15            for (auto& i : buc[t]) cnt[(t ? i.F : i.S)]++;
16            for (int i = 0; i < n; i++)
17                pos[i] = (!i ? 0 : pos[i-1] + cnt[i-1]);
18            for (auto& i : buc[t])
19                buc[t^1][pos[(t ? i.F : i.S)]] = i;
20        }
21    }
22    bool fill_suf() {
23        bool end = true;
24        for (int i = 0; i < n; i++) suf[i] = buc[0][i].S;
25        rk[suf[0]] = 0;
26        for (int i = 1; i < n; i++) {
27            int dif = (buc[0][i].F != buc[0][i-1].F);
28            end &= dif;
29        }
30    }

```

```

28     rk[suf[i]] = rk[suf[i-1]] + dif;
29     } return end;
30 }
31 void sa() {
32     for (int i = 0; i < n; i++)
33         buc[0][i] = make_pair(make_pair(s[i], s[i]), i);
34     sort(buc[0].begin(), buc[0].end());
35     if (fill_suf()) return;
36     for (int k = 0; (1<<k) < n; k++) {
37         for (int i = 0; i < n; i++)
38             buc[0][i] = make_pair(make_pair(rk[i], rk[(i + (1<<k)) % n]), i);
39         radix_sort();
40         if (fill_suf()) return;
41     }
42     void LCP() { int k = 0;
43         for (int i = 0; i < n-1; i++) {
44             if (rk[i] == 0) continue;
45             int pi = rk[i];
46             int j = suf[pi-1];
47             while (i+k < n && j+k < n && s[i+k] == s[j+k]) k++;
48             lcp[pi] = k;
49             k = max(k-1, 0);
50         }
51     };
52     SuffixArray suffixarray;

```

8.7 SA-IS

```

1  const int N=300010;
2  struct SA{
3      #define REP(i,n) for(int i=0;i<int(n);i++)
4      #define REP1(i,a,b) for(int i=(a);i<=int(b);i++)
5      bool _t[N*2]; int _s[N*2],_sa[N*2];
6      int _c[N*2],x[N],_p[N],_q[N*2],hei[N],r[N];
7      int operator [](int i){ return _sa[i]; }
8      void build(int *s,int n,int m){
9          memcpy(_s,s,sizeof(int)*n);
10         sais(_s,_sa,_p,_q,_t,_c,n,m); mkhei(n);
11     }
12     void mkhei(int n){
13         REP(i,n) r[_sa[i]]=i;
14         hei[0]=0;
15         REP(i,n) if(r[i]) {
16             int ans=i>0?max(hei[r[i-1]]-1,0):0;
17             while(_s[i+ans]==_s[_sa[r[i]-1]+ans]) ans++;
18             hei[r[i]]=ans;
19         }
20     }
21     void sais(int *s,int *sa,int *p,int *q,bool *t,int *c,int n,int z){
22         bool uniq=t[n-1]=true,neq;
23         int nn=0,nmxz=-1,*nsa=sa+n,*ns=s+n,lst=-1;
24         #define MS0(x,n) memset((x),0,n*sizeof(*x))
25         #define MAGIC(XD) MS0(sa,n);\
26         memcpy(x,c,sizeof(int)*z); XD;\
27         memcpy(x+1,c,sizeof(int)*(z-1));\
28         REP(i,n) if(sa[i]&&!t[sa[i]-1]) sa[x[s[sa[i]-1]]++] = sa[i]-1;\
29         memcpy(x,c,sizeof(int)*z);\
30         for(int i=n-1;i>=0;i--) if(sa[i]&&t[sa[i]-1]) sa[--x[s[sa[i]-1]]]=sa[i]-1;
31         MS0(c,z); REP(i,n) uniq&=++c[s[i]]<2;
32         REP(i,z-1) c[i+1]+=c[i];
33         if(uniq) { REP(i,n) sa[--c[s[i]]]=i; return; }
34         for(int i=n-2;i>=0;i--)
35             t[i]=(s[i]==s[i+1]?t[i+1]:s[i]<s[i+1]);
36         MAGIC(REP1(i,1,n-1) if(t[i]&&!t[i-1]) sa[--x[s[i]]]=p[q[i]=nn++]=i);
37         REP(i,n) if(sa[i]&&t[sa[i]]&&t[sa[i]-1]){
38             neq=lst<0||memcmp(s+sa[i],s+lst,(p[q[sa[i]]+1]-sa[i])*sizeof(int));
39             ns[q[lst=sa[i]]]=nmxz+=neq;
40         }
41         sais(ns,nsa,p+nn,q+n,t+n,c+z,nn,nmxz+1);
42         MAGIC(for(int i=nn-1;i>=0;i--) sa[--x[s[p[nsa[i]]]]]=p[nsa[i]]);
43     }
44 }sa;

```

```

45 int H[N],SA[N],RA[N];
46 void suffix_array(int* ip,int len){
47     // should padding a zero in the back
48     // ip is int array, len is array length
49     // ip[0..n-1] != 0, and ip[len]=0
50     ip[len++]=0; sa.build(ip,len,128);
51     memcpy(H,sa.hei+1,len<<2); memcpy(SA,sa._sa+1,len<<2);
52     for(int i=0;i<len;i++) RA[i]=sa.r[i]-1;
53     // resulting height, sa array \in [0,len)
54 }

```

8.8 Minimum Rotation

```

1 //rotate(begin(s), begin(s)+minRotation(s), end(s))
2 int minRotation(string s) {
3     int a = 0, n = s.size(); s += s;
4     for(int b = 0; b < n; b++) for(int k = 0; k < n; k++) {
5         if(a + k == b || s[a + k] < s[b + k]) {
6             b += max(0, k - 1);
7             break; }
8         if(s[a + k] > s[b + k]) {
9             a = b;
10            break;
11        } }
12     return a; }

```

8.9 Aho Corasick

```

1 struct ACautomata{
2     struct Node{
3         int cnt;
4         Node *go[26], *fail, *dic;
5         Node (){
6             cnt = 0; fail = 0; dic=0;
7             memset(go,0,sizeof(go));
8         }
9     }pool[1048576],*root;
10    int nMem;
11    Node* new_Node(){
12        pool[nMem] = Node();
13        return &pool[nMem++];
14    }
15    void init() { nMem = 0; root = new_Node(); }
16    void add(const string &str) { insert(root,str,0); }
17    void insert(Node *cur, const string &str, int pos){
18        for(int i=pos;i<str.size();i++){
19            if(!cur->go[str[i]-'a'])
20                cur->go[str[i]-'a'] = new_Node();
21            cur=cur->go[str[i]-'a'];
22        }
23        cur->cnt++;
24    }
25    void make_fail(){
26        queue<Node*> que;
27        que.push(root);
28        while (!que.empty()){
29            Node* fr=que.front(); que.pop();
30            for (int i=0; i<26; i++){
31                if (fr->go[i]){
32                    Node *ptr = fr->fail;
33                    while (ptr && !ptr->go[i]) ptr = ptr->fail;
34                    fr->go[i]->fail=ptr=(ptr?ptr->go[i]:root);
35                    fr->go[i]->dic=(ptr->cnt?ptr:ptr->dic);
36                    que.push(fr->go[i]);
37                } } }
38    }AC;

```

9 Geometry

9.1 Basic Operations

```

1 // Author: Gino
2 typedef long long T;
3 // typedef long double T;
4 const long double eps = 1e-8;
5
6 short sgn(T x) {

```

```

7   if (abs(x) < eps) return 0;
8   return x < 0 ? -1 : 1;
9 }
10
11 struct Pt {
12     T x, y;
13     Pt(T _x=0, T _y=0):x(_x), y(_y) {}
14     Pt operator+(Pt a) { return Pt(x+a.x, y+a.y); }
15     Pt operator-(Pt a) { return Pt(x-a.x, y-a.y); }
16     Pt operator*(T a) { return Pt(x*a, y*a); }
17     Pt operator/(T a) { return Pt(x/a, y/a); }
18     T operator*(Pt a) { return x*a.x + y*a.y; }
19     T operator^(Pt a) { return x*a.y - y*a.x; } // 不要打反
20 bool operator<(Pt a)
21     { return x < a.x || (x == a.x && y < a.y); }
22 //return sgn(x-a.x) < 0 || (sgn(x-a.x) == 0 && sgn(y-a.y) < 0); }
23 bool operator==(Pt a)
24     { return sgn(x-a.x) == 0 && sgn(y-a.y) == 0; }
25 };
26
27 Pt mv(Pt a, Pt b) { return b-a; }
28 T len2(Pt a) { return a*a; }
29 T dis2(Pt a, Pt b) { return len2(b-a); }
30
31 short ori(Pt a, Pt b) { return ((a^b)>0) - ((a^b)<0); }
32 bool onseg(Pt p, Pt l1, Pt l2) {
33     Pt a = mv(p, l1), b = mv(p, l2);
34     return ((a^b) == 0) && ((a*b) <= 0);
35 }

```

9.2 InPoly

```

1 // Author: Gino
2 // Function: Check if a point P sits in a polygon (
3 // doesn't have to be convex hull)
4 // 0 = Bound, 1 = In, -1 = Out
5 short inPoly(Pt p) {
6     for (int i = 0; i < n; i++)
7         if (onseg(p, E[i], E[(i+1)%n])) return 0;
8     int cnt = 0;
9     for (int i = 0; i < n; i++)
10         if (banana(p, Pt(p.x+1, p.y+2e9), E[i], E[(i+1)%n]))
11             cnt ^= 1;
12     return (cnt ? 1 : -1);
13 }

```

9.3 Sort by Angle

```

1 // Author: Gino
2 int ud(Pt a) { // up or down half plane
3     if (a.y > 0) return 0;
4     if (a.y < 0) return 1;
5     return (a.x >= 0 ? 0 : 1);
6 }
7 sort(ALL(E), [&](const Pt& a, const Pt& b){
8     if (ud(a) != ud(b)) return ud(a) < ud(b);
9     return (a^b) > 0;
10 });

```

9.4 Line Intersect Check

```

1 // Author: Gino
2 // Function: check if (p1---p2) (q1---q2) banana
3 inline bool banana(Pt p1, Pt p2, Pt q1, Pt q2) {
4     if (onseg(p1, q1, q2) || onseg(p2, q1, q2) ||
5         onseg(q1, p1, p2) || onseg(q2, p1, p2)) {
6         return true;
7     }
8     Pt p = mv(p1, p2), q = mv(q1, q2);
9     return (ori(p, mv(p1, q1)) * ori(p, mv(p1, q2)) < 0 &&
10         ori(q, mv(q1, p1)) * ori(q, mv(q1, p2)) < 0);
11 }

```

9.5 Line Intersection

```

1 // Author: Gino
2 // T: Long double
3 Pt bananaPoint(Pt p1, Pt p2, Pt q1, Pt q2) {
4     if (onseg(q1, p1, p2)) return q1;
5     if (onseg(q2, p1, p2)) return q2;
6     if (onseg(p1, q1, q2)) return p1;
7     if (onseg(p2, q1, q2)) return p2;
8     double s = abs(mv(p1, p2) ^ mv(p1, q1));
9     double t = abs(mv(p1, p2) ^ mv(p1, q2));
10    return q2 * (s/(s+t)) + q1 * (t/(s+t));
11 }

```

9.6 Convex Hull

```

1 // Author: Gino
2 vector<Pt> hull;
3 void convexHull() {
4     hull.clear(); sort(E.begin(), E.end());
5     for (int t : {0, 1}) {
6         int b = (int)hull.size();
7         for (auto& ei : E) {
8             while ((int)hull.size() - b >= 2 &&
9                 ori(mv(hull[(int)hull.size()-2], hull.
10                     back()),
11                     mv(hull[(int)hull.size()-2], ei)) ==
12                 -1) {
13                 hull.pop_back();
14             }
15             hull.emplace_back(ei);
16         }
17         hull.pop_back();
18         reverse(E.begin(), E.end());
19     }
20 }

```

9.7 Lower Concave Hull

```

1 // Author: Unknown
2 struct Line {
3     mutable ll m, b, p;
4     bool operator<(const Line& o) const { return m < o.m; }
5     bool operator<(ll x) const { return p < x; }
6 };
7
8 struct LineContainer : multiset<Line, less<>> {
9     // (for doubles, use inf = 1/.0, div(a,b) = a/b)
10    const ll inf = LLONG_MAX;
11    ll div(ll a, ll b) { // floored division
12        return a / b - ((a ^ b) < 0 && a % b); }
13    bool isect(iterator x, iterator y) {
14        if (y == end()) { x->p = inf; return false; }
15        if (x->m == y->m) x->p = x->b > y->b ? inf : -inf;
16        else x->p = div(y->b - x->b, x->m - y->m);
17        return x->p >= y->p;
18    }
19    void add(ll m, ll b) {
20        auto z = insert({m, b, 0}), y = z++, x = y;
21        while (isect(y, z)) z = erase(z);
22        if (x != begin() && isect(--x, y)) isect(x, y =
23            erase(y));
24        while ((y = x) != begin() && (--x)->p >= y->p)
25            isect(x, erase(y));
26    }
27    ll query(ll x) {
28        assert(!empty());
29        auto l = *lower_bound(x);
30        return l.m * x + l.b;
31    }
32 };

```

9.8 Polygon Area

```

1 // Author: Gino
2 // Function: Return doubled area of a polygon
3 T dbarea(vector<Pt>& e) {
4     ll res = 0;
5     for (int i = 0; i < (int)e.size(); i++)
6         res += e[i]^e[(i+1)%SZ(e)];
7     return abs(res);
8 }

```


9.9 Pick's Theorem

Consider a polygon which vertices are all lattice points.
Let i = number of points inside the polygon.
Let b = number of points on the boundary of the polygon.

Then we have the following formula:

$$Area = i + \frac{b}{2} - 1$$

9.10 Minimum Enclosing Circle

```
1 // Author: Gino
2 // Function: Find Min Enclosing Circle using Randomized
  O(n) Algorithm
3 Pt circumcenter(Pt A, Pt B, Pt C) {
4     // a1(x-A.x) + b1(y-A.y) = c1
5     // a2(x-A.x) + b2(y-A.y) = c2
6     // solve using Cramer's rule
7     T a1 = B.x-A.x, b1 = B.y-A.y, c1 = dis2(A, B)/2.0;
8     T a2 = C.x-A.x, b2 = C.y-A.y, c2 = dis2(A, C)/2.0;
9     T D = Pt(a1, b1) ^ Pt(a2, b2);
10    T Dx = Pt(c1, b1) ^ Pt(c2, b2);
11    T Dy = Pt(a1, c1) ^ Pt(a2, c2);
12    if (D == 0) return Pt(-INF, -INF);
13    return A + Pt(Dx/D, Dy/D);
14 }
15 Pt center; T r2;
16
17 void minEncloseCircle() {
18     mt19937 gen(chrono::steady_clock::now().
19         time_since_epoch().count());
20     shuffle(ALL(E), gen);
21     center = E[0], r2 = 0;
22
23     for (int i = 0; i < n; i++) {
24         if (dis2(center, E[i]) <= r2) continue;
25         center = E[i], r2 = 0;
26         for (int j = 0; j < i; j++) {
27             if (dis2(center, E[j]) <= r2) continue;
28             center = (E[i] + E[j]) / 2.0;
29             r2 = dis2(center, E[i]);
30             for (int k = 0; k < j; k++) {
31                 if (dis2(center, E[k]) <= r2) continue;
32                 center = circumcenter(E[i], E[j], E[k]);
33                 r2 = dis2(center, E[i]);
34             }
35         }
36     }
```

9.11 PolyUnion

```
1 // Author: Unknown
2 struct PY{
3     int n; Pt pt[5]; double area;
4     Pt& operator[](const int x){ return pt[x]; }
5     void init(){ //n,pt[0~n-1] must be filled
6         area=pt[n-1]^pt[0];
7         for(int i=0;i<n-1;i++) area+=pt[i]^pt[i+1];
8         if((area/=2)<0)reverse(pt,pt+n),area=-area;
9     }
10 };
11 PY py[500]; pair<double,int> c[5000];
12 inline double segP(Pt &p,Pt &p1,Pt &p2){
13     if(dcmp(p1.x-p2.x)==0) return (p.y-p1.y)/(p2.y-p1.y);
14     return (p.x-p1.x)/(p2.x-p1.x);
15 }
16 double polyUnion(int n){ //py[0~n-1] must be filled
17     int i,j,ii,jj,ta,tb,r,d; double z,w,s,sum=0,tc,td;
18     for(i=0;i<n;i++) py[i][py[i].n]=py[i][0];
19     for(i=0;i<n;i++){
20         for(ii=0;ii<py[i].n;ii++){
21             r=0;
22             c[r++]=make_pair(0.0,0); c[r++]=make_pair(1.0,0);
23             for(j=0;j<n;j++){
24                 if(i==j) continue;
25                 for(jj=0;jj<py[j].n;jj++){
26                     ta=dcmp(tri(py[i][ii],py[i][ii+1],py[j][jj]))
```

```
tb=dcmp(tri(py[i][ii],py[i][ii+1],py[j][jj+1]));
31         if(ta==0 && tb==0){
32             if((py[j][jj+1]-py[i][jj])*(py[i][ii+1]-py[i][ii])>0&&j<i){
33                 c[r++]=make_pair(segP(py[j][jj],py[i][ii],py[i][ii+1]),1);
34                 c[r++]=make_pair(segP(py[j][jj+1],py[i][ii],py[i][ii+1]),-1);
35             }
36         }else if(ta>0 && tb<0){
37             tc=tri(py[j][jj],py[j][jj+1],py[i][ii]);
38             td=tri(py[j][jj],py[j][jj+1],py[i][ii+1]);
39             c[r++]=make_pair(tc/(tc-td),1);
40         }else if(ta<0 && tb>0){
41             tc=tri(py[j][jj],py[j][jj+1],py[i][ii]);
42             td=tri(py[j][jj],py[j][jj+1],py[i][ii+1]);
43             c[r++]=make_pair(tc/(tc-td),-1);
44         } }
45     sort(c,c+r);
46     z=min(max(c[0].first,0.0),1.0); d=c[0].second; s=0;
47     for(j=1;j<r;j++){
48         w=min(max(c[j].first,0.0),1.0);
49         if(!d) s+=w-z;
50         d+=c[j].second; z=w;
51     }
52     sum+=(py[i][ii]^py[i][ii+1])*s;
53 }
```

9.12 Minkowski Sum

```
1 // Author: Unknown
2 /* convex hull Minkowski Sum*/
3 #define INF 10000000000000LL
4 int pos(const Pt& tp){
5     if(tp.Y == 0) return tp.X > 0 ? 0 : 1;
6     return tp.Y > 0 ? 0 : 1;
7 }
8 #define N 300030
9 Pt pt[N], qt[N], rt[N];
10 LL Lx,Rx;
11 int dn,un;
12 inline bool cmp(Pt a, Pt b){
13     int pa=pos(a),pb=pos(b);
14     if(pa==pb) return (a^b)>0;
15     return pa<pb;
16 }
17 int minkowskiSum(int n,int m){
18     int i,j,r,p,q,fi,fj;
19     for(i=1,p=0;i<n;i++){
20         if(pt[i].Y<pt[p].Y || (pt[i].Y==pt[p].Y && pt[i].X<pt[p].X) ) p=i; }
21     for(i=1,q=0;i<m;i++){
22         if(qt[i].Y<qt[q].Y || (qt[i].Y==qt[q].Y && qt[i].X<qt[q].X) ) q=i; }
23     rt[0]=pt[p]+qt[q];
24     r=1; i=p; j=q; fi=fj=0;
25     while(1){
26         if((fj&&j==q) || (!fi||i==p) && cmp(pt[(p+1)%n]-pt[p],qt[(q+1)%m]-qt[q]) ) ){
27             rt[r]=rt[r-1]+pt[(p+1)%n]-pt[p];
28             p=(p+1)%n;
29             fi=1;
30         }else{
31             rt[r]=rt[r-1]+qt[(q+1)%m]-qt[q];
32             q=(q+1)%m;
33             fj=1;
34         }
35         if(r<=1 || ((rt[r]-rt[r-1])^(rt[r-1]-rt[r-2]))!=0) r++;
36         else rt[r-1]=rt[r];
37         if(i==p && j==q) break;
38     }
39     return r-1;
40 }
41 void initInConvex(int n){
```



```

46 int i,p,q;
47 LL Ly,Ry;
48 Lx=INF; Rx=-INF;
49 for(i=0;i<n;i++){
50     if(pt[i].X<Lx) Lx=pt[i].X;
51     if(pt[i].X>Rx) Rx=pt[i].X;
52 }
53 Ly=Ry=INF;
54 for(i=0;i<n;i++){
55     if(pt[i].X==Lx && pt[i].Y<Ly){ Ly=pt[i].Y; p=i; }
56     if(pt[i].X==Rx && pt[i].Y>Ry){ Ry=pt[i].Y; q=i; }
57 }
58 for(dn=0,i=p;i!=q;i=(i+1)%n){ qt[dn++]=pt[i]; }
59 qt[dn]=pt[q]; Ly=Ry=-INF;
60 for(i=0;i<n;i++){
61     if(pt[i].X==Lx && pt[i].Y>Ly){ Ly=pt[i].Y; p=i; }
62     if(pt[i].X==Rx && pt[i].Y>Ry){ Ry=pt[i].Y; q=i; }
63 }
64 for(un=0,i=p;i!=q;i=(i+n-1)%n){ rt[un++]=pt[i]; }
65 rt[un]=pt[q];
66 }
67 inline int inConvex(Pt p){
68     int L,R,M;
69     if(p.X<Lx || p.X>Rx) return 0;
70     L=0;R=dn;
71     while(L<R-1){ M=(L+R)/2;
72         if(p.X<qt[M].X) R=M; else L=M; }
73     if(tri(qt[L],qt[R],p)<0) return 0;
74     L=0;R=un;
75     while(L<R-1){ M=(L+R)/2;
76         if(p.X<rt[M].X) R=M; else L=M; }
77     if(tri(rt[L],rt[R],p)>0) return 0;
78     return 1;
79 }
80 int main(){
81     int n,m,i;
82     Pt p;
83     scanf("%d",&n);
84     for(i=0;i<n;i++) scanf("%lld%lld",&pt[i].X,&pt[i].Y);
85     scanf("%d",&m);
86     for(i=0;i<m;i++) scanf("%lld%lld",&qt[i].X,&qt[i].Y);
87     n=minkowskiSum(n,m);
88     for(i=0;i<n;i++) pt[i]=rt[i];
89     scanf("%d",&m);
90     for(i=0;i<m;i++) scanf("%lld%lld",&qt[i].X,&qt[i].Y);
91     n=minkowskiSum(n,m);
92     for(i=0;i<n;i++) pt[i]=rt[i];
93     initInConvex(n);
94     scanf("%d",&m);
95     for(i=0;i<m;i++){
96         scanf("%lld %lld",&p.X,&p.Y);
97         p.X*=3; p.Y*=3;
98         puts(inConvex(p)? "YES": "NO");
99     }
100 }

```

10 Number Theory

10.1 Basic

```

1 // Author: Gino
2 const int maxc = 5e5;
3 ll pw(ll a, ll n) {
4     ll res = 1;
5     while (n) {
6         if (n & 1) res = res * a % MOD;
7         a = a * a % MOD;
8         n >>= 1;
9     }
10    return res;
11 }
12
13 vector<ll> fac, ifac;
14 void build_fac() {
15     reset(fac, maxc + 1, 1LL);
16     reset(ifac, maxc + 1, 1LL);
17     for (int x = 2; x <= maxc; x++) {
18         fac[x] = x * fac[x - 1] % MOD;
19         ifac[x] = pw(fac[x], MOD - 2);
20     }

```

```

21 }
22
23 ll C(ll n, ll k) {
24     if (n < k) return 0LL;
25     return fac[n] * ifac[n - k] % MOD * ifac[k] % MOD;
26 }

```

10.2 Prime Seive and Defactor

```

1 // Author: Gino
2 const int maxc = 1e6 + 1;
3 vector<int> lpf;
4 vector<int> prime;
5
6 void seive() {
7     prime.clear();
8     lpf.resize(maxc, 1);
9     for (int i = 2; i < maxc; i++) {
10         if (lpf[i] == 1) {
11             lpf[i] = i;
12             prime.emplace_back(i);
13         }
14         for (auto& j : prime) {
15             if (i * j >= maxc) break;
16             lpf[i * j] = j;
17             if (j == lpf[i]) break;
18         }
19     }
20     vector<pii> fac;
21     void defactor(int u) {
22         fac.clear();
23         while (u > 1) {
24             int d = lpf[u];
25             fac.emplace_back(make_pair(d, 0));
26             while (u % d == 0) {
27                 u /= d;
28                 fac.back().second++;
29             }
30         }
31     }

```

10.3 Harmonic Series

```

1 // Author: Gino
2 // O(n log n)
3 for (int i = 1; i <= n; i++) {
4     for (int j = i; j <= n; j += i) {
5         // O(1) code
6     }
7 }
8
9 // PIE
10 // given array a[0], a[1], ..., a[n - 1]
11 // calculate dp[x] = number of pairs (a[i], a[j]) such
12 // that
13 // gcd(a[i], a[j]) = x // (i < j)
14 // idea: Let mc(x) = # of y s.t. x|y
15 // f(x) = # of pairs s.t. gcd(a[i], a[j]) >=
16 // x
17 // f(x) = C(mc(x), 2)
18 // dp[x] = f(x) - sum(dp[y], x < y and x|y)
19 const int maxc = 1e6;
20 vector<int> cnt(maxc + 1, 0), dp(maxc + 1, 0);
21 for (int i = 0; i < n; i++)
22     cnt[a[i]]++;
23
24 for (int x = maxc; x >= 1; x--) {
25     ll cnt_mul = 0; // number of multiples of x
26     for (int y = x; y <= maxc; y += x)
27         cnt_mul += cnt[y];
28
29     dp[x] = cnt_mul * (cnt_mul - 1) / 2; // number of
30     // pairs that are divisible by x
31     for (int y = x + x; y <= maxc; y += x)
32         dp[x] -= dp[y]; // PIE: subtract all dp[y] for
33         // y > x and x|y

```

10.4 Count Number of Divisors

```

1 // Author: Gino

```

```

2 // Function: Count the number of divisors for all x <= 10^6 using harmonic series
3 const int maxc = 1e6;
4 vector<int> facs;
5
6 void find_all_divisors() {
7     facs.clear(); facs.resize(maxc + 1, 0);
8     for (int x = 1; x <= maxc; x++) {
9         for (int y = x; y <= maxc; y += x) {
10             facs[y]++;
11         }
12     }
13 }

```

10.5 數論分塊

```

1 // Author: Gino
2 /*
3 n = 17
4 i: 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17
5 n/i: 17 8 5 4 3 2 2 2 1 1 1 1 1 1 1 1 1
6
7           ^      ^
8         L(2)  R(2)
9
10 L(x) := Left bound for n/i = x
11 R(x) := right bound for n/i = x
12
13 ===== FORMULA =====
14 >>> R = n / (n/L) <<<
15 =====
16
17 Example: L(2) = 6
18           R(2) = 17 / (17 / 6)
19              = 17 / 2
20              = 8
21 */
22 // ===== CODE =====
23 for (ll l = 1, r = 1, q = n; l <= n; l = r + 1) {
24     q = n/l;
25     r = n/q;
26     // Process your code here
27 }
28 // q, l, r: 17 1 1
29 // q, l, r: 8 2 2
30 // q, l, r: 5 3 3
31 // q, l, r: 4 4 4
32 // q, l, r: 3 5 5
33 // q, l, r: 2 6 8
34 // q, l, r: 1 9 17

```

10.6 Pollard's rho

```

1 // Author: Unknown
2 // Function: Find a non-trivial factor of a big number
3 // in O(n^(1/4) log^2(n))
4
5 ll find_factor(ll number) {
6     __int128 x = 2;
7     for (__int128 cycle = 1; ; cycle++) {
8         __int128 y = x;
9         for (int i = 0; i < (1<<cycle); i++) {
10             x = (x * x + 1) % number;
11             __int128 factor = __gcd(x - y, number);
12             if (factor > 1)
13                 return factor;
14         }
15     }
16 }
17
18 # Author: Unknown
19 # Function: Find a non-trivial factor of a big number
20 # in O(n^(1/4) log^2(n))
21 from itertools import count
22 from math import gcd
23 from sys import stdin
24
25 for s in stdin:
26     number, x = int(s), 2
27     brk = False

```

```

10 for cycle in count(1):
11     y = x
12     if brk:
13         break
14     for i in range(1 << cycle):
15         x = (x * x + 1) % number
16         factor = gcd(x - y, number)
17         if factor > 1:
18             print(factor)
19             brk = True
20             break

```

10.7 Miller Rabin

```

1 // Author: Unknown
2 // Function: Check if a number is a prime in O(100 *
3 // log^2(n))
4 // miller_rabin(): return 1 if prime, 0 otherwise
5
6 // n < 4,759,123,141          3 : 2, 7, 61
7 // n < 1,122,004,669,633    4 : 2, 13, 23, 1662803
8 // n < 3,474,749,660,383    6 : pimes <= 13
9 // n < 2^64                  7 :
10 // 2, 325, 9375, 28178, 450775, 9780504, 1795265022
11 bool witness(ll a, ll n, ll u, int t) {
12     if (!(a % n)) return 0;
13     ll x = mypow(a, u, n);
14     for (int i = 0; i < t; i++) {
15         ll nx = mul(x, x, n);
16         if (nx == 1 && x != 1 && x != n - 1) return 1;
17         x = nx;
18     }
19     return x != 1;
20 }
21 bool miller_rabin(ll n, int s = 100) {
22     // iterate s times of witness on n
23     if (n < 2) return 0;
24     if (!(n & 1)) return n == 2;
25     ll u = n - 1; int t = 0;
26     while (!(u & 1)) u >>= 1, t++;
27     while (s-- > 0) {
28         ll a = randll() % (n - 1) + 1;
29         if (witness(a, n, u, t)) return 0;
30     }
31     return 1;
32 }

```

10.8 Fast Power

Note: $a^n \equiv a^{(n \bmod (p-1))} \pmod{p}$

10.9 Extend GCD

```

1 // Author: Gino
2 ll GCD;
3 pll extgcd(ll a, ll b) {
4     if (b == 0) {
5         GCD = a;
6         return pll{1, 0};
7     }
8     pll ans = extgcd(b, a % b);
9     return pll{ans.S, ans.F - a/b * ans.S};
10 }
11 pll bezout(ll a, ll b, ll c) {
12     bool negx = (a < 0), negy = (b < 0);
13     pll ans = extgcd(abs(a), abs(b));
14     if (c % GCD != 0) return pll{-LLINF, -LLINF};
15     return pll{ans.F * c/GCD * (negx ? -1 : 1),
16                ans.S * c/GCD * (negy ? -1 : 1)};
17 }
18 ll inv(ll a, ll p) {
19     if (p == 1) return -1;
20     pll ans = bezout(a % p, -p, 1);
21     if (ans == pll{-LLINF, -LLINF}) return -1;
22     return (ans.F % p + p) % p;
23 }

```

10.10 Mu + Phi

```

1 // Author: Gino
2 const int maxn = 1e6 + 5;
3 ll f[maxn];
4 vector<int> lpf, prime;
5 void build() {
6     lpf.clear(); lpf.resize(maxn, 1);
7     prime.clear();
8     f[1] = ...; /* mu[1] = 1, phi[1] = 1 */
9     for (int i = 2; i < maxn; i++) {
10         if (lpf[i] == 1) {
11             lpf[i] = i; prime.emplace_back(i);
12             f[i] = ...; /* mu[i] = 1, phi[i] = i-1 */
13         }
14         for (auto& j : prime) {
15             if (i*j >= maxn) break;
16             lpf[i*j] = j;
17             if (i % j == 0) f[i*j] = ...; /* 0, phi[i]*j */
18             /*
19             else f[i*j] = ...; /* -mu[i], phi[i]*phi[j] */
20             if (j >= lpf[i]) break;
21         }
22     }
23 }

```

10.11 Other Formulas

- Inversion:
 $aa^{-1} \equiv 1 \pmod{m}$. a^{-1} exists iff $\gcd(a, m) = 1$.
- Linear inversion:
 $a^{-1} \equiv (m - \lfloor \frac{m}{a} \rfloor) \times (m \bmod a)^{-1} \pmod{m}$
- Fermat's little theorem:
 $a^p \equiv a \pmod{p}$ if p is prime.
- Euler function:
 $\phi(n) = n \prod_{p|n} \frac{p-1}{p}$
- Euler theorem:
 $a^{\phi(n)} \equiv 1 \pmod{n}$ if $\gcd(a, n) = 1$.
- Extended Euclidean algorithm:
 $ax + by = \gcd(a, b) = \gcd(b, a \bmod b) = \gcd(b, a - \lfloor \frac{a}{b} \rfloor b) = bx_1 + (a - \lfloor \frac{a}{b} \rfloor b)y_1 = ay_1 + b(x_1 - \lfloor \frac{a}{b} \rfloor y_1)$
- Divisor function:
 $\sigma_x(n) = \sum_{d|n} d^x$. $n = \prod_{i=1}^r p_i^{a_i}$.
 $\sigma_x(n) = \prod_{i=1}^r \frac{p_i^{(a_i+1)x} - 1}{p_i^x - 1}$ if $x \neq 0$. $\sigma_0(n) = \prod_{i=1}^r (a_i + 1)$.
- Chinese remainder theorem (Coprime Moduli):
 $x \equiv a_i \pmod{m_i}$.
 $M = \prod m_i$. $M_i = M/m_i$. $t_i = M_i^{-1}$.
 $x = kM + \sum a_i t_i M_i$, $k \in \mathbb{Z}$.
- Chinese remainder theorem:
 $x \equiv a_1 \pmod{m_1}, x \equiv a_2 \pmod{m_2} \Rightarrow x = m_1 p + a_1 = m_2 q + a_2 \Rightarrow m_1 p - m_2 q = a_2 - a_1$
Solve for (p, q) using ExtGCD.
 $x \equiv m_1 p + a_1 \equiv m_2 q + a_2 \pmod{\text{lcm}(m_1, m_2)}$
- Avoiding Overflow: $ca \bmod cb = c(a \bmod b)$
- Dirichlet Convolution: $(f * g)(n) = \sum_{d|n} f(n)g(n/d)$
- Important Multiplicative Functions + Properties:
 - $\epsilon(n) = [n = 1]$
 - $1(n) = 1$
 - $id(n) = n$
 - $\mu(n) = 0$ if n has squared prime factor
 - $\mu(n) = (-1)^k$ if $n = p_1 p_2 \cdots p_k$
 - $\epsilon = \mu * 1$
 - $\phi = \mu * id$
 - $[n = 1] = \sum_{d|n} \mu(d)$
 - $[gcd = 1] = \sum_{d|gcd} \mu(d)$
- Möbius inversion: $f = g * 1 \Leftrightarrow g = f * \mu$

10.12 Polynomial

```

1 // Author: Gino
2 const int maxk = 20;
3 const int maxn = 1<<maxk;
4 const ll LINF = 1e18;
5
6 /* P = r*2^k + 1
7 P          r    k    g
8 998244353      119 23   3
9 1004535809     479 21   3
10
11 P          r    k    g
12 3            1    1   2
13 5            1    2   2
14 17           1    4   3
15 97           3    5   5
16 193          3    6   5
17 257           1    8   3
18 7681         15    9  17
19 12289         3   12  11
20 40961         5   13   3
21 65537         1   16   3
22 786433        3   18  10
23 5767169       11  19   3
24 7340033        7   20   3
25 23068673       11  21   3
26 104857601      25  22   3
27 167772161       5   25   3
28 469762049       7   26   3
29 1004535809     479 21   3
30 2013265921     15  27  31
31 2281701377     17  27   3
32 3221225473      3   30   5
33 75161927681    35  31   3
34 77309411329     9   33   7
35 206158430209    3   36  22
36 2061584302081  15  37   7
37 2748779069441   5   39   3
38 6597069766657   3   41   5
39 39582418599937   9   42   5
40 79164837199873   9   43   5
41 263882790666241  15  44   7
42 1231453023109121 35  45   3
43 1337006139375617 19  46   3
44 3799912185593857 27  47   5
45 4222124650659841 15  48  19
46 7881299347898369 7   50   6
47 31525197391593473 7   52   3
48 180143985094819841 5   55   6
49 1945555039024054273 27  56   5
50 4179340454199820289 29  57   3
51 9097271247288401921 505 54   6 */
52
53 const int g = 3;
54 const ll MOD = 998244353;
55
56 ll pw(ll a, ll n) { /* fast pow */ }
57
58 #define siz(x) (int)x.size()
59
60 template<typename T>
61 vector<T>& operator+=(vector<T>& a, const vector<T>& b)
62 {
63     if (siz(a) < siz(b)) a.resize(siz(b));
64     for (int i = 0; i < min(siz(a), siz(b)); i++) {
65         a[i] += b[i];
66         a[i] -= a[i] >= MOD ? MOD : 0;
67     }
68     return a;
69 }
70
71 template<typename T>
72 vector<T>& operator-=(vector<T>& a, const vector<T>& b)
73 {
74     if (siz(a) < siz(b)) a.resize(siz(b));
75     for (int i = 0; i < min(siz(a), siz(b)); i++) {
76         a[i] -= b[i];
77         a[i] += a[i] < 0 ? MOD : 0;
78     }
79     return a;
80 }

```

```

79
80 template<typename T>
81 vector<T> operator-(const vector<T>& a) {
82     vector<T> ret(siz(a));
83     for (int i = 0; i < siz(a); i++) {
84         ret[i] = -a[i] < 0 ? -a[i] + MOD : -a[i];
85     }
86     return ret;
87 }
88
89 vector<ll> X, iX;
90 vector<int> rev;
91
92 void init_ntt() {
93     X.clear(); X.resize(maxn, 1); // x1 = g^((p-1)/n)
94     iX.clear(); iX.resize(maxn, 1);
95
96     ll u = pw(g, (MOD-1)/maxn);
97     ll iu = pw(u, MOD-2);
98
99     for (int i = 1; i < maxn; i++) {
100         X[i] = X[i-1] * u;
101         iX[i] = iX[i-1] * iu;
102         if (X[i] >= MOD) X[i] %= MOD;
103         if (iX[i] >= MOD) iX[i] %= MOD;
104     }
105
106     rev.clear(); rev.resize(maxn, 0);
107     for (int i = 1, hb = -1; i < maxn; i++) {
108         if (!(i & (i-1))) hb++;
109         rev[i] = rev[i ^ (1<<hb)] | (1<<(maxk-hb-1));
110     }
111 }
112
113 template<typename T>
114 void NTT(vector<T>& a, bool inv=false) {
115     int _n = (int)a.size();
116     int k = __lg(_n) + ((1<<__lg(_n)) != _n);
117     int n = 1<<k;
118     a.resize(n, 0);
119
120     short shift = maxk-k;
121     for (int i = 0; i < n; i++)
122         if (i > (rev[i]>>shift))
123             swap(a[i], a[rev[i]>>shift]);
124
125     for (int len = 2, half = 1, div = maxn>>1; len <= n; len<<=1, half<<=1, div>>=1) {
126         for (int i = 0; i < n; i += len) {
127             for (int j = 0; j < half; j++) {
128                 T u = a[i+j];
129                 T v = a[i+j+half] * (inv ? iX[j*div] :
130                     X[j*div]) % MOD;
131                 a[i+j] = (u+v >= MOD ? u+v-MOD : u+v);
132                 a[i+j+half] = (u-v < 0 ? u-v+MOD : u-v);
133             }
134         }
135     }
136
137     if (inv) {
138         T dn = pw(n, MOD-2);
139         for (auto& x : a) {
140             x *= dn;
141             if (x >= MOD) x %= MOD;
142         }
143     }
144 }
145
146 template<typename T>
147 inline void resize(vector<T>& a) {
148     int cnt = (int)a.size();
149     for (; cnt > 0; cnt--) if (a[cnt-1]) break;
150     a.resize(max(cnt, 1));
151 }
152
153 template<typename T>
154 vector<T>& operator*=(vector<T>& a, vector<T> b) {
155     int na = (int)a.size();
156     int nb = (int)b.size();
157     a.resize(na + nb - 1, 0);
158     b.resize(na + nb - 1, 0);
159
160     NTT(a); NTT(b);
161     for (int i = 0; i < (int)a.size(); i++) {
162         a[i] *= b[i];
163     }
164
165     if (a[i] >= MOD) a[i] %= MOD;
166 }
167
168 template<typename T>
169 void inv(vector<T>& ia, int N) {
170     vector<T> _a(move(ia));
171     ia.resize(1, pw(_a[0], MOD-2));
172     vector<T> a(1, -_a[0] + (-_a[0] < 0 ? MOD : 0));
173
174     for (int n = 1; n < N; n<<=1) {
175         // n -> 2*n
176         // ia' = ia(2-a*ia);
177
178         for (int i = n; i < min(siz(_a), (n<<1)); i++)
179             a.emplace_back(-_a[i] + (-_a[i] < 0 ? MOD : 0));
180
181         vector<T> tmp = ia;
182         ia *= a;
183         ia.resize(n<<1);
184         ia[0] = ia[0] + 2 >= MOD ? ia[0] + 2 - MOD : ia[0] + 2;
185         ia *= tmp;
186         ia.resize(n<<1);
187     }
188     ia.resize(N);
189 }
190
191 template<typename T>
192 void mod(vector<T>& a, vector<T>& b) {
193     int n = (int)a.size()-1, m = (int)b.size()-1;
194     if (n < m) return;
195
196     vector<T> ra = a, rb = b;
197     reverse(ra.begin(), ra.end()); ra.resize(min(n+1, n-m+1));
198     reverse(rb.begin(), rb.end()); rb.resize(min(m+1, n-m+1));
199
200     inv(rb, n-m+1);
201
202     vector<T> q = move(ra);
203     q *= rb;
204     q.resize(n-m+1);
205     reverse(q.begin(), q.end());
206
207     q *= b;
208     a -= q;
209     resize(a);
210 }
211
212 /* Kitamasa Method (Fast Linear Recurrence):
213 Find a[K] (Given a[j] = c[0]a[j-N] + ... + c[N-1]a[j-1])
214 Let B(x) = x^N - c[N-1]x^(N-1) - ... - c[1]x^1 - c[0]
215 Let R(x) = x^K mod B(x) (get x^K using fast pow and use poly mod to get R(x))
216 Let r[i] = the coefficient of x^i in R(x)
217 => a[K] = a[0]r[0] + a[1]r[1] + ... + a[N-1]r[N-1] */

```

11 Linear Algebra

11.1 Gaussian-Jordan Elimination

```

1 int n; vector<vector<ll>> v;
2 void gauss(vector<vector<ll>>& v) {
3     int r = 0;
4     for (int i = 0; i < n; i++) {
5         bool ok = false;
6         for (int j = r; j < n; j++) {
7             if (v[j][i] == 0) continue;
8             swap(v[j], v[r]);
9             ok = true; break;
10        }
11        if (!ok) continue;

```

```

12 ll div = inv(v[r][i]);
13 for (int j = 0; j < n+1; j++) {
14     v[r][j] *= div;
15     if (v[r][j] >= MOD) v[r][j] %= MOD;
16 }
17 for (int j = 0; j < n; j++) {
18     if (j == r) continue;
19     ll t = v[j][i];
20     for (int k = 0; k < n+1; k++) {
21         v[j][k] -= v[r][k] * t % MOD;
22         if (v[j][k] < 0) v[j][k] += MOD;
23     }
24     r++;
25 } }

```

11.2 Determinant

1. Use GJ Elimination, if there's any row consists of only 0, then $\det = 0$, otherwise $\det = \text{product of diagonal elements}$.
2. Properties of \det :
 - Transpose: Unchanged
 - Row Operation 1 - Swap 2 rows: $-\det$
 - Row Operation 2 - $k\vec{r}_i$: $k \times \det$
 - Row Operation 3 - $k\vec{r}_i$ add to \vec{r}_j : Unchanged

12 Flow / Matching

12.1 Dinic

```

1 // Author: Benson
2 // Function: Max Flow,  $O(V^2 E)$ 
3 struct Dinic {
4     struct Edge {
5         int t, c, r;
6         Edge() {}
7         Edge(int _t, int _c, int _r):
8             t(_t), c(_c), r(_r) {}
9     };
10    vector<vector<Edge>> G;
11    vector<int> dis, iter;
12    int s, t;
13    void init(int n) {
14        G.resize(n), dis.resize(n), iter.resize(n);
15        for(int i = 0; i < n; ++i)
16            G[i].clear();
17    }
18    void add(int a, int b, int c) {
19        G[a].eb(b, c, G[b].size());
20        G[b].eb(a, 0, G[a].size() - 1);
21    }
22    bool bfs() {
23        fill(ALL(dis), -1);
24        dis[s] = 0;
25        queue<int> que;
26        que.push(s);
27        while(!que.empty()) {
28            int u = que.front(); que.pop();
29            for(auto& e : G[u]) {
30                if(e.c > 0 && dis[e.t] == -1) {
31                    dis[e.t] = dis[u] + 1;
32                    que.push(e.t);
33                }
34            }
35        }
36        return dis[t] != -1;
37    }
38    int dfs(int u, int cur) {
39        if(u == t) return cur;
40        for(int &i = iter[u]; i < (int)G[u].size(); ++i) {
41            auto& e = G[u][i];
42            if(e.c > 0 && dis[u] + 1 == dis[e.t]) {
43                int ans = dfs(e.t, min(cur, e.c));
44                if(ans > 0) {

```

```

45         G[e.t][e.r].c += ans;
46         e.c -= ans;
47         return ans;
48     }
49 }
50 }
51 return 0;
52 }
53
54 int flow(int a, int b) {
55     s = a, t = b;
56     int ans = 0;
57     while(bfs()) {
58         fill(ALL(iter), 0);
59         int tmp;
60         while((tmp = dfs(s, INF)) > 0)
61             ans += tmp;
62     }
63     return ans;
64 }
65 };

```

12.2 ISAP

```

1 // Author: Unknown
2 // Faster Version of Dinic
3 #define SZ(c) ((int)(c).size())
4 struct Maxflow{
5     static const int MAXV=50010;
6     static const int INF =1000000;
7     struct Edge{
8         int v,c,r;
9         Edge(int _v,int _c,int _r):v(_v),c(_c),r(_r){}
10    };
11    int s,t; vector<Edge> G[MAXV];
12    int iter[MAXV],d[MAXV],gap[MAXV],tot;
13    void init(int n,int _s,int _t){
14        tot=n,s=_s,t=_t;
15        for(int i=0;i<tot;i++){
16            G[i].clear(); iter[i]=d[i]=gap[i]=0;
17        }
18    }
19    void addEdge(int u,int v,int c){
20        G[u].push_back(Edge(v,c,SZ(G[v])));
21        G[v].push_back(Edge(u,0,SZ(G[u])-1));
22    }
23    int DFS(int p,int flow){
24        if(p==t) return flow;
25        for(int &i=iter[p];i<SZ(G[p]);i++){
26            Edge &e=G[p][i];
27            if(e.c>0&&d[p]==d[e.v]+1){
28                int f=DFS(e.v,min(flow,e.c));
29                if(f){ e.c-=f; G[e.v][e.r].c+=f; return f; }
30            }
31        }
32        if(--gap[d[p]]==0) d[s]=tot;
33        else{ d[p]++; iter[p]=0; ++gap[d[p]]; }
34        return 0;
35    }
36    int flow(){
37        int res=0;
38        for(res=0,gap[0]=tot;d[s]<tot;res+=DFS(s,INF));
39        return res;
40    } // reset: set iter,d,gap to 0
41} flow;

```

12.3 MCMF

```

1 // Author: Unknown
2 // Function: First Maximize flow, then minimize flow cost
3 struct MCMF {
4     struct Edge {
5         int to, cap, rev;
6         ll cost;
7         Edge() {}
8         Edge(int _to, int _cap, int _rev, ll _cost) :
9             to(_to), cap(_cap), rev(_rev), cost(_cost) {}
10    };

```

```

11 static const int N = 2000;
12 vector<Edge> G[N];
13 int n, s, t;
14 void init(int _n, int _s, int _t) {
15     n = _n, s = _s, t = _t;
16     for(int i = 0; i <= n; ++i)
17         G[i].clear();
18 }
19 void add_edge(int from, int to, int cap, ll cost) {
20     G[from].eb(to, cap, (int)G[to].size(), cost);
21     G[to].eb(from, 0, (int)G[from].size() - 1, -cost);
22 }
23
24 bool vis[N];
25 int iter[N];
26 ll dis[N];
27 bool SPFA() {
28     for(int i = 0; i <= n; ++i)
29         vis[i] = 0, dis[i] = LINF;
30
31     dis[s] = 0; vis[s] = 1;
32     queue<int> que; que.push(s);
33     while(!que.empty()) {
34         int u = que.front(); que.pop();
35         vis[u] = 0;
36         for(auto& e : G[u]) if(e.cap > 0 && dis[e.to] > dis[u] + e.cost) {
37             dis[e.to] = dis[u] + e.cost;
38             if(!vis[e.to]) {
39                 que.push(e.to);
40                 vis[e.to] = 1;
41             }
42         }
43     }
44     return dis[t] != LINF;
45 }
46
47 int dfs(int u, int cur) {
48     if(u == t) return cur;
49     int ret = 0; vis[u] = 1;
50     for(int &i = iter[u]; i < (int)G[u].size(); ++i) {
51         auto &e = G[u][i];
52         if(e.cap > 0 && dis[e.to] == dis[u] + e.cost && !vis[e.to]) {
53             int tmp = dfs(e.to, min(cur, e.cap));
54             e.cap -= tmp;
55             G[e.to][e.rev].cap += tmp;
56             cur -= tmp;
57             ret += tmp;
58             if(cur == 0) {
59                 vis[u] = 0;
60                 return ret;
61             }
62         }
63     }
64     vis[u] = 0;
65     return ret;
66 }
67
68 pair<int, ll> flow() {
69     int flow = 0; ll cost = 0;
70     while(SPFA()) {
71         memset(iter, 0, sizeof(iter));
72         int tmp = dfs(s, INF);
73         flow += tmp, cost += tmp * dis[t];
74     }
75     return {flow, cost};
76 }

```

12.4 Hopcroft-Karp

```

1 // Author: Gino
2 // Function: Max Bipartite Matching in O(V sqrt(E))
3 // init() -> get() -> Ans = hk.MXCNT
4 struct HopcroftKarp {
5     // id: X = [1, nx], Y = [nx+1, nx+ny]
6     int n, nx, ny, m, MXCNT;
7     vector<vector<int>> > g;
8     vector<int> mx, my, dis, vis;

```

```

9 void init(int nnx, int nny, int mm) {
10     nx = nnx, ny = nny, m = mm;
11     n = nx + ny + 1;
12     g.clear(); g.resize(n);
13 }
14 void add(int x, int y) {
15     g[x].emplace_back(y);
16     g[y].emplace_back(x);
17 }
18 bool dfs(int x) {
19     vis[x] = true;
20     for (auto& y : g[x]) {
21         int px = my[y];
22         if (px == -1 ||
23             (dis[px] == dis[x]+1 &&
24              !vis[px] && dfs(px))) {
25             mx[x] = y;
26             my[y] = x;
27             return true;
28         }
29     }
30     return false;
31 }
32 void get() {
33     mx.clear(); mx.resize(n, -1);
34     my.clear(); my.resize(n, -1);
35
36     while (true) {
37         queue<int> q;
38         dis.clear(); dis.resize(n, -1);
39         for (int x = 1; x <= nx; x++){
40             if (mx[x] == -1) {
41                 dis[x] = 0;
42                 q.push(x);
43             }
44         }
45         while (!q.empty()) {
46             int x = q.front(); q.pop();
47             for (auto& y : g[x]) {
48                 if (my[y] != -1 && dis[my[y]] == -1) {
49                     dis[my[y]] = dis[x] + 1;
50                     q.push(my[y]);
51                 }
52             }
53         }
54         bool brk = true;
55         vis.clear(); vis.resize(n, 0);
56         for (int x = 1; x <= nx; x++)
57             if (mx[x] == -1 && dfs(x))
58                 brk = false;
59
60         if (brk) break;
61     }
62     MXCNT = 0;
63     for (int x = 1; x <= nx; x++) if (mx[x] != -1)
64         MXCNT++;
65 }
66 } hk;

```

12.5 Cover / Independent Set

```

1 V(E) Cover: choose some V(E) to cover all E(V)
2 V(E) Independ: set of V(E) not adj to each other
3
4 M = Max Matching
5 Cv = Min V Cover
6 Ce = Min E Cover
7 Iv = Max V Ind
8 Ie = Max E Ind (equiv to M)
9
10 M = Cv (Konig Theorem)
11 Iv = V \ Cv
12 Ce = V - M
13
14 Construct Cv:
15 1. Run Dinic
16 2. Find s-t min cut
17 3. Cv = {X in T} + {Y in S}

```


12.6 KM

```

1 // Author: Unknown
2 // Function: Weighted Max Bipartite Matching in O(V^3)
3 #include <bits/stdc++.h>
4
5 using namespace std;
6 const int inf = 1e9;
7
8 struct KuhnMunkres {
9     int n;
10    vector<vector<int>> g;
11    vector<int> lx, ly, slack;
12    vector<int> match, visx, visy;
13    KuhnMunkres(int n) : n(n), g(n, vector<int>(n)),
14        lx(n), ly(n), slack(n), match(n), visx(n), visy(n) {}
15    vector<int> & operator[](int i) { return g[i]; }
16    bool dfs(int i, bool aug) { // aug = true 表示要更新 match
17        新 match
18        if(visx[i]) return false;
19        visx[i] = true;
20        for(int j = 0; j < n; j++) {
21            if(visy[j]) continue;
22            // 一邊擴增交錯樹、尋找增廣路徑
23            // 一邊更新 slack: 樹上的點跟樹外的點所造成的最小權重
24            int d = lx[i] + ly[j] - g[i][j];
25            if(d == 0) {
26                visy[j] = true;
27                if(match[j] == -1 || dfs(match[j], aug)) {
28                    if(aug) match[j] = i;
29                    return true;
30                }
31            } else {
32                slack[j] = min(slack[j], d);
33            }
34        }
35        return false;
36    }
37    bool augment() { // 回傳是否有增廣路
38        for(int j = 0; j < n; j++) if(!visy[j] && slack[j] == 0) {
39            visy[j] = true;
40            if(match[j] == -1 || dfs(match[j], false)) {
41                return true;
42            }
43        }
44        return false;
45    }
46    void relabel() {
47        int delta = inf;
48        for(int j = 0; j < n; j++) if(!visy[j]) delta = min(delta, slack[j]);
49        for(int i = 0; i < n; i++) if(visx[i]) lx[i] -= delta;
50        for(int j = 0; j < n; j++) {
51            if(visy[j]) ly[j] += delta;
52            else slack[j] -= delta;
53        }
54    }
55    int solve() {
56        for(int i = 0; i < n; i++) {
57            lx[i] = 0;
58            for(int j = 0; j < n; j++) lx[i] = max(lx[i], g[i][j]);
59        }
60        fill(ly.begin(), ly.end(), 0);
61        fill(match.begin(), match.end(), -1);
62        for(int i = 0; i < n; i++) {
63            // slack 在每一輪都要初始化
64            fill(slack.begin(), slack.end(), inf);
65            fill(visx.begin(), visx.end(), false);
66            fill(visy.begin(), visy.end(), false);
67            if(dfs(i, true)) continue;
68            // 重複調整頂標直到找到增廣路徑
69            while(!augment()) relabel();
70            fill(visx.begin(), visx.end(), false);

```

```

71        fill(visy.begin(), visy.end(), false);
72        dfs(i, true);
73    }
74    int ans = 0;
75    for(int j = 0; j < n; j++) if(match[j] != -1) ans += g[match[j]][j];
76    return ans;
77 }
78 };
79 signed main() {
80     ios_base::sync_with_stdio(0), cin.tie(0);
81     int n;
82     while(cin >> n && n) {
83         KuhnMunkres KM(n);
84         for(int i = 0; i < n; i++) {
85             for(int j = 0; j < n; j++) {
86                 int c;
87                 cin >> c;
88                 if(c > 0) KM[i][j] = c;
89             }
90         }
91         cout << KM.solve() << '\n';
92     }
93 }
94 }

```

13 Combinatorics

13.1 Catalan Number

$$C_0 = 1, C_n = \sum_{i=0}^{n-1} C_i C_{n-1-i}, C_n = C_n^{2n} - C_{n-1}^{2n}$$

0	1	1	2	5
4	14	42	132	429
8	1430	4862	16796	58786
12	208012	742900	2674440	9694845

13.2 Burnside's Lemma

Let X be the original set.

Let G be the group of operations acting on X .

Let X^g be the set of x not affected by g .

Let X/G be the set of orbits.

Then the following equation holds:

$$|X/G| = \frac{1}{|G|} \sum_{g \in G} |X^g|$$

14 Special Numbers

14.1 Fibonacci Series

1	1	1	2	3
5	5	8	13	21
9	34	55	89	144
13	233	377	610	987
17	1597	2584	4181	6765
21	10946	17711	28657	46368
25	75025	121393	196418	317811
29	514229	832040	1346269	2178309
33	3524578	5702887	9227465	14930352

$$f(45) \approx 10^9, f(88) \approx 10^{18}$$

14.2 Prime Numbers

- First 50 prime numbers:

1	2	3	5	7	11
6	13	17	19	23	29
11	31	37	41	43	47
16	53	59	61	67	71
21	73	79	83	89	97
26	101	103	107	109	113
31	127	131	137	139	149
36	151	157	163	167	173
41	179	181	191	193	197
46	199	211	223	227	229

- Very large prime numbers:

1000001333 1000500889 2500001909
 2000000659 900004151 850001359

- $\pi(n) \equiv$ Number of primes $\leq n \approx n/((\ln n) - 1)$

$$\pi(100) = 25, \pi(200) = 46$$

$$\pi(500) = 95, \pi(1000) = 168$$

$$\pi(2000) = 303, \pi(4000) = 550$$

$$\pi(10^4) = 1229, \pi(10^5) = 9592$$

$$\pi(10^6) = 78498, \pi(10^7) = 664579$$