

1 Reminder 1	10.8 AC Automaton..... 12	2 set nu rnu cul mouse=a cin et ts=2 sw=2 sts=2 autochdir
1.1 Observations and Tricks..... 1	10.9 AC Automaton - Dict Links..... 13	3b=unnamedplus
1.2 Bug List..... 1	10.10 AC Automaton - Counting	3 no ; :
2 Init (Linux) 1	Patterns..... 13	4 ino {<CR> {<CR>}<Esc>ko
2.1 vimrc..... 1	10.11 AC Automaton - Pattern	5 ca Hash w !cppg -dD -P \ tr -d '[:space:]' \ openssl sha256
2.2 bashrc..... 1	Position..... 13	-r \ cut -c-6
3 Basic 1	11 Geometry 13	1" Gino's .vimrc "
3.1 Template (Using Codebook)..... 1	11.1 Template..... 13	2"no <C-h> ^ <C-l> \$ h b l e b l e h
3.2 PBDS, Random..... 1	11.2 Basic..... 13	2.2 bashrc
3.3 Debug..... 1	11.3 Line / Segment Intersections..... 13	c08ff4
3.4 SVG Writer..... 1	11.4 Point-Line / Segment Distance..... 13	1 gogo () {
3.5 Python..... 2	11.5 Sort..... 13	2 g++ -std=c++20 -O2 "\$1" && echo run && ./a.out
3.6 Stress Tests..... 2	11.6 Convex Hull..... 14	3}
4 Data Structure 2	11.7 Triangle Centers..... 14	4 alias vig='vim -u ~/.vimrc-gino'
4.1 Mo's Algorithm..... 2	11.8 Point Inside..... 14	3 Basic
4.2 CDQ..... 2	11.9 Point In Triangle..... 14	3.1 Template (Using Codebook)
4.3 Persistent Treap..... 3	11.10 Vector In Polygon..... 14	9f9204
4.4 Li Chao Tree..... 3	11.11 Polygon Cut..... 14	1 // CRYPTOGRAPHER
4.5 Time Segment Tree..... 3	11.12 Half-Plane Intersection..... 14	2 #define SZ(c) ((int)(c).size())
4.6 Segment Tree Beats..... 3	11.13 Cyclic Ternary Search..... 14	3 // kactl
5 DP 4	11.14 Circle Intersections..... 14	4 #define sz(x) (int)(x).size()
5.1 SOS DP..... 4	11.15 Tangents..... 15	5 #define rep(i,a,b) for(int i=(a);i<(b);i++)
5.2 Divide and Conquer DP..... 4	11.16 Bisector..... 15	6 using ll = long long;
5.3 Dynamic DP..... 4	11.17 Minimum Enclosing Circle..... 15	7 using vi = vector<int>;
5.4 Convex Hull Trick..... 4	11.18 Minkowski Sum..... 15	8 using pii = pair<int, int>;
6 Graph 4	11.19 Convex Hull Distance..... 15	9 // ckiseki
6.1 Max Clique..... 4	11.20 Closest Point Pair..... 15	10 #define all(x) begin(x), end(x)
6.2 Bellman-Ford..... 5	11.21 Polygon-Circle Intersection..... 15	11 #define pb emplace_back
6.3 System of Difference Constraints..... 5	11.22 Union of Polygons..... 16	12 #define REP(i, l, r) for (int i=(l); i<=(r); ++i)
6.4 Graph Girth..... 5	11.23 Rotating Sweep Line..... 16	13 const ll LINF = 1e18;
6.5 Euler Trail..... 5	11.24 Pick's Theorem..... 16	14 template <class A, class B> bool chmin(A& a, B& b) {
6.6 Vertex BCC (Round Square Tree)..... 5	12 Number Theory 16	15 return b < a ? a = b, 1 : 0;
6.7 Edge BCC..... 6	12.1 Mod Sum..... 16	16}
6.8 Kth Shortest Path..... 6	12.2 Extended Lucas Theorem..... 16	3.2 PBDS, Random
6.9 SCC - Tarjan..... 7	12.3 Prime Sieve and Defactor..... 17	d9e963
6.10 2SAT..... 7	12.4 Harmonic Series..... 17	1 #include <bits/extc++.h>
7 Tree 7	12.5 Count Number of Divisors..... 17	2 using namespace __gnu_pbds;
7.1 Tree Isomorphism (Rooted Trees)..... 7	12.6 數論分塊..... 17	3 // map
7.2 Tree Isomorphism (Unrooted Trees)..... 7	12.7 Pollard's rho..... 17	4 tree <int, int, less<>, rb_tree_tag,
7.3 Heavy Light Decomposition..... 7	12.8 Miller Rabin..... 18	tree_order_statistics_node_update> tr;
7.4 Virtual Tree..... 7	12.9 Discrete Log..... 18	5 tr.order_of_key (element);
8 Matching 8	12.10 Discrete Sqrt..... 18	6 tr.find_by_order (rank);
8.1 Bipartite Matching..... 8	12.11 Fast Power..... 18	7 // set
8.2 Bipartite Weighted Matching..... 8	12.12 Extend GCD..... 18	8 tree <int, null_type, less<>, rb_tree_tag,
8.3 General Matching..... 8	12.13 Mu + Phi..... 19	tree_order_statistics_node_update> tr;
9 Flow 8	12.14 Other Formulas..... 19	9 tr.order_of_key (element);
9.1 Flow Methods..... 8	12.15 Polynomial..... 19	10 tr.find_by_order (rank);
9.2 Dinic (Flow Decomposition)..... 9	12.16 Counting Primes..... 20	11 // priority queue
9.3 ISAP..... 10	12.17 Linear Sieve for Other Number Theoretic Functions..... 20	12 __gnu_pbds::priority_queue<int, less<int>> big_q;
9.4 Bounded Max Flow..... 10	13 Numerical 21	13 __gnu_pbds::priority_queue<int, greater<int>> small_q;
9.5 MCMF..... 10	13.1 Polynomials and recurrences..... 21	14 ql.join (q2); // join
9.6 Push-Relabel..... 11	13.2 Optimization..... 22	15
9.7 Gomory-Hu Tree..... 11	13.3 Matrices..... 23	16 mt19937
9.8 Global Min Cut..... 11	13.4 Fourier transforms..... 24	gen (chrono::steady_clock::now().time_since_epoch().count());
10 String 11	14 Combinatorics 25	17 uniform_int_distribution <int>(a, b)(rng) // [a, b]
10.1 Rolling Hash..... 11	14.1 Catalan Number..... 25	18 uniform_real_distribution <double>(a, b)(rng) // (a, b)
10.2 KMP..... 11	14.2 Bertrand's Ballot Theorem..... 25	19 shuffle (v.begin(), v.end(), gen);
10.3 Z Value..... 11	14.3 Burnside's Lemma..... 25	3.3 Debug
10.4 Manacher..... 11	15 Special Numbers 25	a265e1
10.5 Suffix Array + LCP..... 12	15.1 Fibonacci Series..... 25	1 #define debug(...) cerr << "\x1b[33m" #__VA_ARGS__ " :
10.6 Suffix Automaton..... 12	15.2 Prime Numbers..... 25	2 \x1b[0m", \
10.7 Minimum Rotation..... 12	15.3 Number of Divisors..... 25	3 [](auto &&... a){ ((cerr << a << ' '), ...); }
	15.4 Distinct Prime Factors..... 25	4 (__VA_ARGS__), cerr << '\n'

1 Reminder

1.1 Observations and Tricks

- Contribution Technique
- 二分圖/Spanning Tree/DFS Tree
- 行、列操作互相獨立
- 奇偶性
- 當 s, t 遞增並且 $t = f(s)$ ，對 s 二分搜不好做，可以改成對 t 二分搜，再算 $f(t)$
- 啟發式合併
- Permutation Normalization (做一些平移對齊兩個 permutation)
- 枚舉 $a_1 \sim a_n$ 再枚舉 $a_n \sim a_1$ 可以包在一個迴圈
- 兩個凸型函數相加還是凸型函數，相減不一定
- 一個區間的 $\text{mex} = k$ ，表示這個區間包含 $0 \sim k-1$ 所有數字，並且「 U -區間」的最小值 $= k$ 。

1.2 Bug List

- 沒開 long long
- 陣列戳出界／陣列開不夠大
- 寫好的函式 (例如 `init()`、`build()`) 忘記呼叫
- 0-base / 1-base
- 線段樹改值懶標初始值不能設為 0
- DFS 的時候不小心覆寫到全域變數
- 多筆測資不能沒讀完直接 return
- vector 超級肥，小 vector 請用 array，例如矩陣快速冪

2 Init (Linux)

2.1 vimrc

```
1 syn on
```

```

12     "viewBox='$ $ $ $>\n"
13     "<style>{*{stroke-width:0.5%;}</style>\n",
14     x1, -y2, x2 - x1, y2 - y1); }
15 ~SVG() { p("</svg>\n"); }
16 void color(string nc) { c = nc; }
17 void line(auto x1, auto y1, auto x2, auto y2) {
18     p("<line x1='$' y1='$' x2='$' y2='$' stroke='$' />\n",
19     x1, -y1, x2, -y2, c); }
20 void circle(auto x, auto y, auto r) {
21     p("<circle cx='$' cy='$' r='$' stroke='$' "
22     "fill='none' />\n", x, -y, r, c); }
23 void text(auto x, auto y, string s, int w = 12) {
24     p("<text x='$' y='$' font-size='$px'></text>\n",
25     x, -y, w, s); }
26 };

```

```

1 SVG svg("out.svg", -200, -200, 200, 200);
2 svg.color("lightgray"); // ↓ drawing x-y plane
3 svg.line(-200, 0, 200, 0); svg.line(0, -200, 0, 200);
4 svg.color("blue"); svg.line(10, 10, 80, 80);
5 svg.color("red"); svg.circle(50, 50, 1);

```

3.5 Python

b16508

```

1 import sys
2 input = sys.stdin.readline
3 readStr = lambda: input().rstrip('\r\n')
4 readInt = lambda: int(input())
5 readInts = lambda: list(map(int, input().split()))
6 from decimal import *
7 getcontext().prec = 50 # precision
8 x = Decimal(str(x))
9 y = Decimal("6.7")
10 x *= y
11 print(x.quantize(Decimal("0.000001"),
12     rounding=ROUND_HALF_EVEN))
13 # ROUND_CEILING : To INF (2.9 -> 3, -2.1 -> -2)
14 # ROUND_FLOOR : To -INF (2.1 -> 2, -2.9 -> -3)
15 # ROUND_HALF_EVEN : To nearest even (2.5 -> 2, 3.5 -> 4)
16 # ROUND_HALF_UP : Half away from 0 (2.5 -> 3, -2.5 -> -3)
17 # ROUND_HALF_DOWN : Half towards 0 (2.5 -> 2, -2.5 -> -2)
18 # ROUND_UP : Away from 0 (2.1 -> 3, -2.1 -> -3)
19 # ROUND_DOWN : Truncate to 0 (2.9 -> 2, -2.9 -> -2)
20 # <Default>: ROUND_HALF_EVEN
21 # <Standard School Math>: ROUND_HALF_UP

```

3.6 Stress Tests

```

1 from random import *
2 n = randint(1, 10)
3 arr = list(randint(1, 20) for i in range(n))
4 print(*arr)
5 # permutation / non-repetitive sequence
6 perm = sample(range(1, n + 1), n)
7 arr = sample(range(1, 10000 + 1), n)
8 # string
9 from string import *
10 s = "".join(choices(ascii_lowercase, k=n))
11 t = "".join(choices(ascii_lowercase[:3], k=n)) # {a|b|c}*
12 u = "".join(choices(ascii_lowercase + ascii_uppercase +
13     digits, k=n))
14 # palindrome
15 half = "".join(choices(ascii_lowercase, k=(n + 1) // 2))
16 palindrome = half + (half[-2::-1] if n % 2 else half[::-1])
17 # ===== tree =====
18 n = 30
19 ## shallow tree
20 edges = [(randint(1, u - 1), u) for u in range(2, n + 1)]
21 ## deep tree
22 ## (suggested k: 2 ~ 5 or int(sqrt(n)) or 2n/D (D is
23     expected depth))
24 from math import *
25 k = int(sqrt(n))
26 edges = [(randint(max(1, u-k), u-1), u) for u in range(2, n
27     + 1)]
28 for e in edges:
29     print(*e)
30 edges = [(1, i) for i in range(2, n + 1)] ## star
31 edges = [(i, i + 1) for i in range(1, n)] ## chain
32 edges = [(i // 2, i) for i in range(2, n + 1)] ## complete
33     binary tree
34 # ===== graph =====
35 ## not necessarily connected, no multi-edge or self-loop
36 n = 10
37 density = 0.3 # graph density (0.0 ~ 1.0)
38 edges = [(i, j) for i in range(1, n+1) for j in range(i+1,
39     n+1) if random() < density]
40 ## connected, no multi-edge or self-loop
41 n, extra_edges = 10, 5
42 edges = set()
43 ##### ... generate spanning tree with codes above
44 while len(edges) < n - 1 + extra_edges:

```

```

40     u, v = randint(1, n), randint(1, n)
41     if u != v:
42         edges.add((min(u, v), max(u, v)))
43 edges = list(edges)
44 ## DAG
45 perm = sample(range(1, n + 1), n)
46 edges = []
47 for i in range(m):
48     i, j = sorted(sample(range(n), 2))
49     edges.append((perm[i], perm[j]))
50 ## Bipartite Graph
51 n1, n2 = 6, 7
52 left, right = list(range(1, n1+1)), list(range(n1+1,
53     n1+n2+1))
54 edges = [(choice(left), choice(right)) for _ in range(m)]

```

```

1 g++ -std=c++20 -o buggy $1
2 g++ -std=c++20 -o ac ac.cpp
3 for i in {1..100}; do
4     echo "TEST $i"
5     python3 gen.py > in
6     ./ac < in > oa
7     ./buggy < in > ob
8     if ! diff -q oa ob; then
9         cat in <(echo "=== AC") oa <(echo "=== WA") ob
10        break
11    fi
12 done

```

4 Data Structure

4.1 Mo's Algorithm

8d7194

```

1 // segments are 0-based
2 int B = max(1, (int)sqrt(n));
3 sort(Q.begin(), Q.end(), [&](const auto& a, const auto& b) {
4     if (a[0]/B != b[0]/B) return a[0]/B < b[0]/B;
5     return (a[0]/B & 1) ? a[1] < b[1] : a[1] > b[1];
6 });
7 ll cur = 0; // current answer
8 int pl = 0, pr = -1;
9 for (auto& qi : Q) {
10    // get (l, r, qid) from qi
11    while (pl < l) del(pl++); while (pl > l) add(--pl);
12    while (pr < r) add(++pr); while (pr > r) del(pr--);
13    ans[qid] = cur;
14 }

```

4.2 CDQ

744a80

```

1 // preparation
2 // 1. write a 1-base BIT
3 // 2. init(n, mxc): n is number of elements, mxc = 值域
4 // 3. build info array CDQ.v by yourself (x, y, z, id)
5 // 4. call solve()
6 // => cdq.ans[i] is number of j s.t. (xj <= xi, yj <= yi, zj
7     <= zi) (j != i)
8 struct CDQ {
9     struct info {
10         int x, y, z, id;
11         info(int x, int y, int z, int id):
12             x(x), y(y), z(z), id(id) {}
13         info():
14             x(0), y(0), z(0), id(0) {}
15     };
16     int n, mxc;
17     BIT bit;
18     vector<info> v;
19     vector<ll> ans;
20     void init(int _n, int _mxc) {
21         n = _n; mxc = _mxc;
22         v.assign(n, info{});
23         ans.assign(n, 0);
24     }
25     void dfs(int l, int r) {
26         if (l >= r) return;
27         int mid = (l+r) >> 1;
28         dfs(l, mid); dfs(mid+1, r);
29         vector<info> tmp;
30         vector<int> bit_op;
31         int pl = l, pr = mid+1;
32         while (pl <= mid && pr <= r) {
33             if (v[pl].y <= v[pr].y) {
34                 tmp.emplace_back(v[pl]);
35                 bit.upd(v[pl].z, 1);
36                 bit_op.emplace_back(v[pl].z);
37                 pl++;
38             }
39             else {
40                 tmp.emplace_back(v[pr]);
41                 ans[v[pr].id] += bit.qry(v[pr].z);
42                 pr++;
43             }
44         }
45         for (auto& p : tmp) v[pr++] = p;
46         bit.reset();
47         for (auto& z : bit_op) ans[z] += bit.qry(z);
48     }
49 }

```

```

43 }
44 while (pl <= mid) {
45     tmp.emplace_back(v[pl]);
46     pl++;
47 }
48 while (pr <= r) {
49     tmp.emplace_back(v[pr]);
50     ans[v[pr].id] += bit.qry(v[pr].z);
51     pr++;
52 }
53 for (int i = l, j = 0; i <= r; i++, j++) v[i] = tmp[j];
54 for (auto& op : bit_op) bit.upd(op, -1);
55 }
56 void solve() {
57     bit.init(mxc);
58     sort(v.begin(), v.end(), [&](const info& a, const info&
59 b){
60         return (a.x == b.x ? (a.y == b.y ? (a.z == b.z ?
61 a.id < b.id : a.z < b.z) : a.y < b.y) : a.x < b.x);
62     });
63     dfs(0, n-1);
64     map<pair<int, pii>, int> s;
65     sort(v.begin(), v.end(), [&](const info& a, const info&
66 b){
67         return a.id > b.id;
68     });
69     for (int i = 0, id = n-1; i < n; i++, id--) {
70         pair<int, pii> tmp = make_pair(v[i].x,
71 make_pair(v[i].y, v[i].z));
72         auto it = s.find(tmp);
73         if (it != s.end())
74             ans[id] += it->second;
75         s[tmp]++;
76     }
77 }
78 }

```

4.3 Persistent Treap

803cce

```

1 // Author: Ian
2 struct node {
3     node *l, *r;
4     char c; int v, sz;
5     node(char x = '$') : c(x), v(mt()), sz(1) {
6         l = r = nullptr;
7     }
8     node(node* p) { *this = *p; }
9     void pull() {
10         sz = 1;
11         for (auto i : {l, r})
12             if (i) sz += i->sz;
13     }
14 } arr[maxn], *ptr = arr;
15 inline int size(node* p) { return p ? p->sz : 0; }
16 node* merge(node* a, node* b) {
17     if (!a || !b) return a ? a : b;
18     if (a->v < b->v) {
19         node* ret = new(ptr++) node(a);
20         ret->r = merge(ret->r, b); ret->pull();
21         return ret;
22     }
23     else {
24         node* ret = new(ptr++) node(b);
25         ret->l = merge(a, ret->l); ret->pull();
26         return ret;
27     }
28 }
29 P<node*> split(node* p, int k) {
30     if (!p) return {nullptr, nullptr};
31     if (k >= size(p->l) + 1) {
32         auto [a, b] = split(p->r, k - size(p->l) - 1);
33         node* ret = new(ptr++) node(p);
34         ret->r = a; ret->pull();
35         return {ret, b};
36     }
37     else {
38         auto [a, b] = split(p->l, k);
39         node* ret = new(ptr++) node(p);
40         ret->l = b; ret->pull();
41         return {a, ret};
42     }
43 }

```

4.4 Li Chao Tree

6c33c2

```

1 // Author: Ian
2 // Function: For a set of lines L, find the maximum L_i(x)
3 in L in O(lg n).
4 typedef long double ld;
5 constexpr int maxn = 5e4 + 5;
6 struct line {
7     ld a, b;

```

```

7     ld operator()(ld x) { return a * x + b; }
8 } arr[(maxn + 1) << 2];
9 bool operator<(line a, line b) { return a.a < b.a; }
10 #define m ((l+r)>>1)
11 void insert(line x, int i = 1, int l = 0, int r = maxn) {
12     if (r - l == 1) {
13         if (x(l) > arr[i](l))
14             arr[i] = x;
15         return;
16     }
17     line a = max(arr[i], x), b = min(arr[i], x);
18     if (a(m) > b(m))
19         arr[i] = a, insert(b, i << 1, l, m);
20     else
21         arr[i] = b, insert(a, i << 1 | 1, m, r);
22 }
23 ld query(int x, int i = 1, int l = 0, int r = maxn) {
24     if (x < l || r <= x) return -numeric_limits<ld>::max();
25     if (r - l == 1) return arr[i](x);
26     return max({arr[i](x), query(x, i << 1, l, m), query(x, i
27 << 1 | 1, m, r)});
28 }
29 #undef m

```

4.5 Time Segment Tree

519775

```

1 // Author: Ian
2 struct Op; // reversible operation
3 const int maxn = 2e5 + 5;
4 vector<Op> arr[(maxn + 1) << 2];
5 #define m ((l + r) >> 1)
6 void insert(int ql, int qr, Op x, int i=1, int l=0, int r=maxn) {
7     if (qr <= l || r <= ql) return;
8     if (ql <= l && r <= qr) { arr[i].push_back(x); return; }
9     if (qr <= m) insert(ql, qr, x, i << 1, l, m);
10    else if (m <= ql) insert(ql, qr, x, i << 1 | 1, m, r);
11    else {
12        insert(ql, qr, x, i << 1, l, m);
13        insert(ql, qr, x, i << 1 | 1, m, r);
14    }
15 }
16 void traversal(vector<int>& ans, int i=1, int l=0, int r=maxn) {
17     int opcnt = 0;
18     for (auto val : arr[i])
19         if (DO_SOMETHING(val)) opcnt++;
20     if (r - l == 1) ans[l] = CALC_ANS();
21     else {
22         traversal(ans, i << 1, l, m);
23         traversal(ans, i << 1 | 1, m, r);
24     }
25     while (opcnt--) UNDO_SOMETHING();
26     arr[i].clear();
27 }
28 #undef m

```

4.6 Segment Tree Beats

f686aa

```

1 // Author: Ian, https://judge.yosupo.jp/submission/400861
2 const int maxn=2e5+5;
3 const ll MX = 1e18+5;
4 const ll MN = -MX;
5 #define m ((l+r)>>1)
6 struct node {
7     ll sum, inc;
8     ll mn, smn; int mnc;
9     ll mx, smx; int mxc;
10    node(ll x=0) : sum(x), inc(0),
11        mn(x), smn(MX), mnc(1),
12        mx(x), smx(MN), mxc(1) {}
13    void pull(int i);
14    void push(int i, int l, int r);
15 } a[(maxn+1)<<2];
16 void node::pull(int i) {
17     sum = a[i<<1].sum+a[i<<1|1].sum;
18     if (a[i<<1].mn == a[i<<1|1].mn) {
19         mn = a[i<<1].mn;
20         smn = min(a[i<<1].smn, a[i<<1|1].smn);
21         mnc = a[i<<1].mnc+a[i<<1|1].mnc;
22     } else {
23         if (a[i<<1].mn < a[i<<1|1].mn) {
24             mn = a[i<<1].mn;
25             smn = min(a[i<<1].smn, a[i<<1|1].mn);
26             mnc = a[i<<1].mnc;
27         } else {
28             mn = a[i<<1|1].mn;
29             smn = min(a[i<<1|1].smn, a[i<<1].mn);
30             mnc = a[i<<1|1].mnc;
31         }
32     }
33     if (a[i<<1].mx == a[i<<1|1].mx) {
34         mx = a[i<<1].mx;
35         smx = max(a[i<<1].smx, a[i<<1|1].smx);
36         mxc = a[i<<1].mxc+a[i<<1|1].mxc;

```

```

36 } else {
37     if (a[i<<1].mx > a[i<<1|1].mx) {
38         mx = a[i<<1].mx;
39         smx = max(a[i<<1].smx, a[i<<1|1].mx);
40         mxc = a[i<<1].mxc;
41     } else {
42         mx = a[i<<1|1].mx;
43         smx = max(a[i<<1|1].smx, a[i<<1].mx);
44         mxc = a[i<<1|1].mxc;
45     }
46 }
47 void updmn(int i, int len, ll v) {
48     a[i].sum += (v-a[i].mn)*a[i].mnc; a[i].mn = v;
49     if (len==1||v>=a[i].mx)
50         a[i].mx = v, a[i].smx = MN;
51     else if (v>a[i].smx)
52         a[i].smx = v;
53 }
54 void updmx(int i, int len, ll v) {
55     a[i].sum -= (a[i].mx-v)*a[i].mxc; a[i].mx = v;
56     if (len==1||v<=a[i].mn)
57         a[i].mn = v, a[i].smn = MX;
58     else if (v<a[i].smn)
59         a[i].smn = v;
60 }
61 void node::push(int i, int l, int r) {
62     if (r-l==1) return;
63     pair<int, int> ch[] = {{i<<1, m-l}, {i<<1|1, r-m}};
64     if (inc!=0) for (auto [j, len]: ch) {
65         a[j].sum += inc*len, a[j].inc += inc;
66         a[j].mx += inc, a[j].smx += inc;
67         a[j].mn += inc, a[j].smn += inc;
68     } inc = 0;
69     for (auto [j, len]: ch) {
70         if (a[j].mn < mn) updmn(j, len, mn);
71         if (a[j].mx > mx) updmx(j, len, mx);
72     }
73 void build(vector<ll>& v, int i=1, int l=0, int r=maxn) {
74     if ((int)v.size()<=l) return;
75     if (r-l==1) { a[i] = node(v[l]); return; }
76     build(v, i<<1, l, m);
77     build(v, i<<1|1, m, r);
78     a[i].pull(i);
79 }
80 void chmin(int ql, int qr, ll v, int i=1, int l=0, int r=maxn) {
81     if (qr<=l||r<=ql||a[i].mx<=v) return;
82     if (ql<=l&&r<=qr&&a[i].smx<v) { updmx(i, r-l, v); return; }
83     a[i].push(i, l, r);
84     chmin(ql, qr, v, i<<1, l, m);
85     chmin(ql, qr, v, i<<1|1, m, r);
86     a[i].pull(i);
87 }
88 void chmax(int ql, int qr, ll v, int i=1, int l=0, int r=maxn) {
89     if (qr<=l||r<=ql||a[i].mn>=v) return;
90     if (ql<=l&&r<=qr&&a[i].smn>v) { updmn(i, r-l, v); return; }
91     a[i].push(i, l, r);
92     chmax(ql, qr, v, i<<1, l, m);
93     chmax(ql, qr, v, i<<1|1, m, r);
94     a[i].pull(i);
95 }
96 void inc(int ql, int qr, ll v, int i=1, int l=0, int r=maxn) {
97     if (qr<=l||r<=ql) return;
98     if (ql<=l && r<=qr) {
99         a[i].sum += v*(r-l);
100         a[i].mx += v, a[i].smx += v;
101         a[i].mn += v, a[i].smn += v;
102         a[i].inc += v;
103         return;
104     }
105     a[i].push(i, l, r);
106     inc(ql, qr, v, i<<1, l, m);
107     inc(ql, qr, v, i<<1|1, m, r);
108     a[i].pull(i);
109 }
110 ll qsum(int ql, int qr, int i=1, int l=0, int r=maxn) {
111     if (qr<=l||r<=ql) return 0;
112     if (ql<=l && r<=qr) return a[i].sum;
113     a[i].push(i, l, r);
114     return qsum(ql, qr, i<<1, l, m)+qsum(ql, qr, i<<1|1, m, r);
115 }
116 #undef m

```

5 DP

5.1 SOS DP

623a08

```

1 // Author: Gino
2 // Function: Solve problems that enumerates subsets of
  subsets (3^n => n*2^n)
3 for (int msk = 0; msk < (1<<n); msk++) {
4     for (int i = 1; i <= n; i++) {

```

```

5         if (msk & (1<<(i - 1))) {
6             // dp[msk][i] = dp[msk][i - 1] + dp[msk ^ (1<<(i - 1))][i - 1];
7         } else {
8             // dp[msk][i] = dp[msk][i - 1];
9         }

```

5.2 Divide and Conquer DP

d36c77

```

1 /* Author: Simon Lindholm (License: CC0)
2 * Description: Given $a[i] = \min_{lo(i) \le k < hi(i)} (f(i, k))$ where the (minimal)
3 * optimal $k$ increases with $i$, computes $a[i]$ for $i = L..R-1$.
4 * Time: $O((N + (hi-lo)) \log N)$ */
5 struct DP { // Modify at will:
6     int lo(int ind) { return 0; }
7     int hi(int ind) { return ind; }
8     ll f(int ind, int k) { return dp[ind][k]; }
9     void store(int ind, int k, ll v) { res[ind] = pii(k, v); }
10    void rec(int L, int R, int LO, int HI) {
11        if (L >= R) return;
12        int mid = (L + R) >> 1;
13        pair<ll, int> best(LLONG_MAX, LO);
14        rep(k, max(LO, lo(mid)), min(HI, hi(mid)))
15            best = min(best, make_pair(f(mid, k), k));
16        store(mid, best.second, best.first);
17        rec(L, mid, LO, best.second+1);
18        rec(mid+1, R, best.second, HI);
19    }
20    void solve(int L, int R) { rec(L, R, INT_MIN, INT_MAX); }
21 };

```

5.3 Dynamic DP

- 適用情境： $dp_i = M_i \cdot dp_{i-1} \Rightarrow dp_i = M_i M_{i-1} \cdots M_1 dp_0$
- 當 M_i 需要動態修改，且 M_i 是廣義矩陣乘法：

$$C_{ij} = \bigoplus_k A_{ik} \otimes B_{kj}$$

- 滿足 $(\oplus, \otimes)$ 是半環 ($\otimes$ 對 $\oplus$ 有分配律、 $\otimes$ 和 $\oplus$ 有結合律、 $\oplus$ 有交換律)
- 此時便可用線段樹維護 $M_n M_{n-1} \cdots M_1$ 的乘積，線段樹上的 pos 是 M_{pos} ，但 pull 時要 $st[idx] = mul(st[cr], st[cl])$

5.4 Convex Hull Trick

bb4a1c

```

1 /**
2 * Author: Simon Lindholm (License: CC0, Source: own work)
3 * Container where you can add lines of the form kx+m,
4 * and query maximum values at points x.
5 * Useful for dynamic programming ('convex hull trick').
6 * Time: $O(\log N)$, Status: stress-tested */
7 struct Line {
8     mutable ll k, m, p;
9     bool operator<(const Line& o) const { return k < o.k; }
10    bool operator<(ll x) const { return p < x; }
11 };
12 struct LineContainer : multiset<Line, less<>> {
13     // (for doubles, use inf = 1/.0, div(a,b) = a/b)
14     static const ll inf = LLONG_MAX;
15     ll div(ll a, ll b) { // floored division
16         return a / b - ((a ^ b) < 0 && a % b);
17     }
18     bool isect(iterator x, iterator y) {
19         if (y == end()) return x->p = inf, 0;
20         if (x->k == y->k) x->p = x->m > y->m ? inf : -inf;
21         else x->p = div(y->m - x->m, x->k - y->k);
22         return x->p >= y->p;
23     }
24     void add(ll k, ll m) {
25         auto z = insert({k, m, 0}), y = z++, x = y;
26         while (isect(y, z)) z = erase(z);
27         if (x != begin() && isect(--x, y)) isect(x, y = erase(y));
28         while ((y = x) != begin() && (--x)->p >= y->p)
29             isect(x, erase(y));
30     }
31     ll query(ll x) {
32         auto l = *lower_bound(x);
33         return l.k * x + l.m;
34     }
35 };

```

6 Graph

6.1 Max Clique

3a1fe5

```

1 // max N = 64
2 typedef unsigned long long ll;
3 struct MaxClique {
4     ll nb[ N ], n, ans;
5     void init( ll _n ) {
6         n = _n;
7         for ( int i = 0 ; i < n ; i ++ ) nb[ i ] = 0LLU;

```

```

8 }
9 void add_edge( ll _u , ll _v ){
10     nb[ _u ] |= ( 1LLU << _v );
11     nb[ _v ] |= ( 1LLU << _u );
12 }
13 void B( ll r , ll p , ll x , ll cnt , ll res ){
14     if( cnt + res < ans ) return;
15     if( p == 0LLU && x == 0LLU ){
16         if( cnt > ans ) ans = cnt;
17         return;
18     }
19     ll y = p | x; y &= -y;
20     ll q = p & ( ~nb[ int( log2( y ) ) ] );
21     while( q ){
22         ll i = int( log2( q & (-q) ) );
23         B( r | ( 1LLU << i ) , p & nb[ i ] , x & nb[ i ]
24             , cnt + 1LLU , __builtin_popcountll( p &
25                 nb[ i ] ) );
26         q &= ~( 1LLU << i );
27         p &= ~( 1LLU << i );
28         x |= ( 1LLU << i );
29     }
30 }
31 int solve(){
32     ans = 0;
33     ll _set = 0;
34     if( n < 64 ) _set = ( 1LLU << n ) - 1;
35     else{
36         for( ll i = 0 ; i < n ; i ++ ) _set |= ( 1LLU << i );
37     }
38     B( 0LLU , _set , 0LLU , 0LLU , n );
39     return ans;
40 }
41 }maxClique;

```

6.2 Bellman-Ford

92b21f

```

1 // Author: Gino
2 // n, m = #(vertices), #(edges), and vertices are 1-based
3 // 1. BellmanFord bf(G, n, m);
4 // 2-1: bf.calcDis(s);
5 // => bf.dis[u] := shortest dis from s to u
6 // => bf.dis[u] := LINF (s can't reach u)
7 // => bf.dis[u] := -LINF (dis[u] can be arbitrary small)
8 // 2-2: bf.findNegCycle();
9 // => false (if no neg cycle)
10 // => true (has neg cycle & gives an example: bf.neg_cycle)
11 // Time: O(VE), Space: O(V + E)
12 const ll LINF = 4e18;
13 struct BellmanFord {
14     const vector<vector<pair<int, ll>>& G;
15     int n, m; // #(vertices), #(edges)
16     BellmanFord(const auto& G, int n, int m):G(G), n(n), m(m) {}
17     vector<ll> dis; vector<int> nth_relax, pa;
18     void run_bf(const auto& src) {
19         dis.assign(n+1, LINF);
20         nth_relax.assign(n+1, 0); pa.assign(n+1, -1);
21         for (auto& s : src) dis[s] = 0;
22         for (int rlx = 1; rlx <= n; rlx++) {
23             for (int u = 1; u <= n; u++) {
24                 if (dis[u] == LINF) continue; // !important
25                 for (auto& [v, w] : G[u]) {
26                     if (dis[v] > dis[u] + w) {
27                         dis[v] = dis[u] + w; pa[v] = u;
28                         if (rlx == n) nth_relax[v] = 1;
29                     }
30                 }
31             }
32             // 5 brackets
33         }
34         void calcDis(int s) {
35             run_bf(vector<int>{s}); queue<int> q;
36             for (int u=1; u<=n; u++) if (nth_relax[u]) q.push(u);
37             while (!q.empty()) { int u = q.front(); q.pop();
38                 for (auto& [v, w] : G[u]) {
39                     if (!nth_relax[v]) {
40                         nth_relax[v] = 1; q.push(v);
41                     }
42                 }
43             }
44             for (int u=1; u<=n; u++) if (nth_relax[u]) dis[u] = -LINF;
45         }
46     }
47     vector<int> neg_cycle;
48     bool findNegCycle() {
49         auto src = views::iota(1, n + 1); run_bf(src);
50         auto it = ranges::find_if(src,
51             [&](int s){ return nth_relax[s]; });
52         if (it == src.end()) return false;
53         int ptr = *it; for (int i=0; i<n; i++) ptr = pa[ptr];
54         neg_cycle.clear(); int cur = ptr;
55         while (true) {
56             neg_cycle.emplace_back(cur);
57             if (cur == ptr && neg_cycle.size() > 1) break;
58             cur = pa[cur];
59         }
60         ranges::reverse(neg_cycle); return true;
61     }
62 }

```

54 } };

6.3 System of Difference Constraints

fe55f9

```

1 vector<vector<pair<int, ll>>> G;
2 void add(int u, int v, ll w) { G[u].push_back({v, w}); }

```

- $x_u - x_v \leq c \Rightarrow \text{add}(v, u, c)$
- $x_u - x_v \geq c \Rightarrow \text{add}(u, v, -c)$
- $x_u - x_v = c \Rightarrow \text{add}(v, u, c), \text{add}(u, v, -c)$
- $x_u \geq c \Rightarrow \text{add super vertex } x_0 = 0, \text{ then } x_u - x_0 \geq c \Rightarrow \text{add}(u, 0, -c)$
- Don't forget non-negative constraints for every variable if specified implicitly.
- Interval sum $\Rightarrow$ Use prefix sum to transform into differential constraints. Don't forget $S_{i+1} - S_i \geq 0$ if x_i needs to be non-negative.
- $x_u/x_v \leq c \Rightarrow \log x_u - \log x_v \leq \log c$

6.4 Graph Girth

Run BFS for every node, when encountered non-BFS-tree edge, update answer (min cycle length) with $\text{dis}[u] + \text{dis}[v] + 1$. Time $O(VE)$.

6.5 Euler Trail

11c393

```

1 // Author: kactl (Simon Lindholm), wrapped by Gino
2 // Vertices are 1-based, Edge ID are 0-based
3 // 1. EulerWalk euler(n, true(directed) / false(undirected));
4 // 2. euler.addEdge(u, v);
5 // 3. int result = euler.solve();
6 // => -1: nothing (euler.path, euler.path_edges = {})
7 // => 1: Euler trail,
8 // => 2: Euler circuit
9 //     euler.path = {u_1, ..., u_{m+1}}
10 //     euler.path_edges = {e_1, ..., e_m}
11 // Time: O(V + E), Space: O(V + E)
12 // Test: V, E <= 2e5, 99ms
13 struct EulerWalk {
14     int n, m = 0; bool dir;
15     vector<vector<pii>> G; vi deg;
16     EulerWalk(int n, bool dir) :
17         n(n), dir(dir), G(n+1), deg(n+1) {}
18     void addEdge(int u, int v) {
19         G[u].push_back({v, m});
20         if (!dir) G[v].push_back({u, m});
21         deg[u]++, deg[v] += dir ? -1 : 1; m++;
22     }
23     vi path, path_edges;
24     void walk(int src) {
25         path.clear(); path_edges.clear();
26         vi its(n+1), visE(m);
27         function<void(int, int)> dfs = [&](int u, int e_in) {
28             while (its[u] < sz(G[u])) {
29                 auto [v, e] = G[u][its[u]++];
30                 if (visE[e]) continue;
31                 visE[e] = 1;
32                 dfs(v, e);
33             }
34             path.push_back(u);
35             if (e_in != -1) path_edges.push_back(e_in);
36         };
37         dfs(src, -1);
38         if (sz(path) != m + 1) {
39             path.clear(); path_edges.clear(); return;
40         }
41         ranges::reverse(path); ranges::reverse(path_edges);
42     }
43     int solve() {
44         int s = -1, odd = 0, src = 0, dst = 0;
45         for (int u = 1; u <= n; u++) {
46             if (!dir && (deg[u] & 1)) odd++, s = u;
47             if (dir && deg[u] == 1) s = u, src++;
48             if (dir && deg[u] == -1) dst++;
49             if (dir && abs(deg[u]) > 1) return -1;
50         }
51         if (!dir && odd != 0 && odd != 2) return -1;
52         if (dir && !((src == 0 && dst == 0) || (src == 1 && dst == 1))) return -1;
53         if (s == -1) for (int u = 1; u <= n; u++)
54             if (!G[u].empty()) { s = u; break; }
55         if (s == -1) s = 1;
56         walk(s);
57         return path.empty() ? -1 :
58             path.front() == path.back() ? 2 : 1;
59     }
60 };

```

6.6 Vertex BCC (Round Square Tree)

e85b0a

```

1 // Author: Ian, https://judge.yosupo.jp/submission/399308
2 // Vertex BCC (Round Square Tree) 0-based; Edge ID 0-based
3 // 1. BCC bcc(n); // n = #(vertices)
4 // 2. bcc.add_edge(u, v);

```

```

5// 3. bcc.build();
6// => bcc[id]: vertices in bcc `id` (square node n+id in T)
7// => T[id]: tree adjacency; square nodes are n..n+ncnt-1
8// => is_cut(x): whether x is a cut vertex
9// => bcc_id(u, v): square node containing tree-edge (u, v)
10 struct BCC {
11     int n, m, t, ncnt;
12     vector<vector<pii>> G;
13     vector<vector<int>> T, bcc;
14     vector<int> dep, low, pa2, dep2, s;
15     void add_edge(int u, int v) {
16         G[u].eb(v, m), G[v].eb(u, m++);
17     }
18     void dfs(int x, int f) {
19         if (~dep[x]) return;
20         dep[x] = low[x] = t++;
21         s.push_back(x);
22         for (auto [y, e]: G[x]) if (e != f) {
23             if (dep[y] == -1) {
24                 dfs(y, e), low[x] = min(low[x], low[y]);
25                 if (low[y] >= dep[x]) {
26                     int id = n + ncnt++; p;
27                     bcc.resize(bcc.size()+1);
28                     do {
29                         p = s.back(), s.pop_back();
30                         T[id].push_back(p), T[p].push_back(id);
31                         bcc.back().push_back(p);
32                     } while (p != y);
33                     T[id].push_back(x), T[x].push_back(id);
34                     bcc.back().push_back(x);
35                 } else low[x] = min(low[x], dep[y]);
36             }
37         }
38         void dfs2(int x, int p) {
39             dep2[x] = ~p ? dep2[p] + 1 : 0, pa2[x] = p;
40             for (auto y: T[x]) if (y != p) dfs2(y, x);
41         }
42         bool is_cut(int x) { return (int)T[x].size() != 1; }
43         int bcc_id(int u, int v) {
44             return pa2[dep2[u] < dep2[v] ? v : u] - n;
45         }
46         void build() {
47             for (int i = 0; i < n; i++) if (dep[i] == -1) {
48                 if (G[i].empty()) { // isolated vertex: singleton bcc
49                     dep[i] = low[i] = t++;
50                     int id = n + ncnt++;
51                     bcc.push_back({i});
52                     T[id].push_back(i), T[i].push_back(id);
53                 } else dfs(i, -1);
54             }
55             dfs2(i, -1);
56         }
57         BCC(int n): n(n), m(0), t(0), ncnt(0), G(n), T(2*n),
58             dep(n, -1), low(n), pa2(2*n), dep2(2*n) {}
59 };

```

6.7 Edge BCC

26729d

```

1// Author: Ian, https://judge.yosupo.jp/submission/399295
2// Edge BCC, 0-based; Edge ID 0-based
3// 1. EBCC ebcc(n); // n = #vertices
4// 2. ebcc.add_edge(u, v);
5// 3. ebcc.build();
6// => bcc[i]: each edge bcc
7// => bccn[x]: in which bcc is x
8// => isbr[e]: whether edge e is a bridge
9 struct EBCC {
10     int n, m, t, ncnt;
11     vector<vector<pii>> G;
12     vector<vector<int>> bcc;
13     vector<bool> isbr;
14     vector<int> dep, low, bccn, s;
15     EBCC(int n): n(n), m(0), t(0), ncnt(0), G(n),
16         dep(n, -1), low(n), bccn(n) {}
17     void add_edge(int u, int v) {
18         G[u].eb(v, m), G[v].eb(u, m++);
19     }
20     void dfs(int x, int f) {
21         if (~dep[x]) return;
22         dep[x] = low[x] = t++;
23         s.push_back(x);
24         for (auto [y, e]: G[x]) if (e != f) {
25             if (dep[y] == -1) {
26                 dfs(y, e), low[x] = min(low[x], low[y]);
27             } else
28                 low[x] = min(low[x], dep[y]);
29         }
30         if (dep[x] == low[x]) {
31             if (~f) isbr[f] = true;
32             bcc.resize(bcc.size()+1);
33             int p; do {
34                 bccn[p = s.back()] = ncnt;
35                 s.pop_back();
36                 bcc.back().push_back(p);
37             } while (p != x); ncnt++;
38         }
39     }
40 }

```

```

38 void build() {
39     isbr.assign(m, false);
40     for (int i=0; i<n; i++) dfs(i, -1);
41 }

```

6.8 Kth Shortest Path

34bacd

```

1// time: O(|E| lg |E|+|V| lg |V|+K)
2// memory: O(|E| lg |E|+|V|)
3 struct KSP { // 1-base
4     struct nd {
5         int u, v; ll d;
6         nd(int ui=0, int vi=0, ll di=INF) { u=ui; v=vi; d=di; }
7     };
8     struct heap { nd* edge; int dep; heap* chd[4]; };
9     static int cmp(heap* a, heap* b) {
10         return a->edge->d > b->edge->d;
11     }
12     struct node {
13         int v; ll d; heap* H; nd* E;
14         node() {}
15         node(ll _d, int _v, nd* _E) { d=_d; v=_v; E=_E; }
16         node(heap* _H, ll _d) { H=_H; d=_d; }
17         friend bool operator<(node a, node b) {
18             return a.d > b.d;
19         }
20     };
21     int n, k, s, t, dst[N]; nd *nxt[N];
22     vector<nd*> g[N], rg[N]; heap *nullNd, *head[N];
23     void init(int _n, int _k, int _s, int _t) {
24         n=_n; k=_k; s=_s; t=_t;
25         for (int i=1; i<=n; i++) {
26             g[i].clear(); rg[i].clear();
27             nxt[i]=NULL; head[i]=NULL; dst[i]=-1;
28         }
29     }
30     void addEdge(int ui, int vi, ll di) {
31         nd* e=new nd(ui, vi, di);
32         g[ui].push_back(e); rg[vi].push_back(e);
33     }
34     queue<int> dfsQ;
35     void dijkstra() {
36         while (dfsQ.size()) dfsQ.pop();
37         priority_queue<node> Q; Q.push(node(0, t, NULL));
38         while (!Q.empty()) {
39             node p=Q.top(); Q.pop(); if (dst[p.v] != -1) continue;
40             dst[p.v]=p.d; nxt[p.v]=p.E; dfsQ.push(p.v);
41             for (auto e: rg[p.v]) Q.push(node(p.d+e->d, e->u, e));
42         }
43     }
44     heap* merge(heap* curNd, heap* newNd) {
45         if (curNd==nullNd) return newNd;
46         heap* root=new heap; memcpy(root, curNd, sizeof(heap));
47         if (newNd->edge->d < curNd->edge->d) {
48             root->edge=newNd->edge;
49             root->chd[2]=newNd->chd[2];
50             root->chd[3]=newNd->chd[3];
51             newNd->edge=curNd->edge;
52             newNd->chd[2]=curNd->chd[2];
53             newNd->chd[3]=curNd->chd[3];
54         }
55         if (root->chd[0]->dep < root->chd[1]->dep)
56             root->chd[0]=merge(root->chd[0], newNd);
57         else root->chd[1]=merge(root->chd[1], newNd);
58         root->dep=max(root->chd[0]->dep,
59                     root->chd[1]->dep)+1;
60         return root;
61     }
62     vector<heap*> V;
63     void build() {
64         nullNd=new heap; nullNd->dep=0; nullNd->edge=new nd;
65         fill(nullNd->chd, nullNd->chd+4, nullNd);
66         while (not dfsQ.empty()) {
67             int u=dfsQ.front(); dfsQ.pop();
68             if (!nxt[u]) head[u]=nullNd;
69             else head[u]=head[nxt[u]->v];
70             V.clear();
71             for (auto& e: g[u]) {
72                 int v=e->v;
73                 if (dst[v] == -1) continue;
74                 e->d+=dst[v]-dst[u];
75                 if (nxt[u] != e) {
76                     heap* p=new heap; fill(p->chd, p->chd+4, nullNd);
77                     p->dep=1; p->edge=e; V.push_back(p);
78                 }
79             }
80         }
81         if (V.empty()) continue;
82         make_heap(V.begin(), V.end(), cmp);
83         #define L(X) ((X<<1)+1)
84         #define R(X) ((X<<1)+2)
85         for (size_t i=0; i<V.size(); i++) {
86             if (L(i)<V.size()) V[i]->chd[2]=V[L(i)];
87             else V[i]->chd[2]=nullNd;
88             if (R(i)<V.size()) V[i]->chd[3]=V[R(i)];
89         }
90     }

```

```

84     else V[i]->chd[3]=nullNd;
85 }
86 head[u]=merge(head[u],V.front());
87 }
88 vector<ll> ans;
89 void first_K(){
90     ans.clear(); priority_queue<node> Q;
91     if(dst[s]==-1) return;
92     ans.push_back(dst[s]);
93     if(head[s]!=nullNd)
94         Q.push(node(head[s],dst[s]+head[s]->edge->d));
95     for(int _=1; <k and not Q.empty();_++){
96         node p=Q.top(); q=Q.pop(); ans.push_back(p.d);
97         if(head[p.H->edge->v]!=nullNd){
98             q.H=head[p.H->edge->v]; q.d=p.d+q.H->edge->d;
99             Q.push(q);
100         }
101         for(int i=0;i<4;i++){
102             if(p.H->chd[i]!=nullNd){
103                 q.H=p.H->chd[i];
104                 q.d=p.d+p.H->edge->d+p.H->chd[i]->edge->d;
105                 Q.push(q);
106             }
107         }
108     }
109     void solve(){ // ans[i] stores the i-th shortest path
110         dijkstra(); build();
111         first_K(); // ans.size() might less than k
112     }
113 } solver;

```

6.9 SCC - Tarjan

7a063d

```

1// Author: Ian, https://judge.yosupo.jp/submission/399291
2// Tarjan SCC, 0-based
3// 1. SCC scc(n); // n = #(vertices)
4// 2. Fill in adj list G
5// 3. scc.build()
6// => scc[i]: each scc
7// => sccn[x]: in which scc is x
8struct SCC {
9    const int inf = 1e9+5;
10    int n, t, ncnt;
11    vector<vector<int>> G, scc;
12    vector<bool> ins;
13    vector<int> sccn, dfn, low, s;
14    SCC(int n): n(n), t(0), ncnt(0), G(n),
15        ins(n, false), sccn(n), dfn(n, -1), low(n, inf) {}
16    void dfs(int x) {
17        if (~dfn[x]) return;
18        dfn[x] = low[x] = t++;
19        s.push_back(x), ins[x] = true;
20        for (auto i: G[x])
21            if (dfs(i), ins[i])
22                low[x] = min(low[x], low[i]);
23        if (dfn[x] == low[x]) {
24            scc.resize(scc.size()+1);
25            int p; do {
26                ins[p = s.back()] = false;
27                s.pop_back(); sccn[p] = ncnt;
28                scc.back().push_back(p);
29            } while (p != x); ncnt++;
30        }
31    }
32    void build() { for (int i=0; i<n; i++) dfs(i); }
33};

```

6.10 2SAT

130351

```

1// Author: Ian, CRyptoGrapheR
2struct TwoSAT: SCC {
3    TwoSAT(int n): SCC(2*n) {}
4    // (var a == na) v (var b == nb)
5    void add_disjunction(int a,int na,int b,int nb) {
6        a = 2*a^na, b = 2*b^nb;
7        G[a^1].push_back(b);
8        G[b^1].push_back(a);
9    }
10    vector<int> solve() {
11        build(); vector<int> assignment(n/2,0);
12        for(int i=0; i<n/2; i++){
13            if (sccn[2*i] == sccn[2*i^1]) return {};
14            assignment[i] = sccn[2*i] > sccn[2*i^1];
15        } return assignment;
16    };

```

7 Tree

7.1 Tree Isomorphism (Rooted Trees)

f3f029

```

1// Author: Gino
2// Checks if 2 rooted trees are isomorphic
3// Time: O(V log V)
4// vector<vector<int>> G1, G2;
5// int root_1, root_2;

```

```

6map<vector<int>, int> dict;
7int encode(const auto& G, int u, int pa = -1) {
8    vector<int> codes;
9    for (auto& v : G[u])
10        if (v != pa)
11            codes.emplace_back(encode(G, v, u));
12    ranges::sort(codes);
13    auto [it, _] = dict.try_emplace(codes, dict.size());
14    return it->second;
15}
16bool isomorphic() {
17    dict.clear(); dict[{}] = 0;
18    return encode(G1, root_1) == encode(G2, root_2);
19}

```

7.2 Tree Isomorphism (Unrooted Trees)

Find the centroid(s) of T_1, T_2 .

Case 1: T_1, T_2 have different number of centroids $\rightarrow$ NO

Case 2: T_1 has centroid c_1, T_2 has centroid c_2

$\rightarrow$ rooted_isomorphic(c_1, c_2)

Case 3: T_1 has centroids c_1, c_1', T_2 has centroids c_2, c_2'

$\rightarrow$ rooted_isomorphic(c_1, c_2) || rooted_isomorphic(c_1', c_2')

7.3 Heavy Light Decomposition

53e45c

```

1// Author: Ian, https://judge.yosupo.jp/submission/399317
2void segbuild(vector<int>&v);
3void segmodify(int p, int k);
4int segquery(int ql, int qr);
5// Insert [ql, qr) segment tree here
6template<class T=int> struct HLD {
7    int n, cnt;
8    vector<int> d, f, sz, son, top, dfn;
9    HLD(int n): n(n), cnt(0), d(n, 0), f(n, 0), sz(n, 1),
10        son(n, -1), top(n, 0), dfn(n, -1) {}
11    void dfs1(int x, int p) {
12        for (auto i: e[x]) if (i != p) {
13            d[i] = d[x]+1, f[i] = x;
14            dfs1(i, x), sz[x] += sz[i];
15            if (son[x] == -1 || sz[son[x]] < sz[i])
16                son[x] = i;
17        }
18    }
19    void dfs2(int x, int t) {
20        dfn[x] = cnt++, top[x] = t;
21        if (son[x] == -1) return;
22        dfs2(son[x], t);
23        for (auto i: e[x])
24            if (!dfn[i]) dfs2(i, i);
25    }
26    void build(const vector<T>&v) {
27        dfs1(0, 0); dfs2(0, 0);
28        vector<T> dfnv(v.size());
29        for (int i=0; i<n; i++)
30            dfnv[dfn[i]] = v[i];
31        segbuild(dfnv);
32    }
33    void modify(int p, T v) { segmodify(dfn[p], v); }
34    T query(int a, int b) {
35        auto agr = [](int x, int y) { return max(x, y); };
36        T ret = 0;
37        while (top[a] != top[b]) {
38            if (d[top[a]] > d[top[b]]) swap(a, b);
39            ret = agr(ret, segquery(dfn[top[b]], dfn[b]+1));
40            b = f[top[b]];
41        }
42        if (dfn[a] > dfn[b]) swap(a, b);
43        return agr(ret, segquery(dfn[a], dfn[b]+1));
44    }

```

7.4 Virtual Tree

172166

```

1// Author: std_abs
2// need lca, in, out
3vector<pii> virtual_tree(vector<int>&v) {
4    auto cmp = [&](int x, int y) { return in[x] < in[y]; };
5    sort(all(v), cmp);
6    for (int i = 1; i < sz(v); ++i)
7        v.pb(lca(v[i-1], v[i]));
8    sort(all(v), cmp);
9    v.resize(unique(all(v)) - v.begin());
10    vector<int> stk(1, v[0]);
11    vector<pii> res;
12    for (int i = 1; i < sz(v); ++i) {
13        int x = v[i];
14        while (out[stk.back()] < out[x]) stk.pop_back();
15        res.emplace_back(stk.back(), x), stk.pb(x);
16    }
17    return res;
18}

```

8 Matching

8.1 Bipartite Matching

f42921

```

1// Author: Gino
2// Function: Max Bipartite Matching in  $O(V \sqrt{E})$ 
3//> hk.init(nx, ny) -> hk.add(x, y (+nx))
4//> hk.max_matching(): the matching plan stores in mx, my
5//> hk.min_vertex_cover(): vertex cover plan stores in vcover
6// (!) vertices are 0-based: X = [0, nx), Y = [nx, nx+ny)
7#define pb emplace_back
8struct HopcroftKarp {
9    int n, nx, ny; vector<vector<int>> G; vector<int> mx, my;
10    void init(int nx, int ny): nx(nx), ny(ny), n(nx + ny) {
11        G.assign(n, vector<int>()); }
12    void add(int x, int y) { G[x].pb(y); G[y].pb(x); }
13    int max_matching() {
14        vector<int> dis, vis;
15        mx.assign(n, -1); my.assign(n, -1);
16        function<bool(int)> dfs = [&](int x) {
17            vis[x] = 1;
18            for (int y : G[x]) {
19                int p = my[y];
20                if (p == -1 ||
21                    (dis[p] == dis[x] + 1 && !vis[p] && dfs(p)))
22                    return mx[x] = y, my[y] = x, true;
23            }
24            return false;
25        };
26        while (true) {
27            dis.assign(n, -1);
28            queue<int> q;
29            for (int x = 0; x < nx; x++)
30                if (mx[x] == -1) dis[x] = 0, q.push(x);
31            while (!q.empty()) {
32                int x = q.front(); q.pop();
33                for (int y : G[x])
34                    if (my[y] != -1 && dis[my[y]] == -1)
35                        dis[my[y]] = dis[x] + 1, q.push(my[y]);
36            }
37            vis.assign(n, 0);
38            bool found = false;
39            for (int x = 0; x < nx; x++)
40                if (mx[x] == -1 && dfs(x)) found = true;
41            if (!found) break;
42        }
43        int ans = 0;
44        for (int x = 0; x < nx; x++) if (mx[x] != -1) ans++;
45        return ans;
46    }
47    vector<int> vcover;
48    int min_vertex_cover() {
49        int ans = max_matching(); vector<int> vis(n, 0);
50        function<void(int)> dfs = [&](int x) {
51            vis[x] = true;
52            for (int y : G[x]) {
53                if (y == mx[x] || my[y] == -1 || vis[y]) continue;
54                vis[y] = true;
55                dfs(my[y]);
56            }
57        };
58        for (int x = 0; x < nx; x++) if (mx[x] == -1) dfs(x);
59        vcover.clear();
60        for (int x = 0; x < nx; x++) if (!vis[x]) vcover.pb(x);
61        for (int y = nx; y < nx + ny; y++) if (vis[y]) vcover.pb(y);
62        return ans;
63    }
64} hk;

```

8.2 Bipartite Weighted Matching

5933aa

```

1// Author: ckiseki, n = #(left vertices) = #(right vertices)
2// left, right vertices labeled 1 ~ n separately
3// 1. build 1-based matrix G of size (n + 1) * (n + 1)
4// G[u][v] := weight between (left u, right v)
5// <!-- if not need perfect matching
6// ==> set weights of all negative edges to 0
7// 2. construct (solve at same time): KM km(n, G);
8// ==> km.ans (max perfect weight sum)
9// ==> km.fl[u] (left u -> right v)
10// ==> km.fr[v] (right v -> left u)
11// Time:  $O(V^3)$ , Space:  $O(V^2)$ , Test:  $V \leq 500$ , 243ms
12struct KM { // maximize, test @ UOJ 80
13    int n, l, r; ll ans; // fl and fr are the match
14    vector<ll> hl, hr; vector<int> fl, fr, pre, q;
15    void bfs(const auto &w, int s) {
16        vector<int> vl(n + 1), vr(n + 1);
17        vector<ll> slk(n + 1, LINF);
18        l = r = 0; vr[q[r++] = s] = true;
19        auto check = [&](int x) -> bool {
20            if (vl[x] || slk[x] > 0) return true;
21            vl[x] = true; slk[x] = LINF;

```

```

22        if (fl[x] != -1) return (vr[q[r++] = fl[x]] = true);
23        while (x != -1) swap(x, fr[fl[x] = pre[x]]);
24        return false;
25    };
26    while (true) {
27        while (l < r)
28            for (int x = 1, y = q[l++]; x <= n; ++x) if (!vl[x])
29                if (ll val = hl[x] + hr[y] - w[x][y]; val < slk[x]) {
30                    slk[x] = val;
31                    if (pre[x] = y, !check(x)) return;
32                }
33        ll d = LINF;
34        for (int x = 1; x <= n; ++x) d = min(d, slk[x]);
35        for (int x = 1; x <= n; ++x)
36            vl[x] ? hl[x] += d : slk[x] -= d;
37        for (int x = 1; x <= n; ++x) if (vr[x]) hr[x] -= d;
38        for (int x = 1; x <= n; ++x) if (!check(x)) return;
39    }
40    KM(int n_, const auto &w) : n(n_), ans(0),
41        hl(n+1, hr(n+1), fl(n+1, -1), fr(fl), pre(n+1), q(n+1) {
42        for (int i = 1; i <= n; ++i) {
43            hl[i] = -LINF;
44            for (int j = 1; j <= n; ++j) hl[i] = max(hl[i], (ll)w[i][j]);
45        }
46        for (int i = 1; i <= n; ++i) bfs(w, i);
47        for (int i = 1; i <= n; ++i) ans += w[i][fl[i]];
48    }
49};

```

8.3 General Matching

93f948

```

1// Author: ckiseki
2// 0. build 1-based graph vector<vector<int>> G(n + 1);
3// 1. construct (solve at same time):
4// GeneralMatching M(G, n); ==> M.ans
5// status: M.match[x] (-1 if not matched, 1 <= x <= n)
6// Time:  $O(V^3)$ , Space:  $O(V + E)$ , Test:  $V \leq 500$ , 11ms
7struct GeneralMatching {
8    queue<int> q; int ans, n;
9    vector<int> fa, s, v, pre, match;
10    int Find(int u) {
11        return u == fa[u] ? u : fa[u] = Find(fa[u]); }
12    int LCA(int x, int y) {
13        static int tk = 0; tk++; x = Find(x); y = Find(y);
14        for (; swap(x, y)) if (x != 0) {
15            if (v[x] == tk) return x;
16            v[x] = tk;
17            x = Find(pre[match[x]]);
18        }
19    }
20    void Blossom(int x, int y, int l) {
21        for (; Find(x) != l; x = pre[y]) {
22            pre[x] = y, y = match[x];
23            if (s[y] == 1) q.push(y), s[y] = 0;
24            for (int z : {x, y}) if (fa[z] == z) fa[z] = l;
25        }
26    }
27    bool Bfs(auto &&g, int r) {
28        iota(all(fa), 0); ranges::fill(s, -1);
29        q = queue<int>(); q.push(r); s[r] = 0;
30        for (; !q.empty(); q.pop()) {
31            for (int x = q.front(); int u : g[x])
32                if (s[u] == -1) {
33                    if (pre[u] = x, s[u] = 1, match[u] == 0) {
34                        for (int a = u, b = x, last;
35                            b != 0; a = last, b = pre[a])
36                            last = match[b], match[b] = a, match[a] = b;
37                        return true;
38                    }
39                    q.push(match[u]); s[match[u]] = 0;
40                }
41            else if (!s[u] && Find(u) != Find(x)) {
42                int l = LCA(u, x);
43                Blossom(x, u, l); Blossom(u, x, l);
44            }
45        }
46        return false;
47    }
48    GeneralMatching(auto &&g, int n_) : ans(0), n(n_),
49        fa(n+1), s(n+1), v(n+1), pre(n+1, 0), match(n+1, 0) {
50        for (int x = 1; x <= n; ++x)
51            if (match[x] == 0) ans += Bfs(g, x);
52        for (int x = 1; x <= n; ++x)
53            if (match[x] == 0) match[x] = -1;
54    }
55};

```

9 Flow

9.1 Flow Methods

9516b6

```

1// Author: CRyptographer (some modified by Gino)
2Maximize  $c^T x$  subject to  $Ax \leq b, x \geq 0$ ;
3with the corresponding symmetric dual problem,
4Minimize  $b^T y$  subject to  $A^T y \geq c, y \geq 0$ .
5Maximize  $c^T x$  subject to  $Ax \leq b$ ;

```

6 with the corresponding asymmetric dual problem,
7 Minimize $b^T y$ subject to $A^T y = c, y \geq 0$.
8 Maximize $\sum x$ subject to $x_i + x_j \leq A_{ij}, x \geq 0$;
9 $\Rightarrow$ Maximize $\sum x$ subject to $x_i + x_j \leq A_{ij}$;
10 $\Rightarrow$ Minimize $A^T y = \sum A_{ij} y_{ij}$ subject to for all v ,
 $\sum_{i=v \text{ or } j=v} y_{ij} = 1, y_{ij} \geq 0$
11 $\Rightarrow$ possible optimal solution: $y_{ij} = \{0, 0.5, 1\}$
12 $\Rightarrow y' = 2y$: $\sum_{i=v \text{ or } j=v} y'_{ij} = 2, y'_{ij} = \{0, 1, 2\}$
13 $\Rightarrow$ Minimum Bipartite perfect matching/2 ($V_1=X, V_2=X, E=A$)
14 General Graph:
15 $|Max \text{ Ind. Set}| + |Min \text{ Vertex Cover}| = |V|$
16 $|Max \text{ Ind. Edge Set}| + |Min \text{ Edge Cover}| = |V|$
17 Bipartite Graph:
18 $|Max \text{ Ind. Set}| = |Min \text{ Edge Cover}|$
19 $|Max \text{ Ind. Edge Set}| = |Min \text{ Vertex Cover}|$
20 To reconstruct the minimum vertex cover, dfs from each
21 unmatched vertex on the left side and with unused edges
22 only. Equivalently, dfs from source with unused edges
23 only and without visiting sink. Then, a vertex is
24 chosen iff. it is on the left side and without visited
25 or on the right side and visited through dfs.
26 Minimum Weighted Bipartite Edge Cover:
27 Construct new bipartite graph with $n+m$ vertices on each
28 side:
29 for each vertex u , duplicate a vertex u' on the other side
30 for each edge (u,v,w) , add edges (u,v,w) and (v',u',w)
31 for each vertex u , add edge $(u,u',2w)$ where w is min edge
32 connects to u
31 then the answer is the minimum perfect matching of the new
32 graph (KM)
33 Maximum density subgraph ($\sum W_e + \sum W_v$) / $|V|$
34 Binary search on answer:
35 For a fixed D , construct a Max flow model as follow:
36 Let S be Sum of all weight (or inf)
37 1. from source to each node with cap = S
38 2. For each (u,v,w) in E , $(u \rightarrow v, \text{cap}=w)$, $(v \rightarrow u, \text{cap}=w)$
39 3. For each node v , from v to sink with cap = $S + 2 * D - \text{deg}[v] - 2 * (W \text{ of } v)$
39 where $\text{deg}[v] = \sum \text{weight of edge associated with } v$
40 If $\text{maxflow} < S * |V|$, D is an answer.
41 Requiring subgraph: all vertex can be reached from source
42 with
43 edge whose cap > 0 .
44 Maximum closed subgraph
45 1. connect source with positive weighted
46 vertex(capacity=weight)
47 2. connect sink with negative weighted vertex(capacity=-
48 weight)
49 3. make capacity of the original edges = inf
49 4. ans = sum(positive weighted vertex weight) - (max flow)
50 (Node-disjoint) Min DAG Path Cover (用最短路徑覆蓋所有點)
51 Node disjoint: 拆出來的路徑不能共用同一個點
52 將一個點 u 裂成 u_+ 和 u_- , 代表進入和出去
53 對於一條邊 (u, v) 建邊 $u_- \Rightarrow v_+$
54 1. $+$ 點們和 $-$ 點們形成一張二分圖
55 2. 最差的答案是 n , 代表每個點自己一個點就是一條路徑
56 3. 只要一組 (u_-, v_+) 匹配成功那對應到的答案恰好會 -1
57 $\Rightarrow$ ans = $n - \text{這張二分圖的最大匹配}$
58 General DAG Path Cover
59 跟 Node-disjoint 版本差在點可以被很多條路共用
60 建邊方式 Node-disjoint 差別在條件比較鬆
61 Node-disjoint: $u_- \Rightarrow v_+$ 只能在 (u, v) 有邊時建
62 General: $u_- \Rightarrow v_+$ 在 u 能走到 v 的時候就建
63 Dilworth Theorem
64 反鏈: 一些節點的集合, 滿足這些節點互相無法抵達
65 最大反鏈 = 最小 General DAG Path Cover
66 Min Cut reconstruction (after running max flow $s \rightarrow t$):
67 From s , BFS/DFS through residual edges with remaining
68 capacity > 0 , marking reached vertices as visited.
69 The cut set is every original edge (u, v) with u visited
70 and v not visited; its capacity sum equals the max flow.
71 Bipartite Matching reconstruction (after running max flow
72 on source $\rightarrow X \rightarrow Y \rightarrow$ sink model):
73 For each edge (x, y) between the X -side and Y -side, it is
74 part of the matching iff. its residual capacity is 0
75 (i.e. it is saturated).
76 Max/Min Flow with Lower Bound (Circulation Problem):
77 1. Construct super source S and super sink T .
78 2. For each edge (x, y, l, u) , connect $x \rightarrow y$ with capacity
79 $u - l$.
80 3. For each vertex v , let $\text{in}(v) = (\text{sum of incoming lower}$
81 $\text{bounds})$
82 $- (\text{sum of outgoing lower bounds})$.
83 4. If $\text{in}(v) > 0$, connect $S \rightarrow v$ with capacity $\text{in}(v)$;
84 otherwise connect $v \rightarrow T$ with capacity $-\text{in}(v)$.
85 To maximize: connect $t \rightarrow s$ with capacity inf (skip this
86 edge
87 for a pure circulation problem), let $f = \text{maxflow}(S, T)$.
88 If
89 $f \neq \text{sum of in}(v) \text{ over all in}(v) > 0$, no solution exists.

84 Otherwise $\text{maxflow}(s, t)$ (found after adding $t \rightarrow s$) is
85 the answer.
86 To minimize: let $f = \text{maxflow}(S, T)$ (without any s - t edge
87 yet).
88 Then connect $t \rightarrow s$ with capacity inf and let f' be the
89 extra
90 flow pushed from S to T . If $f + f' \neq \text{sum of in}(v) \text{ over}$
91 all
92 $\text{in}(v) > 0$, no solution exists. Otherwise f' is the
93 answer.
94 5. The flow on each original edge e is $l_e + f_e$, where f_e
95 is
96 e 's flow in the constructed graph.

9.2 Dinic (Flow Decomposition)

b8e775

```
1// Function: Max Flow + Flow Decomposition,  $O(V^2 E)$ 
2// init -> addEdge; vertices 0-based
3// >>> flow() := return max flow
4// >>> flow_decomposition() := return max flow + store
5// decomposition in flow.D
6struct Dinic{
7    static const int MXN=10000;
8    struct Edge{ int v,c,r,C; bool fw; };
9    int n,s,t,level[MXN]; vector<Edge> G[MXN];
10    void init(int _n,int _s,int _t){
11        n=_n; s=_s; t=_t;
12        for (int i=0; i<n; i++) G[i].clear();
13    }
14    void addEdge(int u,int v,int c){
15        G[u].push_back({v,c,(int)G[v].size(),c,true});
16        G[v].push_back({u,0,(int)G[u].size()-1,0,false});
17    }
18    bool BFS(){
19        for (int i=0; i<n; i++) level[i]=-1;
20        queue<int> que; que.push(s); level[s]=0;
21        while(!que.empty()){
22            int u=que.front(); que.pop();
23            for (auto &it:G[u]){
24                if(it.c>0&&level[it.v]==-1){
25                    level[it.v]=level[u]+1; que.push(it.v);
26                }
27            }
28        }
29        return level[t]!=-1;
30    }
31    int DFS(int u,int nf){
32        if(u==t) return nf;
33        int res=0;
34        for (auto &it:G[u]){
35            if(it.c>0&&level[it.v]==level[u]+1){
36                int tf=DFS(it.v,min(nf,it.c));
37                res+=tf; nf-=tf; it.c-=tf;
38                G[it.v][it.r].c+=tf;
39                if(nf==0) return res;
40            }
41        }
42        if(!res) level[u]=-1;
43        return res;
44    }
45    int flow(int res=0){
46        while(BFS()) res+=DFS(s,2147483647);
47        return res;
48    }
49    // reset: do nothing
50    vector<pair<int, vector<int>>> D; // (flow amount, [path
51    pl ... pk])
52    int flow_decomposition(){
53        int mxflow = flow();
54        vector<vector<Edge>> fG(n); // graph with forward edges
55        for (int u = 0; u < n; u++) {
56            for (auto &e : G[u]) {
57                if (e.fw && e.C - e.c > 0)
58                    fG[u].push_back({e.v, e.C - e.c, e.r, e.C, e.fw});
59            }
60        }
61        vector<int> vis(n, 0);
62        function<int(int, int)> dfs = [&](int u, int cur) {
63            if (u == t) {
64                D.back().second.push_back(u);
65                return cur;
66            }
67            vis[u] = 1;
68            for (auto &e : fG[u]) {
69                if (e.c > 0 && !vis[e.v]) {
70                    int ans = dfs(e.v, min(cur, e.c));
71                    if (ans > 0) {
72                        e.c -= ans;
73                        D.back().second.push_back(u);
74                        return ans;
75                    }
76                }
77            }
78            return 0;
79        };
80        D.clear();
81        int quota = mxflow;
82        while (quota > 0) {
83            D.emplace_back(0, vector<int>());
84            fill(vis.begin(), vis.end(), 0);
85            int f = dfs(s, 2147483647);
86            if (f == 0) break;
87            reverse(D.back().second.begin(),
88                D.back().second.end());
89        }
90    }
91};
```

```

74     D.back().first = f, quota -= f;
75 }
76 return mxflow; }
77 } flow;

```

9.3 ISAP

c13d55

```

1// Author: CRYPTOGRAPHER
2// 1-based: vertices are numbered 1 ~ n
3// 1. flow.init(n, s, t);
4// n = #vertices, s, t = source, sink
5// 2. flow.addEdge(u, v, c); // u, v in [1, n]
6// 3. call: int ans = flow.flow();
7// => ans = max flow value from s to t
8// Time: O(V^2 * E) worst case, usually much faster in practice
9static const int MAXV=50010;
10static const int INF =1000000;
11struct Maxflow{
12    struct Edge{
13        int v, c, r;
14        Edge(int _v, int _c, int _r):v(_v),c(_c),r(_r){}
15    };
16    int s, t; vector<Edge> G[MAXV];
17    int iter[MAXV], d[MAXV], gap[MAXV], tot;
18    void init(int n, int _s, int _t){
19        tot=n, s=_s, t=_t;
20        for(int i=1; i<=tot; i++){
21            G[i].clear(); iter[i]=d[i]=gap[i]=0;
22        }
23    }
24    void addEdge(int u, int v, int c){
25        G[u].push_back(Edge(v, c, SZ(G[v])));
26        G[v].push_back(Edge(u, 0, SZ(G[u])-1));
27    }
28    int DFS(int p, int flow){
29        if(p==t) return flow;
30        for(int &i=iter[p]; i<SZ(G[p]); i++){
31            Edge &e=G[p][i];
32            if(e.c>0&&d[p]==d[e.v]+1){
33                int f=DFS(e.v, min(flow, e.c));
34                if(f){ e.c-=f; G[e.v][e.r].c+=f; return f; }
35            }
36        }
37        if(--gap[d[p]]==0) d[s]=tot;
38        else{ d[p]++; iter[p]=0; ++gap[d[p]]; }
39        return 0;
40    }
41    int flow(){
42        int res=0;
43        for(res=0, gap[0]=tot; d[s]<tot; res+=DFS(s, INF));
44        return res;
45    }
46    void reset(){
47        for(int i=1; i<=tot; i++) iter[i]=d[i]=gap[i]=0;
48    }
49} flow;

```

9.4 Bounded Max Flow

aaf8c3

```

1// Author: CRYPTOGRAPHER
2// Max flow with lower/upper bound on edges (source-sink version)
3// <!-- 1-based: original vertices are numbered 1 ~ n.
4// Super source, sink: n+1, n+2 respectively.
5// <!-- dependency: ISAP.cpp
6// 1. n = #vertices (1 ~ n), m = #edges
7// s, t = original source, sink (both in [1, n])
8// 2. l[i], r[i] := edge i goes from l[i] -> r[i] (l[i], r[i] in [1, n])
9// 3. a[i], b[i] := flow on edge i must lie in [a[i], b[i]]
10// 4. int ans = solve(n, m, s, t);
11// => ans == -1 : no feasible flow exists
12// => ans : feasible max flow value
13// <!-- N, M must be large enough for original graph + 2 super nodes
14// Time: O(V^2 E), Space: O(V + E)
15int in[N], out[N], l[M], r[M], a[M], b[M];
16int solve(int n, int m, int s, int t){
17    flow.init(n+2, n+1, n+2); // super source = n+1, super sink = n+2
18    for(int i = 0; i < m; i++){
19        in[r[i]] += a[i]; out[l[i]] += a[i];
20        flow.addEdge(l[i], r[i], b[i] - a[i]);
21        // flow from l[i] to r[i] must lie in [a[i], b[i]]
22    }
23    int nd = 0;
24    for(int i = 1; i <= n; i++){
25        if(in[i] < out[i]){
26            flow.addEdge(i, flow.t, out[i] - in[i]);
27            nd += out[i] - in[i];
28        }
29    }
30    return nd;
31}

```

```

29     if(out[i] < in[i])
30         flow.addEdge(flow.s, i, in[i] - out[i]);
31 }
32 flow.addEdge(t, s, INF); // original sink -> source
33 if(flow.flow() != nd) return -1; // infeasible
34 int ans = flow.G[s].back().c; // t->s edge's current flow = feasible flow s->t
35 flow.G[s].back().c = flow.G[t].back().c = 0;
36 for(size_t i = 0; i < flow.G[flow.s].size(); i++){
37     Maxflow::Edge &e = flow.G[flow.s][i];
38     flow.G[flow.s][i].c = 0; flow.G[e.v][e.r].c = 0;
39 }
40 for(size_t i = 0; i < flow.G[flow.t].size(); i++){
41     Maxflow::Edge &e = flow.G[flow.t][i];
42     flow.G[flow.t][i].c = 0; flow.G[e.v][e.r].c = 0;
43 }
44 flow.addEdge(flow.s, s, INF); flow.addEdge(t, flow.t, INF);
45 flow.reset(); // keeps G[] intact, only resets search state
46 return ans + flow.flow();
47 }

```

9.5 MCMF

472be6

```

1// Author: CRYPTOGRAPHER
2// MCMF (supports negative edges without negative cycles)
3// <!-- 1-based: vertices are numbered 1 ~ n.
4// 1. MCMF.init(n); // n = #vertices (1 ~ n)
5// 2. MCMF.add(u, v, cap, cost);
6// 3. auto [max_flow, min_cost] = MCMF.flow(s, t); // s, t in [1, n]
7// Time: O(F * E), Space: O(V + E)
8typedef int Tcost;
9const int MAXV = 20010;
10const int INFf = 1000000;
11const Tcost INFc = 1e9;
12struct MCMF {
13    struct Edge{
14        int v, cap;
15        Tcost w;
16        int rev;
17        bool fw;
18        Edge(){}
19        Edge(int t2, int t3, Tcost t4, int t5, bool t6)
20            : v(t2), cap(t3), w(t4), rev(t5), fw(t6) {}
21    };
22    int V, s, t;
23    vector<Edge> G[MAXV];
24    void init(int n){
25        V = n;
26        for(int i = 0; i <= V; i++) G[i].clear();
27    }
28    void add(int a, int b, int cap, Tcost w){
29        G[a].push_back(Edge(b, cap, w, (int)G[b].size(), true));
30        G[b].push_back(Edge(a, 0, -w, (int)G[a].size()-1, false));
31    }
32    Tcost d[MAXV];
33    int id[MAXV], mom[MAXV];
34    bool inqu[MAXV];
35    queue<int> q;
36    pair<int, Tcost> flow(int _s, int _t){
37        s = _s, t = _t;
38        int mxf = 0, Tcost mnc = 0;
39        while(1){
40            fill(d, d+1+V, INFc); // need to use type cast
41            fill(inqu, inqu+1+V, 0);
42            fill(mom, mom+1+V, -1);
43            mom[s] = s;
44            d[s] = 0;
45            q.push(s); inqu[s] = 1;
46            while(q.size()){
47                int u = q.front(); q.pop();
48                inqu[u] = 0;
49                for(int i = 0; i < (int) G[u].size(); i++){
50                    Edge &e = G[u][i];
51                    int v = e.v;
52                    if(e.cap > 0 && d[v] > d[u]+e.w){
53                        d[v] = d[u]+e.w;
54                        mom[v] = u;
55                        id[v] = i;
56                        if(!inqu[v]) q.push(v), inqu[v] = 1;
57                    }
58                }
59            }
60            if(mom[t] == -1) break;
61            int df = INFf;
62            for(int u = t; u != s; u = mom[u])
63                df = min(df, G[mom[u]][id[u]].cap);
64            for(int u = t; u != s; u = mom[u]){

```

```

65     Edge &e = G[mom[u]][id[u]];
66     e.cap -= df;
67     G[e.v][e.rev].cap += df;
68 }
69 mxf += df;
70 mnc += df*d[t];
71 }
72 return make_pair(mxf, mnc);
73 }
74 };

```

9.6 Push-Relabel

fae237

```

1// Author: Simon Lindholm (kactl)
2// 0-based: vertices are numbered 0 ~ n-1
3// 1. PushRelabel pr(n); // n = #vertices
4// 2. pr.addEdge(u, v, c); // u, v in [0, n-1]
5// 3. ll ans = pr.calc(s, t);
6// => ans = max flow value from s to t
7// To obtain actual flow:
8// for (int u = 0; u < n; u++)
9//     for (auto& e : pr.g[u])
10//         if (e.f > 0) => (u, e.dest, e.f)
11// Time:  $O(V^2 * \sqrt{E})$ , better on dense graph
12struct PushRelabel {
13    struct Edge { int dest, back; ll f, c; };
14    vector<vector<Edge>> g;
15    vector<ll> ec;
16    vector<Edge*> cur;
17    vector<vi> hs; vi H;
18    PushRelabel(int n) : g(n), ec(n), cur(n), hs(2*n), H(n) {}
19    void addEdge(int s, int t, ll cap, ll rcap=0) {
20        if (s == t) return;
21        g[s].push_back({t, sz(g[t]), 0, cap});
22        g[t].push_back({s, sz(g[s])-1, 0, rcap});
23    }
24    void addFlow(Edge& e, ll f) {
25        Edge &back = g[e.dest][e.back];
26        if (!ec[e.dest] && f) hs[H[e.dest]].push_back(e.dest);
27        e.f += f; e.c -= f; ec[e.dest] += f;
28        back.f -= f; back.c += f; ec[back.dest] -= f;
29    }
30    ll calc(int s, int t) {
31        int v = sz(g); H[s] = v; ec[t] = 1;
32        vi co(2*v); co[0] = v-1;
33        rep(i, 0, v) cur[i] = g[i].data();
34        for (Edge& e : g[s]) addFlow(e, e.c);
35        for (int hi = 0; ; ) {
36            while (hs[hi].empty()) if (!hi--) return -ec[s];
37            int u = hs[hi].back(); hs[hi].pop_back();
38            while (ec[u] > 0) // discharge u
39                if (cur[u] == g[u].data() + sz(g[u])) {
40                    H[u] = 1e9;
41                    for (Edge& e : g[u]) if (e.c && H[u] >
42                        H[e.dest]+1)
43                        H[u] = H[e.dest]+1, cur[u] = &e;
44                    if (++co[H[u]], !--co[hi] && hi < v)
45                        rep(i, 0, v) if (hi < H[i] && H[i] < v)
46                            --co[H[i]], H[i] = v + 1;
47                    hi = H[u];
48                } else if (cur[u]->c && H[u] == H[cur[u]->dest]+1)
49                    addFlow(*cur[u], min(ec[u], cur[u]->c));
50                else ++cur[u];
51        }
52    bool leftOfMinCut(int a) { return H[a] >= sz(g); }
53};

```

9.7 Gomory-Hu Tree

88b014

```

1// Author: chilli, Takanori MAEHARA (kactl)
2// <!-- Dependency: PushRelabel.cpp
3// Given a list of edges representing an undirected flow
graph,
4// returns edges of the Gomory-Hu tree.
5// maxflow / mincut of (u, v) => min edge from u to v on
Gomory-Hu tree
6// Time:  $O(V) * O(\text{PushRelabel})$ 
7typedef array<ll, 3> Edge; // (u, v, w)
8vector<Edge> gomoryHu(int N, vector<Edge> ed) {
9    vector<Edge> tree;
10    vi par(N);
11    rep(i, 1, N) {
12        PushRelabel D(N); // Dinic also works
13        for (Edge t : ed) D.addEdge(t[0], t[1], t[2], t[2]);
14        tree.push_back({i, par[i], D.calc(i, par[i])});
15        rep(j, i+1, N)
16            if (par[j] == par[i] && D.leftOfMinCut(j)) par[j] = i;
17    }
18    return tree;
19}

```

9.8 Global Min Cut

a040ee

```

1// Author: ckiseki
2// 1-based: vertices are numbered 1 ~ n
3// 1. vector<vector<ll>> G(n+1, vector<ll>(n+1, 0));
4// 2. add_edge(G, u, v, c); // add undirected edge u-v with
weight c, u, v in [1, n]
5// 3. ll ans = mincut(G, n); // n = #vertices
6// => ans = global min cut value
7// Time:  $O(V^3)$ 
8void add_edge(auto &w, int u, int v, int c) {
9    w[u][v] += c; w[v][u] += c; }
10auto phase(const auto &w, int n, vector<int> id) {
11    vector<ll> g(n+1); int s = -1, t = -1;
12    while (!id.empty()) {
13        int c = -1;
14        for (int i : id) if (c == -1 || g[i] > g[c]) c = i;
15        s = t; t = c;
16        id.erase(ranges::find(id, c));
17        for (int i : id) g[i] += w[c][i];
18    } return tuple{s, t, g[t]};
19}
20ll mincut(auto w, int n) {
21    ll cut = numeric_limits<ll>::max();
22    vector<int> id(n); iota(all(id), 1);
23    for (int i = 0; i < n - 1; ++i) {
24        auto [s, t, gt] = phase(w, n, id);
25        id.erase(ranges::find(id, t));
26        cut = min(cut, gt);
27        for (int j = 1; j <= n; ++j)
28            w[s][j] += w[t][j], w[j][s] += w[j][t];
29    } return cut;
30}

```

10 String

10.1 Rolling Hash

c15659

```

1// Author: ckiseki (Modified by Gino)
2// Usage: RH<Sigma, Mod> Hs(s);
3// If no modifications needed, replace BIT with prefix sum
4template <ll P = 127, ll Q = 1051762951>
5class RH {
6    int n; vector<ll> p, inv, d, bit;
7    ll add(ll a, ll b) { return a+b >= Q ? a+b-Q : a+b; }
8    ll sub(ll a, ll b) { return a-b < 0 ? a-b+Q : a-b; }
9    ll mul(ll a, ll b) { return (__int128)a * b % Q; }
10    ll pw(ll a, ll x) {
11        ll r = 1; for (; x; a = mul(a, a), x >>= 1)
12            if (x & 1) r = mul(r, a);
13        return r;
14    }
15    void bit_add(int i, ll x) {
16        for (; i <= n; i += i&-i) bit[i] = add(bit[i], x); }
17    ll bit_qry(int i) {
18        ll s = 0; for (; i; i -= i&-i) s = add(s, bit[i]);
19    }
20public:
21    RH(const auto &s) : n(s.size()),
22        p(n+1, 1), inv(n+1, 1), d(n+1), bit(n+1) {
23        ll iv = pw(P, Q - 2);
24        for (int i = 1; i <= n; i++) {
25            p[i] = mul(p[i-1], P); inv[i] = mul(inv[i-1], iv);
26            d[i] = mul(s[i-1], p[i]); bit_add(i, d[i]);
27        }
28        void update(int i, char c) {
29            ll x = mul(c, p[i]); bit_add(i, sub(x, d[i])); d[i] = x; }
30        ll query(int l, int r) {
31            return mul(sub(bit_qry(r), bit_qry(l-1)), inv[l]); }
32};

```

10.2 KMP

376cdf

```

1// Author: Gino
2vector<int> kmp(auto s){ int n=s.size(); vector<int> f(n,0);
3    for (int i = 1, ptr = 0; i < n; i++) {
4        while (ptr && s[i] != s[ptr]) ptr = f[ptr-1];
5        if (s[i] == s[ptr]) ptr++; f[i] = ptr;
6    } return f;
7}

```

10.3 Z Value

d5b3b9

```

1// Author: std_abs
2vector<int> Z(auto s){ int n=s.size(); vector<int> Z(n);
3    for (int i = 0, l = 0, r = 0; i < n; ++i) {
4        Z[i] = max(min(Z[i-l], r-i), 0);
5        while (i+Z[i] < n && s[Z[i]] == s[i+Z[i]])
6            l = i, r = i+Z[i], Z[i]++;
7    } return Z;
8}

```

10.4 Manacher

193b08

```

1// Author: std_abs
2// return array Z (length == 2N - 1)

```

```

3 // Example: s = "aaaa"
4 //   a       a       a       a
5 // Z_0 Z_1 Z_2 Z_3 Z_4 Z_5 Z_6
6 // 1   2   3   4   3   2   1
7 // The corresponding palindrome s[l..r]:
8 // l = (i - Z[i] + 1) / 2
9 // r = (i + Z[i] - 1) / 2
10 vector<int> manacher(auto tmp) {
11     vector<int> s(1, -1);
12     for (auto c : tmp) s.push_back(c), s.push_back(-1);
13     int l = 0, r = 0, n = (int)s.size();
14     vector<int> Z(n);
15     for (int i = 0; i < n; ++i) {
16         Z[i] = r > i ? min(Z[2 * l - i], r - i) : 1;
17         while (i - Z[i] >= 0 && i + Z[i] < n &&
18             s[i + Z[i]] == s[i - Z[i]]) Z[i]++;
19         if (Z[i] + i > r) l = i, r = Z[i] + i;
20     }
21     for (int i = 0; i < n; ++i)
22         Z[i] = (Z[i] - (i & 1)) / 2 * 2 + (i & 1);
23     return vector<int>(Z.begin() + 1, Z.end() - 1);
24 }

```

10.5 Suffix Array + LCP

c1df5b

```

1 // Author: std_abs
2 // Tested @yosupo, N <= 5e5, 123ms
3 const int N = 5e5 + 10;
4 int sa[N], tmp[2][N], c[N], rk[N], lcp[N];
5 void buildSA(string s) {
6     int *x = tmp[0], *y = tmp[1], m = 256, n = s.size();
7     for (int i = 0; i < m; ++i) c[i] = 0;
8     for (int i = 0; i < n; ++i) c[x[i]] = s[i]++;
9     for (int i = 1; i < m; ++i) c[i] += c[i - 1];
10    for (int i = n - 1; ~i; --i) sa[--c[x[i]]] = i;
11    for (int k = 1; k < n; k <= 1) {
12        for (int i = 0; i < m; ++i) c[i] = 0;
13        for (int i = 0; i < n; ++i) c[x[i]]++;
14        for (int i = 1; i < m; ++i) c[i] += c[i - 1];
15        int p = 0;
16        for (int i = n - k; i < n; ++i) y[p++] = i;
17        for (int i = 0; i < n; ++i) if (sa[i] >= k)
18            y[p++] = sa[i] - k;
19        for (int i = n - 1; ~i; --i)
20            sa[--c[x[y[i]]]] = y[i];
21        y[sa[0]] = p = 0;
22        for (int i = 1; i < n; ++i) {
23            int a = sa[i], b = sa[i - 1];
24            p += !(x[a] == x[b] && a + k < n && b + k < n && x[a + k] == x[b + k]);
25            y[sa[i]] = p;
26        }
27        if (n == p + 1) break;
28        swap(x, y), m = p + 1;
29    }
30    void buildLCP(string s) {
31        // lcp[i] = LCP(sa[i - 1], sa[i])
32        // lcp(i, j) = query_lcp_min [rk[i] + 1, rk[j] + 1)
33        int n = s.length(), x = 0;
34        for (int i = 0; i < n; ++i) rk[sa[i]] = i;
35        for (int i = 0; i < n; ++i) {
36            if (!rk[i]) lcp[rk[i]] = 0;
37            else { if (x) --x;
38                int p = sa[rk[i] - 1];
39                while (x + i < n && x + p < n && s[x + i] == s[x + p]) x++;
40                lcp[rk[i]] = x;
41            }
42        }
43    }

```

10.6 Suffix Automaton

10f751

```

1 // Author: std_abs
2 // state (i.e. node) -> all substr with the same endpos
3 // those substrs' length in range [len(link) + 1, len]
4 // state i's endpos set -> union of pos[i] over the subtree
5 // of i in the suffix link tree
6 // link[i] -> longest suffix with different endpos set
7 // (suffix link tree edge)
8 // len[i] -> length longest suffix of state i
9 // pos[i] -> an example end position of state i (1-based)
10 // cnt[i] -> size of endpos set of state i, built by
11 // build_cnt() (tree DP)
12 const int N = 5e5 + 10, C = 26;
13 struct SAM {
14     int ch[2*N][C], len[2*N], link[2*N], pos[2*N], cnt[2*N], _id;
15     SAM () { reset(); }
16     void reset() { _id = 0, newnode(), link[0] = -1; }
17     int newnode() {
18         fill_n(ch[_id], C, 0);
19         len[_id] = link[_id] = pos[_id] = cnt[_id] = 0;
20         return _id++;
21     }
22     void build(string s) {
23         int last = 0; for (int i = 0; i < (int)s.size(); i++) {

```

```

21         char c = s[i]; int cur = newnode();
22         len[cur] = len[last] + 1, pos[cur] = i + 1;
23         int p = last;
24         while (~p && !ch[p][c - 'a'])
25             ch[p][c - 'a'] = cur, p = link[p];
26         if (p == -1) link[cur] = 0;
27         else { // conflict: p --> q, p --> cur
28             int q = ch[p][c - 'a'];
29             if (len[p] + 1 == len[q]) { // q is suffix of cur
30                 link[cur] = q;
31             } else { // we need auxiliary state
32                 int nxt = newnode();
33                 len[nxt] = len[p] + 1, link[nxt] = link[q];
34                 pos[nxt] = 0;
35                 for (int j = 0; j < C; j++)
36                     ch[nxt][j] = ch[q][j];
37                 while (~p && ch[p][c - 'a'] == q)
38                     ch[p][c - 'a'] = nxt, p = link[p];
39                 link[q] = link[cur] = nxt;
40             }
41             cnt[cur]++, last = cur;
42         }
43     } sam;
44 // void build_cnt() {
45 //     vector<int> p(_id); iota(all(p), 0); sort(all(p),
46 //         [&](int i, int j){ return len[i] > len[j]; });
47 //     for (int i = 0; i < _id; ++i) if (link[p[i]] != -1)
48 //         cnt[link[p[i]]] += cnt[p[i]];
49 // }
50 // bool match(string s) {
51 //     int p = 0; for (auto& c : s) {
52 //         if (!ch[p][c - 'a']) return false;
53 //         p = ch[p][c - 'a'];
54 //     } return true; }

```

10.7 Minimum Rotation

bb235f

```

1 // Author: std_abs
2 string rotate(auto s) { int n=s.size(), i=0, j=1;
3     string t = s + s;
4     while (i < n && j < n) {
5         int k = 0; while (k < n && t[i + k] == t[j + k]) ++k;
6         if (t[i + k] <= t[j + k]) j += k + 1; else i += k + 1;
7         if (i == j) ++j;
8     } return t.substr((i < n ? i : j), n);
9 }

```

10.8 AC Automaton

285968

```

1 // Author: std_abs (slightly modified by Gino)
2 // Recap: fail[s] = s 在 trie 上 (也就是某個 pattern 的前綴
3 // 的最長 proper 後綴
4 // N := sum(length of all patterns) + 1
5 // 1. ac.insert(pat) -> end-node id recorded in ac.pid
6 // 2. ac.build_fail()
7 // 3. run text: ptr = to[ptr][c-'a'] each char;
8 // accumulate on your own arrays
9 // - pull: rep(i ac.order_cnt-1 ~ 0) val[fail[x]] += val[x]
10 // - push: rep(i 0 ~ ac.order_cnt-1) val[x] += val[fail[x]]
11 // Tested @yosupo, N <= 1e6, 323ms on building AC
12 const int N = 1e6 + 5, C = 26;
13 struct AC {
14     int ch[N][C], to[N][C], fail[N], _id, order[N], order_cnt;
15     int np; vector<int> pid; // pattern ID on trie
16     // order[r] := which trie node has BFS order r
17     // fail link tree: (parent) fail[i] <-- i (child)
18     void reset() { _id = np = order_cnt = 0, pid.clear(),
19         newnode(); }
20     int newnode() {
21         fill_n(ch[_id], C, 0), fill_n(to[_id], C, 0);
22         fail[_id] = 0; return _id++;
23     }
24     AC () { reset(); }
25     void insert(string s) {
26         int ptr = 0; for (char c : s) {
27             if (!ch[ptr][c - 'a']) ch[ptr][c - 'a'] = newnode();
28             ptr = ch[ptr][c - 'a'];
29         } np++; pid.emplace_back(ptr);
30     }
31     void build_fail() {
32         queue<int> q; order_cnt = 0;
33         for (int i = 0; i < C; ++i) if (ch[0][i])
34             q.push(ch[0][i]), to[0][i] = ch[0][i];
35         while (!q.empty()) {
36             int u = q.front(); q.pop(); order[order_cnt++] = u;
37             for (int i = 0; i < C; ++i) {
38                 if (!ch[u][i]) to[u][i] = to[fail[u]][i];
39                 else { int v = ch[u][i], k = fail[u];
40                     while (k && !ch[k][i]) k = fail[k];
41                     if (ch[k][i]) k = ch[k][i];
42                     fail[v] = k, to[u][i] = v;

```

```

42         q.push(v);
43     } } } }
44 } ac;

```

10.9 AC Automaton - Dict Links

a62cfa

```

1// Author: Gino, paste this in `struct AC {...}`
2// 3 Modifications to the original AC Automaton:
3// int np; vector<int> pid; bool is_pattern[N];
4// fail[id] = 0, is_pattern[id] = false; return id++;
5// np++; pid.emplace_back(ptr); is_pattern[ptr] = true;
6int dict[N];
7void build_dict() { // call this after build_fail()!
8    for (int i = 0; i < order_cnt; i++) {
9        int u = order[i], f = fail[u];
10        dict[u] = is_pattern[f] ? f : dict[f];
11    }

```

10.10 AC Automaton - Counting Patterns

58fd32

```

1// Author: Gino, paste this in `struct AC {...}`
2ll val[N];
3void count_patterns(string& text, vector<string>& patterns){
4    for (auto& p : patterns) insert(p); build_fail();
5    ranges::fill(val, 0LL);
6    int ptr = 0; for (auto& c : text) {
7        ptr = to[ptr][c - 'a']; val[ptr]++;
8    }
9    for (int x : span(order, order_cnt) | views::reverse)
10        val[fail[x]] += val[x];
11    for (auto& i : pid) cout << val[i] << endl;
12}

```

10.11 AC Automaton - Pattern Position

輸出每個 pattern 在 text 中第一次出現的位置，若不存在則輸出 -1。
走 AC 自動機時 if (val[ptr] == -1) val[ptr] = i; 接著 pull DP
if (val[x] == -1) continue;
if (val[fail[x]] == -1) val[fail[x]] = val[x];
else val[fail[x]] = min(val[fail[x]], val[x]);

11 Geometry

11.1 Template

acaf6b

```

1using T = long long; // or double
2const double eps = 1e-8;
3int sgn(T x) { return (x > eps) - (x < -eps); }
4struct Pt {
5    T x = 0, y = 0;
6    Pt operator+(Pt a) const { return {x + a.x, y + a.y}; }
7    Pt operator-(Pt a) const { return {x - a.x, y - a.y}; }
8    Pt operator*(T k) const { return {x * k, y * k}; }
9    Pt operator/(T k) const { return {x / k, y / k}; }
10    T operator*(Pt a) const { return x * a.x + y * a.y; }
11    T operator^(Pt a) const { return x * a.y - y * a.x; }
12    bool operator<(Pt a) const {
13        return tie(x, y) < tie(a.x, a.y); }
14    bool operator==(Pt a) const {
15        return !sgn(x - a.x) && !sgn(y - a.y); }
16    friend ostream& operator<<(ostream& o, Pt a) {
17        return o << "(" << a.x << ", " << a.y << ")"; }
18};
19struct Line { Pt a, b; }; // a -> b
20struct Cir { Pt o; double r; };
21T abs2(Pt a) { return a * a; }
22double abs(Pt a) { return sqrt(abs2(a)); }
23int ori(Pt o, Pt a, Pt b) // 1: CCW, -1: CW, 0: collinear
24{ return sgn((a - o) ^ (b - o)); }
25bool onseg(Pt p, Pt a, Pt b) // p on segment ab?
26{ return !ori(p, a, b) && sgn((a - p) * (b - p)) <= 0; }

```

11.2 Basic

8507af

```

1int ud(Pt a) // 0: upper half (incl. +x axis), 1: lower
2{ return !sgn(a.y) ? sgn(a.x) < 0 : a.y < 0; }
3bool cmp(Pt a, Pt b) // polar angle in [0, 2PI)
4{ return ud(a) == ud(b) ? sgn(a ^ b) > 0 : ud(a) < ud(b); }
5bool sameVec(Pt a, Pt b, int d)//d=0: parallel, d=1: same dir
6{ return !sgn(a ^ b) && sgn(a * b) > d * 2 - 2; }
7bool sameVec(Line a, Line b, int d)
8{ return sameVec(a.b - a.a, b.b - b.a, d); }
9Pt rot90(Pt a) { return {-a.y, a.x}; } // CCW
10Pt ref(Pt a) { return ud(a) ? Pt(-a.x, -a.y) : a; }
11T dbarea(vector<Pt>& p) { // doubled signed area, CCW > 0
12    T res = 0; for (int i = 0; i < sz(p); i++)
13        res += p[i] ^ p[(i+1) % sz(p)];
14    return res; }
15// ---- T = double ----
16const double PI = acos(-1);
17double normalize(double x) { // to [0, 2pi)
18    while (x < -eps) x += PI * 2;
19    while (x > PI * 2 + eps) x -= PI * 2;
20    return x; }
21double theta(Pt a) { return normalize(atan2(a.y, a.x)); }
22Pt unit(Pt a) { return a / abs(a); }
23Pt rot(Pt a, double o) { // CCW

```

```

24    double c = cos(o), s = sin(o);
25    return Pt(c * a.x - s * a.y, s * a.x + c * a.y); }
26Pt projVec(Pt a, Pt b, Pt c) // vector ac proj to ab
27{ return (b - a) * ((c - a) * (b - a)) / abs2(b - a); }
28Pt projPt(Pt a, Pt b, Pt c) // point c proj to ab
29{ return projVec(a, b, c) + a; }

```

11.3 Line / Segment Intersections

7e8b65

```

1// m=0: segment, m=1: ray from l.a to l.b, m=2: line
2bool banana(Line ls, int ms, Line lt, int mt, int strict) {
3    auto on = [&](Line l, int m, Pt p) {
4        if (ori(l.a, l.b, p) != 0) return false;
5        if (m && abs2(l.a - p) > abs2(l.b - p)) return true;
6        return m == 2 || sgn((p - l.a) * (p - l.b)) <= -strict;
7    };
8    if (sameVec(ls, lt, 0)) {
9        return on(ls, ms, lt.a) || on(ls, ms, lt.b) ||
10            on(lt, mt, ls.a) || on(lt, mt, ls.b);
11    }
12    auto good = [&](Line l, int m, Line o) {
13        if (m && abs((l.a - o.a) ^ (l.a - o.b)) >
14            abs((l.b - o.a) ^ (l.b - o.b))) return true;
15        return m == 2 ||
16            ori(l.a, o.a, o.b) * ori(l.b, o.a, o.b) == -1;
17    };
18    if (good(ls, ms, lt) && good(lt, mt, ls)) return 1;
19    if (!strict) {
20        if (mt != 2 && on(ls, ms, lt.a)) return 1;
21        if (mt == 0 && on(ls, ms, lt.b)) return 1;
22        if (ms != 2 && on(lt, mt, ls.a)) return 1;
23        if (ms == 0 && on(lt, mt, ls.b)) return 1;
24    }
25    return 0;
26}
27// becareful when two lines are parallel
28auto bananaPoint(Line a, Line b) {
29    auto abc = (a.b - a.a) ^ (b.a - a.a);
30    auto abd = (a.b - a.a) ^ (b.b - a.a);
31    return make_pair(b.b * abc - b.a * abd, abc - abd);
32}

```

11.4 Point-Line / Segment Distance

8b23e4

```

1// T = double
2double pointLineDist(Pt p, Line L)
3{ return fabs(((L.b - L.a) ^ (p - L.a)) / abs(L.b - L.a)); }
4double pointSegDist(Pt p, Pt a, Pt b) {
5    if (a == b) return abs(p - a);
6    if (sgn((b - a) * (p - a)) >= 0 &&
7        sgn((a - b) * (p - b)) >= 0)
8        return pointLineDist(p, {a, b});
9    return min(abs(p - a), abs(p - b));
10}

```

11.5 Sort

63db4f

```

1// Dependency: cmp(), btwAngle()
2// cmp in Basic: polar angle sort
3// all points are on line ab. closer to a: front
4bool cmpLine(Pt s, Pt t, Pt a, Pt b) {
5    Pt v = a - b;
6    if (sgn(v.x)) return sgn(s.x - t.x) == sgn(v.x);
7    return sgn(s.y - t.y) == sgn(v.y);
8}
9// intersect points polar angle sort, deno: positive
10bool cmpFractionPolar(pair<Pt, ll> o,
11    pair<Pt, ll> s, pair<Pt, ll> t) {
12    Pt u = s.first * o.second - o.first * s.second;
13    Pt v = t.first * o.second - o.first * t.second;
14    return cmp(u, v);
15}
16struct Seg {
17    Pt a, b; // a.x < b.x
18    bool operator<(const Seg& o) const {
19        if (a == o.a) return ori(o.b, a, b) == 1;
20        if (a.x <= o.a.x) return ori(o.a, a, b) == 1;
21        return ori(a, o.a, o.b) == -1;
22    };
23}
24struct PolarSeg {
25    Pt a, b; // ori(Pt(0, 0), a, b) > 0
26    bool operator<(const PolarSeg& o) const {
27        if (a == o.a) return ori(o.b, a, b) == -1;
28        if (btwAngle(Pt(0, 0), a, b, o.a, 0))
29            return ori(o.a, a, b) == -1;
30        return ori(a, o.a, o.b) == 1;
31    };
32}
33struct Arc {
34    // contain(a, b): circle a inside circle b
35    Cir c;
36    int id, s; // 0 -> up, 1 -> down
37    bool operator<(const Arc& b) const {
38        if (id == b.id) return s < b.s;

```

```

37 if (contain(c, b.c)) return b.s == 1;
38 if (contain(b.c, c)) return s == 0;
39 if (c.o.y == b.c.o.y) return id < b.id;
40 return c.o.y > b.c.o.y;
41 } };
```

11.6 Convex Hull

37fe2b

```

1 auto convexHull(vector<Pt> pts) {
2   sort(all(pts)); vector<Pt> ans = {pts[0]};
3   for (int t = 0; t < 2; t++, reverse(all(pts))) {
4     for (int i = 1, m = sz(ans); i < sz(pts); i++) {
5       while (sz(ans) > m &&
6             ori(ans[sz(ans) - 2], ans.back(), pts[i]) <= 0)
7         ans.pop_back();
8     ans.pb(pts[i]); } }
9   if (sz(ans) > 1) ans.pop_back(); return ans; }
```

11.7 Triangle Centers

9c22fc

```

1 // T = double
2 Pt circenter(Pt a, Pt b, Pt c) { // r = abs(o - a)
3   b = b - a, c = c - a; double m = 2 * (b^c);
4   Pt o = {(abs2(b) * c.y - abs2(c) * b.y) / m,
5           (abs2(c) * b.x - abs2(b) * c.x) / m};
6   return o + a;
7 }
8 Pt incenter(Pt a, Pt b, Pt c) { // r = 2 * area / s
9   double x = abs(b - c), y = abs(c - a);
10  double z = abs(a - b), s = x + y + z;
11  return (a*x + b*y + c*z) / s;
12 }
13 Pt centroid(Pt a, Pt b, Pt c) { return (a + b + c) / 3; }
14 Pt orthocenter(Pt a, Pt b, Pt c) {
15   return centroid(a, b, c) * 3 - circenter(a, b, c) * 2;
16 }
```

11.8 Point Inside

109f6b

```

1 // get edge index: check (0, a), (0, b) first
2 // then after binary search, check (a, b)
3 bool inConvex(vector<Pt>& C, Pt p, bool strict = true) {
4   // only works when no three points are collinear
5   int a = 1, b = sz(C) - 1, r = !strict;
6   if (sz(C) == 0) return false;
7   if (sz(C) < 3) return r && onseg(p, C[0], C.back());
8   if (ori(C[0], C[a], C[b]) > 0) swap(a, b);
9   if (ori(C[0], C[a], p) >= r ||
10      ori(C[0], C[b], p) <= -r) return false;
11   while (abs(a - b) > 1) {
12     int c = (a + b) / 2;
13     (ori(C[0], C[c], p) > 0 ? b : a) = c;
14   }
15   return ori(C[a], C[b], p) < r;
16 }
17 // -1: out, 0: edge, 1: in
18 int inPoly(vector<Pt> poly, Pt o, int strict) {
19   int cnt = 0;
20   for (int i = 0; i < sz(poly); i++) {
21     Pt a = poly[i], b = poly[(i + 1) % sz(poly)];
22     if (onseg(o, a, b)) return !strict;
23     cnt ^= ((o.y < a.y) - (o.y < b.y)) * ori(o, a, b) > 0;
24   }
25   return cnt ? 1 : -1;
26 }
27 // relation of q with circumcircle; T = long long
28 bool inCC(array<Pt, 3> p, Pt q) {
29   __int128 det = 0;
30   for (int i = 0; i < 3; i++)
31     det += __int128(abs2(p[i]) - abs2(q)) *
32           ((p[(i + 1) % 3] - q) ^ (p[(i + 2) % 3] - q));
33   return det > 0; // in: >0, on: =0, out: <0
34 }
```

11.9 Point In Triangle

144fc0

```

1 // number of p with a < p < b and ori(p, a, b) < 0
2 int under(Pt a, Pt b) {}
3 // number of points with a < p < b and ori(p, a, b) = 0
4 int edge(Pt a, Pt b) {}
5 // check if this number is calculated
6 bool check(Pt p) {}
7 // number of points that strictly inside the triangle
8 int inTri(array<Pt, 3> arr) {
9   sort(all(arr)); auto [a, b, c] = arr; intx = ori(b, a, c);
10  if (x == 0) return 0;
11  if (x == 1) return under(a, b) + under(b, c) -
12    under(a, c) - edge(a, c);
13  return under(a, c) - under(a, b) -
14    under(b, c) - edge(a, b) - edge(b, c) - check(b);
15 }
```

11.10 Vector In Polygon

1b2dce

```

1 // ori(a, b, c) >= 0, valid: "strict" angle from a-b to a-c
2 bool btwAngle(Pt a, Pt b, Pt c, Pt p, int strict) {
```

```

3   return ori(a, b, p) >= strict &&
4     ori(a, p, c) >= strict;
5 }
6 // whether vector{cur, p} is in order prv, cur, nxt
7 bool inside(Pt prv, Pt cur, Pt nxt, Pt p, int strict) {
8   if (ori(cur, nxt, prv) >= 0)
9     return btwAngle(cur, nxt, prv, p, strict);
10  return !btwAngle(cur, prv, nxt, p, !strict);
11 }
```

11.11 Polygon Cut

c08d26

```

1 // Dependency: bananaPoint(); T = double
2 // Cut a convex polygon with line (s -> e), keep right side
3 vector<Pt> polyCut(vector<Pt> poly, Pt s, Pt e) {
4   vector<Pt> res; for (int i = 0; i < sz(poly); i++) {
5     Pt cur = poly[i], prv = i ? poly[i - 1] : poly.back();
6     bool side = ori(s, e, cur) < 0;
7     if (side != (ori(s, e, prv) < 0)) {
8       auto [p, d] = bananaPoint({s, e}, {cur, prv});
9       res.pb(p / d);
10    } if (side) res.pb(cur);
11  } return res;
12 }
```

11.12 Half-Plane Intersection

c71070

```

1 // Dependency: sameVec(), cmp(); T = long long
2 /* Having solution, check size > 2 */
3 /* --^-- Line.a --^-- Line.b --^-- */
4 auto halfPlaneIntersection(vector<Line> arr) {
5   auto areaPair = [&](Line a, Line b) {
6     return make_pair((a.b - a.a) ^ (b.a - a.a),
7                      (a.b - a.a) ^ (b.b - a.a));
8   };
9   auto isin = [&](Line l0, Line l1, Line l2) {
10    // Check inter(l1, l2) strictly in l0
11    auto [a02X, a02Y] = areaPair(l0, l2);
12    auto [a12X, a12Y] = areaPair(l1, l2);
13    if (a12X - a12Y < 0) a12X *= -1, a12Y *= -1;
14    return (__int128)a02Y * a12X -
15           (__int128)a02X * a12Y > 0; // C^4
16  };
17  sort(all(arr), [&](Line a, Line b) {
18    if (sameVec(a, b, 1))
19      return ori(a.a, a.b, b.b) < 0;
20    return cmp(a.b - a.a, b.b - b.a);
21  });
22  deque<Line> dq(1, arr[0]);
23  auto popBack = [&](int t, Line p) {
24    while (sz(dq) >= t &&
25           !isin(p, dq[sz(dq) - 2], dq.back()))
26      dq.pop_back();
27  };
28  auto popFront = [&](int t, Line p) {
29    while (sz(dq) >= t && !isin(p, dq[0], dq[1]))
30      dq.pop_front();
31  };
32  for (auto p : arr) if (!sameVec(dq.back(), p, 1))
33    popBack(2, p), popFront(2, p), dq.pb(p);
34  popBack(3, dq[0]), popFront(3, dq.back());
35  return vector<Line>(all(dq));
36 }
```

11.13 Cyclic Ternary Search

e3165d

```

1 /* bool pred(int a, int b);
2 f(0) ~ f(n - 1) is a cyclic-shift U-function
3 return idx s.t. pred(x, idx) is false forall x */
4 int cycTsearch(int n, auto pred) {
5   if (n == 1) return 0;
6   int l = 0, r = n; bool rv = pred(1, 0);
7   while (r - l > 1) {
8     int m = (l + r) / 2;
9     if (pred(0, m) ? rv : pred(m, (m + 1) % n)) r = m;
10    else l = m;
11  } return pred(l, r % n) ? l : r % n;
12 }
```

11.14 Circle Intersections

734f65

```

1 // Dependency: cycTsearch(); T = double for circles
2 vector<Pt> circleLineIntersect(Cir c, Line l) {
3   Pt p = l.a + (l.b - l.a) *
4     ((c.o - l.a) * (l.b - l.a)) / abs2(l.b - l.a);
5   double s = (l.b - l.a) ^ (c.o - l.a);
6   double h2 = c.r * c.r - s * s / abs2(l.b - l.a);
7   if (sgn(h2) == -1) return {};
8   if (sgn(h2) == 0) return {p};
9   Pt h = (l.b - l.a) / abs(l.b - l.a) * sqrt(h2);
10  return {p - h, p + h};
11 }
12 // covered area of c1: arc from res[0] to res[1], CCW
13 vector<Pt> circlesIntersect(Cir c1, Cir c2) {
```

```

14 double d2 = abs2(c1.o - c2.o), d = sqrt(d2);
15 if (d < max(c1.r, c2.r) - min(c1.r, c2.r) ||
16     d > c1.r + c2.r) return {};
17 Pt u = (c1.o + c2.o) / 2 +
18     (c1.o - c2.o) *
19     ((c2.r * c2.r - c1.r * c1.r) / (2 * d2));
20 double A = sqrt((c1.r + c2.r + d) *
21     (c1.r - c2.r + d) * (c1.r + c2.r - d) *
22     (-c1.r + c2.r + d));
23 Pt v = rot90(c2.o - c1.o) * A / (2 * d2);
24 if (sgn(v.x) == 0 && sgn(v.y) == 0) return {u};
25 return {u - v, u + v};
26 }
27 vector<pii> convexLineIntersect(vector<Pt>& C, Line la) {
28     auto dis = [&](int p) {
29         return (la.b - la.a) ^ (C[p] - la.a);
30     };
31     auto gao = [&](int s) {
32         return cycTsearch(sz(C), [&](int i, int j) {
33             return sgn(dis(i) - dis(j)) == s;
34         });
35     };
36     int x = gao(1), y = gao(-1), n = sz(C);
37     if (sgn(dis(x)) < 0 || sgn(dis(y)) > 0) return {};
38     if (sgn(dis(x)) == 0 || sgn(dis(y)) == 0) {
39         int v = ((sgn(dis(x)) == 0 ? x : y) + n - 1) % n;
40         vector<pii> vec;
41         for (int i = 0; i < 3; i++, v = (v + 1) % n)
42             if (sgn(dis(v)) == 0) vec.emplace_back(v, v);
43         return vec;
44     }
45     auto get = [&](int l, int r, int s) {
46         while ((l + 1) % n != r) {
47             int m = ((l + r + (l < r ? 0 : n)) / 2) % n;
48             (sgn(dis(m)) == s ? l : r) = m;
49         }
50         if (sgn(dis(r)) == 0) return pii(r, r);
51         return pii(l, r);
52     };
53     return {get(x, y, 1), get(y, x, -1)};
54 }

```

11.15 Tangents

8def22

```

1 // Dependency: cycTsearch(); T = double for circle tangents
2 auto circlePointTangent(Cir c, Pt p) {
3     vector<Line> res;
4     double dSq = abs2(p - c.o);
5     if (sgn(dSq - c.r * c.r) == 0) {
6         res.push_back({p, p + rot90(p - c.o)});
7     } else if (dSq > c.r * c.r) {
8         double s = dSq - c.r * c.r;
9         Pt v = p + (c.o - p) * s / dSq;
10        Pt u = rot90(c.o - p) * sqrt(s) * c.r / dSq;
11        res.push_back({p, v + u});
12        res.push_back({p, v - u});
13    }
14    return res;
15 }
16 auto circlesTangent(Cir c1, Cir c2, int sign1) {
17     // sign1 = 1 for outer tang, -1 for inter tang
18     vector<Line> res;
19     double dSq = abs2(c1.o - c2.o);
20     if (sgn(dSq) == 0) return res;
21     double d = sqrt(dSq);
22     Pt v = (c2.o - c1.o) / d;
23     double c = (c1.r - sign1 * c2.r) / d;
24     if (c * c > 1) return res;
25     double h = sqrt(max(0.0, 1.0 - c * c));
26     for (int sign2 = 1; sign2 >= -1; sign2 -= 2) {
27         Pt n = Pt(v.x * c - sign2 * h * v.y,
28             v.y * c + sign2 * h * v.x);
29         Pt p1 = c1.o + n * c1.r;
30         Pt p2 = c2.o + n * (c2.r * sign1);
31         if (sgn(p1.x - p2.x) == 0 &&
32             sgn(p1.y - p2.y) == 0)
33             p2 = p1 + rot90(c2.o - c1.o);
34         res.push_back({p1, p2});
35     }
36     return res;
37 }
38 /* The point should be strictly out of hull
39    return arbitrary point on the tangent line */
40 pii pointConvexTangent(vector<Pt>& C, Pt p) {
41     auto gao = [&](int s) {
42         return cycTsearch(sz(C), [&](int x, int y) {
43             return ori(p, C[x], C[y]) == s;
44         });
45     };
46     return pii(gao(1), gao(-1));

```

```

47 } // return (a, b), ori(p, C[a], C[b]) >= 0

```

11.16 Bisector

5348b9

```

1 Pt bisector(Pt a, Pt b, Pt c) { Pt s = b-a, t = c-a;
2   t = t * abs(s) / abs(t); return s + t; }

```

11.17 Minimum Enclosing Circle

04b498

```

1 // Dependency: circenter(); T = double
2 Cir minEnclosingCircle(vector<Pt> p) {
3     auto seed = chrono::steady_clock::now();
4     time_since_epoch().count();
5     shuffle(all(p), mt19937(seed));
6     double r = 0.0; Pt cent = p[0];
7     for (int i = 1; i < sz(p); i++) {
8         if (abs2(cent - p[i]) <= r) continue;
9         cent = p[i]; r = 0.0;
10        for (int j = 0; j < i; j++) {
11            if (abs2(cent - p[j]) <= r) continue;
12            cent = (p[i] + p[j]) / 2; r = abs2(p[j] - cent);
13            for (int k = 0; k < j; k++) {
14                if (abs2(cent - p[k]) <= r) continue;
15                cent = circenter(p[i], p[j], p[k]);
16                r = abs2(p[k] - cent);
17            }
18        }
19    }
20    return {cent, sqrt(r)};

```

11.18 Minkowski Sum

fdd915

```

1 // Dependency: convexHull()
2 auto minkowski(vector<Pt> a, vector<Pt> b) {
3     a = convexHull(a), b = convexHull(b);
4     int n = sz(a), m = sz(b);
5     vector<Pt> c = {a[0] + b[0]}, s1, s2;
6     for (int i = 0; i < n; i++) s1.pb(a[(i+1) % n] - a[i]);
7     for (int i = 0; i < m; i++) s2.pb(b[(i+1) % m] - b[i]);
8     for (int p1 = 0, p2 = 0; p1 < n || p2 < m; )
9         if (p2 == m ||
10             (p1 < n && sgn(s1[p1] ^ s2[p2]) >= 0))
11             c.pb(c.back() + s1[p1++]);
12         else
13             c.pb(c.back() + s2[p2++]);
14     return convexHull(c);
15 }

```

11.19 Convex Hull Distance

f7df29

```

1 // Dependency: minkowski(), inConvex(), pointSegDist()
2 T = double
3 double convexHullDist(vector<Pt> A, vector<Pt> B) {
4     Pt o(0, 0); for (auto& p : B) p = p - o;
5     auto C = minkowski(A, B);
6     if (inConvex(C, 0)) return 0;
7     double ans = pointSegDist(0, C.back(), C[0]);
8     for (int i = 0; i + 1 < sz(C); i++)
9         ans = min(ans, pointSegDist(0, C[i], C[i + 1]));
10    return ans; }

```

11.20 Closest Point Pair

ad1bba

```

1 // returns {min squared dist, {i, j}}, n >= 2, |coord| < 1e9
2 pair<T, pair<int, int>> closestPair(vector<Pt> p) {
3     vector<int> id(sz(p)); iota(all(id), 0);
4     sort(all(id),
5         [&](int a, int b) { return p[a].y < p[b].y; });
6     set<pair<Pt, int>> s; // (point, id)
7     pair<T, pair<int, int>> best = {(T)9e18, {-1, -1}};
8     int l = 0; for (int i : id) {
9         if (!best.first) break;
10        T d = sqrtl(best.first) + is_integral_v<T>;
11        while (p[id[l]].y <= p[i].y - d)
12            s.erase({p[id[l]], id[l]}), l++;
13        auto lo = s.lower_bound({p[i] - Pt{d, 0}, 0});
14        auto hi = s.upper_bound({p[i] + Pt{d, 0}, sz(p)});
15        for (; lo != hi; lo++) {
16            auto [q, j] = *lo;
17            best = min(best,
18                {abs2(q - p[i]), {min(i, j), max(i, j)}});
19        } s.insert({p[i], i});
20    } return best;
21 }

```

11.21 Polygon-Circle Intersection

18454b

```

1 // T = double
2 double areaSector(Pt pa, Pt pb, double r) {
3     if (abs(pa) < abs(pb)) swap(pa, pb);
4     if (abs(pb) < eps) return 0;
5     double S, h, t;
6     double a = abs(pb), b = abs(pa), c = abs(pb - pa);
7     double cosB = pb * (pb - pa) / a / c;
8     double B = acos(cosB);
9     double cosC = pa * pb / a / b, C = acos(cosC);
10    if (a > r) {
11        S = C / 2 * r * r;
12        h = a * b * sin(C) / c;

```

```

13     if (h < r && B < PI / 2)
14         S -= acos(h / r) * r * r - h * sqrt(r * r - h * h);
15     } else if (b > r) {
16         t = PI - B - asin(sin(B) / r * a);
17         S = 0.5 * a * r * sin(t) + (C - t) / 2 * r * r;
18     } else {
19         S = 0.5 * sin(C) * a * b;
20     }
21     return S;
22 }
23 double areaPolyCircle(vector<Pt> poly, Pt O, double r) {
24     double S = 0;
25     int n = sz(poly);
26     for (int i = 0; i < n; i++)
27         S += areaSector(poly[i] - O,
28             poly[(i + 1) % n] - O, r) *
29             ori(O, poly[i], poly[(i + 1) % n]);
30     return fabs(S);
31 }

```

11.22 Union of Polygons

9d7265

```

1 // Dependency: sameVec(), bananaPoint(), cmpLine()
2 // in CCW order, use index as tiebreaker when collinear
3 auto polysBorder(vector<vector<Pt>> poly, int id) {
4     auto get = [&](auto& p, int i) {
5         return make_pair(p[i], p[(i + 1) % sz(p)]);
6     };
7     vector<pair<Pt, Pt>> seg;
8     for (int e = 0; e < sz(poly[id]); e++) {
9         auto [s, t] = get(poly[id], e);
10        vector<pair<Pt, int>> vec;
11        vec.emplace_back(s, -1 << 30);
12        vec.emplace_back(t, 1 << 30);
13        for (int i = 0; i < sz(poly); i++) {
14            int st = find_if(poly[i].begin(), poly[i].end(),
15                [&](Pt p) { return ori(p, s, t) == 1; }) -
16                poly[i].begin();
17            if (st == sz(poly[i])) continue;
18            for (int j = st; j < st + sz(poly[i]); j++) {
19                auto [a, b] = get(poly[i], j % sz(poly[i]));
20                if (sameVec(a - b, s - t, -1)) {
21                    if (ori(a, b, s) == 0 &&
22                        sameVec(a - b, s - t, 1) && i <= id) {
23                        vec.emplace_back(a, -1);
24                        vec.emplace_back(b, 1);
25                    }
26                } else {
27                    int s1 = ori(a, s, t) == 1;
28                    int s2 = ori(b, s, t) == 1;
29                    if (s1 ^ s2) {
30                        auto [p, d] = bananaPoint({a, b}, {s, t});
31                        vec.emplace_back(p / d, s1 ? 1 : -1);
32                    }
33                }
34            }
35        }
36        sort(all(vec), [&](auto i, auto j) {
37            return cmpLine(i.first, j.first, s, t);
38        });
39        int base = 1 << 30;
40        Pt lst(0, 0);
41        for (auto [cur, val] : vec) {
42            if (!base) seg.emplace_back(lst, cur);
43            lst = cur, base += val;
44        }
45        return seg;
46    }
47    double polysUnionArea(vector<vector<Pt>> poly) {
48        double res = 0;
49        for (int i = 0; i < sz(poly); i++) {
50            auto seg = polysBorder(poly, i);
51            for (auto [l, r] : seg) res += l ^ r;
52        }
53        return res / 2;
54    }

```

11.23 Rotating Sweep Line

769b9b

```

1 // Dependency: ref()
2 struct Event {
3     Pt d; int u, v;
4     bool operator<(const Event& o) const {
5         return sgn(d ^ o.d) > 0;
6     };
7 }
8 void rotatingSweepLine(vector<Pt> pts) {
9     int n = sz(pts);
10    vector<int> ord(n), pos(n); vector<Event> e;
11    for (int i = 0; i < n; i++)
12        e.push_back({ref(pts[i] - pts[j]), i, j});
13    sort(all(e)); iota(all(ord), 0);
14    sort(all(ord), [&](int i, int j) {
15        return sgn(pts[i].y - pts[j].y) == 0 ?
16            pts[i].x < pts[j].x : pts[i].y < pts[j].y;
17    });

```

```

18     for (int i = 0; i < n; i++) pos[ord[i]] = i;
19     auto makeReverse = [](auto v) {
20         sort(all(v));
21         v.resize(unique(all(v)) - v.begin());
22         vector<pii> segs;
23         for (int i = 0, j = 0; i < sz(v); i = j) {
24             for (; j < sz(v) && v[j] - v[i] <= j - i; j++);
25             segs.emplace_back(v[i], v[j - 1] + 1 + 1);
26         }
27         return segs;
28     };
29     for (int i = 0, j = 0; i < sz(e); i = j) {
30         vector<int> tmp;
31         for (; j < sz(e) && !e[i] < e[j]; j++)
32             tmp.pb(min(pos[e[j].u], pos[e[j].v]));
33         for (auto [l, r] : makeReverse(tmp)) {
34             reverse(ord.begin() + l, ord.begin() + r);
35             for (int t = l; t < r; t++) pos[ord[t]] = t;
36             // update value here
37         }
38     }

```

11.24 Pick's Theorem

Consider a polygon which vertices are all lattice points.
 Let i = number of points inside the polygon.
 Let b = number of points on the boundary of the polygon.
 Then we have the following formula:

$$\text{Area} = i + b/2 - 1$$

12 Number Theory

12.1 Mod Sum

60beb8

```

1 /**
2  * Author: Simon Lindholm
3  * Date: 2015-06-23
4  * License: CC0
5  * Source: own work
6  * Description: Sums of mod'ed arithmetic progressions.
7  *
8  * \texttt{modsum(to, c, k, m)} = \sum_{i=0}^{\texttt{to}-1} \{ (ki+c) \% m \}.
9  * \texttt{divsum} is similar but for floored division.
10 * Time: \mathcal{O}(\log(m)), with a large constant.
11 * Status: Tested for all |k|, |c|, to, m <= 50, and on
12 * kattis:aladin
13 */
14 typedef unsigned long long ull;
15 ull sumsq(ull to) { return to / 2 * ((to-1) | 1); }
16 // ^ written in a weird way to deal with overflows correctly
17 ull divsum(ull to, ull c, ull k, ull m) {
18     ull res = k / m * sumsq(to) + c / m * to;
19     k %= m; c %= m;
20     if (!k) return res;
21     ull to2 = (to * k + c) / m;
22     return res + (to - 1) * to2 - divsum(to2, m-1 - c, m, k);
23 }
24 ll modsum(ull to, ll c, ll k, ll m) {
25     c = ((c % m) + m) % m;
26     k = ((k % m) + m) % m;
27     return to * c + k * sumsq(to) - m * divsum(to, c, k, m);
28 }

```

12.2 Extended Lucas Theorem

3bed10

```

1 /**
2  * Author: koukanni
3  * Date: 2025
4  * License: CC0
5  * Source:
6  * Description: Computes C(n, m) mod P where P is not
7  * necessarily prime
8  * Functions
9  * exgcd(a, b, x, y): Extended Euclidean algorithm
10 * inv(a, p): Modular inverse of a modulo p
11 * qpow(a, b, p): Fast modular exponentiation
12 * CRT(n, a, m): Chinese Remainder Theorem
13 * calc(n, x, P): Helper function for computing factorial
14 * with prime power
15 * multilucas(n, m, x, P): Lucas theorem for prime power
16 * modulus
17 * exlucas(n, m, P): Main function - Extended Lucas theorem
18 * usage: exlucas(n, m, P) returns C(n, m) mod P
19 * Time: O(P log(P))
20 * Status: tested
21 */
22 typedef long long ll;
23 void exgcd(ll a, ll b, ll& x, ll& y) {
24     if (!b)
25         x = 1, y = 0;
26     else

```

```

24     exgcd(b, a % b, y, x), y -= a / b * x;
25 }
26 ll inv(ll a, ll p) {
27     ll x, y;
28     exgcd(a, p, x, y);
29     return (x + p) % p;
30 }
31 ll qpow(ll a, ll b, ll p) {
32     ll r = 1;
33     for (; b >= 1; a = a * a % p)
34         if (b & 1) r = r * a % p;
35     return r;
36 }
37 ll CRT(int n, ll* a, ll* m) {
38     ll M = 1, p = 0;
39     for (int i = 1; i <= n; i++) M = M * m[i];
40     for (int i = 1; i <= n; i++) {
41         ll w = M / m[i], x, y;
42         exgcd(w, m[i], x, y);
43         p = (p + a[i] * w * x % M) % M;
44     }
45     return (p % M + M) % M;
46 }
47 ll calc(ll n, ll x, ll P) {
48     if (!n) return 1;
49     ll s = 1;
50     for (ll i = 1; i <= P; i++)
51         if (i % x) s = s * i % P;
52     s = qpow(s, n / P, P);
53     for (ll i = n / P * P + 1; i <= n; i++)
54         if (i % x) s = i * P * s % P;
55     return s * calc(n / x, x, P) % P;
56 }
57 ll multilucas(ll n, ll m, ll x, ll P) {
58     if (n < m) return 0;
59     int cnt = 0;
60     for (ll i = n; i; i /= x) cnt += i / x;
61     for (ll i = m; i; i /= x) cnt -= i / x;
62     for (ll i = n - m; i; i /= x) cnt -= i / x;
63     return qpow(x, cnt, P) % P * calc(n, x, P) % P *
64         inv(calc(m, x, P), P) % P *
65         inv(calc(n - m, x, P), P) % P;
66 }
67 ll exlucas(ll n, ll m, ll P) {
68     int cnt = 0;
69     ll p[20], a[20];
70     for (ll i = 2; i * i <= P; i++) {
71         if (P % i == 0) {
72             p[++cnt] = 1;
73             while (P % i == 0) p[cnt] = p[cnt] * i, P /= i;
74             a[cnt] = multilucas(n, m, i, p[cnt]);
75         }
76     }
77     if (P > 1) p[++cnt] = P, a[cnt] = multilucas(n, m, P, P);
78     return CRT(cnt, a, p);
79 }

```

12.3 Prime Sieve and Defactor

e2350f

```

1 // Author: Gino
2 const int maxc = 1e6 + 1;
3 vector<int> lpf;
4 vector<int> prime;
5
6 void seive() {
7     prime.clear();
8     lpf.resize(maxc, 1);
9     for (int i = 2; i < maxc; i++) {
10         if (lpf[i] == 1) {
11             lpf[i] = i;
12             prime.emplace_back(i);
13         }
14         for (auto& j : prime) {
15             if (i * j >= maxc) break;
16             lpf[i * j] = j;
17             if (j == lpf[i]) break;
18         }
19     }
20     vector<pii> fac;
21     void defactor(int u) {
22         fac.clear();
23         while (u > 1) {
24             int d = lpf[u];
25             fac.emplace_back(make_pair(d, 0));
26             while (u % d == 0) {
27                 u /= d;
28                 fac.back().second++;
29             }
30         }
31     }
32 }

```

12.4 Harmonic Series

7c56cc

```

1 // Author: Gino
2 // O(n log n)

```

```

3 for (int i = 1; i <= n; i++) {
4     for (int j = i; j <= n; j += i) {
5         // O(1) code
6     }
7 }
8 // PIE
9 // given array a[0], a[1], ..., a[n - 1]
10 // calculate dp[x] = number of pairs (a[i], a[j]) such that
11 // gcd(a[i], a[j]) = x // (i < j)
12 //
13 // idea: let mc(x) = # of y s.t. x|y
14 // f(x) = # of pairs s.t. gcd(a[i], a[j]) >= x
15 // f(x) = C(mc(x), 2)
16 // dp[x] = f(x) - sum(dp[y], x < y and x|y)
17 const int maxc = 1e6;
18 vector<int> cnt(maxc + 1, 0), dp(maxc + 1, 0);
19 for (int i = 0; i < n; i++)
20     cnt[a[i]]++;
21 for (int x = maxc; x >= 1; x--) {
22     ll cnt_mul = 0; // number of multiples of x
23     for (int y = x; y <= maxc; y += x)
24         cnt_mul += cnt[y];
25     dp[x] = cnt_mul * (cnt_mul - 1) / 2; // number of pairs
26     // that are divisible by x
27     for (int y = x + x; y <= maxc; y += x)
28         dp[x] -= dp[y]; // PIE: subtract all dp[y] for y >
29     // x and x|y
30 }

```

12.5 Count Number of Divisors

0a5616

```

1 // Author: Gino
2 // Function: Count the number of divisors for all x <= 10^6
3 // using harmonic series
4 const int maxc = 1e6;
5 vector<int> facs;
6 void find_all_divisors() {
7     facs.clear(); facs.resize(maxc + 1, 0);
8     for (int x = 1; x <= maxc; x++) {
9         for (int y = x; y <= maxc; y += x) {
10             facs[y]++;
11         }
12     }
13 }

```

12.6 數論分塊

cd4e6b

```

1 // Author: Gino
2 /*
3 n = 17
4 i: 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17
5 n/i: 17 8 5 4 3 2 2 2 1 1 1 1 1 1 1 1 1
6
7 L(2) R(2)
8 L(x) := left bound for n/i = x
9 R(x) := right bound for n/i = x
10 ===== FORMULA =====
11 >>> R = n / (n/L) <<<
12 =====
13 Example: L(2) = 6
14           R(2) = 17 / (17 / 6)
15              = 17 / 2
16              = 8
17 */
18 // ===== CODE =====
19 for (ll l = 1, r = 1, q = n; l <= n; l = r + 1) {
20     q = n / l;
21     r = n / q;
22     // Process your code here
23 }
24 // q, l, r: 17 1 1
25 // q, l, r: 8 2 2
26 // q, l, r: 5 3 3
27 // q, l, r: 4 4 4
28 // q, l, r: 3 5 5
29 // q, l, r: 2 6 8
30 // q, l, r: 1 9 17

```

12.7 Pollard's rho

```

1 // Author: Unknown
2 // Function: Find a non-trivial factor of a big number in
3 // O(n^(1/4) log^2(n))
4 ll find_factor(ll number) {
5     __int128 x = 2;
6     for (__int128 cycle = 1; ; cycle++) {
7         __int128 y = x;
8         for (int i = 0; i < (1 << cycle); i++) {
9             x = (x * x + 1) % number;
10            __int128 factor = __gcd(x - y, number);
11            if (factor > 1)
12                return factor;
13        }
14    }
15 }

```

```

13     }
14 }

1# Author: Unknown
2# Function: Find a non-trivial factor of a big number in
  O(n^(1/4) log^2(n))
3 from itertools import count
4 from math import gcd
5 from sys import stdin
6 for s in stdin:
7     number, x = int(s), 2
8     brk = False
9     for cycle in count(1):
10        y = x
11        if brk:
12            break
13        for i in range(1 << cycle):
14            x = (x * x + 1) % number
15            factor = gcd(x - y, number)
16            if factor > 1:
17                print(factor)
18                brk = True
19                break

```

12.8 Miller Rabin

686187

```

1// Author: Unknown, Modified by Gino
2// Function: Check if a number is a prime in O(100 *
  log^2(n))
3//      miller_rabin(): return 1 if prime, 0 otherwise
4 inline ll mul(ll x, ll y, ll mod) {
5     return (__int128)(x) * y % mod;
6 }
7 ll mypow(ll a, ll b, ll mod) {
8     ll r = 1;
9     while (b > 0) {
10        if (b & 1) r = mul(r, a, mod);
11        a = mul(a, a, mod);
12        b >>= 1;
13    }
14    return r;
15 }
16 bool witness(ll a, ll n, ll u, int t){
17     ll x = mypow(a, u, n);
18     for(int i = 0; i < t; i++) {
19         ll nx = mul(x, x, n);
20         if (nx == 1 && x != 1 && x != n-1) return true;
21         x = nx;
22     }
23     return x != 1;
24 }
25 bool miller_rabin(ll n) {
26     // if n >= 3,474,749,660,383
27     // change {2, 3, 5, 7, 11, 13} to
28     // {2, 325, 9375, 28178, 450775, 9780504, 1795265022}
29     if (n < 2) return false;
30     if (!(n & 1)) return n == 2;
31     ll u = n - 1; int t = 0;
32     while(!(u & 1)) u >>= 1, t++;
33     for (ll a : {2, 3, 5, 7, 11, 13}) {
34         if (a % n == 0) continue;
35         if (witness(a, n, u, t)) return false;
36     }
37     return true;
38 }
39 // bases that make sure no pseudoprimes flee from test
40 // if WA, replace randll(n - 1) with these bases:
41 // n < 4,759,123,141      3 : 2, 7, 61
42 // n < 1,122,004,669,633  4 : 2, 13, 23, 1662803
43 // n < 3,474,749,660,383  6 : pimes <= 13
44 // n < 2^64              7 :
45 // 2, 325, 9375, 28178, 450775, 9780504, 1795265022

```

12.9 Discrete Log

a04e88

```

1// Author: ckiseki
2// find x^? = y (mod M)
3// O(sqrt(M))
4 template<typename Int>
5 Int BSGS(Int x, Int y, Int M) {
6     // x^? \equiv y (mod M)
7     Int t = 1, c = 0, g = 1;
8     for (Int M_ = M; M_ > 0; M_ >>= 1) g = g * x % M;
9     for (g = gcd(g, M); t % g != 0; ++c) {
10        if (t == y) return c;
11        t = t * x % M;
12    }
13    if (y % g != 0) return -1;
14    t /= g, y /= g, M /= g;
15    Int h = 0, gs = 1;
16    for (; h * h < M; ++h) gs = gs * x % M;
17    unordered_map<Int, Int> bs;

```

```

18 for (Int s = 0; s < h; bs[y] = ++s) y = y * x % M;
19 for (Int s = 0; s < M; s += h) {
20     t = t * gs % M;
21     if (bs.count(t)) return c + s + h - bs[t];
22 }
23 return -1;
24 }

```

12.10 Discrete Sqrt

3f16e1

```

1// Author: ckiseki
2// find solution for x^2 = n (mod P)
3// O(log^2 P)
4 int get_root(int n, int P) { // ensure 0 <= n < p
5     if (P == 2 or n == 0) return n;
6     auto check = [&](lld x) {
7         return modpow(int(x), (P - 1) / 2, P); };
8     if (check(n) != 1) return -1;
9     mt19937 rnd(7122); lld z = 1, w;
10    while (check(w = (z * z - n + P) % P) != P - 1)
11        z = rnd() % P;
12    const auto M = [P, w](auto &u, auto &v) {
13        auto [a, b] = u; auto [c, d] = v;
14        return make_pair((a * c + b * d % P * w) % P,
15            (a * d + b * c) % P);
16    };
17    pair<lld, lld> r(1, 0), e(z, 1);
18    for (int q = (P + 1) / 2; q; q >>= 1, e = M(e, e))
19        if (q & 1) r = M(r, e);
20    return int(r.first); // sqrt(n) mod P where P is prime
21 }

```

12.11 Fast Power

Note: $a^n \equiv a^{(n \bmod (p-1))} \pmod{p}$

12.12 Extend GCD

50b7fc

```

1// Author: Gino
2// [Usage]
3// bezout(a, b, c):
4//     find solution to ax + by = c
5//     return {-LINF, -LINF} if no solution
6// inv(a, p):
7//     find modulo inverse of a under p
8//     return -1 if not exist
9// CRT(vector<ll>& a, vector<ll>& m)
10//     find a solution pair (x, mod) satisfies all x = a[i]
  (mod m[i])
11//     return {-LINF, -LINF} if no solution
12
13 const ll LINF = 4e18;
14 typedef pair<ll, ll> pll;
15 template<typename T1, typename T2>
16 T1 chmod(T1 a, T2 m) {
17     return (a % m + m) % m;
18 }
19
20 ll GCD;
21 pll extgcd(ll a, ll b) {
22     if (b == 0) {
23         GCD = a;
24         return pll{1, 0};
25     }
26     pll ans = extgcd(b, a % b);
27     return pll{ans.second, ans.first - a/b * ans.second};
28 }
29 pll bezout(ll a, ll b, ll c) {
30     bool negx = (a < 0), negy = (b < 0);
31     pll ans = extgcd(abs(a), abs(b));
32     if (c % GCD != 0) return pll{-LINF, -LINF};
33     return pll{ans.first * c/GCD * (negx ? -1 : 1),
34         ans.second * c/GCD * (negy ? -1 : 1)};
35 }
36 ll inv(ll a, ll p) {
37     if (p == 1) return -1;
38     pll ans = bezout(a % p, -p, 1);
39     if (ans == pll{-LINF, -LINF}) return -1;
40     return chmod(ans.first, p);
41 }
42 pll CRT(vector<ll>& a, vector<ll>& m) {
43     for (int i = 0; i < (int)a.size(); i++)
44         a[i] = chmod(a[i], m[i]);
45
46     ll x = a[0], mod = m[0];
47     for (int i = 1; i < (int)a.size(); i++) {
48         pll sol = bezout(mod, m[i], a[i] - x);
49         if (sol.first == -LINF) return pll{-LINF, -LINF};
50
51         // prevent long long overflow
52         ll p = chmod(sol.first, m[i] / GCD);
53         ll lcm = mod / GCD * m[i];
54         x = chmod((__int128)p * mod + x, lcm);
55         mod = lcm;

```

```

56     }
57     return pll{x, mod};
58 }

```

12.13 Mu + Phi

ab4a91

```

1// Author: Gino
2const int maxn = 1e6 + 5;
3ll f[maxn];
4vector<int> lpf, prime;
5void build() {
6    lpf.clear(); lpf.resize(maxn, 1);
7    prime.clear();
8    f[1] = ...; /* mu[1] = 1, phi[1] = 1 */
9    for (int i = 2; i < maxn; i++) {
10        if (lpf[i] == 1) {
11            lpf[i] = i; prime.emplace_back(i);
12            f[i] = ...; /* mu[i] = 1, phi[i] = i-1 */
13        }
14        for (auto& j : prime) {
15            if (i*j >= maxn) break;
16            lpf[i*j] = j;
17            if (i % j == 0) f[i*j] = ...; /* 0, phi[i*j] */
18            else f[i*j] = ...; /* -mu[i], phi[i]*phi[j] */
19            if (j >= lpf[i]) break;
20        }
21    }
22 }

```

12.14 Other Formulas

- Pisano Period: 任何線性遞迴 (比如費氏數列) 模任何一個數字 M 都會循環, 找循環節 $\pi(M)$ 先質因數分解 $M = \prod p_i^{e_i}$, 然後 $\pi(M) = \text{lcm}(\pi(p_i^{e_i}))$,
- Inversion: $aa^{-1} \equiv 1 \pmod{m}$. a^{-1} exists iff $\gcd(a, m) = 1$.
- Linear inversion: $a^{-1} \equiv (m - \lfloor \frac{m}{a} \rfloor) \times (m \bmod a)^{-1} \pmod{m}$
- Fermat's little theorem: $a^p \equiv a \pmod{p}$ if p is prime.
- Euler function: $\varphi(n) = n \prod_{p|n} \frac{p-1}{p}$
- Euler theorem: $a^{\varphi(n)} \equiv 1 \pmod{n}$ if $\gcd(a, n) = 1$. If a, n are not coprime: 質因數分解 $n = \prod p_i^{e_i}$, 對每個 $p_i^{e_i}$ 分開看他們跟 a 是否互質 (互質: Fermat / 不互質: 夠大的指數會直接削成 0), 最後用 CRT 合併。
- Extended Euclidean algorithm: $ax + by = \gcd(a, b) = \gcd(b, a - \lfloor \frac{a}{b} \rfloor b) = \gcd(b, a - \lfloor \frac{a}{b} \rfloor b)$
- Divisor function: $\sigma_x(n) = \sum_{d|n} d^x$. $n = \prod_{i=1}^r p_i^{a_i}$.
 $\sigma_x(n) = \prod_{i=1}^r \frac{p_i^{(a_i+1)x} - 1}{p_i^x - 1}$ if $x \neq 0$. $\sigma_0(n) = \prod_{i=1}^r (a_i + 1)$.
- Chinese remainder theorem (Coprime Moduli):
 $x \equiv a_i \pmod{m_i}$.
 $M = \prod m_i$. $M_i = \frac{M}{m_i}$. $t_i = M_i^{-1}$.
 $x = kM + \sum a_i t_i M_i$, $k \in \mathbb{Z}$.
- Chinese remainder theorem:
 $x \equiv a_1 \pmod{m_1}, x \equiv a_2 \pmod{m_2} \Rightarrow x = m_1 p + a_1 = m_2 q + a_2 \Rightarrow m_1 p - m_2 q = a_2 - a_1$
Solve for (p, q) using ExtGCD.
 $x \equiv m_1 p + a_1 \equiv m_2 q + a_2 \pmod{\text{lcm}(m_1, m_2)}$
- Avoiding Overflow: $ca \bmod cb = c(a \bmod b)$
- Dirichlet Convolution: $(f * g)(n) = \sum_{d|n} f(d)g(\frac{n}{d})$
- Important Multiplicative Functions + Properties:
 - $\varepsilon(n) = [n = 1]$
 - $1(n) = 1$
 - $id(n) = n$
 - $\mu(n) = 0$ if n has squared prime factor
 - $\mu(n) = (-1)^k$ if $n = p_1 p_2 \dots p_k$
 - $\varepsilon = \mu * 1$
 - $\varphi = \mu * id$
 - $[n = 1] = \sum_{d|n} \mu(d)$
 - $[gcd = 1] = \sum_{d|gcd} \mu(d)$
- Möbius inversion: $f = g * 1 \Leftrightarrow g = f * \mu$

12.15 Polynomial

57318b

```

1// Author: Gino
2// Preparation: first set_mod(mod, g), then init_ntt()
3// everytime you change modulus, you have to call
  init_ntt() again
4//
5// [Usage]
6// polynomial: vector<ll> a, b
7// negation: -a
8// add/subtract: a += b, a -= b
9// convolution: a *= b

```

```

10// in-place modulo: mod(a, b)
11// in-place inversion under mod x^N: inv(ia, N)
12const int maxk = 20;
13const int maxn = 1<<maxk;
14using u64 = unsigned long long;
15using u128 = __uint128_t;
16int g;
17u64 MOD;
18u64 BARRETT_IM; // [ 2^64 / MOD ]
19inline void set_mod(u64 m, int _g) {
20    g = _g;
21    MOD = m;
22    BARRETT_IM = (u128(1) << 64) / m;
23}
24inline u64 chmod(u128 x) {
25    u64 q = (u64)((x * BARRETT_IM) >> 64);
26    u64 r = (u64)(x - (u128)q * MOD);
27    if (r >= MOD) r -= MOD;
28    return r;
29}
30inline u64 mmul(u64 a, u64 b) {
31    return chmod((u128)a * b);
32}
33ll pw(ll a, ll n) {
34    ll ret = 1;
35    while (n > 0) {
36        if (n & 1) ret = mmul(ret, a);
37        a = mmul(a, a);
38        n >>= 1;
39    }
40    return ret;
41}
42vector<ll> X, iX;
43vector<int> rev;
44void init_ntt() {
45    X.assign(maxn, 1); // x1 = g^((p-1)/n)
46    iX.assign(maxn, 1);
47    ll u = pw(g, (MOD-1)/maxn);
48    ll iu = pw(u, MOD-2);
49    for (int i = 1; i < maxn; i++) {
50        X[i] = mmul(X[i-1], u);
51        iX[i] = mmul(iX[i-1], iu);
52    }
53    if ((int)rev.size() == maxn) return;
54    rev.assign(maxn, 0);
55    for (int i = 1, hb = -1; i < maxn; i++) {
56        if (!(i & (i-1))) hb++;
57        rev[i] = rev[i ^ (1<<hb)] | (1<<(maxk-hb-1));
58    }
59    template<typename T>
60    void NTT(vector<T>& a, bool inv=false) {
61        int _n = (int)a.size();
62        int k = __lg(_n) + ((1<<__lg(_n)) != _n);
63        int n = 1<<k;
64        a.resize(n, 0);
65        short shift = maxk-k;
66        for (int i = 0; i < n; i++)
67            if (i > (rev[i]>>shift))
68                swap(a[i], a[rev[i]>>shift]);
69        for (int len = 2, half = 1, div = maxn>>1; len <= n;
70            len<<=1, half<<=1, div>>=1) {
71            for (int i = 0; i < n; i += len) {
72                for (int j = 0; j < half; j++) {
73                    T u = a[i+j];
74                    T v = mmul(a[i+j+half], (inv ? iX[j*div] :
75                        X[j*div]));
76                    a[i+j] = (u+v >= MOD ? u+v-MOD : u+v);
77                    a[i+j+half] = (u-v < 0 ? u-v+MOD : u-v);
78                }
79            }
80            if (inv) {
81                T dn = pw(n, MOD-2);
82                for (auto& x : a) {
83                    x = mmul(x, dn);
84                }
85            }
86        }
87    }
88    template<typename T>
89    inline void shrink(vector<T>& a) {
90        int cnt = (int)a.size();
91        for (; cnt > 0; cnt--) if (a[cnt-1]) break;
92        a.resize(max(cnt, 1));
93    }
94    template<typename T>
95    vector<T>& operator*=(vector<T>& a, vector<T> b) {
96        int na = (int)a.size();
97        int nb = (int)b.size();
98        a.resize(na + nb - 1, 0);
99        b.resize(na + nb - 1, 0);
100        NTT(a); NTT(b);
101        for (int i = 0; i < (int)a.size(); i++)

```

```

96     a[i] = mmul(a[i], b[i]);
97     NTT(a, true);
98     shrink(a);
99     return a;
100 }
101 inline ll crt(ll a0, ll a1, ll m1, ll m2, ll
    inv_m1_mod_m2){
102     // x ≡ a0 (mod m1), x ≡ a1 (mod m2)
103     // t = (a1 - a0) * inv(m1) mod m2
104     // x = a0 + t * m1 (mod m1*m2)
105     ll t = chmod(a1 - a0);
106     if (t < 0) t += m2;
107     t = (ll)((__int128)t * inv_m1_mod_m2 % m2);
108     return a0 + (ll)((__int128)t * m1);
109 }
110 void mul_crt() {
111     // a copy to a1, a2 | b copy to b1, b2
112     ll M1 = 998244353, M2 = 1004535809;
113     g = 3; set_mod(M1); init_ntt(); a1 *= b1;
114     g = 3; set_mod(M2); init_ntt(); a2 *= b2;
115     ll inv_m1_mod_m2 = pw(M1, M2 - 2);
116     for (int i = 2; i <= 2 * k; i++)
117         cout << crt(a1[i], a2[i], M1, M2, inv_m1_mod_m2)
118         << ' ';
119     cout << endl;
120 }
121 /* P = r*2^k + 1
122 998244353      r    k    g
123 1004535809    479 21   3
124 P            r    k    g
125 3             1    1    2
126 5             1    2    2
127 17            1    4    3
128 97            3    5    5
129 193           3    6    5
130 257           1    8    3
131 7681          15   9   17
132 12289         3   12   11
133 40961         5   13   3
134 65537         1   16   3
135 786433        3   18  10
136 5767169       11  19   3
137 7340033       7   20   3
138 23068673      11  21   3
139 104857601     25  22   3
140 167772161     5   25   3
141 469762049     7   26   3
142 1004535809   479 21   3
143 2013265921   15  27  31
144 2281701377   17  27   3
145 3221225473   3   30   5
146 75161927681 35  31   3
147 77309411329 9   33   7
148 206158430209 3   36  22
149 2061584302081 15 37   7
150 2748779069441 5   39   3
151 6597069766657 3   41   5
152 3958241859937 9   42   5
153 79164837199873 9  43   5
154 263882790666241 15 44   7
155 1231453023109121 35 45   3
156 1337006139375617 19 46   3
157 3799912185593857 27 47   5
158 4222124650659841 15 48  19
159 7881299347898369 7   50   6
160 31525197391593473 7  52   3
161 180143985094819841 5  55   6
162 1945555039024054273 27 56   5
163 4179340454199820289 29 57   3
164 9097271247288401921 505 54 6 */

```

12.16 Counting Primes

1662d0

```

1 // prime_count - #primes in [1..n] (O(n^{2/3}) time,
2 // O(sqrt(n)) memory)
3 using u64 = unsigned long long;
4 static inline u64 prime_count(u64 n){
5     if(n<=1) return 0;
6     int v = (int)floor(sqrt((long double)n));
7     int s = (v+1)>>1, pc = 0;
8     vector<int> smalls(s), roughs(s), skip(v+1);
9     vector<long long> larges(s);
10    for(int i=0; i<s; ++i){
11        smalls[i]=i;
12        roughs[i]=2*i+1;
13        larges[i]=(long long)((n/roughs[i]-1)>>1);
14    }
15    for(int p=3; p<=v; p+=2) if(!skip[p]){
16        int q = p*p;
17        if(1LL*q*q > (long long)n) break;

```

```

17    skip[p]=1;
18    for(int i=q; i<=v; i+=2*p) skip[i]=1;
19    int ns=0;
20    for(int k=0; k<s; ++k){
21        int i = roughs[k];
22        if(skip[i]) continue;
23        u64 d = (u64)i * (u64)p;
24        long long sub = (d <= (u64)v)
25            ? larges[smalls[(int)(d>>1)] - pc]
26            : smalls[(int)((n/d - 1) >> 1)];
27        larges[ns] = larges[k] - sub + pc;
28        roughs[ns++] = i;
29    }
30    s = ns;
31    for(int i=(v-1)>>1, j=((v/p)-1)|1; j>=p; j-=2){
32        int c = smalls[j>>1] - pc;
33        for(int e=(j*p)>>1; i>=e; --i) smalls[i] -= c;
34    }
35    ++pc;
36 }
37 larges[0] += 1LL*(s + 2*(pc-1))*(s-1) >> 1;
38 for(int k=1; k<s; ++k) larges[0] -= larges[k];
39 for(int l=1; l<s; ++l){
40     int q = roughs[l];
41     u64 m = n / (u64)q;
42     long long t = 0;
43     int e = smalls[(int)((m/q - 1) >> 1)] - pc;
44     if(e < l+1) break;
45     for(int k=l+1; k<=e; ++k) t += smalls[(int)((m/
46         (u64)roughs[k] - 1) >> 1)];
47     larges[0] += t - 1LL*(e - l)*(pc + l - 1);
48 }
49 return (u64)(larges[0] + 1);

```

12.17 Linear Sieve for Other Number Theoretic Functions

d9fd0b

```

1 // linear_sieve(n, primes, lp, phi, mu, d, sigma)
2 // Outputs over the index range 0..n (n >= 1):
3 // primes : all primes in [2..n], increasing.
4 // lp      : lowest prime factor; lp[1]=0, lp[x] is the
5 //            smallest prime dividing x.
6 // phi     : Euler totient, phi[x] = |{1<=k<=x :
7 //            gcd(k,x)=1}|. Multiplicative.
8 // mu      : Möbius; mu[1]=1, mu[x]=0 if x has a squared
9 //            prime factor, else (-1)^{#distinct primes}.
10 // d       : number of divisors; if x=∏ p_i^{e_i}, then
11 //            d[x]=∏(e_i+1). Multiplicative.
12 // sigma  : sum of divisors; if x=∏ p_i^{e_i}, then
13 //            sigma[x]=∏(1+p_i+...+p_i^{e_i}). (use ll)
14 // Complexity: O(n) time, O(n) memory.
15 // Notes: Arrays are resized inside; primes is cleared and
16 //         reserved. sigma uses ll to avoid 32-bit overflow.
17 static inline void linear_sieve(
18     int n,
19     std::vector<int> &primes,
20     std::vector<int> &lp,
21     std::vector<int> &phi,
22     std::vector<int> &mu,
23     std::vector<int> &d,
24     std::vector<ll> &sigma
25 ) {
26     lp.assign(n + 1, 0); phi.assign(n + 1, 0); mu.assign(n +
27     1, 0); d.assign(n + 1, 0); sigma.assign(n + 1, 0);
28     primes.clear(); primes.reserve(n > 1 ? n / 10 : 0);
29     std::vector<int> cnt(n + 1, 0), core(n + 1, 1);
30     std::vector<ll> p_pow(n + 1, 1), sum_p(n + 1, 1);
31     phi[1] = mu[1] = d[1] = sigma[1] = 1;
32     for (int i = 2; i <= n; ++i) {
33         if (!lp[i]) {
34             lp[i] = i; primes.push_back(i);
35             phi[i] = i - 1; mu[i] = -1; d[i] = 2;
36             cnt[i] = 1; p_pow[i] = i; core[i] = 1;
37             sum_p[i] = 1 + (ll)i; sigma[i] = sum_p[i];
38         }
39         for (int p : primes) {
40             long long ip = 1LL * i * p;
41             if (ip > n) break;
42             lp[ip] = p;
43             if (p == lp[i]) {
44                 cnt[ip] = cnt[i] + 1; p_pow[ip] = p_pow[i] * p;
45                 core[ip] = core[i];
46                 sum_p[ip] = sum_p[i] + p_pow[ip];
47                 phi[ip] = phi[i] * p; mu[ip] = 0;
48                 d[ip] = d[core[ip]] * (cnt[ip] + 1);
49                 sigma[ip] = sigma[core[ip]] * sum_p[ip];
50                 break; // critical for linear complexity
51             } else {
52                 cnt[ip] = 1; p_pow[ip] = p; core[ip] = i;

```

```

46     sum_p[ip] = 1 + (ll)p;
47     phi[ip] = phi[i] * (p - 1); mu[ip] = -mu[i];
48     d[ip] = d[i] * 2;
49     sigma[ip] = sigma[i] * sum_p[ip];
50 }
51 }
52 }
53 }
54 // Optional helper: factorize x in O(log x) using lp
  (requires x in [2..n])
55 static inline std::vector<std::pair<int,int>>
  factorize(int x, const std::vector<int>& lp) {
56     std::vector<std::pair<int,int>> res;
57     while (x > 1) {
58         int p = lp[x], e = 0;
59         do { x /= p; ++e; } while (x % p == 0);
60         res.push_back({p, e});
61     }
62     return res;
63 }

```

13 Numerical

13.1 Polynomials and recurrences

```

1/* Author: David Rydh, Per Austrin
2* Description: */
3struct Poly {
4    vector<double> a;
5    double operator()(double x) const {
6        double val = 0;
7        for (int i = sz(a); i--;) (val *= x) += a[i];
8        return val;
9    }
10 void diff() {
11     rep(i, 1, sz(a)) a[i-1] = i*a[i];
12     a.pop_back();
13 }
14 void divroot(double x0) {
15     double b = a.back(), c; a.back() = 0;
16     for (int i = sz(a)-1; i--;) c = a[i], a[i] = a[i+1]*x0+b,
17     b=c;
18     a.pop_back();
19 };
20
21 /* Author: Per Austrin (License: CC0)
22 * Description: Finds the real roots to a polynomial.
23 * Usage: polyRoots({{2, -3, 1}}, -1e9, 1e9) // solve x^2-3x+2 =
24         0
25 * Time: O(n^2 \log(1/\epsilon)) */
26 #include "Polynomial.h"
27 vector<double> polyRoots(Poly p, double xmin, double xmax) {
28     if (sz(p.a) == 2) { return {-p.a[0]/p.a[1]}; }
29     vector<double> ret;
30     Poly der = p;
31     der.diff();
32     auto dr = polyRoots(der, xmin, xmax);
33     dr.push_back(xmin-1);
34     dr.push_back(xmax+1);
35     sort(all(dr));
36     rep(i, 0, sz(dr)-1) {
37         double l = dr[i], h = dr[i+1];
38         bool sign = p(l) > 0;
39         if (sign ^ (p(h) > 0)) {
40             rep(it, 0, 60) { // while (h - l > 1e-8)
41                 double m = (l + h) / 2, f = p(m);
42                 if ((f <= 0) ^ sign) l = m;
43                 else h = m;
44             }
45             ret.push_back((l + h) / 2);
46         }
47     }
48     return ret;
49 }
50
51 /* Author: Simon Lindholm (License: CC0)
52 * Description: Given $n$ points $(x[i], y[i])$, computes an
53 $n-1$-degree polynomial $p$ that
54 * passes through them: $p(x) = a[0]*x^0 + \dots +
55 a[n-1]*x^{n-1}$.
56 * For numerical precision, pick $x[k] = c*\cos(k/(n-1)*\pi)$,
57 $k=0 \dots n-1$.
58 * Time: O(n^2) */
59 typedef vector<double> vd;
60 vd interpolate(vd x, vd y, int n) {
61     vd res(n), temp(n);
62     rep(k, 0, n-1) rep(i, k+1, n)
63         y[i] = (y[i] - y[k]) / (x[i] - x[k]);
64     double last = 0; temp[0] = 1;
65     rep(k, 0, n) rep(i, 0, n) {
66         res[i] += y[k] * temp[i];

```

```

14     swap(last, temp[i]);
15     temp[i] -= last * x[k];
16 }
17 return res;
18 }
19
20 /* Author: koukanni (License: CC0)
21 * Description: Lagrange interpolation for polynomial
22 evaluation at integer points.
23 * Given polynomial values $f[0], f[1], \dots, f[n-1]$, computes
24 $f(c)$.
25 * Time: O(n)
26 * Status: tested */
27 Mint lagrange_iota(const vector<Mint> &f, const int c) {
28     const int n = int(size(f));
29     if (c < n) {
30         return f[c];
31     }
32     vector<Mint> fac(n), ifac(n);
33     fac[0] = 1;
34     for (int i = 1; i < n; i++) fac[i] = fac[i-1] * i;
35     ifac[n-1] = fac[n-1].inv();
36     for (int i = n-1; i >= 1; i--) ifac[i-1] = ifac[i] *
37     i;
38     vector<Mint> g(n);
39     for (int i = 0; i < n; i++) {
40         g[i] = f[i] * ifac[i] * ifac[n-1-i];
41         if ((n-1-i) & 1) g[i] *= -1;
42     }
43     vector<Mint> lp(n+1), rp(n+1);
44     lp[0] = rp[n] = 1;
45     for (int i = 0; i < n; i++) lp[i+1] = lp[i] * Mint(c -
46     i);
47     for (int i = n-1; i >= 0; i--) rp[i] = rp[i+1] *
48     Mint(c - i);
49     Mint ans = 0;
50     for (int i = 0; i < n; i++) ans += g[i] * lp[i] * rp[i +
51     1];
52     return ans;
53 }
54
55 /* Author: Lucian Bicsi (License: CC0)
56 * Description: Recovers any $n$-order linear recurrence
57 relation from the first
58 * $2n$ terms of the recurrence.
59 * Useful for guessing linear recurrences after brute-forcing
60 the first terms.
61 * Should work on any field, but numerical stability for
62 floats is not guaranteed.
63 * Output will have size $\le n$.
64 * Usage: berlekampMassey({0, 1, 1, 3, 5, 11}) // {1, 2}
65 * Time: O(N^2), Status: brute-force-tested mod 5 for $n \le 5$
66 and all $s$ */
67 #include "../number-theory/ModPow.h"
68 vector<ll> berlekampMassey(vector<ll> s) {
69     int n = sz(s), L = 0, m = 0;
70     vector<ll> C(n), B(n), T;
71     C[0] = B[0] = 1;
72     ll b = 1;
73     rep(i, 0, n) { ++m;
74         ll d = s[i] % mod;
75         rep(j, 1, L+1) d = (d + C[j] * s[i-j]) % mod;
76         if (!d) continue;
77         T = C; ll coef = d * modpow(b, mod-2) % mod;
78         rep(j, m, n) C[j] = (C[j] - coef * B[j-m]) % mod;
79         if (2 * L > i) continue;
80         L = i + 1 - L; B = T; b = d; m = 0;
81     }
82     // assert(2 * L + 30 <= n);
83     C.resize(L + 1); C.erase(C.begin());
84     for (ll& x : C) x = (mod - x) % mod;
85     return C;
86 }
87
88 /* Author: Lucian Bicsi (License: CC0)
89 * Description: Generates the $k$'th term of an $n$-order
90 linear recurrence $S[i] = \sum_j S[i-j-1]tr[j]$,
91 * given $S[0] \dots \ge n-1$ and $tr[0] \dots n-1$.
92 * Faster than matrix multiplication.
93 * Useful together with Berlekamp-Massey.
94 * Usage: linearRec({0, 1}, {1, 1}, k) // k'th Fibonacci
95 number
96 * Time: O(n^2 \log k)
97 * Status: brute-force-tested mod 5 for $n \le 5$ */
98 const ll mod = 5; /** exclude-line */
99 typedef vector<ll> Poly;
100 ll linearRec(Poly S, Poly tr, ll k) {
101     int n = sz(tr);
102     auto combine = [&](Poly a, Poly b) {
103         Poly res(n * 2 + 1);
104         rep(i, 0, n+1) rep(j, 0, n+1)

```

```

17     res[i + j] = (res[i + j] + a[i] * b[j]) % mod;
18     for (int i = 2 * n; i > n; --i) rep(j, 0, n)
19         res[i - 1 - j] = (res[i - 1 - j] + res[i] * tr[j]) %
mod;
20     res.resize(n + 1);
21     return res;
22 };
23 Poly pol(n + 1, e(pol);
24 pol[0] = e[1] = 1;
25 for (++k; k; k /= 2) {
26     if (k % 2) pol = combine(pol, e);
27     e = combine(e, e);
28 }
29 ll res = 0;
30 rep(i, 0, n) res = (res + pol[i + 1] * S[i]) % mod;
31 return res;
32 }

```

13.2 Optimization

```

1/* Author: Ulf Lundstrom (License: CC0)
2* Description: Finds the argument minimizing the function
3* $f$ in the interval $[a,b]$
4* assuming $f$ is unimodal on the interval, i.e. has only
5* one local minimum and no local
6* maximum. The maximum error in the result is $eps$. Works
7* equally well for maximization
8* with a small change in the code. See TernarySearch.h in
9* the Various chapter for a
10* discrete version.
11* Usage: double func(double x) { return 4+x-.3*x*x; }
12* double xmin = gss(-1000,1000,func);
13* Time: $O(\log((b-a) / \epsilon))$, Status: tested */
14// It is important for r to be precise, otherwise we don't
15// necessarily maintain the inequality $a < x_1 < x_2 < b$.
16double gss(double a, double b, double (*f)(double)) {
17    double r = (sqrt(5)-1)/2, eps = 1e-7;
18    double x1 = b - r*(b-a), x2 = a + r*(b-a);
19    double f1 = f(x1), f2 = f(x2);
20    while (b-a > eps)
21        if (f1 < f2) { //change to > to find maximum
22            b = x2; x2 = x1; f2 = f1;
23            x1 = b - r*(b-a); f1 = f(x1);
24        } else {
25            a = x1; x1 = x2; f1 = f2;
26            x2 = a + r*(b-a); f2 = f(x2);
27        }
28    return a;
29 }
30
31/* Author: Simon Lindholm (License: CC0)
32* Description: Poor man's optimization for unimodal
33* functions.
34* Status: used with great success */
35typedef array<double, 2> P;
36template<class F> pair<double, P> hillClimb(P start, F f) {
37    pair<double, P> cur(f(start), start);
38    for (double jmp = 1e9; jmp > 1e-20; jmp /= 2) {
39        rep(j, 0, 100) rep(dx, -1, 2) rep(dy, -1, 2) {
40            P p = cur.second;
41            p[0] += dx*jmp;
42            p[1] += dy*jmp;
43            cur = min(cur, make_pair(f(p), p));
44        }
45    }
46    return cur;
47 }
48
49/* Author: Simon Lindholm (License: CC0)
50* Description: Simple integration of a function over an
51* interval using
52* Simpson's rule. The error should be proportional to $h^4$,
53* although in
54* practice you will want to verify that the result is stable
55* to desired
56* precision when epsilon changes.
57* Status: mostly untested */
58template<class F>
59double quad(double a, double b, F f, const int n = 1000) {
60    double h = (b - a) / 2 / n, v = f(a) + f(b);
61    rep(i, 1, n*2)
62        v += f(a + i*h) * (i%4 ? 4 : 2);
63    return v * h / 3;
64 }
65
66/* Author: Simon Lindholm (License: CC0)
67* Description: Fast integration using an adaptive Simpson's
68* rule.
69* Usage:
70* double sphereVolume = quad(-1, 1, [](double x) {
71*     return quad(-1, 1, [](double y) {
72*         return quad(-1, 1, [](double z) {

```

```

73*         return x*x + y*y + z*z < 1; }));});});
74* Status: mostly untested */
75typedef double d;
76#define S(a,b) (f(a) + 4*f((a+b) / 2) + f(b)) * (b-a) / 6
77template<class F>
78d rec(F& f, d a, d b, d eps, d S) {
79    d c = (a + b) / 2;
80    d S1 = S(a, c), S2 = S(c, b), T = S1 + S2;
81    if (abs(T - S) <= 15 * eps || b - a < 1e-10)
82        return T + (T - S) / 15;
83    return rec(f, a, c, eps / 2, S1) + rec(f, c, b, eps / 2,
84        S2);
85 }
86 template<class F>
87 d quad(d a, d b, F f, d eps = 1e-8) {
88     return rec(f, a, b, eps, S(a, b));
89 }
90
91/* Author: Stanford (License: MIT)
92* Description: Solves a general linear maximization problem:
93* maximize $c^T x$ subject to $Ax \le b$, $x \ge 0$.
94* Returns -inf if there is no solution, inf if there are
95* arbitrarily good solutions, or the maximum value of $c^T x$
96* otherwise.
97* The input vector is set to an optimal $x$ (or in the
98* unbounded case, an arbitrary solution fulfilling the
99* constraints).
100* Numerical stability is not guaranteed. For better
101* performance, define variables such that $x = 0$ is viable.
102* Usage:
103* vvd A = {{1,-1}, {-1,1}, {-1,-2}};
104* vd b = {1,1,-4}, c = {-1,-1}, x;
105* T val = LPSolver(A, b, c).solve(x);
106* Time: $O(NM * \log(\text{pivots}))$, where a pivot may be e.g. an edge
107* relaxation. $O(2^n)$ in the general case.
108* Status: seems to work? */
109typedef double T; // long double, Rational, double +
110mod<P>...
111typedef vector<T> vd;
112typedef vector<vd> vvd;
113const T eps = 1e-8, inf = 1/.0;
114#define MP make_pair
115#define ltj(X) if(s == -1 || MP(X[j],N[j]) < MP(X[s],N[s]))
116    s=j
117struct LPSolver {
118    int m, n; vi N, B; vvd D;
119    LPSolver(const vvd& A, const vd& b, const vd& c) :
120        m(sz(b)), n(sz(c)), N(n+1), B(m), D(m+2, vd(n+2)) {
121        rep(i, 0, m) rep(j, 0, n) D[i][j] = A[i][j];
122        rep(i, 0, m) { B[i] = n+1; D[i][n] = -1; D[i][n+1] =
123            b[i]; }
124        rep(j, 0, n) { N[j] = j; D[m][j] = -c[j]; }
125        N[n] = -1; D[m+1][n] = 1;
126    }
127    void pivot(int r, int s) {
128        T *a = D[r].data(), inv = 1 / a[s];
129        rep(i, 0, m+2) if (i != r && abs(D[i][s]) > eps) {
130            T *b = D[i].data(), inv2 = b[s] * inv;
131            rep(j, 0, n+2) b[j] -= a[j] * inv2;
132            b[s] = a[s] * inv2;
133        }
134        rep(j, 0, n+2) if (j != s) D[r][j] *= inv;
135        rep(i, 0, m+2) if (i != r) D[i][s] *= -inv;
136        D[r][s] = inv;
137        swap(B[r], N[s]);
138    }
139    bool simplex(int phase) {
140        int x = m + phase - 1;
141        for (;;) {
142            int s = -1;
143            rep(j, 0, n+1) if (N[j] != -phase) ltj(D[x]);
144            if (D[x][s] >= -eps) return true;
145            int r = -1;
146            rep(i, 0, m) {
147                if (D[i][s] <= eps) continue;
148                if (r == -1 || MP(D[i][n+1] / D[i][s], B[i])
149                    < MP(D[r][n+1] / D[r][s], B[r])) r = i;
150            }
151            if (r == -1) return false;
152            pivot(r, s);
153        }
154    }
155    T solve(vd &x) {
156        int r = 0;
157        rep(i, 1, m) if (D[i][n+1] < D[r][n+1]) r = i;
158        if (D[r][n+1] < -eps) {
159            pivot(r, n);
160            if (!simplex(2) || D[m+1][n+1] < -eps) return -inf;
161            rep(i, 0, m) if (B[i] == -1) {
162                int s = 0;

```

```

63     rep(j,1,n+1) ltj(D[i]);
64     pivot(i, s);
65 }
66 }
67 bool ok = simplex(1); x = vd(n);
68 rep(i,0,m) if (B[i] < n) x[B[i]] = D[i][n+1];
69 return ok ? D[m][n+1] : inf;
70 }
71 };

```

13.3 Matrices

```

1/* Author: Simon Lindholm (License: CC0)
2* Description: Calculates determinant of a matrix. Destroys
the matrix.
3* Time:  $O(N^3)$ , Status: somewhat tested */
4double det(vector<vector<double>>& a) {
5    int n = sz(a); double res = 1;
6    rep(i,0,n) {
7        int b = i;
8        rep(j,i+1,n) if (fabs(a[j][i]) > fabs(a[b][i])) b = j;
9        if (i != b) swap(a[i], a[b]), res *= -1;
10       res *= a[i][i];
11       if (res == 0) return 0;
12       rep(j,i+1,n) {
13           double v = a[j][i] / a[i][i];
14           if (v != 0) rep(k,i+1,n) a[j][k] -= v * a[i][k];
15       }
16   }
17   return res;
18 }
19
20 /* Author: Unknown
21 * Description: Calculates determinant using modular
arithmetic.
22 * Modulos can also be removed to get a pure-integer version.
23 * Time:  $O(N^3)$ 
24 * Status: brute-force-tested for  $N \leq 3$ , mod  $\leq 7$  */
25 const ll mod = 12345;
26 ll det(vector<vector<ll>>& a) {
27     int n = sz(a); ll ans = 1;
28     rep(i,0,n) {
29         rep(j,i+1,n) {
30             while (a[j][i] != 0) { // gcd step
31                 ll t = a[i][i] / a[j][i];
32                 if (t) rep(k,i,n)
33                     a[i][k] = (a[i][k] - a[j][k] * t) % mod;
34                 swap(a[i], a[j]);
35                 ans *= -1;
36             }
37         }
38         ans = ans * a[i][i] % mod;
39         if (!ans) return 0;
40     }
41     return (ans + mod) % mod;
42 }
43
44 /* Author: Per Austrin, Simon Lindholm (License: CC0)
45 * Description: Solves  $AX = B$ . If there are multiple
solutions, an arbitrary one is returned.
46 * Returns rank, or -1 if no solutions. Data in  $A$  and  $B$ 
is lost.
47 * Time:  $O(n^2 m)$ 
48 * Status: tested on kattis:equationsolver, and brute-force-
tested mod 3 and 5 for  $n, m \leq 3$  */
49 typedef vector<double> vd;
50 const double eps = 1e-12;
51 int solveLinear(vector<vd>& A, vd& b, vd& x) {
52     int n = sz(A), m = sz(x), rank = 0, br, bc;
53     if (n) assert(sz(A[0]) == m);
54     vi col(m); iota(all(col), 0);
55     rep(i,0,n) {
56         double v, bv = 0;
57         rep(r,i,n) rep(c,i,m)
58             if ((v = fabs(A[r][c])) > bv)
59                 br = r, bc = c, bv = v;
60         if (bv <= eps) {
61             rep(j,i,n) if (fabs(b[j]) > eps) return -1;
62             break;
63         }
64         swap(A[i], A[br]);
65         swap(b[i], b[br]);
66         swap(col[i], col[bc]);
67         rep(j,0,n) swap(A[j][i], A[j][bc]);
68         bv = 1/A[i][i];
69         rep(j,i+1,n) {
70             double fac = A[j][i] * bv;
71             b[j] -= fac * b[i];
72             rep(k,i+1,m) A[j][k] -= fac * A[i][k];
73         }
74         rank++;
75     }
76 }

```

```

33 x.assign(m, 0);
34 for (int i = rank; i--;) {
35     b[i] /= A[i][i];
36     x[col[i]] = b[i];
37     rep(j,0,i) b[j] -= A[j][i] * b[i];
38 }
39 return rank; // (multiple solutions if rank < m)
40 }
41
42 /* Author: Simon Lindholm (License: CC0)
43 * Description: To get all uniquely determined values of  $x$ 
back from SolveLinear, make the following changes:
44 * Status: tested on kattis:equationsolverplus, stress-tested
*/
45 #include "SolveLinear.h"
46 rep(j,0,n) if (j != i) // instead of rep(j,i+1,n)
47 // ... then at the end:
48 x.assign(m, undefined);
49 rep(i,0,rank) {
50     rep(j,rank,m) if (fabs(A[i][j]) > eps) goto fail;
51     x[col[i]] = b[i] / A[i][i];
52 fail; }
53
54 /* Author: Simon Lindholm (License: CC0)
55 * Description: Solves  $AX = B$  over  $\mathbb{F}_2$ . If there
are multiple solutions, one is returned arbitrarily.
56 * Returns rank, or -1 if no solutions. Destroys  $A$  and  $B$ .
57 * Time:  $O(n^2 m)$ 
58 * Status: brute-force-tested for  $n, m \leq 4$  */
59 typedef bitset<1000> bs;
60 int solveLinear(vector<bs>& A, vi& b, bs& x, int m) {
61     int n = sz(A), rank = 0, br;
62     assert(m <= sz(x));
63     vi col(m); iota(all(col), 0);
64     rep(i,0,n) {
65         for (br=i; br<n; ++br) if (A[br].any()) break;
66         if (br == n) {
67             rep(j,i,n) if (b[j]) return -1;
68             break;
69         }
70         int bc = (int)A[br]._Find_next(i-1);
71         swap(A[i], A[br]);
72         swap(b[i], b[br]);
73         swap(col[i], col[bc]);
74         rep(j,0,n) if (A[j][i] != A[j][bc]) {
75             A[j].flip(i); A[j].flip(bc);
76         }
77         rep(j,i+1,n) if (A[j][i]) {
78             b[j] ^= b[i];
79             A[j] ^= A[i];
80         }
81         rank++;
82     }
83     x = bs();
84     for (int i = rank; i--;) {
85         if (!b[i]) continue;
86         x[col[i]] = 1;
87         rep(j,0,i) b[j] ^= A[j][i];
88     }
89     return rank; // (multiple solutions if rank < m)
90 }
91
92 /* Author: Max Bennedich
93 * Description: Invert matrix  $A$ . Returns rank; result is
stored in  $A$  unless singular (rank < n).
94 * Can easily be extended to prime moduli; for prime powers,
repeatedly
95 * set  $A^{-1} = A^{-1} (2I - AA^{-1}) \pmod{p^k}$ 
where  $A^{-1}$  starts as
96 * the inverse of  $A \pmod{p}$ , and  $k$  is doubled in each step.
97 * Time:  $O(n^3)$ 
98 * Status: Slightly tested */
99 int matInv(vector<vector<double>>& A) {
100     int n = sz(A); vi col(n);
101     vector<vector<double>> tmp(n, vector<double>(n));
102     rep(i,0,n) tmp[i][i] = 1, col[i] = i;
103     rep(i,0,n) {
104         int r = i, c = i;
105         rep(j,i,n) rep(k,i,n)
106             if (fabs(A[j][k]) > fabs(A[r][c]))
107                 r = j, c = k;
108         if (fabs(A[r][c]) < 1e-12) return i;
109         A[i].swap(A[r]); tmp[i].swap(tmp[r]);
110         rep(j,0,n)
111             swap(A[j][i], A[j][c]), swap(tmp[j][i], tmp[j][c]);
112         double v = A[i][i];
113         rep(j,i+1,n) {
114             double f = A[j][i] / v;
115             A[j][i] = 0;

```

```

26     rep(k,i+1,n) A[j][k] -= f*A[i][k];
27     rep(k,0,n) tmp[j][k] -= f*tmp[i][k];
28 }
29 rep(j,i+1,n) A[i][j] /= v;
30 rep(j,0,n) tmp[i][j] /= v;
31 A[i][i] = 1;
32 }
33 // forget A at this point, just eliminate tmp backward
34 for (int i = n-1; i > 0; --i) rep(j,0,i) {
35     double v = A[j][i];
36     rep(k,0,n) tmp[j][k] -= v*tmp[i][k];
37 }
38 rep(i,0,n) rep(j,0,n) A[col[i]][col[j]] = tmp[i][j];
39 return n;
40 }

1/* Author: Simon Lindholm
2 * Description: Invert matrix $A$ modulo a prime.
3 * Returns rank; result is stored in $A$ unless singular
  (rank < n).
4 * For prime powers, repeatedly set $A^{-1} = A^{-1} (2I -
  AA^{-1}) \pmod{p^k}$ where $A^{-1}$ starts as
5 * the inverse of $A \bmod p$, and $k$ is doubled in each step.
6 * Time: $O(n^3)$
7 * Status: Slightly tested */
8#include "../number-theory/ModPow.h"
9int matInv(vector<vector<ll>>& A) {
10    int n = sz(A); vi col(n);
11    vector<vector<ll>> tmp(n, vector<ll>(n));
12    rep(i,0,n) tmp[i][i] = 1, col[i] = i;
13    rep(i,0,n) {
14        int r = i, c = i;
15        rep(j,i,n) rep(k,i,n) if (A[j][k]) {
16            r = j; c = k; goto found;
17        }
18        return i;
19    found:
20        A[i].swap(A[r]); tmp[i].swap(tmp[r]);
21        rep(j,0,n)
22            swap(A[j][i], A[j][c]), swap(tmp[j][i], tmp[j][c]);
23        swap(col[i], col[c]);
24        ll v = modpow(A[i][i], mod - 2);
25        rep(j,i+1,n) {
26            ll f = A[j][i] * v % mod;
27            A[j][i] = 0;
28            rep(k,i+1,n) A[j][k] = (A[j][k] - f*A[i][k]) % mod;
29            rep(k,0,n) tmp[j][k] = (tmp[j][k] - f*tmp[i][k]) %
mod;
30        }
31        rep(j,i+1,n) A[i][j] = A[i][j] * v % mod;
32        rep(j,0,n) tmp[i][j] = tmp[i][j] * v % mod;
33        A[i][i] = 1;
34    }
35    for (int i = n-1; i > 0; --i) rep(j,0,i) {
36        ll v = A[j][i];
37        rep(k,0,n) tmp[j][k] = (tmp[j][k] - v*tmp[i][k]) % mod;
38    }
39    rep(i,0,n) rep(j,0,n)
40        A[col[i]][col[j]] = tmp[i][j] % mod + (tmp[i][j] <
0)*mod;
41    return n;
42 }

1/* Author: Ulf Lundstrom, Simon Lindholm (License: CC0)
2 * Description: Solves the tridiagonal matrix equation
  system:
3 * [ b_0 ] [ d_0 p_0 0 0 ... 0 ] [ x_0 ]
4 * [ b_1 ] [ q_0 d_1 p_1 0 ... 0 ] [ x_1 ]
5 * [ b_2 ] [ 0 q_1 d_2 p_2 ... 0 ] [ x_2 ]
6 * [ ... ] [ ... ... ... ... ... ] [ ... ]
7 * [ b_{n-1} ] [ 0 0 ... 0 q_{n-2} d_{n-1} ] [ x_{n-1} ]
8 * Application:
9 * Solves linear recurrence systems of the form:
10 * a_i = b_i * a_{i-1} + c_i * a_{i+1} + d_i (1 <= i <=
n)
11 * where a_0, a_{n+1}, b_i, c_i, and d_i are given.
12 * The solution vector a can be obtained via:
13 * d = { 1, -1, -1, ..., -1, 1 }
14 * p = { 0, c_1, c_2, ..., c_n }
15 * q = { b_1, b_2, ..., b_n, 0 }
16 * b = { a_0, d_1, d_2, ..., d_n, a_{n+1} }
17 * Numerical Stability:
18 * - Fails if the solution is not unique.
19 * - Numerically stable without pivot checks if:
20 * 1) Strictly diagonally dominant:
21 * |d_i| > |p_i| + |q_{i-1}| for all i, OR
22 * |d_i| > |p_{i-1}| + |q_i| for all i
23 * 2) The matrix is symmetric positive-definite.
24 * Complexity: O(N) time, O(N) space. Status: Brute-force
  tested mod 5 and 7, stress-tested for real matrices. */

```

```

25 typedef double T;
26 vector<T> tridiagonal(vector<T> diag, const vector<T>&
super,
27     const vector<T>& sub, vector<T> b) {
28     int n = sz(b); vi tr(n);
29     rep(i,0,n-1) {
30         if (abs(diag[i]) < 1e-9 * abs(super[i])) { // diag[i] ==
0
31             b[i+1] -= b[i] * diag[i+1] / super[i];
32             if (i+2 < n) b[i+2] -= b[i] * sub[i+1] / super[i];
33             diag[i+1] = sub[i]; tr[i+1] = 1;
34         } else {
35             diag[i+1] -= super[i]*sub[i]/diag[i];
36             b[i+1] -= b[i]*sub[i]/diag[i];
37         }
38     }
39     for (int i = n; i--;) {
40         if (tr[i]) {
41             swap(b[i], b[i-1]);
42             diag[i-1] = diag[i];
43             b[i] /= super[i-1];
44         } else {
45             b[i] /= diag[i];
46             if (i) b[i-1] -= b[i]*super[i-1];
47         }
48     }
49     return b;
50 }

```

13.4 Fourier transforms

```

1/**
2 * Author: chilli, Ludo Pulles, Simon Lindholm (License:
  CC0)
3 * Description: Higher precision FFT, can be used for
  convolutions modulo arbitrary integers
4 * as long as N log_2 N * mod < 8.6e14 (in practice 10^16 or
  higher).
5 * Inputs must be in [0, mod).
6 * Time: O(N log N), where N = |A| + |B| (twice as slow as
  NTT or normal FFT), Status: stress-tested */
7 typedef complex<double> C;
8 typedef vector<ll> vl;
9 void fft(vector<C>& a) {
10     int n = sz(a), L = 31 - __builtin_clz(n);
11     static vector<complex<long double>> R(2, 1);
12     static vector<C> rt(2, 1);
13     for (static int k = 2; k < n; k *= 2) {
14         R.resize(n); rt.resize(n);
15         auto x = polar(1.0L, acos(-1.0L) / k);
16         rep(i, k, 2 * k) rt[i] = R[i] = i & 1 ? R[i / 2] * x :
R[i / 2];
17     }
18     vi rev(n);
19     rep(i, 0, n) rev[i] = (rev[i / 2] | (i & 1) << L) / 2;
20     rep(i, 0, n) if (i < rev[i]) swap(a[i], a[rev[i]]);
21     for (int k = 1; k < n; k *= 2)
22         for (int i = 0; i < n; i += 2 * k) rep(j, 0, k) {
23             auto x = (double *)&rt[j + k], y = (double *)&a[i + j
+ k];
24             C z(x[0] * y[0] - x[1] * y[1], x[0] * y[1] + x[1] *
y[0]);
25             a[i + j + k] = a[i + j] - z;
26             a[i + j] += z;
27         }
28 }
29 template<int M> vl convMod(const vl &a, const vl &b) {
30     if (a.empty() || b.empty()) return {};
31     vl res(sz(a) + sz(b) - 1);
32     int B = 32 - __builtin_clz(sz(res)), n = 1 << B, cut =
int(sqrt(M));
33     vector<C> L(n), R(n), outs(n), outl(n);
34     rep(i, 0, sz(a)) L[i] = C((int)a[i] / cut, (int)a[i] %
cut);
35     rep(i, 0, sz(b)) R[i] = C((int)b[i] / cut, (int)b[i] %
cut);
36     fft(L), fft(R);
37     rep(i, 0, n) {
38         int j = -i & (n - 1);
39         outl[j] = (L[i] + conj(L[j])) * R[i] / (2.0 * n);
40         outs[j] = (L[i] - conj(L[j])) * R[i] / (2.0 * n) / 1i;
41     }
42     fft(outl), fft(outs);
43     rep(i, 0, sz(res)) {
44         ll av = ll(real(outl[i]) + .5), cv = ll(imag(outs[i])
+ .5);
45         ll bv = ll(imag(outl[i]) + .5) + ll(real(outs[i]) + .5);
46         res[i] = ((av % M * cut + bv) % M * cut + cv) % M;
47     }
48     return res;
49 }

```

```

1/* Author: Lucian Bicsi (License: GNU Free Documentation
   License 1.2)
2* Description: Transform to a basis with fast convolutions
   of the form
3* c[z] = \sum_{z = x \oplus y} a[x] * b[y]
4* where \oplus is one of AND, OR, XOR.
5* The size of $a$ must be a power of 2.
6* Time: $O(N \log N)$, Status: stress-tested */
7void FST(vi& a, bool inv) {
8    for (int n = sz(a), step = 1; step < n; step *= 2) {
9        for (int i = 0; i < n; i += 2 * step) rep(j, i, i+step) {
10            int &u = a[j], &v = a[j + step]; tie(u, v) =
11                inv ? pii(v - u, u) : pii(v, u + v); // AND
12                // inv ? pii(v, u - v) : pii(u + v, u); // OR ///
13            include-line
14                // pii(u + v, u - v); // XOR ///
15            include-line
16        }
17    }
18    // if (inv) for (int& x : a) x /= sz(a); // XOR only ///
19    include-line
20}
21vi conv(vi a, vi b) {
22    FST(a, 0); FST(b, 0);
23    rep(i, 0, sz(a)) a[i] *= b[i];
24    FST(a, 1); return a;
25}

```

- Useful bounds: $n \leq 10^6 \Rightarrow \tau(n) \leq 240$
 $n \leq 10^9 \Rightarrow \tau(n) \leq 1344$
 $n \leq 10^{12} \Rightarrow \tau(n) \leq 6720$
 $n \leq 10^{15} \Rightarrow \tau(n) \leq 26880$
 $n \leq 10^{18} \Rightarrow \tau(n) \leq 103680$

15.4 Distinct Prime Factors

- Let $\omega(n)$ = number of distinct prime factors.
- Minimum number with k distinct prime factors is the product of the first k primes.
 - $2 \cdot 3 \cdot 5 \cdot 7 \cdot 11 \cdot 13 \cdot 17 \cdot 19 = 9699690$
 - $2 \cdot 3 \cdot \dots \cdot 23 = 223092870$
 - $2 \cdot 3 \cdot \dots \cdot 29 = 6469693230$
 - $n \leq 10^9 \Rightarrow \omega(n) \leq 9, n \leq 10^{18} \Rightarrow \omega(n) \leq 15$
- Number of square-free divisors = $2^{\omega(n)}$
 - $n \leq 10^9 \Rightarrow \leq 512, n \leq 10^{18} \Rightarrow \leq 32768$

14 Combinatorics

14.1 Catalan Number

$$C_0 = 1, C_n = \sum_{i=0}^{n-1} C_i C_{n-1-i}, C_n = C_n^{2n} - C_{n-1}^{2n}$$

0	1	1	2	5
4	14	42	132	429
8	1430	4862	16796	58786
12	208012	742900	2674440	9694845

14.2 Bertrand's Ballot Theorem

- A always $> B$: $C(p+q, p) - 2C(p+q-1, p)$
- A always $\geq B$: $C(p+q, p) \times \frac{p+1-q}{p+1}$

14.3 Burnside's Lemma

Let X be the original set.

Let G be the group of operations acting on X .

Let X^g be the set of x not affected by g .

Let X/G be the set of orbits. Then the following equation holds:

$$|X/G| = \frac{1}{|G|} \sum_{g \in G} |X^g|$$

15 Special Numbers

15.1 Fibonacci Series

1	1	1	2	3
5	5	8	13	21
9	34	55	89	144
13	233	377	610	987
17	1597	2584	4181	6765
21	10946	17711	28657	46368
25	75025	121393	196418	317811
29	514229	832040	1346269	2178309
33	3524578	5702887	9227465	14930352

$$f(45) \approx 10^9, f(88) \approx 10^{18}$$

15.2 Prime Numbers

- $\pi(n) \equiv$ Number of primes $\leq n \approx \frac{n}{(\ln n)-1}$
 $\pi(100) = 25, \pi(200) = 46$
 $\pi(500) = 95, \pi(1000) = 168$
 $\pi(2000) = 303, \pi(4000) = 550$
 $\pi(10^4) = 1229, \pi(10^5) = 9592$
 $\pi(10^6) = 78498, \pi(10^7) = 664579$

15.3 Number of Divisors

- If $n = \prod p_i^{a_i}$, then $\tau(n) = \prod (a_i + 1)$
- Maximum $\tau(n)$ for $n \leq 10^k$:

k	$\max \tau(n)$	k	$\max \tau(n)$	k	$\max \tau(n)$
3	32	9	1344	15	26880
4	64	10	2304	16	41472
5	128	11	4032	17	64512
6	240	12	6720	18	103680
7	448	13	10752		
8	768	14	17280		