

1	Reminder	1
1.1	Observations and Tricks	1
1.2	Bug List	1
2	Init (Linux)	1
2.1	vimrc	2
2.2	run.sh	2
3	Basic	2
3.1	PBDS	2
3.2	Random	2
4	Python	2
4.1	I/O	2
4.2	Decimal	2
5	Data Structure	2
5.1	CDQ	2
5.2	Mo's Algorithm	3
5.3	Heavy Light Decomposition	3
5.4	Leftist Heap	3
5.5	Persistent Treap	3
5.6	Li Chao Tree	3
5.7	Time Segment Tree	3
6	DP	4
6.1	Aliens	4
6.2	SOS DP	5
6.3	期望 DP (Expected Value DP)	5
6.4	數位 DP (Digit DP)	5
7	Graph	5
7.1	Blossom	5
7.2	Weighted Blossom	6
7.3	Max Clique	7
7.4	Bellman-Ford + SPFA	7
7.5	BCC - AP	8
7.6	BCC - Bridge	8
7.7	SCC - Tarjan with 2-SAT	8
7.8	Eulerian Path - Undir	9
7.9	Eulerian Path - Dir	9
7.10	Kth Shortest Path	9
7.11	System of Difference Constraints	10
8	String	10
8.1	Rolling Hash	10
8.2	Trie	10
8.3	KMP	10
8.4	Z Value	10
8.5	Manacher	10
8.6	Suffix Array	11
8.7	Suffix Automaton	11
8.8	SA-IS	11
8.9	Minimum Rotation	11
8.10	Aho Corasick	12
9	Geometry	12
9.1	Template	12
9.2	Basic Operations	12
9.3	Lower Concave Hull	12
9.4	Pick's Theorem	13
9.5	Minimum Enclosing Circle	13
9.6	PolyUnion	13
9.7	Minkowski Sum	13
10	Number Theory	14
10.1	Prime Sieve and Defactor	14
10.2	Harmonic Series	14
10.3	Count Number of Divisors	14
10.4	數論分塊	14
10.5	Pollard's rho	14
10.6	Miller Rabin	15
10.7	Discrete Log	15
10.8	Discrete Sqrt	15
10.9	Fast Power	15
10.10	Extend GCD	15
10.11	Mu + Phi	16
10.12	Other Formulas	16
10.13	Polynomial	16
10.14	Counting Primes	17
10.15	Linear Sieve for Other Number Theoretic Functions	17
11	Linear Algebra	18
11.1	Gaussian-Jordan Elimination	18
11.2	Determinant	18
12	Flow / Matching	18
12.1	Flow Methods	18
12.2	Dinic	18
12.3	ISAP	19
12.4	Bounded Max Flow	20
12.5	MCMF	20
12.6	Hopcroft-Karp	20
12.7	Cover / Independent Set	21
12.8	Kuhn Munkres	21
13	Combinatorics	21
13.1	Catalan Number	21
13.2	Bertrand's Ballot Theorem	21
13.3	Burnside's Lemma	21
14	Special Numbers	21
14.1	Fibonacci Series	21
14.2	Prime Numbers	21

1 Reminder

1.1 Observations and Tricks

- Contribution Technique
- 二分圖/Spanning Tree/DFS Tree
- 行、列操作互相獨立
- 奇偶性
- 當 s, t 遞增並且 $t = f(s)$ ，對 s 二分搜不好做，可以改成對 t 二分搜，再算 $f(t)$
- 啟發式合併
- Permutation Normalization (做一些平移對齊兩個 permutation)
- 枚舉 $a_1 \sim a_n$ 再枚舉 $a_n \sim a_1$ 可以包在一個迴圈
- 兩個凸型函數相加還是凸型函數，相減不一定
- 一個區間的 $\text{mex} = k$ ，表示這個區間包含 $0 \sim k-1$ 所有數字，並且「 U - 區間」的最小值 $= k$ 。

1.2 Bug List

- 沒開 long long
- 陣列截出界／陣列開不夠大
- 寫好的函式忘記呼叫
- 0-base / 1-base
- 忘記初始化
- == 打成 =
- <= 打成 <+
- dp[i] 從 dp[i-1] 轉移時忘記特判 $i > 0$
- std::sort 比較運算子寫成 $<$ 或是讓 $=$ 的情況為 true
- 漏 case
- 線段樹改值懶標初始值不能設為 0
- DFS 的時候不小心覆寫到全域變數
- 浮點數誤差
- unsigned int128
- 多筆測資不能沒讀完直接 return
- 記得刪 cerr
- vector 超級肥，小 vector 請用 array，例如矩陣快速冪



2 Init (Linux)

開場流程：

```

1 vim ~/.vimrc
2 mkdir contest && cd contest
3
4 vim template.cpp
5 for c in {A..P}; do
6     cp template.cpp $c.cpp

```

```
7 done
8
9 vim run.sh && chmod 777 run.sh
```

2.1 vimrc

```
1 syn on
2 set nu rnu ru cul mouse=a
3 set cin et ts=4 sw=4 sts=4
4 set autochdir
5 set clipboard=unnamedplus
6
7 colo koehler
8
9 no <C-h> ^
10 no <C-l> $
11 no ; :
12
13 inoremap {<CR> {<CR>}<Esc>ko
```

2.2 run.sh

```
1#!/bin/bash
2
3g++ -std=c++17 -O2 -g -fsanitize=undefined,address $1 &&
4echo DONE COMPILE || exit 1
5./a.out
```

3 Basic

3.1 PBDS

```
1#include <bits/extc++.h>
2using namespace __gnu_pbds;
3
4// map
5tree<int, int, less<>, rb_tree_tag,
6  tree_order_statistics_node_update> tr;
7tr.order_of_key(element);
8tr.find_by_order(rank);
9
10// set
11tree<int, null_type, less<>, rb_tree_tag,
12  tree_order_statistics_node_update> tr;
13tr.order_of_key(element);
14tr.find_by_order(rank);
15
16// priority queue
17__gnu_pbds::priority_queue<int, less<int> > big_q; // Big First
18__gnu_pbds::priority_queue<int, greater<int> > small_q; // Small First
19
20ol.join(a2); // join
```

3.2 Random

```
1mt19937
2gen(chrono::steady_clock::now().time_since_epoch().count());
3#define RANDINT(a, b) uniform_int_distribution<int>(a, b)(rng) // inclusive
4#define RANDLL(a, b) uniform_int_distribution<long long>(a, b)(rng) // inclusive
5#define RANDFLOAT(a, b) uniform_real_distribution<float>(a, b)(rng) // exclusive
6#define RANDDOUBLE(a, b) uniform_real_distribution<double>(a, b)(rng) // exclusive
7shuffle(v.begin(), v.end(), gen);
```

4 Python

4.1 I/O

```
1import sys
2input = sys.stdin.readline
3
4# Input
5def readInt():
6    return int(input())
7def readIntList():
8    return list(map(int, input().split()))
9def readStr():
10    s = input()
11    return list(s[:len(s) - 1])
12def readInts():
13    return map(int, input().split())
```

4.2 Decimal

```
1from decimal import *
2getcontext().prec = 500 # precision
3getcontext().Emax = 500 # 科學記號指數最大值
4# 將東西轉成 Decimal
5Decimal(x)
6Decimal(y)
7Decimal(0.0)
8# 運算子跟一般浮點數一樣
9x *= y
10# 輸出
11print(x.quantize(Decimal("0.000001"),
12  rounding=ROUND_HALF_EVEN))
13# ROUND_CEILING (2.9=>3, -2.1=>-2)
```

```
13# ROUND_FLOOR (2.1=>2, -2.9=>-3)
14# ROUND_HALF_EVEN (2.5=>2, 3.5=>4)
15# ROUND_HALF_UP (2.5=>3, -2.5=>-3)
16# ROUND_HALF_DOWN (2.5=>2, -2.5=>-2)
17# ROUND_UP (2.1=>3, -2.1=>-3)
18# ROUND_DOWN (2.9=>2, -2.9=>-2)
```

5 Data Structure

5.1 CDQ

```
1// preparation
2// 1. write a 1-base BIT
3// 2. init(n, mxc): n is number of elements, mxc = 值域
4// 3. build info array CDQ.v by yourself (x, y, z, id)
5// 4. call solve()
6// => cdq.ans[i] is number of j s.t. (xj <= xi, yj <= yi, zj <= zi) (j != i)
7struct CDQ {
8    struct info {
9        int x, y, z, id;
10        info(int x, int y, int z, int id):
11            x(x), y(y), z(z), id(id) {}
12        info():
13            x(0), y(0), z(0), id(0) {}
14    };
15    int n, mxc;
16    BIT bit;
17    vector<info> v;
18    vector<ll> ans;
19    void init(int _n, int _mxc) {
20        n = _n; mxc = _mxc;
21        v.assign(n, info{});
22        ans.assign(n, 0);
23    }
24    void dfs(int l, int r) {
25        if (l >= r) return;
26        int mid = (l+r) >> 1;
27        dfs(l, mid); dfs(mid+1, r);
28
29        vector<info> tmp;
30        vector<int> bit_op;
31        int pl = l, pr = mid+1;
32
33        while (pl <= mid && pr <= r) {
34            if (v[pl].y <= v[pr].y) {
35                tmp.emplace_back(v[pl]);
36                bit.upd(v[pl].z, 1);
37                bit_op.emplace_back(v[pl].z);
38                pl++;
39            }
40            else {
41                tmp.emplace_back(v[pr]);
42                ans[v[pr].id] += bit.qry(v[pr].z);
43                pr++;
44            }
45        }
46        while (pl <= mid) {
47            tmp.emplace_back(v[pl]);
48            pl++;
49        }
50        while (pr <= r) {
51            tmp.emplace_back(v[pr]);
52            ans[v[pr].id] += bit.qry(v[pr].z);
53            pr++;
54        }
55        for (int i = l, j = 0; i <= r; i++, j++) v[i] = tmp[j];
56        for (auto& op : bit_op) bit.upd(op, -1);
57    }
58    void solve() {
59        bit.init(mxc);
60        sort(v.begin(), v.end(), [&](const info& a, const info& b){
61            return (a.x == b.x ? (a.y == b.y ? (a.z == b.z ?
62                a.id < b.id : a.z < b.z) : a.y < b.y) : a.x < b.x);
63        });
64        dfs(0, n-1);
65        map<pair<int, pii>, int> s;
66        sort(v.begin(), v.end(), [&](const info& a, const info& b){
67            return a.id > b.id;
68        });
69        for (int i = 0, id = n-1; i < n; i++, id--) {
70            pair<int, pii> tmp = make_pair(v[i].x,
71                make_pair(v[i].y, v[i].z));
72            auto it = s.find(tmp);
73            if (it != s.end())
74                ans[id] += it->second;
75            s[tmp]++;
76        }
77    }
78}
```

```
75 }
76};
```

5.2 Mo's Algorithm

```
1// segments are 0-based
2ll cur = 0; // current answer
3int pl = 0, pr = -1;
4for (auto& qi : Q) {
5    // get (l, r, qid) from qi
6    while (pl < l) del(pl++);
7    while (pl > l) add(--pl);
8    while (pr < r) add(++pr);
9    while (pr > r) del(pr--);
10    ans[qid] = cur;
11}
```

5.3 Heavy Light Decomposition

```
1// Author: Ian
2void build(V<int>&v);
3void modify(int p, int k);
4int query(int ql, int qr);
5// Insert [ql, qr] segment tree here
6inline void solve(){
7    int n, q; cin >> n >> q;
8    V<int> v(n);
9    for (auto& i: v) cin >> i;
10    V<V<int>> e(n);
11    for(int i = 1; i < n; i++){
12        int a, b; cin >> a >> b, a--, b--;
13        e[a].emplace_back(b);
14        e[b].emplace_back(a);
15    }
16    V<int> d(n, 0), f(n, 0), sz(n, 1), son(n, -1);
17    F<void(int, int)> dfs1 = [&](int x, int pre) {
18        for (auto i: e[x]) if (i != pre) {
19            d[i] = d[x]+1, f[i] = x;
20            dfs1(i, x), sz[x] += sz[i];
21            if (son[x] == -1 || sz[son[x]] < sz[i])
22                son[x] = i;
23        }
24    }; dfs1(0, 0);
25    V<int> top(n, 0), dfn(n, -1);
26    F<void(int, int)> dfs2 = [&](int x, int t) {
27        static int cnt = 0;
28        dfn[x] = cnt++, top[x] = t;
29        if (son[x] == -1) return;
30        dfs2(son[x], t);
31        for (auto i: e[x]) if (!dfn[i])
32            dfs2(i, i);
33    }; dfs2(0, 0);
34    V<int> dfnv(n);
35    for (int i = 0; i < n; i++)
36        dfnv[dfn[i]] = v[i];
37    build(dfnv);
38    while(q--){
39        int op, a, b, ans; cin >> op >> a >> b;
40        switch(op){
41            case 1:
42                modify(dfn[a-1], b);
43                break;
44            case 2:
45                a--, b--, ans = 0;
46                while (top[a] != top[b]) {
47                    if (d[top[a]] > d[top[b]]) swap(a, b);
48                    ans = max(ans, query(dfn[top[a]], dfn[b]+1));
49                    b = f[top[b]];
50                }
51                if (dfn[a] > dfn[b]) swap(a, b);
52                ans = max(ans, query(dfn[a], dfn[b]+1));
53                cout << ans << endl;
54                break;
55        }
56    }
57}
```

5.4 Leftist Heap

```
1// Author: Ian
2// Function: min-heap, with worst-time O(lg n) merge
3struct node {
4    node *l, *r; int d, v;
5    node(int x): d(1), v(x) { l = r = nullptr; }
6};
7static inline int d(node* x) { return x ? x->d : 0; }
8node* merge(node* a, node* b) {
9    if (!a || !b) return a ? b : a;
10    if (a->v > b->v) swap(a, b);
11    a->r = merge(a->r, b);
12    if (d(a->l) < d(a->r))
13        swap(a->l, a->r);
14    a->d = d(a->r) + 1;
```

```
15 return a;
16}
```

5.5 Persistent Treap

```
1// Author: Ian
2struct node {
3    node *l, *r;
4    char c; int v, sz;
5    node(char x = '$'): c(x), v(mt()), sz(1) {
6        l = r = nullptr;
7    }
8    node(node* p) { *this = *p; }
9    void pull() {
10        sz = 1;
11        for (auto i : {l, r})
12            if (i) sz += i->sz;
13    }
14    arr[maxn], *ptr = arr;
15    inline int size(node* p) { return p ? p->sz : 0; }
16    node* merge(node* a, node* b) {
17        if (!a || !b) return a ? b : a;
18        if (a->v < b->v) {
19            node* ret = new(ptr++) node(a);
20            ret->r = merge(ret->r, b), ret->pull();
21            return ret;
22        }
23        else {
24            node* ret = new(ptr++) node(b);
25            ret->l = merge(a, ret->l), ret->pull();
26            return ret;
27        }
28    }
29    P<node*> split(node* p, int k) {
30        if (!p) return {nullptr, nullptr};
31        if (k >= size(p->l) + 1) {
32            auto [a, b] = split(p->r, k - size(p->l) - 1);
33            node* ret = new(ptr++) node(p);
34            ret->r = a, ret->pull();
35            return {ret, b};
36        }
37        else {
38            auto [a, b] = split(p->l, k);
39            node* ret = new(ptr++) node(p);
40            ret->l = b, ret->pull();
41            return {a, ret};
42        }
43    }
```

5.6 Li Chao Tree

```
1// Author: Ian
2// Function: For a set of lines L, find the maximum L_i(x)
in L in O(lg n).
3typedef long double ld;
4constexpr int maxn = 5e4 + 5;
5struct line {
6    ld a, b;
7    ld operator()(ld x) { return a * x + b; }
8} arr[(maxn + 1) << 2];
9bool operator<(line a, line b) { return a.a < b.a; }
10#define m ((l+r)>>1)
11void insert(line x, int i = 1, int l = 0, int r = maxn) {
12    if (r - l == 1) {
13        if (x(l) > arr[i](l))
14            arr[i] = x;
15        return;
16    }
17    line a = max(arr[i], x), b = min(arr[i], x);
18    if (a(m) > b(m))
19        arr[i] = a, insert(b, i << 1, l, m);
20    else
21        arr[i] = b, insert(a, i << 1 | 1, m, r);
22}
23ld query(int x, int i = 1, int l = 0, int r = maxn) {
24    if (x < l || r <= x) return -numeric_limits<ld>::max();
25    if (r - l == 1) return arr[i](x);
26    return max({arr[i](x), query(x, i << 1, l, m), query(x, i
<< 1 | 1, m, r)});
27}
28#undef m
```

5.7 Time Segment Tree

```
1// Author: Ian
2constexpr int maxn = 1e5 + 5;
3V<P<int>> arr[(maxn + 1) << 2];
4V<int> dsu, sz;
5V<tuple<int, int, int>> his;
6int cnt, q;
7int find(int x) {
8    return x == dsu[x] ? x : find(dsu[x]);
9};
```

```

10 inline bool merge(int x, int y) {
11     int a = find(x), b = find(y);
12     if (a == b) return false;
13     if (sz[a] > sz[b]) swap(a, b);
14     his.emplace_back(a, b, sz[b]), dsu[a] = b, sz[b] +=
sz[a];
15     return true;
16 };
17 inline void undo() {
18     auto [a, b, s] = his.back(); his.pop_back();
19     dsu[a] = a, sz[b] = s;
20 }
21 #define m ((l + r) >> 1)
22 void insert(int ql, int qr, P<int> x, int i = 1, int l = 0,
int r = q) {
23     // debug(ql, qr, x); return;
24     if (qr <= l || r <= ql) return;
25     if (ql <= l && r <= qr) {arr[i].push_back(x); return;}
26     if (qr <= m)
27         insert(ql, qr, x, i << 1, l, m);
28     else if (m <= ql)
29         insert(ql, qr, x, i << 1 | 1, m, r);
30     else {
31         insert(ql, qr, x, i << 1, l, m);
32         insert(ql, qr, x, i << 1 | 1, m, r);
33     }
34 }
35 void traversal(V<int>& ans, int i = 1, int l = 0, int r = q)
{
36     int opcnt = 0;
37     // debug(i, l, r);
38     for (auto [a, b] : arr[i])
39         if (merge(a, b))
40             opcnt++, cnt--;
41     if (r - l == 1) ans[l] = cnt;
42     else {
43         traversal(ans, i << 1, l, m);
44         traversal(ans, i << 1 | 1, m, r);
45     }
46     while (opcnt--)
47         undo(), cnt++;
48     arr[i].clear();
49 }
50 #undef m
51 inline void solve() {
52     int n, m; cin >> n >> m >> q; q++;
53     dsu.resize(cnt = n), sz.assign(n, 1);
54     iota(dsu.begin(), dsu.end(), 0);
55     // a, b, time, operation
56     unordered_map<ll, V<int>> s;
57     for (int i = 0; i < m; i++) {
58         int a, b; cin >> a >> b;
59         if (a > b) swap(a, b);
60         s[(ll)a << 32 | b].emplace_back(0);
61     }
62     for (int i = 1; i < q; i++) {
63         int op, a, b;
64         cin >> op >> a >> b;
65         if (a > b) swap(a, b);
66         switch (op) {
67             case 1:
68                 s[(ll)a << 32 | b].push_back(i);
69                 break;
70             case 2:
71                 auto tmp = s[(ll)a << 32 | b].back();
72                 s[(ll)a << 32 | b].pop_back();
73                 insert(tmp, i, P<int> {a, b});
74             }
75     }
76     for (auto [p, v] : s) {
77         int a = p >> 32, b = p & -1;
78         while (v.size()) {
79             insert(v.back(), q, P<int> {a, b});
80             v.pop_back();
81         }
82     }
83     V<int> ans(q);
84     traversal(ans);
85     for (auto i : ans)
86         cout << i << ' ';
87     cout << endl;
88 }

```

6 DP

• 區間 DP

- 狀態： $dp[l][r]$ = 區間 $[l, r]$ 的最佳值/方案數
- 轉移：枚舉劃分點 k

- 思考：是否滿足四邊形不等式、Knuth 優化可加速
- 背包 DP
 - 狀態： $dp[i][w]$ = 前 i 個物品容量 w 的最佳值
 - 判斷是 0/1、多重、分組 $\Rightarrow$ 決定轉移方式
 - 若容量大 $\Rightarrow$ bitset / 數學變形 / meet-in-the-middle
- 樹形 DP
 - 狀態： $dp[u][flag]$ = 子樹 u 的最佳值
 - 合併子樹資訊 $\Rightarrow$ 小到大合併 / 捲積式轉移
 - 注意 reroot 技巧 (dp on tree + dp2 上傳)
- 數位 DP
 - 狀態： $(pos, tight, property)$
 - tight 控制是否貼上界
 - property 常為「餘數、數字和、相鄰限制」
- 狀壓 DP
 - 狀態： $dp[mask][last]$
 - 常見於 TSP / Hamiltonian path / 覆蓋問題
 - $n \leq 20$ 可做，否則要容斥 / FFT
- 期望 / 機率 DP
 - 狀態 $E[s]$ = 從狀態 s 到終點的期望
 - 式子： $E[s] = c + \sum P(s \rightarrow s')E[s']$
 - 線性期望：能拆就拆，少算分布
 - 輸出 mod $\Rightarrow$ 分數化 $\Rightarrow$ 模逆元
- 計數 DP / 組合數
 - 狀態表示方案數，常搭配「模數取餘」
 - 若轉移是捲積型 $\Rightarrow$ FFT/NTT 加速
 - 若能公式化 (Catalan / Ballot / Stirling) $\Rightarrow$ 直接套公式
- 優化 DP
 - 判斷轉移方程 $dp[i] = \min_j (dp[j] + C(j, i))$ 的性質
 - 單調性 $\Rightarrow$ 分治優化
 - 凸性 $\Rightarrow$ Convex Hull Trick / 斜率優化
 - 四邊形不等式 $\Rightarrow$ Knuth 優化

6.1 Aliens

```

1 // Author: Gino
2 // Function: TODO
3 int n; ll k;
4 vector<ll> a;
5 vector<pll> dp[2];
6 void init() {
7     cin >> n >> k;
8     for (auto& d : dp) d.clear(), d.resize(n);
9     a.clear(); a.resize(n);
10    for (auto& i : a) cin >> i;
11 }
12 pll calc(ll p) {
13     dp[0][0] = make_pair(0, 0);
14     dp[1][0] = make_pair(-a[0], 0);
15     for (int i = 1; i < n; i++) {
16         if (dp[0][i-1].first > dp[1][i-1].first + a[i] - p) {
17             dp[0][i] = dp[0][i-1];
18         } else if (dp[0][i-1].first < dp[1][i-1].first + a[i] -
p) {
19             dp[0][i] = make_pair(dp[1][i-1].first + a[i] - p,
dp[1][i-1].second+1);
20         } else {
21             dp[0][i] = make_pair(dp[0][i-1].first, min(dp[0][
i-1].second, dp[1][i-1].second+1));
22         }
23         if (dp[0][i-1].first - a[i] > dp[1][i-1].first) {
24             dp[1][i] = make_pair(dp[0][i-1].first - a[i], dp[0][
i-1].second);
25         } else if (dp[0][i-1].first - a[i] < dp[1][i-1].first) {
26             dp[1][i] = dp[1][i-1];
27         } else {
28             dp[1][i] = make_pair(dp[1][i-1].first, min(dp[0][
i-1].second, dp[1][i-1].second));
29         }
30     }
31     return dp[0][n-1];
32 }
33 void solve() {
34     ll l = 0, r = 1e7;
35     pll res = calc(0);
36     if (res.second <= k) return cout << res.first << endl,
void();
37     while (l < r) {
38         ll mid = (l+r)>>1;
39         res = calc(mid);
40         if (res.second <= k) r = mid;
41         else l = mid+1;
42     }

```

```

43 res = calc(l);
44 cout << res.first + k*l << endl;
45 }

```

6.2 SOS DP

```

1 // Author: Gino
2 // Function: Solve problems that enumerates subsets of
  subsets (3^n => n*2^n)
3 for (int msk = 0; msk < (1<<n); msk++) {
4     for (int i = 1; i <= n; i++) {
5         if (msk & (1<<(i - 1))) {
6             // dp[msk][i] = dp[msk][i - 1] + dp[msk ^ (1<<(i
  - 1))][i - 1];
7         } else {
8             // dp[msk][i] = dp[msk][i - 1];
9         }
10    }
11 }

```

6.3 期望 DP (Expected Value DP)

- 狀態設計： $E[s]$ 是從狀態 s 出發到終點的期望值
- 列式子： $E[s] = (\text{當前代價}) + \sum_{s'} P(s \rightarrow s') \cdot E[s']$
- 若存在自環，把 $E[s]$ 移到左邊，整理成 $(1 - P(s \rightarrow s))E[s] = c + \sum_{s' \neq s} P(s \rightarrow s') \cdot E[s']$
- 線性期望技巧：能拆就拆，避免處理整個分布
- 輸出 mod 時，分母要用模逆元： $q^{-1} \equiv q^{M-2} \pmod{M}$ (質數模數)

常見題型

- 擲骰子遊戲 (到達終點的期望步數)
- 隨機遊走 hitting time
- 重複試驗直到成功
- 博弈遊戲的期望值
- 機率 DP：計算到某步時在某狀態的機率

範例：擲骰子到 n 格

$$E[i] = 1 + \frac{1}{6} \sum_{d=1}^6 E[i+d], \quad (i < n), \quad E[n] = 0$$

```

1 int main(){
2     int n;
3     cin >> n; // 終點位置
4
5     // E[i] = 從位置 i 走到終點的期望步數
6     // 因為每次最多走 6，所以要開 n+6 以避免越界
7     vector<double> E(n+7, 0.0);
8
9     // 從終點往前推 (backward DP)
10    for(int i=n-1; i>=0; i--){
11        double sum=0;
12        // 期望公式: E[i] = 1 + (E[i+1]+...+E[i+6]) / 6
13        for(int d=1; d<=6; d++) sum += E[i+d];
14        E[i] = 1 + sum/6.0;
15    }
16
17    // 輸出 E[0]，即從起點到終點的期望擲骰次數
18    cout << fixed << setprecision(10) << E[0] << "\n";
19 }

```

6.4 數位 DP (Digit DP)

- 狀態： $(pos, tight, property)$
 - pos = 當前處理到第幾位
 - $tight$ = 是否受限於上界 N
 - $property$ = 額外屬性 (如數位和、餘數、相鄰限制...)
- 遞迴：枚舉當前位數字，遞迴下一位
- 終止條件： $pos == \text{長度} \Rightarrow$ 回傳屬性是否滿足
- 記憶化： $dp[pos][tight][property]$

常見題型

- 計算 $[0, N]$ 中數位和可被 k 整除的數字個數
- 不含連續相同數字的數字個數
- 含特定數字次數的數字個數
- 位數和 / 餘數 / mod pattern

範例：計算 $[0, N]$ 中數位和 mod $k = 0$ 的數字個數

$$dp[pos][tight][sum \bmod k]$$

```

1 string s; // N 轉成字串，方便逐位處理
2 int k;    // 除數
3
4 // dp[pos][tight][sum_mod]

```

```

5 // pos = 當前處理到哪一位 (0 = 最高位)
6 // tight = 是否仍受限於 N 的數字 (1 = 是, 0 = 否)
7 // sum_mod = 當前數位和 mod k 的值
8 long long dp[20][2][105];
9
10 // 計算: 從 pos 開始, tight 狀態下, 數位和 mod k = sum_mod 的方案數
11 long long dfs(int pos, int tight, int sum_mod){
12     // 終止條件: 所有位數都處理完
13     if(pos == (int)s.size()){
14         // 若數位和 mod k == 0, 算作一個合法數字
15         return (sum_mod % k == 0);
16
17         // 記憶化查詢
18         if(dp[pos][tight][sum_mod] != -1)
19             return dp[pos][tight][sum_mod];
20
21         long long res = 0;
22         // 如果 tight = 1, 本位數字上限 = N 的該位數字
23         // 如果 tight = 0, 本位數字上限 = 9
24         int limit = tight ? (s[pos]-'0') : 9;
25
26         // 枚舉當前位可以填的數字
27         for(int d=0; d<=limit; d++){
28             // 下一位是否仍然 tight?
29             int next_tight = (tight && d==limit);
30             // 更新數位和 mod k
31             int next_mod = (sum_mod + d) % k;
32             res += dfs(pos+1, next_tight, next_mod);
33         }
34
35         // 存結果
36         return dp[pos][tight][sum_mod] = res;
37     }
38
39 int main(){
40     long long N;
41     cin >> N >> k;
42     s = to_string(N); // 把 N 轉成字串，方便取每一位
43     memset(dp, -1, sizeof(dp));
44     cout << dfs(0, 1, 0) << "\n"; // 從最高位開始，初始 tight=1,
  sum=0
45 }

```

7 Graph

7.1 Blossom

```

1 // Author: ckiseki
2 // usage: first build 0-based graph vector<vector<int>> g on
  your own
3 // then construct the object: Matching M(g)
4 // => M.ans
5 // to check matching status: M.match[x] (== n if not
  matched)
6 struct Matching {
7     queue<int> q; int ans, n;
8     vector<int> fa, s, v, pre, match;
9     int Find(int u) {
10         return u == fa[u] ? u : fa[u] = Find(fa[u]); }
11     int LCA(int x, int y) {
12         static int tk = 0; tk++; x = Find(x); y = Find(y);
13         for(;; swap(x, y)) if (x != n) {
14             if (v[x] == tk) return x;
15             v[x] = tk;
16             x = Find(pre[match[x]]);
17         }
18     }
19     void Blossom(int x, int y, int l) {
20         for(;; Find(x) != l; x = pre[y]) {
21             pre[x] = y, y = match[x];
22             if (s[y] == 1) q.push(y), s[y] = 0;
23             for(int z: {x, y}) if (fa[z] == z) fa[z] = l;
24         }
25     }
26     bool Bfs(auto &&g, int r) {
27         iota(all(fa), 0); ranges::fill(s, -1);
28         q = queue<int>(); q.push(r); s[r] = 0;
29         for(;; !q.empty(); q.pop()) {
30             for(int x = q.front(); int u : g[x])
31                 if (s[u] == -1) {
32                     if (pre[u] = x, s[u] = 1, match[u] == n) {
33                         for(int a = u, b = x, last;
34                             b != n; a = last, b = pre[a])
35                             last = match[b], match[b] = a, match[a] = b;
36                         return true;
37                     }
38                     q.push(match[u]); s[match[u]] = 0;
39                 } else if (!s[u] && Find(u) != Find(x)) {
40                     int l = LCA(u, x);
41                     Blossom(x, u, l); Blossom(u, x, l);

```



```

42     }
43 }
44 return false;
45 }
46 Matching(auto &&g) : ans(0), n(int(g.size())),
47 fa(n+1), s(n+1), v(n+1), pre(n+1, n), match(n+1, n) {
48     for(int x = 0; x < n; ++x)
49         if (match[x] == n) ans += Bfs(g, x);
50 } // match[x] == n means not matched
51}; // test @ vosupo judge

```

7.2 Weighted Blossom

```

1 struct WeightGraph {
2     static const int INF=INT_MAX, N=514;
3     struct edge{
4         int u, v, w; edge(){}
5         edge(int ui, int vi, int wi):u(ui), v(vi), w(wi){}
6     };
7     int n, n_x, lab[N*2], match[N*2], slack[N*2], st[N*2];
8     int pa[N*2], flo_from[N*2][N+1], S[N*2], vis[N*2];
9     edge g[N*2][N*2]; vector<int> flo[N*2]; queue<int> q;
10    int e_delta(const edge &e){
11        return lab[e.u]+lab[e.v]-g[e.u][e.v].w*2;
12    }
13    void update_slack(int u, int x){
14        if(!slack[x] || e_delta(g[u][x]) <
15            e_delta(g[slack[x]][x])) slack[x]=u;
16    }
17    void set_slack(int x){
18        slack[x]=0;
19        for(int u=1; u<=n; ++u)
20            if(g[u][x].w>0 && st[u] != x && S[st[u]]==0)
21                update_slack(u, x);
22    }
23    void q_push(int x){
24        if(x<=n) q.push(x);
25        else for(size_t i=0; i<flo[x].size(); ++i)
26            q_push(flo[x][i]);
27    }
28    void set_st(int x, int b){
29        st[x]=b;
30        if(x>n) for(size_t i=0; i<flo[x].size(); ++i)
31            set_st(flo[x][i], b);
32    }
33    int get_pr(int b, int xr){
34        int pr=find(flo[b].begin(), flo[b].end(), xr)-
35        flo[b].begin();
36        if(pr%2==1){
37            reverse(flo[b].begin()+1, flo[b].end());
38            return (int)flo[b].size()-pr;
39        }else return pr;
40    }
41    void set_match(int u, int v){
42        match[u]=g[u][v].v; if(u<=n) return; edge e=g[u][v];
43        int xr=flo_from[u][e.u], pr=get_pr(u, xr);
44        for(int i=0; i<pr; ++i)
45            set_match(flo[u][i], flo[u][i+1]);
46        set_match(xr, v);
47        rotate(flo[u].begin(), flo[u].begin()+pr, flo[u].end());
48    }
49    void augment(int u, int v){
50        for(;;){
51            int xnv=st[match[u]]; set_match(u, v);
52            if(!xnv) return;
53            set_match(xnv, st[pa[xnv]]); u=st[pa[xnv]], v=xnv;
54        }
55    }
56    int get_lca(int u, int v){
57        static int t=0;
58        for(++t; u || v; swap(u, v)){
59            if(u==0) continue; if(vis[u]==t) return u;
60            vis[u]=t; u=st[match[u]]; if(u) u=st[pa[u]];
61        }
62        return 0;
63    }
64    void add_blossom(int u, int lca, int v){
65        int b=n+1; while(b<=n_x && st[b]) ++b; if(b>n_x) ++n_x;
66        lab[b]=0, S[b]=0; match[b]=match[lca];
67        flo[b].clear(); flo[b].push_back(lca);
68        for(int x=u, y; x!=lca; x=st[pa[y]])
69            flo[b].push_back(x), flo[b].push_back(y=st[match[x]]), q_push(y);
70        reverse(flo[b].begin()+1, flo[b].end());
71        for(int x=v, y; x!=lca; x=st[pa[y]])
72            flo[b].push_back(x), flo[b].push_back(y=st[match[x]]), q_push(y);
73        set_st(b, b);
74        for(int x=1; x<=n_x; ++x) g[b][x].w=g[x][b].w*0;
75        for(int x=1; x<=n; ++x) flo_from[b][x]=0;

```

```

76    for(size_t i=0; i<flo[b].size(); ++i){
77        int xs=flo[b][i];
78        for(int x=1; x<=n_x; ++x)
79            if(g[b][x].w==0 || e_delta(g[xs][x])<e_delta(
80                g[b][x])) g[b][x]=g[xs][x], g[x][b]=g[x][xs];
81        for(int x=1; x<=n; ++x)
82            if(flo_from[xs][x]) flo_from[b][x]=xs;
83    }
84    set_slack(b);
85 }
86 void expand_blossom(int b){
87     for(size_t i=0; i<flo[b].size(); ++i)
88         set_st(flo[b][i], flo[b][i]);
89     int xr=flo_from[b][g[b][pa[b]].u], pr=get_pr(b, xr);
90     for(int i=0; i<pr; ++i){
91         int xs=flo[b][i], xns=flo[b][i+1];
92         pa[xs]=g[xns][xs].u; S[xs]=1, S[xns]=0;
93         slack[xs]=0, set_slack(xns); q_push(xns);
94     }
95     S[xr]=1, pa[xr]=pa[b];
96     for(size_t i=pr+1; i<flo[b].size(); ++i){
97         int xs=flo[b][i]; S[xs]=-1, set_slack(xs);
98     }
99     st[b]=0;
100 }
101 bool on_found_edge(const edge &e){
102     int u=st[e.u], v=st[e.v];
103     if(S[v]==-1){
104         pa[v]=e.u, S[v]=1; int nu=st[match[v]];
105         slack[v]=slack[nu]=0; S[nu]=0, q_push(nu);
106     }else if(S[v]==0){
107         int lca=get_lca(u, v);
108         if(!lca) return augment(u, v), augment(v, u), true;
109         else add_blossom(u, lca, v);
110     }
111     return false;
112 }
113 bool matching(){
114     memset(S+1, -1, sizeof(int)*n_x);
115     memset(slack+1, 0, sizeof(int)*n_x); q=queue<int>();
116     for(int x=1; x<=n_x; ++x)
117         if(st[x]==x && !match[x]) pa[x]=0, S[x]=0, q_push(x);
118     if(q.empty()) return false;
119     for(;;){ while(q.size()){
120         int u=q.front(), q.pop(); if(S[st[u]]==1) continue;
121         for(int v=1; v<=n; ++v)
122             if(g[u][v].w>0 && st[u] != st[v]){
123                 if(e_delta(g[u][v])==0){
124                     if(on_found_edge(g[u][v])) return true;
125                     else update_slack(u, st[v]);
126                 }
127             }
128         int d=INF;
129         for(int b=n+1; b<=n_x; ++b)
130             if(st[b]==b && S[b]==1) d=min(d, lab[b]/2);
131         for(int x=1; x<=n_x; ++x) if(st[x]==x && slack[x]){
132             if(S[x]==-1) d=min(d, e_delta(g[slack[x]][x]));
133             else if(S[x]==0)
134                 d=min(d, e_delta(g[slack[x]][x])/2);
135         }
136         for(int u=1; u<=n; ++u){ if(S[st[u]]==0){
137             if(lab[u]<=d) return 0; lab[u]-=d;
138             }else if(S[st[u]]==1) lab[u]+=d;
139         }
140         for(int b=n+1; b<=n_x; ++b) if(st[b]==b){
141             if(S[st[b]]==0) lab[b]+=d*2;
142             else if(S[st[b]]==1) lab[b]-=d*2;
143         }
144         q=queue<int>();
145         for(int x=1; x<=n_x; ++x)
146             if(st[x]==x && slack[x] && st[slack[x]] !=
147                 x && e_delta(g[slack[x]][x])==0)
148                 if(on_found_edge(g[slack[x]][x])) return true;
149         for(int b=n+1; b<=n_x; ++b) if(st[b]==b && S[b]==1 &&
150             lab[b]==0) expand_blossom(b);
151     }
152     return false;
153 }
154 pair<long long, int> solve(){
155     memset(match+1, 0, sizeof(int)*n); n_x=n;
156     int n_matches=0, w_max=0; long long tot_weight=0;
157     for(int u=0; u<=n; ++u) st[u]=u, flo[u].clear();
158     for(int u=1; u<=n; ++u) for(int v=1; v<=n; ++v){
159         flo_from[u][v]=(u==v?u:0);
160         w_max=max(w_max, g[u][v].w);
161     }
162     for(int u=1; u<=n; ++u) lab[u]=w_max;
163     while(matching()) ++n_matches;
164     for(int u=1; u<=n; ++u) if(match[u] && match[u]<u)

```

```

164     tot_weight+=g[u][match[u]].w;
165     return make_pair(tot_weight,n_matches);
166 }
167 void add_edge(int ui,int vi,int wi)
168 { g[ui][vi].w=g[vi][ui].w=wi; }
169 void init(int _n){
170     n=_n;
171     for(int u=1;u<=n;++u) for(int v=1;v<=n;++v)
172         g[u][v]=edge(u,v,0);
173 }
174 }graph;

```

7.3 Max Clique

```

1 // max N = 64
2 typedef unsigned long long ll;
3 struct MaxClique{
4     ll nb[ N ] , n , ans;
5     void init( ll _n ){
6         n = _n;
7         for( int i = 0 ; i < n ; i ++ ) nb[ i ] = 0LLU;
8     }
9     void add_edge( ll _u , ll _v ){
10         nb[ _u ] |= ( 1LLU << _v );
11         nb[ _v ] |= ( 1LLU << _u );
12     }
13     void B( ll r , ll p , ll x , ll cnt , ll res ){
14         if( cnt + res < ans ) return;
15         if( p == 0LLU && x == 0LLU ){
16             if( cnt > ans ) ans = cnt;
17             return;
18         }
19         ll y = p | x; y &= -y;
20         ll q = p & ( ~nb[ int( log2( y ) ) ] );
21         while( q ){
22             ll i = int( log2( q & (-q) ) );
23             B( r | ( 1LLU << i ) , p & nb[ i ] , x & nb[ i ]
24             , cnt + 1LLU , __builtin_popcountll( p &
25             nb[ i ] ) );
26             q &= ~( 1LLU << i );
27             p &= ~( 1LLU << i );
28             x |= ( 1LLU << i );
29         }
30     int solve(){
31         ans = 0;
32         ll _set = 0;
33         if( n < 64 ) _set = ( 1LLU << n ) - 1;
34         else{
35             for( ll i = 0 ; i < n ; i ++ ) _set |= ( 1LLU << i );
36         }
37         B( 0LLU , _set , 0LLU , 0LLU , n );
38         return ans;
39     }
40 }maxClique;

```

7.4 Bellman-Ford + SPFA

```

1 int n, m;
2
3 // Graph
4 vector<vector<pair<int, ll> > > g;
5 vector<ll> dis;
6 vector<bool> negCycle;
7
8 // SPFA
9 vector<int> rlx;
10 queue<int> q;
11 vector<bool> inq;
12 vector<int> pa;
13 void SPFA(vector<int>& src) {
14     dis.assign(n+1, LINF);
15     negCycle.assign(n+1, false);
16     rlx.assign(n+1, 0);
17     while (!q.empty()) q.pop();
18     inq.assign(n+1, false);
19     pa.assign(n+1, -1);
20
21     for (auto& s : src) {
22         dis[s] = 0;
23         q.push(s); inq[s] = true;
24     }
25
26     while (!q.empty()) {
27         int u = q.front();
28         q.pop(); inq[u] = false;
29         if (rlx[u] >= n) {
30             negCycle[u] = true;
31         }
32         else for (auto& e : g[u]) {
33             int v = e.first;

```

```

34             ll w = e.second;
35             if (dis[v] > dis[u] + w) {
36                 dis[v] = dis[u] + w;
37                 rlx[v] = rlx[u] + 1;
38                 pa[v] = u;
39                 if (!inq[v]) {
40                     q.push(v);
41                     inq[v] = true;
42                 } } } }
43
44 // Bellman-Ford
45 queue<int> q;
46 vector<int> pa;
47 void BellmanFord(vector<int>& src) {
48     dis.assign(n+1, LINF);
49     negCycle.assign(n+1, false);
50     pa.assign(n+1, -1);
51
52     for (auto& s : src) dis[s] = 0;
53
54     for (int rlx = 1; rlx <= n; rlx++) {
55         for (int u = 1; u <= n; u++) {
56             if (dis[u] == LINF) continue; // Important!!
57             for (auto& e : g[u]) {
58                 int v = e.first; ll w = e.second;
59                 if (dis[v] > dis[u] + w) {
60                     dis[v] = dis[u] + w;
61                     pa[v] = u;
62                     if (rlx == n) negCycle[v] = true;
63                 } } } }
64
65 // Negative Cycle Detection
66 void NegCycleDetect() {
67     /* No Neg Cycle: NO
68     Exist Any Neg Cycle: YES
69     v0 v1 v2 ... vk v0 */
70     vector<int> src;
71     for (int i = 1; i <= n; i++)
72         src.emplace_back(i);
73
74     SPFA(src);
75     // BellmanFord(src);
76
77     int ptr = -1;
78     for (int i = 1; i <= n; i++) if (negCycle[i])
79         ptr = i; break; }
80
81     if (ptr == -1) { return cout << "NO" << endl, void(); }
82
83     cout << "YES\n";
84     vector<int> ans;
85     vector<bool> vis(n+1, false);
86
87     while (true) {
88         ans.emplace_back(ptr);
89         if (vis[ptr]) break;
90         vis[ptr] = true;
91         ptr = pa[ptr];
92     }
93     reverse(ans.begin(), ans.end());
94
95     vis.assign(n+1, false);
96     for (auto& x : ans) {
97         cout << x << ' ';
98         if (vis[x]) break;
99         vis[x] = true;
100     }
101     cout << endl;
102
103 // Distance Calculation
104 void calcDis(int s) {
105     vector<int> src;
106     src.emplace_back(s);
107     SPFA(src);
108     // BellmanFord(src);
109
110     while (!q.empty()) q.pop();
111     for (int i = 1; i <= n; i++)
112         if (negCycle[i]) q.push(i);
113
114     while (!q.empty()) {
115         int u = q.front(); q.pop();
116         for (auto& e : g[u]) {
117             int v = e.first;
118             if (!negCycle[v]) {

```

```

124     q.push(v);
125     negCycle[v] = true;
126 } } }

```

7.5 BCC - AP

```

1 int n, m;
2 int low[maxn], dfn[maxn], instp;
3 vector<int> E, g[maxn];
4 bitset<maxn> isap;
5 bitset<maxn> vis;
6 stack<int> stk;
7 int bccnt;
8 vector<int> bcc[maxn];
9 inline void popout(int u) {
10     bccnt++;
11     bcc[bccnt].emplace_back(u);
12     while (!stk.empty()) {
13         int v = stk.top();
14         if (u == v) break;
15         stk.pop();
16         bcc[bccnt].emplace_back(v);
17     }
18 }
19 void dfs(int u, bool rt = 0) {
20     stk.push(u);
21     low[u] = dfn[u] = ++instp;
22     int kid = 0;
23     Each(e, g[u]) {
24         if (vis[e]) continue;
25         vis[e] = true;
26         int v = E[e]^u;
27         if (!dfn[v]) {
28             // tree edge
29             kid++; dfs(v);
30             low[u] = min(low[u], low[v]);
31             if (!rt && low[v] >= dfn[u]) {
32                 // bcc found: u is ap
33                 isap[u] = true;
34                 popout(u);
35             }
36         } else {
37             // back edge
38             low[u] = min(low[u], dfn[v]);
39         }
40     }
41     // special case: root
42     if (rt) {
43         if (kid > 1) isap[u] = true;
44         popout(u);
45     }
46 }
47 void init() {
48     cin >> n >> m;
49     fill(low, low+maxn, INF);
50     REP(i, m) {
51         int u, v;
52         cin >> u >> v;
53         g[u].emplace_back(i);
54         g[v].emplace_back(i);
55         E.emplace_back(u^v);
56     }
57 }
58 void solve() {
59     FOR(i, 1, n+1, 1) {
60         if (!dfn[i]) dfs(i, true);
61     }
62     vector<int> ans;
63     int cnt = 0;
64     FOR(i, 1, n+1, 1) {
65         if (isap[i]) cnt++, ans.emplace_back(i);
66     }
67     cout << cnt << endl;
68     Each(i, ans) cout << i << ' ';
69     cout << endl;
70 }

```

7.6 BCC - Bridge

```

1 int n, m;
2 vector<int> g[maxn], E;
3 int low[maxn], dfn[maxn], instp;
4 int bccnt, bccid[maxn];
5 stack<int> stk;
6 bitset<maxn> vis, isbrg;
7 void init() {
8     cin >> n >> m;
9     REP(i, m) {
10         int u, v;
11         cin >> u >> v;
12         E.emplace_back(u^v);

```

```

13         g[u].emplace_back(i);
14         g[v].emplace_back(i);
15     }
16     fill(low, low+maxn, INF);
17 }
18 void popout(int u) {
19     bccnt++;
20     while (!stk.empty()) {
21         int v = stk.top();
22         if (v == u) break;
23         stk.pop();
24         bccid[v] = bccnt;
25     }
26 }
27 void dfs(int u) {
28     stk.push(u);
29     low[u] = dfn[u] = ++instp;
30
31     Each(e, g[u]) {
32         if (vis[e]) continue;
33         vis[e] = true;
34
35         int v = E[e]^u;
36         if (dfn[v]) {
37             // back edge
38             low[u] = min(low[u], dfn[v]);
39         } else {
40             // tree edge
41             dfs(v);
42             low[u] = min(low[u], low[v]);
43             if (low[v] == dfn[v]) {
44                 isbrg[e] = true;
45                 popout(u);
46             }
47         }
48     }
49 }
50 void solve() {
51     FOR(i, 1, n+1, 1) {
52         if (!dfn[i]) dfs(i);
53     }
54     vector<pii> ans;
55     vis.reset();
56     FOR(u, 1, n+1, 1) {
57         Each(e, g[u]) {
58             if (!isbrg[e] || vis[e]) continue;
59             vis[e] = true;
60             int v = E[e]^u;
61             ans.emplace_back(mp(u, v));
62         }
63     }
64     cout << (int)ans.size() << endl;
65     Each(e, ans) cout << e.F << ' ' << e.S << endl;
66 }

```

7.7 SCC - Tarjan with 2-SAT

```

1 // Author: Ian
2 // 2-sat + tarjan SCC
3 void solve() {
4     int n, r, l; cin >> n >> r >> l;
5     V<P<int>> v(l);
6     for (auto& [a, b] : v)
7         cin >> a >> b;
8     V<V<int>> e(2 * l);
9     for (int i = 0; i < l; i++)
10         for (int j = i + 1; j < l; j++) {
11             if (v[i].first == v[j].first && abs(v[i].second -
12                 v[j].second) <= 2 * r) {
13                 e[i << 1].emplace_back(j << 1 | 1);
14                 e[j << 1].emplace_back(i << 1 | 1);
15             }
16             if (v[i].second == v[j].second && abs(v[i].first -
17                 v[j].first) <= 2 * r) {
18                 e[i << 1 | 1].emplace_back(j << 1);
19                 e[j << 1 | 1].emplace_back(i << 1);
20             }
21         }
22     V<bool> ins(2 * l, false);
23     V<int> scc(2 * l), dfn(2 * l, -1), low(2 * l, inf);
24     stack<int> s;
25     function<void(int)> dfs = [&](int x) {
26         if (~dfn[x]) return;
27         static int t = 0;
28         dfn[x] = low[x] = t++;
29         s.push(x), ins[x] = true;
30         for (auto i : e[x])
31             if (dfs(i), ins[i])
32                 low[x] = min(low[x], low[i]);
33         if (dfn[x] == low[x]) {

```



```

32 static int ncnt = 0;
33 int p; do {
34     ins[p = s.top()] = false;
35     s.pop(), scc[p] = ncnt;
36 } while (p != x); ncnt++;
37 }
38 };
39 for (int i = 0; i < 2 * l; i++)
40     dfs(i);
41 for (int i = 0; i < l; i++)
42     if (scc[i <= 1] == scc[i <= 1 | 1]) {
43         cout << "NO" << endl;
44         return;
45     }
46 cout << "YES" << endl;
47 }

```

7.8 Eulerian Path - Undir

```

1// Author: Gino
2// Usage: build deg, G first, then eulerian()
3int n, m; // number of vertices and edges
4vector<int> deg; // degree
5vector<set<pii>> G; // G[u] := {(v, edge id)}
6
7vector<int> path_u, path_e;
8void dfs(int u) {
9    while (!G[u].empty()) {
10        auto it = G[u].begin();
11        auto [v, i] = *it; G[u].erase(it);
12        G[v].erase(make_pair(u, i)); dfs(v);
13        path_u.emplace_back(v);
14        path_e.emplace_back(i);
15    }
16}
17void gogo(int s) {
18    path_u.clear(); path_e.clear();
19    dfs(s); path_u.emplace_back(s);
20    reverse(path_u.begin(), path_u.end());
21    reverse(path_e.begin(), path_e.end());
22}
23bool eulerian() {
24    int oddcnt = 0, s = -1;
25    for (int u = 1; u <= n; u++)
26        if (deg[u] & 1)
27            oddcnt++, s = u;
28
29    if (oddcnt != 0 && oddcnt != 2) return false;
30    if (s == -1) {
31        s = 1; for (int u = 1; u <= n; u++)
32            if (deg[u] > 0)
33                s = u;
34    }
35    gogo(s);
36
37    for (int u = 1; u <= n; u++)
38        if ((int)G[u].size() > 0)
39            return false;
40    return true;
41}

```

7.9 Eulerian Path - Dir

```

1// Author: Gino
2// Usage: build ind, oud, G first, then eulerian()
3int n, m; // number of vertices, edges
4vector<vector> ind, oud; // indegree, outdegree
5vector<vector<pii>> G; // G[u] := {(v, edge id)}
6
7vector<int> path_u, path_e;
8void dfs(int u) {
9    while (!G[u].empty()) {
10        auto [v, i] = G[u].back(); G[u].pop_back();
11        dfs(v);
12        path_u.emplace_back(v);
13        path_e.emplace_back(i);
14    }
15}
16void gogo(int s) {
17    path_u.clear(); path_e.clear();
18    dfs(s); path_u.emplace_back(s);
19    reverse(path_u.begin(), path_u.end());
20    reverse(path_e.begin(), path_e.end());
21}
22bool eulerian() {
23    int s = -1;
24    for (int u = 1; u <= n; u++) {
25        if (abs(oud[u] - ind[u]) > 1) return false;
26        if (oud[u] - ind[u] == 1) {
27            if (s != -1) return false;
28            s = u;
29        }
30    }
31}

```

```

30 }
31 if (s == -1) {
32     s = 1; for (int u = 1; u <= n; u++)
33         if (ind[u] > 0)
34             s = u;
35 }
36 gogo(s);
37 for (int u = 1; u <= n; u++)
38     if ((int)G[u].size() > 0)
39         return false;
40
41 return true;
42}

```

7.10 Kth Shortest Path

```

1// time: O(|E| \lg |E|+|V| \lg |V|+K)
2// memory: O(|E| \lg |E|+|V|)
3struct KSP{ // 1-base
4    struct nd{
5        int u,v; ll d;
6        nd(int ui=0,int vi=0,ll di=INF){ u=ui; v=vi; d=di; }
7    };
8    struct heap{ nd* edge; int dep; heap* chd[4]; };
9    static int cmp(heap* a,heap* b)
10    { return a->edge->d > b->edge->d; }
11    struct node{
12        int v; ll d; heap* H; nd* E;
13        node(){}
14        node(ll _d,int _v,nd* _E){ d=_d; v=_v; E=_E; }
15        node(heap* _H,ll _d){ H=_H; d=_d; }
16        friend bool operator<(node a,node b)
17        { return a.d>b.d; }
18    };
19    int n,k,s,t,dst[N]; nd *nxt[N];
20    vector<nd*> g[N],rg[N]; heap *nullNd,*head[N];
21    void init(int _n,int _k,int _s,int _t){
22        n=_n; k=_k; s=_s; t=_t;
23        for(int i=1;i<=n;i++){
24            g[i].clear(); rg[i].clear();
25            nxt[i]=NULL; head[i]=NULL; dst[i]=-1;
26        }
27    }
28    void addEdge(int ui,int vi,ll di){
29        nd* e=new nd(ui,vi,di);
30        g[ui].push_back(e); rg[vi].push_back(e);
31    }
32    queue<int> dfsQ;
33    void dijkstra(){
34        while(dfsQ.size()) dfsQ.pop();
35        priority_queue<node> Q; Q.push(node(0,t,NULL));
36        while (!Q.empty()){
37            node p=Q.top(); Q.pop(); if(dst[p.v]!=-1)continue;
38            dst[p.v]=p.d; nxt[p.v]=p.E; dfsQ.push(p.v);
39            for(auto e:rg[p.v]) Q.push(node(p.d+e->d,e->u,e));
40        }
41    }
42    heap* merge(heap* curNd,heap* newNd){
43        if(curNd==nullNd) return newNd;
44        heap* root=new heap; memcpy(root,curNd,sizeof(heap));
45        if(newNd->edge->d<curNd->edge->d){
46            root->edge=newNd->edge;
47            root->chd[2]=newNd->chd[2];
48            root->chd[3]=newNd->chd[3];
49            newNd->edge=curNd->edge;
50            newNd->chd[2]=curNd->chd[2];
51            newNd->chd[3]=curNd->chd[3];
52        }
53        if(root->chd[0]->dep<root->chd[1]->dep)
54            root->chd[0]=merge(root->chd[0],newNd);
55        else root->chd[1]=merge(root->chd[1],newNd);
56        root->dep=max(root->chd[0]->dep,
57                    root->chd[1]->dep)+1;
58        return root;
59    }
60    vector<heap*> V;
61    void build(){
62        nullNd=new heap; nullNd->dep=0; nullNd->edge=new nd;
63        fill(nullNd->chd,nullNd->chd+4,nullNd);
64        while(not dfsQ.empty()){
65            int u=dfsQ.front(); dfsQ.pop();
66            if(!nxt[u]) head[u]=nullNd;
67            else head[u]=head[nxt[u]->v];
68            V.clear();
69            for(auto&& e:g[u]){
70                int v=e->v;
71                if(dst[v]==-1) continue;
72                e->d+=dst[v]-dst[u];
73                if(nxt[u]!=e){
74                    heap* p=new heap; fill(p->chd,p->chd+4,nullNd);

```

```

75     p->dep=1; p->edge=e; V.push_back(p);
76 }
77 }
78 if(V.empty()) continue;
79 make_heap(V.begin(), V.end(), cmp);
80 #define L(X) ((X<<1)+1)
81 #define R(X) ((X<<1)+2)
82 for(size_t i=0; i<V.size(); i++){
83     if(L(i)<V.size()) V[i]->chd[2]=V[L(i)];
84     else V[i]->chd[2]=nullNd;
85     if(R(i)<V.size()) V[i]->chd[3]=V[R(i)];
86     else V[i]->chd[3]=nullNd;
87 }
88 head[u]=merge(head[u], V.front());
89 }
90 }
91 vector<ll> ans;
92 void first_K(){
93     ans.clear(); priority_queue<node> Q;
94     if(dst[s]==-1) return;
95     ans.push_back(dst[s]);
96     if(head[s]!=nullNd)
97         Q.push(node(head[s], dst[s]+head[s]->edge->d));
98     for(int _=1; _<k and not Q.empty(); _++){
99         node p=Q.top(); Q.pop(); ans.push_back(p.d);
100         if(head[p.H->edge->v]!=nullNd){
101             q.H=head[p.H->edge->v]; q.d=p.d+q.H->edge->d;
102             Q.push(q);
103         }
104         for(int i=0; i<4; i++){
105             if(p.H->chd[i]!=nullNd){
106                 q.H=p.H->chd[i];
107                 q.d=p.d+p.H->edge->d+p.H->chd[i]->edge->d;
108                 Q.push(q);
109             }
110 }
111 void solve(){ // ans[i] stores the i-th shortest path
112     dijkstra(); build();
113     first_K(); // ans.size() might less than k
114 }
115 } solver;

```

7.11 System of Difference Constraints

```

1 vector<vector<pair<int, ll>>> G;
2 void add(int u, int v, ll w) {
3     G[u].emplace_back(make_pair(v, w));
4 }

```

- $x_u - x_v \leq c \Rightarrow \text{add}(v, u, c)$
- $x_u - x_v \geq c \Rightarrow \text{add}(u, v, -c)$
- $x_u - x_v = c \Rightarrow \text{add}(v, u, c), \text{add}(u, v, -c)$
- $x_u \geq c \Rightarrow \text{add super vertex } x_0 = 0, \text{ then } x_u - x_0 \geq c \Rightarrow \text{add}(u, 0, -c)$
- Don't forget non-negative constraints for every variable if specified implicitly.
- Interval sum $\Rightarrow$ Use prefix sum to transform into differential constraints. Don't forget $S_{i+1} - S_i \geq 0$ if x_i needs to be non-negative.
- $\frac{x_u}{x_v} \leq c \Rightarrow \log x_u - \log x_v \leq \log c$

8 String

8.1 Rolling Hash

```

1 const ll C = 27;
2 inline int id(char c) {return c-'a'+1;}
3 struct RollingHash {
4     string s; int n; ll mod;
5     vector<ll> Cexp, hs;
6     RollingHash(string& _s, ll _mod):
7         s(_s), n((int)_s.size()), mod(_mod)
8     {
9         Cexp.assign(n, 0);
10        hs.assign(n, 0);
11        Cexp[0] = 1;
12        for (int i = 1; i < n; i++) {
13            Cexp[i] = Cexp[i-1] * C;
14            if (Cexp[i] >= mod) Cexp[i] %= mod;
15        }
16        hs[0] = id(s[0]);
17        for (int i = 1; i < n; i++) {
18            hs[i] = hs[i-1] * C + id(s[i]);
19            if (hs[i] >= mod) hs[i] %= mod;
20        }
21        inline ll query(int l, int r) {
22            ll res = hs[r] - (l ? hs[l-1] * Cexp[r-l+1] : 0);
23            res = (res % mod + mod) % mod;
24            return res;
25 };

```

8.2 Trie

```

1 struct node {
2     int c[26]; ll cnt;
3     node(): cnt(0) {memset(c, 0, sizeof(c));}
4     node(ll x): cnt(x) {memset(c, 0, sizeof(c));}
5 };
6 struct Trie {
7     vector<node> t;
8     void init() {
9         t.clear();
10        t.emplace_back(node());
11    }
12    void insert(string s) { int ptr = 0;
13        for (auto& i : s) {
14            if (!t[ptr].c[i-'a']) {
15                t.emplace_back(node());
16                t[ptr].c[i-'a'] = (int)t.size()-1;
17                ptr = t[ptr].c[i-'a'];
18            }
19        }
20    }
21 };

```

8.3 KMP

```

1 int n, m;
2 string s, p;
3 vector<int> f;
4 void build() {
5     f.clear(); f.resize(m, 0);
6     int ptr = 0; for (int i = 1; i < m; i++) {
7         while (ptr && p[i] != p[ptr]) ptr = f[ptr-1];
8         if (p[i] == p[ptr]) ptr++;
9         f[i] = ptr;
10    }
11    void init() {
12        cin >> s >> p;
13        n = (int)s.size();
14        m = (int)p.size();
15        build();
16    }
17    void solve() {
18        int ans = 0, pi = 0;
19        for (int si = 0; si < n; si++) {
20            while (pi && s[si] != p[pi]) pi = f[pi-1];
21            if (s[si] == p[pi]) pi++;
22            if (pi == m) ans++, pi = f[pi-1];
23        }
24        cout << ans << endl;
25    }

```

8.4 Z Value

```

1 string is, it, s;
2 int n; vector<int> z;
3 void init() {
4     cin >> is >> it;
5     s = it+'0'+is;
6     n = (int)s.size();
7     z.resize(n, 0);
8 }
9 void solve() {
10    int ans = 0; z[0] = n;
11    for (int i = 1, l = 0, r = 0; i < n; i++) {
12        if (i <= r) z[i] = min(z[i-l], r-i+1);
13        while (i+z[i] < n && s[z[i]] == s[i+z[i]]) z[i]++;
14        if (i+z[i]-1 > r) l = i, r = i+z[i]-1;
15        if (z[i] == (int)it.size()) ans++;
16    }
17    cout << ans << endl;
18 }

```

8.5 Manacher

```

1 int n; string S, s;
2 vector<int> m;
3 void manacher() {
4     s.clear(); s.resize(2*n+1, '.');
5     for (int i = 0, j = 1; i < n; i++, j += 2) s[j] = S[i];
6     m.clear(); m.resize(2*n+1, 0);
7     // m[i] := max k such that s[i-k, i+k] is palindrome
8     int mx = 0, mxk = 0;
9     for (int i = 1; i < 2*n+1; i++) {
10        if (mx-(i-mx) >= 0) m[i] = min(m[mx-(i-mx)], mx+mxk-i);
11        while (0 <= i-m[i]-1 && i+m[i]+1 < 2*n+1 &&
12            s[i-m[i]-1] == s[i+m[i]+1]) m[i]++;
13        if (i+m[i] > mx+mxk) mx = i, mxk = m[i];
14    }
15    void init() { cin >> S; n = (int)S.size(); }
16    void solve() {
17        manacher();
18        int mx = 0, ptr = 0;
19        for (int i = 0; i < 2*n+1; i++) if (mx < m[i])
20            { mx = m[i]; ptr = i; }
21        for (int i = ptr-mx; i <= ptr+mx; i++)
22            if (s[i] != '.') cout << s[i];
23        cout << endl;
24    }

```

8.6 Suffix Array

```

1 #define F first
2 #define S second
3 struct SuffixArray { // don't forget s += "$";
4     int n; string s;
5     vector<int> suf, lcp, rk;
6     vector<int> cnt, pos;
7     vector<pair<pii, int>> buc[2];
8     void init(string _s) {
9         s = _s; n = (int)s.size();
10 // resize(n): suf, rk, cnt, pos, lcp, buc[0~1]
11     }
12     void radix_sort() {
13         for (int t : {0, 1}) {
14             fill(cnt.begin(), cnt.end(), 0);
15             for (auto& i : buc[t]) cnt[(t ? i.F : i.S)]++;
16             for (int i = 0; i < n; i++)
17                 pos[i] = (!i ? 0 : pos[i-1] + cnt[i-1]);
18             for (auto& i : buc[t])
19                 buc[t][i].pos[(t ? i.F : i.S)] = i;
20         }
21         bool fill_suf() {
22             bool end = true;
23             for (int i = 0; i < n; i++) suf[i] = buc[0][i].S;
24             rk[suf[0]] = 0;
25             for (int i = 1; i < n; i++) {
26                 int dif = (buc[0][i].F != buc[0][i-1].F);
27                 end &= dif;
28                 rk[suf[i]] = rk[suf[i-1]] + dif;
29             } return end;
30         }
31         void sa() {
32             for (int i = 0; i < n; i++)
33                 buc[0][i] = make_pair(make_pair(s[i], s[i]), i);
34             sort(buc[0].begin(), buc[0].end());
35             if (fill_suf()) return;
36             for (int k = 0; (1<<k) < n; k++) {
37                 for (int i = 0; i < n; i++)
38                     buc[0][i] = make_pair(make_pair(rk[i], rk[(i
39 + (1<<k)) % n]), i);
40                 radix_sort();
41                 if (fill_suf()) return;
42             }
43             void LCP() { int k = 0;
44                 for (int i = 0; i < n-1; i++) {
45                     if (rk[i] == 0) continue;
46                     int pi = rk[i];
47                     int j = suf[pi-1];
48                     while (i+k < n && j+k < n && s[i+k] == s[j+k])
49                         k++;
50                     lcp[pi] = k;
51                     k = max(k-1, 0);
52                 }
53             }
54         }
55     }
56 } SuffixArray suffixarrav;

```

8.7 Suffix Automaton

```

1 // any path start from root forms a substring of S
2 // occurrence of P: iff SAM can run on input word P
3 // number of different substring: ds[1]-1
4 // total length of all different substring: dsl[1]
5 // max/min length of state i: mx[i]/mx[mom[i]]+1
6 // assume a run on input word P end at state i:
7 // number of occurrences of P: cnt[i]
8 // first occurrence position of P: fp[i]-|P|+1
9 // all position: !clone nodes in dfs from i through rmom
10 const int MXM=1000010;
11 struct SAM{
12     int tot, root, lst, mom[MXM], mx[MXM]; // ind[MXM]
13     int nxt[MXM][33]; // cnt[MXM], ds[MXM], dsl[MXM], fp[MXM]
14     // bool v[MXM], clone[MXN]
15     int newNode(){
16         int res=++tot; fill(nxt[res], nxt[res]+33, 0);
17         mom[res]=mx[res]=0; // cnt=ds=dsL=fp=v=clone=0
18         return res;
19     }
20     void init(){ tot=0; root=newNode(); lst=root; }
21     void push(int c){
22         int p=lst, np=newNode(); // cnt[np]=1, clone[np]=0
23         mx[np]=mx[p]+1; // fp[np]=mx[np]-1
24         for (p&&nxt[p][c]==0; p=mom[p]) nxt[p][c]=np;
25         if (p==0) mom[np]=root;
26         else{
27             int q=nxt[p][c];
28             if (mx[p]+1==mx[q]) mom[np]=q;
29             else{
30                 int nq=newNode(); // fp[nq]=fp[q], clone[nq]=1
31                 mx[nq]=mx[p]+1;

```

```

32         for (int i=0; i<33; i++) nxt[nq][i]=nxt[q][i];
33         mom[nq]=mom[q]; mom[q]=nq; mom[np]=nq;
34         for (p&&nxt[p][c]==q; p=mom[p]) nxt[p][c]=nq;
35     }
36     lst=np;
37 }
38 void calc(){
39     calc(root); iota(ind, ind+tot, 1);
40     sort(ind, ind+tot, [&](int i, int j){ return mx[i]<mx[j]; });
41     for (int i=tot-1; i>=0; i--)
42         cnt[mom[ind[i]]] += cnt[ind[i]];
43 }
44 void calc(int x){
45     v[x]=ds[x]=1; dsl[x]=0; // rmom[mom[x]].push_back(x);
46     for (int i=0; i<26; i++){
47         if (nxt[x][i]){
48             if (!v[nxt[x][i]]) calc(nxt[x][i]);
49             ds[x] += ds[nxt[x][i]];
50             dsl[x] += ds[nxt[x][i]] + dsl[nxt[x][i]];
51         }
52     }
53     void push(char *str){
54         for (int i=0; str[i]; i++) push(str[i]-'a');
55     }
56 } sam;

```

8.8 SA-IS

```

1 const int N=300010;
2 struct SA{
3     #define REP(i,n) for(int i=0; i<int(n); i++)
4     #define REP1(i,a,b) for(int i=(a); i<=int(b); i++)
5     bool t[N*2]; int _s[N*2], _sa[N*2];
6     int _c[N*2], x[N], _p[N], _q[N*2], hei[N], r[N];
7     int operator [](int i){ return _sa[i]; }
8     void build(int *s, int n, int m){
9         memcpy(_s, s, sizeof(int)*n);
10        sais(_s, _sa, _p, _q, t, _c, n, m); mkhei(n);
11    }
12    void mkhei(int n){
13        REP(i,n) r[_sa[i]]=i;
14        hei[0]=0;
15        REP(i,n) if (r[i]) {
16            int ans=i>0?max(hei[r[i-1]]-1, 0):0;
17            while (_s[i+ans]==_s[_sa[r[i]-1]+ans]) ans++;
18            hei[r[i]]=ans;
19        }
20    }
21    void sais(int *s, int *sa, int *p, int *q, bool *t, int *c, int
22    n, int z){
23        bool uniq=t[n-1]=true, neq;
24        int nn=0, nmzx=-1, *nsa=sa+n, *ns=s+n, lst=-1;
25        #define MS0(x,n) memset((x), 0, n*sizeof(*(x)))
26        #define MAGIC(XD) MS0(sa,n); \
27        memcpy(x,c, sizeof(int)*z); XD; \
28        memcpy(x+1,c, sizeof(int)*(z-1)); \
29        REP(i,n) if (sa[i]&&!t[sa[i]-1]) sa[x[s[sa[i]-1]]++] = sa[i]-1; \
30        memcpy(x,c, sizeof(int)*z); \
31        for (int i=n-1; i>=0; i--) if (sa[i]&&t[sa[i]-1]) sa[--
32        x[s[sa[i]-1]]] = sa[i]-1;
33        MS0(c,z); REP(i,n) uniq&=++c[s[i]]<2;
34        REP(i,z-1) c[i+1]+=c[i];
35        if (uniq) { REP(i,n) sa[--c[s[i]]]=i; return; }
36        for (int i=n-2; i>=0; i--){
37            t[i]=(s[i]==s[i+1])?t[i+1]:s[i]<s[i+1];
38            MAGIC(REP1(i,1,n-1) if (t[i]&&!t[i-1]) sa[--
39            x[s[i]]]=p[q[i]=nn++] = i);
40            REP(i,n) if (sa[i]&&t[sa[i]]&&t[sa[i]-1]){
41                neq=lst<0||memcmp(s+sa[i], s+lst, (p[q[sa[i]]+1]-
42                sa[i])*sizeof(int));
43                ns[q[lst=sa[i]]]=nmzx+=neq;
44            }
45            sais(ns, nsa, p+nn, q+n, t+n, c+z, nn, nmzx+1);
46            MAGIC(for (int i=nn-1; i>=0; i--) sa[--
47            x[s[p[nsa[i]]]]]=p[nsa[i]]);
48        }
49        int H[N], SA[N], RA[N];
50        void suffix_array(int *ip, int len){
51            // should padding a zero in the back
52            // ip is int array, len is array length
53            // ip[0..n-1] != 0, and ip[len]=0
54            ip[len]=0; sa.build(ip, len, 128);
55            memcpy(H, sa, hei+1, len<2); memcpy(SA, sa, _sa+1, len<2);
56            for (int i=0; i<len; i++) RA[i]=sa.r[i]-1;
57            // resulting height, sa array in [0, len)
58        }
59    }

```

8.9 Minimum Rotation

```
1 // lexicographically minimal rotation
```

```

2 // rotate(begin(s), begin(s)+minRotation(s), end(s))
3 int minRotation(string s) {
4     int a = 0, n = s.size(); s += s;
5     for(int b = 0; b < n; b++) for(int k = 0; k < n; k++) {
6         if(a + k == b || s[a + k] < s[b + k]) {
7             b += max(0, k - 1);
8             break;
9         }
10        if(s[a + k] > s[b + k]) {
11            a = b;
12            break;
13        }
14    }
15    return a;
16 }

```

8.10 Aho Corasick

```

1 struct ACautomata{
2     struct Node{
3         int cnt;
4         Node *go[26], *fail, *dic;
5         Node(){
6             cnt = 0; fail = 0; dic = 0;
7             memset(go, 0, sizeof(go));
8         }
9     } pool[1048576], *root;
10    int nMem;
11    Node* new_Node(){
12        pool[nMem] = Node();
13        return &pool[nMem++];
14    }
15    void init() { nMem = 0; root = new_Node(); }
16    void add(const string &str) { insert(root, str, 0); }
17    void insert(Node *cur, const string &str, int pos){
18        for(int i = pos; i < str.size(); i++){
19            if(!cur->go[str[i]-'a'])
20                cur->go[str[i]-'a'] = new_Node();
21            cur = cur->go[str[i]-'a'];
22        }
23        cur->cnt++;
24    }
25    void make_fail(){
26        queue<Node*> que;
27        que.push(root);
28        while (!que.empty()){
29            Node* fr = que.front(); que.pop();
30            for (int i = 0; i < 26; i++){
31                if (fr->go[i]){
32                    Node *ptr = fr->fail;
33                    while (ptr && !ptr->go[i]) ptr = ptr->fail;
34                    fr->go[i]->fail = ptr ? ptr->go[i] : root;
35                    fr->go[i]->dic = (ptr->cnt ? ptr->dic : 0);
36                    que.push(fr->go[i]);
37                }
38            }
39        }
40    }
41 } AC;

```

9 Geomtrv

9.1 Template

```

1 // Author: Gino
2 typedef long long T;
3 // typedef long double T;
4 const long double eps = 1e-8;
5
6 short sgn(T x) {
7     if (abs(x) < eps) return 0;
8     return x < 0 ? -1 : 1;
9 }
10
11 struct Pt {
12     T x, y;
13     Pt(T _x=0, T _y=0):x(_x), y(_y) {}
14     Pt operator+(Pt a) { return Pt(x+a.x, y+a.y); }
15     Pt operator-(Pt a) { return Pt(x-a.x, y-a.y); }
16     Pt operator*(T a) { return Pt(x*a, y*a); }
17     Pt operator/(T a) { return Pt(x/a, y/a); }
18     T operator*(Pt a) { return x*a.x + y*a.y; }
19     T operator^(Pt a) { return x*a.y - y*a.x; } // 不要打反
20     bool operator<(Pt a) {
21         { return x < a.x || (x == a.x && y < a.y); }
22         // return sgn(x-a.x) < 0 || (sgn(x-a.x) == 0 && sgn(y-a.y) < 0);
23     }
24     bool operator==(Pt a) {
25         { return sgn(x-a.x) == 0 && sgn(y-a.y) == 0; }
26     }
27     Pt mv(Pt a, Pt b) { return b-a; }
28     T len2(Pt a) { return a*a; }
29     T dis2(Pt a, Pt b) { return len2(b-a); }
30
31     short ori(Pt a, Pt b) { return ((a^b)>0) - ((a^b)<0); }
32     bool onseg(Pt p, Pt l1, Pt l2) {
33         Pt a = mv(p, l1), b = mv(p, l2);

```

```

34     return ((a^b) == 0) && ((a^b) <= 0);
35 }

```

9.2 Basic Operations

```

1 // Author: Gino
2 // Function: Check if a point P sits in a polygon (doesn't
3 // have to be convex hull)
4 // 0 = Bound, 1 = In, -1 = Out
5 short inPoly(Pt p) {
6     for (int i = 0; i < n; i++)
7         if (onseg(p, E[i], E[(i+1)%n])) return 0;
8     int cnt = 0;
9     for (int i = 0; i < n; i++)
10        if (banana(p, Pt(p.x+1, p.y+2e9), E[i], E[(i+1)%n]))
11            cnt ^= 1;
12    return (cnt ? 1 : -1);
13 }

```

```

1 // Author: Gino
2 int ud(Pt a) { // up or down half plane
3     if (a.y > 0) return 0;
4     if (a.y < 0) return 1;
5     return (a.x >= 0 ? 0 : 1);
6 }
7 sort(ALL(E), [&](const Pt& a, const Pt& b){
8     if (ud(a) != ud(b)) return ud(a) < ud(b);
9     return (a^b) > 0;
10 });

```

```

1 // Author: Gino
2 // Function: check if (p1--p2) (q1--q2) banana
3 inline bool banana(Pt p1, Pt p2, Pt q1, Pt q2) {
4     if (onseg(p1, q1, q2) || onseg(p2, q1, q2) ||
5         onseg(q1, p1, p2) || onseg(q2, p1, p2)) {
6         return true;
7     }
8     Pt p = mv(p1, p2), q = mv(q1, q2);
9     return (ori(p, mv(p1, q1)) * ori(p, mv(p1, q2)) < 0 &&
10         ori(q, mv(q1, p1)) * ori(q, mv(q1, p2)) < 0);
11 }

```

```

1 // Author: Gino
2 // T: long double
3 Pt bananaPoint(Pt p1, Pt p2, Pt q1, Pt q2) {
4     if (onseg(q1, p1, p2)) return q1;
5     if (onseg(q2, p1, p2)) return q2;
6     if (onseg(p1, q1, q2)) return p1;
7     if (onseg(p2, q1, q2)) return p2;
8     double s = abs(mv(p1, p2) ^ mv(p1, q1));
9     double t = abs(mv(p1, p2) ^ mv(p1, q2));
10    return q2 * (s/(s+t)) + q1 * (t/(s+t));
11 }

```

```

1 // Author: Gino
2 vector<Pt> hull;
3 void convexHull() {
4     hull.clear(); sort(E.begin(), E.end());
5     for (int t = 0; t < 1; t++) {
6         int b = (int)hull.size();
7         for (auto& ei : E) {
8             while ((int)hull.size() - b >= 2 &&
9                 ori(mv(hull[(int)hull.size()-2],
10                     mv(hull[(int)hull.size()-2], ei)) == -1)
11                 {
12                 }
13             hull.emplace_back(ei);
14         }
15         hull.pop_back();
16         reverse(E.begin(), E.end());
17     }
18 }

```

```

1 // Author: Gino
2 // Function: Return doubled area of a polygon
3 T dbarea(vector<Pt>& e) {
4     ll res = 0;
5     for (int i = 0; i < (int)e.size(); i++)
6         res += e[i]^e[(i+1)%SZ(e)];
7     return abs(res);
8 }

```

9.3 Lower Concave Hull

```

1 // Author: Unknown
2 struct Line {
3     mutable ll m, b, p;
4     bool operator<(const Line& o) const { return m < o.m; }
5     bool operator<(ll x) const { return p < x; }
6 };
7
8 struct LineContainer : multiset<Line, less<>> {
9     // (for doubles, use inf = 1/.0, div(a,b) = a/b)

```

```

10 const ll inf = LLONG_MAX;
11 ll div(ll a, ll b) { // floored division
12     return a / b - ((a ^ b) < 0 && a % b); }
13 bool isect(iterator x, iterator y) {
14     if (y == end()) { x->p = inf; return false; }
15     if (x->m == y->m) x->p = x->b > y->b ? inf : -inf;
16     else x->p = div(y->b - x->b, x->m - y->m);
17     return x->p >= y->p;
18 }
19 void add(ll m, ll b) {
20     auto z = insert({m, b, 0}), y = z++, x = y;
21     while (isect(y, z)) z = erase(z);
22     if (x != begin() && isect(--x, y)) isect(x, y = erase(y));
23     while ((y = x) != begin() && (--x->p >= y->p)
24         isect(x, erase(y)));
25 }
26 ll query(ll x) {
27     assert(!empty());
28     auto l = *lower_bound(x);
29     return l.m * x + l.b;
30 }
31 };

```

9.4 Pick's Theorem

Consider a polygon which vertices are all lattice points.

Let i = number of points inside the polygon.

Let b = number of points on the boundary of the polygon.

Then we have the following formula:

$$\text{Area} = i + \frac{b}{2} - 1$$

9.5 Minimum Enclosing Circle

```

1 // Author: Gino
2 // Function: Find Min Enclosing Circle using Randomized O(n)
  Algorithm
3 Pt circumcenter(Pt A, Pt B, Pt C) {
4     a1(x-A.x) + b1(y-A.y) = c1
5     a2(x-A.x) + b2(y-A.y) = c2
6     // solve using Cramer's rule
7     T a1 = B.x-A.x, b1 = B.y-A.y, c1 = dis2(A, B)/2.0;
8     T a2 = C.x-A.x, b2 = C.y-A.y, c2 = dis2(A, C)/2.0;
9     T D = Pt(a1, b1) ^ Pt(a2, b2);
10    T Dx = Pt(c1, b1) ^ Pt(c2, b2);
11    T Dy = Pt(a1, c1) ^ Pt(a2, c2);
12    if (D == 0) return Pt(-INF, -INF);
13    return A + Pt(Dx/D, Dy/D);
14 }
15 Pt center; T r2;
16
17 void minEncloseCircle() {
18     mt19937
19     gen(chrono::steady_clock::now().time_since_epoch().count());
20     shuffle(ALL(E), gen);
21     center = E[0], r2 = 0;
22     for (int i = 0; i < n; i++) {
23         if (dis2(center, E[i]) <= r2) continue;
24         center = E[i], r2 = 0;
25         for (int j = 0; j < i; j++) {
26             if (dis2(center, E[j]) <= r2) continue;
27             center = (E[i] + E[j]) / 2.0;
28             r2 = dis2(center, E[i]);
29             for (int k = 0; k < j; k++) {
30                 if (dis2(center, E[k]) <= r2) continue;
31                 center = circumcenter(E[i], E[j], E[k]);
32                 r2 = dis2(center, E[i]);
33             }
34         }
35     }

```

9.6 PolyUnion

```

1 // Author: Unknown
2 struct PY{
3     int n; Pt pt[5]; double area;
4     Pt& operator[](const int x){ return pt[x]; }
5     void init(){ //n,pt[0~n-1] must be filled
6         area=pt[n-1]^pt[0];
7         for(int i=0;i<n-1;i++) area+=pt[i]^pt[i+1];
8         if((area/=2)<0)reverse(pt,pt+n),area=-area;
9     }
10 };
11 PY py[500]; pair<double,int> c[5000];
12 inline double segP(Pt &p,Pt &p1,Pt &p2){
13     if(dcmp(p1.x-p2.x)==0) return (p.y-p1.y)/(p2.y-p1.y);
14     return (p.x-p1.x)/(p2.x-p1.x);

```

```

15 }
16 double polyUnion(int n){ //py[0~n-1] must be filled
17     int i,j,ii,jj,ta,tb,r,d; double z,w,s,sum=0,tc,td;
18     for(i=0;i<n;i++) py[i][py[i].n]=py[i][0];
19     for(i=0;i<n;i++){
20         for(ii=0;ii<py[i].n;ii++){
21             r=0;
22             c[r++]=make_pair(0.0,0); c[r++]=make_pair(1.0,0);
23             for(j=0;j<n;j++){
24                 if(i==j) continue;
25                 for(jj=0;jj<py[j].n;jj++){
26                     ta=dcmp(tri(py[i][ii],py[i][ii+1],py[j][jj]));
27                     tb=dcmp(tri(py[i][ii],py[i][ii+1],py[j][jj+1]));
28                     if(ta==0 && tb==0){
29                         if((py[j][jj+1]-py[j][jj])*(py[i][ii+1]-py[i][
30                             [ii])>0&&j<i){
31                             c[r++]=make_pair(segP(py[j][jj],py[i]
32                                 [ii],py[i][ii+1]),1);
33                             c[r++]=make_pair(segP(py[j][jj+1],py[i]
34                                 [ii],py[i][ii+1]),-1);
35                         }
36                     }else if(ta>0 && tb<0){
37                         tc=tri(py[j][jj],py[j][jj+1],py[i][ii]);
38                         td=tri(py[j][jj],py[j][jj+1],py[i][ii+1]);
39                         c[r++]=make_pair(tc/(tc-td),1);
40                     }else if(ta<0 && tb>0){
41                         tc=tri(py[j][jj],py[j][jj+1],py[i][ii]);
42                         td=tri(py[j][jj],py[j][jj+1],py[i][ii+1]);
43                         c[r++]=make_pair(tc/(tc-td),-1);
44                     }
45                 }
46             }
47             sort(c,c+r);
48             z=min(max(c[0].first,0.0),1.0); d=c[0].second; s=0;
49             for(j=1;j<r;j++){
50                 w=min(max(c[j].first,0.0),1.0);
51                 if(!d) s+=w-z;
52                 d+=c[j].second; z=w;
53             }
54             sum+=(py[i][ii]^py[i][ii+1])*s;
55         }
56     }
57     return sum/2;
58 }

```

9.7 Minkowski Sum

```

1 // Author: Unknown
2 /* convex hull Minkowski Sum*/
3 #define INF 1000000000000000LL
4 int pos(const Pt& tp){
5     if( tp.Y == 0 ) return tp.X > 0 ? 0 : 1;
6     return tp.Y > 0 ? 0 : 1;
7 }
8 #define N 300030
9 Pt pt[ N ], qt[ N ], rt[ N ];
10 LL Lx,Rx;
11 int dn,un;
12 inline bool cmp( Pt a, Pt b ){
13     int pa=pos( a ),pb=pos( b );
14     if(pa==pb) return (a^b)>0;
15     return pa<pb;
16 }
17 int minkowskiSum(int n,int m){
18     int i,j,r,p,q,fi,fj;
19     for(i=1,p=0;i<n;i++){
20         if( pt[i].Y<pt[p].Y ||
21             (pt[i].Y==pt[p].Y && pt[i].X<pt[p].X) ) p=i; }
22     for(i=1,q=0;i<m;i++){
23         if( qt[i].Y<qt[q].Y ||
24             (qt[i].Y==qt[q].Y && qt[i].X<qt[q].X) ) q=i; }
25     rt[0]=pt[p]+qt[q];
26     r=1; i=p; j=q; fi=fj=0;
27     while(1){
28         if((fj&&j==q) ||
29             (!fi||i==p) &&
30             cmp(pt[(p+1)%n]-pt[p],qt[(q+1)%m]-qt[q])){
31             rt[r]=rt[r-1]+pt[(p+1)%n]-pt[p];
32             p=(p+1)%n;
33             fi=1;
34         }else{
35             rt[r]=rt[r-1]+qt[(q+1)%m]-qt[q];
36             q=(q+1)%m;
37             fj=1;
38         }
39         if(r<=1 || ((rt[r]-rt[r-1])^(rt[r-1]-rt[r-2]))!=0) r++;
40         else rt[r-1]=rt[r];
41         if(i==p && j==q) break;
42     }
43     return r-1;
44 }
45 void initInConvex(int n){
46     int i,p,q;

```



```

47 LL Ly,Ry;
48 Lx=INF; Rx=-INF;
49 for(i=0;i<n;i++){
50     if(pt[i].X<Lx) Lx=pt[i].X;
51     if(pt[i].X>Rx) Rx=pt[i].X;
52 }
53 Ly=Ry=INF;
54 for(i=0;i<n;i++){
55     if(pt[i].X==Lx && pt[i].Y<Ly){ Ly=pt[i].Y; p=i; }
56     if(pt[i].X==Rx && pt[i].Y>Ry){ Ry=pt[i].Y; q=i; }
57 }
58 for(dn=0,i=p;i!=q;i=(i+1)%n){ qt[dn++]=pt[i]; }
59 qt[dn]=pt[q]; Ly=Ry=-INF;
60 for(i=0;i<n;i++){
61     if(pt[i].X==Lx && pt[i].Y>Ly){ Ly=pt[i].Y; p=i; }
62     if(pt[i].X==Rx && pt[i].Y<Ry){ Ry=pt[i].Y; q=i; }
63 }
64 for(un=0,i=p;i!=q;i=(i+n-1)%n){ rt[un++]=pt[i]; }
65 rt[un]=pt[q];
66 }
67 inline int inConvex(Pt p){
68     int L,R,M;
69     if(p.X<Lx || p.X>Rx) return 0;
70     L=0;R=dn;
71     while(L<R-1){ M=(L+R)/2;
72         if(p.X<qt[M].X) R=M; else L=M; }
73     if(tri(qt[L],qt[R],p)<0) return 0;
74     L=0;R=un;
75     while(L<R-1){ M=(L+R)/2;
76         if(p.X<rt[M].X) R=M; else L=M; }
77     if(tri(rt[L],rt[R],p)>0) return 0;
78     return 1;
79 }
80 int main(){
81     int n,m,i;
82     Pt p;
83     scanf("%d",&n);
84     for(i=0;i<n;i++) scanf("%lld%lld",&pt[i].X,&pt[i].Y);
85     scanf("%d",&m);
86     for(i=0;i<m;i++) scanf("%lld%lld",&qt[i].X,&qt[i].Y);
87     n=minkowskiSum(n,m);
88     for(i=0;i<n;i++) pt[i]=rt[i];
89     scanf("%d",&m);
90     for(i=0;i<m;i++) scanf("%lld%lld",&qt[i].X,&qt[i].Y);
91     n=minkowskiSum(n,m);
92     for(i=0;i<n;i++) pt[i]=rt[i];
93     initInConvex(n);
94     scanf("%d",&m);
95     for(i=0;i<m;i++){
96         scanf("%lld %lld",&p.X,&p.Y);
97         p.X*=3; p.Y*=3;
98         puts(inConvex(p)?"YES":"NO");
99     }
100 }

```

10 Number Theory

10.1 Prime Sieve and Defactor

```

1 // Author: Gino
2 const int maxc = 1e6 + 1;
3 vector<int> lpf;
4 vector<int> prime;
5
6 void seive() {
7     prime.clear();
8     lpf.resize(maxc, 1);
9     for (int i = 2; i < maxc; i++) {
10         if (lpf[i] == 1) {
11             lpf[i] = i;
12             prime.emplace_back(i);
13         }
14         for (auto& j : prime) {
15             if (i * j >= maxc) break;
16             lpf[i * j] = j;
17             if (j == lpf[i]) break;
18         }
19     }
20     vector<pii> fac;
21     void defactor(int u) {
22         fac.clear();
23         while (u > 1) {
24             int d = lpf[u];
25             fac.emplace_back(make_pair(d, 0));
26             while (u % d == 0) {
27                 u /= d;
28                 fac.back().second++;
29             }
30         }
31     }
32 }

```

10.2 Harmonic Series

```

1 // Author: Gino
2 // O(n log n)

```

```

3 for (int i = 1; i <= n; i++) {
4     for (int j = i; j <= n; j += i) {
5         // O(1) code
6     }
7 }
8
9 // PIE
10 // given array a[0], a[1], ..., a[n - 1]
11 // calculate dp[x] = number of pairs (a[i], a[j]) such that
12 // gcd(a[i], a[j]) = x // (i < j)
13 //
14 // idea: let mc(x) = # of y s.t. x|y
15 // f(x) = # of pairs s.t. gcd(a[i], a[j]) >= x
16 // f(x) = C(mc(x), 2)
17 // dp[x] = f(x) - sum(dp[y], x < y and x|y)
18 const int maxc = 1e6;
19 vector<int> cnt(maxc + 1, 0), dp(maxc + 1, 0);
20 for (int i = 0; i < n; i++)
21     cnt[a[i]]++;
22
23 for (int x = maxc; x >= 1; x--) {
24     ll cnt_mul = 0; // number of multiples of x
25     for (int y = x; y <= maxc; y += x)
26         cnt_mul += cnt[y];
27
28     dp[x] = cnt_mul * (cnt_mul - 1) / 2; // number of pairs
29     // that are divisible by x
30     for (int y = x + x; y <= maxc; y += x)
31         dp[x] -= dp[y]; // PIE: subtract all dp[y] for y >
32     // x and x|y
33 }

```

10.3 Count Number of Divisors

```

1 // Author: Gino
2 // Function: Count the number of divisors for all x <= 10^6
3 // using harmonic series
4 const int maxc = 1e6;
5 vector<int> facs;
6
7 void find_all_divisors() {
8     facs.clear(); facs.resize(maxc + 1, 0);
9     for (int x = 1; x <= maxc; x++) {
10         for (int y = x; y <= maxc; y += x) {
11             facs[y]++;
12         }
13     }
14 }

```

10.4 數論分塊

```

1 // Author: Gino
2 /*
3 n = 17
4 i: 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17
5 n/i: 17 8 5 4 3 2 2 2 1 1 1 1 1 1 1 1 1
6
7           L(2)   R(2)
8
9 L(x) := left bound for n/i = x
10 R(x) := right bound for n/i = x
11
12 ===== FORMULA =====
13 >>> R = n / (n/L) <<<
14 =====
15
16 Example: L(2) = 6
17           R(2) = 17 / (17 / 6)
18              = 17 / 2
19              = 8
20 */
21 // ===== CODE =====
22
23 for (ll l = 1, r = 1, q = n; l <= n; l = r + 1) {
24     q = n/l;
25     r = n/q;
26     // Process your code here
27 }
28 // q, l, r: 17 1 1
29 // q, l, r: 8 2 2
30 // q, l, r: 5 3 3
31 // q, l, r: 4 4 4
32 // q, l, r: 3 5 5
33 // q, l, r: 2 6 8
34 // q, l, r: 1 9 17

```

10.5 Pollard's rho

```

1 // Author: Unknown
2 // Function: Find a non-trivial factor of a big number in
3 // O(n^(1/4) log^2(n))
4
5 ll find_factor(ll number) {
6     __int128 x = 2;

```

```

6   for (__int128 cycle = 1; ; cycle++) {
7       __int128 y = x;
8       for (int i = 0; i < (1<<cycle); i++) {
9           x = (x * x + 1) % number;
10          __int128 factor = __gcd(x - y, number);
11          if (factor > 1)
12              return factor;
13      }
14  }
15}

```

1# Author: Unknown

2# Function: Find a non-trivial factor of a big number in $O(n^{1/4} \log^2(n))$

3 from itertools import count

4 from math import gcd

5 from sys import stdin

```

6
7 for s in stdin:
8     number, x = int(s), 2
9     brk = False
10    for cycle in count(1):
11        y = x
12        if brk:
13            break
14        for i in range(1 << cycle):
15            x = (x * x + 1) % number
16            factor = gcd(x - y, number)
17            if factor > 1:
18                print(factor)
19                brk = True
20            break

```

10.6 Miller Rabin

1// Author: Unknown, Modified by Gino

2// Function: Check if a number is a prime in $O(100 * \log^2(n))$

3// miller_rabin(): return 1 if prime, 0 otherwise

4 inline ll mul(ll x, ll y, ll mod) {

5 return (__int128)(x) * y % mod;

6 }

7 ll mypow(ll a, ll b, ll mod) {

8 ll r = 1;

9 while (b > 0) {

10 if (b & 1) r = mul(r, a, mod);

11 a = mul(a, a, mod);

12 b >>= 1;

13 }

14 return r;

15 }

16 bool witness(ll a, ll n, ll u, int t){

17 ll x = mypow(a, u, n);

18 for(int i = 0; i < t; i++) {

19 ll nx = mul(x, x, n);

20 if (nx == 1 && x != 1 && x != n-1) return true;

21 x = nx;

22 }

23 return x != 1;

24 }

25 bool miller_rabin(ll n) {

26 // if n >= 3,474,749,660,383

27 // change {2, 3, 5, 7, 11, 13} to

28 // {2, 325, 9375, 28178, 450775, 9780504, 1795265022}

29 if (n < 2) return false;

30 if(!(n & 1)) return n == 2;

31 ll u = n - 1; int t = 0;

32 while(!(u & 1)) u >>= 1, t++;

33 for (ll a : {2, 3, 5, 7, 11, 13}) {

34 if (a % n == 0) continue;

35 if (witness(a, n, u, t)) return false;

36 }

37 return true;

38 }

39 // bases that make sure no pseudoprimes flee from test

40 // if WA, replace randll(n - 1) with these bases:

41 // n < 4,759,123,141 3 : 2, 7, 61

42 // n < 1,122,004,669,633 4 : 2, 13, 23, 1662803

43 // n < 3,474,749,660,383 6 : pirms <= 13

44 // n < 2^64 7 :

45 // 2, 325, 9375, 28178, 450775, 9780504, 1795265022

10.7 Discrete Log

1// Author: ckiseki

2// find $x^? = y \pmod{M}$

3// $O(\sqrt{M})$

4 template<typename Int>

5 Int BSGS(Int x, Int y, Int M) {

6 // $x^? \equiv y \pmod{M}$

7 Int t = 1, c = 0, g = 1;

8 for (Int M_ = M; M_ > 0; M_ >>= 1) g = g * x % M;

9 for (g = gcd(g, M); t % g != 0; ++c) {

10 if (t == y) return c;

11 t = t * x % M;

12 }

13 if (y % g != 0) return -1;

14 t /= g, y /= g, M /= g;

15 Int h = 0, gs = 1;

16 for (; h * h < M; ++h) gs = gs * x % M;

17 unordered_map<Int, Int> bs;

18 for (Int s = 0; s < h; bs[y] = ++s) y = y * x % M;

19 for (Int s = 0; s < M; s += h) {

20 t = t * gs % M;

21 if (bs.count(t)) return c + s + h - bs[t];

22 }

23 return -1;

24 }

10.8 Discrete Sqrt

1// Author: ckiseki

2// find solution for $x^2 = n \pmod{P}$

3// $O(\log^2 P)$

4 int get_root(int n, int P) { // ensure $0 \leq n < P$

5 if (P == 2 or n == 0) return n;

6 auto check = [&](ll x) {

7 return modpow(int(x), (P - 1) / 2, P);

8 }; if (check(n) != 1) return -1;

9 mt19937 rnd(7122); ll z = 1, w;

10 while (check(w = (z * z - n + P) % P) != P - 1)

11 z = rnd() % P;

12 const auto M = [P, w](auto &u, auto &v) {

13 auto [a, b] = u; auto [c, d] = v;

14 return make_pair((a * c + b * d % P * w) % P,

15 (a * d + b * c) % P);

16 };

17 pair<ll, ll> r(1, 0), e(z, 1);

18 for (int q = (P + 1) / 2; q >= 1, e = M(e, e))

19 if (q & 1) r = M(r, e);

20 return int(r.first); // sqrt(n) mod P where P is prime

21 }

10.9 Fast Power

Note: $a^n \equiv a^{(n \bmod (p-1))} \pmod{p}$

10.10 Extend GCD

1// Author: Gino

2// [Usage]

3// bezout(a, b, c):

4// find solution to $ax + by = c$

5// return {-LINF, -LINF} if no solution

6// inv(a, p):

7// find modulo inverse of a under p

8// return -1 if not exist

9// CRT(vector<ll>& a, vector<ll>& m)

10// find a solution pair (x, mod) satisfies all $x = a[i]$

(mod m[i])

11// return {-LINF, -LINF} if no solution

12 }

13 const ll LINF = 4e18;

14 typedef pair<ll, ll> pll;

15 template<typename T1, typename T2>

16 T1 chmod(T1 a, T2 m) {

17 return (a % m + m) % m;

18 }

19 }

20 ll GCD;

21 pll extgcd(ll a, ll b) {

22 if (b == 0) {

23 GCD = a;

24 return pll{1, 0};

25 }

26 pll ans = extgcd(b, a % b);

27 return pll{ans.second, ans.first - a/b * ans.second};

28 }

29 pll bezout(ll a, ll b, ll c) {

30 bool negx = (a < 0), negy = (b < 0);

31 pll ans = extgcd(abs(a), abs(b));

32 if (c % GCD != 0) return pll{-LINF, -LINF};

33 return pll{ans.first * c/GCD * (negx ? -1 : 1),

34 ans.second * c/GCD * (negy ? -1 : 1)};

35 }

36 ll inv(ll a, ll p) {

37 if (p == 1) return -1;

38 pll ans = bezout(a % p, -p, 1);

39 if (ans == pll{-LINF, -LINF}) return -1;

40 return chmod(ans.first, p);

41 }

42 pll CRT(vector<ll>& a, vector<ll>& m) {

43 for (int i = 0; i < (int)a.size(); i++)

44 a[i] = chmod(a[i], m[i]);

45 }

46 ll x = a[0], mod = m[0];

```

47 for (int i = 1; i < (int)a.size(); i++) {
48     pll sol = bezout(mod, m[i], a[i] - x);
49     if (sol.first == -LINF) return pll{-LINF, -LINF};
50
51     // prevent long long overflow
52     ll p = chmod(sol.first, m[i] / GCD);
53     ll lcm = mod / GCD * m[i];
54     x = chmod((__int128)p * mod + x, lcm);
55     mod = lcm;
56 }
57 return pll{x, mod};
58 }

```

10.11 Mu + Phi

```

1 // Author: Gino
2 const int maxn = 1e6 + 5;
3 ll f[maxn];
4 vector<int> lpf, prime;
5 void build() {
6     lpf.clear(); lpf.resize(maxn, 1);
7     prime.clear();
8     f[1] = ...; /* mu[1] = 1, phi[1] = 1 */
9     for (int i = 2; i < maxn; i++) {
10         if (lpf[i] == 1) {
11             lpf[i] = i; prime.emplace_back(i);
12             f[i] = ...; /* mu[i] = 1, phi[i] = i-1 */
13         }
14         for (auto& j : prime) {
15             if (i*j >= maxn) break;
16             lpf[i*j] = j;
17             if (i % j == 0) f[i*j] = ...; /* 0, phi[i]*j */
18             else f[i*j] = ...; /* -mu[i], phi[i]*phi[j] */
19             if (j >= lpf[i]) break;
20         }
21     }
22 }

```

10.12 Other Formulas

- Pisano Period: 任何線性遞迴 (比如費氏數列) 模任何一個數字 M 都會循環, 找循環節 $\pi(M)$ 先質因數分解 $M = \prod p_i^{e_i}$, 然後 $\pi(M) = \text{lcm}(\pi(p_i^{e_i}))$,
- Inversion: $aa^{-1} \equiv 1 \pmod{m}$. a^{-1} exists iff $\gcd(a, m) = 1$.
- Linear inversion: $a^{-1} \equiv (m - \lfloor \frac{m}{a} \rfloor) \times (m \bmod a)^{-1} \pmod{m}$
- Fermat's little theorem: $a^p \equiv a \pmod{p}$ if p is prime.
- Euler function: $\varphi(n) = n \prod_{p|n} \frac{p-1}{p}$
- Euler theorem: $a^{\varphi(n)} \equiv 1 \pmod{n}$ if $\gcd(a, n) = 1$. If a, n are not coprime: 質因數分解 $n = \prod p_i^{e_i}$, 對每個 $p_i^{e_i}$ 分開看他們跟 a 是否互質 (互質: Fermat / 不互質: 夠大的指數會直接削成 0), 最後用 CRT 合併.
- Extended Euclidean algorithm: $ax + by = \gcd(a, b) = \gcd(b, a - \lfloor \frac{a}{b} \rfloor b) = bx_1 + (a - \lfloor \frac{a}{b} \rfloor b)y_1 = ay_1 + b(x_1 - \lfloor \frac{a}{b} \rfloor y_1)$
- Divisor function: $\sigma_x(n) = \sum_{d|n} d^x$. $n = \prod_{i=1}^r p_i^{a_i}$.
 $\sigma_x(n) = \prod_{i=1}^r \frac{p_i^{(a_i+1)x} - 1}{p_i^x - 1}$ if $x \neq 0$. $\sigma_0(n) = \prod_{i=1}^r (a_i + 1)$.
- Chinese remainder theorem (Coprime Moduli):
 $M \equiv a_i \pmod{m_i}$.
 $M = \prod m_i$. $M_i = \frac{M}{m_i}$. $t_i = M_i^{-1}$.
 $x = kM + \sum a_i t_i M_i$, $k \in \mathbb{Z}$.
- Chinese remainder theorem:
 $x \equiv a_1 \pmod{m_1}, x \equiv a_2 \pmod{m_2} \Rightarrow x = m_1 p + a_1 = m_2 q + a_2 \Rightarrow m_1 p - m_2 q = a_2 - a_1$
Solve for (p, q) using ExtGCD.
 $x \equiv m_1 p + a_1 \equiv m_2 q + a_2 \pmod{\text{lcm}(m_1, m_2)}$
- Avoiding Overflow: $ca \bmod cb = c(a \bmod b)$
- Dirichlet Convolution: $(f * g)(n) = \sum_{d|n} f(d)g(\frac{n}{d})$
- Important Multiplicative Functions + Properties:
 - $\varepsilon(n) = [n=1]$
 - $1(n) = 1$
 - $id(n) = n$
 - $\mu(n) = 0$ if n has squared prime factor
 - $\mu(n) = (-1)^k$ if $n = p_1 p_2 \dots p_k$
 - $\varepsilon = \mu * 1$
 - $\varphi = \mu * id$
 - $[n=1] = \sum_{d|n} \mu(d)$
 - $[gcd=1] = \sum_{d|gcd} \mu(d)$

- Möbius inversion: $f = g * 1 \Leftrightarrow g = f * \mu$

10.13 Polynomial

```

1 // Author: Gino
2 // Preparation: first set_mod(mod, g), then init_ntt()
3 // everytime you change the mod, you have to call init_ntt()
  again
4 //
5 // [Usage]
6 // polynomial: vector<ll> a, b
7 // negation: -a
8 // add/subtract: a += b, a -= b
9 // convolution: a *= b
10 // in-place modulo: mod(a, b)
11 // in-place inversion under mod x^N: inv(ia, N)
12
13
14 const int maxk = 20;
15 const int maxn = 1<<maxk;
16
17 using u64 = unsigned long long;
18 using u128 = __uint128_t;
19
20 int g;
21 u64 MOD;
22 u64 BARRETT_IM; // [ 2^64 / MOD ]
23
24 inline void set_mod(u64 m, int _g) {
25     g = _g;
26     MOD = m;
27     BARRETT_IM = (u128(1) << 64) / m;
28 }
29
30 inline u64 chmod(u128 x) {
31     u64 q = (u64)((x * BARRETT_IM) >> 64);
32     u64 r = (u64)(x - (u128)q * MOD);
33     if (r >= MOD) r -= MOD;
34     return r;
35 }
36
37 inline u64 mmul(u64 a, u64 b) {
38     return chmod((u128)a * b);
39 }
40
41 ll pw(ll a, ll n) {
42     ll ret = 1;
43     while (n > 0) {
44         if (n & 1) ret = mmul(ret, a);
45         a = mmul(a, a);
46         n >>= 1;
47     }
48     return ret;
49 }
50
51 vector<ll> X, iX;
52 vector<int> rev;
53 void init_ntt() {
54     X.assign(maxn, 1); // x1 = g^((p-1)/n)
55     iX.assign(maxn, 1);
56
57     ll u = pw(g, (MOD-1)/maxn);
58     ll iu = pw(u, MOD-2);
59     for (int i = 1; i < maxn; i++) {
60         X[i] = mmul(X[i-1], u);
61         iX[i] = mmul(iX[i-1], iu);
62     }
63
64     if ((int)rev.size() == maxn) return;
65     rev.assign(maxn, 0);
66     for (int i = 1, hb = -1; i < maxn; i++) {
67         if (!(i & (i-1))) hb++;
68         rev[i] = rev[i ^ (1<<hb)] | (1<<(maxk-hb-1));
69     }
70 }
71
72 template<typename T>
73 void NTT(vector<T>& a, bool inv=false) {
74     int _n = (int)a.size();
75     int k = __lg(_n) + ((1<<__lg(_n)) != _n);
76     int n = 1<<k;
77     a.resize(n, 0);
78
79     short shift = maxk-k;
80     for (int i = 0; i < n; i++)
81         if (i > (rev[i]>>shift))
82             swap(a[i], a[rev[i]>>shift]);
83
84     for (int len = 2, half = 1, div = maxn>>1; len <= n; len<<=1, half<<=1, div>>=1) {
85         for (int i = 0; i < n; i += len) {
86             for (int j = 0; j < half; j++) {
87                 T u = a[i+j];
88                 T v = mmul(a[i+j+half], (inv ? iX[j*div] : X[j*div]));
89                 a[i+j] = (u+v >= MOD ? u+v-MOD : u+v);
90                 a[i+j+half] = (u-v < 0 ? u-v+MOD : u-v);
91             }
92         }
93     }
94 }

```

```

85     } } }
86     if (inv) {
87         T dn = pw(n, MOD-2);
88         for (auto& x : a) {
89             x = mmul(x, dn);
90         } }
91     template<typename T>
92     inline void shrink(vector<T>& a) {
93         int cnt = (int)a.size();
94         for (; cnt > 0; cnt--) if (a[cnt-1]) break;
95         a.resize(max(cnt, 1));
96     }
97     template<typename T>
98     vector<T>& operator*=(vector<T>& a, vector<T> b) {
99         int na = (int)a.size();
100        int nb = (int)b.size();
101        a.resize(na + nb - 1, 0);
102        b.resize(na + nb - 1, 0);
103
104        NTT(a); NTT(b);
105        for (int i = 0; i < (int)a.size(); i++)
106            a[i] = mmul(a[i], b[i]);
107        NTT(a, true);
108
109        shrink(a);
110        return a;
111    }
112    inline ll crt(ll a0, ll a1, ll m1, ll m2, ll inv_m1_mod_m2) {
113        // x ≡ a0 (mod m1), x ≡ a1 (mod m2)
114        // t = (a1 - a0) * inv(m1) mod m2
115        // x = a0 + t * m1 (mod m1*m2)
116        ll t = chmod(a1 - a0);
117        if (t < 0) t += m2;
118        t = (ll)((__int128)t * inv_m1_mod_m2 % m2);
119        return a0 + (ll)((__int128)t * m1);
120    }
121    void mul_crt() {
122        // a copy to a1, a2 | b copy to b1, b2
123        ll M1 = 998244353, M2 = 1004535809;
124        g = 3; set_mod(M1); init_ntt(); a1 *= b1;
125        g = 3; set_mod(M2); init_ntt(); a2 *= b2;
126
127        ll inv_m1_mod_m2 = pw(M1, M2 - 2);
128        for (int i = 2; i <= 2 * k; i++)
129            cout << crt(a1[i], a2[i], M1, M2, inv_m1_mod_m2) <<
130            '\n';
131        cout << endl;
132    }
133    /* P = r*2^k + 1
134    P      r      k      g
135    998244353      119 23 3
136    1004535809      479 21 3
137
138    P      r      k      g
139    3          1      1  2
140    5          1      2  2
141    17         1      4  3
142    97         3      5  5
143    193        3      6  5
144    257        1      8  3
145    7681       15     9  17
146    12289      3     12  11
147    40961      5     13  3
148    65537      1     16  3
149    786433     3     18  10
150    5767169    11     19  3
151    7340033     7     20  3
152    23068673    11     21  3
153    104857601   25     22  3
154    167772161   5     25  3
155    469762049   7     26  3
156    1004535809  479    21  3
157    2013265921  15     27  31
158    2281701377  17     27  3
159    3221225473  3     30  5
160    75161927681 35     31  3
161    77309411329 9      33  7
162    206158430209 3     36  22
163    2061584302081 15    37  7
164    2748779069441 5     39  3
165    6597069766657 3     41  5
166    39582418599937 9     42  5
167    79164837199873 9     43  5
168    263882790666241 15   44  7
169    1231453023109121 35   45  3
170    1337006139375617 19   46  3
171    3799912185593857 27   47  5

```

```

172 4222124650659841      15  48  19
173 7881299347898369      7   50  6
174 31525197391593473      7   52  3
175 180143985094819841      5   55  6
176 1945555039024054273 27   56  5
177 4179340454199820289 29   57  3
178 9097271247288401921 505  54  6 */

```

10.14 Counting Primes

```

1 // prime count - #primes in [1..n] (O(n^{2/3}) time,
2 // O(sqrt(n)) memory)
3 using u64 = unsigned long long;
4 static inline u64 prime_count(u64 n) {
5     if (n <= 1) return 0;
6     int v = (int)floor(sqrt((long double)n));
7     int s = (v+1)>>1, pc = 0;
8     vector<int> smalls(s), roughs(s), skip(v+1);
9     vector<long long> larges(s);
10
11     for (int i=0; i<s; ++i) {
12         smalls[i] = i;
13         roughs[i] = 2*i+1;
14         larges[i] = (long long)((n/roughs[i]-1)>>1);
15     }
16
17     for (int p=3; p<=v; p+=2) if (!skip[p]) {
18         int q = p*p;
19         if (1LL*q > (long long)n) break;
20         skip[p] = 1;
21         for (int i=q; i<=v; i+=2*p) skip[i] = 1;
22
23         int ns=0;
24         for (int k=0; k<s; ++k) {
25             int i = roughs[k];
26             if (skip[i]) continue;
27             u64 d = (u64)i * (u64)p;
28             long long sub = (d <= (u64)v)
29                 ? larges[smalls[(int)(d>>1)] - pc]
30                 : smalls[(int)((n/d - 1) >> 1)];
31             larges[ns] = larges[k] - sub + pc;
32             roughs[ns++] = i;
33         }
34         s = ns;
35         for (int i=(v-1)>>1, j=((v/p)-1)|1; j>=p; j-=2) {
36             int c = smalls[j>>1] - pc;
37             for (int e=(j*p)>>1; i>=e; --i) smalls[i] -= c;
38         }
39         ++pc;
40     }
41
42     larges[0] += 1LL*(s + 2*(pc-1))*(s-1) >> 1;
43     for (int k=1; k<s; ++k) larges[0] -= larges[k];
44
45     for (int l=1; l<s; ++l) {
46         int q = roughs[l];
47         u64 m = n / (u64)q;
48         long long t = 0;
49         int e = smalls[(int)((m/q - 1) >> 1)] - pc;
50         if (e < l+1) break;
51         for (int k=l+1; k<=e; ++k) t += smalls[(int)((m/
52             (u64)roughs[k] - 1) >> 1)];
53         larges[0] += t - 1LL*(e - l)*(pc + l - 1);
54     }
55     return (u64)(larges[0] + 1);

```

10.15 Linear Sieve for Other Number Theoretic Functions

```

1 // linear_sieve(n, primes, lp, phi, mu, d, sigma)
2 // Outputs over the index range 0..n (n >= 1):
3 // primes : all primes in [2..n], increasing.
4 // lp      : lowest prime factor; lp[1]=0, lp[x] is the
5 //            smallest prime dividing x.
6 // phi     : Euler totient, phi[x] = |{1<=k<=x :
7 //            gcd(k,x)=1}|. Multiplicative.
8 // mu      : Möbius; mu[1]=1, mu[x]=0 if x has a squared
9 //            prime factor, else (-1)^{#distinct primes}.
10 // d       : number of divisors; if x=∏ p_i^{e_i}, then
11 //            d[x]=∏(e_i+1). Multiplicative.
12 // sigma   : sum of divisors; if x=∏ p_i^{e_i}, then
13 //            sigma[x]=∏(1+p_i+...+p_i^{e_i}). (use ll)
14 //
15 // Complexity: O(n) time, O(n) memory.
16 // Notes: Arrays are resized inside; primes is cleared and
17 //         reserved. sigma uses ll to avoid 32-bit overflow.
18
19 static inline void linear_sieve(
20     int n,
21     std::vector<int> &primes,
22     std::vector<int> &lp,

```



```

17 std::vector<int> &phi,
18 std::vector<int> &mu,
19 std::vector<int> &d,
20 std::vector<ll> &sigma
21 ) {
22   lp.assign(n + 1, 0); phi.assign(n + 1, 0); mu.assign(n +
23   1, 0); d.assign(n + 1, 0); sigma.assign(n + 1, 0);
24   primes.clear(); primes.reserve(n > 1 ? n / 10 : 0);
25   std::vector<int> cnt(n + 1, 0), core(n + 1, 1);
26   std::vector<ll> p_pow(n + 1, 1), sum_p(n + 1, 1);
27   phi[1] = mu[1] = d[1] = sigma[1] = 1;
28   for (int i = 2; i <= n; ++i) {
29     if (!lp[i]) {
30       lp[i] = i; primes.push_back(i);
31       phi[i] = i - 1; mu[i] = -1; d[i] = 2;
32       cnt[i] = 1; p_pow[i] = i; core[i] = 1;
33       sum_p[i] = 1 + (ll)i; sigma[i] = sum_p[i];
34     }
35     for (int p : primes) {
36       long long ip = 1LL * i * p;
37       if (ip > n) break;
38       lp[ip] = p;
39       if (p == lp[i]) {
40         cnt[ip] = cnt[i] + 1; p_pow[ip] = p_pow[i] * p;
41         core[ip] = core[i];
42         sum_p[ip] = sum_p[i] + p_pow[ip];
43         phi[ip] = phi[i] * p; mu[ip] = 0;
44         d[ip] = d[core[ip]] * (cnt[ip] + 1);
45         sigma[ip] = sigma[core[ip]] * sum_p[ip];
46         break; // critical for linear complexity
47       } else {
48         cnt[ip] = 1; p_pow[ip] = p; core[ip] = i;
49         sum_p[ip] = 1 + (ll)p;
50         phi[ip] = phi[i] * (p - 1); mu[ip] = -mu[i];
51         d[ip] = d[i] * 2;
52         sigma[ip] = sigma[i] * sum_p[ip];
53       }
54     }
55   }
56   // Optional helper: factorize x in O(log x) using lp
57   (requires x in [2..n])
58   static inline std::vector<std::pair<int,int>> factorize(int
59   x, const std::vector<int>& lp) {
60     std::vector<std::pair<int,int>> res;
61     while (x > 1) {
62       int p = lp[x], e = 0;
63       do { x /= p; ++e; } while (x % p == 0);
64       res.push_back({p, e});
65     }
66     return res;

```

11 Linear Algebra

11.1 Gaussian-Jordan Elimination

```

1 int n; vector<vector<ll>> > v;
2 void gauss(vector<vector<ll>>& v) {
3   int r = 0;
4   for (int i = 0; i < n; i++) {
5     bool ok = false;
6     for (int j = r; j < n; j++) {
7       if (v[j][i] == 0) continue;
8       swap(v[j], v[r]);
9       ok = true; break;
10    }
11    if (!ok) continue;
12    ll div = inv(v[r][i]);
13    for (int j = 0; j < n+1; j++) {
14      v[r][j] *= div;
15      if (v[r][j] >= MOD) v[r][j] %= MOD;
16    }
17    for (int j = 0; j < n; j++) {
18      if (j == r) continue;
19      ll t = v[j][i];
20      for (int k = 0; k < n+1; k++) {
21        v[j][k] -= v[r][k] * t % MOD;
22        if (v[j][k] < 0) v[j][k] += MOD;
23      }
24      r++;
25    }

```

11.2 Determinant

1. Use GJ Elimination, if there's any row consists of only 0, then $\det = 0$, otherwise $\det = \text{product of diagonal elements}$.
2. Properties of $\det$:
 - Transpose: Unchanged
 - Row Operation 1 - Swap 2 rows: $-\det$

- Row Operation 2 - $k\vec{r}_i$: $k \times \det$
- Row Operation 3 - $k\vec{r}_i$ add to $\vec{r}_j$: Unchanged

12 Flow / Matching

12.1 Flow Methods

```

1 // Author: CRYPTOGRAPHER (some modified by Gino)
2 Maximize  $c^T x$  subject to  $Ax \leq b, x \geq 0$ ;
3 with the corresponding symmetric dual problem,
4 Minimize  $b^T y$  subject to  $A^T y \geq c, y \geq 0$ .
5
6 Maximize  $c^T x$  subject to  $Ax \leq b$ ;
7 with the corresponding asymmetric dual problem,
8 Minimize  $b^T y$  subject to  $A^T y = c, y \geq 0$ .
9
10 Maximize  $\sum x$  subject to  $x_i + x_j \leq A_{ij}, x \geq 0$ ;
11 => Maximize  $\sum x$  subject to  $x_i + x_j \leq A_{ij}$ ;
12 => Minimize  $A^T y = \sum A_{ij} y_{ij}$  subject to for all  $v$ ,
13    $\sum_{i=v \text{ or } j=v} y_{ij} = 1, y_{ij} \geq 0$ 
14 => possible optimal solution:  $y_{ij} = \{0, 0.5, 1\}$ 
15 =>  $y' = 2y$ :  $\sum_{i=v \text{ or } j=v} y'_{ij} = 2, y'_{ij} = \{0, 1, 2\}$ 
16
17 General Graph:
18 |Max Ind. Set| + |Min Vertex Cover| = |V|
19 |Max Ind. Edge Set| + |Min Edge Cover| = |V|
20 Bipartite Graph:
21 |Max Ind. Set| = |Min Edge Cover|
22 |Max Ind. Edge Set| = |Min Vertex Cover|
23
24 To reconstruct the minimum vertex cover, dfs from each
25 unmatched vertex on the left side and with unused edges
26 only. Equivalently, dfs from source with unused edges
27 only and without visiting sink. Then, a vertex is
28 chosen iff. it is on the left side and without visited
29 or on the right side and visited through dfs.
30
31 Minimum Weighted Bipartite Edge Cover:
32 Construct new bipartite graph with  $n+m$  vertices on each
33 side:
34 for each vertex  $u$ , duplicate a vertex  $u'$  on the other side
35 for each edge  $(u,v,w)$ , add edges  $(u,v,w)$  and  $(v',u',w)$ 
36 for each vertex  $u$ , add edge  $(u,u',2w)$  where  $w$  is min edge
37 connects to  $u$ 
38 then the answer is the minimum perfect matching of the new
39 graph (KM)
40
41 Maximum density subgraph (  $\sum W_e + \sum W_v$  ) / |V|
42 Binary search on answer:
43 For a fixed  $D$ , construct a Max flow model as follow:
44 Let  $S$  be Sum of all weight ( or inf)
45 1. from source to each node with  $\text{cap} = S$ 
46 2. For each  $(u,v,w)$  in  $E$ ,  $(u \rightarrow v, \text{cap}=w), (v \rightarrow u, \text{cap}=w)$ 
47 3. For each node  $v$ , from  $v$  to sink with  $\text{cap} = S + 2 * D - \text{deg}[v] - 2 * (W \text{ of } v)$ 
48 where  $\text{deg}[v] = \sum \text{weight of edge associated with } v$ 
49 If  $\text{maxflow} < S * |V|$ ,  $D$  is an answer.
50
51 Requiring subgraph: all vertex can be reached from source
52 with
53 edge whose  $\text{cap} > 0$ .
54
55 Maximum closed subgraph
56 1. connect source with positive weighted
57 vertex( $\text{capacity}=\text{weight}$ )
58 2. connect sink with negative weighted vertex( $\text{capacity}=-\text{weight}$ )
59 3. make capacity of the original edges = inf
60 4. ans = sum(positive weighted vertex weight) - (max flow)
61
62 (Node-disjoint) Min DAG Path Cover (用最少路徑覆蓋所有點)
63 Node disjoint: 拆出來的路徑不能共用同一個點
64 將一個點  $u$  裂成  $u_+$  和  $u_-$ , 代表進入和出去
65 對於一條邊  $(u, v)$  建邊  $u_- \Rightarrow v_+$ 
66 1. 點們和 - 點們形成一張二分圖
67 2. 最差的答案是  $n$ , 代表每個點自己一個點就是一條路徑
68 3. 只要一組  $(u_-, v_+)$  匹配成功那對應到的答案恰好會 -1
69 >>> ans =  $n - \text{這張二分圖的最大匹配}$ 
70
71 General DAG Path Cover
72 跟 Node-disjoint 版本差在點可以被很多條路共用
73 建邊方式 Node-disjoint 差別在條件比較鬆
74 Node-disjoint:  $u_- \Rightarrow v_+$  只能在  $(u, v)$  有邊時建
75 General:  $u_- \Rightarrow v_+$  在  $u$  能走到  $v$  的時候就建
76
77 Dilworth Theorem
78 反鏈: 一些節點的集合, 滿足這些節點互相無法抵達
79 最大反鏈 = 最小 General DAG Path Cover
80
81 Dinic
82 // Author: Benson (Extensions by Gino)
83 // Function: Max Flow,  $O(V^2 E)$ 

```



```

3// Usage: Call init(n) first, then add(u, v, w) based on
  your model
4// (!) vertices 0-based
5// >>> flow() := return max flow
6// >>> find_cut() := return min cut + store cut set in
  dinic.cut
7// >>> find_matching() := return |M| + store matching plan
  in dinic.matching
8// >>> flow_decomposition := return max flow + store
  decomposition in dinic.D
9#define int long long
10#define eb emplace_back
11#define ALL(a) a.begin(), a.end()
12struct Dinic {
13    struct Edge {
14        // t: to | C: original capacity | c: current capacity |
15        r: residual edge | f: current flow
16        int t, C, c, r, f;
17        bool fw; // is in forward-edge graph
18        Edge() {}
19        Edge(int t, int C, int r, bool fw, int f=0):
20            t(t), C(C), c(C), r(r), fw(fw), f(f) {}
21    };
22    vector<vector<Edge>> G;
23    vector<int> dis, iter;
24    int n, s, t;
25    void init(int _n) {
26        n = _n;
27        G.resize(n), dis.resize(n), iter.resize(n);
28        for(int i = 0; i < n; ++i)
29            G[i].clear();
30    }
31    void add(int a, int b, int c) {
32        G[a].eb(b, c, G[b].size(), true);
33        G[b].eb(a, 0, G[a].size() - 1, false);
34    }
35    bool bfs() {
36        fill(ALL(dis), -1);
37        dis[s] = 0;
38        queue<int> que;
39        que.push(s);
40        while(!que.empty()) {
41            int u = que.front(); que.pop();
42            for(auto& e : G[u]) {
43                if(e.c > 0 && dis[e.t] == -1) {
44                    dis[e.t] = dis[u] + 1;
45                    que.push(e.t);
46                }
47            }
48        }
49        return dis[t] != -1;
50    }
51    int dfs(int u, int cur) {
52        if(u == t) return cur;
53        for(int &i = iter[u]; i < (int)G[u].size(); ++i) {
54            auto& e = G[u][i];
55            if(e.c > 0 && dis[u] + 1 == dis[e.t]) {
56                int ans = dfs(e.t, min(cur, e.c));
57                if(ans > 0) {
58                    G[e.t][e.r].c += ans;
59                    e.c -= ans;
60                    return ans;
61                }
62            }
63        }
64        return 0;
65    }
66    // find max flow
67    int flow(int a, int b) {
68        s = a, t = b;
69        int ans = 0;
70        while(bfs()) {
71            fill(ALL(iter), 0);
72            int tmp;
73            while((tmp = dfs(s, INF)) > 0)
74                ans += tmp;
75        }
76        return ans;
77    }
78    // min cut plan
79    vector<pair<pair<int, int>, int>> cut;
80    int find_cut(int a, int b) {
81        int cut_sz = flow(a, b);
82        vector<int> vis(n, 0);
83        cut.clear();
84        function<void(int)> dfs = [&](int u) {
85            vis[u] = 1;
86            for(auto& e : G[u])
87                if(e.c > 0 && !vis[e.t])
88                    dfs(e.t);
89        };
90        dfs(a);
91        for(int u = 0; u < n; u++)

```

```

87        if(vis[u])
88            for(auto& e : G[u])
89                if(!vis[e.t])
90                    cut.eb(make_pair(make_pair(u, e.t), G[e.t]
91                        [e.r].c));
92        return cut_sz;
93    }
94    // bipartite matching plan
95    vector<pair<int, int>> matching;
96    int find_matching(int Xstart, int Xend, int Ystart, int
97        Yend, int a, int b) {
98        int msz = flow(a, b);
99        matching.clear();
100        for(int x = Xstart; x <= Xend; x++)
101            for(auto& e : G[x])
102                if(e.c == 0 && Ystart <= e.t && e.t <= Yend)
103                    matching.emplace_back(make_pair(x, e.t));
104        return msz;
105    }
106    // flow decomposition
107    vector<pair<int, vector<int>>> D; // (flow amount, [path
108        p1 ... pk])
109    int flow_decomposition(int a, int b) {
110        int mxflow = flow(a, b);
111        vector<vector<Edge>> fG(n); // graph consists of forward
112            edges
113        for(int u = 0; u < n; u++) {
114            for(auto& e : G[u]) {
115                if(e.fw) {
116                    e.f = e.C - e.c;
117                    if(e.f > 0) fG[u].eb(e);
118                }
119            }
120        }
121        vector<int> vis;
122        function<int(int, int)> dfs = [&](int u, int cur) {
123            if(u == b) {
124                D.back().second.eb(u);
125                return cur;
126            }
127            vis[u] = 1;
128            for(auto& e : fG[u]) {
129                if(e.f > 0 && !vis[e.t]) {
130                    int ans = dfs(e.t, min(cur, e.f));
131                    if(ans > 0) {
132                        e.f -= ans;
133                        D.back().second.eb(u);
134                        return ans;
135                    }
136                }
137            }
138            return 0LL;
139        };
140        D.clear();
141        int quota = mxflow;
142        while(quota > 0) {
143            D.emplace_back(make_pair(0, vector<int>()));
144            vis.assign(n, 0);
145            int f = dfs(a, INF);
146            if(f == 0) break;
147            reverse(D.back().second.begin(),
148                D.back().second.end());
149            D.back().first = f, quota -= f;
150        }
151        return mxflow;
152    }
153 };

```

12.3 ISAP

```

1// Author: CRYptoGRapHeR
2#define SZ(c) ((int)(c).size())
3static const int MAXV=50010;
4static const int INF =1000000;
5struct Maxflow{
6    struct Edge{
7        int v,c,r;
8        Edge(int _v,int _c,int _r):v(_v),c(_c),r(_r){}
9    };
10    int s,t; vector<Edge> G[MAXV];
11    int iter[MAXV],d[MAXV],gap[MAXV],tot;
12    void init(int n,int _s,int _t){
13        tot=n,s=_s,t=_t;
14        for(int i=0;i<=tot;i++){
15            G[i].clear(); iter[i]=d[i]=gap[i]=0;
16        }
17    }
18    void addEdge(int u,int v,int c){
19        G[u].push_back(Edge(v,c,SZ(G[v])));
20        G[v].push_back(Edge(u,0,SZ(G[u])-1));
21    }
22    int DFS(int p,int flow){

```

```

23     if(p==t) return flow;
24     for(int &i=iter[p]; i<SZ(G[p]); i++){
25         Edge &e=G[p][i];
26         if(e.c>0&&d[p]==d[e.v]+1){
27             int f=DFS(e.v,min(flow,e.c));
28             if(f){ e.c-=f; G[e.v][e.r].c+=f; return f; }
29         }
30     }
31     if(--gap[d[p]]==0) d[s]=tot;
32     else{ d[p]++; iter[p]=0; ++gap[d[p]]; }
33     return 0;
34 }
35 int flow(){
36     int res=0;
37     for(res=0,gap[0]=tot;d[s]<tot;res+=DFS(s,INF));
38     return res;
39 } // reset: set iter,d,gap to 0
40 } flow:

```

12.4 Bounded Max Flow

```

1// Author: CRYPTOGRAPHER
2// Max flow with lower/upper bound on edges
3// use with ISAP, l,r,a,b must be filled
4int in[N],out[N],l[M],r[M],a[M],b[M];
5int solve(int n, int m, int s, int t){
6    flow.init(n+2,n,n+1);
7    for(int i=0;i<m;i++){
8        in[r[i]]+=a[i]; out[l[i]]+=a[i];
9        flow.addEdge(l[i],r[i],b[i]-a[i]);
10       // flow from l[i] to r[i] must in [a[i], b[i]]
11    }
12    int nd=0;
13    for(int i=0;i<=n;i++){
14        if(in[i]<out[i]){
15            flow.addEdge(i,flow.t,out[i]-in[i]);
16            nd+=out[i]-in[i];
17        }
18        if(out[i]<in[i])
19            flow.addEdge(flow.s,i,in[i]-out[i]);
20    }
21    // original sink to source
22    flow.addEdge(t,s,INF);
23    if(flow.flow()!=nd) return -1; // no solution
24    int ans=flow.G[s].back().c; // source to sink
25    flow.G[s].back().c=flow.G[t].back().c=0;
26    // take out super source and super sink
27    for(size_t i=0;i<flow.G[flow.s].size();i++){
28        Maxflow::Edge &e=flow.G[flow.s][i];
29        flow.G[flow.s][i].c=0; flow.G[e.v][e.r].c=0;
30    }
31    for(size_t i=0;i<flow.G[flow.t].size();i++){
32        Maxflow::Edge &e=flow.G[flow.t][i];
33        flow.G[flow.t][i].c=0; flow.G[e.v][e.r].c=0;
34    }
35    flow.addEdge(flow.s,s,INF);flow.addEdge(t,flow.t,INF);
36    flow.reset(); return ans+flow.flow();
37}

```

12.5 MCMF

```

1// Author: CRYPTOGRAPHER
2// Usage:
3// 1. MCMF.init(n, s, t)
4// 2. MCMF.add(u, v, cap, cost)
5// 3. auto [max_flow, min_cost] = MCMF.flow()
6typedef int Tcost;
7const int MAXV = 20010;
8const int INFf = 1000000;
9const Tcost INFc = 1e9;
10struct MCMF {
11    struct Edge{
12        int v, cap;
13        Tcost w;
14        int rev;
15        bool fw;
16        Edge(){}
17        Edge(int t2, int t3, Tcost t4, int t5, bool t6)
18            : v(t2), cap(t3), w(t4), rev(t5), fw(t6) {}
19    };
20    int V, s, t;
21    vector<Edge> G[MAXV];
22    void init(int n){
23        V = n;
24        for(int i = 0; i <= V; i++) G[i].clear();
25    }
26    void add(int a, int b, int cap, Tcost w){
27        G[a].push_back(Edge(b, cap, w, (int)G[b].size(), true));
28        G[b].push_back(Edge(a, 0, -w, (int)G[a].size()-1, false));
29    }
30    Tcost d[MAXV];

```

```

31    int id[MAXV], mom[MAXV];
32    bool inqu[MAXV];
33    queue<int> q;
34    pair<int, Tcost> flow(int _s, int _t){
35        s = _s, t = _t;
36        int mxf = 0, Tcost mnc = 0;
37        while(1){
38            fill(d, d+1+V, INFc); // need to use type cast
39            fill(inqu, inqu+1+V, 0);
40            fill(mom, mom+1+V, -1);
41            mom[s] = s;
42            d[s] = 0;
43            q.push(s); inqu[s] = 1;
44            while(q.size()){
45                int u = q.front(); q.pop();
46                inqu[u] = 0;
47                for(int i = 0; i < (int) G[u].size(); i++){
48                    Edge &e = G[u][i];
49                    int v = e.v;
50                    if(e.cap > 0 && d[v] > d[u]+e.w){
51                        d[v] = d[u]+e.w;
52                        mom[v] = u;
53                        id[v] = i;
54                        if(!inqu[v]) q.push(v), inqu[v] = 1;
55                    }
56                }
57            }
58            if(mom[t] == -1) break;
59            int df = INFf;
60            for(int u = t; u != s; u = mom[u])
61                df = min(df, G[mom[u]][id[u]].cap);
62            for(int u = t; u != s; u = mom[u]){
63                Edge &e = G[mom[u]][id[u]];
64                e.cap -= df;
65                G[e.v][e.rev].cap += df;
66            }
67            mxf += df;
68            mnc += df*d[t];
69        }
70        return make_pair(mxf, mnc);
71    }
72}

```

12.6 Hopcroft-Karp

```

1// Author: Gino
2// Function: Max Bipartite Matching in O(V sqrt(E))
3// Usage:
4// >>> init(nx, ny, m) -> add(x, y (+nx))
5// >>> hk.max_matching() := the matching plan stores in mx, my
6// >>> hk.min_vertex_cover() := the vertex cover plan stores in vcover
7// (!) vertices are 0-based: X = [0, nx), Y = [nx, nx+ny)
8struct HopcroftKarp {
9    int n, nx, ny;
10    vector<vector<int>> > G;
11    vector<int> mx, my;
12    void init(int _nx, int _ny) {
13        nx = _nx, ny = _ny;
14        n = nx + ny;
15        G.clear(); G.resize(n);
16    }
17    void add(int x, int y) {
18        G[x].emplace_back(y);
19        G[y].emplace_back(x);
20    }
21    int max_matching() {
22        vector<int> dis, vis;
23        mx.clear(); mx.resize(n, -1);
24        my.clear(); my.resize(n, -1);
25
26        function<bool(int)> dfs = [&](int x) {
27            vis[x] = true;
28            for (auto& y : G[x]) {
29                int px = my[y];
30                if (px == -1 ||
31                    (dis[px] == dis[x]+1 &&
32                     !vis[px] && dfs(px))) {
33                    mx[x] = y;
34                    my[y] = x;
35                    return true;
36                }
37            }
38            return false;
39        };
40        while (true) {
41            queue<int> q;
42            dis.clear(); dis.resize(n, -1);
43            for (int x = 0; x < nx; x++){

```

```

44     if (mx[x] == -1) {
45         dis[x] = 0;
46         q.push(x);
47     } }
48     while (!q.empty()) {
49         int x = q.front(); q.pop();
50         for (auto& y : G[x]) {
51             if (my[y] != -1 && dis[my[y]] == -1) {
52                 dis[my[y]] = dis[x] + 1;
53                 q.push(my[y]);
54             } }
55         bool brk = true;
56         vis.clear(); vis.resize(n, 0);
57         for (int x = 0; x < nx; x++)
58             if (mx[x] == -1 && dfs(x))
59                 brk = false;
60         if (brk) break;
61     }
62     int ans = 0;
63     for (int x = 0; x < nx; x++) if (mx[x] != -1) ans++;
64     return ans;
65 }
66 vector<int> vcover;
67 int min_vertex_cover() {
68     int ans = max_matching();
69     vcover.clear();
70
71     vector<int> vis(n, 0);
72     function<void(int)> dfs = [&](int x) {
73         vis[x] = true;
74         for (auto& y : G[x]) {
75             if (y == mx[x] || my[y] == -1 || vis[y]) continue;
76             vis[y] = true;
77             dfs(my[y]);
78         }
79     };
80
81     for (int x = 0; x < nx; x++) if (mx[x] == -1) dfs(x);
82     for (int x = 0; x < nx; x++) if (!vis[x])
83         vcover.emplace_back(x);
84     for (int y = nx; y < nx + ny; y++) if (vis[y])
85         vcover.emplace_back(y);
86     return ans;
87 }
88 }
89 }

```

12.7 Cover / Independent Set

1 最大邊獨立集 (Ie) 就是最大匹配 (M)
2 二分圖上，M 和 Cv 對偶
3 對任何圖都有 $|Iv| + |Cv| = |V|$
4 對任何圖都有 $|Ie| + |Ce| = |V|$
5 二分圖最小帶權點覆蓋 $\Rightarrow$ 建模 (s, u, w[u]) (u, v, INF) (v, t, w[v]) 算最小割

12.8 Kuhn Munkres

```

1 // Author: CRyptoGRapheR
2 static const int MXN=2001; // 1-based
3 static const ll INF=0x3f3f3f3f;
4 struct KM { // max weight, for min negate the weights
5     int n, mx[MXN], my[MXN], pa[MXN]; bool vx[MXN], vy[MXN];
6     ll g[MXN][MXN], lx[MXN], ly[MXN], sy[MXN];
7     void init(int _n) {
8         n = _n; for (int i=1; i<=n; i++) fill(g[i], g[i]+n+1, 0);
9     }
10    void addEdge(int x, int y, ll w) { g[x][y]=w; }
11    void addEdge(int y) {
12        for (int x, z; y=z) x=pa[y], z=mx[x], my[y]=x, mx[x]=y;
13    }
14    void bfs(int st) {
15        for (int i=1; i<=n; ++i) sy[i]=INF, vx[i]=vy[i]=0;
16        queue<int> q; q.push(st);
17        for (;;) {
18            while (q.size()) {
19                int x=q.front(); q.pop(); vx[x]=1;
20                for (int y=1; y<=n; ++y) if (!vy[y]) {
21                    ll t=lx[x]+ly[y]-g[x][y];
22                    if (t==0) {
23                        pa[y]=x;
24                        if (!my[y]) { augment(y); return; }
25                        vy[y]=1, q.push(my[y]);
26                    } else if (sy[y]>t) pa[y]=x, sy[y]=t;
27                }
28            }
29            ll cut=INF;
30            for (int y=1; y<=n; ++y)
31                if (!vy[y] && cut>sy[y]) cut=sy[y];
32            for (int j=1; j<=n; ++j) {
33                if (vx[j]) lx[j]-=cut;
34                if (vy[j]) ly[j]+=cut;
35                else sy[j]-=cut;

```

```

36    }
37    for (int y=1; y<=n; ++y) if (!vy[y] && sy[y]==0) {
38        if (!my[y]) { augment(y); return; }
39        vy[y]=1, q.push(my[y]);
40    } } }
41    ll solve() {
42        fill(mx, mx+n+1, 0); fill(my, my+n+1, 0);
43        fill(ly, ly+n+1, 0); fill(lx, lx+n+1, -INF);
44        for (int x=1; x<=n; ++x) for (int y=1; y<=n; ++y)
45            lx[x]=max(lx[x], g[x][y]);
46        for (int x=1; x<=n; ++x) bfs(x);
47        ll ans=0;
48        for (int y=1; y<=n; ++y) ans+=g[my[y]][y];
49        return ans;
50    }
51 } graph;

```

13 Combinatorics

13.1 Catalan Number

$$C_0 = 1, C_n = \sum_{i=0}^{n-1} C_i C_{n-1-i}, C_n = C_n^{2n} - C_{n-1}^{2n}$$

0	1	1	2	5
4	14	42	132	429
8	1430	4862	16796	58786
12	208012	742900	2674440	9694845

13.2 Bertrand's Ballot Theorem

- A always $>$ B: $C(p+q, p) - 2C(p+q-1, p)$
- A always $\geq$ B: $C(p+q, p) \times \frac{p+1-q}{p+1}$

13.3 Burnside's Lemma

Let X be the original set.

Let G be the group of operations acting on X .

Let X^g be the set of x not affected by g .

Let X/G be the set of orbits.

Then the following equation holds:

$$|X/G| = \frac{1}{|G|} \sum_{g \in G} |X^g|$$

14 Special Numbers

14.1 Fibonacci Series

1	1	1	2	3
5	5	8	13	21
9	34	55	89	144
13	233	377	610	987
17	1597	2584	4181	6765
21	10946	17711	28657	46368
25	75025	121393	196418	317811
29	514229	832040	1346269	2178309
33	3524578	5702887	9227465	14930352

$$f(45) \approx 10^9, f(88) \approx 10^{18}$$

14.2 Prime Numbers

- $\pi(n) \equiv$ Number of primes $\leq n \approx \frac{n}{(\ln n) - 1}$
- $\pi(100) = 25, \pi(200) = 46$
- $\pi(500) = 95, \pi(1000) = 168$
- $\pi(2000) = 303, \pi(4000) = 550$
- $\pi(10^4) = 1229, \pi(10^5) = 9592$
- $\pi(10^6) = 78498, \pi(10^7) = 664579$

