

1 Reminder

1.1 Observations and Tricks

1.2 Bug List

- 沒開 long long
- 陣列戳出界／陣列開不夠大
- 寫好的函式忘記呼叫
- 0-base / 1-base
- 忘記初始化
- == 打成 =
- <= 打成 <+
- dp[i] 從 dp[i-1] 轉移時忘記特判 $i > 0$
- std::sort 比較運算子寫成 $<$ 或是讓 $=$ 的情況為 true
- 漏 case
- 線段樹改值懶標初始值不能設為 0
- DFS 的時候不小心覆寫到全域變數
- 浮點數誤差
- unsigned int128
- 多筆測資不能沒讀完直接 return
- 記得刪 cerr
- vector 超級肥，小 vector 請用 array，例如矩陣快速冪

[illegible]

2 Init (Linux)

2.1 vimrc

1

2.2 bashrc

```
1 gogo() {
2   g++ -std=c++20 -O2 "$1" && echo run && ./a.out
3 }
4 alias vig='vim -u ~/.vimrc-gino'
```

3 Basic

3.1 Template (Using Codebook)

```
1 // CRYptoGRapHer
2 #define SZ(c) ((int)(c).size())
3 // kactl
4 #define sz(x) (int)(x).size()
5 #define rep(i,a,b) for(int i=(a);i<(b);i++)
6 using ll = long long;
7 using vi = vector<int>;
8 using pii = pair<int, int>;
9 // ckiseki
10 #define all(x) begin(x), end(x)
11 #define pb emplace_back
12 #define REP(i, l, r) for (int i=(l); i<=(r); ++i)
13 const ll LINF = 1e18;
14 template<class A, class B> bool chmin(A& a, B& b) {
15     return b < a ? a = b, 1 : 0;
16 }
```

3.2 PBDS, Random

```
1 #include <bits/extc++.h>
2 using namespace __gnu_pbds;
3 // map
4 tree<int, int, less<>, rb_tree_tag,
5   tree_order_statistics_node_update> tr;
6 tr.order_of_key(element);
7 tr.find_by_order(rank);
8 // set
9 tree<int, null_type, less<>, rb_tree_tag,
10   tree_order_statistics_node_update> tr;
11 tr.order_of_key(element);
12 tr.find_by_order(rank);
13 // priority queue
14 __gnu_pbds::priority_queue<int, less<int>> big_q;
15 __gnu_pbds::priority_queue<int, greater<int>> small_q;
16 ql.join(q2); // join
17 mt19937
18 gen(chrono::steady_clock::now().time_since_epoch().count());
19 uniform_int_distribution<int>(a, b)(rng) // [a, b]
20 uniform_real_distribution<double>(a, b)(rng) // (a, b)
21 shuffle(v.begin(), v.end(), gen);
```

3.3 Debug

```
1 #define debug(...) cerr << "\x1b[33m" #__VA_ARGS__ " : \
2   \x1b[0m" \
3   [ (auto&&... a) { (cerr << a << ' ', ...); }
4   (__VA_ARGS__), cerr << '\n'
5 #define output(...) \
6   [ (auto&&... a) { (cout << a << ' ', ...); }
7   (__VA_ARGS__), cout << '\n'
8 int v = 42;
9 format("{:b}", v); // "101010"
10 format("{:#b}", v); // "0b101010"
11 format("{:x}", v); // "0x2a"
12 format("{:X}", v); // "0X2A"
13 int x = 7;
14 format("{:05d}", x); // "00007"
15 format("{:>5}", x); // " 7"
16 format("{:<5}", x); // "7 "
17 format("{:^5}", x); // " 7 "
18 format("{:*^5}", x); // "***7***"
19 double pi = 3.1415926535;
20 format("{:.2f}", pi); // "3.14"
```

3.4 SVG Writer

```
1 // Author: ckiseki
2 class SVG {
3     void p(string_view s) { o << s; }
4     void p(string_view s, auto v, auto... vs) {
5         auto i = s.find('$');
6         o << s.substr(0, i) << v, p(s.substr(i + 1), vs...);
7     }
8     ofstream o; string c = "red";
9 public:
10    SVG(auto f, auto x1, auto y1, auto x2, auto y2) : o(f) {
11        p("<svg xmlns='http://www.w3.org/2000/svg' "
12          "viewBox='$ $ $ $'>\n"
13          "<style*>{stroke-width:0.5%;}</style>\n",
14          x1, -y2, x2 - x1, y2 - y1); }
15    ~SVG() { p("</svg>\n"); }
16    void color(string nc) { c = nc; }
17    void line(auto x1, auto y1, auto x2, auto y2) {
```

```
18    p("<line x1='$' y1='$' x2='$' y2='$' stroke='$'>\n",
19      x1, -y1, x2, -y2, c); }
20    void circle(auto x, auto y, auto r) {
21        p("<circle cx='$' cy='$' r='$' stroke='$' "
22          "fill='none'/>\n", x, -y, r, c); }
23    void text(auto x, auto y, string s, int w = 12) {
24        p("<text x='$' y='$' font-size='$px'>$</text>\n",
25          x, -y, w, s); }
26};
```

```
1 SVG svg("out.svg", -200, -200, 200, 200);
2 svg.color("lightgray"); // drawing x-y plane
3 svg.line(-200, 0, 200, 0); svg.line(0, -200, 0, 200);
4 svg.color("blue"); svg.line(10, 10, 80, 80);
5 svg.color("red"); svg.circle(50, 50, 1);
```

3.5 Python

```
1 import sys
2 input = sys.stdin.readline
3 readStr = lambda: input().rstrip('\r\n')
4 readInt = lambda: int(input())
5 readInts = lambda: list(map(int, input().split()))
6
7 from decimal import *
8 getcontext().prec = 50 # precision
9 x = Decimal(str(x))
10 y = Decimal("6.7")
11 x *= y
12 print(x.quantize(Decimal("0.000001"),
13   rounding=ROUND_HALF_EVEN))
14 # ROUND_CEILING : To INF (2.9 -> 3, -2.1 -> -2)
15 # ROUND_FLOOR : To -INF (2.1 -> 2, -2.9 -> -3)
16 # ROUND_HALF_EVEN: To nearest even (2.5 -> 2, 3.5 -> 4)
17 # ROUND_HALF_UP : Half away from 0 (2.5 -> 3, -2.5 -> -3)
18 # ROUND_HALF_DOWN: Half towards 0 (2.5 -> 2, -2.5 -> -2)
19 # ROUND_UP : Away from 0 (2.1 -> 3, -2.1 -> -3)
20 # ROUND_DOWN : Truncate to 0 (2.9 -> 2, -2.9 -> -2)
21 # <Default>: ROUND_HALF_EVEN
22 # <Standard School Math>: ROUND_HALF_UP
```

3.6 Stress Tests

```
1 from random import *
2 n = randint(1, 10)
3 arr = list(randint(1, 20) for i in range(n))
4 print(*arr)
5 # permutation / non-repetitive sequence
6 perm = sample(range(1, n + 1), n)
7 arr = sample(range(1, 10000 + 1), n)
8 # string
9 from string import *
10 s = "".join(choices(ascii_lowercase, k=n))
11 t = "".join(choices(ascii_lowercase[:3], k=n)) # (a|b|c)*
12 u = "".join(choices(ascii_lowercase + ascii_uppercase +
13   digits, k=n))
13 # palindrome
14 half = "".join(choices(ascii_lowercase, k=(n + 1) // 2))
15 palindrome = half + (half[-2::-1] if n % 2 else half[::-1])
16 # ===== tree =====
17 n = 30
18 ## shallow tree
19 edges = [(randint(1, u - 1), u) for u in range(2, n + 1)]
20 ## deep tree
21 ## (suggested k: 2 ~ 5 or int(sqrt(n)) or 2n/D (D is
22   expected depth))
23 from math import *
24 k = int(sqrt(n))
25 edges = [(randint(max(1, u - k), u - 1), u) for u in range(2, n
26   + 1)]
27 for e in edges:
28     print(*e)
29
30 edges = [(1, i) for i in range(2, n + 1)] ## star
31 edges = [(i, i + 1) for i in range(1, n)] ## chain
32 edges = [(i // 2, i) for i in range(2, n + 1)] ## complete
33   binary tree
34 # ===== graph =====
35 # not necessarily connected, no multi-edge or self-loop
36 n = 10
37 density = 0.3 # graph density (0.0 ~ 1.0)
38 edges = [(i, j) for i in range(1, n+1) for j in range(i+1,
39   n+1) if random() < density]
40 ## connected, no multi-edge or self-loop
41 n, extra_edges = 10, 5
42 edges = set()
43 ##### ... generate spanning tree with codes above
44 while len(edges) < n - 1 + extra_edges:
45     u, v = randint(1, n), randint(1, n)
46     if u != v:
47         edges.add((min(u, v), max(u, v)))
48 edges = list(edges)
```

```

45 ## DAG
46 perm = sample(range(1, n + 1), n)
47 edges = []
48 for _ in range(m):
49     i, j = sorted(sample(range(n), 2))
50     edges.append((perm[i], perm[j]))
51 ## Bipartite Graph
52 n1, n2 = 6, 7
53 left, right = list(range(1, n1+1)), list(range(n1+1,
54     n1+n2+1))
55 edges = [(choice(left), choice(right)) for _ in range(m)]
56 g++ -std=c++20 -o buggy $1
57 g++ -std=c++20 -o ac ac.cpp
58 for i in {1..100}; do
59     echo "TEST $i"
60     python3 gen.py > in
61     ./ac < in > oa
62     ./buggy < in > ob
63     if ! diff -q oa ob; then
64         cat in <(echo "=== AC") oa <(echo "=== WA") ob
65         break
66     fi
67 done

```

4 Data Structure

4.1 CDQ

```

1 // preparation
2 // 1. write a 1-base BIT
3 // 2. init(n, mxc): n is number of elements, mxc = 值域
4 // 3. build info array CDQ.v by yourself (x, y, z, id)
5 // 4. call solve()
6 // => cdq.ans[i] is number of j s.t. (xj <= xi, yj <= yi, zj
7 //    <= zi) (j != i)
8 struct CDQ {
9     struct info {
10         int x, y, z, id;
11         info(int x, int y, int z, int id):
12             x(x), y(y), z(z), id(id) {}
13         info():
14             x(0), y(0), z(0), id(0) {}
15     };
16     int n, mxc;
17     BIT bit;
18     vector<info> v;
19     vector<ll> ans;
20     void init(int _n, int _mxc) {
21         n = _n; mxc = _mxc;
22         v.assign(n, info{});
23         ans.assign(n, 0);
24     }
25     void dfs(int l, int r) {
26         if (l >= r) return;
27         int mid = (l+r) >> 1;
28         dfs(l, mid); dfs(mid+1, r);
29
30         vector<info> tmp;
31         vector<int> bit_op;
32         int pl = l, pr = mid+1;
33
34         while (pl <= mid && pr <= r) {
35             if (v[pl].y <= v[pr].y) {
36                 tmp.emplace_back(v[pl]);
37                 bit_op.emplace_back(v[pl].z);
38                 pl++;
39             }
40             else {
41                 tmp.emplace_back(v[pr]);
42                 ans[v[pr].id] += bit.qry(v[pr].z);
43                 pr++;
44             }
45         }
46         while (pl <= mid) {
47             tmp.emplace_back(v[pl]);
48             pl++;
49         }
50         while (pr <= r) {
51             tmp.emplace_back(v[pr]);
52             ans[v[pr].id] += bit.qry(v[pr].z);
53             pr++;
54         }
55         for (int i = l, j = 0; i <= r; i++, j++) v[i] =
56             tmp[j];
57     }
58     void solve() {
59         bit.init(mxc);

```

```

60         sort(v.begin(), v.end(), [&](const info& a, const
61             info& b){
62                 return (a.x == b.x ? (a.y == b.y ? (a.z == b.z ?
63                     a.id < b.id : a.z < b.z) : a.y < b.y) : a.x < b.x);
64             });
65         dfs(0, n-1);
66         map<pair<int, pii>, int> s;
67         sort(v.begin(), v.end(), [&](const info& a, const
68             info& b){
69                 return a.id > b.id;
70             });
71         for (int i = 0, id = n-1; i < n; i++, id--) {
72             pair<int, pii> tmp = make_pair(v[i].x,
73                 make_pair(v[i].y, v[i].z));
74             auto it = s.find(tmp);
75             if (it != s.end())
76                 ans[id] += it->second;
77             s[tmp]++;
78         }
79     }
80 };

```

4.2 Mo's Algorithm

```

1 // segments are 0-based
2 ll cur = 0; // current answer
3 int pl = 0, pr = -1;
4 for (auto& qi : Q) {
5     // get (l, r, qid) from qi
6     while (pl < l) del(pl++);
7     while (pl > l) add(--pl);
8     while (pr < r) add(++pr);
9     while (pr > r) del(pr--);
10    ans[qid] = cur;
11 }

```

4.3 Leftist Heap

```

1 // Author: Ian
2 // Function: min-heap, with worst-time O(lg n) merge
3 struct node {
4     node *l, *r; int d, v;
5     node(int x): d(1), v(x) { l = r = nullptr; }
6 };
7 static inline int d(node* x) { return x ? x->d : 0; }
8 node* merge(node* a, node* b) {
9     if (!a || !b) return a ? b : a;
10    if (a->v > b->v) swap(a, b);
11    a->r = merge(a->r, b);
12    if (d(a->l) < d(a->r))
13        swap(a->l, a->r);
14    a->d = d(a->r) + 1;
15    return a;
16 }

```

4.4 Persistent Treap

```

1 // Author: Ian
2 struct node {
3     node *l, *r;
4     char c; int v, sz;
5     node(char x = '$'): c(x), v(mt()), sz(1) {
6         l = r = nullptr;
7     }
8     node(node* p) { *this = *p; }
9     void pull() {
10         sz = 1;
11         for (auto i : {l, r})
12             if (i) sz += i->sz;
13     }
14 } arr[maxn], *ptr = arr;
15 inline int size(node* p) { return p ? p->sz : 0; }
16 node* merge(node* a, node* b) {
17     if (!a || !b) return a ? b : a;
18     if (a->v < b->v) {
19         node* ret = new(ptr++) node(a);
20         ret->r = merge(ret->r, b); ret->pull();
21         return ret;
22     }
23     else {
24         node* ret = new(ptr++) node(b);
25         ret->l = merge(a, ret->l); ret->pull();
26         return ret;
27     }
28 }
29 P<node*> split(node* p, int k) {
30     if (!p) return {nullptr, nullptr};
31     if (k >= size(p->l) + 1) {
32         auto [a, b] = split(p->r, k - size(p->l) - 1);
33         node* ret = new(ptr++) node(p);
34         ret->r = a; ret->pull();
35         return {ret, b};
36     }

```

```

37 else {
38     auto [a, b] = split(p->l, k);
39     node* ret = new(ptr++) node(p);
40     ret->l = b, ret->pull();
41     return {a, ret};
42 }
43 }

```

4.5 Li Chao Tree

```

1// Author: Ian
2// Function: For a set of lines L, find the maximum L_i(x)
  in L in O(lg n).
3typedef long double ld;
4constexpr int maxn = 5e4 + 5;
5struct line {
6    ld a, b;
7    ld operator()(ld x) {return a * x + b;}
8} arr[(maxn + 1) << 2];
9bool operator<(line a, line b) {return a.a < b.a;}
10#define m ((l+r)>>1)
11void insert(line x, int i = 1, int l = 0, int r = maxn) {
12    if (r - l == 1) {
13        if (x(l) > arr[i](l))
14            arr[i] = x;
15        return;
16    }
17    line a = max(arr[i], x), b = min(arr[i], x);
18    if (a(m) > b(m))
19        arr[i] = a, insert(b, i << 1, l, m);
20    else
21        arr[i] = b, insert(a, i << 1 | 1, m, r);
22}
23ld query(int x, int i = 1, int l = 0, int r = maxn) {
24    if (x < l || r <= x) return -numeric_limits<ld>::max();
25    if (r - l == 1) return arr[i](x);
26    return max({arr[i](x), query(x, i << 1, l, m), query(x, i
  << 1 | 1, m, r)});
27}
28#undef m

```

4.6 Time Segment Tree

```

1// Author: Ian
2constexpr int maxn = 1e5 + 5;
3V<P<int>> arr[(maxn + 1) << 2];
4V<int> dsu, sz;
5V<tuple<int, int, int>> his;
6int cnt, q;
7int find(int x) {
8    return x == dsu[x] ? x : find(dsu[x]);
9};
10inline bool merge(int x, int y) {
11    int a = find(x), b = find(y);
12    if (a == b) return false;
13    if (sz[a] > sz[b]) swap(a, b);
14    his.emplace_back(a, b, sz[b]), dsu[a] = b, sz[b] +=
  sz[a];
15    return true;
16};
17inline void undo() {
18    auto [a, b, s] = his.back(); his.pop_back();
19    dsu[a] = a, sz[b] = s;
20}
21#define m ((l + r) >> 1)
22void insert(int ql, int qr, P<int> x, int i = 1, int l = 0,
  int r = q) {
23    // debug(ql, qr, x); return;
24    if (qr <= l || r <= ql) return;
25    if (ql <= l && r <= qr) {arr[i].push_back(x); return;}
26    if (qr <= m)
27        insert(ql, qr, x, i << 1, l, m);
28    else if (m <= ql)
29        insert(ql, qr, x, i << 1 | 1, m, r);
30    else {
31        insert(ql, qr, x, i << 1, l, m);
32        insert(ql, qr, x, i << 1 | 1, m, r);
33    }
34}
35void traversal(V<int>& ans, int i = 1, int l = 0, int r = q)
  {
36    int opcnt = 0;
37    // debug(i, l, r);
38    for (auto [a, b] : arr[i])
39        if (merge(a, b))
40            opcnt++, cnt--;
41    if (r - l == 1) ans[l] = cnt;
42    else {
43        traversal(ans, i << 1, l, m);
44        traversal(ans, i << 1 | 1, m, r);
45    }
46    while (opcnt--)

```

```

47    undo(), cnt++;
48    arr[i].clear();
49}
50#undef m
51inline void solve() {
52    int n, m; cin>>n>>m>>q, q++;
53    dsu.resize(cnt = n), sz.assign(n, 1);
54    iota(dsu.begin(), dsu.end(), 0);
55    // a, b, time, operation
56    unordered_map<ll, V<int>> s;
57    for (int i = 0; i < m; i++) {
58        int a, b; cin>>a>>b;
59        if (a > b) swap(a, b);
60        s[(ll)a << 32 | b].emplace_back(0);
61    }
62    for (int i = 1; i < q; i++) {
63        int op, a, b;
64        cin>>op>>a>>b;
65        if (a > b) swap(a, b);
66        switch (op) {
67            case 1:
68                s[(ll)a << 32 | b].push_back(i);
69                break;
70            case 2:
71                auto tmp = s[(ll)a << 32 | b].back();
72                s[(ll)a << 32 | b].pop_back();
73                insert(tmp, i, P<int> {a, b});
74        }
75    }
76    for (auto [p, v] : s) {
77        int a = p >> 32, b = p & -1;
78        while (v.size()) {
79            insert(v.back(), q, P<int> {a, b});
80            v.pop_back();
81        }
82    }
83    V<int> ans(q);
84    traversal(ans);
85    for (auto i : ans)
86        cout<<i<<' ';
87    cout<<endl;
88}

```

5 DP

5.1 SOS DP

```

1// Author: Gino
2// Function: Solve problems that enumerates subsets of
  subsets ( $3^n \Rightarrow n * 2^n$ )
3for (int msk = 0; msk < (1<<n); msk++) {
4    for (int i = 1; i <= n; i++) {
5        if (msk & (1<<(i - 1))) {
6            dp[msk][i] = dp[msk][i - 1] + dp[msk ^ (1<<(i - 1))][i -
  1];
7        } else {
8            dp[msk][i] = dp[msk][i - 1];
9        }
10    }
11}

```

6 Graph

6.1 Max Clique

```

1// max N = 64
2typedef unsigned long long ll;
3struct MaxClique {
4    ll nb[N], n, ans;
5    void init(ll _n) {
6        n = _n;
7        for (int i = 0; i < n; i++) nb[i] = 0LLU;
8    }
9    void add_edge(ll _u, ll _v) {
10        nb[_u] |= (1LLU << _v);
11        nb[_v] |= (1LLU << _u);
12    }
13    void B(ll r, ll p, ll x, ll cnt, ll res) {
14        if (cnt + res < ans) return;
15        if (p == 0LLU && x == 0LLU) {
16            if (cnt > ans) ans = cnt;
17            return;
18        }
19        ll y = p | x; y &= -y;
20        ll q = p & (~nb[ int( log2(y) ) ]);
21        while (q) {
22            ll i = int( log2(q & (-q)) );
23            B(r | (1LLU << i), p & nb[i], x & nb[i]
  &
24            cnt + 1LLU, __builtin_popcountll(p &
  nb[i]
25            ));
26            q &= ~(1LLU << i);
27            p &= ~(1LLU << i);
28            x |= (1LLU << i);
29        }
30    }
31}

```

```

28 }
29 }
30 int solve(){
31     ans = 0;
32     ll _set = 0;
33     if( n < 64 ) _set = ( 1LLU << n ) - 1;
34     else{
35         for( ll i = 0 ; i < n ; i ++ ) _set |= ( 1LLU << i );
36     }
37     B( 0LLU , _set , 0LLU , 0LLU , n );
38     return ans;
39 }
40 }maxClique;

```

6.2 Bellman-Ford

```

1 // Author: Gino
2 // n, m = #(vertices), #(edges), and vertices are 1-based
3 // 1. BellmanFord bf(G, n, m);
4 // 2-1: bf.calcDis(s);
5 // => bf.dis[u] := shortest dis from s to u
6 // => bf.dis[u] := LINF (s can't reach u)
7 // => bf.dis[u] := -LINF (dis[u] can be arbitrary small)
8 // 2-2: bf.findNegCycle();
9 // => return false (if no neg cycle)
10 // => return true (has neg cycle, and gives an example:
    bf.neg_cycle)
11 // Time: O(VE), Space: O(V + E)
12 const ll LINF = 4e18;
13 struct BellmanFord {
14     const vector<vector<pair<int, ll>>>& G;
15     int n, m; // #(vertices), #(edges)
16     BellmanFord(const auto& G, int n, int m):
        G(G), n(n), m(m) {}
17
18     vector<ll> dis;
19     vector<int> nth_relax, pa;
20     void run_bf(const auto& src) {
21         dis.assign(n + 1, LINF);
22         nth_relax.assign(n + 1, 0);
23         pa.assign(n + 1, -1);
24         for (auto& s : src) dis[s] = 0;
25         for (int rlx = 1; rlx <= n; rlx++) {
26             for (int u = 1; u <= n; u++) {
27                 if (dis[u] == LINF) continue; // !important
28                 for (auto& [v, w] : G[u]) {
29                     if (dis[v] > dis[u] + w) {
30                         dis[v] = dis[u] + w;
31                         pa[v] = u;
32                         if (rlx == n) nth_relax[v] = 1;
33                     }
34                 }
35             }
36         }
37         void calcDis(int s) {
38             run_bf(vector<int>{s});
39             queue<int> q;
40             for (int u = 1; u <= n; u++)
41                 if (nth_relax[u]) q.push(u);
42             while (!q.empty()) {
43                 int u = q.front(); q.pop();
44                 for (auto& [v, w] : G[u]) {
45                     if (!nth_relax[v]) {
46                         nth_relax[v] = 1;
47                         q.push(v);
48                     }
49                 }
50             }
51             vector<int> neg_cycle;
52             bool findNegCycle() {
53                 auto src = views::iota(1, n + 1);
54                 run_bf(src);
55                 auto it = ranges::find_if(src, [&](int s){ return
                    nth_relax[s]; });
56                 if (it == src.end()) return false;
57                 int ptr = *it;
58                 for (int i = 0; i < n; i++) ptr = pa[ptr];
59                 neg_cycle.clear();
60                 int cur = ptr;
61                 while (true) {
62                     neg_cycle.emplace_back(cur);
63                     if (cur == ptr && neg_cycle.size() > 1) break;
64                     cur = pa[cur];
65                 }
66                 ranges::reverse(neg_cycle);
67                 return true;
68             }
69 };

```

6.3 System of Difference Constraints

```

1 vector<vector<pair<int, ll>>> G;
2 void add(int u, int v, ll w) { G[u].push_back({v, w}); }

```

- $x_u - x_v \leq c \Rightarrow \text{add}(v, u, c)$
- $x_u - x_v \geq c \Rightarrow \text{add}(u, v, -c)$
- $x_u - x_v = c \Rightarrow \text{add}(v, u, c), \text{add}(u, v, -c)$
- $x_u \geq c \Rightarrow \text{add super vertex } x_0 = 0, \text{ then } x_u - x_0 \geq c \Rightarrow \text{add}(u, 0, -c)$
- Don't forget non-negative constraints for every variable if specified implicitly.
- Interval sum $\Rightarrow$ Use prefix sum to transform into differential constraints. Don't forget $S_{i+1} - S_i \geq 0$ if x_i needs to be non-negative.
- $x_u/x_v \leq c \Rightarrow \log x_u - \log x_v \leq \log c$

6.4 Graph Girth

Run BFS for every node, when encountered non-BFS-tree edge, update answer (min cycle length) with $\text{dis}[u] + \text{dis}[v] + 1$. Time $O(VE)$.

6.5 Euler Trail

```

1 // Author: kactl (Simon Lindholm), wrapped by Gino
2 // Vertices are 1-based, Edge ID are 0-based
3 // 1. EulerWalk euler(n, true(directed) / false(undirected));
4 // 2. euler.addEdge(u, v);
5 // 3. int result = euler.solve();
6 // => -1: nothing (euler.path, euler.path_edges = {})
7 // => 1: Euler trail,
8 // => 2: Euler circuit
9 //     euler.path = {u_1, ..., u_{m+1}}
10 //     euler.path_edges = {e_1, ..., e_m}
11 // Time: O(V + E), Space: O(V + E)
12 // Test: V, E <= 2e5, 99ms
13 struct EulerWalk {
14     int n, m = 0; bool dir;
15     vector<vector<pii>> G; vi deg;
16     EulerWalk(int n, bool dir) : n(n), dir(dir), G(n + 1),
        deg(n + 1) {}
17     void addEdge(int u, int v) {
18         G[u].push_back({v, m});
19         if (!dir) G[v].push_back({u, m});
20         deg[u]++, deg[v] += dir ? -1 : 1;
21         m++;
22     }
23     vi path, path_edges;
24     void walk(int src) {
25         path.clear(); path_edges.clear();
26         vi its(n + 1), visE(m);
27         function<void(int, int)> dfs = [&](int u, int e_in) {
28             while (its[u] < sz(G[u])) {
29                 auto [v, e] = G[u][its[u]++];
30                 if (visE[e]) continue;
31                 visE[e] = 1;
32                 dfs(v, e);
33             }
34             path.push_back(u);
35             if (e_in != -1) path_edges.push_back(e_in);
36         };
37         dfs(src, -1);
38         if (sz(path) != m + 1) {
39             path.clear(); path_edges.clear(); return;
40         }
41         ranges::reverse(path); ranges::reverse(path_edges);
42     }
43     int solve() {
44         int s = -1, odd = 0, src = 0, dst = 0;
45         for (int u = 1; u <= n; u++) {
46             if (!dir && (deg[u] & 1)) odd++, s = u;
47             if (dir && deg[u] == 1) s = u, src++;
48             if (dir && deg[u] == -1) dst++;
49             if (dir && abs(deg[u]) > 1) return -1;
50         }
51         if (!dir && odd != 0 && odd != 2) return -1;
52         if (dir && !((src == 0 && dst == 0) || (src == 1 && dst == 1))) return -1;
53         if (s == -1) for (int u = 1; u <= n; u++) if (!
            G[u].empty()) { s = u; break; }
54         if (s == -1) s = 1;
55         walk(s); return path.empty() ? -1 : path.front() ==
            path.back() ? 2 : 1;
56     }
57 };

```

6.6 Vertex BCC (Round Square Tree)

```

1 // Author: std_abs
2 struct BCC { // 1-based, remember to build
3     int n, nbcc; // note for isolated point
4     vector<vector<int>> g, _g; // id > n: bcc
5     vector<int> pa, dep, low, stk, pa2, dep2;

```



```

6 void dfs(int v, int p) {
7     dep[v] = low[v] = ~p ? dep[p] + 1 : 0;
8     stk.pb(v), pa[v] = p;
9     for (int u : g[v]) if (u != p) {
10         if (low[u] == -1) {
11             dfs(u, v), low[v] = min(low[v], low[u]);
12             if (low[u] >= dep[v]) {
13                 int id = nbcc++, x;
14                 do {
15                     x = stk.back(), stk.pop_back();
16                     _g[id + n + 1].pb(x), _g[x].pb(id + n + 1);
17                 } while (x != u);
18                 _g[id + n + 1].pb(v), _g[v].pb(id + n + 1);
19             }
20         } else low[v] = min(low[v], dep[u]);
21     }
22 }
23 bool is_cut(int x) { return sz(_g[x]) != 1; }
24 vector<int> bcc(int id) { return _g[id + n + 1]; }
25 int bcc_id(int u, int v) {
26     return pa2[dep2[u] < dep2[v] ? v : u] - n - 1; }
27 void dfs2(int v, int p) {
28     dep2[v] = ~p ? dep2[p] + 1 : 0, pa2[v] = p;
29     for (int u : _g[v]) if (u != p) dfs2(u, v);
30 }
31 void build() {
32     low.assign(n + 1, -1);
33     for (int i = 1; i <= n; ++i) if (low[i] == -1)
34         dfs(i, -1), dfs2(i, -1);
35 }
36 void add_edge(int u, int v) {
37     g[u].pb(v), g[v].pb(u); }
38 BCC (int _n) : n(_n), nbcc(0), g(n + 1), _g(2 * n + 1),
39     pa(n + 1), dep(n + 1), low(n + 1), stk(), pa2(2 * n +
40     1), dep2(2 * n + 1) {}
41 };

```

6.7 Edge BCC

```

1 // Author: std_abs
2 // Vertices 1-based
3 // Edge ID 0-based, BCCID 0-based
4 // 1. EBCC ebcc(n); // n = #(vertices)
5 // 2. ebcc.add_edge(u, v);
6 // 3. ebcc.build();
7 // => nbcc: number of EBCC
8 // => bccs: stores all edge bccs
9 // => bcc_id[u], is_bridge[Edge ID]
10 struct EBCC { // 1-based, remember to build
11     int n, m, nbcc;
12     vector<vector<pair<int, int>>> G;
13     vector<vector<int>> bccs;
14     vector<int> pa, low, dep, bcc_id, stk, is_bridge;
15     void dfs(int v, int p, int f) {
16         low[v] = dep[v] = ~p ? dep[p] + 1 : 0;
17         stk.push_back(v), pa[v] = p;
18         for (auto [u, e] : G[v]) {
19             if (low[u] == -1)
20                 dfs(u, v, e), low[v] = min(low[v], low[u]);
21             else if (e != f)
22                 low[v] = min(low[v], dep[u]);
23         }
24         if (low[v] == dep[v]) {
25             if (~f) is_bridge[f] = true;
26             bccs.push_back({});
27             int id = nbcc++, x;
28             do {
29                 x = stk.back(), stk.pop_back();
30                 bcc_id[x] = id;
31                 bccs[id].emplace_back(x);
32             } while (x != v);
33         }
34     }
35     void build() {
36         is_bridge.assign(m, 0);
37         for (int i = 1; i <= n; ++i) if (low[i] == -1)
38             dfs(i, -1, -1);
39     }
40     void add_edge(int u, int v) {
41         G[u].emplace_back(v, m), G[v].emplace_back(u, m++);
42     }
43     EBCC (int _n) : n(_n), m(0), nbcc(0), G(n + 1), pa(n + 1),
44         low(n + 1, -1), dep(n + 1), bcc_id(n + 1), stk() {}
45 };

```

6.8 Kth Shortest Path

```

1 // time: O(|E| lg |E| + |V| lg |V| + K)
2 // memory: O(|E| lg |E| + |V|)
3 struct KSP { // 1-base

```

```

4     struct nd {
5         int u, v; ll d;
6         nd(int ui=0, int vi=0, ll di=INF) { u=ui; v=vi; d=di; }
7     };
8     struct heap { nd* edge; int dep; heap* chd[4]; };
9     static int cmp(heap* a, heap* b)
10     { return a->edge->d > b->edge->d; }
11     struct node {
12         int v; ll d; heap* H; nd* E;
13         node() {}
14         node(ll _d, int _v, nd* _E) { d=_d; v=_v; E=_E; }
15         node(heap* _H, ll _d) { H=_H; d=_d; }
16         friend bool operator<(node a, node b)
17         { return a.d > b.d; }
18     };
19     int n, k, s, t, dst[N]; nd *nxt[N];
20     vector<nd*> g[N], rg[N]; heap *nullNd, *head[N];
21     void init(int _n, int _k, int _s, int _t) {
22         n=_n; k=_k; s=_s; t=_t;
23         for (int i=1; i<=n; i++) {
24             g[i].clear(); rg[i].clear();
25             nxt[i]=NULL; head[i]=NULL; dst[i]=-1;
26         }
27     }
28     void addEdge(int ui, int vi, ll di) {
29         nd* e=new nd(ui, vi, di);
30         g[ui].push_back(e); rg[vi].push_back(e);
31     }
32     queue<int> dfsQ;
33     void dijkstra() {
34         while(dfsQ.size()) dfsQ.pop();
35         priority_queue<node> Q; Q.push(node(0, t, NULL));
36         while (!Q.empty()) {
37             node p=Q.top(); Q.pop(); if (dst[p.v] != -1) continue;
38             dst[p.v]=p.d; nxt[p.v]=p.E; dfsQ.push(p.v);
39             for (auto e: rg[p.v]) Q.push(node(p.d+e->d, e->u, e));
40         }
41     }
42     heap* merge(heap* curNd, heap* newNd) {
43         if (curNd==nullNd) return newNd;
44         heap* root=new heap; memcpy(root, curNd, sizeof(heap));
45         if (newNd->edge->d < curNd->edge->d) {
46             root->edge=newNd->edge;
47             root->chd[2]=newNd->chd[2];
48             root->chd[3]=newNd->chd[3];
49             newNd->edge=curNd->edge;
50             newNd->chd[2]=curNd->chd[2];
51             newNd->chd[3]=curNd->chd[3];
52         }
53         if (root->chd[0]->dep < root->chd[1]->dep)
54             root->chd[0]=merge(root->chd[0], newNd);
55         else root->chd[1]=merge(root->chd[1], newNd);
56         root->dep=max(root->chd[0]->dep,
57             root->chd[1]->dep)+1;
58         return root;
59     }
60     vector<heap*> V;
61     void build() {
62         nullNd=new heap; nullNd->dep=0; nullNd->edge=new nd;
63         fill(nullNd->chd, nullNd->chd+4, nullNd);
64         while (not dfsQ.empty()) {
65             int u=dfsQ.front(); dfsQ.pop();
66             if (!nxt[u]) head[u]=nullNd;
67             else head[u]=head[nxt[u]->v];
68             V.clear();
69             for (auto& e: g[u]) {
70                 int v=e->v;
71                 if (dst[v] == -1) continue;
72                 e->d+=dst[v]-dst[u];
73                 if (nxt[u] != e) {
74                     heap* p=new heap; fill(p->chd, p->chd+4, nullNd);
75                     p->dep=1; p->edge=e; V.push_back(p);
76                 }
77             }
78             if (V.empty()) continue;
79             make_heap(V.begin(), V.end(), cmp);
80             #define L(X) ((X<<1)+1)
81             #define R(X) ((X<<1)+2)
82             for (size_t i=0; i<V.size(); i++) {
83                 if (L(i)<V.size()) V[i]->chd[2]=V[L(i)];
84                 else V[i]->chd[2]=nullNd;
85                 if (R(i)<V.size()) V[i]->chd[3]=V[R(i)];
86                 else V[i]->chd[3]=nullNd;
87             }
88             head[u]=merge(head[u], V.front());
89         }
90     }
91     vector<ll> ans;
92     void first_K() {

```

```

93 ans.clear(); priority_queue<node> Q;
94 if(dst[s]==-1) return;
95 ans.push_back(dst[s]);
96 if(head[s]!=nullNd)
97     Q.push(node(head[s], dst[s]+head[s]->edge->d));
98 for(int i=1; i<k and not Q.empty(); i++){
99     node p=Q.top(); Q.pop(); ans.push_back(p.d);
100     if(head[p.H->edge->v]!=nullNd){
101         q.H=head[p.H->edge->v]; q.d=p.d+q.H->edge->d;
102         Q.push(q);
103     }
104     for(int i=0; i<4; i++){
105         if(p.H->chd[i]!=nullNd){
106             q.H=p.H->chd[i];
107             q.d=p.d+p.H->edge->d+p.H->chd[i]->edge->d;
108             Q.push(q);
109         }
110     }
111 void solve(){ // ans[i] stores the i-th shortest path
112     dijkstra(); build();
113     first_K(); // ans.size() might less than k
114 }
115 } solver;

```

6.9 SCC - Tarjan with 2-SAT

```

1 // Author: Ian
2 // 2-sat + tarjan SCC
3 void solve() {
4     int n, r, l; cin >> n >> r >> l;
5     V<P<int>> v(l);
6     for (auto& [a, b] : v)
7         cin >> a >> b;
8     V<V<int>> e(2 * l);
9     for (int i = 0; i < 4; i++)
10        for (int j = i + 1; j < l; j++) {
11            if (v[i].first == v[j].first && abs(v[i].second -
12                v[j].second) <= 2 * r) {
13                e[i << 1].emplace_back(j << 1 | 1);
14                e[j << 1].emplace_back(i << 1 | 1);
15            }
16            if (v[i].second == v[j].second && abs(v[i].first -
17                v[j].first) <= 2 * r) {
18                e[i << 1 | 1].emplace_back(j << 1);
19                e[j << 1 | 1].emplace_back(i << 1);
20            }
21        }
22 V<bool> ins(2 * l, false);
23 V<int> scc(2 * l), dfn(2 * l, -1), low(2 * l, inf);
24 stack<int> s;
25 function<void(int)> dfs = [&](int x) {
26     if (~dfn[x]) return;
27     static int t = 0;
28     dfn[x] = low[x] = t++;
29     s.push(x), ins[x] = true;
30     for (auto i : e[x])
31         if (dfs(i), ins[i])
32             low[x] = min(low[x], low[i]);
33     if (dfn[x] == low[x]) {
34         static int ncnt = 0;
35         int p; do {
36             ins[p = s.top()] = false;
37             s.pop(), scc[p] = ncnt;
38             while (p != x); ncnt++;
39         } while (p != x);
40     }
41     for (int i = 0; i < 2 * l; i++)
42         dfs(i);
43     for (int i = 0; i < l; i++)
44         if (scc[i << 1] == scc[i << 1 | 1]) {
45             cout << "NO" << endl;
46             return;
47         }
48     cout << "YES" << endl;
49 }

```

7 Tree

7.1 Tree Isomorphism (Rooted Trees)

```

1 // Author: Gino
2 // Checks if 2 rooted trees are isomorphic
3 // Time: O(V log V)
4 // vector<vector<int>> G1, G2;
5 // int root_1, root_2;
6 map<vector<int>, int> dict;
7 int encode(const auto& G, int u, int pa = -1) {
8     vector<int> codes;
9     for (auto& v : G[u])
10        if (v != pa)
11            codes.emplace_back(encode(G, v, u));
12     ranges::sort(codes);

```

```

13     auto [it, _] = dict.try_emplace(codes, dict.size());
14     return it->second;
15 }
16 bool isomorphic() {
17     dict.clear(); dict[{}] = 0;
18     return encode(G1, root_1) == encode(G2, root_2);
19 }

```

7.2 Tree Isomorphism (Unrooted Trees)

Find the centroid(s) of T_1, T_2 .

Case 1: T_1, T_2 have different number of centroids $\rightarrow$ NO

Case 2: T_1 has centroid c_1 , T_2 has centroid c_2

$\rightarrow$ rooted_isomorphic(c_1, c_2)

Case 3: T_1 has centroids c_1, c'_1 , T_2 has centroids c_2, c'_2

$\rightarrow$ rooted_isomorphic(c_1, c_2) || rooted_isomorphic(c'_1, c'_2)

7.3 Heavy Light Decomposition

```

1 // Author: Ian
2 void build(V<int>&v);
3 void modify(int p, int k);
4 int query(int ql, int qr);
5 // Insert [ql, qr] segment tree here
6 inline void solve(){
7     int n, q; cin >> n >> q;
8     V<int> v(n);
9     for (auto& i : v) cin >> i;
10    V<V<int>> e(n);
11    for(int i = 1; i < n; i++){
12        int a, b; cin >> a >> b, a--, b--;
13        e[a].emplace_back(b);
14        e[b].emplace_back(a);
15    }
16    V<int> d(n, 0), f(n, 0), sz(n, 1), son(n, -1);
17    F<void(int, int)> dfs1 = [&](int x, int pre) {
18        for (auto i : e[x]) if (i != pre) {
19            d[i] = d[x]+1, f[i] = x;
20            dfs1(i, x), sz[x] += sz[i];
21            if (son[x] == -1 || sz[son[x]] < sz[i])
22                son[x] = i;
23        }
24    }; dfs1(0, 0);
25    V<int> top(n, 0), dfn(n, -1);
26    F<void(int, int)> dfs2 = [&](int x, int t) {
27        static int cnt = 0;
28        dfn[x] = cnt++, top[x] = t;
29        if (son[x] == -1) return;
30        dfs2(son[x], t);
31        for (auto i : e[x]) if (!dfn[i])
32            dfs2(i, i);
33    }; dfs2(0, 0);
34    V<int> dfnv(n);
35    for (int i = 0; i < n; i++)
36        dfnv[dfn[i]] = v[i];
37    build(dfnv);
38    while(q--){
39        int op, a, b, ans; cin >> op >> a >> b;
40        switch(op){
41            case 1:
42                modify(dfn[a-1], b);
43                break;
44            case 2:
45                a--, b--, ans = 0;
46                while (top[a] != top[b]) {
47                    if (d[top[a]] > d[top[b]]) swap(a, b);
48                    ans = max(ans, query(dfn[top[b]], dfn[b]+1));
49                    b = f[top[b]];
50                }
51                if (dfn[a] > dfn[b]) swap(a, b);
52                ans = max(ans, query(dfn[a], dfn[b]+1));
53                cout << ans << endl;
54                break;
55        }
56    }
57 }

```

8 Matching

8.1 Bipartite Matching

```

1 // Author: Gino
2 // Function: Max Bipartite Matching in O(V sqrt(E))
3 // Usage:
4 // >>> init(nx, ny) -> add(x, y (+nx))
5 // >>> hk.max_matching() := the matching plan stores in mx,
6 // my
7 // >>> hk.min_vertex_cover() := the vertex cover plan stores
8 // in vcover
9 // (!) vertices are 0-based: X = [0, nx), Y = [nx, nx+ny)
10 #define pb emplace_back

```

```

9 struct HopcroftKarp {
10     int n, nx, ny;
11     vector<vector<int>> G;
12     vector<int> mx, my;
13     void init(int _nx, int _ny) {
14         nx = _nx, ny = _ny;
15         n = nx + ny;
16         G.assign(n, vector<int>());
17     }
18     void add(int x, int y) { G[x].pb(y); G[y].pb(x); }
19     int max_matching() {
20         vector<int> dis, vis;
21         mx.assign(n, -1); my.assign(n, -1);
22         function<bool(int)> dfs = [&](int x) {
23             vis[x] = 1;
24             for (int y : G[x]) {
25                 int p = my[y];
26                 if (p == -1 || (dis[p] == dis[x] + 1 && !vis[p] &&
27                     dfs(p)))
28                     return mx[x] = y, my[y] = x, true;
29             }
30             return false;
31         };
32         while (true) {
33             dis.assign(n, -1);
34             queue<int> q;
35             for (int x = 0; x < nx; x++)
36                 if (mx[x] == -1) dis[x] = 0, q.push(x);
37             while (!q.empty()) {
38                 int x = q.front(); q.pop();
39                 for (int y : G[x])
40                     if (my[y] != -1 && dis[my[y]] == -1)
41                         dis[my[y]] = dis[x] + 1, q.push(my[y]);
42             }
43             vis.assign(n, 0);
44             bool found = false;
45             for (int x = 0; x < nx; x++)
46                 if (mx[x] == -1 && dfs(x)) found = true;
47             if (!found) break;
48         }
49         int ans = 0;
50         for (int x = 0; x < nx; x++) if (mx[x] != -1) ans++;
51         return ans;
52     }
53     vector<int> vcover;
54     int min_vertex_cover() {
55         int ans = max_matching();
56         vector<int> vis(n, 0);
57         function<void(int)> dfs = [&](int x) {
58             vis[x] = true;
59             for (int y : G[x]) {
60                 if (y == mx[x] || my[y] == -1 || vis[y]) continue;
61                 vis[y] = true;
62                 dfs(my[y]);
63             }
64         };
65         for (int x = 0; x < nx; x++) if (mx[x] == -1) dfs(x);
66         vcover.clear();
67         for (int x = 0; x < nx; x++) if (!vis[x]) vcover.pb(x);
68         for (int y = nx; y < nx + ny; y++) if (vis[y])
69             vcover.pb(y);
70         return ans;
71     }
72 } hk;

```

8.2 Bipartite Weighted Matching

```

1 // Author: ckiseki
2 // n = #(left vertices) = #(right vertices)
3 // left, right vertices labeled 1 ~ n separately
4 // 1. build 1-based matrix G of size (n + 1) * (n + 1)
5 // G[u][v] := weight between (left u, right v)
6 // <!-- if not need perfect matching => set weights of all
7 // negative edges to 0
8 // 2. constrcut (solve at same time): KM km(n, G);
9 // => km.ans (max perfect weight sum)
10 // => km.fl[u] (left u -> right v)
11 // => km.fr[v] (right v -> left u)
12 // Time: O(V^3), Space: O(V^2)
13 // Test: V <= 500, 243ms
14 struct KM { // maximize, test @ UOJ 80
15     int n, l, r; ll ans; // fl and fr are the match
16     vector<ll> hl, hr; vector<int> fl, fr, pre, q;
17     void bfs(const auto &w, int s) {
18         vector<int> vl(n + 1), vr(n + 1); vector<ll> slk(n + 1,
19             LINF);
20         l = r = 0; vr[q[r++] = s] = true;
21         auto check = [&](int x) -> bool {
22             if (vl[x] || slk[x] > 0) return true;
23             vl[x] = true; slk[x] = LINF;

```

```

22         if (fl[x] != -1) return (vr[q[r++] = fl[x]] = true);
23         while (x != -1) swap(x, fr[fl[x] = pre[x]]);
24         return false;
25     };
26     while (true) {
27         while (l < r)
28             for (int x = 1; x <= n; ++x) d = min(d, slk[x]);
29         for (int x = 1; x <= n; ++x) d = min(d, slk[x]);
30         for (int x = 1; x <= n; ++x)
31             vl[x] ? hl[x] += d : slk[x] -= d;
32         for (int x = 1; x <= n; ++x) if (vr[x]) hr[x] -= d;
33         for (int x = 1; x <= n; ++x) if (!check(x)) return;
34     }
35     KM(int n_, const auto &w) : n(n_), ans(0),
36         hl(n + 1), hr(n + 1), fl(n + 1, -1), fr(fl), pre(n + 1),
37         q(n + 1) {
38         for (int i = 1; i <= n; ++i) {
39             hl[i] = -LINF;
40             for (int j = 1; j <= n; ++j) hl[i] = max(hl[i],
41                 (ll)w[i][j]);
42         }
43         for (int i = 1; i <= n; ++i) bfs(w, i);
44         for (int i = 1; i <= n; ++i) ans += w[i][fl[i]];
45     }
46 };

```

8.3 General Matching

```

1 // Author: ckiseki
2 // 0. build 1-based graph vector<vector<int>> G(n + 1);
3 // 1. construct (solve at same time):
4 //     GeneralMatching M(G, n); => M.ans
5 // status: M.match[x] (== -1 if not matched, 1 <= x <= n)
6 // Time: O(V^3), Space: O(V + E)
7 // Test: V <= 500, 11ms
8 struct GeneralMatching {
9     queue<int> q; int ans, n;
10     vector<int> fa, s, v, pre, match;
11     int Find(int u) {
12         return u == fa[u] ? u : fa[u] = Find(fa[u]);
13     }
14     int LCA(int x, int y) {
15         static int tk = 0; tk++; x = Find(x); y = Find(y);
16         for (; swap(x, y);) if (x != 0) {
17             if (v[x] == tk) return x;
18             v[x] = tk;
19             x = Find(pre[match[x]]);
20         }
21     }
22     void Blossom(int x, int y, int l) {
23         for (; Find(x) != l; x = pre[y]) {
24             pre[x] = y, y = match[x];
25             if (s[y] == 1) q.push(y), s[y] = 0;
26             for (int z : {x, y}) if (fa[z] == z) fa[z] = l;
27         }
28     }
29     bool Bfs(auto &g, int r) {
30         iota(all(fa), 0); ranges::fill(s, -1);
31         q = queue<int>(); q.push(r); s[r] = 0;
32         for (; !q.empty(); q.pop()) {
33             for (int x = q.front(); int u : g[x])
34                 if (s[u] == -1) {
35                     if (pre[u] == x, s[u] = 1, match[u] == 0) {
36                         for (int a = u, b = x, last;
37                             b != 0; a = last, b = pre[a])
38                             last = match[b], match[b] = a, match[a] = b;
39                         return true;
40                     }
41                     q.push(match[u]); s[match[u]] = 0;
42                 } else if (!s[u] && Find(u) != Find(x)) {
43                     int l = LCA(u, x);
44                     Blossom(x, u, l); Blossom(u, x, l);
45                 }
46             }
47         return false;
48     }
49     GeneralMatching(auto &g, int n_) : ans(0), n(n_),
50         fa(n + 1), s(n + 1), v(n + 1), pre(n + 1, 0), match(n + 1,
51             0) {
52         for (int x = 1; x <= n; ++x)
53             if (match[x] == 0) ans += Bfs(g, x);
54         for (int x = 1; x <= n; ++x)
55             if (match[x] == 0) match[x] = -1;
56     }
57 };

```



```
55}; // tested @ yosupo judge
```

8.4 General Weighted Matching

```
1// Author: ckiseki
2// 1. GeneralWeightedMatching M(n);
3// (1-based, 1 <= u, v <= n)
4// 2. add edges: M.set_edge(u, v, w);
5// 3. auto [tot_weight, n_matches] = M.solve();
6// 4. M.match[u] (== -1 if not matched, 1-based index if
   matched)
7// Time: O(V^3), Space: O(V^2)
8// Test: V <= 500, 369ms
9struct GeneralWeightedMatching { // 1-based
10 static const int inf = INT_MAX;
11 struct edge { int u, v, w; }; int n, nx;
12 vector<int> lab; vector<vector<edge>> g;
13 vector<int> slack, match, st, pa, S, vis;
14 vector<vector<int>> flo, flo_from; queue<int> q;
15 GeneralWeightedMatching(int n_) : n(n_), nx(n * 2), lab(nx
   + 1),
16 g(nx + 1, vector<edge>(nx + 1)), slack(nx + 1),
17 flo(nx + 1), flo_from(nx + 1, vector(n + 1, 0)) {
18     match = st = pa = S = vis = slack;
19     REP(u, 1, n) REP(v, 1, n) g[u][v] = {u, v, 0};
20 }
21 int ED(edge e) {
22     return lab[e.u] + lab[e.v] - g[e.u][e.v].w * 2; }
23 void update_slack(int u, int x, int &s) {
24     if (!s || ED(g[u][x]) < ED(g[s][x])) s = u; }
25 void set_slack(int x) {
26     slack[x] = 0;
27     REP(u, 1, n)
28         if (g[u][x].w > 0 && st[u] != x && S[st[u]] == 0)
29             update_slack(u, x, slack[x]);
30 }
31 void q_push(int x) {
32     if (x <= n) q.push(x);
33     else for (int y : flo[x]) q.push(y);
34 }
35 void set_st(int x, int b) {
36     st[x] = b;
37     if (x > n) for (int y : flo[x]) set_st(y, b);
38 }
39 vector<int> split_flo(auto &f, int xr) {
40     auto it = find(all(f), xr);
41     if (auto pr = it - f.begin(); pr % 2 == 1)
42         reverse(1 + all(f), it = f.end() - pr;
43     auto res = vector(f.begin(), it);
44     return f.erase(f.begin(), it), res;
45 }
46 void set_match(int u, int v) {
47     match[u] = g[u][v].v;
48     if (u <= n) return;
49     int xr = flo_from[u][g[u][v].u];
50     auto &f = flo[u], z = split_flo(f, xr);
51     REP(i, 0, int(z.size())-1) set_match(z[i], z[i ^ 1]);
52     set_match(xr, v); f.insert(f.end(), all(z));
53 }
54 void augment(int u, int v) {
55     for (;;) {
56         int xnv = st[match[u]]; set_match(u, v);
57         if (!xnv) return;
58         set_match(v = xnv, u = st[pa[xnv]]);
59     }
60 }
61 /* SPLIT_HASH_HERE */
62 int lca(int u, int v) {
63     static int t = 0; ++t;
64     for (++t; u || v; swap(u, v)) if (u) {
65         if (vis[u] == t) return u;
66         vis[u] = t; u = st[match[u]];
67         if (u) u = st[pa[u]];
68     }
69     return 0;
70 }
71 void add_blossom(int u, int o, int v) {
72     int b = int(find(n + 1 + all(st), 0) - begin(st));
73     lab[b] = 0, S[b] = 0; match[b] = match[o];
74     vector<int> f = {o};
75     for (int x : {u, v}) {
76         for (int y; x != o; x = st[pa[y]])
77             f.pb(x), f.pb(y = st[match[x]]), q_push(y);
78         reverse(1 + all(f));
79     }
80     flo[b] = f; set_st(b, b);
81     REP(x, 1, nx) g[b][x].w = g[x][b].w = 0;
82     REP(x, 1, n) flo_from[b][x] = 0;
83     for (int xs : flo[b]) {
84         REP(x, 1, nx)
```

```
85         if (g[b][x].w == 0 || ED(g[xs][x]) < ED(g[b][x]))
86             g[b][x] = g[xs][x], g[x][b] = g[x][xs];
87         REP(x, 1, n)
88             if (flo_from[xs][x]) flo_from[b][x] = xs;
89     }
90     set_slack(b);
91 }
92 void expand_blossom(int b) {
93     for (int x : flo[b]) set_st(x, x);
94     int xr = flo_from[b][g[b][pa[b]].u], xs = -1;
95     for (int x : split_flo(flo[b], xr)) {
96         if (xs == -1) { xs = x; continue; }
97         pa[xs] = g[x][xs].u; S[xs] = 1, S[x] = 0;
98         slack[xs] = 0; set_slack(x); q_push(x); xs = -1;
99     }
100     for (int x : flo[b])
101         if (x == xr) S[x] = 1, pa[x] = pa[b];
102         else S[x] = -1, set_slack(x);
103     st[b] = 0;
104 }
105 bool on_found_edge(const edge &e) {
106     if (int u = st[e.u], v = st[e.v]; S[v] == -1) {
107         int nu = st[match[v]]; pa[v] = e.u; S[v] = 1;
108         slack[v] = slack[nu] = 0; S[nu] = 0; q_push(nu);
109     } else if (S[v] == 0) {
110         if (int o = lca(u, v)) add_blossom(u, o, v);
111         else return augment(u, v), augment(v, u), true;
112     }
113     return false;
114 }
115 /* SPLIT_HASH_HERE */
116 bool matching() {
117     ranges::fill(S, -1); ranges::fill(slack, 0);
118     q = queue<int>();
119     REP(x, 1, nx) if (st[x] == x && !match[x])
120         pa[x] = 0, S[x] = 0, q.push(x);
121     if (q.empty()) return false;
122     for (;;) {
123         while (q.size()) {
124             int u = q.front(); q.pop();
125             if (S[st[u]] == 1) continue;
126             REP(v, 1, n)
127                 if (g[u][v].w > 0 && st[u] != st[v]) {
128                     if (ED(g[u][v]) != 0)
129                         update_slack(u, st[v], slack[st[v]]);
130                     else if (on_found_edge(g[u][v])) return true;
131                 }
132         }
133         int d = inf;
134         REP(b, n + 1, nx) if (st[b] == b && S[b] == 1)
135             d = min(d, lab[b] / 2);
136         REP(x, 1, nx)
137             if (int s = slack[x]; st[x] == x && s && S[x] <= 0)
138                 d = min(d, ED(g[s][x]) / (S[x] + 2));
139         REP(u, 1, n)
140             if (S[st[u]] == 1) lab[u] += d;
141             else if (S[st[u]] == 0) {
142                 if (lab[u] <= d) return false;
143                 lab[u] -= d;
144             }
145         REP(b, n + 1, nx) if (st[b] == b && S[b] >= 0)
146             lab[b] += d * (2 - 4 * S[b]);
147         REP(x, 1, nx)
148             if (int s = slack[x]; st[x] == x &&
149                 s && st[s] != x && ED(g[s][x]) == 0)
150                 if (on_found_edge(g[s][x])) return true;
151         REP(b, n + 1, nx)
152             if (st[b] == b && S[b] == 1 && lab[b] == 0)
153                 expand_blossom(b);
154     }
155     return false;
156 }
157 pair<ll, int> solve() {
158     ranges::fill(match, 0);
159     REP(u, 0, n) st[u] = u, flo[u].clear();
160     int w_max = 0;
161     REP(u, 1, n) REP(v, 1, n) {
162         flo_from[u][v] = (u == v ? u : 0);
163         w_max = max(w_max, g[u][v].w);
164     }
165     REP(u, 1, n) lab[u] = w_max;
166     int n_matches = 0; ll tot_weight = 0;
167     while (matching()) ++n_matches;
168     REP(u, 1, n) if (match[u] && match[u] < u)
169         tot_weight += g[u][match[u]].w;
170     REP(u, 1, n) if (match[u] == 0) match[u] = -1;
171     return make_pair(tot_weight, n_matches);
172 }
173 void set_edge(int u, int v, int w) {
```

```
174 g[u][v].w = g[v][u].w = w; }
175 };
```

9 Flow

9.1 Flow Methods

```
1// Author: CRYPTOGRAPHER (some modified by Gino)
2Maximize  $c^T x$  subject to  $Ax \leq b, x \geq 0$ ;
3with the corresponding symmetric dual problem,
4Minimize  $b^T y$  subject to  $A^T y \geq c, y \geq 0$ .
5
6Maximize  $c^T x$  subject to  $Ax \leq b$ ;
7with the corresponding asymmetric dual problem,
8Minimize  $b^T y$  subject to  $A^T y = c, y \geq 0$ .
9
10Maximize  $\sum x$  subject to  $x_i + x_j \leq A_{ij}, x \geq 0$ ;
11=> Maximize  $\sum x$  subject to  $x_i + x_j \leq A_{ij}$ ;
12=> Minimize  $A^T y = \sum A_{ij} y_{ij}$  subject to for all  $v$ ,
     $\sum_{i=v \text{ or } j=v} y_{ij} = 1, y_{ij} \geq 0$ 
13=> possible optimal solution:  $y_{ij} = \{0, 0.5, 1\}$ 
14=>  $y'=2y: \sum_{i=v \text{ or } j=v} y'_{ij} = 2, y'_{ij} = \{0, 1, 2\}$ 
15=> Minimum Bipartite perfect matching/2 ( $V_1=X, V_2=X, E=A$ )
16
17General Graph:
18|Max Ind. Set| + |Min Vertex Cover| = |V|
19|Max Ind. Edge Set| + |Min Edge Cover| = |V|
20Bipartite Graph:
21|Max Ind. Set| = |Min Edge Cover|
22|Max Ind. Edge Set| = |Min Vertex Cover|
23
24To reconstruct the minimum vertex cover, dfs from each
25unmatched vertex on the left side and with unused edges
26only. Equivalently, dfs from source with unused edges
27only and without visiting sink. Then, a vertex is
28chosen iff. it is on the left side and without visited
29or on the right side and visited through dfs.
30
31Minimum Weighted Bipartite Edge Cover:
32Construct new bipartite graph with  $n+m$  vertices on each
    side:
33for each vertex  $u$ , duplicate a vertex  $u'$  on the other side
34for each edge  $(u,v,w)$ , add edges  $(u,v,w)$  and  $(v',u',w)$ 
35for each vertex  $u$ , add edge  $(u,u',2w)$  where  $w$  is min edge
    connects to  $u$ 
36then the answer is the minimum perfect matching of the new
    graph (KM)
37
38Maximum density subgraph (  $\sum\{W_e\} + \sum\{W_v\}$  ) / |V|
39Binary search on answer:
40For a fixed  $D$ , construct a Max flow model as follow:
41Let  $S$  be Sum of all weight( or inf)
421. from source to each node with cap =  $S$ 
432. For each  $(u,v,w)$  in  $E$ ,  $(u \rightarrow v, \text{cap}=w), (v \rightarrow u, \text{cap}=w)$ 
443. For each node  $v$ , from  $v$  to sink with cap =  $S + 2 * D - \text{deg}[v] - 2 * (W \text{ of } v)$ 
45where  $\text{deg}[v] = \sum \text{weight of edge associated with } v$ 
46If  $\text{maxflow} < S * |V|$ ,  $D$  is an answer.
47
48Requiring subgraph: all vertex can be reached from source
    with
49edge whose cap > 0.
50
51Maximum closed subgraph
521. connect source with positive weighted
    vertex(capacity=weight)
532. connect sink with negative weighted vertex(capacity=-
    weight)
543. make capacity of the original edges = inf
554. ans = sum(positive weighted vertex weight) - (max flow)
56
57(Node-disjoint) Min DAG Path Cover (用最少路徑覆蓋所有點)
58Node disjoint: 拆出來的路徑不能共用同一個點
59將一個點  $u$  裂成  $u+$  和  $u-$ , 代表進入和出去
60對於一條邊  $(u, v)$  建邊  $u- \Rightarrow v+$ 
611. +點們和 -點們形成一張二分圖
622. 最差的答案是  $n$ , 代表每個點自己一個點就是一條路徑
633. 只要一組  $(u-, v+)$  匹配成功那對應到的答案恰好會  $-1$ 
64>>> ans =  $n -$  這張二分圖的最大匹配
65
66General DAG Path Cover
67跟 Node-disjoint 版本差在點可以被很多條路共用
68建邊方式 Node-disjoint 差別在條件比較鬆
69Node-disjoint:  $u- \Rightarrow v+$  只能在  $(u, v)$  有邊時建
70General:  $u- \Rightarrow v+$  在  $u$  能走到  $v$  的時候就建
71
72Dilworth Theorem
73反鍵: 一些節點的集合, 滿足這些節點互相無法抵達
74最大反鍵 = 最小 General DAG Path Cover
```

9.2 Dinic

```
1// Author: Benson (Extensions by Gino)
```

```
2// Function: Max Flow,  $O(V^2 E)$ 
3// Usage: Call init(n) first, then add(u, v, w) based on
    your model
4// (!) vertices 0-based
5// >>> flow() := return max flow
6// >>> find_cut() := return min cut + store cut set in
    dinic.cut
7// >>> find_matching() := return |M| + store matching plan
    in dinic.matching
8// >>> flow_decomposition := return max flow + store
    decomposition in dinic.D
9#define int long long
10#define eb emplace_back
11#define ALL(a) a.begin(), a.end()
12struct Dinic {
13    struct Edge {
14        // t: to | C: original capacity | c: current capacity |
        r: residual edge | f: current flow
15        int t, C, c, r, f;
16        bool fw; // is in forward-edge graph
17        Edge() {}
18        Edge(int _t, int _C, int _r, bool _fw, int _f=0):
            t(_t), C(_C), c(_C), r(_r), fw(_fw), f(_f) {}
19    };
20    vector<vector<Edge>> G;
21    vector<int> dis, iter;
22    int n, s, t;
23    void init(int _n) {
24        n = _n;
25        G.resize(n), dis.resize(n), iter.resize(n);
26        for(int i = 0; i < n; ++i)
27            G[i].clear();
28    }
29    void add(int a, int b, int c) {
30        G[a].eb(b, c, G[b].size(), true);
31        G[b].eb(a, 0, G[a].size() - 1, false);
32    }
33    bool bfs() {
34        fill(ALL(dis), -1);
35        dis[s] = 0;
36        queue<int> que;
37        que.push(s);
38        while(!que.empty()) {
39            int u = que.front(); que.pop();
40            for(auto& e : G[u]) {
41                if(e.c > 0 && dis[e.t] == -1) {
42                    dis[e.t] = dis[u] + 1;
43                    que.push(e.t);
44                }
45            }
46        }
47        return dis[t] != -1;
48    }
49    int dfs(int u, int cur) {
50        if(u == t) return cur;
51        for(int &i = iter[u]; i < (int)G[u].size(); ++i) {
52            auto& e = G[u][i];
53            if(e.c > 0 && dis[u] + 1 == dis[e.t]) {
54                int ans = dfs(e.t, min(cur, e.c));
55                if(ans > 0) {
56                    G[e.t][e.r].c += ans;
57                    e.c -= ans;
58                    return ans;
59                }
60            }
61        }
62        return 0;
63    }
64    // find max flow
65    int flow(int a, int b) {
66        s = a, t = b;
67        int ans = 0;
68        while(bfs()) {
69            int tmp;
70            while((tmp = dfs(s, INF)) > 0)
71                ans += tmp;
72        }
73        return ans;
74    }
75    // min cut plan
76    vector<pair<pair<int, int>, int>> cut;
77    int find_cut(int a, int b) {
78        int cut_sz = flow(a, b);
79        vector<int> vis(n, 0);
80        cut.clear();
81        function<void(int)> dfs = [&](int u) {
82            vis[u] = 1;
83            for (auto& e : G[u])
84                if (e.c > 0 && !vis[e.t])
85                    dfs(e.t);
86        };
87        dfs(a);
```

```

86     for (int u = 0; u < n; u++)
87         if (vis[u])
88             for (auto& e : G[u])
89                 if (!vis[e.t])
90                     cut.pb(make_pair(make_pair(u, e.t), G[e.t]
[e.r].c));
91     return cut.sz;
92 }
93 // bipartite matching plan
94 vector<pair<int, int>> matching;
95 int find_matching(int Xstart, int Xend, int Ystart, int
Yend, int a, int b) {
96     int msz = flow(a, b);
97     matching.clear();
98     for (int x = Xstart; x <= Xend; x++)
99         for (auto& e : G[x])
100             if (e.c == 0 && Ystart <= e.t && e.t <= Yend)
101                 matching.emplace_back(make_pair(x, e.t));
102     return msz;
103 }
104 // flow decomposition
105 vector<pair<int, vector<int>>> D; // (flow amount, [path
p1 ... pk])
106 int flow_decomposition(int a, int b) {
107     int mxflow = flow(a, b);
108
109     vector<vector<Edge>> fG(n); // graph consists of forward
edges
110     for (int u = 0; u < n; u++) {
111         for (auto& e : G[u]) {
112             if (e.fw) {
113                 e.f = e.C - e.c;
114                 if (e.f > 0) fG[u].pb(e);
115             } }
116
117     vector<int> vis;
118     function<int(int, int)> dfs = [&](int u, int cur) {
119         if (u == b) {
120             D.back().second.pb(u);
121             return cur;
122         }
123         vis[u] = 1;
124         for (auto& e : fG[u]) {
125             if (e.f > 0 && !vis[e.t]) {
126                 int ans = dfs(e.t, min(cur, e.f));
127                 if (ans > 0) {
128                     e.f -= ans;
129                     D.back().second.pb(u);
130                     return ans;
131                 } }
132         return 0LL;
133     };
134     D.clear();
135     int quota = mxflow;
136     while (quota > 0) {
137         D.emplace_back(make_pair(0, vector<int>()));
138         vis.assign(n, 0);
139         int f = dfs(a, INF);
140         if (f == 0) break;
141         reverse(D.back().second.begin(),
D.back().second.end());
142         D.back().first = f, quota -= f;
143     }
144     return mxflow;
145 }
146 };

```

9.3 ISAP

```

1 // Author: CRYPTOGRAPHER
2 // 1-based: vertices are numbered 1 ~ n
3 // 1. flow.init(n, s, t);
4 //    n = #vertices, s, t = source, sink
5 // 2. flow.addEdge(u, v, c); // u, v in [1, n]
6 // 3. call: int ans = flow.flow();
7 // => ans = max flow value from s to t
8 // Time: O(V^2 * E) worst case, usually much faster in
practice
9 static const int MAXV=50010;
10 static const int INF =1000000;
11 struct Maxflow{
12     struct Edge{
13         int v, c, r;
14         Edge(int _v, int _c, int _r):v(_v),c(_c),r(_r){}
15     };
16     int s, t; vector<Edge> G[MAXV];
17     int iter[MAXV], d[MAXV], gap[MAXV], tot;
18     void init(int n, int _s, int _t){
19         tot=n, s=_s, t=_t;
20         for (int i=1; i<=tot; i++){

```

```

21             G[i].clear(); iter[i]=d[i]=gap[i]=0;
22         }
23     }
24     void addEdge(int u, int v, int c){
25         G[u].push_back(Edge(v, c, SZ(G[v])));
26         G[v].push_back(Edge(u, 0, SZ(G[u])-1));
27     }
28     int DFS(int p, int flow){
29         if(p==t) return flow;
30         for (int &i=iter[p]; i<SZ(G[p]); i++){
31             Edge &e=G[p][i];
32             if (e.c>0&&d[p]==d[e.v]+1){
33                 int f=DFS(e.v, min(flow, e.c));
34                 if(f){ e.c-=f; G[e.v][e.r].c+=f; return f; }
35             }
36         }
37         if(--gap[d[p]]==0) d[s]=tot;
38         else{ d[p]++; iter[p]=0; ++gap[d[p]]; }
39         return 0;
40     }
41     int flow(){
42         int res=0;
43         for (res=0, gap[0]=tot, d[s]<tot; res+=DFS(s, INF); )
44             return res;
45     }
46     void reset(){
47         for (int i=1; i<=tot; i++) iter[i]=d[i]=gap[i]=0;
48     }
49 } flow;

```

9.4 Bounded Max Flow

```

1 // Author: CRYPTOGRAPHER
2 // Max flow with lower/upper bound on edges (source-sink
version)
3 // <!-- 1-based: original vertices are numbered 1 ~ n.
4 //    Super source, sink: n+1, n+2 respectively.
5 // <!-- dependency: ISAP.cpp
6 // 1. n = #vertices (1 ~ n), m = #edges
7 //    s, t = original source, sink (both in [1, n])
8 // 2. l[i], r[i] := edge i goes from l[i] -> r[i] (l[i],
r[i] in [1, n])
9 // 3. a[i], b[i] := flow on edge i must lie in [a[i], b[i]]
10 // 4. int ans = solve(n, m, s, t);
11 // => ans == -1 : no feasible flow exists
12 // => ans : feasible max flow value
13 // <!-- N, M must be large enough for original graph + 2
super nodes
14 // Time: O(V^2 E), Space: O(V + E)
15 int in[N], out[N], l[M], r[M], a[M], b[M];
16 int solve(int n, int m, int s, int t){
17     flow.init(n+2, n+1, n+2); // super source = n+1, super
sink = n+2
18     for (int i = 0; i < m; i++){
19         in[r[i]] += a[i]; out[l[i]] += a[i];
20         flow.addEdge(l[i], r[i], b[i] - a[i]);
21         // flow from l[i] to r[i] must lie in [a[i], b[i]]
22     }
23     int nd = 0;
24     for (int i = 1; i <= n; i++){
25         if (in[i] < out[i]){
26             flow.addEdge(i, flow.t, out[i] - in[i]);
27             nd += out[i] - in[i];
28         }
29         if (out[i] < in[i])
30             flow.addEdge(flow.s, i, in[i] - out[i]);
31     }
32     flow.addEdge(t, s, INF); // original sink -> source
33     if (flow.flow() != nd) return -1; // infeasible
34     int ans = flow.G[s].back().c; // t->s edge's current flow
= feasible flow s->t
35     flow.G[s].back().c = flow.G[t].back().c = 0;
36     for (size_t i = 0; i < flow.G[flow.s].size(); i++){
37         Maxflow::Edge &e = flow.G[flow.s][i];
38         flow.G[flow.s][i].c = 0; flow.G[e.v][e.r].c = 0;
39     }
40     for (size_t i = 0; i < flow.G[flow.t].size(); i++){
41         Maxflow::Edge &e = flow.G[flow.t][i];
42         flow.G[flow.t][i].c = 0; flow.G[e.v][e.r].c = 0;
43     }
44     flow.addEdge(flow.s, s, INF); flow.addEdge(t, flow.t,
INF);
45     flow.reset(); // keeps G[] intact, only resets search
state
46     return ans + flow.flow();
47 }

```

9.5 MCMF

```

1 // Author: CRYPTOGRAPHER
2 // MCMF (supports negative edges without negative cycles)
3 // <!-- 1-based: vertices are numbered 1 ~ n.

```

```

4// 1. MCMF.init(n); // n = #vertices (1 ~ n)
5// 2. MCMF.add(u, v, cap, cost);
6// 3. auto [max_flow, min_cost] = MCMF.flow(s, t); // s, t
  in [1, n]
7// Time: O(F * E), Space: O(V + E)
8typedef int Tcost;
9const int MAXV = 20010;
10const int INFf = 1000000;
11const Tcost INFc = 1e9;
12struct MCMF {
13    struct Edge {
14        int v, cap;
15        Tcost w;
16        int rev;
17        bool fw;
18        Edge() {}
19        Edge(int t2, int t3, Tcost t4, int t5, bool t6)
20            : v(t2), cap(t3), w(t4), rev(t5), fw(t6) {}
21    };
22    int V, s, t;
23    vector<Edge> G[MAXV];
24    void init(int n) {
25        V = n;
26        for(int i = 0; i <= V; i++) G[i].clear();
27    }
28    void add(int a, int b, int cap, Tcost w) {
29        G[a].push_back(Edge(b, cap, w, (int)G[b].size(), true));
30        G[b].push_back(Edge(a, 0, -w, (int)G[a].size()-1,
31            false));
32    }
33    Tcost d[MAXV];
34    int id[MAXV], mom[MAXV];
35    bool inqu[MAXV];
36    queue<int> q;
37    pair<int, Tcost> flow(int _s, int _t) {
38        s = _s, t = _t;
39        int mxf = 0, Tcost mnc = 0;
40        while(1) {
41            fill(d, d+V, INFc); // need to use type cast
42            fill(inqu, inqu+V, 0);
43            fill(mom, mom+V, -1);
44            mom[s] = s;
45            d[s] = 0;
46            q.push(s); inqu[s] = 1;
47            while(q.size()) {
48                int u = q.front(); q.pop();
49                inqu[u] = 0;
50                for(int i = 0; i < (int) G[u].size(); i++) {
51                    Edge &e = G[u][i];
52                    int v = e.v;
53                    if(e.cap > 0 && d[v] > d[u]+e.w) {
54                        d[v] = d[u]+e.w;
55                        mom[v] = u;
56                        id[v] = i;
57                        if(!inqu[v]) q.push(v), inqu[v] = 1;
58                    }
59                }
60                if(mom[t] == -1) break;
61                int df = INFf;
62                for(int u = t; u != s; u = mom[u])
63                    df = min(df, G[mom[u]][id[u]].cap);
64                for(int u = t; u != s; u = mom[u]) {
65                    Edge &e = G[mom[u]][id[u]];
66                    e.cap -= df;
67                    G[e.v][e.rev].cap += df;
68                }
69                mxf += df;
70                mnc += df*d[t];
71            }
72            return make_pair(mxf, mnc);
73        }
74    };

```

9.6 Push-Relabel

```

1// Author: Simon Lindholm (kactl)
2// 0-based: vertices are numbered 0 ~ n-1
3// 1. PushRelabel pr(n); // n = #vertices
4// 2. pr.addEdge(u, v, c); // u, v in [0, n-1]
5// 3. ll ans = pr.calc(s, t);
6// => ans = max flow value from s to t
7// To obtain actual flow:
8// for (int u = 0; u < n; u++)
9//     for (auto& e : pr.g[u])
10//         if (e.f > 0) => (u, e.dest, e.f)
11// Time: O(V^2 * sqrt(E)), better on dense graph
12struct PushRelabel {
13    struct Edge { int dest, back; ll f, c; };
14    vector<vector<Edge>> g;

```

```

15    vector<ll> ec;
16    vector<Edge*> cur;
17    vector<vi> hs; vi H;
18    PushRelabel(int n) : g(n), ec(n), cur(n), hs(2*n), H(n) {}
19
20    void addEdge(int s, int t, ll cap, ll rcap=0) {
21        if (s == t) return;
22        g[s].push_back({t, sz(g[t]), 0, cap});
23        g[t].push_back({s, sz(g[s])-1, 0, rcap});
24    }
25    void addFlow(Edge& e, ll f) {
26        Edge &back = g[e.dest][e.back];
27        if (!ec[e.dest] && f) hs[H[e.dest]].push_back(e.dest);
28        e.f += f; e.c -= f; ec[e.dest] += f;
29        back.f -= f; back.c += f; ec[back.dest] -= f;
30    }
31    ll calc(int s, int t) {
32        int v = sz(g); H[s] = v; ec[t] = 1;
33        vi co(2*v); co[0] = v-1;
34        rep(i, 0, v) cur[i] = g[i].data();
35        for (Edge& e : g[s]) addFlow(e, e.c);
36
37        for (int hi = 0;;) {
38            while (hs[hi].empty()) if (!hi--) return -ec[s];
39            int u = hs[hi].back(); hs[hi].pop_back();
40            while (ec[u] > 0) // discharge u
41                if (cur[u] == g[u].data() + sz(g[u])) {
42                    H[u] = 1e9;
43                    for (Edge& e : g[u]) if (e.c && H[u] >
44                        H[e.dest]+1)
45                        H[u] = H[e.dest]+1, cur[u] = &e;
46                    if (++co[H[u]], !--co[hi] && hi < v)
47                        rep(i, 0, v) if (hi < H[i] && H[i] < v)
48                            --co[H[i]], H[i] = v + 1;
49                    hi = H[u];
50                } else if (cur[u]->c && H[u] == H[cur[u]->dest]+1)
51                    addFlow(*cur[u], min(ec[u], cur[u]->c));
52                else ++cur[u];
53            }
54        bool leftOfMinCut(int a) { return H[a] >= sz(g); }
55    };

```

9.7 Gomory-Hu Tree

```

1// Author: chilli, Takanori MAEHARA (kactl)
2// <!> Dependency: PushRelabel.cpp
3// Given a list of edges representing an undirected flow
  graph,
4// returns edges of the Gomory-Hu tree.
5// maxflow / mincut of (u, v) => min edge from u to v on
  Gomory-Hu tree
6// Time: O(V) * O(PushRelabel)
7typedef array<ll, 3> Edge; // (u, v, w)
8vector<Edge> gomoryHu(int N, vector<Edge> ed) {
9    vector<Edge> tree;
10    vi par(N);
11    rep(i, 1, N) {
12        PushRelabel D(N); // Dinic also works
13        for (Edge t : ed) D.addEdge(t[0], t[1], t[2], t[2]);
14        tree.push_back({i, par[i], D.calc(i, par[i])});
15        rep(j, i+1, N)
16            if (par[j] == par[i] && D.leftOfMinCut(j)) par[j] = i;
17    }
18    return tree;
19}

```

9.8 Global Min Cut

```

1// Author: ckiseki
2// 1-based: vertices are numbered 1 ~ n
3// 1. vector<vector<ll>> G(n+1, vector<ll>(n+1, 0));
4// 2. add_edge(G, u, v, c); // add undirected edge u-v with
  weight c, u, v in [1, n]
5// 3. ll ans = mincut(G, n); // n = #vertices
6// => ans = global min cut value
7// Time: O(V^3)
8void add_edge(auto& w, int u, int v, int c) {
9    w[u][v] += c; w[v][u] += c; }
10auto phase(const auto& w, int n, vector<int> id) {
11    vector<ll> g(n+1); int s = -1, t = -1;
12    while (!id.empty()) {
13        int c = -1;
14        for (int i : id) if (c == -1 || g[i] > g[c]) c = i;
15        s = t; t = c;
16        id.erase(ranges::find(id, c));
17        for (int i : id) g[i] += w[c][i];
18    }
19    return tuple{s, t, g[t]};
20}
21ll mincut(auto w, int n) {
22    ll cut = numeric_limits<ll>::max();

```



```

23 vector<int> id(n); iota(all(id), 1);
24 for (int i = 0; i < n - 1; ++i) {
25     auto [s, t, gt] = phase(w, n, id);
26     id.erase(ranges::find(id, t));
27     cut = min(cut, gt);
28     for (int j = 1; j <= n; ++j)
29         w[s][j] += w[t][j], w[j][s] += w[j][t];
30 }
31 return cut;
32 }

```

10 String

10.1 Rolling Hash

```

1 const ll C = 27;
2 inline int id(char c) {return c-'a'+1;}
3 struct RollingHash {
4     string s; int n; ll mod;
5     vector<ll> Cexp, hs;
6     RollingHash(string& _s, ll _mod):
7         s(_s), n((int)_s.size()), mod(_mod)
8     {
9         Cexp.assign(n, 0);
10        hs.assign(n, 0);
11        Cexp[0] = 1;
12        for (int i = 1; i < n; i++) {
13            Cexp[i] = Cexp[i-1] * C;
14            if (Cexp[i] >= mod) Cexp[i] %= mod;
15        }
16        hs[0] = id(s[0]);
17        for (int i = 1; i < n; i++) {
18            hs[i] = hs[i-1] * C + id(s[i]);
19            if (hs[i] >= mod) hs[i] %= mod;
20        }
21        inline ll query(int l, int r) {
22            ll res = hs[r] - (l ? hs[l-1] * Cexp[r-l+1] : 0);
23            res = (res % mod + mod) % mod;
24            return res;
25        };

```

10.2 Trie

```

1 struct node {
2     int c[26]; ll cnt;
3     node(): cnt(0) {memset(c, 0, sizeof(c));}
4     node(ll x): cnt(x) {memset(c, 0, sizeof(c));}
5 };
6 struct Trie {
7     vector<node> t;
8     void init() {
9         t.clear();
10        t.emplace_back(node());
11    }
12    void insert(string s) { int ptr = 0;
13        for (auto& i : s) {
14            if (!t[ptr].c[i-'a']) {
15                t.emplace_back(node());
16                t[ptr].c[i-'a'] = (int)t.size()-1;
17                ptr = t[ptr].c[i-'a'];
18            }
19        }
20        t[ptr].cnt++;
21    }
22 };

```

10.3 KMP

```

1 int n, m;
2 string s, p;
3 vector<int> f;
4 void build() {
5     f.clear(); f.resize(m, 0);
6     int ptr = 0; for (int i = 1; i < m; i++) {
7         while (ptr && p[i] != p[ptr]) ptr = f[ptr-1];
8         if (p[i] == p[ptr]) ptr++;
9         f[i] = ptr;
10    }
11    void init() {
12        cin >> s >> p;
13        n = (int)s.size();
14        m = (int)p.size();
15        build();
16    }
17    void solve() {
18        int ans = 0, pi = 0;
19        for (int si = 0; si < n; si++) {
20            while (pi && s[si] != p[pi]) pi = f[pi-1];
21            if (s[si] == p[pi]) pi++;
22            if (pi == m) ans++, pi = f[pi-1];
23        }
24        cout << ans << endl;
25    }

```

10.4 Z Value

```

1 string is, it, s;
2 int n; vector<int> z;

```

```

3 void init() {
4     cin >> is >> it;
5     s = it+'0'+is;
6     n = (int)s.size();
7     z.resize(n, 0);
8 }
9 void solve() {
10    int ans = 0; z[0] = n;
11    for (int i = 1, l = 0, r = 0; i < n; i++) {
12        if (i <= r) z[i] = min(z[i-l], r-i+1);
13        while (i+z[i] < n && s[z[i]] == s[i+z[i]]) z[i]++;
14        if (i+z[i]-1 > r) l = i, r = i+z[i]-1;
15        if (z[i] == (int)it.size()) ans++;
16    }
17    cout << ans << endl;
18 }

```

10.5 Manacher

```

1 int n; string S, s;
2 vector<int> m;
3 void manacher() {
4     s.clear(); s.resize(2*n+1, '.');
5     for (int i = 0, j = 1; i < n; i++, j += 2) s[j] = S[i];
6     m.clear(); m.resize(2*n+1, 0);
7     // m[i] := max k such that s[i-k, i+k] is palindrome
8     int mx = 0, mxk = 0;
9     for (int i = 1; i < 2*n+1; i++) {
10        if (mx-(i-mx) >= 0) m[i] = min(m[mx-(i-mx)], mx+mxk-i);
11        while (0 <= i-m[i]-1 && i+m[i]+1 < 2*n+1 &&
12            s[i-m[i]-1] == s[i+m[i]+1]) m[i]++;
13        if (i+m[i] > mx+mxk) mx = i, mxk = m[i];
14    }
15 }
16 void init() { cin >> S; n = (int)S.size(); }
17 void solve() {
18     manacher();
19     int mx = 0, ptr = 0;
20     for (int i = 0; i < 2*n+1; i++) if (mx < m[i])
21         { mx = m[i]; ptr = i; }
22     for (int i = ptr-mx; i <= ptr+mx; i++)
23         if (s[i] != '.') cout << s[i];
24     cout << endl;
25 }

```

10.6 Suffix Array

```

1 #define F first
2 #define S second
3 struct SuffixArray { // don't forget s += "$";
4     int n; string s;
5     vector<int> suf, lcp, rk;
6     vector<int> cnt, pos;
7     vector<pair<pii, int>> buc[2];
8     void init(string _s) {
9         s = _s; n = (int)s.size();
10        // resize(n): suf, rk, cnt, pos, lcp, buc[0-1]
11    }
12    void radix_sort() {
13        for (int t : {0, 1}) {
14            fill(cnt.begin(), cnt.end(), 0);
15            for (auto& i : buc[t]) cnt[(t ? i.F.F : i.F.S) ]++;
16            for (int i = 0; i < n; i++)
17                pos[i] = (!i ? 0 : pos[i-1] + cnt[i-1]);
18            for (auto& i : buc[t])
19                buc[t][i].pos[ (t ? i.F.F : i.F.S) ]++ = i;
20        }
21    }
22    bool fill_suf() {
23        bool end = true;
24        for (int i = 0; i < n; i++) suf[i] = buc[0][i].S;
25        rk[suf[0]] = 0;
26        for (int i = 1; i < n; i++) {
27            int dif = (buc[0][i].F != buc[0][i-1].F);
28            end &= dif;
29            rk[suf[i]] = rk[suf[i-1]] + dif;
30        }
31        return end;
32    }
33    void sa() {
34        for (int i = 0; i < n; i++)
35            buc[0][i] = make_pair(make_pair(s[i], s[i]), i);
36        sort(buc[0].begin(), buc[0].end());
37        if (fill_suf()) return;
38        for (int k = 0; (1<<k) < n; k++) {
39            for (int i = 0; i < n; i++)
40                buc[0][i] = make_pair(make_pair(rk[i], rk[(i
41                    + (1<<k)) % n]), i);
42            radix_sort();
43            if (fill_suf()) return;
44        }
45    }
46    void LCP() { int k = 0;
47        for (int i = 0; i < n-1; i++) {
48            if (rk[i] == 0) continue;
49            int pi = rk[i];
50            int j = suf[pi-1];

```

```

47     while (i+k < n && j+k < n && s[i+k] == s[j+k])
48         k++;
49     lcp[pi] = k;
50     k = max(k-1, 0);
51 }
52 SuffixArray suffixarray;

```

10.7 Suffix Automaton

```

1 // any path start from root forms a substring of S
2 // occurrence of P: iff SAM can run on input word P
3 // number of different substring: ds[1]-1
4 // total length of all different substring: dsl[1]
5 // max/min length of state i: mx[i]/mx[mom[i]]+1
6 // assume a run on input word P end at state i:
7 // number of occurrences of P: cnt[i]
8 // first occurrence position of P: fp[i]-|P|+1
9 // all position: !clone nodes in dfs from i through rmom
10 const int MXM=1000010;
11 struct SAM{
12     int tot,root,lst,mom[MXM],mx[MXM]; // ind[MXM]
13     int nxt[MXM][33]; // cnt[MXM],ds[MXM],dsl[MXM],fp[MXM]
14     // bool v[MXM],clone[MXN]
15     int newNode(){
16         int res=++tot; fill(nxt[res],nxt[res]+33,0);
17         mom[res]=mx[res]=0; // cnt=ds=dsl=fp=v=clone=0
18         return res;
19     }
20     void init(){ tot=0;root=newNode();lst=root; }
21     void push(int c){
22         int p=lst,np=newNode(); // cnt[np]=1,clone[np]=0
23         mx[np]=mx[p]+1; // fp[np]=mx[np]-1
24         for(,p&&nxt[p][c]==0;p=mom[p]) nxt[p][c]=np;
25         if(p==0) mom[np]=root;
26         else{
27             int q=nxt[p][c];
28             if(mx[p]+1==mx[q]) mom[np]=q;
29             else{
30                 int nq=newNode(); // fp[nq]=fp[q],clone[nq]=1
31                 mx[nq]=mx[p]+1;
32                 for(int i=0;i<33;i++) nxt[nq][i]=nxt[q][i];
33                 mom[nq]=mom[q]; mom[q]=nq; mom[np]=nq;
34                 for(,p&&nxt[p][c]==q;p=mom[p]) nxt[p][c]=nq;
35             }
36         }
37         lst=np;
38     }
39     void calc(){
40         calc(root); iota(ind,ind+tot,1);
41         sort(ind,ind+tot,&[](int i,int j){return mx[i]<mx[j];});
42         for(int i=tot-1;i>=0;i--)
43             cnt[mom[ind[i]]]+=cnt[ind[i]];
44     }
45     void calc(int x){
46         v[x]=ds[x]=1,dsl[x]=0; // rmom[mom[x]].push_back(x);
47         for(int i=0;i<26;i++){
48             if(nxt[x][i]){
49                 if(!v[nxt[x][i]]) calc(nxt[x][i]);
50                 ds[x]+=ds[nxt[x][i]];
51                 dsl[x]+=ds[nxt[x][i]]+dsl[nxt[x][i]];
52             }
53         }
54         void push(char *str){
55             for(int i=0;str[i];i++) push(str[i]-'a');
56         }
57     } sam;

```

10.8 SA-IS

```

1 const int N=300010;
2 struct SA{
3     #define REP(i,n) for(int i=0;i<int(n);i++)
4     #define REPl(i,a,b) for(int i=(a);i<=int(b);i++)
5     bool t[N*2]; int s[N*2],_sa[N*2];
6     int _c[N*2],x[N],_p[N],_q[N*2],hei[N],r[N];
7     int operator [](int i){ return _sa[i]; }
8     void build(int *s,int n,int m){
9         memcpy(_s,s,sizeof(int)*n);
10        sais(_s,_sa,_p,_q,_t,_c,n,m); mkhei(n);
11    }
12    void mkhei(int n){
13        REP(i,n) r[_sa[i]]=i;
14        hei[0]=0;
15        REP(i,n) if(r[i]){
16            int ans=i>0?max(hei[r[i-1]]-1,0):0;
17            while(_s[i+ans]==_s[_sa[r[i]-1]+ans]) ans++;
18            hei[r[i]]=ans;
19        }
20    }
21    void sais(int *s,int *sa,int *p,int *q,bool *t,int *c,int
22    n,int z){
23        bool uniq=t[n-1]=true,neq;

```

```

23     int nn=0,nmxz=-1,*nsa=sa+n,*ns=s+n,lst=-1;
24     #define MS0(x,n) memset((x),0,n*sizeof(*(x)))
25     #define MAGIC(XD) MS0(sa,n);\
26     memcpy(x,c,sizeof(int)*z); XD;\
27     memcpy(x+1,c,sizeof(int)*(z-1));\
28     REP(i,n) if(sa[i]&&!t[sa[i]-1]) sa[x[s[sa[i]-1]]++]=sa[i]-1;
29     memcpy(x,c,sizeof(int)*z);\
30     for(int i=n-1;i>=0;i--) if(sa[i]&&t[sa[i]-1]) sa[--
31     x[s[sa[i]-1]]]=sa[i]-1;
32     MS0(c,z); REP(i,n) uniq&=++c[s[i]]<2;
33     REP(i,z-1) c[i+1]+=c[i];
34     if(uniq) { REP(i,n) sa[--c[s[i]]]=i; return; }
35     for(int i=n-2;i>=0;i--)
36         t[i]=(s[i]==s[i+1]?t[i+1]:s[i]<s[i+1]);
37     MAGIC(REPl(i,1,n-1) if(t[i]&&!t[i-1]) sa[--
38     x[s[i]]]=p[q[i]=nn++]=i);
39     REP(i,n) if(sa[i]&&t[sa[i]]&&t[sa[i]-1]){
40         neq=lst<0||memcmp(s+sa[i],s+lst,(p[q[sa[i]]+1]-
41         sa[i])*sizeof(int));
42         ns[q[lst=sa[i]]]=nmxz+=neq;
43     }
44     sa;
45     int H[N],SA[N],RA[N];
46     void suffix_array(int* ip,int len){
47         // should padding a zero in the back
48         // ip is int array, len is array length
49         // ip[0..n-1] != 0, and ip[len]=0
50         ip[len]=0; sa.build(ip,len,128);
51         memcpy(H,sa,hei+1,len<2); memcpy(SA,sa._sa+1,len<2);
52         for(int i=0;i<len;i++) RA[i]=sa.r[i]-1;
53         // resulting height, sa array \in [0,len)
54     }

```

10.9 Minimum Rotation

```

1 // lexicographically minimal rotation
2 // rotate(begin(s), begin(s)+minRotation(s), end(s))
3 int minRotation(string s) {
4     int a = 0, n = s.size(); s += s;
5     for(int b = 0; b < n; b++) for(int k = 0; k < n; k++) {
6         if(a + k == b || s[a + k] < s[b + k]) {
7             b += max(0, k - 1);
8             break;
9         }
10        if(s[a + k] > s[b + k]) {
11            a = b;
12            break;
13        }
14    }
15    return a;

```

10.10 Aho Corasick

```

1 struct ACautomata{
2     struct Node{
3         int cnt;
4         Node *go[26], *fail, *dic;
5         Node(){
6             cnt = 0; fail = 0; dic = 0;
7             memset(go,0,sizeof(go));
8         }
9     } pool[1048576],*root;
10    int nMem;
11    Node* new_Node(){
12        pool[nMem] = Node();
13        return &pool[nMem++];
14    }
15    void init() { nMem = 0; root = new_Node(); }
16    void add(const string &str) { insert(root,str,0); }
17    void insert(Node *cur, const string &str, int pos){
18        for(int i=pos;i<str.size();i++){
19            if(!cur->go[str[i]-'a'])
20                cur->go[str[i]-'a'] = new_Node();
21            cur=cur->go[str[i]-'a'];
22        }
23        cur->cnt++;
24    }
25    void make_fail(){
26        queue<Node*> que;
27        que.push(root);
28        while(!que.empty()){
29            Node* fr=que.front(); que.pop();
30            for(int i=0;i<26;i++){
31                if(fr->go[i]){
32                    Node *ptr = fr->fail;
33                    while(ptr && !ptr->go[i]) ptr = ptr->fail;
34                    fr->go[i]->fail=ptr=(ptr?ptr->go[i]:root);
35                    fr->go[i]->dic=(ptr->cnt?ptr:ptr->dic);

```

```

36         que.push(fr->go[i]);
37     } } } }
38 }AC;

```

11 Geometry

11.1 Template

```

1 // Author: Gino
2 typedef long long T;
3 // typedef long double T;
4 const long double eps = 1e-8;
5
6 short sgn(T x) {
7     if (abs(x) < eps) return 0;
8     return x < 0 ? -1 : 1;
9 }
10
11 struct Pt {
12     T x, y;
13     Pt(T _x=0, T _y=0):x(_x), y(_y) {}
14     Pt operator+(Pt a) { return Pt(x+a.x, y+a.y); }
15     Pt operator-(Pt a) { return Pt(x-a.x, y-a.y); }
16     Pt operator*(T a) { return Pt(x*a, y*a); }
17     Pt operator/(T a) { return Pt(x/a, y/a); }
18     T operator*(Pt a) { return x*a.x + y*a.y; }
19     T operator^(Pt a) { return x*a.y - y*a.x; } // 不要打反
20     bool operator<(Pt a)
21     { return x < a.x || (x == a.x && y < a.y); }
22     // return sgn(x-a.x) < 0 || (sgn(x-a.x) == 0 && sgn(y-a.y) < 0); }
23     bool operator==(Pt a)
24     { return sgn(x-a.x) == 0 && sgn(y-a.y) == 0; }
25 };
26
27 Pt mv(Pt a, Pt b) { return b-a; }
28 T len2(Pt a) { return a*a; }
29 T dis2(Pt a, Pt b) { return len2(b-a); }
30
31 short ori(Pt a, Pt b) { return ((a^b)>0) - ((a^b)<0); }
32 bool onseg(Pt p, Pt l1, Pt l2) {
33     Pt a = mv(p, l1), b = mv(p, l2);
34     return ((a^b) == 0) && ((a*b) <= 0);
35 }

```

11.2 Basic Operations

```

1 // Author: Gino
2 // Function: Check if a point P sits in a polygon (doesn't
3 // have to be convex hull)
4 // 0 = Bound, 1 = In, -1 = Out
5 short inPoly(Pt p) {
6     for (int i = 0; i < n; i++)
7         if (onseg(p, E[i], E[(i+1)%n])) return 0;
8     int cnt = 0;
9     for (int i = 0; i < n; i++)
10         if (banana(p, Pt(p.x+1, p.y+2e9), E[i], E[(i+1)%n]))
11             cnt ^= 1;
12     return (cnt ? 1 : -1);
13 }

```

```

1 // Author: Gino
2 int ud(Pt a) { // up or down half plane
3     if (a.y > 0) return 0;
4     if (a.y < 0) return 1;
5     return (a.x >= 0 ? 0 : 1);
6 }
7 sort(ALL(E), [&](const Pt& a, const Pt& b) {
8     if (ud(a) != ud(b)) return ud(a) < ud(b);
9     return (a^b) > 0;
10 });

```

```

1 // Author: Gino
2 // Function: check if (p1---p2) (q1---q2) banana
3 inline bool banana(Pt p1, Pt p2, Pt q1, Pt q2) {
4     if (onseg(p1, q1, q2) || onseg(p2, q1, q2) ||
5         onseg(q1, p1, p2) || onseg(q2, p1, p2)) {
6         return true;
7     }
8     Pt p = mv(p1, p2), q = mv(q1, q2);
9     return (ori(p, mv(p1, q1)) * ori(p, mv(p1, q2)) < 0 &&
10         ori(q, mv(q1, p1)) * ori(q, mv(q1, p2)) < 0);
11 }

```

```

1 // Author: Gino
2 // T: long double
3 Pt bananaPoint(Pt p1, Pt p2, Pt q1, Pt q2) {
4     if (onseg(q1, p1, p2)) return q1;
5     if (onseg(q2, p1, p2)) return q2;
6     if (onseg(p1, q1, q2)) return p1;
7     if (onseg(p2, q1, q2)) return p2;
8     double s = abs(mv(p1, p2) ^ mv(p1, q1));
9     double t = abs(mv(p1, p2) ^ mv(p1, q2));

```

```

10 return q2 * (s/(s+t)) + q1 * (t/(s+t));
11 }
12
13 // Author: Gino
14 vector<Pt> hull;
15 void convexHull() {
16     hull.clear(); sort(E.begin(), E.end());
17     for (int t : {0, 1}) {
18         int b = (int)hull.size();
19         for (auto& ei : E) {
20             while ((int)hull.size() - b >= 2 &&
21                 ori(mv(hull[(int)hull.size()-2],
22                     mv(hull[(int)hull.size()-2], ei)) == -1)
23             {
24                 hull.pop_back();
25             }
26             hull.emplace_back(ei);
27         }
28         hull.pop_back();
29         reverse(E.begin(), E.end());
30     }
31 }
32
33 // Author: Gino
34 // Function: Return doubled area of a polygon
35 T dbarea(vector<Pt>& e) {
36     ll res = 0;
37     for (int i = 0; i < (int)e.size(); i++)
38         res += e[i]^e[(i+1)%SZ(e)];
39     return abs(res);
40 }

```

11.3 Lower Concave Hull

```

1 // Author: Unknown
2 struct Line {
3     mutable ll m, b, p;
4     bool operator<(const Line& o) const { return m < o.m; }
5     bool operator<(ll x) const { return p < x; }
6 };
7
8 struct LineContainer : multiset<Line, less<>> {
9     // (for doubles, use inf = 1/.0, div(a,b) = a/b)
10     const ll inf = LLONG_MAX;
11     ll div(ll a, ll b) { // floored division
12         return a / b - ((a ^ b) < 0 && a % b); }
13     bool isect(iterator x, iterator y) {
14         if (y == end()) { x->p = inf; return false; }
15         if (x->m == y->m) x->p = x->b > y->b ? inf : -inf;
16         else x->p = div(y->b - x->b, x->m - y->m);
17         return x->p >= y->p;
18     }
19     void add(ll m, ll b) {
20         auto z = insert({m, b, 0}), y = z++, x = y;
21         while (isect(y, z)) z = erase(z);
22         if (x != begin() && isect(--x, y)) isect(x, y = erase(y));
23         while ((y = x) != begin() && (--x)->p >= y->p)
24             isect(x, erase(y));
25     }
26     ll query(ll x) {
27         assert(!empty());
28         auto l = *lower_bound(x);
29         return l.m * x + l.b;
30     }
31 };

```

11.4 Pick's Theorem

Consider a polygon which vertices are all lattice points.

Let i = number of points inside the polygon.

Let b = number of points on the boundary of the polygon.

Then we have the following formula:

$$\text{Area} = i + \frac{b}{2} - 1$$

11.5 Minimum Enclosing Circle

```

1 // Author: Gino
2 // Function: Find Min Enclosing Circle using Randomized O(n)
3 // Algorithm
4 Pt circumcenter(Pt A, Pt B, Pt C) {
5     // a1(x-A.x) + b1(y-A.y) = c1
6     // a2(x-A.x) + b2(y-A.y) = c2
7     // solve using Cramer's rule
8     T a1 = B.x-A.x, b1 = B.y-A.y, c1 = dis2(A, B)/2.0;
9     T a2 = C.x-A.x, b2 = C.y-A.y, c2 = dis2(A, C)/2.0;
10    T D = Pt(a1, b1) ^ Pt(a2, b2);
11    T Dx = Pt(c1, b1) ^ Pt(c2, b2);

```

```

11 T Dy = Pt(a1, c1) ^ Pt(a2, c2);
12 if (D == 0) return Pt(-INF, -INF);
13 return A + Pt(Dx/D, Dy/D);
14 }
15 Pt center; T r2;
16
17 void minEncloseCircle() {
18 mt19937
19   gen(chrono::steady_clock::now().time_since_epoch().count());
20   shuffle(ALL(E), gen);
21   center = E[0], r2 = 0;
22   for (int i = 0; i < n; i++) {
23     if (dis2(center, E[i]) <= r2) continue;
24     center = E[i], r2 = 0;
25     for (int j = 0; j < i; j++) {
26       if (dis2(center, E[j]) <= r2) continue;
27       center = (E[i] + E[j]) / 2.0;
28       r2 = dis2(center, E[i]);
29       for (int k = 0; k < j; k++) {
30         if (dis2(center, E[k]) <= r2) continue;
31         center = circumcenter(E[i], E[j], E[k]);
32         r2 = dis2(center, E[i]);
33       }
34     }
35   }

```

11.6 PolyUnion

```

1 // Author: Unknown
2 struct PY{
3   int n; Pt pt[5]; double area;
4   Pt& operator[](const int x){ return pt[x]; }
5   void init(){ //n,pt[0~n-1] must be filled
6     area=pt[n-1]^pt[0];
7     for(int i=0;i<n-1;i++) area+=pt[i]^pt[i+1];
8     if((area/=2)<0)reverse(pt,pt+n),area=-area;
9   }
10 };
11 PY py[500]; pair<double,int> c[5000];
12 inline double segP(Pt &p,Pt &p1,Pt &p2){
13   if(dcmp(p1.x-p2.x)==0) return (p.y-p1.y)/(p2.y-p1.y);
14   return (p.x-p1.x)/(p2.x-p1.x);
15 }
16 double polyUnion(int n){ //py[0~n-1] must be filled
17   int i,j,ii,jj,ta,tb,r,d; double z,w,s,sum=0,tc,td;
18   for(i=0;i<n;i++) py[i][py[i].n]=py[i][0];
19   for(i=0;i<n;i++){
20     for(ii=0;ii<py[i].n;ii++){
21       r=0;
22       c[r++]=make_pair(0.0,0); c[r++]=make_pair(1.0,0);
23       for(j=0;j<n;j++){
24         if(i==j) continue;
25         for(jj=0;jj<py[j].n;jj++){
26           ta=dcmp(tri(py[i][ii],py[i][ii+1],py[j][jj]));
27           tb=dcmp(tri(py[i][ii],py[i][ii+1],py[j][jj+1]));
28           if(ta==0 && tb==0){
29             if((py[j][jj+1]-py[j][jj])*(py[i][ii+1]-py[i][ii])>0&&j<i){
30               c[r++]=make_pair(segP(py[j][jj],py[i][ii],py[i][ii+1]),1);
31               c[r++]=make_pair(segP(py[j][jj+1],py[i][ii],py[i][ii+1]),-1);
32             }
33             else if(ta>0 && tb<0){
34               tc=tri(py[j][jj],py[j][jj+1],py[i][ii]);
35               td=tri(py[j][jj],py[j][jj+1],py[i][ii+1]);
36               c[r++]=make_pair(tc/(tc-td),1);
37             }
38             else if(ta<0 && tb>0){
39               tc=tri(py[j][jj],py[j][jj+1],py[i][ii]);
40               td=tri(py[j][jj],py[j][jj+1],py[i][ii+1]);
41               c[r++]=make_pair(tc/(tc-td),-1);
42             }
43             sort(c,c+r);
44             z=min(max(c[0].first,0.0),1.0); d=c[0].second; s=0;
45             for(j=1;j<r;j++){
46               w=min(max(c[j].first,0.0),1.0);
47               if(!d) s+=w-z;
48               d+=c[j].second; z=w;
49             }
50             sum+=(py[i][ii]^py[i][ii+1])*s;
51           }
52         }
53       }
54     }
55   }
56   return sum/2;

```

11.7 Minkowski Sum

```

1 // Author: Unknown
2 /* convex hull Minkowski Sum*
3 #define INF 10000000000000LL
4 int pos( const Pt& tp ){

```

```

5   if( tp.Y == 0 ) return tp.X > 0 ? 0 : 1;
6   return tp.Y > 0 ? 0 : 1;
7 }
8 #define N 300030
9 Pt pt[ N ], qt[ N ], rt[ N ];
10 LL Lx,Rx;
11 int dn,un;
12 inline bool cmp( Pt a, Pt b ){
13   int pa=pos( a ),pb=pos( b );
14   if(pa==pb) return (a^b)>0;
15   return pa<pb;
16 }
17 int minkowskiSum(int n,int m){
18   int i,j,r,p,q,fi,fj;
19   for(i=1,p=0;i<n;i++){
20     if( pt[i].Y<pt[p].Y ||
21        (pt[i].Y==pt[p].Y && pt[i].X<pt[p].X) ) p=i; }
22   for(i=1,q=0;i<m;i++){
23     if( qt[i].Y<qt[q].Y ||
24        (qt[i].Y==qt[q].Y && qt[i].X<qt[q].X) ) q=i; }
25   rt[0]=pt[p]+qt[q];
26   r=1; i=p; j=q; fi=fj=0;
27   while(1){
28     if((fj&&j==q) ||
29        ( (!fi||i==p) &&
30          cmp(pt[(p+1)%n]-pt[p],qt[(q+1)%m]-qt[q]) ) ){
31       rt[r]=rt[r-1]+pt[(p+1)%n]-pt[p];
32       p=(p+1)%n;
33       fi=1;
34     }
35     else{
36       rt[r]=rt[r-1]+qt[(q+1)%m]-qt[q];
37       q=(q+1)%m;
38       fj=1;
39     }
40     if(r<=1 || ((rt[r]-rt[r-1])^(rt[r-1]-rt[r-2]))!=0) r++;
41     else rt[r-1]=rt[r];
42     if(i==p && j==q) break;
43   }
44   return r-1;
45 }
46 void initInConvex(int n){
47   int i,p,q;
48   LL Ly,Ry;
49   Lx=INF; Rx=-INF;
50   for(i=0;i<n;i++){
51     if(pt[i].X<Lx) Lx=pt[i].X;
52     if(pt[i].X>Rx) Rx=pt[i].X;
53   }
54   Ly=Ry=INF;
55   for(i=0;i<n;i++){
56     if(pt[i].X==Lx && pt[i].Y<Ly){ Ly=pt[i].Y; p=i; }
57     if(pt[i].X==Rx && pt[i].Y<Ry){ Ry=pt[i].Y; q=i; }
58   }
59   for(dn=0,i=p;i!=q;i=(i+1)%n){ qt[dn++]=pt[i]; }
60   qt[dn]=pt[q]; Ly=Ry=-INF;
61   for(i=0;i<n;i++){
62     if(pt[i].X==Lx && pt[i].Y>Ly){ Ly=pt[i].Y; p=i; }
63     if(pt[i].X==Rx && pt[i].Y>Ry){ Ry=pt[i].Y; q=i; }
64   }
65   for(un=0,i=p;i!=q;i=(i+n-1)%n){ rt[un++]=pt[i]; }
66   rt[un]=pt[q];
67 }
68 inline int inConvex(Pt p){
69   int L,R,M;
70   if(p.X<Lx || p.X>Rx) return 0;
71   L=0;R=dn;
72   while(L<R-1){ M=(L+R)/2;
73     if(p.X<qt[M].X) R=M; else L=M; }
74   if(tri(qt[L],qt[R],p)<0) return 0;
75   L=0;R=un;
76   while(L<R-1){ M=(L+R)/2;
77     if(p.X<rt[M].X) R=M; else L=M; }
78   if(tri(rt[L],rt[R],p)>0) return 0;
79   return 1;
80 }
81 int main(){
82   int n,m,i;
83   Pt p;
84   scanf("%d",&n);
85   for(i=0;i<n;i++) scanf("%lld%lld",&pt[i].X,&pt[i].Y);
86   scanf("%d",&m);
87   for(i=0;i<m;i++) scanf("%lld%lld",&qt[i].X,&qt[i].Y);
88   n=minkowskiSum(n,m);
89   for(i=0;i<n;i++) pt[i]=rt[i];
90   scanf("%d",&m);
91   for(i=0;i<m;i++) scanf("%lld%lld",&qt[i].X,&qt[i].Y);
92   n=minkowskiSum(n,m);
93   for(i=0;i<n;i++) pt[i]=rt[i];

```



```

93 initInConvex(n);
94 scanf("%d", &m);
95 for(i=0; i<m; i++){
96     scanf("%lld %lld", &p.X, &p.Y);
97     p.X*=3; p.Y*=3;
98     puts(inConvex(p)? "YES": "NO");
99 }
100 }

```

12 Number Theory

12.1 Prime Sieve and Defactor

```

1 // Author: Gino
2 const int maxc = 1e6 + 1;
3 vector<int> lpf;
4 vector<int> prime;
5
6 void seive() {
7     prime.clear();
8     lpf.resize(maxc, 1);
9     for (int i = 2; i < maxc; i++) {
10         if (lpf[i] == 1) {
11             lpf[i] = i;
12             prime.emplace_back(i);
13         }
14         for (auto& j : prime) {
15             if (i * j >= maxc) break;
16             lpf[i * j] = j;
17             if (j == lpf[i]) break;
18         }
19     }
20     vector<pii> fac;
21     void defactor(int u) {
22         fac.clear();
23         while (u > 1) {
24             int d = lpf[u];
25             fac.emplace_back(make_pair(d, 0));
26             while (u % d == 0) {
27                 u /= d;
28                 fac.back().second++;
29             }
30         }
31     }
32 }

```

12.2 Harmonic Series

```

1 // Author: Gino
2 // O(n log n)
3 for (int i = 1; i <= n; i++) {
4     for (int j = i; j <= n; j += i) {
5         // O(1) code
6     }
7 }
8
9 // PIE
10 // given array a[0], a[1], ..., a[n - 1]
11 // calculate dp[x] = number of pairs (a[i], a[j]) such that
12 // gcd(a[i], a[j]) = x // (i < j)
13 //
14 // idea: let mc(x) = # of y s.t. x|y
15 // f(x) = # of pairs s.t. gcd(a[i], a[j]) >= x
16 // f(x) = C(mc(x), 2)
17 // dp[x] = f(x) - sum(dp[y], x < y and x|y)
18 const int maxc = 1e6;
19 vector<int> cnt(maxc + 1, 0), dp(maxc + 1, 0);
20 for (int i = 0; i < n; i++)
21     cnt[a[i]]++;
22
23 for (int x = maxc; x >= 1; x--) {
24     ll cnt_mul = 0; // number of multiples of x
25     for (int y = x; y <= maxc; y += x)
26         cnt_mul += cnt[y];
27
28     dp[x] = cnt_mul * (cnt_mul - 1) / 2; // number of pairs
29     // that are divisible by x
30     for (int y = x + x; y <= maxc; y += x)
31         dp[x] -= dp[y]; // PIE: subtract all dp[y] for y >
32 // x and x|y
33 }

```

12.3 Count Number of Divisors

```

1 // Author: Gino
2 // Function: Count the number of divisors for all x <= 10^6
3 // using harmonic series
4 const int maxc = 1e6;
5 vector<int> facs;
6
7 void find_all_divisors() {
8     facs.clear(); facs.resize(maxc + 1, 0);
9     for (int x = 1; x <= maxc; x++) {
10         for (int y = x; y <= maxc; y += x) {
11             facs[y]++;
12         }
13     }
14 }

```

13}

12.4 數論分塊

```

1 // Author: Gino
2 /*
3 n = 17
4 i: 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17
5 n/i: 17 8 5 4 3 2 2 2 1 1 1 1 1 1 1 1 1
6
7         ^      ^
8         L(2)  R(2)
9 L(x) := left bound for n/i = x
10 R(x) := right bound for n/i = x
11
12 ===== FORMULA =====
13 >>> R = n / (n/L) <<<
14 =====
15
16 Example: L(2) = 6
17             R(2) = 17 / (17 / 6)
18                = 17 / 2
19                = 8
20 */
21 // ===== CODE =====
22
23 for (ll l = 1, r = 1, q = n; l <= n; l = r + 1) {
24     q = n/l;
25     r = n/q;
26     // Process your code here
27 }
28 // q, l, r: 17 1 1
29 // q, l, r: 8 2 2
30 // q, l, r: 5 3 3
31 // q, l, r: 4 4 4
32 // q, l, r: 3 5 5
33 // q, l, r: 2 6 8
34 // q, l, r: 1 9 17

```

12.5 Pollard's rho

```

1 // Author: Unknown
2 // Function: Find a non-trivial factor of a big number in
3 // O(n^(1/4) log^2(n))
4 ll find_factor(ll number) {
5     __int128 x = 2;
6     for (__int128 cycle = 1; ; cycle++) {
7         __int128 y = x;
8         for (int i = 0; i < (1 << cycle); i++) {
9             x = (x * x + 1) % number;
10            __int128 factor = __gcd(x - y, number);
11            if (factor > 1)
12                return factor;
13        }
14    }
15 }
16
17 1# Author: Unknown
18 2# Function: Find a non-trivial factor of a big number in
19 // O(n^(1/4) log^2(n))
20 from itertools import count
21 from math import gcd
22 from sys import stdin
23
24 for s in stdin:
25     number, x = int(s), 2
26     brk = False
27     for cycle in count(1):
28         y = x
29         if brk:
30             break
31         for i in range(1 << cycle):
32             x = (x * x + 1) % number
33             factor = gcd(x - y, number)
34             if factor > 1:
35                 print(factor)
36                 brk = True
37                 break
38     break

```

12.6 Miller Rabin

```

1 // Author: Unknown, Modified by Gino
2 // Function: Check if a number is a prime in O(100 *
3 // log^2(n))
4 // miller_rabin(): return 1 if prime, 0 otherwise
5 inline ll mul(ll x, ll y, ll mod) {
6     return (__int128)(x) * y % mod;
7 }
8 ll mypow(ll a, ll b, ll mod) {
9     ll r = 1;
10    while (b > 0) {
11        if (b & 1) r = mul(r, a, mod);
12    }
13 }

```

```

11     a = mul(a, a, mod);
12     b >>= 1;
13 }
14 return r;
15 }
16 bool witness(ll a, ll n, ll u, int t){
17     ll x = mypow(a, u, n);
18     for(int i = 0; i < t; i++) {
19         ll nx = mul(x, x, n);
20         if (nx == 1 && x != 1 && x != n-1) return true;
21         x = nx;
22     }
23     return x != 1;
24 }
25 bool miller_rabin(ll n) {
26     // if n >= 3,474,749,660,383
27     // change {2, 3, 5, 7, 11, 13} to
28     // {2, 325, 9375, 28178, 450775, 9780504, 1795265022}
29     if (n < 2) return false;
30     if (!(n & 1)) return n == 2;
31     ll u = n - 1; int t = 0;
32     while(!(u & 1)) u >>= 1, t++;
33     for (ll a : {2, 3, 5, 7, 11, 13}) {
34         if (a % n == 0) continue;
35         if (witness(a, n, u, t)) return false;
36     }
37     return true;
38 }
39 // bases that make sure no pseudoprimes flee from test
40 // if WA, replace randll(n - 1) with these bases:
41 // n < 4,759,123,141      3 : 2, 7, 61
42 // n < 1,122,004,669,633  4 : 2, 13, 23, 1662803
43 // n < 3,474,749,660,383  6 : pimes <= 13
44 // n < 2^64              7 :
45 // 2, 325, 9375, 28178, 450775, 9780504, 1795265022

```

12.7 Discrete Log

```

1 // Author: ckiseki
2 // find x^? = y (mod M)
3 // O(sqrt(M))
4 template<typename Int>
5 Int BSGS(Int x, Int y, Int M) {
6     // x^? ≡ y (mod M)
7     Int t = 1, c = 0, g = 1;
8     for (Int M_ = M; M_ > 0; M_ >>= 1) g = g * x % M;
9     for (g = gcd(g, M); t % g != 0; ++c) {
10         if (t == y) return c;
11         t = t * x % M;
12     }
13     if (y % g != 0) return -1;
14     t /= g, y /= g, M /= g;
15     Int h = 0, gs = 1;
16     for (; h * h < M; ++h) gs = gs * x % M;
17     unordered_map<Int, Int> bs;
18     for (Int s = 0; s < h; bs[y] = ++s) y = y * x % M;
19     for (Int s = 0; s < M; s += h) {
20         t = t * gs % M;
21         if (bs.count(t)) return c + s + h - bs[t];
22     }
23     return -1;
24 }

```

12.8 Discrete Sqrt

```

1 // Author: ckiseki
2 // find solution for x^2 = n (mod P)
3 // O(log^2 P)
4 int get_root(int n, int P) { // ensure 0 <= n < P
5     if (P == 2 || n == 0) return n;
6     auto check = [&](ll x) {
7         return modpow(x, (P - 1) / 2, P);
8     };
9     if (check(n) != 1) return -1;
10    mt19937 rnd(7122); ll z = 1, w;
11    while (check(w = (z * z - n + P) % P) != P - 1)
12        z = rnd() % P;
13    const auto M = [P, w](auto &u, auto &v) {
14        auto [a, b] = u; auto [c, d] = v;
15        return make_pair((a * c + b * d % P * w) % P,
16                          (a * d + b * c) % P);
17    };
18    pair<ll, ll> r(1, 0), e(z, 1);
19    for (int q = (P + 1) / 2; q; q >>= 1, e = M(e, e))
20        if (q & 1) r = M(r, e);
21    return int(r.first); // sqrt(n) mod P where P is prime

```

12.9 Fast Power

Note: $a^n \equiv a^{(n \bmod (p-1))} \pmod{p}$

12.10 Extend GCD

1 // Author: Gino

```

2 // [Usage]
3 // bezout(a, b, c):
4 //     find solution to ax + by = c
5 //     return {-LINF, -LINF} if no solution
6 // inv(a, p):
7 //     find modulo inverse of a under p
8 //     return -1 if not exist
9 // CRT(vector<ll>& a, vector<ll>& m)
10 //     find a solution pair (x, mod) satisfies all x = a[i]
11 //         (mod m[i])
12 //     return {-LINF, -LINF} if no solution
13 const ll LINF = 4e18;
14 typedef pair<ll, ll> pll;
15 template<typename T1, typename T2>
16 T1 chmod(T1 a, T2 m) {
17     return (a % m + m) % m;
18 }
19
20 ll GCD;
21 pll extgcd(ll a, ll b) {
22     if (b == 0) {
23         GCD = a;
24         return pll{1, 0};
25     }
26     pll ans = extgcd(b, a % b);
27     return pll{ans.second, ans.first - a/b * ans.second};
28 }
29 pll bezout(ll a, ll b, ll c) {
30     bool negx = (a < 0), negy = (b < 0);
31     pll ans = extgcd(abs(a), abs(b));
32     if (c % GCD != 0) return pll{-LINF, -LINF};
33     return pll{ans.first * c/GCD * (negx ? -1 : 1),
34               ans.second * c/GCD * (negy ? -1 : 1)};
35 }
36 ll inv(ll a, ll p) {
37     if (p == 1) return -1;
38     pll ans = bezout(a % p, -p, 1);
39     if (ans == pll{-LINF, -LINF}) return -1;
40     return chmod(ans.first, p);
41 }
42 pll CRT(vector<ll>& a, vector<ll>& m) {
43     for (int i = 0; i < (int)a.size(); i++)
44         a[i] = chmod(a[i], m[i]);
45
46     ll x = a[0], mod = m[0];
47     for (int i = 1; i < (int)a.size(); i++) {
48         pll sol = bezout(mod, m[i], a[i] - x);
49         if (sol.first == -LINF) return pll{-LINF, -LINF};
50
51         // prevent long long overflow
52         ll p = chmod(sol.first, m[i] / GCD);
53         ll lcm = mod / GCD * m[i];
54         x = chmod((__int128)p * mod + x, lcm);
55         mod = lcm;
56     }
57     return pll{x, mod};
58 }

```

12.11 Mu + Phi

```

1 // Author: Gino
2 const int maxn = 1e6 + 5;
3 ll f[maxn];
4 vector<int> lpf, prime;
5 void build() {
6     lpf.clear(); lpf.resize(maxn, 1);
7     prime.clear();
8     f[1] = ...; /* mu[1] = 1, phi[1] = 1 */
9     for (int i = 2; i < maxn; i++) {
10         if (lpf[i] == 1) {
11             lpf[i] = i; prime.emplace_back(i);
12             f[i] = ...; /* mu[i] = 1, phi[i] = i-1 */
13         }
14         for (auto& j : prime) {
15             if (i*j >= maxn) break;
16             lpf[i*j] = j;
17             if (i % j == 0) f[i*j] = ...; /* 0, phi[i]*j */
18             else f[i*j] = ...; /* -mu[i], phi[i]*phi[j] */
19             if (j >= lpf[i]) break;
20         }
21     }
22 }

```

12.12 Other Formulas

- Pisano Period: 任何線性遞迴 (比如費氏數列) 模任何一個數字 M 都會循環, 找循環節 $\pi(M)$ 先質因數分解 $M = \prod p_i^{e_i}$, 然後 $\pi(M) = \text{lcm}(\pi(p_i^{e_i}))$,
- Inversion:
 $aa^{-1} \equiv 1 \pmod{m}$. a^{-1} exists iff $\text{gcd}(a, m) = 1$.

- Linear inversion:
 $a^{-1} \equiv (m - \lfloor \frac{m}{a} \rfloor) \times (m \bmod a)^{-1} \pmod{m}$
- Fermat's little theorem:
 $a^p \equiv a \pmod{p}$ if p is prime.
- Euler function:
 $\varphi(n) = n \prod_{p|n} \frac{p-1}{p}$
- Euler theorem:
 $a^{\varphi(n)} \equiv 1 \pmod{n}$ if $\gcd(a, n) = 1$. If a, n are not coprime: 質因數分解 $n = \prod p_i^{e_i}$, 對每個 $p_i^{e_i}$ 分開看他們跟 a 是否互質 (互質: Fermat/不互質: 夠大的指數會直接削成 0), 最後用 CRT 合併.
- Extended Euclidean algorithm:
 $ax + by = \gcd(a, b) = \gcd(b, a \bmod b) = \gcd(b, a - \lfloor \frac{a}{b} \rfloor b) = bx_1 + (a - \lfloor \frac{a}{b} \rfloor b)y_1 = ay_1 + b(x_1 - \lfloor \frac{a}{b} \rfloor y_1)$
- Divisor function:
 $\sigma_x(n) = \sum_{d|n} d^x \cdot n = \prod_{i=1}^r p_i^{a_i}$
 $\sigma_x(n) = \prod_{i=1}^r \frac{p_i^{(a_i+1)x} - 1}{p_i^x - 1}$ if $x \neq 0$. $\sigma_0(n) = \prod_{i=1}^r (a_i + 1)$.
- Chinese remainder theorem (Coprime Moduli):
 $x \equiv a_i \pmod{m_i}$.
 $M = \prod m_i$. $M_i = \frac{M}{m_i}$. $t_i = M_i^{-1}$.
 $x = kM + \sum a_i t_i M_i$, $k \in \mathbb{Z}$.
- Chinese remainder theorem:
 $x \equiv a_1 \pmod{m_1}, x \equiv a_2 \pmod{m_2} \Rightarrow x = m_1 p + a_1 = m_2 q + a_2 \Rightarrow m_1 p - m_2 q = a_2 - a_1$
Solve for (p, q) using ExtGCD.
 $x \equiv m_1 p + a_1 \equiv m_2 q + a_2 \pmod{\text{lcm}(m_1, m_2)}$
- Avoiding Overflow: $ca \bmod cb = c(a \bmod b)$
- Dirichlet Convolution: $(f * g)(n) = \sum_{d|n} f(d)g(\frac{n}{d})$
- Important Multiplicative Functions + Properties:
 - $\varepsilon(n) = [n = 1]$
 - $1(n) = 1$
 - $id(n) = n$
 - $\mu(n) = 0$ if n has squared prime factor
 - $\mu(n) = (-1)^k$ if $n = p_1 p_2 \dots p_k$
 - $\varepsilon = \mu * 1$
 - $\varphi = \mu * id$
 - $[n = 1] = \sum_{d|n} \mu(d)$
 - $[gcd = 1] = \sum_{d|gcd} \mu(d)$
- Möbius inversion: $f = g * 1 \Leftrightarrow g = f * \mu$

12.13 Polynomial

```

1// Author: Gino
2// Preparation: first set_mod(mod, g), then init_ntt()
3// everytime you change modulus, you have to call init_ntt()
  again
4//
5// [Usage]
6// polynomial: vector<ll> a, b
7// negation: -a
8// add/subtract: a += b, a -= b
9// convolution: a *= b
10// in-place modulo: mod(a, b)
11// in-place inversion under mod x^N: inv(ia, N)
12
13
14const int maxk = 20;
15const int maxn = 1<<maxk;
16
17using u64 = unsigned long long;
18using u128 = __uint128_t;
19
20int g;
21u64 MOD;
22u64 BARRETT_IM; // [ 2^64 / MOD ]
23
24inline void set_mod(u64 m, int _g) {
25    g = _g;
26    MOD = m;
27    BARRETT_IM = (u128(1) << 64) / m;
28}
29inline u64 chmod(u128 x) {
30    u64 q = (u64)((x * BARRETT_IM) >> 64);
31    u64 r = (u64)(x - (u128)q * MOD);
32    if (r >= MOD) r -= MOD;
33    return r;
34}
35inline u64 mmul(u64 a, u64 b) {
36    return chmod((u128)a * b);
37}
38ll pw(ll a, ll n) {

```

```

39    ll ret = 1;
40    while (n > 0) {
41        if (n & 1) ret = mmul(ret, a);
42        a = mmul(a, a);
43        n >>= 1;
44    }
45    return ret;
46}
47
48vector<ll> X, iX;
49vector<int> rev;
50void init_ntt() {
51    X.assign(maxn, 1); // x1 = g^((p-1)/n)
52    iX.assign(maxn, 1);
53
54    ll u = pw(g, (MOD-1)/maxn);
55    ll iu = pw(u, MOD-2);
56    for (int i = 1; i < maxn; i++) {
57        X[i] = mmul(X[i-1], u);
58        iX[i] = mmul(iX[i-1], iu);
59    }
60
61    if ((int)rev.size() == maxn) return;
62    rev.assign(maxn, 0);
63    for (int i = 1, hb = -1; i < maxn; i++) {
64        if (!(i & (i-1))) hb++;
65        rev[i] = rev[i ^ (1<<hb)] | (1<<(maxk-hb-1));
66    }
67}
68template<typename T>
69void NTT(vector<T>& a, bool inv=false) {
70    int _n = (int)a.size();
71    int k = __lg(_n) + ((1<<__lg(_n)) != _n);
72    int n = 1<<k;
73    a.resize(n, 0);
74
75    short shift = maxk-k;
76    for (int i = 0; i < n; i++)
77        if (i > (rev[i]>>shift))
78            swap(a[i], a[rev[i]>>shift]);
79    for (int len = 2, half = 1, div = maxn>>1; len <= n;
80        len<=<len, half<=<half, div>>=1) {
81        for (int i = 0; i < n; i += len) {
82            for (int j = 0; j < half; j++) {
83                T u = a[i+j];
84                T v = mmul(a[i+j+half], (inv ? iX[j*div] :
85                    X[j*div]));
86                a[i+j] = (u+v >= MOD ? u+v-MOD : u+v);
87                a[i+j+half] = (u-v < 0 ? u-v+MOD : u-v);
88            }
89        }
90    }
91    if (inv) {
92        T dn = pw(n, MOD-2);
93        for (auto& x : a) {
94            x = mmul(x, dn);
95        }
96    }
97}
98template<typename T>
99inline void shrink(vector<T>& a) {
100    int cnt = (int)a.size();
101    for (; cnt > 0; cnt--) if (a[cnt-1]) break;
102    a.resize(max(cnt, 1));
103}
104template<typename T>
105vector<T>& operator*=(vector<T>& a, vector<T> b) {
106    int na = (int)a.size();
107    int nb = (int)b.size();
108    a.resize(na + nb - 1, 0);
109    b.resize(na + nb - 1, 0);
110
111    NTT(a); NTT(b);
112    for (int i = 0; i < (int)a.size(); i++)
113        a[i] = mmul(a[i], b[i]);
114    NTT(a, true);
115
116    shrink(a);
117    return a;
118}
119
120inline ll crt(ll a0, ll a1, ll m1, ll m2, ll inv_m1_mod_m2) {
121    // x ≡ a0 (mod m1), x ≡ a1 (mod m2)
122    // t = (a1 - a0) * inv(m1) mod m2
123    // x = a0 + t * m1 (mod m1*m2)
124    ll t = chmod(a1 - a0);
125    if (t < 0) t += m2;
126    t = (ll)((__int128)t * inv_m1_mod_m2 % m2);
127    return a0 + (ll)((__int128)t * m1);
128}
129
130void mul_crt() {
131    // a copy to a1, a2 | b copy to b1, b2
132    ll M1 = 998244353, M2 = 1004535809;
133    g = 3; set_mod(M1); init_ntt(); a1 *= b1;
134    g = 3; set_mod(M2); init_ntt(); a2 *= b2;

```

```

126
127 ll inv_m1_mod_m2 = pw(M1, M2 - 2);
128 for (int i = 2; i <= 2 * k; i++)
129     cout << crt(a1[i], a2[i], M1, M2, inv_m1_mod_m2) <<
    ;
130 cout << endl;
131 }
132
133 /* P = r*2^k + 1
134 P          r    k    g
135 998244353    119 23   3
136 1004535809   479 21   3
137
138 P          r    k    g
139 3           1    1    2
140 5           1    2    2
141 17          1    4    3
142 97          3    5    5
143 193         3    6    5
144 257         1    8    3
145 7681        15   9   17
146 12289       3   12   11
147 40961       5   13   3
148 65537       1   16   3
149 786433      3   18   10
150 5767169     11   19   3
151 7340033     7   20   3
152 23068673    11   21   3
153 104857601   25   22   3
154 167772161   5   25   3
155 469762049   7   26   3
156 1004535809  479 21   3
157 2013265921  15  27  31
158 2281701377  17  27   3
159 3221225473  3   30   5
160 75161927681 35  31   3
161 77309411329 9   33   7
162 206158430209 3  36  22
163 2061584302081 15 37   7
164 2748779069441 5  39   3
165 6597069766657 3  41   5
166 39582418599937 9  42   5
167 79164837199873 9  43   5
168 263882790666241 15 44   7
169 1231453023109121 35 45   3
170 1337006139375617 19 46   3
171 3799912185593857 27 47   5
172 4222124650659841 15 48  19
173 7881299347898369 7   50   6
174 31525197391593473 7   52   3
175 180143985094819841 5   55   6
176 1945555039024054273 27 56   5
177 4179340454199820289 29 57   3
178 9097271247288401921 505 54 6 */

```

12.14 Counting Primes

```

1 // prime_count - #primes in [1..n] (O(n^{2/3}) time,
2 // O(sqrt(n)) memory)
3 using u64 = unsigned long long;
4 static inline u64 prime_count(u64 n){
5     if(n<=1) return 0;
6     int v = (int)floor(sqrt((long double)n));
7     int s = (v+1)>>1, pc = 0;
8     vector<int> smalls(s), roughs(s), skip(v+1);
9     vector<long long> larges(s);
10
11     for(int i=0; i<s; ++i){
12         smalls[i]=i;
13         roughs[i]=2*i+1;
14         larges[i]=(long long)((n/roughs[i]-1)>>1);
15     }
16
17     for(int p=3; p<=v; p+=2) if(!skip[p]){
18         int q = p*p;
19         if(1LL*q*q > (long long)n) break;
20         skip[p]=1;
21         for(int i=q; i<=v; i+=2*p) skip[i]=1;
22
23         int ns=0;
24         for(int k=0; k<s; ++k){
25             int i = roughs[k];
26             if(skip[i]) continue;
27             u64 d = (u64)i * (u64)p;
28             long long sub = (d <= (u64)v)
29                 ? larges[smalls[(int)(d>>1)] - pc]
30                 : smalls[(int)((n/d - 1) >> 1)];
31             larges[ns] = larges[k] - sub + pc;
32             roughs[ns++] = i;

```

```

33     }
34     s = ns;
35     for(int i=(v-1)>>1, j=((v/p)-1)|1; j>=p; j-=2){
36         int c = smalls[j>>1] - pc;
37         for(int e=(j*p)>>1; i>=e; --i) smalls[i] -= c;
38     }
39     ++pc;
40 }
41
42 larges[0] += 1LL*(s + 2*(pc-1))*(s-1) >> 1;
43 for(int k=1; k<s; ++k) larges[0] -= larges[k];
44
45 for(int l=1; l<s; ++l){
46     int q = roughs[l];
47     u64 m = n / (u64)q;
48     long long t = 0;
49     int e = smalls[(int)((m/q - 1) >> 1)] - pc;
50     if(e < l+1) break;
51     for(int k=l+1; k<=e; ++k) t += smalls[(int)((m/
52         (u64)roughs[k] - 1) >> 1)];
53     larges[0] += t - 1LL*(e - l)*(pc + l - 1);
54 }
55 return (u64)(larges[0] + 1);
56 }

```

12.15 Linear Sieve for Other Number Theoretic Functions

```

1 // linear_sieve(n, primes, lp, phi, mu, d, sigma)
2 // Outputs over the index range 0..n (n >= 1):
3 // primes : all primes in [2..n], increasing.
4 // lp      : lowest prime factor; lp[1]=0, lp[x] is the
5 //            smallest prime dividing x.
6 // phi     : Euler totient, phi[x] = |{1<=k<=x :
7 //            gcd(k,x)=1}|. Multiplicative.
8 // mu      : Möbius; mu[1]=1, mu[x]=0 if x has a squared
9 //            prime factor, else (-1)^{#distinct primes}.
10 // d       : number of divisors; if x=∏ p_i^{e_i}, then
11 //            d[x]=∏(e_i+1). Multiplicative.
12 // sigma   : sum of divisors; if x=∏ p_i^{e_i}, then
13 //            sigma[x]=∏(1+p_i+...+p_i^{e_i}). (use 1LL)
14 // Complexity: O(n) time, O(n) memory.
15 // Notes: Arrays are resized inside; primes is cleared and
16 //         reserved. sigma uses ll to avoid 32-bit overflow.
17
18 static inline void linear_sieve(
19     int n,
20     std::vector<int> &primes,
21     std::vector<int> &lp,
22     std::vector<int> &phi,
23     std::vector<int> &mu,
24     std::vector<int> &d,
25     std::vector<ll> &sigma
26 ) {
27     lp.assign(n + 1, 0); phi.assign(n + 1, 0); mu.assign(n +
28     1, 0); d.assign(n + 1, 0); sigma.assign(n + 1, 0);
29     primes.clear(); primes.reserve(n > 1 ? n / 10 : 0);
30     std::vector<int> cnt(n + 1, 0), core(n + 1, 1);
31     std::vector<ll> p_pow(n + 1, 1), sum_p(n + 1, 1);
32     phi[1] = mu[1] = d[1] = sigma[1] = 1;
33
34     for (int i = 2; i <= n; ++i) {
35         if (!lp[i]) {
36             lp[i] = i; primes.push_back(i);
37             phi[i] = i - 1; mu[i] = -1; d[i] = 2;
38             cnt[i] = 1; p_pow[i] = i; core[i] = 1;
39             sum_p[i] = 1 + (ll)i; sigma[i] = sum_p[i];
40         }
41         for (int p : primes) {
42             long long ip = 1LL * i * p;
43             if (ip > n) break;
44             lp[ip] = p;
45             if (p == lp[i]) {
46                 cnt[ip] = cnt[i] + 1; p_pow[ip] = p_pow[i] * p;
47                 core[ip] = core[i];
48                 sum_p[ip] = sum_p[i] + p_pow[ip];
49                 phi[ip] = phi[i] * p; mu[ip] = 0;
50                 d[ip] = d[core[ip]] * (cnt[ip] + 1);
51                 sigma[ip] = sigma[core[ip]] * sum_p[ip];
52                 break; // critical for linear complexity
53             } else {
54                 cnt[ip] = 1; p_pow[ip] = p; core[ip] = i;
55                 sum_p[ip] = 1 + (ll)p;
56                 phi[ip] = phi[i] * (p - 1); mu[ip] = -mu[i];
57                 d[ip] = d[i] * 2;
58                 sigma[ip] = sigma[i] * sum_p[ip];
59             }
60         }
61     }
62 }

```



```

56
57 // Optional helper: factorize x in O(log x) using lp
  (requires x in [2..n])
58 static inline std::vector<std::pair<int,int>> factorize(int
  x, const std::vector<int>& lp) {
59     std::vector<std::pair<int,int>> res;
60     while (x > 1) {
61         int p = lp[x], e = 0;
62         do { x /= p; ++e; } while (x % p == 0);
63         res.push_back({p, e});
64     }
65     return res;
66 }

```

13 Linear Algebra

13.1 Gaussian-Jordan Elimination

```

1 int n; vector<vector<ll>> > v;
2 void gauss(vector<vector<ll>>& v) {
3     int r = 0;
4     for (int i = 0; i < n; i++) {
5         bool ok = false;
6         for (int j = r; j < n; j++) {
7             if (v[j][i] == 0) continue;
8             swap(v[j], v[r]);
9             ok = true; break;
10        }
11        if (!ok) continue;
12        ll div = inv(v[r][i]);
13        for (int j = 0; j < n+1; j++) {
14            v[r][j] *= div;
15            if (v[r][j] >= MOD) v[r][j] %= MOD;
16        }
17        for (int j = 0; j < n; j++) {
18            if (j == r) continue;
19            ll t = v[j][i];
20            for (int k = 0; k < n+1; k++) {
21                v[j][k] -= v[r][k] * t % MOD;
22                if (v[j][k] < 0) v[j][k] += MOD;
23            }
24        }
25    }

```

13.2 Determinant

1. Use GJ Elimination, if there's any row consists of only 0, then $\det = 0$, otherwise $\det = \text{product of diagonal elements}$.
2. Properties of $\det$:
 - Transpose: Unchanged
 - Row Operation 1 - Swap 2 rows: $-\det$
 - Row Operation 2 - $k\vec{r}_i$: $k \times \det$
 - Row Operation 3 - $k\vec{r}_i$ add to $\vec{r}_j$: Unchanged

14 Combinatorics

14.1 Catalan Number

$$C_0 = 1, C_n = \sum_{i=0}^{n-1} C_i C_{n-1-i}, C_n = C_n^{2n} - C_{n-1}^{2n}$$

0	1	1	2	5
4	14	42	132	429
8	1430	4862	16796	58786
12	208012	742900	2674440	9694845

14.2 Bertrand's Ballot Theorem

- A always $> B$: $C(p+q, p) - 2C(p+q-1, p)$
- A always $\geq B$: $C(p+q, p) \times \frac{p+1-q}{p+1}$

14.3 Burnside's Lemma

Let X be the original set.

Let G be the group of operations acting on X .

Let X^g be the set of x not affected by g .

Let X/G be the set of orbits.

Then the following equation holds:

$$|X/G| = \frac{1}{|G|} \sum_{g \in G} |X^g|$$

15 Special Numbers

15.1 Fibonacci Series

1	1	1	2	3
5	5	8	13	21
9	34	55	89	144
13	233	377	610	987
17	1597	2584	4181	6765
21	10946	17711	28657	46368
25	75025	121393	196418	317811
29	514229	832040	1346269	2178309
33	3524578	5702887	9227465	14930352

$$f(45) \approx 10^9, f(88) \approx 10^{18}$$

15.2 Prime Numbers

- $\pi(n) \equiv \text{Number of primes} \leq n \approx \frac{n}{(\ln n)-1}$

$$\begin{aligned} \pi(100) &= 25, \pi(200) = 46 \\ \pi(500) &= 95, \pi(1000) = 168 \\ \pi(2000) &= 303, \pi(4000) = 550 \\ \pi(10^4) &= 1229, \pi(10^5) = 9592 \\ \pi(10^6) &= 78498, \pi(10^7) = 664579 \end{aligned}$$

