

1	Reminder	1
1.1	Observations and Tricks	1
1.2	Bug List	1
2	Init (Linux)	1
2.1	vimrc	2
2.2	run.sh	2
3	Basic	2
3.1	Template (Using Codebook)	2
3.2	PBDS	2
3.3	Random	2
4	Python	2
4.1	I/O	2
4.2	Decimal	2
5	Data Structure	2
5.1	CDQ	2
5.2	Mo's Algorithm	3
5.3	Heavy Light Decomposition	3
5.4	Leftist Heap	3
5.5	Persistent Treap	3
5.6	Li Chao Tree	3
5.7	Time Segment Tree	4
6	DP	4
6.1	Aliens	4
6.2	SOS DP	5
6.3	期望 DP (Expected Value DP)	5
6.4	數位 DP (Digit DP)	5
7	Graph	5
7.1	Max Clique	5
7.2	Bellman-Ford + SPFA	6
7.3	BCC - AP	6
7.4	BCC - Bridge	7
7.5	SCC - Tarjan with 2-SAT	7
7.6	Eulerian Path - Undir	7
7.7	Eulerian Path - Dir	8
7.8	Kth Shortest Path	8
7.9	System of Difference Constraints	9
8	String	9
8.1	Rolling Hash	9
8.2	Trie	9
8.3	KMP	9
8.4	Z Value	9
8.5	Manacher	9
8.6	Suffix Array	9
8.7	Suffix Automaton	10
8.8	SA-IS	10
8.9	Minimum Rotation	10
8.10	Aho Corasick	10
9	Geometry	11
9.1	Template	11
9.2	Basic Operations	11
9.3	Lower Concave Hull	11
9.4	Pick's Theorem	11
9.5	Minimum Enclosing Circle	11
9.6	PolyUnion	12
9.7	Minkowski Sum	12
10	Number Theory	13
10.1	Prime Sieve and Defactor	13
10.2	Harmonic Series	13
10.3	Count Number of Divisors	13
10.4	數論分塊	13
10.5	Pollard's rho	13
10.6	Miller Rabin	13
10.7	Discrete Log	14
10.8	Discrete Sqrt	14
10.9	Fast Power	14
10.10	Extend GCD	14
10.11	Mu + Phi	14
10.12	Other Formulas	14
10.13	Polynomial	15
10.14	Counting Primes	16
10.15	Linear Sieve for Other Number Theoretic Functions	16
11	Linear Algebra	17
11.1	Gaussian-Jordan Elimination	17
11.2	Determinant	17
12	Matching	17
12.1	Bipartite Matching	17
12.2	Bipartite Weighted Matching	17
12.3	General Matching	18
12.4	General Weighted Matching	18
13	Flow	19
13.1	Flow Methods	19
13.2	Dinic	19
13.3	ISAP	20
13.4	Bounded Max Flow	21
13.5	MCMF	21
13.6	Push-Relabel	21
13.7	Gomory-Hu Tree	22
13.8	Global Min Cut	22
14	Combinatorics	22
14.1	Catalan Number	22
14.2	Bertrand's Ballot Theorem	22
14.3	Burnside's Lemma	22
15	Special Numbers	22
15.1	Fibonacci Series	22
15.2	Prime Numbers	22

1.1 Observations and Tricks

- Contribution Technique
- 二分圖/Spanning Tree/DFS Tree
- 行、列操作互相獨立
- 奇偶性
- 當 s, t 遞增並且 $t = f(s)$ ，對 s 二分搜不好做，可以改成對 t 二分搜，再算 $f(t)$
- 啟發式合併
- Permutation Normalization (做一些平移對齊兩個 permutation)
- 枚舉 $a_1 \sim a_n$ 再枚舉 $a_n \sim a_1$ 可以包在一個迴圈
- 兩個凸型函數相加還是凸型函數，相減不一定
- 一個區間的 $\text{mex} = k$ ，表示這個區間包含 $0 \sim k-1$ 所有數字，並且「 U - 區間」的最小值 $= k$ 。

1.2 Bug List

- 沒開 long long
- 陣列截出界／陣列開不夠大
- 寫好的函式忘記呼叫
- 0-base / 1-base
- 忘記初始化
- == 打成 =
- <= 打成 <+
- dp[i] 從 dp[i-1] 轉移時忘記特判 $i > 0$
- std::sort 比較運算子寫成 $<$ 或是讓 $=$ 的情況為 true
- 漏 case
- 線段樹改值懶標初始值不能設為 0
- DFS 的時候不小心覆寫到全域變數
- 浮點數誤差
- unsigned int l28
- 多筆測資不能沒讀完直接 return
- 記得刪 cerr
- vector 超級肥，小 vector 請用 array，例如矩陣快速幂

2 Init (Linux)

```
1 vim ~/.vimrc
2 mkdir contest && cd contest
3
4 vim template.cpp
5 for c in {A..P}: do
```

```
6 cp template.cpp $c.cpp
7 done
8
9 vim run.sh && chmod 777 run.sh
```

2.1 vimrc

```
1 syn on
2 set nu rnu ru cul mouse=a
3 set cin et ts=4 sw=4 sts=4
4 set autochdir
5 set clipboard=unnamedplus
6
7 colo koehler
8
9 no <C-h> ^
10 no <C-l> $
11 no ; :
12
13 inoremap {<CR> {<CR>}<Esc>ko
```

2.2 run.sh

```
1#!/bin/bash
2
3g++ -std=c++17 -O2 -g -fsanitize=undefined,address $1 &&
echo DONE COMPILE || exit 1
4./a.out
```

3 Basic

3.1 Template (Using Codebook)

```
1// CRyptGRapheR
2#define SZ(c) ((int)(c).size())
3
4// kactl
5#define sz(x) (int)(x).size()
6#define rep(i,a,b) for(int i=(a);i<(b);i++)
7using ll = long long;
8using vi = vector<int>;
9
10// ckiseki
11#define all(x) begin(x), end(x)
12#define pb emplace_back
13#define REP(i, l, r) for (int i=(l); i<=(r); ++i)
14const ll LINF = 1e18;
15template<class A, class B> bool chmin(A& a, B& b) {
16    return b < a ? a = b, 1 : 0;
17}
```

3.2 PBDS

```
1#include <bits/extc++.h>
2using namespace __gnu_pbds;
3
4// map
5tree<int, int, less<>, rb_tree_tag,
tree_order_statistics_node_update> tr;
6tr.order_of_key(element);
7tr.find_by_order(rank);
8
9// set
10tree<int, null_type, less<>, rb_tree_tag,
tree_order_statistics_node_update> tr;
11tr.order_of_key(element);
12tr.find_by_order(rank);
13
14// priority queue
15__gnu_pbds::priority_queue<int, less<int> > big_q; // Big
First
16__gnu_pbds::priority_queue<int, greater<int> > small_q; //
Small First
17al.join(a2); // join
```

3.3 Random

```
1mt19937
gen(chrono::steady_clock::now().time_since_epoch().count());
2#define RANDINT(a, b) uniform_int_distribution<int>(a, b)
(rng) // inclusive
3#define RANDLL(a, b) uniform_int_distribution<long long>(a,
b)(rng) // inclusive
4#define RANDFLOAT(a, b) uniform_real_distribution<float>(a,
b)(rng) // exclusive
5#define RANDDOUBLE(a, b)
uniform_real_distribution<double>(a, b)(rng) // exclusive
6shuffle(v.begin(), v.end(), gen);
```

4 Python

4.1 I/O

```
1import sys
2input = sys.stdin.readline
3
4# Input
5def readInt():
6    return int(input())
7def readIntList():
8    return list(map(int,input().split()))
9def readStr():
```

```
10 s = input()
11 return list(s[:len(s) - 1])
12def readInts():
13    return map(int,input().split())
```

4.2 Decimal

```
1from decimal import *
2getcontext().prec = 500 # precision
3getcontext().Emax = 500 # 科學記號指數最大值
4# 將東西轉成 Decimal
5Decimal(x)
6Decimal(y)
7Decimal(0.0)
8# 運算子跟一般浮點數一樣
9x *= y
10# 輸出
11print(x.quantize(Decimal("0.000001"),
rounding=ROUND_HALF_EVEN))
12# ROUND_CEILING (2.9=>3, -2.1=>-2)
13# ROUND_FLOOR (2.1=>2, -2.9=>-3)
14# ROUND_HALF_EVEN (2.5=>2, 3.5=>4)
15# ROUND_HALF_UP (2.5=>3, -2.5=>-3)
16# ROUND_HALF_DOWN (2.5=>2, -2.5=>-2)
17# ROUND_UP (2.1=>3, -2.1=>-3)
18# ROUND_DOWN (2.9=>2, -2.9=>-2)
```

5 Data Structure

5.1 CDQ

```
1// preparation
2// 1. write a 1-base BIT
3// 2. init(n, mxc): n is number of elements, mxc = 值域
4// 3. build info array CDQ.v by yourself (x, y, z, id)
5// 4. call solve()
6// => cdq.ans[i] is number of j s.t. (xj <= xi, yj <= yi, zj
<= zi) (j != i)
7struct CDQ {
8    struct info {
9        int x, y, z, id;
10        info(int x, int y, int z, int id):
11            x(x), y(y), z(z), id(id) {}
12        info():
13            x(0), y(0), z(0), id(0) {}
14    };
15    int n, mxc;
16    BIT bit;
17    vector<info> v;
18    vector<ll> ans;
19    void init(int _n, int _mxc) {
20        n = _n; mxc = _mxc;
21        v.assign(n, info{});
22        ans.assign(n, 0);
23    }
24    void dfs(int l, int r) {
25        if (l >= r) return;
26        int mid = (l+r) >> 1;
27        dfs(l, mid); dfs(mid+1, r);
28
29        vector<info> tmp;
30        vector<int> bit_op;
31        int pl = l, pr = mid+1;
32
33        while (pl <= mid && pr <= r) {
34            if (v[pl].y <= v[pr].y) {
35                tmp.emplace_back(v[pl]);
36                bit.upd(v[pl].z, 1);
37                bit_op.emplace_back(v[pl].z);
38                pl++;
39            }
40            else {
41                tmp.emplace_back(v[pr]);
42                ans[v[pr].id] += bit.qry(v[pr].z);
43                pr++;
44            }
45        }
46        while (pl <= mid) {
47            tmp.emplace_back(v[pl]);
48            pl++;
49        }
50        while (pr <= r) {
51            tmp.emplace_back(v[pr]);
52            ans[v[pr].id] += bit.qry(v[pr].z);
53            pr++;
54        }
55        for (int i = l, j = 0; i <= r; i++, j++) v[i] =
tmp[j];
56        for (auto& op : bit_op) bit.upd(op, -1);
57    }
58    void solve() {
59        bit.init(mxc);
```

```

60     sort(v.begin(), v.end(), [&](const info& a, const
info& b){
61         return (a.x == b.x ? (a.y == b.y ? (a.z == b.z ?
a.id < b.id : a.z < b.z) : a.y < b.y) : a.x < b.x);
62     });
63     dfs(0, n-1);
64     map<pair<int, pii>, int> s;
65     sort(v.begin(), v.end(), [&](const info& a, const
info& b){
66         return a.id > b.id;
67     });
68     for (int i = 0, id = n-1; i < n; i++, id--) {
69         pair<int, pii> tmp = make_pair(v[i].x,
make_pair(v[i].y, v[i].z));
70         auto it = s.find(tmp);
71         if (it != s.end())
72             ans[id] += it->second;
73         s[tmp]++;
74     }
75 }
76 };
```

5.2 Mo's Algorithm

```

1// segments are 0-based
2ll cur = 0; // current answer
3int pl = 0, pr = -1;
4for (auto& qi : Q) {
5    // get (l, r, qid) from qi
6    while (pl < l) del(pl++);
7    while (pl > l) add(--pl);
8    while (pr < r) add(++pr);
9    while (pr > r) del(pr--);
10   ans[qid] = cur;
11}
```

5.3 Heavy Light Decomposition

```

1// Author: Ian
2void build(V<int>&v);
3void modify(int p, int k);
4int query(int ql, int qr);
5// Insert [ql, qr] segment tree here
6inline void solve(){
7    int n, q; cin >> n >> q;
8    V<int> v(n);
9    for (auto& i: v) cin >> i;
10   V<V<int>> e(n);
11   for(int i = 1; i < n; i++){
12       int a, b; cin >> a >> b, a--, b--;
13       e[a].emplace_back(b);
14       e[b].emplace_back(a);
15   }
16   V<int> d(n, 0), f(n, 0), sz(n, 1), son(n, -1);
17   F<void(int, int)> dfs1 = [&](int x, int pre) {
18       for (auto i: e[x]) if (i != pre) {
19           d[i] = d[x]+1, f[i] = x;
20           dfs1(i, x), sz[x] += sz[i];
21           if (son[x] == -1 || sz[son[x]] < sz[i])
22               son[x] = i;
23       }
24   }; dfs1(0, 0);
25   V<int> top(n, 0), dfn(n, -1);
26   F<void(int, int)> dfs2 = [&](int x, int t) {
27       static int cnt = 0;
28       dfn[x] = cnt++, top[x] = t;
29       if (son[x] == -1) return;
30       dfs2(son[x], t);
31       for (auto i: e[x]) if (i != dfn[i])
32           dfs2(i, i);
33   }; dfs2(0, 0);
34   V<int> dfnv(n);
35   for (int i = 0; i < n; i++)
36       dfnv[dfn[i]] = v[i];
37   build(dfnv);
38   while(q--){
39       int op, a, b, ans; cin >> op >> a >> b;
40       switch(op){
41           case 1:
42               modify(dfn[a-1], b);
43               break;
44           case 2:
45               a--, b--, ans = 0;
46               while (top[a] != top[b]) {
47                   if (d[top[a]] > d[top[b]]) swap(a, b);
48                   ans = max(ans, query(dfn[top[b]], dfn[b+1]));
49                   b = f[top[b]];
50               }
51               if (dfn[a] > dfn[b]) swap(a, b);
52               ans = max(ans, query(dfn[a], dfn[b+1]));
53               cout << ans << endl;
54               break;
55       }
```

5.4 Leftist Heap

```

1// Author: Ian
2// Function: min-heap, with worst-time O(lg n) merge
3struct node {
4    node *l, *r; int d, v;
5    node(int x): d(1), v(x) { l = r = nullptr; }
6};
7static inline int d(node* x) { return x ? x->d : 0; }
8node* merge(node* a, node* b) {
9    if (!a || !b) return a ? b;
10   if (a->v > b->v) swap(a, b);
11   a->r = merge(a->r, b);
12   if (d(a->l) < d(a->r))
13       swap(a->l, a->r);
14   a->d = d(a->r) + 1;
15   return a;
16}
```

5.5 Persistent Treap

```

1// Author: Ian
2struct node {
3    node *l, *r;
4    char c; int v, sz;
5    node(char x = '$'): c(x), v(mt()), sz(1) {
6        l = r = nullptr;
7    }
8    node(node* p) { *this = *p; }
9    void pull() {
10        sz = 1;
11        for (auto i : {l, r})
12            if (i) sz += i->sz;
13    }
14    arr[maxn], *ptr = arr;
15    inline int size(node* p) { return p ? p->sz : 0; }
16    node* merge(node* a, node* b) {
17        if (!a || !b) return a ? b;
18        if (a->v < b->v) {
19            node* ret = new(ptr++) node(a);
20            ret->r = merge(ret->r, b), ret->pull();
21            return ret;
22        }
23        else {
24            node* ret = new(ptr++) node(b);
25            ret->l = merge(a, ret->l), ret->pull();
26            return ret;
27        }
28    }
29    P<node*> split(node* p, int k) {
30        if (!p) return {nullptr, nullptr};
31        if (k >= size(p->l) + 1) {
32            auto [a, b] = split(p->r, k - size(p->l) - 1);
33            node* ret = new(ptr++) node(p);
34            ret->r = a, ret->pull();
35            return {ret, b};
36        }
37        else {
38            auto [a, b] = split(p->l, k);
39            node* ret = new(ptr++) node(p);
40            ret->l = b, ret->pull();
41            return {a, ret};
42        }
43    }
```

5.6 Li Chao Tree

```

1// Author: Ian
2// Function: For a set of lines L, find the maximum L_i(x)
in L in O(lg n).
3typedef long double ld;
4constexpr int maxn = 5e4 + 5;
5struct line {
6    ld a, b;
7    ld operator()(ld x) { return a * x + b; }
8} arr[(maxn + 1) << 2];
9bool operator<(line a, line b) { return a.a < b.a; }
10#define m ((l+r)>>1)
11void insert(line x, int l = 1, int r = 0, int m = maxn) {
12    if (r - l == 1) {
13        if (x(l) > arr[m](l))
14            arr[m] = x;
15        return;
16    }
17    line a = max(arr[l], x), b = min(arr[r], x);
18    if (a(m) > b(m))
19        arr[m] = a, insert(b, l << 1, l, m);
20    else
21        arr[m] = b, insert(a, l << 1 | 1, m, r);
22}
```

```

23 ld query(int x, int i = 1, int l = 0, int r = maxn) {
24   if (x < l || r <= x) return -numeric_limits<ld>::max();
25   if (r - l == 1) return arr[i](x);
26   return max({arr[i](x), query(x, i << 1, l, m), query(x, i
  << 1 | 1, m, r)});
27 }
28 #undef m

```

5.7 Time Segment Tree

```

1 // Author: Ian
2 constexpr int maxn = 1e5 + 5;
3 V<P<int>> arr[(maxn + 1) << 2];
4 V<int> dsu, sz;
5 V<tuple<int, int, int>> his;
6 int cnt, q;
7 int find(int x) {
8   return x == dsu[x] ? x : find(dsu[x]);
9 };
10 inline bool merge(int x, int y) {
11   int a = find(x), b = find(y);
12   if (a == b) return false;
13   if (sz[a] > sz[b]) swap(a, b);
14   his.emplace_back(a, b, sz[b]), dsu[a] = b, sz[b] +=
    sz[a];
15   return true;
16 };
17 inline void undo() {
18   auto [a, b, s] = his.back(); his.pop_back();
19   dsu[a] = a, sz[b] = s;
20 };
21 #define m ((l + r) >> 1)
22 void insert(int ql, int qr, P<int> x, int i = 1, int l = 0,
  int r = q) {
23   // debug(ql, qr, x); return;
24   if (qr <= l || r <= ql) return;
25   if (ql <= l && r <= qr) {arr[i].push_back(x); return;}
26   if (qr <= m)
27     insert(ql, qr, x, i << 1, l, m);
28   else if (m <= ql)
29     insert(ql, qr, x, i << 1 | 1, m, r);
30   else {
31     insert(ql, qr, x, i << 1, l, m);
32     insert(ql, qr, x, i << 1 | 1, m, r);
33   }
34 }
35 void traversal(V<int>& ans, int i = 1, int l = 0, int r = q)
  {
36   int opcnt = 0;
37   // debug(i, l, r);
38   for (auto [a, b] : arr[i])
39     if (merge(a, b))
40       opcnt++, cnt--;
41   if (r - l == 1) ans[l] = cnt;
42   else {
43     traversal(ans, i << 1, l, m);
44     traversal(ans, i << 1 | 1, m, r);
45   }
46   while (opcnt--)
47     undo(), cnt++;
48   arr[i].clear();
49 }
50 #undef m
51 inline void solve() {
52   int n, m; cin >> n >> m >> q; q++;
53   dsu.resize(cnt = n), sz.assign(n, 1);
54   iota(dsu.begin(), dsu.end(), 0);
55   // a, b, time, operation
56   unordered_map<ll, V<int>> s;
57   for (int i = 0; i < m; i++) {
58     int a, b; cin >> a >> b;
59     if (a > b) swap(a, b);
60     s[(ll)a << 32 | b].emplace_back(0);
61   }
62   for (int i = 1; i < q; i++) {
63     int op, a, b;
64     cin >> op >> a >> b;
65     if (a > b) swap(a, b);
66     switch (op) {
67       case 1:
68         s[(ll)a << 32 | b].push_back(i);
69         break;
70       case 2:
71         auto tmp = s[(ll)a << 32 | b].back();
72         s[(ll)a << 32 | b].pop_back();
73         insert(tmp, i, P<int> {a, b});
74     }
75   }
76   for (auto [p, v] : s) {
77     int a = p >> 32, b = p & -1;

```

```

78   while (v.size()) {
79     insert(v.back(), q, P<int> {a, b});
80     v.pop_back();
81   }
82 }
83 V<int> ans(q);
84 traversal(ans);
85 for (auto i : ans)
86   cout << i << ' ';
87 cout << endl;
88 }

```

6 DP

- 區間 DP
 - 狀態： $dp[l][r]$ = 區間 $[l, r]$ 的最佳值/方案數
 - 轉移：枚舉劃分點 k
 - 思考：是否滿足四邊形不等式、Knuth 優化可加速
- 背包 DP
 - 狀態： $dp[i][w]$ = 前 i 個物品容量 w 的最佳值
 - 判斷是 0/1、多重、分組 $\Rightarrow$ 決定轉移方式
 - 若容量大 $\Rightarrow$ bitset / 數學變形 / meet-in-the-middle
- 樹形 DP
 - 狀態： $dp[u][flag]$ = 子樹 u 的最佳值
 - 合併子樹資訊 $\Rightarrow$ 小到大合併 / 捲積式轉移
 - 注意 reroot 技巧 (dp on tree + dp2 上傳)
- 數位 DP
 - 狀態： $(pos, tight, property)$
 - tight 控制是否貼上界
 - property 常為「餘數、數字和、相鄰限制」
- 狀壓 DP
 - 狀態： $dp[mask][last]$
 - 常見於 TSP / Hamiltonian path / 覆蓋問題
 - $n \leq 20$ 可做，否則要容斥 / FFT
- 期望 / 機率 DP
 - 狀態 $E[s]$ = 從狀態 s 到終點的期望
 - 式子： $E[s] = c + \sum P(s \rightarrow s')E[s']$
 - 線性期望：能拆就拆，少算分布
 - 輸出 mod $\Rightarrow$ 分數化 $\Rightarrow$ 模逆元
- 計數 DP / 組合數
 - 狀態表示方案數，常搭配「模數取餘」
 - 若轉移是捲積型 $\Rightarrow$ FFT/NTT 加速
 - 若能公式化 (Catalan / Ballot / Stirling) $\Rightarrow$ 直接套公式
- 優化 DP
 - 判斷轉移方程 $dp[i] = \min_j (dp[j] + C(j, i))$ 的性質
 - 單調性 $\Rightarrow$ 分治優化
 - 凸性 $\Rightarrow$ Convex Hull Trick / 斜率優化
 - 四邊形不等式 $\Rightarrow$ Knuth 優化

6.1 Aliens

```

1 // Author: Gino
2 // Function: TODO
3 int n; ll k;
4 vector<ll> a;
5 vector<pll> dp[2];
6 void init() {
7   cin >> n >> k;
8   for (auto& d : dp) d.clear(), d.resize(n);
9   a.clear(); a.resize(n);
10  for (auto& i : a) cin >> i;
11 }
12 pll calc(ll p) {
13   dp[0][0] = make_pair(0, 0);
14   dp[1][0] = make_pair(-a[0], 0);
15   for (int i = 1; i < n; i++) {
16     if (dp[0][i-1].first > dp[1][i-1].first + a[i] - p) {
17       dp[0][i] = dp[0][i-1];
18     } else if (dp[0][i-1].first < dp[1][i-1].first + a[i] -
    p) {
19       dp[0][i] = make_pair(dp[1][i-1].first + a[i] - p,
    dp[1][i-1].second+1);
20     } else {
21       dp[0][i] = make_pair(dp[0][i-1].first, min(dp[0][
    i-1].second, dp[1][i-1].second+1));
22     }
23     if (dp[0][i-1].first - a[i] > dp[1][i-1].first) {
24       dp[1][i] = make_pair(dp[0][i-1].first - a[i], dp[0][
    i-1].second);
25     } else if (dp[0][i-1].first - a[i] < dp[1][i-1].first) {
26       dp[1][i] = dp[1][i-1];

```

```

27     } else {
28         dp[l][i] = make_pair(dp[l][i-1].first, min(dp[0][
[i-1].second, dp[l][i-1].second));
29     }
30 }
31 return dp[0][n-1];
32 }
33 void solve() {
34     ll l = 0, r = 1e7;
35     pll res = calc(0);
36     if (res.second <= k) return cout << res.first << endl,
void();
37     while (l < r) {
38         ll mid = (l+r)>>1;
39         res = calc(mid);
40         if (res.second <= k) r = mid;
41         else l = mid+1;
42     }
43     res = calc(l);
44     cout << res.first + k*l << endl;
45 }

```

6.2 SOS DP

```

1 // Author: Gino
2 // Function: Solve problems that enumerates subsets of
subsets (3^n => n*2^n)
3 for (int msk = 0; msk < (1<<n); msk++) {
4     for (int i = 1; i <= n; i++) {
5         if (msk & (1<<(i - 1))) {
6             // dp[msk][i] = dp[msk][i - 1] + dp[msk ^ (1<<(i
- 1))][i - 1];
7         } else {
8             // dp[msk][i] = dp[msk][i - 1];
9         }
10    }
11 }

```

6.3 期望 DP (Expected Value DP)

- 狀態設計： $E[s]$ = 從狀態 s 出發到終點的期望值
- 列式子： $E[s] = (\text{當前代價}) + \sum_{s'} P(s \rightarrow s') \cdot E[s']$
- 若存在自環，把 $E[s]$ 移到左邊，整理成 $(1 - P(s \rightarrow s))E[s] = c + \sum_{s' \neq s} P(s \rightarrow s') \cdot E[s']$
- 線性期望技巧：能拆就拆，避免處理整個分布
- 輸出 mod 時，分母要用模逆元： $q^{-1} \equiv q^{M-2} \pmod{M}$ (質數模數)

常見題型

- 擲骰子遊戲 (到達終點的期望步數)
- 隨機遊走 hitting time
- 重複試驗直到成功
- 博弈遊戲的期望值
- 機率 DP：計算到某步時在某狀態的機率

範例：擲骰子到 n 格

$$E[i] = 1 + \frac{1}{6} \sum_{d=1}^6 E[i+d], \quad (i < n), \quad E[n] = 0$$

```

1 int main(){
2     int n;
3     cin >> n; // 終點位置
4
5     // E[i] = 從位置 i 走到終點的期望步數
6     // 因為每次最多走 6，所以要開 n+6 以避免越界
7     vector<double> E(n+7, 0.0);
8
9     // 從終點往前推 (backward DP)
10    for (int i=n-1; i>=0; i--){
11        double sum=0;
12        // 期望公式: E[i] = 1 + (E[i+1]+...+E[i+6]) / 6
13        for (int d=1; d<=6; d++) sum += E[i+d];
14        E[i] = 1 + sum/6.0;
15    }
16
17    // 輸出 E[0]，即從起點到終點的期望擲骰次數
18    cout << fixed << setprecision(10) << E[0] << "\n";
19 }

```

6.4 數位 DP (Digit DP)

- 狀態： $(pos, tight, property)$
 - pos = 當前處理到第幾位
 - $tight$ = 是否受限於上界 N
 - $property$ = 額外屬性 (如數位和、餘數、相鄰限制...)
- 遞迴：枚舉當前位數字，遞迴下一位
- 終止條件： $pos == \text{長度} \Rightarrow$ 回傳屬性是否滿足

- 記憶化： $dp[pos][tight][property]$

常見題型

- 計算 $[0, N]$ 中數位和可被 k 整除的數字個數
- 不含連續相同數字的數字個數
- 含特定數字次數的數字個數
- 位數和 / 餘數 / mod pattern

範例：計算 $[0, N]$ 中數位和 $\bmod k = 0$ 的數字個數

$$dp[pos][tight][sum \bmod k]$$

```

1 string s; // N 轉成字串，方便逐位處理
2 int k; // 除數
3
4 // dp[pos][tight][sum_mod]
5 // pos = 當前處理到哪一位 (0 = 最高位)
6 // tight = 是否仍受限於 N 的數字 (1 = 是, 0 = 否)
7 // sum_mod = 當前數位和 mod k 的值
8 long long dp[20][2][105];
9
10 // 計算：從 pos 開始，tight 狀態下，數位和 mod k = sum_mod 的方案
11 long long dfs(int pos, int tight, int sum_mod){
12     // 終止條件：所有位數都處理完
13     if (pos == (int)s.size())
14         // 若數位和 mod k == 0，算作一個合法數字
15         return (sum_mod % k == 0);
16
17     // 記憶化查詢
18     if (dp[pos][tight][sum_mod] != -1)
19         return dp[pos][tight][sum_mod];
20
21     long long res = 0;
22     // 如果 tight = 1，本位數字上限 = N 的該位數字
23     // 如果 tight = 0，本位數字上限 = 9
24     int limit = tight ? (s[pos] - '0') : 9;
25
26     // 枚舉當前位可以填的數字
27     for (int d=0; d<=limit; d++){
28         // 下一位是否仍然 tight?
29         int next_tight = (tight && d==limit);
30         // 更新數位和 mod k
31         int next_mod = (sum_mod + d) % k;
32         res += dfs(pos+1, next_tight, next_mod);
33     }
34
35     // 存結果
36     dp[pos][tight][sum_mod] = res;
37 }
38
39 int main(){
40     long long N;
41     cin >> N >> k;
42     s = to_string(N); // 把 N 轉成字串，方便取每一位
43     memset(dp, -1, sizeof(dp));
44     cout << dfs(0, 1, 0) << "\n"; // 從最高位開始，初始 tight=1,
sum=0
45 }

```

7 Graph

7.1 Max Clique

```

1 // max N = 64
2 typedef unsigned long long ll;
3 struct MaxClique{
4     ll nb[ N ], n, ans;
5     void init( ll _n ){
6         n = _n;
7         for (int i = 0; i < n; i++) nb[ i ] = 0LLU;
8     }
9     void add_edge( ll _u, ll _v ){
10        nb[ _u ] |= ( 1LLU << _v );
11        nb[ _v ] |= ( 1LLU << _u );
12    }
13    void B( ll r, ll p, ll x, ll cnt, ll res ){
14        if ( cnt + res < ans ) return;
15        if ( p == 0LLU && x == 0LLU ){
16            if ( cnt > ans ) ans = cnt;
17            return;
18        }
19        ll y = p | x; y &= -y;
20        ll q = p & ( ~nb[ int( log2( y ) ) ] );
21        while( q ){
22            ll i = int( log2( q & (-q) ) );
23            B( r | ( 1LLU << i ), p & nb[ i ], x & nb[ i ]
24            , cnt + 1LLU, __builtin_popcountll( p &
nb[ i ] ) );
25            q &= ~( 1LLU << i );

```



```

26     p &= ~( 1LLU << i );
27     x |= ( 1LLU << i );
28 }
29 }
30 int solve(){
31     ans = 0;
32     ll _set = 0;
33     if( n < 64 ) _set = ( 1LLU << n ) - 1;
34     else{
35         for( ll i = 0; i < n; i++ ) _set |= ( 1LLU << i );
36     }
37     B( 0LLU, _set, 0LLU, 0LLU, n );
38     return ans;
39 }
40 } maxClique:

```

7.2 Bellman-Ford + SPFA

```

1 int n, m;
2
3 // Graph
4 vector<vector<pair<int, ll> > > g;
5 vector<ll> dis;
6 vector<bool> negCycle;
7
8 // SPFA
9 vector<int> rlx;
10 queue<int> q;
11 vector<bool> inq;
12 vector<int> pa;
13 void SPFA(vector<int>& src) {
14     dis.assign(n+1, LINF);
15     negCycle.assign(n+1, false);
16     rlx.assign(n+1, 0);
17     while (!q.empty()) q.pop();
18     inq.assign(n+1, false);
19     pa.assign(n+1, -1);
20
21     for (auto& s : src) {
22         dis[s] = 0;
23         q.push(s); inq[s] = true;
24     }
25
26     while (!q.empty()) {
27         int u = q.front();
28         q.pop(); inq[u] = false;
29         if (rlx[u] >= n) {
30             negCycle[u] = true;
31         }
32         else for (auto& e : g[u]) {
33             int v = e.first;
34             ll w = e.second;
35             if (dis[v] > dis[u] + w) {
36                 dis[v] = dis[u] + w;
37                 rlx[v] = rlx[u] + 1;
38                 pa[v] = u;
39                 if (!inq[v]) {
40                     q.push(v);
41                     inq[v] = true;
42                 }
43             }
44         }
45     }
46
47 // Bellman-Ford
48 queue<int> q;
49 vector<int> pa;
50 void BellmanFord(vector<int>& src) {
51     dis.assign(n+1, LINF);
52     negCycle.assign(n+1, false);
53     pa.assign(n+1, -1);
54
55     for (auto& s : src) dis[s] = 0;
56
57     for (int rlx = 1; rlx <= n; rlx++) {
58         for (int u = 1; u <= n; u++) {
59             if (dis[u] == LINF) continue; // Important!!
60             for (auto& e : g[u]) {
61                 int v = e.first; ll w = e.second;
62                 if (dis[v] > dis[u] + w) {
63                     dis[v] = dis[u] + w;
64                     pa[v] = u;
65                     if (rlx == n) negCycle[v] = true;
66                 }
67             }
68         }
69     }
70
71 // Negative Cycle Detection
72 void NegCycleDetect() {
73     /* No Neg Cycle: NO
74     Exist Any Neg Cycle:
75     YES
76     v0 v1 v2 ... vk v0 */

```

```

73
74 vector<int> src;
75 for (int i = 1; i <= n; i++)
76     src.emplace_back(i);
77
78 SPFA(src);
79 // BellmanFord(src);
80
81 int ptr = -1;
82 for (int i = 1; i <= n; i++) if (negCycle[i])
83     { ptr = i; break; }
84
85 if (ptr == -1) { return cout << "NO" << endl, void(); }
86
87 cout << "YES\n";
88 vector<int> ans;
89 vector<bool> vis(n+1, false);
90
91 while (true) {
92     ans.emplace_back(ptr);
93     if (vis[ptr]) break;
94     vis[ptr] = true;
95     ptr = pa[ptr];
96 }
97 reverse(ans.begin(), ans.end());
98
99 vis.assign(n+1, false);
100 for (auto& x : ans) {
101     cout << x << ' ';
102     if (vis[x]) break;
103     vis[x] = true;
104 }
105 cout << endl;
106 }
107
108 // Distance Calculation
109 void calcDis(int s) {
110     vector<int> src;
111     src.emplace_back(s);
112     SPFA(src);
113     // BellmanFord(src);
114
115     while (!q.empty()) q.pop();
116     for (int i = 1; i <= n; i++)
117         if (negCycle[i]) q.push(i);
118
119     while (!q.empty()) {
120         int u = q.front(); q.pop();
121         for (auto& e : g[u]) {
122             int v = e.first;
123             if (!negCycle[v]) {
124                 q.push(v);
125                 negCycle[v] = true;
126             }
127         }
128     }

```

7.3 BCC - AP

```

1 int n, m;
2 int low[maxn], dfn[maxn], instp;
3 vector<int> E, g[maxn];
4 bitset<maxn> isap;
5 bitset<maxn> vis;
6 stack<int> stk;
7 int bccnt;
8 vector<int> bcc[maxn];
9 inline void popout(int u) {
10     bccnt++;
11     bcc[bccnt].emplace_back(u);
12     while (!stk.empty()) {
13         int v = stk.top();
14         if (u == v) break;
15         stk.pop();
16         bcc[bccnt].emplace_back(v);
17     }
18 }
19 void dfs(int u, bool rt = 0) {
20     stk.push(u);
21     low[u] = dfn[u] = ++instp;
22     int kid = 0;
23     Each(e, g[u]) {
24         if (vis[e]) continue;
25         vis[e] = true;
26         int v = E[e]^u;
27         if (!dfn[v]) {
28             // tree edge
29             kid++; dfs(v);
30             low[u] = min(low[u], low[v]);
31             if (!rt && low[v] >= dfn[u]) {
32                 // bcc found: u is ap
33                 isap[u] = true;
34                 popout(u);

```

```

35     }
36   } else {
37     // back edge
38     low[u] = min(low[u], dfn[v]);
39   }
40 }
41 // special case: root
42 if (rt) {
43   if (kid > 1) isap[u] = true;
44   popout(u);
45 }
46 }
47 void init() {
48   cin >> n >> m;
49   fill(low, low+maxn, INF);
50   REP(i, m) {
51     int u, v;
52     cin >> u >> v;
53     g[u].emplace_back(i);
54     g[v].emplace_back(i);
55     E.emplace_back(u^v);
56   }
57 }
58 void solve() {
59   FOR(i, 1, n+1, 1) {
60     if (!dfn[i]) dfs(i, true);
61   }
62   vector<int> ans;
63   int cnt = 0;
64   FOR(i, 1, n+1, 1) {
65     if (isap[i]) cnt++, ans.emplace_back(i);
66   }
67   cout << cnt << endl;
68   Each(i, ans) cout << i << ' ';
69   cout << endl;
70 }

```

7.4 BCC - Bridge

```

1 int n, m;
2 vector<int> g[maxn], E;
3 int low[maxn], dfn[maxn], instp;
4 int bccnt, bccid[maxn];
5 stack<int> stk;
6 bitset<maxn> vis, isbrg;
7 void init() {
8   cin >> n >> m;
9   REP(i, m) {
10     int u, v;
11     cin >> u >> v;
12     E.emplace_back(u^v);
13     g[u].emplace_back(i);
14     g[v].emplace_back(i);
15   }
16   fill(low, low+maxn, INF);
17 }
18 void popout(int u) {
19   bccnt++;
20   while (!stk.empty()) {
21     int v = stk.top();
22     if (v == u) break;
23     stk.pop();
24     bccid[v] = bccnt;
25   }
26 }
27 void dfs(int u) {
28   stk.push(u);
29   low[u] = dfn[u] = ++instp;
30
31   Each(e, g[u]) {
32     if (vis[e]) continue;
33     vis[e] = true;
34
35     int v = E[e]^u;
36     if (dfn[v]) {
37       // back edge
38       low[u] = min(low[u], dfn[v]);
39     } else {
40       // tree edge
41       dfs(v);
42       low[u] = min(low[u], low[v]);
43       if (low[v] == dfn[v]) {
44         isbrg[e] = true;
45         popout(u);
46       }
47     }
48   }
49 }
50 void solve() {
51   FOR(i, 1, n+1, 1) {

```

```

52     if (!dfn[i]) dfs(i);
53   }
54   vector<pii> ans;
55   vis.reset();
56   FOR(u, 1, n+1, 1) {
57     Each(e, g[u]) {
58       if (!isbrg[e] || vis[e]) continue;
59       vis[e] = true;
60       int v = E[e]^u;
61       ans.emplace_back(mp(u, v));
62     }
63   }
64   cout << (int)ans.size() << endl;
65   Each(e, ans) cout << e.F << ' ' << e.S << endl;
66 }

```

7.5 SCC - Tarjan with 2-SAT

```

1 // Author: Ian
2 // 2-sat + tarjan SCC
3 void solve() {
4   int n, r, l; cin >> n >> r >> l;
5   V<P<int>> v(l);
6   for (auto& [a, b] : v)
7     cin >> a >> b;
8   V<V<int>> e(2 * l);
9   for (int i = 0; i < l; i++)
10     for (int j = i + 1; j < l; j++) {
11       if (v[i].first == v[j].first && abs(v[i].second -
12         v[j].second) <= 2 * r) {
13         e[i << 1].emplace_back(j << 1 | 1);
14         e[j << 1].emplace_back(i << 1 | 1);
15       }
16       if (v[i].second == v[j].second && abs(v[i].first -
17         v[j].first) <= 2 * r) {
18         e[i << 1 | 1].emplace_back(j << 1);
19         e[j << 1 | 1].emplace_back(i << 1);
20       }
21     }
22   V<bool> ins(2 * l, false);
23   V<int> scc(2 * l, dfn(2 * l, -1), low(2 * l, inf));
24   stack<int> s;
25   function<void(int)> dfs = [&](int x) {
26     if (!dfn[x]) return;
27     static int t = 0;
28     dfn[x] = low[x] = t++;
29     s.push(x), ins[x] = true;
30     for (auto i : e[x])
31       if (dfs(i), ins[i])
32         low[x] = min(low[x], low[i]);
33     if (dfn[x] == low[x]) {
34       static int ncnt = 0;
35       int p; do {
36         ins[p = s.top()] = false;
37         s.pop(), scc[p] = ncnt;
38       } while (p != x); ncnt++;
39     }
40   };
41   for (int i = 0; i < 2 * l; i++)
42     dfs(i);
43   for (int i = 0; i < l; i++)
44     if (scc[i << 1] == scc[i << 1 | 1]) {
45       cout << "NO" << endl;
46       return;
47     }
48   cout << "YES" << endl;
49 }

```

7.6 Eulerian Path - Undir

```

1 // Author: Gino
2 // Usage: build deg, G first, then eulerian()
3 int n, m; // number of vertices and edges
4 vector<int> deg; // degree
5 vector<set<pii>> G; // G[u] := {(v, edge id)}
6
7 vector<int> path_u, path_e;
8 void dfs(int u) {
9   while (!G[u].empty()) {
10     auto it = G[u].begin();
11     auto [v, i] = *it; G[u].erase(it);
12     G[v].erase(make_pair(u, i)); dfs(v);
13     path_u.emplace_back(v);
14     path_e.emplace_back(i);
15   }
16 }
17 void gogo(int s) {
18   path_u.clear(); path_e.clear();
19   dfs(s); path_u.emplace_back(s);
20   reverse(path_u.begin(), path_u.end());
21   reverse(path_e.begin(), path_e.end());
22 }

```

```

23 bool eulerian() {
24     int oddcnt = 0, s = -1;
25     for (int u = 1; u <= n; u++)
26         if (deg[u] & 1)
27             oddcnt++, s = u;
28
29     if (oddcnt != 0 && oddcnt != 2) return false;
30     if (s == -1) {
31         s = 1; for (int u = 1; u <= n; u++)
32             if (deg[u] > 0)
33                 s = u;
34     }
35     gogo(s);
36
37     for (int u = 1; u <= n; u++)
38         if ((int)G[u].size() > 0)
39             return false;
40     return true;
41 }

```

7.7 Eulerian Path - Dir

```

1 // Author: Gino
2 // Usage: build ind, oud, G first, then eulerian()
3 int n, m; // number of vertices, edges
4 vector<int> ind, oud; // indegree, outdegree
5 vector<vector<pii>> G; // G[u] := {(v, edge id)}
6
7 vector<int> path_u, path_e;
8 void dfs(int u) {
9     while (!G[u].empty()) {
10         auto [v, i] = G[u].back(); G[u].pop_back();
11         dfs(v);
12         path_u.emplace_back(v);
13         path_e.emplace_back(i);
14     }
15 }
16 void gogo(int s) {
17     path_u.clear(); path_e.clear();
18     dfs(s); path_u.emplace_back(s);
19     reverse(path_u.begin(), path_u.end());
20     reverse(path_e.begin(), path_e.end());
21 }
22 bool eulerian() {
23     int s = -1;
24     for (int u = 1; u <= n; u++) {
25         if (abs(oud[u] - ind[u]) > 1) return false;
26         if (oud[u] - ind[u] == 1) {
27             if (s != -1) return false;
28             s = u;
29         }
30     }
31     if (s == -1) {
32         s = 1; for (int u = 1; u <= n; u++)
33             if (ind[u] > 0)
34                 s = u;
35     }
36     gogo(s);
37     for (int u = 1; u <= n; u++)
38         if ((int)G[u].size() > 0)
39             return false;
40
41     return true;
42 }

```

7.8 Kth Shortest Path

```

1 // time: O(|E| lg |E| + |V| lg |V| + K)
2 // memory: O(|E| lg |E| + |V|)
3 struct KSP { // 1-base
4     struct nd {
5         int u, v; ll d;
6         nd(int ui=0, int vi=0, ll di=INF) { u=ui; v=vi; d=di; }
7     };
8     struct heap { nd* edge; int dep; heap* chd[4]; };
9     static int cmp(heap* a, heap* b)
10     { return a->edge->d > b->edge->d; }
11     struct node {
12         int v; ll d; heap* H; nd* E;
13         node() {}
14         node(ll _d, int _v, nd* _E) { d=_d; v=_v; E=_E; }
15         node(heap* _H, ll _d) { H=_H; d=_d; }
16         friend bool operator<(node a, node b)
17         { return a.d > b.d; }
18     };
19     int n, k, s, t, dst[N]; nd *nxt[N];
20     vector<nd*> g[N], rg[N]; heap *nullNd, *head[N];
21     void init(int _n, int _k, int _s, int _t) {
22         n=_n; k=_k; s=_s; t=_t;
23         for (int i=1; i<=n; i++) {
24             g[i].clear(); rg[i].clear();
25             nxt[i]=NULL; head[i]=NULL; dst[i]=-1;

```

```

26     }
27 }
28 void addEdge(int ui, int vi, ll di) {
29     nd* e=new nd(ui, vi, di);
30     g[ui].push_back(e); rg[vi].push_back(e);
31 }
32 queue<int> dfsQ;
33 void dijkstra() {
34     while(dfsQ.size()) dfsQ.pop();
35     priority_queue<node> Q; Q.push(node(0, t, NULL));
36     while (!Q.empty()) {
37         node p=Q.top(); Q.pop(); if (dst[p.v] != -1) continue;
38         dst[p.v]=p.d; nxt[p.v]=p.E; dfsQ.push(p.v);
39         for (auto e: rg[p.v]) Q.push(node(p.d+e->d, e->u, e));
40     }
41 }
42 heap* merge(heap* curNd, heap* newNd) {
43     if (curNd==nullNd) return newNd;
44     heap* root=new heap; memcpy(root, curNd, sizeof(heap));
45     if (newNd->edge->d < curNd->edge->d) {
46         root->edge=newNd->edge;
47         root->chd[2]=newNd->chd[2];
48         root->chd[3]=newNd->chd[3];
49         newNd->edge=curNd->edge;
50         newNd->chd[2]=curNd->chd[2];
51         newNd->chd[3]=curNd->chd[3];
52     }
53     if (root->chd[0]->dep < root->chd[1]->dep)
54         root->chd[0]=merge(root->chd[0], newNd);
55     else root->chd[1]=merge(root->chd[1], newNd);
56     root->dep=max(root->chd[0]->dep,
57                 root->chd[1]->dep)+1;
58     return root;
59 }
60 vector<heap*> V;
61 void build() {
62     nullNd=new heap; nullNd->dep=0; nullNd->edge=new nd;
63     fill(nullNd->chd, nullNd->chd+4, nullNd);
64     while (not dfsQ.empty()) {
65         int u=dfsQ.front(); dfsQ.pop();
66         if (!nxt[u]) head[u]=nullNd;
67         else head[u]=head[nxt[u]->v];
68         V.clear();
69         for (auto&& e: g[u]) {
70             int v=e->v;
71             if (dst[v]==-1) continue;
72             e->d+=dst[v]-dst[u];
73             if (nxt[u]!=e) {
74                 heap* p=new heap; fill(p->chd, p->chd+4, nullNd);
75                 p->dep=1; p->edge=e; V.push_back(p);
76             }
77         }
78         if (V.empty()) continue;
79         make_heap(V.begin(), V.end(), cmp);
80 #define L(X) ((X<<1)+1)
81 #define R(X) ((X<<1)+2)
82         for (size_t i=0; i<V.size(); i++) {
83             if (L(i)<V.size()) V[i]->chd[2]=V[L(i)];
84             else V[i]->chd[2]=nullNd;
85             if (R(i)<V.size()) V[i]->chd[3]=V[R(i)];
86             else V[i]->chd[3]=nullNd;
87         }
88         head[u]=merge(head[u], V.front());
89     }
90 }
91 vector<ll> ans;
92 void first_K() {
93     ans.clear(); priority_queue<node> Q;
94     if (dst[s]==-1) return;
95     ans.push_back(dst[s]);
96     if (head[s]!=nullNd)
97         Q.push(node(head[s], dst[s]+head[s]->edge->d));
98     for (int _=1; _<k and not Q.empty(); _++) {
99         node p=Q.top(); Q.pop(); ans.push_back(p.d);
100         if (head[p.H->edge->v]!=nullNd) {
101             q.H=head[p.H->edge->v]; q.d=p.d+q.H->edge->d;
102             Q.push(q);
103         }
104         for (int i=0; i<4; i++)
105             if (p.H->chd[i]!=nullNd) {
106                 q.H=p.H->chd[i];
107                 q.d=p.d+p.H->edge->d+p.H->chd[i]->edge->d;
108                 Q.push(q);
109             }
110     }
111     void solve() { // ans[i] stores the i-th shortest path
112         dijkstra(); build();
113         first_K(); // ans.size() might less than k

```


114} solver;

7.9 System of Difference Constraints

```
1 vector<vector<pair<int, ll>>> G;
2 void add(int u, int v, ll w) {
3     G[u].emplace_back(make_pair(v, w));
4 }
```

- $x_u - x_v \leq c \Rightarrow \text{add}(v, u, c)$
- $x_u - x_v \geq c \Rightarrow \text{add}(u, v, -c)$
- $x_u - x_v = c \Rightarrow \text{add}(v, u, c), \text{add}(u, v, -c)$
- $x_u \geq c \Rightarrow \text{add super vertex } x_0 = 0, \text{ then } x_u - x_0 \geq c \Rightarrow \text{add}(u, 0, -c)$
- Don't forget non-negative constraints for every variable if specified implicitly.
- Interval sum $\Rightarrow$ Use prefix sum to transform into differential constraints. Don't forget $S_{i+1} - S_i \geq 0$ if x_i needs to be non-negative.
- $\frac{x_u}{x_v} \leq c \Rightarrow \log x_u - \log x_v \leq \log c$

8 String

8.1 Rolling Hash

```
1 const ll C = 27;
2 inline int id(char c) {return c - 'a' + 1;}
3 struct RollingHash {
4     string s; int n; ll mod;
5     vector<ll> Cexp, hs;
6     RollingHash(string& _s, ll _mod):
7         s(_s), n((int)s.size()), mod(_mod)
8     {
9         Cexp.assign(n, 0);
10        hs.assign(n, 0);
11        Cexp[0] = 1;
12        for (int i = 1; i < n; i++) {
13            Cexp[i] = Cexp[i-1] * C;
14            if (Cexp[i] >= mod) Cexp[i] %= mod;
15        }
16        hs[0] = id(s[0]);
17        for (int i = 1; i < n; i++) {
18            hs[i] = hs[i-1] * C + id(s[i]);
19            if (hs[i] >= mod) hs[i] %= mod;
20        }
21        inline ll query(int l, int r) {
22            ll res = hs[r] - (l ? hs[l-1] * Cexp[r-l+1] : 0);
23            res = (res % mod + mod) % mod;
24            return res;
25 };
```

8.2 Trie

```
1 struct node {
2     int c[26]; ll cnt;
3     node(): cnt(0) {memset(c, 0, sizeof(c));}
4     node(ll x): cnt(x) {memset(c, 0, sizeof(c));}
5 };
6 struct Trie {
7     vector<node> t;
8     void init() {
9         t.clear();
10        t.emplace_back(node());
11    }
12    void insert(string s) { int ptr = 0;
13        for (auto& i : s) {
14            if (!t[ptr].c[i - 'a']) {
15                t.emplace_back(node());
16                t[ptr].c[i - 'a'] = (int)t.size() - 1;
17                ptr = t[ptr].c[i - 'a'];
18            }
19            t[ptr].cnt++;
20        }
21    }
22 };
```

8.3 KMP

```
1 int n, m;
2 string s, p;
3 vector<int> f;
4 void build() {
5     f.clear(); f.resize(m, 0);
6     int ptr = 0; for (int i = 1; i < m; i++) {
7         while (ptr && p[i] != p[ptr]) ptr = f[ptr-1];
8         if (p[i] == p[ptr]) ptr++;
9         f[i] = ptr;
10    }
11    void init() {
12        cin >> s >> p;
13        n = (int)s.size();
14        m = (int)p.size();
15        build();
16    }
17    void solve() {
18        int ans = 0, pi = 0;
```

```
18 for (int si = 0; si < n; si++) {
19     while (pi && s[si] != p[pi]) pi = f[pi-1];
20     if (s[si] == p[pi]) pi++;
21     if (pi == m) ans++, pi = f[pi-1];
22 }
23 cout << ans << endl; }
```

8.4 Z Value

```
1 string is, it, s;
2 int n; vector<int> z;
3 void init() {
4     cin >> is >> it;
5     s = it + '0' + is;
6     n = (int)s.size();
7     z.resize(n, 0);
8 }
9 void solve() {
10    int ans = 0; z[0] = n;
11    for (int i = 1, l = 0, r = 0; i < n; i++) {
12        if (i <= r) z[i] = min(z[i-l], r-i+1);
13        while (i+z[i] < n && s[z[i]] == s[i+z[i]]) z[i]++;
14        if (i+z[i]-1 > r) l = i, r = i+z[i]-1;
15        if (z[i] == (int)it.size()) ans++;
16    }
17    cout << ans << endl; }
```

8.5 Manacher

```
1 int n; string S, s;
2 vector<int> m;
3 void manacher() {
4     s.clear(); s.resize(2*n+1, '.');
5     for (int i = 0, j = 1; i < n; i++, j += 2) s[j] = S[i];
6     m.clear(); m.resize(2*n+1, 0);
7     // m[i] := max k such that s[i-k, i+k] is palindrome
8     int mx = 0, mxk = 0;
9     for (int i = 1; i < 2*n+1; i++) {
10        if (mx - (i-mx) >= 0) m[i] = min(m[mx - (i-mx)], mx + mxk - i);
11        while (0 <= i-m[i]-1 && i+m[i]+1 < 2*n+1 &&
12            s[i-m[i]-1] == s[i+m[i]+1]) m[i]++;
13        if (i+m[i] > mx+mxk) mx = i, mxk = m[i];
14    }
15    void init() { cin >> S; n = (int)S.size(); }
16    void solve() {
17        manacher();
18        int mx = 0, ptr = 0;
19        for (int i = 0; i < 2*n+1; i++) if (mx < m[i])
20            { mx = m[i]; ptr = i; }
21        for (int i = ptr-mx; i <= ptr+mx; i++)
22            if (s[i] != '.') cout << s[i];
23    }
24    cout << endl; }
```

8.6 Suffix Array

```
1 #define F first
2 #define S second
3 struct SuffixArray { // don't forget s += "$";
4     int n; string s;
5     vector<int> suf, lcp, rk;
6     vector<int> cnt, pos;
7     vector<pair<pii, int>> buc[2];
8     void init(string _s) {
9         s = _s; n = (int)s.size();
10        // resize(n): suf, rk, cnt, pos, lcp, buc[0-1]
11    }
12    void radix_sort() {
13        for (int t : {0, 1}) {
14            fill(cnt.begin(), cnt.end(), 0);
15            for (auto& i : buc[t]) cnt[(t ? i.F.F : i.F.S) ]++;
16        }
17        for (int i = 0; i < n; i++)
18            pos[i] = (!i ? 0 : pos[i-1] + cnt[i-1]);
19        for (auto& i : buc[t])
20            buc[t][1][pos[ (t ? i.F.F : i.F.S) ]++] = i;
21    }
22    bool fill_suf() {
23        bool end = true;
24        for (int i = 0; i < n; i++) suf[i] = buc[0][i].S;
25        rk[suf[0]] = 0;
26        for (int i = 1; i < n; i++) {
27            int dif = (buc[0][i].F != buc[0][i-1].F);
28            end &= dif;
29            rk[suf[i]] = rk[suf[i-1]] + dif;
30        }
31        return end;
32    }
33    void sa() {
34        for (int i = 0; i < n; i++)
35            buc[0][i] = make_pair(make_pair(s[i], s[i]), i);
36        sort(buc[0].begin(), buc[0].end());
37        if (fill_suf()) return;
38        for (int k = 0; (1<<k) < n; k++) {
39            for (int i = 0; i < n; i++)
40                buc[0][i] = make_pair(make_pair(rk[i], rk[(i
41                    + (1<<k)) % n]), i);
```

```

39     radix_sort();
40     if (fill_suf()) return;
41 }
42 void LCP() { int k = 0;
43     for (int i = 0; i < n-1; i++) {
44         if (rk[i] == 0) continue;
45         int pi = rk[i];
46         int j = suf[pi-1];
47         while (i+k < n && j+k < n && s[i+k] == s[j+k])
48             k++;
49         lcp[pi] = k;
50         k = max(k-1, 0);
51     }
52 }

```

52 SuffixArray suffixarray;

8.7 Suffix Automaton

```

1 // any path start from root forms a substring of S
2 // occurrence of P: iff SAM can run on input word P
3 // number of different substring: ds[1]-1
4 // total length of all different substring: ds[1]
5 // max/min length of state i: mx[i]/mx[mom[i]]+1
6 // assume a run on input word P end at state i:
7 // number of occurrences of P: cnt[i]
8 // first occurrence position of P: fp[i]-|P|+1
9 // all position: !clone nodes in dfs from i through rmom
10 const int MXM=1000010;
11 struct SAM{
12     int tot, root, lst, mom[MXM], mx[MXM]; // ind[MXM]
13     int nxt[MXM][33]; // cnt[MXM], ds[MXM], dsl[MXM], fp[MXM]
14     // bool v[MXM], clone[MXN]
15     int newNode(){
16         int res=++tot; fill(nxt[res],nxt[res]+33,0);
17         mom[res]=mx[res]=0; // cnt=ds=ds1=fp=v=clone=0
18         return res;
19     }
20     void init(){ tot=0; root=newNode(); lst=root; }
21     void push(int c){
22         int p=lst, np=newNode(); // cnt[np]=1, clone[np]=0
23         mx[np]=mx[p]+1; // fp[np]=mx[np]-1
24         for(, p&&nxt[p][c]==0; p=mom[p]) nxt[p][c]=np;
25         if(p==0) mom[np]=root;
26         else{
27             int q=nxt[p][c];
28             if(mx[p]+1==mx[q]) mom[np]=q;
29             else{
30                 int nq=newNode(); // fp[nq]=fp[q], clone[nq]=1
31                 mx[nq]=mx[p]+1;
32                 for(int i=0; i<33; i++) nxt[nq][i]=nxt[q][i];
33                 mom[nq]=mom[q]; mom[q]=nq; mom[np]=nq;
34                 for(, p&&nxt[p][c]==q; p=mom[p]) nxt[p][c]=nq;
35             }
36         }
37         lst=np;
38     }
39     void calc(){
40         calc(root); iota(ind, ind+tot, 1);
41         sort(ind, ind+tot, [&](int i, int j){return mx[i]<mx[j];});
42         for(int i=tot-1; i>=0; i--){
43             cnt[mom[ind[i]]]+=cnt[ind[i]];
44         }
45     }
46     void calc(int x){
47         v[x]=ds[x]=1; dsl[x]=0; // rmom[mom[x]].push_back(x);
48         for(int i=0; i<26; i++){
49             if(nxt[x][i]){
50                 if(!v[nxt[x][i]]) calc(nxt[x][i]);
51                 ds[x]+=ds[nxt[x][i]];
52                 dsl[x]+=dsl[nxt[x][i]]+ds[nxt[x][i]];
53             }
54         }
55     }
56     void push(char *str){
57         for(int i=0; str[i]; i++) push(str[i]-'a');
58     }
59 } sam;

```

8.8 SA-IS

```

1 const int N=300010;
2 struct SA{
3     #define REP(i,n) for(int i=0; i<int(n); i++)
4     #define REPI(i,a,b) for(int i=(a); i<=int(b); i++)
5     bool t[N*2]; int s[N*2], sa[N*2];
6     int c[N*2], x[N], p[N], q[N*2], hei[N], r[N];
7     int operator [](int i){ return _sa[i]; }
8     void build(int *s, int n, int m){
9         memcpy(_s, s, sizeof(int)*n);
10        sais(_s, _sa, p, q, t, c, n, m); mkhei(n);
11    }
12    void mkhei(int n){
13        REP(i,n) r[_sa[i]]=i;
14        hei[0]=0;

```

```

15    REP(i,n) if(r[i]) {
16        int ans=i>0?max(hei[r[i-1]]-1,0):0;
17        while(_s[i+ans]==_s[_sa[r[i]-1]+ans]) ans++;
18        hei[r[i]]=ans;
19    }
20 }
21 void sais(int *s, int *sa, int *p, int *q, bool *t, int *c, int
n, int z){
22     bool uniq=t[n-1]=true, neq;
23     int nn=0, nmz=-1, *nsa=sa+n, *ns=s+n, lst=-1;
24     #define MS0(x,n) memset((x),0,n*sizeof(*(x)))
25     #define MAGIC(XD) MS0(sa,n);\
26     memcpy(x,c,sizeof(int)*z); XD;\
27     memcpy(x+1,c,sizeof(int)*(z-1));\
28     REP(i,n) if(sa[i]&&!t[sa[i]-1]) sa[x[s[sa[i]-1]]++]=sa[i]-1;
29     \
30     memcpy(x,c,sizeof(int)*z);\
31     for(int i=n-1; i>=0; i--) if(sa[i]&&t[sa[i]-1]) sa[--
x[s[sa[i]-1]]]=sa[i]-1;
32     MS0(c,z); REP(i,n) uniq&=+c[s[i]]<2;
33     REP(i,z-1) c[i+1]=c[i];
34     if(uniq) { REP(i,n) sa[--c[s[i]]]=i; return; }
35     for(int i=n-2; i>=0; i--){
36         t[i]=(s[i]==s[i+1])?t[i+1]:s[i]<s[i+1];
37         MAGIC(REPI(i,1,n-1) if(t[i]&&!t[i-1]) sa[--
x[s[i]]]=p[q[i]=nn++]=i);
38         REP(i,n) if(sa[i]&&t[sa[i]]&&t[sa[i]-1]){
39             neq=lst<0||memcmp(sa+sa[i],sa+lst,(p[q[sa[i]]+1]-
sa[i])*sizeof(int));
40             ns[q[lst=sa[i]]]=nmz+=neq;
41         }
42         sais(ns, nsa, p+nn, q+n, t+n, c+z, nn, nmz+1);
43         MAGIC(for(int i=nn-1; i>=0; i--) sa[--
x[s[p[nsa[i]]]]=p[nsa[i]]]);
44     }
45     sa;
46     int H[N], SA[N], RA[N];
47     void suffix_array(int *ip, int len){
48         // should padding a zero in the back
49         // ip is int array, len is array length
50         // ip[0..n-1] != 0, and ip[len]=0
51         ip[len]=0; sa.build(ip, len, 128);
52         memcpy(H, sa, hei+1, len<<2); memcpy(SA, sa, _sa+1, len<<2);
53         for(int i=0; i<len; i++) RA[i]=sa.r[i]-1;
54         // resulting height, sa array \in [0, len)
55     }

```

8.9 Minimum Rotation

```

1 // lexicographically minimal rotation
2 // rotate(begin(s), begin(s)+minRotation(s), end(s))
3 int minRotation(string s) {
4     int a = 0, n = s.size(); s += s;
5     for(int b = 0; b < n; b++) for(int k = 0; k < n; k++) {
6         if(a + k == b || s[a + k] < s[b + k]) {
7             b += max(0, k - 1);
8             break; }
9         if(s[a + k] > s[b + k]) {
10            a = b;
11            break;
12        }
13    }
14    return a; }

```

8.10 Aho Corasick

```

1 struct ACAutomata{
2     struct Node{
3         int cnt;
4         Node *go[26], *fail, *dic;
5         Node(){
6             cnt = 0; fail = 0; dic = 0;
7             memset(go, 0, sizeof(go));
8         }
9     } pool[1048576], *root;
10    int nMem;
11    Node* new_Node(){
12        pool[nMem] = Node();
13        return &pool[nMem++];
14    }
15    void init() { nMem = 0; root = new_Node(); }
16    void add(const string &str) { insert(root, str, 0); }
17    void insert(Node *cur, const string &str, int pos){
18        for(int i=pos; i<str.size(); i++){
19            if(!cur->go[str[i]-'a'])
20                cur->go[str[i]-'a'] = new_Node();
21            cur=cur->go[str[i]-'a'];
22        }
23        cur->cnt++;
24    }
25    void make_fail(){
26        queue<Node*> que;
27        que.push(root);
28        while (!que.empty()){

```

```

29 Node* fr=que.front(); que.pop();
30 for (int i=0; i<26; i++){
31     if (fr->go[i]){
32         Node *ptr = fr->fail;
33         while (ptr && !ptr->go[i]) ptr = ptr->fail;
34         fr->go[i]->fail=ptr=(ptr?ptr->go[i]:root);
35         fr->go[i]->dic=(ptr?cnt[ptr:ptr->dic];
36         que.push(fr->go[i]);
37     } } }
38 }AC;

```

9 Geomtry

9.1 Template

```

1 // Author: Gino
2 typedef long long T;
3 // typedef long double T;
4 const long double eps = 1e-8;
5
6 short sgn(T x) {
7     if (abs(x) < eps) return 0;
8     return x < 0 ? -1 : 1;
9 }
10
11 struct Pt {
12     T x, y;
13     Pt(T _x=0, T _y=0):x(_x), y(_y) {}
14     Pt operator+(Pt a) { return Pt(x+a.x, y+a.y); }
15     Pt operator-(Pt a) { return Pt(x-a.x, y-a.y); }
16     Pt operator*(T a) { return Pt(x*a, y*a); }
17     Pt operator/(T a) { return Pt(x/a, y/a); }
18     T operator*(Pt a) { return x*a.x + y*a.y; }
19     T operator^(Pt a) { return x*a.y - y*a.x; } // 不要打反
20     bool operator<(Pt a)
21     { return x < a.x || (x == a.x && y < a.y); }
22 //return sgn(x-a.x) < 0 || (sgn(x-a.x) == 0 && sgn(y-a.y) < 0); }
23 bool operator==(Pt a)
24 { return sgn(x-a.x) == 0 && sgn(y-a.y) == 0; }
25 };
26
27 Pt mv(Pt a, Pt b) { return b-a; }
28 T len2(Pt a) { return a*a; }
29 T dis2(Pt a, Pt b) { return len2(b-a); }
30
31 short ori(Pt a, Pt b) { return ((a^b)>0) - ((a^b)<0); }
32 bool onseg(Pt p, Pt l1, Pt l2) {
33     Pt a = mv(p, l1), b = mv(p, l2);
34     return ((a^b) == 0) && ((a^b) <= 0);
35 }

```

9.2 Basic Operations

```

1 // Author: Gino
2 // Function: Check if a point P sits in a polygon (doesn't
   have to be convex hull)
3 // 0 = Bound, 1 = In, -1 = Out
4 short inPoly(Pt p) {
5     for (int i = 0; i < n; i++)
6         if (onseg(p, E[i], E[(i+1)%n])) return 0;
7     int cnt = 0;
8     for (int i = 0; i < n; i++)
9         if (banana(p, Pt(p.x+1, p.y+2e9), E[i], E[(i+1)%n]))
10             cnt ^= 1;
11     return (cnt ? 1 : -1);
12 }
13
14 // Author: Gino
15 int ud(Pt a) { // up or down half plane
16     if (a.y > 0) return 0;
17     if (a.y < 0) return 1;
18     return (a.x >= 0 ? 0 : 1);
19 }
20
21 sort(ALL(E), [&](const Pt& a, const Pt& b){
22     if (ud(a) != ud(b)) return ud(a) < ud(b);
23     return (a^b) > 0;
24 });
25
26 // Author: Gino
27 // Function: check if (p1---p2) (q1---q2) banana
28 inline bool banana(Pt p1, Pt p2, Pt q1, Pt q2) {
29     if (onseg(p1, q1, q2) || onseg(p2, q1, q2) ||
30         onseg(q1, p1, p2) || onseg(q2, p1, p2)) {
31         return true;
32     }
33     Pt p = mv(p1, p2), q = mv(q1, q2);
34     return (ori(p, mv(p1, q1)) * ori(p, mv(p1, q2)) < 0 &&
35         ori(q, mv(q1, p1)) * ori(q, mv(q1, p2)) < 0);
36 }
37
38 // Author: Gino
39 // T: long double

```

```

3 Pt bananaPoint(Pt p1, Pt p2, Pt q1, Pt q2) {
4     if (onseg(q1, p1, p2)) return q1;
5     if (onseg(q2, p1, p2)) return q2;
6     if (onseg(p1, q1, q2)) return p1;
7     if (onseg(p2, q1, q2)) return p2;
8     double s = abs(mv(p1, p2) ^ mv(p1, q1));
9     double t = abs(mv(p1, p2) ^ mv(p1, q2));
10    return q2 * (s/(s+t)) + q1 * (t/(s+t));
11 }
12
13 // Author: Gino
14 vector<Pt> hull;
15 void convexHull() {
16     hull.clear(); sort(E.begin(), E.end());
17     for (int t : {0, 1}) {
18         int b = (int)hull.size();
19         for (auto& ei : E) {
20             while ((int)hull.size() - b >= 2 &&
21                 ori(mv(hull[(int)hull.size()-2],
22                     mv(hull[(int)hull.size()-1],
23                         ei)) >= 0))
24                 hull.pop_back();
25             hull.emplace_back(ei);
26         }
27         hull.pop_back();
28         reverse(E.begin(), E.end());
29     }
30 }
31
32 // Author: Gino
33 // Function: Return doubled area of a polygon
34 T dbarea(vector<Pt>& e) {
35     ll res = 0;
36     for (int i = 0; i < (int)e.size(); i++)
37         res += e[i]^e[(i+1)%SZ(e)];
38     return abs(res);
39 }

```

9.3 Lower Concave Hull

```

1 // Author: Unknown
2 struct Line {
3     mutable ll m, b, p;
4     bool operator<(const Line& o) const { return m < o.m; }
5     bool operator<(ll x) const { return p < x; }
6 };
7
8 struct LineContainer : multiset<Line, less<>> {
9     // (for doubles, use inf = 1/.0, div(a,b) = a/b)
10    const ll inf = LLONG_MAX;
11    ll div(ll a, ll b) { // floored division
12        return a / b - ((a ^ b) < 0 && a % b); }
13    bool isect(iterator x, iterator y) {
14        if (y == end()) { x->p = inf; return false; }
15        if (x->m == y->m) x->p = x->b > y->b ? inf : -inf;
16        else x->p = div(y->b - x->b, x->m - y->m);
17        return x->p >= y->p;
18    }
19    void add(ll m, ll b) {
20        auto z = insert({m, b, 0}), y = z++, x = y;
21        while (isect(y, z)) z = erase(z);
22        if (x != begin() && isect(--x, y)) isect(x, y =
23            erase(y));
24        while ((y = x) != begin() && (--x)->p >= y->p)
25            isect(x, erase(y));
26    }
27    ll query(ll x) {
28        assert(!empty());
29        auto l = *lower_bound(x);
30        return l.m * x + l.b;
31    }
32 };

```

9.4 Pick's Theorem

Consider a polygon which vertices are all lattice points.

Let i = number of points inside the polygon.

Let b = number of points on the boundary of the polygon.

Then we have the following formula:

$$\text{Area} = i + \frac{b}{2} - 1$$

9.5 Minimum Enclosing Circle

```

1 // Author: Gino
2 // Function: Find Min Enclosing Circle using Randomized O(n)
   Algorithm
3 Pt circumcenter(Pt A, Pt B, Pt C) {
4     a1(x-A.x) + b1(y-A.y) = c1

```

```

5 // a2(x-A.x) + b2(y-A.y) = c2
6 // solve using Cramer's rule
7 T a1 = B.x-A.x, b1 = B.y-A.y, c1 = dis2(A, B)/2.0;
8 T a2 = C.x-A.x, b2 = C.y-A.y, c2 = dis2(A, C)/2.0;
9 T D = Pt(a1, b1) ^ Pt(a2, b2);
10 T Dx = Pt(c1, b1) ^ Pt(c2, b2);
11 T Dy = Pt(a1, c1) ^ Pt(a2, c2);
12 if (D == 0) return Pt(-INF, -INF);
13 return A + Pt(Dx/D, Dy/D);
14 }
15 Pt center; T r2;
16
17 void minEncloseCircle() {
18 mt19937
19   gen(chrono::steady_clock::now().time_since_epoch().count());
20 shuffle(ALL(E), gen);
21 center = E[0], r2 = 0;
22
23 for (int i = 0; i < n; i++) {
24   if (dis2(center, E[i]) <= r2) continue;
25   center = E[i], r2 = 0;
26   for (int j = 0; j < i; j++) {
27     if (dis2(center, E[j]) <= r2) continue;
28     center = (E[i] + E[j]) / 2.0;
29     r2 = dis2(center, E[i]);
30     for (int k = 0; k < j; k++) {
31       if (dis2(center, E[k]) <= r2) continue;
32       center = circumcenter(E[i], E[j], E[k]);
33       r2 = dis2(center, E[i]);
34     }
35   }
36 }

```

9.6 PolyUnion

```

1 // Author: Unknown
2 struct PY{
3   int n; Pt pt[5]; double area;
4   Pt& operator[](const int x){ return pt[x]; }
5   void init(){ //n,pt[0~n-1] must be filled
6     area=pt[n-1]^pt[0];
7     for(int i=0;i<n-1;i++) area+=pt[i]^pt[i+1];
8     if((area/=2)<0)reverse(pt,pt+n),area=-area;
9   }
10 };
11 PY py[500]; pair<double,int> c[5000];
12 inline double segP(Pt &p,Pt &p1,Pt &p2){
13   if(dcmp(p1.x-p2.x)==0) return (p.y-p1.y)/(p2.y-p1.y);
14   return (p.x-p1.x)/(p2.x-p1.x);
15 }
16 double polyUnion(int n){ //py[0~n-1] must be filled
17   int i,j,ii,jj,ta,tb,r,d; double z,w,s,sum=0,tc,td;
18   for(i=0;i<n;i++) py[i][py[i].n]=py[i][0];
19   for(i=0;i<n;i++){
20     for(ii=0;ii<py[i].n;ii++){
21       r=0;
22       c[r++]=make_pair(0.0,0); c[r++]=make_pair(1.0,0);
23       for(j=0;j<n;j++){
24         if(i==j) continue;
25         for(jj=0;jj<py[j].n;jj++){
26           ta=dcmp(tri(py[i][ii],py[i][ii+1],py[j][jj]));
27           tb=dcmp(tri(py[i][ii],py[i][ii+1],py[j][jj+1]));
28           if(ta==0 && tb==0){
29             if((py[j][jj+1]-py[j][jj])*(py[i][ii+1]-py[i][ii])>0 && j<i){
30               c[r++]=make_pair(segP(py[j][jj],py[i][ii],py[i][ii+1]),1);
31               c[r++]=make_pair(segP(py[j][jj+1],py[i][ii],py[i][ii+1]),-1);
32             }
33             else if(ta>=0 && tb<0){
34               tc=tri(py[j][jj],py[j][jj+1],py[i][ii]);
35               td=tri(py[j][jj],py[j][jj+1],py[i][ii+1]);
36               c[r++]=make_pair(tc/(tc+td),1);
37             }
38             else if(ta<0 && tb>=0){
39               tc=tri(py[j][jj],py[j][jj+1],py[i][ii]);
40               td=tri(py[j][jj],py[j][jj+1],py[i][ii+1]);
41               c[r++]=make_pair(tc/(tc+td),-1);
42             }
43           }
44         }
45       }
46       sort(c,c+r);
47       z=min(max(c[0].first,0.0),1.0); d=c[0].second; s=0;
48       for(j=1;j<r;j++){
49         w=min(max(c[j].first,0.0),1.0);
50         if(!d) s+=w-z;
51         d+=c[j].second; z=w;
52       }
53       sum+=(py[i][ii]^py[i][ii+1])*s;
54     }
55   }
56   return sum/2;
57 }

```

53 }

9.7 Minkowski Sum

```

1 // Author: Unknown
2 /* convex hull Minkowski Sum*/
3 #define INF 10000000000000LL
4 int pos(const Pt& tp){
5   if(tp.Y == 0) return tp.X > 0 ? 0 : 1;
6   return tp.Y > 0 ? 0 : 1;
7 }
8 #define N 300030
9 Pt pt[N], qt[N], rt[N];
10 LL Lx,Rx;
11 int dn,un;
12 inline bool cmp(Pt a, Pt b){
13   int pa=pos(a),pb=pos(b);
14   if(pa==pb) return (a^b)>0;
15   return pa<pb;
16 }
17 int minkowskiSum(int n,int m){
18   int i,j,r,p,q,fi,fj;
19   for(i=1,p=0;i<n;i++){
20     if(pt[i].Y<pt[p].Y ||
21        (pt[i].Y==pt[p].Y && pt[i].X<pt[p].X)) p=i;
22   }
23   for(i=1,q=0;i<m;i++){
24     if(qt[i].Y<qt[q].Y ||
25        (qt[i].Y==qt[q].Y && qt[i].X<qt[q].X)) q=i;
26   }
27   rt[0]=pt[p]+qt[q];
28   r=1; i=p; j=q; fi=fj=0;
29   while(1){
30     if((fj&&j==q) ||
31        (!fi||i!=p) &&
32        cmp(pt[(p+1)%n]-pt[p],qt[(q+1)%m]-qt[q])){
33       rt[r]=rt[r-1]+pt[(p+1)%n]-pt[p];
34       p=(p+1)%n;
35       fi=1;
36     }
37     else{
38       rt[r]=rt[r-1]+qt[(q+1)%m]-qt[q];
39       q=(q+1)%m;
40       fj=1;
41     }
42     if(r<=1 || ((rt[r]-rt[r-1])^(rt[r-1]-rt[r-2]))!=0) r++;
43     else rt[r-1]=rt[r];
44     if(i==p && j==q) break;
45   }
46   return r-1;
47 }
48 void initInConvex(int n){
49   int i,p,q;
50   LL Ly,Ry;
51   Lx=INF; Rx=-INF;
52   for(i=0;i<n;i++){
53     if(pt[i].X<Lx) Lx=pt[i].X;
54     if(pt[i].X>Rx) Rx=pt[i].X;
55   }
56   Ly=Ry=INF;
57   for(i=0;i<n;i++){
58     if(pt[i].X==Lx && pt[i].Y<Ly){ Ly=pt[i].Y; p=i; }
59     if(pt[i].X==Rx && pt[i].Y<Ry){ Ry=pt[i].Y; q=i; }
60   }
61   for(dn=0,i=p;i!=q;i=(i+1)%n){ qt[dn++]=pt[i]; }
62   qt[dn]=pt[q]; Ly=Ry=-INF;
63   for(i=0;i<n;i++){
64     if(pt[i].X==Lx && pt[i].Y>Ly){ Ly=pt[i].Y; p=i; }
65     if(pt[i].X==Rx && pt[i].Y>Ry){ Ry=pt[i].Y; q=i; }
66   }
67   for(un=0,i=p;i!=q;i=(i+1)%n){ rt[un++]=pt[i]; }
68   rt[un]=pt[q];
69 }
70 inline int inConvex(Pt p){
71   int L,R,M;
72   if(p.X<Lx || p.X>Rx) return 0;
73   L=0; R=dn;
74   while(L<R-1){ M=(L+R)/2;
75     if(p.X<rt[M].X) R=M; else L=M; }
76   if(tri(qt[L],qt[R],p)<0) return 0;
77   L=0; R=un;
78   while(L<R-1){ M=(L+R)/2;
79     if(p.X<rt[M].X) R=M; else L=M; }
80   if(tri(rt[L],rt[R],p)>0) return 0;
81   return 1;
82 }
83 int main(){
84   int n,m,i;
85   Pt p;
86   scanf("%d",&n);
87   for(i=0;i<n;i++) scanf("%lld%lld",&pt[i].X,&pt[i].Y);
88   scanf("%d",&m);
89   for(i=0;i<m;i++) scanf("%lld%lld",&qt[i].X,&qt[i].Y);

```

```

87 n=minkowskiSum(n,m);
88 for(i=0;i<n;i++) pt[i]=rt[i];
89 scanf("%d",&m);
90 for(i=0;i<m;i++) scanf("%lld%lld",&qt[i].X,&qt[i].Y);
91 n=minkowskiSum(n,m);
92 for(i=0;i<n;i++) pt[i]=rt[i];
93 initInConvex(n);
94 scanf("%d",&m);
95 for(i=0;i<m;i++){
96     scanf("%lld %lld",&p.X,&p.Y);
97     p.X*=3; p.Y*=3;
98     puts(inConvex(p)?"YES":"NO");
99 }
100 }

```

10 Number Theory

10.1 Prime Sieve and Defactor

```

1 // Author: Gino
2 const int maxc = 1e6 + 1;
3 vector<int> lpf;
4 vector<int> prime;
5
6 void seive() {
7     prime.clear();
8     lpf.resize(maxc, 1);
9     for (int i = 2; i < maxc; i++) {
10         if (lpf[i] == 1) {
11             lpf[i] = i;
12             prime.emplace_back(i);
13         }
14         for (auto& j : prime) {
15             if (i * j >= maxc) break;
16             lpf[i * j] = j;
17             if (j == lpf[i]) break;
18         }
19     }
20     vector<pii> fac;
21     void defactor(int u) {
22         fac.clear();
23         while (u > 1) {
24             int d = lpf[u];
25             fac.emplace_back(make_pair(d, 0));
26             while (u % d == 0) {
27                 u /= d;
28                 fac.back().second++;
29             }
30         }
31     }
32 }

```

10.2 Harmonic Series

```

1 // Author: Gino
2 // O(n log n)
3 for (int i = 1; i <= n; i++) {
4     for (int j = i; j <= n; j += i) {
5         // O(1) code
6     }
7 }
8
9 // PIE
10 // given array a[0], a[1], ..., a[n - 1]
11 // calculate dp[x] = number of pairs (a[i], a[j]) such that
12 // gcd(a[i], a[j]) = x // (i < j)
13 //
14 // idea: let mc(x) = # of y s.t. x|y
15 // f(x) = # of pairs s.t. gcd(a[i], a[j]) >= x
16 // f(x) = C(mc(x), 2)
17 // dp[x] = f(x) - sum(dp[y], x < y and x|y)
18 const int maxc = 1e6;
19 vector<int> cnt(maxc + 1, 0), dp(maxc + 1, 0);
20 for (int i = 0; i < n; i++)
21     cnt[a[i]]++;
22
23 for (int x = maxc; x >= 1; x--) {
24     ll cnt_mul = 0; // number of multiples of x
25     for (int y = x; y <= maxc; y += x)
26         cnt_mul += cnt[y];
27
28     dp[x] = cnt_mul * (cnt_mul - 1) / 2; // number of pairs
29     // that are divisible by x
30     for (int y = x + x; y <= maxc; y += x)
31         dp[x] -= dp[y]; // PIE: subtract all dp[y] for y >
32     // x and x|y
33 }

```

10.3 Count Number of Divisors

```

1 // Author: Gino
2 // Function: Count the number of divisors for all x <= 10^6
3 // using harmonic series
4 const int maxc = 1e6;
5 vector<int> facs;
6
7 void find_all_divisors() {
8     facs.clear(); facs.resize(maxc + 1, 0);
9     for (int x = 1; x <= maxc; x++) {

```

```

9         for (int y = x; y <= maxc; y += x) {
10             facs[y]++;
11         }
12     }
13 }

```

10.4 數論分塊

```

1 // Author: Gino
2 /*
3 n = 17
4 i: 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17
5 n/i: 17 8 5 4 3 2 2 2 1 1 1 1 1 1 1 1 1
6
7             ^      ^
8             L(2)  R(2)
9 L(x) := left bound for n/i = x
10 R(x) := right bound for n/i = x
11
12 ===== FORMULA =====
13 >>> R = n / (n/L) <<<
14 =====
15
16 Example: L(2) = 6
17             R(2) = 17 / (17 / 6)
18                 = 17 / 2
19                 = 8
20 */
21 // ===== CODE =====
22
23 for (ll l = 1, r = 1, q = n; l <= n; l = r + 1) {
24     q = n/l;
25     r = n/q;
26     // Process your code here
27 }
28 // q, l, r: 17 1 1
29 // q, l, r: 8 2 2
30 // q, l, r: 5 3 3
31 // q, l, r: 4 4 4
32 // q, l, r: 3 5 5
33 // q, l, r: 2 6 8
34 // q, l, r: 1 9 17

```

10.5 Pollard's rho

```

1 // Author: Unknown
2 // Function: Find a non-trivial factor of a big number in
3 // O(n^(1/4) log^2(n))
4 ll find_factor(ll number) {
5     __int128 x = 2;
6     for (__int128 cycle = 1; ; cycle++) {
7         __int128 y = x;
8         for (int i = 0; i < (1<<cycle); i++) {
9             x = (x * x + 1) % number;
10            __int128 factor = __gcd(x - y, number);
11            if (factor > 1)
12                return factor;
13        }
14    }
15 }

```

```

1 # Author: Unknown
2 # Function: Find a non-trivial factor of a big number in
3 // O(n^(1/4) log^2(n))
4 from itertools import count
5 from math import gcd
6 from sys import stdin
7
8 for s in stdin:
9     number, x = int(s), 2
10    brk = False
11    for cycle in count(1):
12        y = x
13        if brk:
14            break
15        for i in range(1 << cycle):
16            x = (x * x + 1) % number
17            factor = gcd(x - y, number)
18            if factor > 1:
19                print(factor)
20                brk = True
21                break

```

10.6 Miller Rabin

```

1 // Author: Unknown, Modified by Gino
2 // Function: Check if a number is a prime in O(100 *
3 // log^2(n))
4 // miller_rabin(): return 1 if prime, 0 otherwise
5 inline ll mul(ll x, ll y, ll mod) {
6     return (__int128)(x) * y % mod;
7 }
8
9 ll mypow(ll a, ll b, ll mod) {

```



```

8   ll r = 1;
9   while (b > 0) {
10      if (b & 1) r = mul(r, a, mod);
11      a = mul(a, a, mod);
12      b >>= 1;
13   }
14   return r;
15 }
16 bool witness(ll a, ll n, ll u, int t){
17   ll x = mypow(a, u, n);
18   for(int i = 0; i < t; i++) {
19     ll nx = mul(x, x, n);
20     if (nx == 1 && x != 1 && x != n-1) return true;
21     x = nx;
22   }
23   return x != 1;
24 }
25 bool miller_rabin(ll n) {
26   // if n >= 3,474,749,660,383
27   // change {2, 3, 5, 7, 11, 13} to
28   // {2, 325, 9375, 28178, 450775, 9780504, 1795265022}
29   if (n < 2) return false;
30   if (!(n & 1)) return n == 2;
31   ll u = n - 1; int t = 0;
32   while (!(u & 1)) u >>= 1, t++;
33   for (ll a : {2, 3, 5, 7, 11, 13}) {
34     if (a % n == 0) continue;
35     if (witness(a, n, u, t)) return false;
36   }
37   return true;
38 }
39 // bases that make sure no pseudoprimes flee from test
40 // if WA, replace randll(n - 1) with these bases:
41 // n < 4,759,123,141      3 : 2, 7, 61
42 // n < 1,122,004,669,633 4 : 2, 13, 23, 1662803
43 // n < 3,474,749,660,383 6 : pirms <= 13
44 // n < 2^64              7 :
45 // 2, 325, 9375, 28178, 450775, 9780504, 1795265022

```

10.7 Discrete Log

```

1 // Author: ckiseki
2 // find x^? = y (mod M)
3 // O(sqrt(M))
4 template<typename Int>
5 Int BSGS(Int x, Int y, Int M) {
6   // x^? \equiv y (mod M)
7   Int t = 1, c = 0, g = 1;
8   for (Int M_ = M; M_ > 0; M_ >>= 1) g = g * x % M;
9   for (g = gcd(g, M); t % g != 0; ++c) {
10     if (t == y) return c;
11     t = t * x % M;
12   }
13   if (y % g != 0) return -1;
14   t /= g, y /= g, M /= g;
15   Int h = 0, gs = 1;
16   for (; h * h < M; ++h) gs = gs * x % M;
17   unordered_map<Int, Int> bs;
18   for (Int s = 0; s < h; bs[y] = ++s) y = y * x % M;
19   for (Int s = 0; s < M; s += h) {
20     t = t * gs % M;
21     if (bs.count(t)) return c + s + h - bs[t];
22   }
23   return -1;
24 }

```

10.8 Discrete Sqrt

```

1 // Author: ckiseki
2 // find solution for x^2 = n (mod P)
3 // O(log^2 P)
4 int get_root(int n, int P) { // ensure 0 <= n < p
5   if (P == 2 || n == 0) return n;
6   auto check = [&](lld x) {
7     return modpow(int(x), (P - 1) / 2, P);
8   };
9   if (check(n) != 1) return -1;
10   mt19937 rnd(7122); lld z = 1, w;
11   while (check(w = (z * z - n + P) % P) != P - 1)
12     z = rnd() % P;
13   const auto M = [P, w](auto &u, auto &v) {
14     auto [a, b] = u; auto [c, d] = v;
15     return make_pair((a * c + b * d % P * w) % P,
16                      (a * d + b * c) % P);
17   };
18   pair<lld, lld> r(1, 0), e(z, 1);
19   for (int q = (P + 1) / 2; q >>= 1; e = M(e, e))
20     if (q & 1) r = M(r, e);
21   return int(r.first); // sqrt(n) mod P where P is prime

```

10.9 Fast Power

Note: $a^n \equiv a^{(n \bmod (p-1))} \pmod{p}$

10.10 Extend GCD

```

1 // Author: Gino
2 // [Usage]
3 // bezout(a, b, c):
4 //   find solution to ax + by = c
5 //   return {-LINF, -LINF} if no solution
6 // inv(a, p):
7 //   find modulo inverse of a under p
8 //   return -1 if not exist
9 // CRT(vector<ll>& a, vector<ll>& m)
10 //   find a solution pair (x, mod) satisfies all x = a[i]
11 //   (mod m[i])
12 //   return {-LINF, -LINF} if no solution
13 const ll LINF = 4e18;
14 typedef pair<ll, ll> pll;
15 template<typename T1, typename T2>
16 T1 chmod(T1 a, T2 m) {
17   return (a % m + m) % m;
18 }
19
20 ll GCD;
21 pll extgcd(ll a, ll b) {
22   if (b == 0) {
23     GCD = a;
24     return pll{1, 0};
25   }
26   pll ans = extgcd(b, a % b);
27   return pll{ans.second, ans.first - a/b * ans.second};
28 }
29 pll bezout(ll a, ll b, ll c) {
30   bool negx = (a < 0), negy = (b < 0);
31   pll ans = extgcd(abs(a), abs(b));
32   if (c % GCD != 0) return pll{-LINF, -LINF};
33   return pll{ans.first * c/GCD * (negx ? -1 : 1),
34             ans.second * c/GCD * (negy ? -1 : 1)};
35 }
36 ll inv(ll a, ll p) {
37   if (p == 1) return -1;
38   pll ans = bezout(a % p, -p, 1);
39   if (ans == pll{-LINF, -LINF}) return -1;
40   return chmod(ans.first, p);
41 }
42 pll CRT(vector<ll>& a, vector<ll>& m) {
43   for (int i = 0; i < (int)a.size(); i++)
44     a[i] = chmod(a[i], m[i]);
45
46   ll x = a[0], mod = m[0];
47   for (int i = 1; i < (int)a.size(); i++) {
48     pll sol = bezout(mod, m[i], a[i] - x);
49     if (sol.first == -LINF) return pll{-LINF, -LINF};
50
51     // prevent long long overflow
52     ll p = chmod(sol.first, m[i] / GCD);
53     ll lcm = mod / GCD * m[i];
54     x = chmod((__int128)p * mod + x, lcm);
55     mod = lcm;
56   }
57   return pll{x, mod};
58 }

```

10.11 Mu + Phi

```

1 // Author: Gino
2 const int maxn = 1e6 + 5;
3 ll f[maxn];
4 vector<int> lpf, prime;
5 void build() {
6   lpf.clear(); lpf.resize(maxn, 1);
7   prime.clear();
8   f[1] = ...; /* mu[1] = 1, phi[1] = 1 */
9   for (int i = 2; i < maxn; i++) {
10     if (lpf[i] == 1) {
11       lpf[i] = i; prime.emplace_back(i);
12       f[i] = ...; /* mu[i] = 1, phi[i] = i-1 */
13     }
14     for (auto& j : prime) {
15       if (i*j >= maxn) break;
16       lpf[i*j] = j;
17       if (i % j == 0) f[i*j] = ...; /* 0, phi[i]*j */
18       else f[i*j] = ...; /* -mu[i], phi[i]*phi[j] */
19       if (j >= lpf[i]) break;
20     }
21   }
22 }

```

10.12 Other Formulas

- Pisano Period: 任何線性遞迴 (比如費氏數列) 模任何一個數字 M 都會循環, 找循環節 $\pi(M)$ 先質因數分解 $M = \prod p_i^{e_i}$, 然後 $\pi(M) = \text{lcm}(\pi(p_i^{e_i}))$,

- Inversion:
 $aa^{-1} \equiv 1 \pmod{m}$. a^{-1} exists iff $\gcd(a, m) = 1$.
- Linear inversion:
 $a^{-1} \equiv (m - \lfloor \frac{m}{a} \rfloor) \times (m \bmod a)^{-1} \pmod{m}$
- Fermat's little theorem:
 $a^p \equiv a \pmod{p}$ if p is prime.
- Euler function:
 $\varphi(n) = n \prod_{p|n} \frac{p-1}{p}$
- Euler theorem:
 $a^{\varphi(n)} \equiv 1 \pmod{n}$ if $\gcd(a, n) = 1$. If a, n are not coprime: 質因數分解 $n = \prod p_i^{e_i}$, 對每個 $p_i^{e_i}$ 分開看他們跟 a 是否互質 (互質: Fermat / 不互質: 夠大的指數會直接削成 0), 最後用 CRT 合併.
- Extended Euclidean algorithm:
 $ax + by = \gcd(a, b) = \gcd(b, a \bmod b) = \gcd(b, a - \lfloor \frac{a}{b} \rfloor b) = bx_1 + (a - \lfloor \frac{a}{b} \rfloor b)y_1 = ay_1 + b(x_1 - \lfloor \frac{a}{b} \rfloor y_1)$
- Divisor function:
 $\sigma_x(n) = \sum_{d|n} d^x \cdot n = \prod_{i=1}^r p_i^{a_i}$.
 $\sigma_x(n) = \prod_{i=1}^r \frac{p_i^{(a_i+1)x} - 1}{p_i^x - 1}$ if $x \neq 0$. $\sigma_0(n) = \prod_{i=1}^r (a_i + 1)$.
- Chinese remainder theorem (Coprime Moduli):
 $x \equiv a_i \pmod{m_i}$.
 $M = \prod m_i$. $M_i = \frac{M}{m_i}$. $t_i = M_i^{-1}$.
 $x = kM + \sum a_i t_i M_i$, $k \in \mathbb{Z}$.
- Chinese remainder theorem:
 $x \equiv a_1 \pmod{m_1}, x \equiv a_2 \pmod{m_2} \Rightarrow x = m_1 p + a_1 = m_2 q + a_2 \Rightarrow m_1 p - m_2 q = a_2 - a_1$
Solve for (p, q) using ExtGCD.
 $x \equiv m_1 p + a_1 \equiv m_2 q + a_2 \pmod{\text{lcm}(m_1, m_2)}$
- Avoiding Overflow: $ca \bmod cb = c(a \bmod b)$
- Dirichlet Convolution: $(f * g)(n) = \sum_{d|n} f(d)g(\frac{n}{d})$
- Important Multiplicative Functions + Properties:
 1. $\varepsilon(n) = [n = 1]$
 2. $1(n) = 1$
 3. $id(n) = n$
 4. $\mu(n) = 0$ if n has squared prime factor
 5. $\mu(n) = (-1)^k$ if $n = p_1 p_2 \dots p_k$
 6. $\varepsilon = \mu * 1$
 7. $\varphi = \mu * id$
 8. $[n = 1] = \sum_{d|n} \mu(d)$
 9. $[gcd = 1] = \sum_{d|gcd} \mu(d)$
- Möbius inversion: $f = g * 1 \Leftrightarrow g = f * \mu$

10.13 Polynomial

```

1 // Author: Gino
2 // Preparation: first set_mod(mod, g), then init_ntt()
3 // everytime you change the mod, you have to call init_ntt()
  again
4 //
5 // [Usage]
6 // polynomial: vector<ll> a, b
7 // negation: -a
8 // add/subtract: a += b, a -= b
9 // convolution: a *= b
10 // in-place modulo: mod(a, b)
11 // in-place inversion under mod x^N: inv(ia, N)
12
13
14 const int maxk = 20;
15 const int maxn = 1<<maxk;
16
17 using u64 = unsigned long long;
18 using u128 = __uint128_t;
19
20 int g;
21 u64 MOD;
22 u64 BARRETT_IM; // [ 2^64 / MOD ]
23
24 inline void set_mod(u64 m, int _g) {
25     g = _g;
26     MOD = m;
27     BARRETT_IM = (u128(1) << 64) / m;
28 }
29 inline u64 chmod(u128 x) {
30     u64 q = (u64)((x * BARRETT_IM) >> 64);
31     u64 r = (u64)(x - (u128)q * MOD);
32     if (r >= MOD) r -= MOD;
33     return r;
34 }
35 inline u64 mmul(u64 a, u64 b) {
36     return chmod((u128)a * b);

```

```

37 }
38 ll pw(ll a, ll n) {
39     ll ret = 1;
40     while (n > 0) {
41         if (n & 1) ret = mmul(ret, a);
42         a = mmul(a, a);
43         n >>= 1;
44     }
45     return ret;
46 }
47
48 vector<ll> X, iX;
49 vector<int> rev;
50 void init_ntt() {
51     X.assign(maxn, 1); // x1 = g^((p-1)/n)
52     iX.assign(maxn, 1);
53
54     ll u = pw(g, (MOD-1)/maxn);
55     ll iu = pw(u, MOD-2);
56     for (int i = 1; i < maxn; i++) {
57         X[i] = mmul(X[i-1], u);
58         iX[i] = mmul(iX[i-1], iu);
59     }
60
61     if ((int)rev.size() == maxn) return;
62     rev.assign(maxn, 0);
63     for (int i = 1, hb = -1; i < maxn; i++) {
64         if (!(i & (i-1))) hb++;
65         rev[i] = rev[i ^ (1<<hb)] | (1<<(maxk-hb-1));
66     }
67
68 template<typename T>
69 void NTT(vector<T>& a, bool inv=false) {
70     int _n = (int)a.size();
71     int k = __lg(_n) + ((1<<__lg(_n)) != _n);
72     int n = 1<<k;
73     a.resize(n, 0);
74
75     short shift = maxk-k;
76     for (int i = 0; i < n; i++)
77         if (i > (rev[i]>>shift))
78             swap(a[i], a[rev[i]>>shift]);
79     for (int len = 2, half = 1, div = maxn>>1; len <= n;
80         len<<=1, half<<=1, div>>=1) {
81         for (int i = 0; i < n; i += len) {
82             for (int j = 0; j < half; j++) {
83                 T u = a[i+j];
84                 T v = mmul(a[i+j+half], (inv ? iX[j*div] :
85                     X[j*div]));
86                 a[i+j] = (u+v >= MOD ? u+v-MOD : u+v);
87                 a[i+j+half] = (u-v < 0 ? u-v+MOD : u-v);
88             }
89         }
90     }
91
92     if (inv) {
93         T dn = pw(n, MOD-2);
94         for (auto& x : a) {
95             x = mmul(x, dn);
96         }
97     }
98
99 template<typename T>
100 inline void shrink(vector<T>& a) {
101     int cnt = (int)a.size();
102     for (; cnt > 0; cnt--) if (a[cnt-1]) break;
103     a.resize(max(cnt, 1));
104 }
105
106 template<typename T>
107 vector<T>& operator*=(vector<T>& a, vector<T> b) {
108     int na = (int)a.size();
109     int nb = (int)b.size();
110     a.resize(na + nb - 1, 0);
111     b.resize(na + nb - 1, 0);
112
113     NTT(a); NTT(b);
114     for (int i = 0; i < (int)a.size(); i++)
115         a[i] = mmul(a[i], b[i]);
116     NTT(a, true);
117
118     shrink(a);
119     return a;
120 }
121
122 inline ll crt(ll a0, ll a1, ll m1, ll m2, ll inv_m1_mod_m2) {
123     // x ≡ a0 (mod m1), x ≡ a1 (mod m2)
124     // t = (a1 - a0) * inv(m1) mod m2
125     // x = a0 + t * m1 (mod m1*m2)
126     ll t = chmod(a1 - a0);
127     if (t < 0) t += m2;
128     t = (ll)((__int128)t * inv_m1_mod_m2 % m2);
129     return a0 + (ll)((__int128)t * m1);
130 }
131
132 void mul_crt() {
133     // a copy to a1, a2 | b copy to b1, b2
134     ll M1 = 998244353, M2 = 1004535809;

```

```

124 g = 3; set_mod(M1); init_ntt(); a1 *= b1;
125 g = 3; set_mod(M2); init_ntt(); a2 *= b2;
126
127 ll inv_m1_mod_m2 = pw(M1, M2 - 2);
128 for (int i = 2; i <= 2 * k; i++)
129     cout << crt(a1[i], a2[i], M1, M2, inv_m1_mod_m2) <<
130     '\n';
131 cout << endl;
132 }
133 /* P = r*2^k + 1
134 P          r    k    g
135 998244353    119 23    3
136 1004535809    479 21    3
137
138 P          r    k    g
139 3           1    1    2
140 5           1    2    2
141 17          1    4    3
142 97          3    5    5
143 193         3    6    5
144 257         1    8    3
145 7681        15    9   17
146 12289       3   12   11
147 40961       5   13    3
148 65537       1   16    3
149 786433      3   18   10
150 5767169     11   19    3
151 7340033     7   20    3
152 23068673    11  21    3
153 104857601   25  22    3
154 167772161   5   25    3
155 469762049   7   26    3
156 1004535809  479 21    3
157 2013265921  15  27   31
158 2281701377  17  27    3
159 3221225473  3   30    5
160 75161927681 35  31    3
161 77309411329 9   33    7
162 206158430209 3   36  22
163 2061584302081 15  37    7
164 2748779069441 5   39    3
165 6597069766657 3   41    5
166 3958241859937 9   42    5
167 79164837199873 9   43    5
168 263882790666241 15  44    7
169 1231453023109121 35  45    3
170 1337006139375617 19  46    3
171 3799912185593857 27  47    5
172 4222124650659841 15  48   19
173 7881299347898369 7   50    6
174 31525197391593473 7   52    3
175 180143985094819841 5   55    6
176 1945555039024054273 27  56    5
177 4179340454199820289 29  57    3
178 9097271247288401921 505 54, 6 */

```

10.14 Counting Primes

```

1 // prime_count - #primes in [1..n] (O(n^{2/3}) time,
2 // O(sqrt(n)) memory)
3 using u64 = unsigned long long;
4 static inline u64 prime_count(u64 n){
5     if(n<=1) return 0;
6     int v = (int)floor(sqrt((long double)n));
7     int s = (v+1)>>1, pc = 0;
8     vector<int> smalls(s), roughs(s), skip(v+1);
9     vector<long long> larges(s);
10
11     for(int i=0;i<s;++i){
12         smalls[i]=i;
13         roughs[i]=2*i+1;
14         larges[i]=(long long)((n/roughs[i]-1)>>1);
15     }
16
17     for(int p=3;p<=v;p+=2) if(!skip[p]){
18         int q = p*p;
19         if(1LL*q*q > (long long)n) break;
20         skip[p]=1;
21         for(int i=q;i<=v;i+=2*p) skip[i]=1;
22
23         int ns=0;
24         for(int k=0;k<s;++k){
25             int i = roughs[k];
26             if(skip[i]) continue;
27             u64 d = (u64)i * (u64)p;
28             long long sub = (d <= (u64)v)
29                 ? larges[smalls[(int)(d>>1)] - pc]
30                 : smalls[(int)((n/d - 1) >> 1)];

```

```

31         larges[ns] = larges[k] - sub + pc;
32         roughs[ns++] = i;
33     }
34     s = ns;
35     for(int i=(v-1)>>1, j=((v/p)-1)|1; j>=p; j-=2){
36         int c = smalls[j>>1] - pc;
37         for(int e=(j*p)>>1; i>=e; --i) smalls[i] -= c;
38     }
39     ++pc;
40 }
41
42 larges[0] += 1LL*(s + 2*(pc-1))*(s-1) >> 1;
43 for(int k=1;k<s;++k) larges[0] -= larges[k];
44
45 for(int l=1;l<s;++l){
46     int q = roughs[l];
47     u64 m = n / (u64)q;
48     long long t = 0;
49     int e = smalls[(int)((m/q - 1) >> 1)] - pc;
50     if(e < l+1) break;
51     for(int k=l+1;k<=e;++k) t += smalls[(int)((m/
52         (u64)roughs[k] - 1) >> 1)];
53     larges[0] += t - 1LL*(e - l)*(pc + l - 1);
54 }
55 return (u64)(larges[0] + 1);

```

10.15 Linear Sieve for Other Number Theoretic Functions

```

1 // linear_sieve(n, primes, lp, phi, mu, d, sigma)
2 // Outputs over the index range 0..n (n >= 1):
3 // primes : all primes in [2..n], increasing.
4 // lp      : lowest prime factor; lp[1]=0, lp[x] is the
5 //           smallest prime dividing x.
6 // phi     : Euler totient, phi[x] = |{1<=k<=x :
7 //           gcd(k,x)=1}|. Multiplicative.
8 // mu      : Möbius; mu[1]=1, mu[x]=0 if x has a squared
9 //           prime factor, else (-1)^{#distinct primes}.
10 // d       : number of divisors; if x=∏ p_i^{e_i}, then
11 //           d[x]=∏(e_i+1). Multiplicative.
12 // sigma   : sum of divisors; if x=∏ p_i^{e_i}, then
13 //           sigma[x]=∏(1+p_i+...+p_i^{e_i}). (use 1LL)
14 // Complexity: O(n) time, O(n) memory.
15 // Notes: Arrays are resized inside; primes is cleared and
16 //         reserved. sigma uses ll to avoid 32-bit overflow.
17
18 static inline void linear_sieve(
19     int n,
20     std::vector<int> &primes,
21     std::vector<int> &lp,
22     std::vector<int> &phi,
23     std::vector<int> &mu,
24     std::vector<int> &d,
25     std::vector<ll> &sigma
26 ) {
27     lp.assign(n + 1, 0); phi.assign(n + 1, 0); mu.assign(n +
28     1, 0); d.assign(n + 1, 0); sigma.assign(n + 1, 0);
29     primes.clear(); primes.reserve(n > 1 ? n / 10 : 0);
30     std::vector<int> cnt(n + 1, 0), core(n + 1, 1);
31     std::vector<ll> p_pow(n + 1, 1), sum_p(n + 1, 1);
32     phi[1] = mu[1] = d[1] = sigma[1] = 1;
33
34     for (int i = 2; i <= n; ++i) {
35         if (!lp[i]) {
36             lp[i] = i; primes.push_back(i);
37             phi[i] = i - 1; mu[i] = -1; d[i] = 2;
38             cnt[i] = 1; p_pow[i] = i; core[i] = 1;
39             sum_p[i] = 1 + (ll)i; sigma[i] = sum_p[i];
40         }
41         for (int p : primes) {
42             long long ip = 1LL * i * p;
43             if (ip > n) break;
44             lp[ip] = p;
45             if (p == lp[i]) {
46                 cnt[ip] = cnt[i] + 1; p_pow[ip] = p_pow[i] * p;
47                 core[ip] = core[i];
48                 sum_p[ip] = sum_p[i] + p_pow[ip];
49                 phi[ip] = phi[i] * p; mu[ip] = 0;
50                 d[ip] = d[core[ip]] * (cnt[ip] + 1);
51                 sigma[ip] = sigma[core[ip]] * sum_p[ip];
52                 break; // critical for linear complexity
53             } else {
54                 cnt[ip] = 1; p_pow[ip] = p; core[ip] = i;
55                 sum_p[ip] = 1 + (ll)p;
56                 phi[ip] = phi[i] * (p - 1); mu[ip] = -mu[i];
57                 d[ip] = d[i] * 2;
58                 sigma[ip] = sigma[i] * sum_p[ip];
59             }
60         }
61     }
62 }

```

```

54 }
55 }
56 // Optional helper: factorize x in O(log x) using lp
57 (requires x in [2..n])
58 static inline std::vector<std::pair<int,int>> factorize(int
59 x, const std::vector<int>& lp) {
60     std::vector<std::pair<int,int>> res;
61     while (x > 1) {
62         int p = lp[x], e = 0;
63         do { x /= p; ++e; } while (x % p == 0);
64         res.push_back({p, e});
65     }
66     return res;

```

11 Linear Algebra

11.1 Gaussian-Jordan Elimination

```

1 int n; vector<vector<ll>> > v;
2 void gauss(vector<vector<ll>>& v) {
3     int r = 0;
4     for (int i = 0; i < n; i++) {
5         bool ok = false;
6         for (int j = r; j < n; j++) {
7             if (v[j][i] == 0) continue;
8             swap(v[j], v[r]);
9             ok = true; break;
10        }
11        if (!ok) continue;
12        ll div = inv(v[r][i]);
13        for (int j = 0; j < n+1; j++) {
14            v[r][j] *= div;
15            if (v[r][j] >= MOD) v[r][j] %= MOD;
16        }
17        for (int j = 0; j < n; j++) {
18            if (j == r) continue;
19            ll t = v[j][i];
20            for (int k = 0; k < n+1; k++) {
21                v[j][k] -= v[r][k] * t % MOD;
22                if (v[j][k] < 0) v[j][k] += MOD;
23            }
24            r++;
25        }

```

11.2 Determinant

1. Use GJ Elimination, if there's any row consists of only 0, then $\det = 0$, otherwise $\det = \text{product of diagonal elements}$.
2. Properties of $\det$:
 - Transpose: Unchanged
 - Row Operation 1 - Swap 2 rows: $-\det$
 - Row Operation 2 - $k\vec{r}_i$: $k \times \det$
 - Row Operation 3 - $k\vec{r}_i$ add to $\vec{r}_j$: Unchanged

12 Matching

12.1 Bipartite Matching

```

1 // Author: Gino
2 // Function: Max Bipartite Matching in O(V sqrt(E))
3 // Usage:
4 // >>> init(nx, ny) -> add(x, y (+nx))
5 // >>> hk.max_matching() := the matching plan stores in mx,
6 // my
7 // >>> hk.min_vertex_cover() := the vertex cover plan stores
8 // in vcover
9 // (!) vertices are 0-based: X = [0, nx), Y = [nx, nx+ny)
10 #define pb emplace_back
11 struct HopcroftKarp {
12     int n, nx, ny;
13     vector<vector<int>> > G;
14     vector<int> mx, my;
15     void init(int _nx, int _ny) {
16         nx = _nx, ny = _ny;
17         n = nx + ny;
18         G.assign(n, vector<int>());
19     }
20     void add(int x, int y) { G[x].pb(y); G[y].pb(x); }
21     int max_matching() {
22         vector<int> dis, vis;
23         mx.assign(n, -1); my.assign(n, -1);
24         function<bool(int)> dfs = [&](int x) {
25             vis[x] = 1;
26             for (int y : G[x]) {
27                 int p = my[y];
28                 if (p == -1 || (dis[p] == dis[x] + 1 && !vis[p] &&
29                     dfs(p)))
30                     return mx[x] = y, my[y] = x, true;
31             }
32             return false;
33         };

```

```

31 while (true) {
32     dis.assign(n, -1);
33     queue<int> q;
34     for (int x = 0; x < nx; x++)
35         if (mx[x] == -1) dis[x] = 0, q.push(x);
36     while (!q.empty()) {
37         int x = q.front(); q.pop();
38         for (int y : G[x])
39             if (my[y] != -1 && dis[my[y]] == -1)
40                 dis[my[y]] = dis[x] + 1, q.push(my[y]);
41     }
42     vis.assign(n, 0);
43     bool found = false;
44     for (int x = 0; x < nx; x++)
45         if (mx[x] == -1 && dfs(x)) found = true;
46     if (!found) break;
47 }
48 int ans = 0;
49 for (int x = 0; x < nx; x++) if (mx[x] != -1) ans++;
50 return ans;
51 }
52 vector<int> vcover;
53 int min_vertex_cover() {
54     int ans = max_matching();
55     vector<int> vis(n, 0);
56     function<void(int)> dfs = [&](int x) {
57         vis[x] = true;
58         for (int y : G[x]) {
59             if (y == mx[x] || my[y] == -1 || vis[y]) continue;
60             vis[y] = true;
61             dfs(my[y]);
62         }
63     };
64     for (int x = 0; x < nx; x++) if (mx[x] == -1) dfs(x);
65     vcover.clear();
66     for (int x = 0; x < nx; x++) if (!vis[x]) vcover.pb(x);
67     for (int y = nx; y < nx + ny; y++) if (vis[y])
68         vcover.pb(y);
69     return ans;
70 } hk;

```

12.2 Bipartite Weighted Matching

```

1 // Author: ckiseki
2 // n = #(left vertices) = #(right vertices)
3 // left, right vertices labeled 1 ~ n separately
4 // 1. build 1-based matrix G of size (n + 1) * (n + 1)
5 // G[u][v] := weight between (left u, right v)
6 // <!=> if not need perfect matching => set weights of all
7 // negative edges to 0
8 // 2. constrcut (solve at same time): KM km(n, G);
9 // => km.ans (max perfect weight sum)
10 // => km.fl[u] (left u -> right v)
11 // => km.fr[v] (right v -> left u)
12 // Time: O(V^3), Space: O(V^2)
13 // Test: V <= 500, 243ms
14 struct KM { // maximize, test @ UOJ 80
15     int n, l, r; ll ans; // fl and fr are the match
16     vector<ll> hl, hr; vector<int> fl, fr, pre, q;
17     void bfs(const auto &w, int s) {
18         vector<int> vl(n + 1), vr(n + 1); vector<ll> slk(n + 1,
19             LINF);
20         l = r = 0; vr[q[r++] = s] = true;
21         auto check = [&](int x) -> bool {
22             if (vl[x] || slk[x] > 0) return true;
23             vl[x] = true; slk[x] = LINF;
24             if (fl[x] != -1) return (vr[q[r++] = fl[x]] = true);
25             while (x != -1) swap(x, fr[fl[x] = pre[x]]);
26             return false;
27         };
28         while (true) {
29             while (l < r)
30                 for (int x = l, y = q[l++]; x <= n; ++x) if (!vl[x])
31                     if (ll val = hl[x] + hr[y] - w[x][y], val <
32                         slk[x]) {
33                         slk[x] = val;
34                         if (pre[x] = y, !check(x)) return;
35                     }
36             ll d = LINF;
37             for (int x = 1; x <= n; ++x) d = min(d, slk[x]);
38             for (int x = 1; x <= n; ++x)
39                 vl[x] ? hl[x] += d : slk[x] -= d;
40             for (int x = 1; x <= n; ++x) if (vr[x]) hr[x] -= d;
41             for (int x = 1; x <= n; ++x) if (!check(x)) return;
42         }
43         KM(int n_, const auto &w) : n(n_), ans(0),
44             hl(n + 1), hr(n + 1), fl(n + 1, -1), fr(fl), pre(n + 1),
45             q(n + 1) {
46             for (int i = 1; i <= n; ++i) {

```



```

44     hl[i] = -LINF;
45     for (int j = 1; j <= n; ++j) hl[i] = max(hl[i],
46         (ll)w[i][j]);
47     for (int i = 1; i <= n; ++i) bfs(w, i);
48     for (int i = 1; i <= n; ++i) ans += w[i][fl[i]];
49 }
50 }

```

12.3 General Matching

```

1// Author: ckiseki
2// 0. build 1-based graph vector<vector<int>> G(n + 1);
3// 1. construct (solve at same time):
4//     GeneralMatching M(G, n); => M.ans
5// status: M.match[x] (== -1 if not matched, 1 <= x <= n)
6// Time: O(V^3), Space: O(V + E)
7// Test: V <= 500, lms
8struct GeneralMatching {
9    queue<int> q; int ans, n;
10    vector<int> fa, s, v, pre, match;
11    int Find(int u) {
12        return u == fa[u] ? u : fa[u] = Find(fa[u]);
13    }
14    int LCA(int x, int y) {
15        static int tk = 0; tk++; x = Find(x); y = Find(y);
16        for (; swap(x, y) if (x != 0) {
17            if (v[x] == tk) return x;
18            v[x] = tk;
19            x = Find(pre[match[x]]);
20        }
21    }
22    void Blossom(int x, int y, int l) {
23        for (; Find(x) != l; x = pre[y]) {
24            pre[x] = y, y = match[x];
25            if (s[y] == 1) q.push(y), s[y] = 0;
26            for (int z : {x, y}) if (fa[z] == z) fa[z] = l;
27        }
28    }
29    bool Bfs(auto &&g, int r) {
30        iota(all(fa), 0); ranges::fill(s, -1);
31        q = queue<int>(); q.push(r); s[r] = 0;
32        for (; !q.empty(); q.pop()) {
33            for (int x = q.front(); int u : g[x])
34                if (s[u] == -1) {
35                    if (pre[u] == x, s[u] = 1, match[u] == 0) {
36                        for (int a = u, b = x, last;
37                            b != 0; a = last, b = pre[a])
38                            last = match[b], match[b] = a, match[a] = b;
39                        return true;
40                    }
41                    q.push(match[u]); s[match[u]] = 0;
42                } else if (!s[u] && Find(u) != Find(x)) {
43                    int l = LCA(u, x);
44                    Blossom(x, u, l); Blossom(u, x, l);
45                }
46            }
47        return false;
48    }
49    GeneralMatching(auto &&g, int n_) : ans(0), n(n_),
50        fa(n + 1), s(n + 1), v(n + 1), pre(n + 1, 0), match(n + 1,
51        0) {
52        for (int x = 1; x <= n; ++x)
53            if (match[x] == 0) ans += Bfs(g, x);
54        for (int x = 1; x <= n; ++x)
55            if (match[x] == 0) match[x] = -1;
56    }
57 } // tested @ vosupo judge

```

```

21 int ED(edge e) {
22     return lab[e.u] + lab[e.v] - g[e.u][e.v].w * 2;
23 }
24 void update_slack(int u, int x, int &s) {
25     if (!s || ED(g[u][x]) < ED(g[s][x])) s = u;
26 }
27 void set_slack(int x) {
28     slack[x] = 0;
29     REP(u, 1, n)
30         if (g[u][x].w > 0 && st[u] != x && S[st[u]] == 0)
31             update_slack(u, x, slack[x]);
32 }
33 void q_push(int x) {
34     if (x <= n) q.push(x);
35     else for (int y : flo[x]) q.push(y);
36 }
37 void set_st(int x, int b) {
38     st[x] = b;
39     if (x > n) for (int y : flo[x]) set_st(y, b);
40 }
41 vector<int> split_flo(auto &f, int xr) {
42     auto it = find(all(f), xr);
43     if (auto pr = it - f.begin(); pr % 2 == 1)
44         reverse(1 + all(f), it = f.end() - pr);
45     auto res = vector(f.begin(), it);
46     return f.erase(f.begin(), it), res;
47 }
48 void set_match(int u, int v) {
49     match[u] = g[u][v].v;
50     if (u <= n) return;
51     int xr = flo_from[u][g[u][v].u];
52     auto &f = flo[u], z = split_flo(f, xr);
53     REP(i, 0, int(z.size()) - 1) set_match(z[i], z[i ^ 1]);
54     set_match(xr, v); f.insert(f.end(), all(z));
55 }
56 void augment(int u, int v) {
57     for (;;) {
58         int xnv = st[match[u]]; set_match(u, v);
59         if (!xnv) return;
60         set_match(v = xnv, u = st[pa[xnv]]);
61     }
62 }
63 /* SPLIT_HASH_HERE */
64 int lca(int u, int v) {
65     static int t = 0; ++t;
66     for (++t; u || v; swap(u, v)) if (u) {
67         if (vis[u] == t) return u;
68         vis[u] = t; u = st[match[u]];
69         if (u) u = st[pa[u]];
70     }
71     return 0;
72 }
73 void add_blossom(int u, int o, int v) {
74     int b = int(find(n + 1 + all(st), 0) - begin(st));
75     lab[b] = 0, S[b] = 0; match[b] = match[o];
76     vector<int> f = {o};
77     for (int x : {u, v}) {
78         for (int y; x != o; x = st[pa[y]])
79             f.pb(x), f.pb(y = st[match[x]]), q_push(y);
80         reverse(1 + all(f));
81     }
82     flo[b] = f; set_st(b, b);
83     REP(x, 1, nx) g[b][x].w = g[x][b].w = 0;
84     REP(x, 1, n) flo_from[b][x] = 0;
85     for (int xs : flo[b]) {
86         REP(x, 1, nx)
87             if (g[b][x].w == 0 || ED(g[xs][x]) < ED(g[b][x]))
88                 g[b][x] = g[xs][x], g[x][b] = g[x][xs];
89         REP(x, 1, n)
90             if (flo_from[xs][x]) flo_from[b][x] = xs;
91     }
92     set_slack(b);
93 }
94 void expand_blossom(int b) {
95     for (int x : flo[b]) set_st(x, x);
96     int xr = flo_from[b][g[b][pa[b]].u], xs = -1;
97     for (int x : split_flo(flo[b], xr)) {
98         if (xs == -1) { xs = x; continue; }
99         pa[xs] = g[x][xs].u; S[xs] = 1, S[x] = 0;
100         slack[xs] = 0; set_slack(x); q_push(x); xs = -1;
101     }
102     for (int x : flo[b])
103         if (x == xr) S[x] = 1, pa[x] = pa[b];
104         else S[x] = -1, set_slack(x);
105     st[b] = 0;
106 }
107 bool on_found_edge(const edge &e) {
108     if (int u = st[e.u], v = st[e.v]; S[v] == -1) {
109         int nu = st[match[v]]; pa[v] = e.u; S[v] = 1;
110         slack[v] = slack[nu] = 0; S[nu] = 0; q_push(nu);
111     }
112 }

```



```

109 } else if (S[v] == 0) {
110     if (int o = lca(u, v)) add_blossom(u, o, v);
111     else return augment(u, v), augment(v, u), true;
112 }
113 return false;
114 }
115 /* SPLIT_HASH_HERE */
116 bool matching() {
117     ranges::fill(S, -1); ranges::fill(slack, 0);
118     q = queue<int>();
119     REP(x, 1, nx) if (st[x] == x && !match[x])
120         pa[x] = 0, S[x] = 0, q.push(x);
121     if (q.empty()) return false;
122     for (;;) {
123         while (q.size()) {
124             int u = q.front(); q.pop();
125             if (S[st[u]] == 1) continue;
126             REP(v, 1, n)
127                 if (g[u][v].w > 0 && st[u] != st[v]) {
128                     if (ED(g[u][v]) != 0)
129                         update_slack(u, st[v], slack[st[v]]);
130                     else if (on_found_edge(g[u][v])) return true;
131                 }
132         }
133         int d = inf;
134         REP(b, n + 1, nx) if (st[b] == b && S[b] == 1)
135             d = min(d, lab[b] / 2);
136         REP(x, 1, nx)
137             if (int s = slack[x]; st[x] == x && s && S[x] <= 0)
138                 d = min(d, ED(g[s][x]) / (S[x] + 2));
139         REP(u, 1, n)
140             if (S[st[u]] == 1) lab[u] += d;
141             else if (S[st[u]] == 0) {
142                 if (lab[u] <= d) return false;
143                 lab[u] -= d;
144             }
145         REP(b, n + 1, nx) if (st[b] == b && S[b] >= 0)
146             lab[b] += d * (2 - 4 * S[b]);
147         REP(x, 1, nx)
148             if (int s = slack[x]; st[x] == x &&
149                 s && st[s] != x && ED(g[s][x]) == 0)
150                 if (on_found_edge(g[s][x])) return true;
151         REP(b, n + 1, nx)
152             if (st[b] == b && S[b] == 1 && lab[b] == 0)
153                 expand_blossom(b);
154     }
155     return false;
156 }
157 pair<ll, int> solve() {
158     ranges::fill(match, 0);
159     REP(u, 0, n) st[u] = u, flo[u].clear();
160     int w_max = 0;
161     REP(u, 1, n) REP(v, 1, n) {
162         flo_from[u][v] = (u == v ? u : 0);
163         w_max = max(w_max, g[u][v].w);
164     }
165     REP(u, 1, n) lab[u] = w_max;
166     int n_matches = 0; ll tot_weight = 0;
167     while (matching()) ++n_matches;
168     REP(u, 1, n) if (match[u] && match[u] < u)
169         tot_weight += g[u][match[u]].w;
170     REP(u, 1, n) if (match[u] == 0) match[u] = -1;
171     return make_pair(tot_weight, n_matches);
172 }
173 void set_edge(int u, int v, int w) {
174     g[u][v].w = g[v][u].w = w; }
175 };
```

13 Flow

13.1 Flow Methods

```

1 // Author: CRYPTOGRAPHER (some modified by Gino)
2 Maximize  $c^T x$  subject to  $Ax \leq b, x \geq 0$ ;
3 with the corresponding symmetric dual problem,
4 Minimize  $b^T y$  subject to  $A^T y \geq c, y \geq 0$ .
5
6 Maximize  $c^T x$  subject to  $Ax \leq b$ ;
7 with the corresponding asymmetric dual problem,
8 Minimize  $b^T y$  subject to  $A^T y = c, y \geq 0$ .
9
10 Maximize  $\sum x$  subject to  $x_i + x_j \leq A_{ij}, x \geq 0$ ;
11 => Maximize  $\sum x$  subject to  $x_i + x_j \leq A_{ij}$ ;
12 => Minimize  $A^T y = \sum A_{ij} y_{ij}$  subject to for all  $v$ ,
13      $\sum_{i=v \text{ or } j=v} y_{ij} = 1, y_{ij} \geq 0$ 
14 => possible optimal solution:  $y_{ij} = \{0, 0.5, 1\}$ 
15 =>  $y' = 2y: \sum_{i=v \text{ or } j=v} y'_{ij} = 2, y'_{ij} = \{0, 1, 2\}$ 
16
17 General Graph:
```

```

18 |Max Ind. Set| + |Min Vertex Cover| = |V|
19 |Max Ind. Edge Set| + |Min Edge Cover| = |V|
20 Bipartite Graph:
21 |Max Ind. Set| = |Min Edge Cover|
22 |Max Ind. Edge Set| = |Min Vertex Cover|
23
24 To reconstruct the minimum vertex cover, dfs from each
25 unmatched vertex on the left side and with unused edges
26 only. Equivalently, dfs from source with unused edges
27 only and without visiting sink. Then, a vertex is
28 chosen iff. it is on the left side and without visited
29 or on the right side and visited through dfs.
30
31 Minimum Weighted Bipartite Edge Cover:
32 Construct new bipartite graph with  $n+m$  vertices on each
33 side:
34 for each vertex  $u$ , duplicate a vertex  $u'$  on the other side
35 for each edge  $(u,v,w)$ , add edges  $(u,v,w)$  and  $(v',u',w)$ 
36 for each vertex  $u$ , add edge  $(u,u',2w)$  where  $w$  is min edge
37 connects to  $u$ 
38 then the answer is the minimum perfect matching of the new
39 graph (KM)
40
41 Maximum density subgraph (  $\sum\{W_e\} + \sum\{W_v\}$  ) / |V|
42 Binary search on answer:
43 For a fixed  $D$ , construct a Max flow model as follow:
44 Let  $S$  be Sum of all weight( or inf)
45 1. from source to each node with cap =  $S$ 
46 2. For each  $(u,v,w)$  in  $E$ ,  $(u \rightarrow v, \text{cap}=w), (v \rightarrow u, \text{cap}=w)$ 
47 3. For each node  $v$ , from  $v$  to sink with cap =  $S + 2 * D - \text{deg}[v]$ 
48 where  $\text{deg}[v] = \sum \text{weight of edge associated with } v$ 
49 If  $\text{maxflow} < S * |V|$ ,  $D$  is an answer.
50
51 Requiring subgraph: all vertex can be reached from source
52 with
53 edge whose cap > 0.
54
55 Maximum closed subgraph
56 1. connect source with positive weighted
57 vertex(capacity=weight)
58 2. connect sink with negative weighted vertex(capacity=-
59 weight)
60 3. make capacity of the original edges = inf
61 4. ans = sum(positive weighted vertex weight) - (max flow)
62
63 (Node-disjoint) Min DAG Path Cover (用最少路徑覆蓋所有點)
64 Node disjoint: 拆出來的路徑不能共用同一個點
65 將一個點  $u$  裂成  $u_+$  和  $u_-$ , 代表進入和出去
66 對於一條邊  $(u, v)$  建邊  $u_- \rightarrow v_+$ 
67 1.  $+$ 點們和  $-$ 點們形成一張二分圖
68 2. 最差的答案是  $n$ , 代表每個點自己一個點就是一條路徑
69 3. 只要一組  $(u_-, v_+)$  匹配成功那對應到的答案恰好會  $-1$ 
70 >>> ans =  $n -$  這張二分圖的最大匹配
71
72 General DAG Path Cover
73 跟 Node-disjoint 版本差在點可以被很多條路共用
74 建邊方式 Node-disjoint 差別在條件比較鬆
75 Node-disjoint:  $u_- \rightarrow v_+$  只能在  $(u, v)$  有邊時建
76 General:  $u_- \rightarrow v_+$  在  $u$  能走到  $v$  的時候就建
77
78 Dilworth Theorem
79 反鏈：一些節點的集合，滿足這些節點互相無法抵達
80 最大反鏈 = 最小 General DAG Path Cover
```

13.2 Dinic

```

1 // Author: Benson (Extensions by Gino)
2 // Function: Max Flow,  $O(V^2 E)$ 
3 // Usage: Call init(n) first, then add(u, v, w) based on
4 // your model
5 // (!) vertices 0-based
6 // >>> flow() := return max flow
7 // >>> find_cut() := return min cut + store cut set in
8 // dinic.cut
9 // >>> find_matching() := return |M| + store matching plan
10 // in dinic.matching
11 // >>> flow_decomposition := return max flow + store
12 // decomposition in dinic.D
13 #define int long long
14 #define eb emplace_back
15 #define ALL(a) a.begin(), a.end()
16 struct Dinic {
17     struct Edge {
18         // t: to | C: original capacity | c: current capacity |
19         // r: residual edge | f: current flow
20         int t, C, c, r, f;
21         bool fw; // is in forward-edge graph
22     };
23     Edge() {}
24     Edge(int t, int C, int r, bool fw, int f=0):
25         t(t), C(C), c(r), r(r), fw(fw), f(f) {}
26 };
27 vector<vector<Edge>> G;
```

```

22 vector<int> dis, iter;
23 int n, s, t;
24 void init(int _n) {
25     n = _n;
26     G.resize(n), dis.resize(n), iter.resize(n);
27     for(int i = 0; i < n; ++i)
28         G[i].clear();
29 }
30 void add(int a, int b, int c) {
31     G[a].eb(b, c, G[b].size(), true);
32     G[b].eb(a, 0, G[a].size() - 1, false);
33 }
34 bool bfs() {
35     fill(ALL(dis), -1);
36     dis[s] = 0;
37     queue<int> que;
38     que.push(s);
39     while(!que.empty()) {
40         int u = que.front(); que.pop();
41         for(auto& e : G[u]) {
42             if(e.c > 0 && dis[e.t] == -1) {
43                 dis[e.t] = dis[u] + 1;
44                 que.push(e.t);
45             }
46         }
47     }
48     return dis[t] != -1;
49 }
50 int dfs(int u, int cur) {
51     if(u == t) return cur;
52     for(int &i = iter[u]; i < (int)G[u].size(); ++i) {
53         auto& e = G[u][i];
54         if(e.c > 0 && dis[u] + 1 == dis[e.t]) {
55             int ans = dfs(e.t, min(cur, e.c));
56             if(ans > 0) {
57                 G[e.t][e.r].c += ans;
58                 e.c -= ans;
59                 return ans;
60             }
61         }
62     }
63     return 0;
64 }
65 // find max flow
66 int flow(int a, int b) {
67     s = a, t = b;
68     int ans = 0;
69     while(bfs()) {
70         fill(ALL(iter), 0);
71         int tmp;
72         while((tmp = dfs(s, INF)) > 0)
73             ans += tmp;
74     }
75     return ans;
76 }
77 // min cut plan
78 vector<pair<pair<int, int>, int>> cut;
79 int find_cut(int a, int b) {
80     int cut_sz = flow(a, b);
81     vector<int> vis(n, 0);
82     cut.clear();
83     function<void(int)> dfs = [&](int u) {
84         vis[u] = 1;
85         for (auto& e : G[u])
86             if (e.c > 0 && !vis[e.t])
87                 dfs(e.t);
88     };
89     dfs(a);
90     for (int u = 0; u < n; u++)
91         if (vis[u])
92             for (auto& e : G[u])
93                 if (!vis[e.t])
94                     cut.emplace_back(make_pair(u, e.t), G[e.t][e.r].c);
95     return cut_sz;
96 }
97 // bipartite matching plan
98 vector<pair<int, int>> matching;
99 int find_matching(int Xstart, int Xend, int Ystart, int Yend, int a, int b) {
100     int msz = flow(a, b);
101     matching.clear();
102     for (int x = Xstart; x <= Xend; x++)
103         for (auto& e : G[x])
104             if (e.c == 0 && Ystart <= e.t && e.t <= Yend)
105                 matching.emplace_back(make_pair(x, e.t));
106     return msz;
107 }
108 // flow decomposition
109 vector<pair<int, vector<int>>> D; // (flow amount, [path p1 ... pk])
110 int flow_decomposition(int a, int b) {

```

```

107     int mxflow = flow(a, b);
108 }
109 vector<vector<Edge>> fG(n); // graph consists of forward edges
110 for (int u = 0; u < n; u++) {
111     for (auto& e : G[u]) {
112         if (e.fw) {
113             e.f = e.C - e.c;
114             if (e.f > 0) fG[u].eb(e);
115         }
116     }
117 }
118 vector<int> vis;
119 function<int(int, int)> dfs = [&](int u, int cur) {
120     if (u == b) {
121         D.back().second.eb(u);
122         return cur;
123     }
124     vis[u] = 1;
125     for (auto& e : fG[u]) {
126         if (e.f > 0 && !vis[e.t]) {
127             int ans = dfs(e.t, min(cur, e.f));
128             if (ans > 0) {
129                 e.f -= ans;
130                 D.back().second.eb(u);
131                 return ans;
132             }
133         }
134     }
135     return 0LL;
136 };
137 D.clear();
138 int quota = mxflow;
139 while (quota > 0) {
140     D.emplace_back(make_pair(0, vector<int>()));
141     vis.assign(n, 0);
142     int f = dfs(a, INF);
143     if (f == 0) break;
144     reverse(D.back().second.begin(), D.back().second.end());
145     D.back().first = f, quota -= f;
146 }
147 return mxflow;
148 }

```

13.3 ISAP

```

1 // Author: CRYptoGRapheR
2 // 1-based: vertices are numbered 1 ~ n
3 // 1. flow.init(n, s, t);
4 // n = #vertices, s, t = source, sink
5 // 2. flow.addEdge(u, v, c); // u, v in [1, n]
6 // 3. call: int ans = flow.flow();
7 // => ans = max flow value from s to t
8 // Time: O(V^2 * E) worst case, usually much faster in practice
9 static const int MAXV=50010;
10 static const int INF =1000000;
11 struct Maxflow{
12     struct Edge{
13         int v,c,r;
14         Edge(int _v,int _c,int _r):v(_v),c(_c),r(_r){}
15     };
16     int s,t; vector<Edge> G[MAXV];
17     int iter[MAXV],d[MAXV],gap[MAXV],tot;
18     void init(int n,int _s,int _t){
19         tot=n,s=_s,t=_t;
20         for(int i=1;i<=tot;i++){
21             G[i].clear(); iter[i]=d[i]=gap[i]=0;
22         }
23     }
24     void addEdge(int u,int v,int c){
25         G[u].push_back(Edge(v,c,SZ(G[v])));
26         G[v].push_back(Edge(u,0,SZ(G[u])-1));
27     }
28     int DFS(int p,int flow){
29         if(p==t) return flow;
30         for(int &i=iter[p]; i<SZ(G[p]); i++){
31             Edge &e=G[p][i];
32             if(e.c>0&&d[p]==d[e.v]+1){
33                 int f=DFS(e.v,min(flow,e.c));
34                 if(f){ e.c-=f; G[e.v][e.r].c+=f; return f; }
35             }
36         }
37         if(--gap[d[p]]==0) d[s]=tot;
38         else{ d[p]++; iter[p]=0; ++gap[d[p]]; }
39         return 0;
40     }
41     int flow(){
42         int res=0;
43         for(res=0,gap[0]=tot;d[s]<tot;res+=DFS(s,INF));
44         return res;
45     }

```

```

46 void reset(){
47     for(int i=1; i<=tot; i++) iter[i]=d[i]=gap[i]=0;
48 }
49 } flow;

```

13.4 Bounded Max Flow

```

1// Author: CRYPTOGRAPHER
2// Max flow with lower/upper bound on edges (source-sink
  version)
3// <!-- 1-based: original vertices are numbered 1 ~ n.
4//      Super source, sink: n+1, n+2 respectively.
5// <!-- dependency: ISAP.cpp
6// 1. n = #vertices (1 ~ n), m = #edges
7//      s, t = original source, sink (both in [1, n])
8// 2. l[i], r[i] := edge i goes from l[i] -> r[i] (l[i],
9//      r[i] in [1, n])
10// 3. a[i], b[i] := flow on edge i must lie in [a[i], b[i]]
11// 4. int ans = solve(n, m, s, t);
12// => ans == -1 : no feasible flow exists
13// => ans      : feasible max flow value
14// <!-- N, M must be large enough for original graph + 2
   super nodes
15// Time: O(V^2 E), Space: O(V + E)
16int in[N], out[N], l[M], r[M], a[M], b[M];
17int solve(int n, int m, int s, int t){
18    flow.init(n+2, n+1, n+2); // super source = n+1, super
   sink = n+2
19    for(int i = 0; i < m; i++){
20        in[r[i]] += a[i]; out[l[i]] += a[i];
21        flow.addEdge(l[i], r[i], b[i] - a[i]);
22        // flow from l[i] to r[i] must lie in [a[i], b[i]]
23    }
24    int nd = 0;
25    for(int i = 1; i <= n; i++){
26        if(in[i] < out[i]){
27            flow.addEdge(i, flow.t, out[i] - in[i]);
28            nd += out[i] - in[i];
29        }
30        if(out[i] < in[i])
31            flow.addEdge(flow.s, i, in[i] - out[i]);
32    }
33    flow.addEdge(t, s, INF); // original sink -> source
34    if(flow.flow() != nd) return -1; // infeasible
35    int ans = flow.G[s].back().c; // t->s edge's current flow
   = feasible flow s->t
36    flow.G[s].back().c = flow.G[t].back().c = 0;
37    for(size_t i = 0; i < flow.G[flow.s].size(); i++){
38        Maxflow::Edge &e = flow.G[flow.s][i];
39        flow.G[flow.s][i].c = 0; flow.G[e.v][e.r].c = 0;
40    }
41    for(size_t i = 0; i < flow.G[flow.t].size(); i++){
42        Maxflow::Edge &e = flow.G[flow.t][i];
43        flow.G[flow.t][i].c = 0; flow.G[e.v][e.r].c = 0;
44    }
45    flow.addEdge(flow.s, s, INF); flow.addEdge(t, flow.t,
   INF);
46    flow.reset(); // keeps G[] intact, only resets search
   state
47    return ans + flow.flow();

```

13.5 MCMF

```

1// Author: CRYPTOGRAPHER
2// MCMF (supports negative edges without negative cycles)
3// <!-- 1-based: vertices are numbered 1 ~ n.
4// 1. MCMF.init(n); // n = #vertices (1 ~ n)
5// 2. MCMF.add(u, v, cap, cost);
6// 3. auto [max_flow, min_cost] = MCMF.flow(s, t); // s, t
   in [1, n]
7// Time: O(F * E), Space: O(V + E)
8typedef int Tcost;
9const int MAXV = 20010;
10const int INFf = 1000000;
11const Tcost INFc = 1e9;
12struct MCMF {
13    struct Edge {
14        int v, cap;
15        Tcost w;
16        int rev;
17        bool fw;
18        Edge(){}
19        Edge(int t2, int t3, Tcost t4, int t5, bool t6)
20            : v(t2), cap(t3), w(t4), rev(t5), fw(t6) {}
21    };
22    int V, s, t;
23    vector<Edge> G[MAXV];
24    void init(int n){
25        V = n;
26        for(int i = 0; i <= V; i++) G[i].clear();
27    }

```

```

28 void add(int a, int b, int cap, Tcost w){
29     G[a].push_back(Edge(b, cap, w, (int)G[b].size(), true));
30     G[b].push_back(Edge(a, 0, -w, (int)G[a].size()-1,
   false));
31 }
32 Tcost d[MAXV];
33 int id[MAXV], mom[MAXV];
34 bool inqu[MAXV];
35 queue<int> q;
36 pair<int, Tcost> flow(int _s, int _t){
37     s = _s, t = _t;
38     int mxf = 0; Tcost mnc = 0;
39     while(1){
40         fill(d, d+V, INFc); // need to use type cast
41         fill(inqu, inqu+V, 0);
42         fill(mom, mom+V, -1);
43         mom[s] = s;
44         d[s] = 0;
45         q.push(s); inqu[s] = 1;
46         while(q.size()){
47             int u = q.front(); q.pop();
48             inqu[u] = 0;
49             for(int i = 0; i < (int) G[u].size(); i++){
50                 Edge &e = G[u][i];
51                 int v = e.v;
52                 if(e.cap > 0 && d[v] > d[u]+e.w){
53                     d[v] = d[u]+e.w;
54                     mom[v] = u;
55                     id[v] = i;
56                     if(!inqu[v]) q.push(v), inqu[v] = 1;
57                 }
58             }
59         }
60         if(mom[t] == -1) break;
61         int df = INFf;
62         for(int u = t; u != s; u = mom[u])
63             df = min(df, G[mom[u]][id[u]].cap);
64         for(int u = t; u != s; u = mom[u]){
65             Edge &e = G[mom[u]][id[u]];
66             e.cap -= df;
67             G[e.v][e.rev].cap += df;
68         }
69         mxf += df;
70         mnc += df*d[t];
71     }
72     return make_pair(mxf, mnc);
73 }
74 }

```

13.6 Push-Relabel

```

1// Author: Simon Lindholm (kactl)
2// 0-based: vertices are numbered 0 ~ n-1
3// 1. PushRelabel pr(n); // n = #vertices
4// 2. pr.addEdge(u, v, c); // u, v in [0, n-1]
5// 3. ll ans = pr.calc(s, t);
6// => ans = max flow value from s to t
7// To obtain actual flow:
8// for (int u = 0; u < n; u++)
9//     for (auto& e : pr.g[u])
10//         if (e.f > 0) => (u, e.dest, e.f)
11// Time: O(V^2 * sqrt(E)), better on dense graph
12struct PushRelabel {
13    struct Edge { int dest, back; ll f, c; };
14    vector<vector<Edge>> g;
15    vector<ll> ec;
16    vector<Edge*> cur;
17    vector<vi> hs; vi H;
18    PushRelabel(int n) : g(n), ec(n), cur(n), hs(2*n), H(n) {}
19
20    void addEdge(int s, int t, ll cap, ll rcap=0) {
21        if (s == t) return;
22        g[s].push_back({t, sz(g[t]), 0, cap});
23        g[t].push_back({s, sz(g[s])-1, 0, rcap});
24    }
25
26    void addFlow(Edge& e, ll f) {
27        Edge &back = g[e.dest][e.back];
28        if (!ec[e.dest] && f) hs[H[e.dest]].push_back(e.dest);
29        e.f += f; e.c -= f; ec[e.dest] += f;
30        back.f -= f; back.c += f; ec[back.dest] -= f;
31    }
32
33    ll calc(int s, int t) {
34        int v = sz(g); H[s] = v; ec[t] = 1;
35        vi co(2*v); co[0] = v-1;
36        rep(i, 0, v) cur[i] = g[i].data();
37        for (Edge& e : g[s]) addFlow(e, e.c);
38
39        for (int hi = 0; ; ) {
40            while (hs[hi].empty()) if (!hi--) return -ec[s];
41            int u = hs[hi].back(); hs[hi].pop_back();
42            while (ec[u] > 0) // discharge u

```

```

41     if (cur[u] == g[u].data() + sz(g[u])) {
42         H[u] = 1e9;
43         for (Edge& e : g[u]) if (e.c && H[u] >
H[e.dest]+1)
44             H[u] = H[e.dest]+1, cur[u] = &e;
45         if (++co[H[u]], !--co[hi] && hi < v)
46             rep(i,0,v) if (hi < H[i] && H[i] < v)
47                 --co[H[i]], H[i] = v + 1;
48         hi = H[u];
49     } else if (cur[u]->c && H[u] == H[cur[u]->dest]+1)
50         addFlow(*cur[u], min(ec[u], cur[u]->c));
51     else ++cur[u];
52 }
53 }
54 bool leftOfMinCut(int a) { return H[a] >= sz(g); }
55 }

```

13.7 Gomory-Hu Tree

```

1// Author: chilli, Takanori MAEHARA (kactl)
2// <!> Dependency: PushRelabel.cpp
3// Given a list of edges representing an undirected flow
graph,
4// returns edges of the Gomory-Hu tree.
5// maxflow / mincut of (u, v) => min edge from u to v on
Gomory-Hu tree
6// Time: O(V) * O(PushRelabel)
7typedef array<ll, 3> Edge; // (u, v, w)
8vector<Edge> gomoryHu(int N, vector<Edge> ed) {
9    vector<Edge> tree;
10    vi par(N);
11    rep(i,1,N) {
12        PushRelabel D(N); // Dinic also works
13        for (Edge t : ed) D.addEdge(t[0], t[1], t[2], t[2]);
14        tree.push_back({i, par[i], D.calc(i, par[i])});
15        rep(j,i+1,N)
16            if (par[j] == par[i] && D.leftOfMinCut(j)) par[j] = i;
17    }
18    return tree;
19}

```

13.8 Global Min Cut

```

1// Author: ckiseki
2// 1-based: vertices are numbered 1 ~ n
3// 1. vector<vector<ll>> G(n+1, vector<ll>(n+1, 0));
4// 2. add edge(G, u, v, c); // add undirected edge u-v with
weight c, u,v in [1,n]
5// 3. ll ans = mincut(G, n); // n = #vertices
6// => ans = global min cut value
7// Time: O(V^3)
8void add_edge(auto &w, int u, int v, int c) {
9    w[u][v] += c; w[v][u] += c; }
10auto phase(const auto &w, int n, vector<int> id) {
11    vector<ll> g(n+1); int s = -1, t = -1;
12    while (!id.empty()) {
13        int c = -1;
14        for (int i : id) if (c == -1 || g[i] > g[c]) c = i;
15        s = t; t = c;
16        id.erase(ranges::find(id, c));
17        for (int i : id) g[i] += w[c][i];
18    }
19    return tuple{s, t, g[t]};
20}
21ll mincut(auto w, int n) {
22    ll cut = numeric_limits<ll>::max();
23    vector<int> id(n); iota(all(id), 1);
24    for (int i = 0; i < n - 1; ++i) {
25        auto [s, t, gt] = phase(w, n, id);
26        id.erase(ranges::find(id, t));
27        cut = min(cut, gt);
28        for (int j = 1; j <= n; ++j)
29            w[s][j] += w[t][j], w[j][s] += w[j][t];
30    }
31    return cut;
32}

```

14 Combinatorics

14.1 Catalan Number

$$C_0 = 1, C_n = \sum_{i=0}^{n-1} C_i C_{n-1-i}, C_n = C_n^{2n} - C_{n-1}^{2n}$$

0	1	1	2	5
4	14	42	132	429
8	1430	4862	16796	58786
12	208012	742900	2674440	9694845

14.2 Bertrand's Ballot Theorem

- A always $> B$: $C(p+q, p) - 2C(p+q-1, p)$

- A always $\geq B$: $C(p+q, p) \times \frac{p+1-q}{p+1}$

14.3 Burnside's Lemma

Let X be the original set.

Let G be the group of operations acting on X .

Let X^g be the set of x not affected by g .

Let X/G be the set of orbits.

Then the following equation holds:

$$|X/G| = \frac{1}{|G|} \sum_{g \in G} |X^g|$$

15 Special Numbers

15.1 Fibonacci Series

1	1	1	2	3
5	5	8	13	21
9	34	55	89	144
13	233	377	610	987
17	1597	2584	4181	6765
21	10946	17711	28657	46368
25	75025	121393	196418	317811
29	514229	832040	1346269	2178309
33	3524578	5702887	9227465	14930352

$$f(45) \approx 10^9, f(88) \approx 10^{18}$$

15.2 Prime Numbers

- $\pi(n) \equiv$ Number of primes $\leq n \approx \frac{n}{(\ln n)-1}$

$$\begin{aligned} \pi(100) &= 25, \pi(200) = 46 \\ \pi(500) &= 95, \pi(1000) = 168 \\ \pi(2000) &= 303, \pi(4000) = 550 \\ \pi(10^4) &= 1229, \pi(10^5) = 9592 \\ \pi(10^6) &= 78498, \pi(10^7) = 664579 \end{aligned}$$

