

1 Reminder	1	12.13 Mu + Phi	19
1.1 Observations and Tricks	1	12.14 Other Formulas	19
1.2 Bug List	1	12.15 Polynomial	19
2 Init (Linux)	1	12.16 Counting Primes	20
2.1 vimrc	1	12.17 Linear Sieve for Other Number Theoretic Functions	21
2.2 bashrc	1	13 Numerical	21
3 Basic	1	13.1 Polynomials and recurrences	21
3.1 Template (Using Codebook)	1	13.2 Optimization	22
3.2 PBDS, Random	1	13.3 Matrices	23
3.3 Debug	2	13.4 Fourier transforms	25
3.4 SVG Writer	2	14 Combinatorics	25
3.5 Python	2	14.1 Catalan Number	25
3.6 Stress Tests	2	14.2 Bertrand's Ballot Theorem	25
4 Data Structure	2	14.3 Burnside's Lemma	25
4.1 Mo's Algorithm	2	15 Special Numbers	25
4.2 CDQ	3	15.1 Fibonacci Series	25
4.3 Persistent Treap	3	15.2 Prime Numbers	26
4.4 Li Chao Tree	3	15.3 Number of Divisors	26
4.5 Time Segment Tree	3	15.4 Distinct Prime Factors	26
4.6 Segment Tree Beats	4	1 Reminder	
5 DP	4	1.1 Observations and Tricks	
5.1 SOS DP	4	• Contribution Technique	
5.2 Divide and Conquer DP	4	• 二分圖/Spanning Tree/DFS Tree	
5.3 Dynamic DP	4	• 行、列操作互相獨立	
5.4 Convex Hull Trick	5	• 奇偶性	
6 Graph	5	• 當 s, t 遞增並且 $t = f(s)$ ，對 s 二分搜不好做，可以改成對 t 二分搜，再算 $f(t)$	
6.1 Max Clique	5	• 啟發式合併	
6.2 Bellman-Ford	5	• Permutation Normalization (做一些平移對齊兩個 permutation)	
6.3 System of Difference Constraints	5	• 枚舉 $a_1 \sim a_n$ 再枚舉 $a_n \sim a_1$ 可以包在一個迴圈	
6.4 Graph Girth	5	• 兩個凸型函數相加還是凸型函數，相減不一定	
6.5 Euler Trail	5	• 一個區間的 $\text{mex} = k$ ，表示這個區間包含 $0 \sim k - 1$ 所有數字，並且「 U - 區間」的最小值 $= k$ 。	
6.6 Vertex BCC (Round Square Tree)	6	1.2 Bug List	
6.7 Edge BCC	6	• 沒開 long long	
6.8 Kth Shortest Path	6	• 陣列戳出界／陣列開不夠大	
6.9 SCC - Tarjan	7	• 寫好的函式 (例如 <code>init()</code> 、 <code>build()</code>) 忘記呼叫	
6.10 2SAT	7	• 0-base / 1-base	
7 Tree	7	• 線段樹改值懶標初始值不能設為 0	
7.1 Tree Isomorphism (Rooted Trees)	7	• DFS 的時候不小心覆寫到全域變數	
7.2 Tree Isomorphism (Unrooted Trees)	7	• 多筆測資不能沒讀完直接 return	
7.3 Heavy Light Decomposition	7	• vector 超級肥，小 vector 請用 array，例如矩陣快速冪	
7.4 Virtual Tree	8	2 Init (Linux)	
8 Matching	8	2.1 vimrc	
8.1 Bipartite Matching	8	<code>1 syn on</code>	
8.2 Bipartite Weighted Matching	8	<code>2 set nu rnu cul mouse=a cin et ts=2 sw=2 sts=2 autochdir</code>	
8.3 General Matching	8	<code>cb=unnamedplus</code>	
9 Flow	9	<code>3 no ; :</code>	
9.1 Flow Methods	9	<code>4 ino {<CR> {<CR>}<Esc>ko</code>	
9.2 Dinic (Flow Decomposition)	9	<code>5 ca Hash w !cpp -dD -P \ tr -d '[:space:]' \ openssl sha256</code>	
9.3 ISAP	10	<code>-r \ cut -c-6</code>	
9.4 Bounded Max Flow	10	<code>1" Gino's .vimrc "</code>	
9.5 MCMF	10	<code>2"no <C-h> ^ <C-l> \$ h b l e b l e h</code>	
9.6 Push-Relabel	11	2.2 bashrc	c08ff4
9.7 Gomory-Hu Tree	11	<code>1 gogo() {</code>	
9.8 Global Min Cut	11	<code>2 g++ -std=c++20 -O2 "\$1" && echo run && ./a.out</code>	
10 String	12	<code>3}</code>	
10.1 Rolling Hash	12	<code>4 alias vig='vim -u ~/.vimrc-gino'</code>	
10.2 KMP	12	3 Basic	
10.3 Z Value	12	3.1 Template (Using Codebook)	9f9204
10.4 Manacher	12	<code>1 // CryptoGraper</code>	
10.5 Suffix Array + LCP	12	<code>2 #define SZ(c) ((int)(c).size())</code>	
10.6 Suffix Automaton	12	<code>3 // kactl</code>	
10.7 Minimum Rotation	13	<code>4 #define sz(x) (int)(x).size()</code>	
10.8 AC Automaton	13	<code>5 #define rep(i, a, b) for(int i=(a); i<(b); i++)</code>	
10.9 AC Automaton - Dict Links	13	<code>6 using ll = long long;</code>	
10.10 AC Automaton - Counting Patterns	13	<code>7 using vi = vector<int>;</code>	
10.11 AC Automaton - Pattern Position	13	<code>8 using pii = pair<int, int>;</code>	
11 Geometry	13	<code>9 // ckiseki</code>	
11.1 Template	13	<code>10 #define all(x) begin(x), end(x)</code>	
11.2 Basic	13	<code>11 #define pb emplace_back</code>	
11.3 Line / Segment Intersections	13	<code>12 #define REP(i, l, r) for (int i=(l); i<=(r); ++i)</code>	
11.4 Point-Line / Segment Distance	14	<code>13 const ll LINF = 1e18;</code>	
11.5 Sort	14	<code>14 template<class A, class B> bool chmin(A& a, B& b) {</code>	
11.6 Convex Hull	14	<code>15 return b < a ? a = b, 1 : 0;</code>	
11.7 Triangle Centers	14	<code>16}</code>	
11.8 Point Inside	14	3.2 PBDS, Random	d9e963
11.9 Point In Triangle	14	<code>1 #include <bits/extc++.h></code>	
11.10 Vector In Polygon	14	<code>2 using namespace __gnu_pbds;</code>	
11.11 Polygon Cut	14	<code>3 // map</code>	
11.12 Half-Plane Intersection	15	<code>4 tree<int, int, less<>, rb_tree_tag,</code>	
11.13 Cyclic Ternary Search	15	<code>tree_order_statistics_node_update> tr;</code>	
11.14 Circle Intersections	15		
11.15 Tangents	15		
11.16 Bisector	15		
11.17 Minimum Enclosing Circle	15		
11.18 Minkowski Sum	16		
11.19 Convex Hull Distance	16		
11.20 Closest Point Pair	16		
11.21 Polygon-Circle Intersection	16		
11.22 Union of Polygons	16		
11.23 Rotating Sweep Line	16		
11.24 Pick's Theorem	17		
12 Number Theory	17		
12.1 Mod Sum	17		
12.2 Extended Lucas Theorem	17		
12.3 Prime Sieve and Defactor	17		
12.4 Harmonic Series	17		
12.5 Count Number of Divisors	18		
12.6 數論分塊	18		
12.7 Pollard's rho	18		
12.8 Miller Rabin	18		
12.9 Discrete Log	18		
12.10 Discrete Sqrt	19		
12.11 Fast Power	19		
12.12 Extend GCD	19		

```

5 tr.order_of_key(element);
6 tr.find_by_order(rank);
7 // set
8 tree<int, null_type, less<>, rb_tree_tag,
  tree_order_statistics_node_update> tr;
9 tr.order_of_key(element);
10 tr.find_by_order(rank);
11 // priority queue
12 __gnu_pbds::priority_queue<int, less<int>> big_q;
13 __gnu_pbds::priority_queue<int, greater<int>> small_q;
14 q1.join(q2); // join
15
16 mt19937
17 gen(chrono::steady_clock::now().time_since_epoch().count());
18 uniform_int_distribution<int>(a, b)(rng) // [a, b]
19 uniform_real_distribution<double>(a, b)(rng) // (a, b)
20 shuffle(v.begin(), v.end(), gen);

```

3.3 Debug

a265e1

```

1 #define debug(...) cerr << "\x1b[33m" #__VA_ARGS__ " : \
  \x1b[0m" \
2   [__VA_ARGS__], cerr << '\n'
3 #define output(...) \
4   [__VA_ARGS__], cout << '\n'
5 int v = 42;
6 format("{:b}", v); // "101010"
7 format("{:#b}", v); // "0b101010"
8 format("{:x}", v); // "0x2a"
9 format("{:X}", v); // "0X2A"
10 int x = 7;
11 format("{:05d}", x); // "00007"
12 format("{:>5}", x); // " 7"
13 format("{:<5}", x); // "7 "
14 format("{:^5}", x); // " 7 "
15 format("{:*^5}", x); // "***7***"
16 double pi = 3.1415926535;
17 format("{:.2f}", pi); // "3.14"

```

3.4 SVG Writer

```

1 // Author: ckiseki
2 class SVG {
3   void p(string_view s) { o << s; }
4   void p(string_view s, auto v, auto... vs) {
5     auto i = s.find('$');
6     o << s.substr(0, i) << v, p(s.substr(i + 1), vs...);
7   }
8   ofstream o; string c = "red";
9 public:
10  SVG(auto f, auto x1, auto y1, auto x2, auto y2) : o(f) {
11    p("<svg xmlns='http://www.w3.org/2000/svg' "
12      "viewBox='$ $ $ $'>\n"
13      "<style>{*stroke-width:0.5%;}</style>\n",
14      x1, -y2, x2 - x1, y2 - y1); }
15  ~SVG() { p("</svg>\n"); }
16  void color(string nc) { c = nc; }
17  void line(auto x1, auto y1, auto x2, auto y2) {
18    p("<line x1='$' y1='$' x2='$' y2='$' stroke='$'>\n",
19      x1, -y1, x2, -y2, c); }
20  void circle(auto x, auto y, auto r) {
21    p("<circle cx='$' cy='$' r='$' stroke='$' "
22      "fill='none'>\n", x, -y, r, c); }
23  void text(auto x, auto y, string s, int w = 12) {
24    p("<text x='$' y='$' font-size='$px'>$</text>\n",
25      x, -y, w, s); }
26 };

```

```

1 SVG svg("out.svg", -200, -200, 200, 200);
2 svg.color("lightgray"); // ↓ drawing x-y plane
3 svg.line(-200, 0, 200, 0); svg.line(0, -200, 0, 200);
4 svg.color("blue"); svg.line(10, 10, 80, 80);
5 svg.color("red"); svg.circle(50, 50, 1);

```

3.5 Python

00e632

```

1 import sys
2 input = sys.stdin.readline
3 readStr = lambda: input().rstrip('\r\n')
4 readInt = lambda: int(input())
5 readInts = lambda: list(map(int, input().split()))
6
7 from decimal import *
8 getcontext().prec = 50 # precision
9 x = Decimal(str(x))
10 y = Decimal("6.7")
11 x *= y
12 print(x.quantize(Decimal("0.000001"),
  rounding=ROUND_HALF_EVEN))
13 # ROUND_CEILING : To INF (2.9 -> 3, -2.1 -> -2)
14 # ROUND_FLOOR : To -INF (2.1 -> 2, -2.9 -> -3)
15 # ROUND_HALF_EVEN: To nearest even (2.5 -> 2, 3.5 -> 4)

```

```

16# ROUND_HALF_UP : Half away from 0 (2.5 -> 3, -2.5 -> -3)
17# ROUND_HALF_DOWN: Half towards 0 (2.5 -> 2, -2.5 -> -2)
18# ROUND_UP : Away from 0 (2.1 -> 3, -2.1 -> -3)
19# ROUND_DOWN : Truncate to 0 (2.9 -> 2, -2.9 -> -2)
20# <Default>: ROUND_HALF_EVEN
21# <Standard School Math>: ROUND_HALF_UP

```

3.6 Stress Tests

```

1 from random import *
2 n = randint(1, 10)
3 arr = list(randint(1, 20) for i in range(n))
4 print(*arr)
5 # permutation / non-repetitive sequence
6 perm = sample(range(1, n + 1), n)
7 arr = sample(range(1, 10000 + 1), n)
8 # string
9 from string import *
10 s = "".join(choices(ascii_lowercase, k=n))
11 t = "".join(choices(ascii_lowercase[:3], k=n)) # (a|b|c)*
12 u = "".join(choices(ascii_lowercase + ascii_uppercase +
  digits, k=n))
13 # palindrome
14 half = "".join(choices(ascii_lowercase, k=(n + 1) // 2))
15 palindrome = half + (half[-2::-1] if n % 2 else half[::-1])
16 # ===== tree =====
17 n = 30
18 ## shallow tree
19 edges = [(randint(1, u - 1), u) for u in range(2, n + 1)]
20 ## deep tree
21 ## (suggested k: 2 ~ 5 or int(sqrt(n)) or 2n/D (D is
  expected depth))
22 from math import *
23 k = int(sqrt(n))
24 edges = [(randint(max(1, u-k), u-1), u) for u in range(2, n
  + 1)]
25 for e in edges:
26   print(*e)
27
28 edges = [(1, i) for i in range(2, n + 1)] ## star
29 edges = [(i, i + 1) for i in range(1, n)] ## chain
30 edges = [(i // 2, i) for i in range(2, n + 1)] ## complete
  binary tree
31 # ===== graph =====
32 ## not necessarily connected, no multi-edge or self-loop
33 n = 10
34 density = 0.3 # graph density (0.0 ~ 1.0)
35 edges = [(i, j) for i in range(1, n+1) for j in range(i+1,
  n+1) if random() < density]
36 ## connected, no multi-edge or self-loop
37 n, extra_edges = 10, 5
38 edges = set()
39 ### ... generate spanning tree with codes above
40 while len(edges) < n - 1 + extra_edges:
41   u, v = randint(1, n), randint(1, n)
42   if u != v:
43     edges.add((min(u, v), max(u, v)))
44 edges = list(edges)
45 ## DAG
46 perm = sample(range(1, n + 1), n)
47 edges = []
48 for i in range(m):
49   i, j = sorted(sample(range(n), 2))
50   edges.append((perm[i], perm[j]))
51 ## Bipartite Graph
52 n1, n2 = 6, 7
53 left, right = list(range(1, n1+1)), list(range(n1+1,
  n1+n2+1))
54 edges = [(choice(left), choice(right)) for _ in range(m)]

```

```

1 g++ -std=c++20 -o buggy $1
2 g++ -std=c++20 -o ac ac.cpp
3 for i in {1..100}; do
4   echo "TEST $i"
5   python3 gen.py > in
6   ./ac < in > oa
7   ./buggy < in > ob
8   if ! diff -q oa ob; then
9     cat in <(echo "=== AC") oa <(echo "=== WA") ob
10    break
11  fi
12 done

```

4 Data Structure

4.1 Mo's Algorithm

8d7194

```

1 // segments are 0-based
2 int B = max(1, (int)sqrt(n));
3 sort(Q.begin(), Q.end(), [&](const auto& a, const auto& b) {
4   if (a[0]/B != b[0]/B) return a[0]<b[0];
5   return (a[0]/B & 1) ? a[1]<b[1] : a[1]>b[1];
6 });
7 ll cur = 0; // current answer

```

```

8 int pl = 0, pr = -1;
9 for (auto& qi : Q) {
10     // get (l, r, qid) from qi
11     while (pl < l) del(pl++); while (pl > l) add(--pl);
12     while (pr < r) add(++pr); while (pr > r) del(pr--);
13     ans[qid] = cur;
14 }

```

4.2 CDQ

744a80

```

1 // preparation
2 // 1. write a 1-base BIT
3 // 2. init(n, mxc): n is number of elements, mxc = 值域
4 // 3. build info array CDQ.v by yourself (x, y, z, id)
5 // 4. call solve()
6 // => cdq.ans[i] is number of j s.t. (xj <= xi, yj <= yi, zj
7 //    <= zi) (j != i)
8 struct CDQ {
9     struct info {
10         int x, y, z, id;
11         info(int x, int y, int z, int id):
12             x(x), y(y), z(z), id(id) {}
13         info():
14             x(0), y(0), z(0), id(0) {}
15     };
16     int n, mxc;
17     BIT bit;
18     vector<info> v;
19     vector<ll> ans;
20     void init(int _n, int _mxc) {
21         n = _n; mxc = _mxc;
22         v.assign(n, info{});
23         ans.assign(n, 0);
24     }
25     void dfs(int l, int r) {
26         if (l >= r) return;
27         int mid = (l+r) >> 1;
28         dfs(l, mid); dfs(mid+1, r);
29
30         vector<info> tmp;
31         vector<int> bit_op;
32         int pl = l, pr = mid+1;
33
34         while (pl <= mid && pr <= r) {
35             if (v[pl].y <= v[pr].y) {
36                 tmp.emplace_back(v[pl]);
37                 bit_op.emplace_back(v[pl].z);
38                 pl++;
39             }
40             else {
41                 tmp.emplace_back(v[pr]);
42                 ans[v[pr].id] += bit.qry(v[pr].z);
43                 pr++;
44             }
45         }
46         while (pl <= mid) {
47             tmp.emplace_back(v[pl]);
48             pl++;
49         }
50         while (pr <= r) {
51             tmp.emplace_back(v[pr]);
52             ans[v[pr].id] += bit.qry(v[pr].z);
53             pr++;
54         }
55         for (int i = l, j = 0; i <= r; i++, j++) v[i] = tmp[j];
56         for (auto& op : bit_op) bit.upd(op, -1);
57     }
58     void solve() {
59         bit.init(mxc);
60         sort(v.begin(), v.end(), [&](const info& a, const info&
61 b){
62             return (a.x == b.x ? (a.y == b.y ? (a.z == b.z ?
63 a.id < b.id : a.z < b.z) : a.y < b.y) : a.x < b.x);
64         });
65         dfs(0, n-1);
66         map<pair<int, pii>, int> s;
67         sort(v.begin(), v.end(), [&](const info& a, const info&
68 b){
69             return a.id > b.id;
70         });
71         for (int i = 0, id = n-1; i < n; i++, id--) {
72             pair<int, pii> tmp = make_pair(v[i].x,
73 make_pair(v[i].y, v[i].z));
74             auto it = s.find(tmp);
75             if (it != s.end())
76                 ans[id] += it->second;
77             s[tmp]++;
78         }
79     }
80 }

```

76};

4.3 Persistent Treap

803cce

```

1 // Author: Ian
2 struct node {
3     node *l, *r;
4     char c; int v, sz;
5     node(char x = '$'): c(x), v(mt()), sz(1) {
6         l = r = nullptr;
7     }
8     node(node* p) { *this = *p; }
9     void pull() {
10         sz = 1;
11         for (auto i : {l, r})
12             if (i) sz += i->sz;
13     }
14     arr[maxn], *ptr = arr;
15     inline int size(node* p) { return p ? p->sz : 0; }
16     node* merge(node* a, node* b) {
17         if (!a || !b) return a ? a : b;
18         if (a->v < b->v) {
19             node* ret = new(ptr++) node(a);
20             ret->r = merge(ret->r, b); ret->pull();
21             return ret;
22         }
23         else {
24             node* ret = new(ptr++) node(b);
25             ret->l = merge(a, ret->l); ret->pull();
26             return ret;
27         }
28     }
29     P<node*> split(node* p, int k) {
30         if (!p) return {nullptr, nullptr};
31         if (k >= size(p->l) + 1) {
32             auto [a, b] = split(p->r, k - size(p->l) - 1);
33             node* ret = new(ptr++) node(p);
34             ret->r = a, ret->pull();
35             return {ret, b};
36         }
37         else {
38             auto [a, b] = split(p->l, k);
39             node* ret = new(ptr++) node(p);
40             ret->l = b, ret->pull();
41             return {a, ret};
42         }
43     }
44 }

```

4.4 Li Chao Tree

6c33c2

```

1 // Author: Ian
2 // Function: For a set of lines L, find the maximum L_i(x)
3 // in L in O(lg n).
4 typedef long double ld;
5 constexpr int maxn = 5e4 + 5;
6 struct line {
7     ld a, b;
8     ld operator()(ld x) { return a * x + b; }
9     arr[(maxn + 1) << 2];
10     bool operator<(line a, line b) { return a.a < b.a; }
11 #define m ((l+r)>>1)
12 void insert(line x, int i = 1, int l = 0, int r = maxn) {
13     if (r - l == 1) {
14         if (x(l) > arr[i](l))
15             arr[i] = x;
16         return;
17     }
18     line a = max(arr[i], x), b = min(arr[i], x);
19     if (a(m) > b(m))
20         arr[i] = a, insert(b, i << 1, l, m);
21     else
22         arr[i] = b, insert(a, i << 1 | 1, m, r);
23 }
24 ld query(int x, int i = 1, int l = 0, int r = maxn) {
25     if (x < l || r <= x) return -numeric_limits<ld>::max();
26     if (r - l == 1) return arr[i](x);
27     return max({arr[i](x), query(x, i << 1, l, m), query(x, i
28 << 1 | 1, m, r)});
29 }
30 #undef m

```

4.5 Time Segment Tree

519775

```

1 // Author: Ian
2 struct Op; // reversible operation
3 const int maxn = 2e5 + 5;
4 vector<Op> arr[(maxn + 1) << 2];
5 #define m ((l + r) >> 1)
6 void insert(int ql, int qr, Op x, int i=1, int l=0, int r=maxn) {
7     if (qr <= l || r <= ql) return;
8     if (ql <= l && r <= qr) { arr[i].push_back(x); return; }
9     if (qr <= m) insert(ql, qr, x, i << 1, l, m);
10     else if (m <= ql) insert(ql, qr, x, i << 1 | 1, m, r);
11     else {

```

```

12     insert(ql, qr, x, i << 1, l, m);
13     insert(ql, qr, x, i << 1 | 1, m, r);
14 }
15 void traversal(vector<int>& ans, int i=1, int l=0, int r=maxn){
16     int opcnt = 0;
17     for (auto val : arr[i])
18         if (DO_SOMETHING(val)) opcnt++;
19     if (r - l == 1) ans[l] = CALC_ANS();
20     else {
21         traversal(ans, i << 1, l, m);
22         traversal(ans, i << 1 | 1, m, r);
23     }
24     while (opcnt--) UNDO_SOMETHING();
25     arr[i].clear();
26 }
27 #undef m

```

4.6 Segment Tree Beats

f686aa

1// Author: Ian, <https://judge.yosupo.jp/submission/400861>

```

2 const int maxn=2e5+5;
3 const ll MX = 1e18+5;
4 const ll MN = -MX;
5 #define m ((l+r)>>1)
6 struct node {
7     ll sum, inc;
8     ll mn, smn; int mnc;
9     ll mx, smx; int mxc;
10    node(ll x=0): sum(x), inc(0),
11        mn(x), smn(MX), mnc(1),
12        mx(x), smx(MN), mxc(1) {}
13    void pull(int i);
14    void push(int i, int l, int r);
15 } a[(maxn+1)<<2];
16 void node::pull(int i) {
17     sum = a[i<<1].sum+a[i<<1|1].sum;
18     if (a[i<<1].mn == a[i<<1|1].mn) {
19         mn = a[i<<1].mn;
20         smn = min(a[i<<1].smn, a[i<<1|1].smn);
21         mnc = a[i<<1].mnc+a[i<<1|1].mnc;
22     } else {
23         if (a[i<<1].mn < a[i<<1|1].mn) {
24             mn = a[i<<1].mn;
25             smn = min(a[i<<1].smn, a[i<<1|1].mn);
26             mnc = a[i<<1].mnc;
27         } else {
28             mn = a[i<<1|1].mn;
29             smn = min(a[i<<1|1].smn, a[i<<1].mn);
30             mnc = a[i<<1|1].mnc;
31         }
32     }
33     if (a[i<<1].mx == a[i<<1|1].mx) {
34         mx = a[i<<1].mx;
35         smx = max(a[i<<1].smx, a[i<<1|1].smx);
36         mxc = a[i<<1].mxc+a[i<<1|1].mxc;
37     } else {
38         if (a[i<<1].mx > a[i<<1|1].mx) {
39             mx = a[i<<1].mx;
40             smx = max(a[i<<1].smx, a[i<<1|1].mx);
41             mxc = a[i<<1].mxc;
42         } else {
43             mx = a[i<<1|1].mx;
44             smx = max(a[i<<1|1].smx, a[i<<1].mx);
45             mxc = a[i<<1|1].mxc;
46         }
47     }
48 }

```

```

49 void updmn(int i, int len, ll v) {
50     a[i].sum += (v-a[i].mn)*a[i].mnc; a[i].mn = v;
51     if (len==1 || v>=a[i].mx)
52         a[i].mx = v, a[i].smx = MN;
53     else if (v>a[i].smx)
54         a[i].smx = v;
55 }
56 void updmx(int i, int len, ll v) {
57     a[i].sum -= (a[i].mx-v)*a[i].mxc; a[i].mx = v;
58     if (len==1 || v<=a[i].mn)
59         a[i].mn = v, a[i].smn = MX;
60     else if (v<a[i].smn)
61         a[i].smn = v;
62 }
63 void node::push(int i, int l, int r) {
64     if (r-l==1) return;
65     pair<int, int> ch[] = {{i<<1, m-l}, {i<<1|1, r-m}};
66     if (inc!=0) for (auto [j, len]: ch) {
67         a[j].sum += inc*len, a[j].inc += inc;
68         a[j].mx += inc, a[j].smx += inc;
69         a[j].mn += inc, a[j].smn += inc;
70     } inc = 0;
71     for (auto [j, len]: ch) {
72         if (a[j].mn < mn) updmn(j, len, mn);
73         if (a[j].mx > mx) updmx(j, len, mx);
74     }
75 }

```

```

72 }
73 void build(vector<ll>& v, int i=1, int l=0, int r=maxn) {
74     if ((int)v.size()<=l) return;
75     if (r-l==1) { a[i] = node(v[l]); return; }
76     build(v, i<<1, l, m);
77     build(v, i<<1|1, m, r);
78     a[i].pull(i);
79 }
80 void chmin(int ql, int qr, ll v, int i=1, int l=0, int r=maxn){
81     if (qr<=l || r<=ql || a[i].mx<=v) return;
82     if (ql<=l && r<=qr && a[i].smx<v) {updmx(i, r-l, v);return;}
83     a[i].push(i, l, r);
84     chmin(ql, qr, v, i<<1, l, m);
85     chmin(ql, qr, v, i<<1|1, m, r);
86     a[i].pull(i);
87 }
88 void chmax(int ql, int qr, ll v, int i=1, int l=0, int r=maxn){
89     if (qr<=l || r<=ql || a[i].mn>=v) return;
90     if (ql<=l && r<=qr && a[i].smn>v) {updmn(i, r-l, v);return;}
91     a[i].push(i, l, r);
92     chmax(ql, qr, v, i<<1, l, m);
93     chmax(ql, qr, v, i<<1|1, m, r);
94     a[i].pull(i);
95 }
96 void inc(int ql, int qr, ll v, int i=1, int l=0, int r=maxn){
97     if (qr<=l || r<=ql) return;
98     if (ql<=l && r<=qr) {
99         a[i].sum += v*(r-l);
100        a[i].mx += v, a[i].smx += v;
101        a[i].mn += v, a[i].smn += v;
102        a[i].inc += v;
103        return;
104    }
105    a[i].push(i, l, r);
106    inc(ql, qr, v, i<<1, l, m);
107    inc(ql, qr, v, i<<1|1, m, r);
108    a[i].pull(i);
109 }
110 ll qsum(int ql, int qr, int i=1, int l=0, int r=maxn) {
111     if (qr<=l || r<=ql) return 0;
112     if (ql<=l && r<=qr) return a[i].sum;
113     a[i].push(i, l, r);
114     return qsum(ql, qr, i<<1, l, m)+qsum(ql, qr, i<<1|1, m, r);
115 }
116 #undef m

```

5 DP

5.1 SOS DP

623a08

```

1// Author: Gino
2// Function: Solve problems that enumerates subsets of
3// subsets (3^n => n*2^n)
4 for (int msk = 0; msk < (1<<n); msk++) {
5     for (int i = 1; i <= n; i++) {
6         if (msk & (1<<(i-1))) {
7             dp[msk][i] = dp[msk][i-1] + dp[msk ^ (1<<(i-1))][i-1];
8         } else {
9             dp[msk][i] = dp[msk][i-1];
10        }
11    }
12 }

```

5.2 Divide and Conquer DP

d36c77

```

1/* Author: Simon Lindholm (License: CC0)
2 * Description: Given $a[i] = \min_{lo(i) \le k < hi(i)} (f(i, k))$ where the (minimal)
3 * optimal $k$ increases with $i$, computes $a[i]$ for $i = L..R-1$.
4 * Time: $O((N + (hi-lo)) \log N)$ */
5 struct DP { // Modify at will:
6     int lo(int ind) { return 0; }
7     int hi(int ind) { return ind; }
8     ll f(int ind, int k) { return dp[ind][k]; }
9     void store(int ind, int k, ll v) { res[ind] = pii(k, v); }
10 }
11 void rec(int L, int R, int LO, int HI) {
12     if (L >= R) return;
13     int mid = (L + R) >> 1;
14     pair<ll, int> best(LLONG_MAX, LO);
15     rep(k, max(LO, lo(mid)), min(HI, hi(mid)))
16         best = min(best, make_pair(f(mid, k), k));
17     store(mid, best.second, best.first);
18     rec(L, mid, LO, best.second+1);
19     rec(mid+1, R, best.second, HI);
20 }
21 void solve(int L, int R) { rec(L, R, INT_MIN, INT_MAX); }
22 }

```

5.3 Dynamic DP

- 適用情境： $dp_i = M_i \cdot dp_{i-1} \Rightarrow dp_i = M_i M_{i-1} \cdots M_1 dp_0$
- 當 M_i 需要動態修改，且 M_i 是廣義矩陣乘法：

$$C_{ij} = \bigoplus_k A_{ik} \otimes B_{kj}$$

- 滿足 $(\oplus, \otimes)$ 是半環 ($\otimes$ 對 $\oplus$ 有分配律、 $\otimes$ 和 $\oplus$ 有結合律、 $\oplus$ 有交換律)
- 此時便可用線段樹維護 $M_n M_{n-1} \dots M_1$ 的乘積。線段樹上的 pos 是 M_{pos} ，但 pull 時要 $\text{st}[\text{id}x] = \text{mul}(\text{st}[\text{cr}], \text{st}[\text{cl}])$

5.4 Convex Hull Trick

bb4a1c

```
1/**
2 * Author: Simon Lindholm (License: CC0, Source: own work)
3 * Container where you can add lines of the form kx+m,
4 * and query maximum values at points x.
5 * Useful for dynamic programming ('convex hull trick').
6 * Time: O(log N), Status: stress-tested */
7struct Line {
8    mutable ll k, m, p;
9    bool operator<(const Line& o) const { return k < o.k; }
10   bool operator<(ll x) const { return p < x; }
11};
12struct LineContainer : multiset<Line, less<>> {
13    // (for doubles, use inf = 1/.0, div(a,b) = a/b)
14    static const ll inf = LLONG_MAX;
15    ll div(ll a, ll b) { // floored division
16        return a / b - ((a ^ b) < 0 && a % b); }
17    bool isect(iterator x, iterator y) {
18        if (y == end()) return x->p = inf, 0;
19        if (x->k == y->k) x->p = x->m > y->m ? inf : -inf;
20        else x->p = div(y->m - x->m, x->k - y->k);
21        return x->p >= y->p;
22    }
23    void add(ll k, ll m) {
24        auto z = insert({k, m, 0}), y = z++, x = y;
25        while (isect(y, z)) z = erase(z);
26        if (x != begin() && isect(--x, y)) isect(x, y = erase(y));
27        while ((y = x) != begin() && (--x)->p >= y->p)
28            isect(x, erase(y));
29    }
30    ll query(ll x) {
31        auto l = *lower_bound(x);
32        return l.k * x + l.m;
33    }
34};
```

6 Graph

6.1 Max Clique

3a1fe5

```
1// max N = 64
2typedef unsigned long long ll;
3struct MaxClique {
4    ll nb[ N ], n, ans;
5    void init( ll _n ) {
6        n = _n;
7        for( int i = 0 ; i < n ; i ++ ) nb[ i ] = 0LLU;
8    }
9    void add_edge( ll _u , ll _v ){
10        nb[ _u ] |= ( 1LLU << _v );
11        nb[ _v ] |= ( 1LLU << _u );
12    }
13    void B( ll r , ll p , ll x , ll cnt , ll res ){
14        if( cnt + res < ans ) return;
15        if( p == 0LLU && x == 0LLU ){
16            if( cnt > ans ) ans = cnt;
17            return;
18        }
19        ll y = p | x; y &= -y;
20        ll q = p & ( ~nb[ int( log2( y ) ) ] );
21        while( q ){
22            ll i = int( log2( q & (-q) ) );
23            B( r | ( 1LLU << i ) , p & nb[ i ] , x & nb[ i ] ,
24                cnt + 1LLU , __builtin_popcountll( p &
25                    nb[ i ] ) );
26            q &= ~( 1LLU << i );
27            p &= ~( 1LLU << i );
28            x |= ( 1LLU << i );
29        }
30    }
31    int solve(){
32        ans = 0;
33        ll _set = 0;
34        if( n < 64 ) _set = ( 1LLU << n ) - 1;
35        else{
36            for( ll i = 0 ; i < n ; i ++ ) _set |= ( 1LLU << i );
37        }
38        B( 0LLU , _set , 0LLU , 0LLU , n );
39        return ans;
40    }
41};
```

6.2 Bellman-Ford

92b21f

```
1// Author: Gino
2// n, m = #(vertices), #(edges), and vertices are 1-based
3// 1. BellmanFord bf(G, n, m);
4// 2-1: bf.calcDis(s);
5// => bf.dis[u] := shortest dis from s to u
6// => bf.dis[u] := LINF (s can't reach u)
7// => bf.dis[u] := -LINF (dis[u] can be arbitrary small)
8// 2-2: bf.findNegCycle();
9// => false (if no neg cycle)
10// => true (has neg cycle & gives an example: bf.neg_cycle)
11// Time: O(VE), Space: O(V + E)
12const ll LINF = 4e18;
13struct BellmanFord {
14    const vector<vector<pair<int, ll>>>& G;
15    int n, m; // #(vertices), #(edges)
16    BellmanFord(const auto& G, int n, int m):G(G), n(n), m(m) {}
17    vector<ll> dis; vector<int> nth_relax, pa;
18    void run_bf(const auto& src) {
19        dis.assign(n+1, LINF);
20        nth_relax.assign(n+1, 0); pa.assign(n+1, -1);
21        for (auto& s : src) dis[s] = 0;
22        for (int rlx = 1; rlx <= n; rlx++) {
23            for (int u = 1; u <= n; u++) {
24                if (dis[u] == LINF) continue; // !important
25                for (auto& [v, w] : G[u]) {
26                    if (dis[v] > dis[u] + w) {
27                        dis[v] = dis[u] + w; pa[v] = u;
28                        if (rlx == n) nth_relax[v] = 1;
29                    } } } } // 5 brackets
30    }
31    void calcDis(int s) {
32        run_bf(vector<int>{s}); queue<int> q;
33        for (int u=1; u<=n; u++) if (nth_relax[u]) q.push(u);
34        while (!q.empty()) { int u = q.front(); q.pop();
35            for (auto& [v, w] : G[u]) {
36                if (!nth_relax[v]) {
37                    nth_relax[v] = 1; q.push(v);
38                } } }
39        for (int u=1; u<=n; u++) if (nth_relax[u]) dis[u] = -LINF;
40    }
41    vector<int> neg_cycle;
42    bool findNegCycle() {
43        auto src = views::iota(1, n + 1); run_bf(src);
44        auto it = ranges::find_if(src,
45            [&](int s){ return nth_relax[s]; });
46        if (it == src.end()) return false;
47        int ptr = *it; for (int i=0; i<n; i++) ptr = pa[ptr];
48        neg_cycle.clear(); int cur = ptr;
49        while (true) {
50            neg_cycle.emplace_back(cur);
51            if (cur == ptr && neg_cycle.size() > 1) break;
52            cur = pa[cur];
53        }
54        ranges::reverse(neg_cycle); return true;
55    }
56};
```

6.3 System of Difference Constraints

fe55f9

```
1vector<vector<pair<int, ll>>> G;
2void add(int u, int v, ll w) { G[u].push_back({v, w}); }
```

- $x_u - x_v \leq c \Rightarrow \text{add}(v, u, c)$
- $x_u - x_v \geq c \Rightarrow \text{add}(u, v, -c)$
- $x_u - x_v = c \Rightarrow \text{add}(v, u, c), \text{add}(u, v, -c)$
- $x_u \geq c \Rightarrow \text{add super vertex } x_0 = 0, \text{ then } x_u - x_0 \geq c \Rightarrow \text{add}(u, 0, -c)$
- Don't for get non-negative constraints for every variable if specified implicitly.
- Interval sum $\Rightarrow$ Use prefix sum to transform into differential constraints. Don't for get $S_{i+1} - S_i \geq 0$ if x_i needs to be non-negative.
- $x_u/x_v \leq c \Rightarrow \log x_u - \log x_v \leq \log c$

6.4 Graph Girth

Run BFS for every node, when encountered non-BFS-tree edge, update answer (min cycle length) with $\text{dis}[u] + \text{dis}[v] + 1$. Time $O(VE)$.

6.5 Euler Trail

11c393

```
1// Author: kactl (Simon Lindholm), wrapped by Gino
2// Vertices are 1-based, Edge ID are 0-based
3// 1. EulerWalk euler(n, true(directed) / false(undirected));
4// 2. euler.addEdge(u, v);
5// 3. int result = euler.solve();
6// => -1: nothing (euler.path, euler.path_edges = {} )
7// => 1: Euler trail,
8// => 2: Euler circuit
9//     euler.path = {u_1, ..., u_{m+1}}
10//     euler.path_edges = {e_1, ..., e_m}
11// Time: O(V + E), Space: O(V + E)
```

```

12 // Test: V, E <= 2e5, 99ms
13 struct EulerWalk {
14     int n, m = 0; bool dir;
15     vector<vector<pii>> G; vi deg;
16     EulerWalk(int n, bool dir) :
17         n(n), dir(dir), G(n + 1), deg(n + 1) {}
18     void addEdge(int u, int v) {
19         G[u].push_back({v, m});
20         if (!dir) G[v].push_back({u, m});
21         deg[u]++, deg[v] += dir ? -1 : 1; m++;
22     }
23     vi path, path_edges;
24     void walk(int src) {
25         path.clear(); path_edges.clear();
26         vi its(n + 1), visE(m);
27         function<void(int, int)> dfs = [&](int u, int e_in) {
28             while (its[u] < sz(G[u])) {
29                 auto [v, e] = G[u][its[u]++];
30                 if (visE[e]) continue;
31                 visE[e] = 1;
32                 dfs(v, e);
33             }
34             path.push_back(u);
35             if (e_in != -1) path_edges.push_back(e_in);
36         };
37         dfs(src, -1);
38         if (sz(path) != m + 1) {
39             path.clear(); path_edges.clear(); return;
40         }
41         ranges::reverse(path); ranges::reverse(path_edges);
42     }
43     int solve() {
44         int s = -1, odd = 0, src = 0, dst = 0;
45         for (int u = 1; u <= n; u++) {
46             if (!dir && (deg[u] & 1)) odd++, s = u;
47             if (dir && deg[u] == 1) s = u, src++;
48             if (dir && deg[u] == -1) dst++;
49             if (dir && abs(deg[u]) > 1) return -1;
50         }
51         if (!dir && odd != 0 && odd != 2) return -1;
52         if (dir && !(src == 0 && dst == 0)
53             || (src == 1 && dst == 1)) return -1;
54         if (s == -1) for (int u = 1; u <= n; u++)
55             if (!G[u].empty()) { s = u; break; }
56         if (s == -1) s = 1;
57         walk(s);
58         return path.empty() ? -1 :
59             path.front() == path.back() ? 2 : 1;
60     };

```

6.6 Vertex BCC (Round Square Tree)

e85b0a

```

1 // Author: Ian, https://judge.yosupo.jp/submission/399308
2 // Vertex BCC (Round Square Tree) 0-based; Edge ID 0-based
3 // 1. BCC bcc(n); // n = #(vertices)
4 // 2. bcc.add_edge(u, v);
5 // 3. bcc.build();
6 // => bcc[id]: vertices in bcc `id` (square node n+id in T)
7 // => T[id]: tree adjacency; square nodes are n..n+ncnt-1
8 // => is_cut(x): whether x is a cut vertex
9 // => bcc_id(u, v): square node containing tree-edge (u, v)
10 struct BCC {
11     int n, m, t, ncnt;
12     vector<vector<pii>> G;
13     vector<vector<int>> T, bcc;
14     vector<int> dep, low, pa2, dep2, s;
15     void add_edge(int u, int v) {
16         G[u].eb(v, m), G[v].eb(u, m++);
17     }
18     void dfs(int x, int f) {
19         if (~dep[x]) return;
20         dep[x] = low[x] = t++;
21         s.push_back(x);
22         for (auto [y, e]: G[x]) if (e != f) {
23             if (dep[y] == -1) {
24                 dfs(y, e), low[x] = min(low[x], low[y]);
25                 if (low[y] >= dep[x]) {
26                     int id = n + ncnt++, p;
27                     bcc.resize(bcc.size() + 1);
28                     do {
29                         p = s.back(), s.pop_back();
30                         T[id].push_back(p), T[p].push_back(id);
31                         bcc.back().push_back(p);
32                     } while (p != y);
33                     T[id].push_back(x), T[x].push_back(id);
34                     bcc.back().push_back(x);
35                 } else low[x] = min(low[x], dep[y]);
36             }
37         }
38         void dfs2(int x, int p) {
39             dep2[x] = ~p ? dep2[p] + 1 : 0, pa2[x] = p;
40             for (auto y: T[x]) if (y != p) dfs2(y, x);
41         }

```

```

39 bool is_cut(int x) { return (int)T[x].size() != 1; }
40 int bcc_id(int u, int v) {
41     return pa2[dep2[u] < dep2[v] ? v : u] - n;
42 }
43 void build() {
44     for (int i = 0; i < n; i++) if (dep[i] == -1) {
45         if (G[i].empty()) { // isolated vertex: singleton bcc
46             dep[i] = low[i] = t++;
47             int id = n + ncnt++;
48             bcc.push_back({i});
49             T[id].push_back(i), T[i].push_back(id);
50             else dfs(i, -1);
51             dfs2(i, -1);
52         }
53     }
54     BCC(int n): n(n), m(0), t(0), ncnt(0), G(n), T(2*n),
55     dep(n, -1), low(n), pa2(2*n), dep2(2*n) {}

```

6.7 Edge BCC

26729d

```

1 // Author: Ian, https://judge.yosupo.jp/submission/399295
2 // Edge BCC, 0-based; Edge ID 0-based
3 // 1. EBCC ebcc(n); // n = #(vertices)
4 // 2. ebcc.add_edge(u, v);
5 // 3. ebcc.build();
6 // => bcc[i]: each edge bcc
7 // => bccn[x]: in which bcc is x
8 // => isbr[e]: whether edge e is a bridge
9 struct EBCC {
10     int n, m, t, ncnt;
11     vector<vector<pii>> G;
12     vector<vector<int>> bcc;
13     vector<bool> isbr;
14     vector<int> dep, low, bccn, s;
15     EBCC(int n): n(n), m(0), t(0), ncnt(0), G(n),
16     dep(n, -1), low(n), bccn(n) {}
17     void add_edge(int u, int v) {
18         G[u].eb(v, m), G[v].eb(u, m++);
19     }
20     void dfs(int x, int f) {
21         if (~dep[x]) return;
22         dep[x] = low[x] = t++;
23         s.push_back(x);
24         for (auto [y, e]: G[x]) if (e != f) {
25             if (dep[y] == -1) {
26                 dfs(y, e), low[x] = min(low[x], low[y]);
27             } else
28                 low[x] = min(low[x], dep[y]);
29         }
30         if (dep[x] == low[x]) {
31             if (~f) isbr[f] = true;
32             bcc.resize(bcc.size() + 1);
33             int p; do {
34                 bccn[p = s.back()] = ncnt;
35                 s.pop_back();
36                 bcc.back().push_back(p);
37             } while (p != x); ncnt++;
38         }
39         void build() {
40             isbr.assign(m, false);
41             for (int i = 0; i < n; i++) dfs(i, -1);
42         }

```

6.8 Kth Shortest Path

34bacd

```

1 // time: O(|E| lg |E| + |V| lg |V| + K)
2 // memory: O(|E| lg |E| + |V|)
3 struct KSP { // 1-base
4     struct nd {
5         int u, v; ll d;
6         nd(int ui=0, int vi=0, ll di=INF) { u=ui; v=vi; d=di; }
7     };
8     struct heap { nd* edge; int dep; heap* chd[4]; };
9     static int cmp(heap* a, heap* b) {
10         return a->edge->d > b->edge->d;
11     }
12     struct node {
13         int v; ll d; heap* H; nd* E;
14         node() {}
15         node(ll _d, int _v, nd* _E) { d=_d; v=_v; E=_E; }
16         node(heap* _H, ll _d) { H=_H; d=_d; }
17         friend bool operator<(node a, node b) {
18             return a.d > b.d;
19         }
20     };
21     int n, k, s, t, dst[N]; nd* nxt[N];
22     vector<nd*> g[N], rg[N]; heap* nullNd, *head[N];
23     void init(int _n, int _k, int _s, int _t) {
24         n=_n; k=_k; s=_s; t=_t;
25         for (int i=1; i<=n; i++) {
26             g[i].clear(); rg[i].clear();
27             nxt[i]=NULL; head[i]=NULL; dst[i]=-1;
28         }
29     }
30     void addEdge(int ui, int vi, ll di) {
31         nd* e=new nd(ui, vi, di);
32         g[ui].push_back(e); rg[vi].push_back(e);

```

```

30 }
31 queue<int> dfsQ;
32 void dijkstra(){
33     while(dfsQ.size()) dfsQ.pop();
34     priority_queue<node> Q; Q.push(node(0,t,NULL));
35     while (!Q.empty()){
36         node p=Q.top(); Q.pop(); if(dst[p.v]==-1)continue;
37         dst[p.v]=p.d; nxt[p.v]=p.E; dfsQ.push(p.v);
38         for(auto e:rg[p.v]) Q.push(node(p.d+e->d,e->u,e));
39     }
40     heap* merge(heap* curNd,heap* newNd){
41         if(curNd==nullNd) return newNd;
42         heap* root=new heap;memcpy(root,curNd,sizeof(heap));
43         if(newNd->edge->d<curNd->edge->d){
44             root->edge=newNd->edge;
45             root->chd[2]=newNd->chd[2];
46             root->chd[3]=newNd->chd[3];
47             newNd->edge=curNd->edge;
48             newNd->chd[2]=curNd->chd[2];
49             newNd->chd[3]=curNd->chd[3];
50         }
51         if(root->chd[0]->dep<root->chd[1]->dep)
52             root->chd[0]=merge(root->chd[0],newNd);
53         else root->chd[1]=merge(root->chd[1],newNd);
54         root->dep=max(root->chd[0]->dep,
55                     root->chd[1]->dep)+1;
56         return root;
57     }
58     vector<heap*> V;
59     void build(){
60         nullNd=new heap; nullNd->dep=0; nullNd->edge=new nd;
61         fill(nullNd->chd,nullNd->chd+4,nullNd);
62         while(not dfsQ.empty()){
63             int u=dfsQ.front(); dfsQ.pop();
64             if(!nxt[u]) head[u]=nullNd;
65             else head[u]=head[nxt[u]->v];
66             V.clear();
67             for(auto& e:g[u]){
68                 int v=e->v;
69                 if(dst[v]==-1) continue;
70                 e->d+=dst[v]-dst[u];
71                 if(nxt[u]!=e){
72                     heap* p=new heap;fill(p->chd,p->chd+4,nullNd);
73                     p->dep=1; p->edge=e; V.push_back(p);
74                 }
75             }
76             if(V.empty()) continue;
77             make_heap(V.begin(),V.end(),cmp);
78 #define L(X) ((X<<1)+1)
79 #define R(X) ((X<<1)+2)
80             for(size_t i=0;i<V.size();i++){
81                 if(L(i)<V.size()) V[i]->chd[2]=V[L(i)];
82                 else V[i]->chd[2]=nullNd;
83                 if(R(i)<V.size()) V[i]->chd[3]=V[R(i)];
84                 else V[i]->chd[3]=nullNd;
85             }
86             head[u]=merge(head[u],V.front());
87         }
88     }
89     vector<ll> ans;
90     void first_K(){
91         ans.clear(); priority_queue<node> Q;
92         if(dst[s]==-1) return;
93         ans.push_back(dst[s]);
94         if(head[s]!=nullNd)
95             Q.push(node(head[s],dst[s]+head[s]->edge->d));
96         for(int _=1;_<k and not Q.empty();_++){
97             node p=Q.top();q; Q.pop(); ans.push_back(p.d);
98             if(head[p.H->edge->v]!=nullNd){
99                 q.H=head[p.H->edge->v]; q.d=p.d+q.H->edge->d;
100                 Q.push(q);
101             }
102             for(int i=0;i<4;i++){
103                 if(p.H->chd[i]!=nullNd){
104                     q.H=p.H->chd[i];
105                     q.d=p.d-p.H->edge->d+p.H->chd[i]->edge->d;
106                     Q.push(q);
107                 }
108             }
109         }
110     }
111 } solver;

```

6.9 SCC - Tarjan

7a063d

```

1 // Author: Ian, https://judge.yosupo.jp/submission/399291
2 // Tarjan SCC, 0-based
3 // 1. SCC scc(n); // n = #(vertices)
4 // 2. Fill in adj list G
5 // 3. scc.build()

```

```

6 // => scc[i]: each scc
7 // => sccn[x]: in which scc is x
8 struct SCC {
9     const int inf = 1e9+5;
10    int n, t, ncnt;
11    vector<vector<int>> G, scc;
12    vector<bool> ins;
13    vector<int> sccn, dfn, low, s;
14    SCC(int n): n(n), t(0), ncnt(0), G(n),
15        ins(n, false), sccn(n), dfn(n, -1), low(n, inf) {}
16    void dfs(int x) {
17        if (~dfn[x]) return;
18        dfn[x] = low[x] = t++;
19        s.push_back(x), ins[x] = true;
20        for (auto i: G[x])
21            if (dfs(i), ins[i])
22                low[x] = min(low[x], low[i]);
23        if (dfn[x] == low[x]) {
24            scc.resize(scc.size()+1);
25            int p; do {
26                ins[p = s.back()] = false;
27                s.pop_back(); sccn[p] = ncnt;
28                scc.back().push_back(p);
29            } while (p != x); ncnt++;
30        }
31    }
32    void build() { for (int i=0; i<n; i++) dfs(i); }
33 };

```

6.10 2SAT

130351

```

1 // Author: Ian, CRYPTOGRAPHER
2 struct TwoSAT: SCC {
3     TwoSAT(int n): SCC(2*n) {}
4     // (var a == na) v (var b == nb)
5     void add_disjunction(int a,int na,int b,int nb) {
6         a = 2*a^na, b = 2*b^nb;
7         G[a^1].push_back(b);
8         G[b^1].push_back(a);
9     }
10    vector<int> solve() {
11        build(); vector<int> assignment(n/2,0);
12        for(int i=0; i<n/2; i++) {
13            if (sccn[2*i] == sccn[2*i^1]) return {};
14            assignment[i] = sccn[2*i] > sccn[2*i^1];
15        } return assignment;
16    };

```

7 Tree

7.1 Tree Isomorphism (Rooted Trees)

f3f029

```

1 // Author: Gino
2 // Checks if 2 rooted trees are isomorphic
3 // Time: O(V log V)
4 // vector<vector<int>> G1, G2;
5 // int root_1, root_2;
6 map<vector<int>, int> dict;
7 int encode(const auto& G, int u, int pa = -1) {
8     vector<int> codes;
9     for (auto& v : G[u])
10         if (v != pa)
11             codes.emplace_back(encode(G, v, u));
12     ranges::sort(codes);
13     auto [it, _] = dict.try_emplace(codes, dict.size());
14     return it->second;
15 }
16 bool isomorphic() {
17     dict.clear(); dict[{}] = 0;
18     return encode(G1, root_1) == encode(G2, root_2);
19 }

```

7.2 Tree Isomorphism (Unrooted Trees)

Find the centroid(s) of T_1, T_2 .
 Case 1: T_1, T_2 have different number of centroids $\rightarrow$ NO
 Case 2: T_1 has centroid c_1, T_2 has centroid c_2
 $\rightarrow$ rooted_isomorphic(c_1, c_2)
 Case 3: T_1 has centroids c_1, c'_1, T_2 has centroids c_2, c'_2
 $\rightarrow$ rooted_isomorphic(c_1, c_2) || rooted_isomorphic(c'_1, c'_2)

7.3 Heavy Light Decomposition

53e45c

```

1 // Author: Ian, https://judge.yosupo.jp/submission/399317
2 void segbuild(vector<int>&v);
3 void segmodify(int p, int k);
4 int segquery(int ql, int qr);
5 // Insert [ql, qr] segment tree here
6 template<class T=int> struct HLD {
7     int n, cnt;
8     vector<int> d, f, sz, son, top, dfn;
9     HLD(int n): n(n), cnt(0), d(n, 0), f(n, 0), sz(n, 1),
10         son(n, -1), top(n, 0), dfn(n, -1) {}
11     void dfs1(int x, int p) {

```

```

12 for (auto i: e[x]) if (i != p) {
13     d[i] = d[x]+1, f[i] = x;
14     dfs1(i, x), sz[x] += sz[i];
15     if (son[x] == -1 || sz[son[x]] < sz[i])
16         son[x] = i;
17 }
18 void dfs2(int x, int t) {
19     dfn[x] = cnt++, top[x] = t;
20     if (son[x] == -1) return;
21     dfs2(son[x], t);
22     for (auto i: e[x])
23         if (!dfn[i]) dfs2(i, i);
24 }
25 void build(const vector<T> &v) {
26     dfs1(0, 0); dfs2(0, 0);
27     vector<T> dfnv(v.size());
28     for (int i=0; i<n; i++)
29         dfnv[dfn[i]] = v[i];
30     segbuild(dfnv); }
31 void modify(int p, T v) { segmodify(dfn[p], v); }
32 T query(int a, int b) {
33     auto aggr = [](int x, int y) { return max(x, y); };
34     T ret = 0;
35     while (top[a] != top[b]) {
36         if (d[top[a]] > d[top[b]]) swap(a, b);
37         ret = aggr(ret, segquery(dfn[top[b]], dfn[b]+1));
38         b = f[top[b]];
39     }
40     if (dfn[a] > dfn[b]) swap(a, b);
41     return aggr(ret, segquery(dfn[a], dfn[b]+1));
42 }
43 };

```

7.4 Virtual Tree

172166

```

1 // Author: std_abs
2 // need lca, in, out
3 vector<pii> virtual_tree(vector<int> &v) {
4     auto cmp = [&](int x, int y) { return in[x] < in[y]; };
5     sort(all(v), cmp);
6     for (int i = 1; i < sz(v); ++i)
7         v.pb(lca(v[i-1], v[i]));
8     sort(all(v), cmp);
9     v.resize(unique(all(v)) - v.begin());
10    vector<int> stk(1, v[0]);
11    vector<pii> res;
12    for (int i = 1; i < sz(v); ++i) {
13        int x = v[i];
14        while (out[stk.back()] < out[x]) stk.pop_back();
15        res.emplace_back(stk.back(), x), stk.pb(x);
16    }
17    return res;
18 }

```

8 Matching

8.1 Bipartite Matching

f42921

```

1 // Author: Gino
2 // Function: Max Bipartite Matching in O(V sqrt(E))
3 //> hk.init(nx, ny) -> hk.add(x, y (+nx))
4 //> hk.max_matching(): the matching plan stores in mx, my
5 //> hk.min_vertex_cover(): vertex cover plan stores in vcover
6 // (!) vertices are 0-based: X = [0, nx), Y = [nx, nx+ny)
7 #define pb emplace_back
8 struct HopcroftKarp {
9     int n, nx, ny; vector<vector<int>> G; vector<int> mx, my;
10    void init(int nx, int ny): nx(nx), ny(ny), n(nx + ny) {
11        G.assign(n, vector<int>()); }
12    void add(int x, int y) { G[x].pb(y); G[y].pb(x); }
13    int max_matching() {
14        vector<int> dis, vis;
15        mx.assign(n, -1); my.assign(n, -1);
16        function<bool(int)> dfs = [&](int x) {
17            vis[x] = 1;
18            for (int y: G[x]) {
19                int p = my[y];
20                if (p == -1 ||
21                    (dis[p] == dis[x] + 1 && !vis[p] && dfs(p)))
22                    return mx[x] = y, my[y] = x, true;
23            }
24            return false;
25        };
26        while (true) {
27            dis.assign(n, -1);
28            queue<int> q;
29            for (int x = 0; x < nx; x++)
30                if (mx[x] == -1) dis[x] = 0, q.push(x);
31            while (!q.empty()) {
32                int x = q.front(); q.pop();
33                for (int y: G[x])
34                    if (my[y] != -1 && dis[my[y]] == -1)

```

```

35                dis[my[y]] = dis[x] + 1, q.push(my[y]);
36            }
37            vis.assign(n, 0);
38            bool found = false;
39            for (int x = 0; x < nx; x++)
40                if (mx[x] == -1 && dfs(x)) found = true;
41            if (!found) break;
42        }
43        int ans = 0;
44        for (int x = 0; x < nx; x++) if (mx[x] != -1) ans++;
45        return ans;
46    }
47    vector<int> vcover;
48    int min_vertex_cover() {
49        int ans = max_matching(); vector<int> vis(n, 0);
50        function<void(int)> dfs = [&](int x) {
51            vis[x] = true;
52            for (int y: G[x]) {
53                if (y == mx[x] || my[y] == -1 || vis[y]) continue;
54                vis[y] = true;
55                dfs(my[y]);
56            }
57        };
58        for (int x = 0; x < nx; x++) if (mx[x] == -1) dfs(x);
59        vcover.clear();
60        for (int x=0; x < nx; x++) if (!vis[x]) vcover.pb(x);
61        for (int y=nx; y < nx+ny; y++) if (vis[y]) vcover.pb(y);
62        return ans;
63    } hk;

```

8.2 Bipartite Weighted Matching

5933aa

```

1 // Author: ckiseki, n = #(left vertices) = #(right vertices)
2 // left, right vertices labeled 1 ~ n separately
3 // 1. build 1-based matrix G of size (n + 1) * (n + 1)
4 // G[u][v] := weight between (left u, right v)
5 // <!=> if not need perfect matching
6 // => set weights of all negative edges to 0
7 // 2. construct (solve at same time): KM km(n, G);
8 // => km.ans (max perfect weight sum)
9 // => km.fl[u] (left u -> right v)
10 // => km.fr[v] (right v -> left u)
11 // Time: O(V^3), Space: O(V^2), Test: V <= 500, 243ms
12 struct KM { // maximize, test @ UOJ 80
13     int n, l, r; ll ans; // fl and fr are the match
14     vector<ll> hl, hr; vector<int> fl, fr, pre, q;
15     void bfs(const auto &w, int s) {
16         vector<int> vl(n + 1), vr(n + 1);
17         vector<ll> slk(n + 1, LINF);
18         l = r = 0; vr[q[r++] = s] = true;
19         auto check = [&](int x) -> bool {
20             if (vl[x] || slk[x] > 0) return true;
21             vl[x] = true; slk[x] = LINF;
22             if (fl[x] != -1) return (vr[q[r++] = fl[x]] = true);
23             while (x != -1) swap(x, fr[fl[x] = pre[x]]);
24             return false;
25         };
26         while (true) {
27             while (l < r)
28                 for (int x = 1, y = q[l++]; x <= n; ++x) if (!vl[x])
29                     if (ll val = hl[x]+hr[y]-w[x][y], val < slk[x]) {
30                         slk[x] = val;
31                         if (pre[x] = y, !check(x)) return;
32                     }
33             ll d = LINF;
34             for (int x = 1; x <= n; ++x) d = min(d, slk[x]);
35             for (int x = 1; x <= n; ++x)
36                 vl[x] ? hl[x] += d : slk[x] -= d;
37             for (int x = 1; x <= n; ++x) if (vr[x]) hr[x] -= d;
38             for (int x = 1; x <= n; ++x) if (!check(x)) return;
39         }
40         KM(int n_, const auto &w) : n(n_), ans(0),
41             hl(n+1), hr(n+1), fl(n+1, -1), fr(fl), pre(n+1), q(n+1) {
42             for (int i = 1; i <= n; ++i) {
43                 hl[i] = -LINF;
44                 for (int j=1; j<=n; ++j) hl[i]=max(hl[i], (ll)w[i][j]);
45             }
46             for (int i = 1; i <= n; ++i) bfs(w, i);
47             for (int i = 1; i <= n; ++i) ans += w[i][fl[i]];
48         }
49     };

```

8.3 General Matching

93f948

```

1 // Author: ckiseki
2 // 0. build 1-based graph vector<vector<int>> G(n + 1);
3 // 1. construct (solve at same time):
4 // GeneralMatching M(G, n); => M.ans
5 // status: M.match[x] (== -1 if not matched, 1 <= x <= n)
6 // Time: O(V^3), Space: O(V + E), Test: V <= 500, 11ms
7 struct GeneralMatching {
8     queue<int> q; int ans, n;

```

```

9 vector<int> fa, s, v, pre, match;
10 int Find(int u) {
11     return u == fa[u] ? u : fa[u] = Find(fa[u]); }
12 int LCA(int x, int y) {
13     static int tk = 0; tk++; x = Find(x); y = Find(y);
14     for (; swap(x, y)) if (x != 0) {
15         if (v[x] == tk) return x;
16         v[x] = tk;
17         x = Find(pre[match[x]]);
18     } }
19 void Blossom(int x, int y, int l) {
20     for (; Find(x) != l; x = pre[y]) {
21         pre[x] = y, y = match[x];
22         if (s[y] == 1) q.push(y), s[y] = 0;
23         for (int z : {x, y}) if (fa[z] == z) fa[z] = l;
24     } }
25 bool Bfs(auto &&g, int r) {
26     iota(all(fa), 0); ranges::fill(s, -1);
27     q = queue<int>(); q.push(r); s[r] = 0;
28     for (; !q.empty(); q.pop()) {
29         for (int x = q.front(); int u : g[x])
30             if (s[u] == -1) {
31                 if (pre[u] = x, s[u] = 1, match[u] == 0) {
32                     for (int a = u, b = x, last;
33                          b != 0; a = last, b = pre[a])
34                         last = match[b], match[b] = a, match[a] = b;
35                     return true;
36                 }
37                 q.push(match[u]); s[match[u]] = 0;
38             } else if (!s[u] && Find(u) != Find(x)) {
39                 int l = LCA(u, x);
40                 Blossom(x, u, l); Blossom(u, x, l);
41             }
42     }
43     return false;
44 }
45 GeneralMatching(auto &&g, int n_) : ans(0), n(n_),
46     fa(n+1), s(n+1), v(n+1), pre(n+1, 0), match(n+1, 0) {
47     for (int x = 1; x <= n; ++x)
48         if (match[x] == 0) ans += Bfs(g, x);
49     for (int x = 1; x <= n; ++x)
50         if (match[x] == 0) match[x] = -1;
51 } };

```

9 Flow

9.1 Flow Methods

c5090e

```

1 // Author: CRyptoGRapheR (some modified by Gino)
2 Maximize  $c^T x$  subject to  $Ax \leq b, x \geq 0$ ;
3 with the corresponding symmetric dual problem,
4 Minimize  $b^T y$  subject to  $A^T y \geq c, y \geq 0$ .
5
6 Maximize  $c^T x$  subject to  $Ax \leq b$ ;
7 with the corresponding asymmetric dual problem,
8 Minimize  $b^T y$  subject to  $A^T y = c, y \geq 0$ .
9
10 Maximize  $\sum x$  subject to  $x_i + x_j \leq A_{ij}, x \geq 0$ ;
11  $\Rightarrow$  Maximize  $\sum x$  subject to  $x_i + x_j \leq A_{ij}$ ;
12  $\Rightarrow$  Minimize  $A^T y = \sum A_{ij} y_{ij}$  subject to for all  $v$ ,
13      $\sum_{i=v \text{ or } j=v} y_{ij} = 1, y_{ij} \geq 0$ 
14  $\Rightarrow$  possible optimal solution:  $y_{ij} = \{0, 0.5, 1\}$ 
15  $\Rightarrow y' = 2y: \sum_{i=v \text{ or } j=v} y'_{ij} = 2, y'_{ij} = \{0, 1, 2\}$ 
16  $\Rightarrow$  Minimum Bipartite perfect matching/2 ( $V_1=X, V_2=X, E=A$ )
17
18 General Graph:
19 |Max Ind. Set| + |Min Vertex Cover| = |V|
20 |Max Ind. Edge Set| + |Min Edge Cover| = |V|
21
22 Bipartite Graph:
23 |Max Ind. Set| = |Min Edge Cover|
24 |Max Ind. Edge Set| = |Min Vertex Cover|
25
26 To reconstruct the minimum vertex cover, dfs from each
27 unmatched vertex on the left side and with unused edges
28 only. Equivalently, dfs from source with unused edges
29 only and without visiting sink. Then, a vertex is
30 chosen iff. it is on the left side and without visited
31 or on the right side and visited through dfs.
32
33 Minimum Weighted Bipartite Edge Cover:
34 Construct new bipartite graph with  $n+m$  vertices on each
35 side:
36 for each vertex  $u$ , duplicate a vertex  $u'$  on the other side
37 for each edge  $(u,v,w)$ , add edges  $(u,v,w)$  and  $(v',u',w)$ 
38 for each vertex  $u$ , add edge  $(u,u',2w)$  where  $w$  is min edge
39 connects to  $u$ 
40 then the answer is the minimum perfect matching of the new
41 graph (KM)
42
43 Maximum density subgraph (  $\sum W_e + \sum W_v$  ) / |V|
44
45 Binary search on answer:

```

```

40 For a fixed  $D$ , construct a Max flow model as follow:
41 Let  $S$  be Sum of all weight( or inf)
42 1. from source to each node with  $cap = S$ 
43 2. For each  $(u,v,w)$  in  $E$ ,  $(u \rightarrow v, cap=w), (v \rightarrow u, cap=w)$ 
44 3. For each node  $v$ , from  $v$  to sink with  $cap = S + 2 * D - \deg[v] - 2 * (W \text{ of } v)$ 
45 where  $\deg[v] = \sum \text{weight of edge associated with } v$ 
46 If  $\text{maxflow} < S * |V|$ ,  $D$  is an answer.
47
48 Requiring subgraph: all vertex can be reached from source
49 with
50 edge whose  $cap > 0$ .
51
52 Maximum closed subgraph
53 1. connect source with positive weighted
54     vertex(capacity=weight)
55 2. connect sink with negative weighted vertex(capacity=-
56     weight)
57 3. make capacity of the original edges = inf
58 4. ans = sum(positive weighted vertex weight) - (max flow)
59
60 (Node-disjoint) Min DAG Path Cover (用最少路徑覆蓋所有點)
61 Node disjoint: 拆出來的路徑不能共用同一個點
62 將一個點  $u$  裂成  $u_+$  和  $u_-$ , 代表進入和出去
63 對於一條邊  $(u, v)$  建邊  $u_- \Rightarrow v_+$ 
64 1.  $+$ 點們和  $-$ 點們形成一張二分圖
65 2. 最差的答案是  $n$ , 代表每個點自己一個點就是一條路徑
66 3. 只要一組  $(u_-, v_+)$  匹配成功那對應到的答案恰好會  $-1$ 
67  $\ggg$  ans =  $n$  - 這張二分圖的最大匹配
68
69 General DAG Path Cover
70 跟 Node-disjoint 版本差在點可以被很多條路共用
71 建邊方式 Node-disjoint 差別在條件比較鬆
72 Node-disjoint:  $u_- \Rightarrow v_+$  只能在  $(u, v)$  有邊時建
73 General:  $u_- \Rightarrow v_+$  在  $u$  能走到  $v$  的時候就建
74
75 Dilworth Theorem
76 反鏈：一些節點的集合，滿足這些節點互相無法抵達
77 最大反鏈 = 最小 General DAG Path Cover
78
79 Min Cut reconstruction (after running max flow  $s \rightarrow t$ ):
80 From  $s$ , BFS/DFS through residual edges with remaining
81 capacity  $> 0$ , marking reached vertices as visited.
82 The cut set is every original edge  $(u, v)$  with  $u$  visited
83 and  $v$  not visited; its capacity sum equals the max flow.
84
85 Bipartite Matching reconstruction (after running max flow
86 on source  $\rightarrow X \rightarrow Y \rightarrow$  sink model):
87 For each edge  $(x, y)$  between the  $X$ -side and  $Y$ -side, it is
88 part of the matching iff. its residual capacity is 0
89 (i.e. it is saturated).
90
91 Max/Min Flow with Lower Bound (Circulation Problem):
92 1. Construct super source  $S$  and super sink  $T$ .
93 2. For each edge  $(x, y, l, u)$ , connect  $x \rightarrow y$  with capacity
94      $u - l$ .
95 3. For each vertex  $v$ , let  $\text{in}(v) = (\text{sum of incoming lower}$ 
96      $\text{bounds})$ 
97     - (sum of outgoing lower bounds).
98 4. If  $\text{in}(v) > 0$ , connect  $S \rightarrow v$  with capacity  $\text{in}(v)$ ;
99     otherwise connect  $v \rightarrow T$  with capacity  $-\text{in}(v)$ .
100 To maximize: connect  $t \rightarrow s$  with capacity inf (skip this
101 edge
102 for a pure circulation problem), let  $f = \text{maxflow}(S, T)$ .
103 If
104      $f \neq \text{sum of in}(v) \text{ over all } \text{in}(v) > 0$ , no solution exists.
105 Otherwise  $\text{maxflow}(s, t)$  (found after adding  $t \rightarrow s$ ) is
106 the answer.
107 To minimize: let  $f = \text{maxflow}(S, T)$  (without any  $s$ - $t$  edge
108 yet).
109 Then connect  $t \rightarrow s$  with capacity inf and let  $f'$  be the
110 extra
111 flow pushed from  $S$  to  $T$ . If  $f + f' \neq \text{sum of in}(v) \text{ over}$ 
112      $\text{all}$ 
113      $\text{in}(v) > 0$ , no solution exists. Otherwise  $f'$  is the
114     answer.
115 5. The flow on each original edge  $e$  is  $l_e + f_e$ , where  $f_e$ 
116     is
117      $e$ 's flow in the constructed graph.

```

9.2 Dinic (Flow Decomposition)

b8e775

```

1 // Function: Max Flow + Flow Decomposition,  $O(V^2 E)$ 
2 // init  $\rightarrow$  addEdge; vertices 0-based
3 //  $\ggg$  flow() := return max flow
4 //  $\ggg$  flow_decomposition() := return max flow + store
5     decomposition in flow.D
6 struct Dinic{
7     static const int MXN=10000;
8     struct Edge{ int v,c,r,C; bool fw; };
9     int n,s,t,level[MXN]; vector<Edge> G[MXN];
10    void init(int _n,int _s,int _t){
11        n=_n; s=_s; t=_t;

```

```

11     for (int i=0; i<n; i++) G[i].clear(); }
12 void addEdge(int u,int v,int c){
13     G[u].push_back({v,c,(int)G[v].size(),c,true});
14     G[v].push_back({u,0,(int)G[u].size()-1,0,false}); }
15 bool BFS(){
16     for (int i=0;i<n;i++) level[i]=-1;
17     queue<int> que; que.push(s); level[s]=0;
18     while(!que.empty()){
19         int u=que.front(); que.pop();
20         for (auto &it:G[u]){
21             if(it.c>0&&level[it.v]==-1){
22                 level[it.v]=level[u]+1; que.push(it.v);
23             } }
24     return level[t]!=-1; }
25 int DFS(int u,int nf){
26     if(u==t) return nf;
27     int res=0;
28     for (auto &it:G[u]){
29         if(it.c>0&&level[it.v]==level[u]+1){
30             int tf=DFS(it.v,min(nf,it.c));
31             res+=tf; nf-=tf; it.c-=tf;
32             G[it.v][it.r].c+=tf;
33             if(nf==0) return res;
34         } }
35     if(!res) level[u]=-1;
36     return res; }
37 int flow(int res=0){
38     while(BFS()) res+=DFS(s,2147483647);
39     return res;
40 } // reset: do nothing
41 vector<pair<int, vector<int>>> D; // (flow amount, [path
42   pl ... pk])
43 int flow_decomposition(){
44     int mxflow = flow();
45     vector<vector<Edge>> fG(n); // graph with forward edges
46     for (int u = 0; u < n; u++) {
47         for (auto &e : G[u]) {
48             if (e.fw && e.c - e.c > 0)
49                 fG[u].push_back({e.v, e.c - e.c, e.r, e.c, e.fw});
50         }
51     }
52     vector<int> vis(n, 0);
53     function<int(int, int)> dfs = [&](int u, int cur) {
54         if (u == t) {
55             D.back().second.push_back(u);
56             return cur; }
57         vis[u] = 1;
58         for (auto &e : fG[u]) {
59             if (e.c > 0 && !vis[e.v]) {
60                 int ans = dfs(e.v, min(cur, e.c));
61                 if (ans > 0) {
62                     e.c -= ans;
63                     D.back().second.push_back(u);
64                     return ans;
65                 } }
66         return 0; };
67     D.clear();
68     int quota = mxflow;
69     while (quota > 0) {
70         D.emplace_back(0, vector<int>());
71         fill(vis.begin(), vis.end(), 0);
72         int f = dfs(s, 2147483647);
73         if (f == 0) break;
74         reverse(D.back().second.begin(),
75               D.back().second.end());
76         D.back().first = f, quota -= f;
77     }
78     return mxflow; }
79 }flow;

```

9.3 ISAP

c13d55

```

1 // Author: CRYPTOGRAPHER
2 // 1-based: vertices are numbered 1 ~ n
3 // 1. flow.init(n, s, t);
4 // n = #vertices, s, t = source, sink
5 // 2. flow.addEdge(u, v, c); // u, v in [1, n]
6 // 3. call: int ans = flow.flow();
7 // => ans = max flow value from s to t
8 // Time: O(V^2 * E) worst case, usually much faster in
9 // practice
10 static const int MAXV=50010;
11 static const int INF=1000000;
12 struct Maxflow{
13     struct Edge{
14         int v,c,r;
15         Edge(int _v,int _c,int _r):v(_v),c(_c),r(_r){}
16     };
17     int s,t; vector<Edge> G[MAXV];
18     int iter[MAXV],d[MAXV],gap[MAXV],tot;
19     void init(int n,int _s,int _t){

```

```

19     tot=n,s=_s,t=_t;
20     for(int i=1;i<=tot;i++){
21         G[i].clear(); iter[i]=d[i]=gap[i]=0;
22     }
23 }
24 void addEdge(int u,int v,int c){
25     G[u].push_back(Edge(v,c,SZ(G[v])));
26     G[v].push_back(Edge(u,0,SZ(G[u])-1));
27 }
28 int DFS(int p,int flow){
29     if(p==t) return flow;
30     for(int &i=iter[p];i<SZ(G[p]);i++){
31         Edge &e=G[p][i];
32         if(e.c>0&&d[p]==d[e.v]+1){
33             int f=DFS(e.v,min(flow,e.c));
34             if(f){ e.c-=f; G[e.v][e.r].c+=f; return f; }
35         }
36     }
37     if(--gap[d[p]]==0) d[s]=tot;
38     else{ d[p]++; iter[p]=0; ++gap[d[p]]; }
39     return 0;
40 }
41 int flow(){
42     int res=0;
43     for(res=0,gap[0]=tot,d[s]<tot;res+=DFS(s,INF);)
44         return res;
45 }
46 void reset(){
47     for(int i=1;i<=tot;i++) iter[i]=d[i]=gap[i]=0;
48 }
49 }flow;

```

9.4 Bounded Max Flow

aaf8c3

```

1 // Author: CRYPTOGRAPHER
2 // Max flow with lower/upper bound on edges (source-sink
3 // version)
4 // <!-- 1-based: original vertices are numbered 1 ~ n.
5 // Super source, sink: n+1, n+2 respectively.
6 // dependency: ISAP.cpp
7 // 1. n = #vertices (1 ~ n), m = #edges
8 // s, t = original source, sink (both in [1, n])
9 // 2. l[i], r[i] := edge i goes from l[i] -> r[i] (l[i],
10 // r[i] in [1, n])
11 // 3. a[i], b[i] := flow on edge i must lie in [a[i], b[i]]
12 // 4. int ans = solve(n, m, s, t);
13 // => ans == -1 : no feasible flow exists
14 // => ans : feasible max flow value
15 // N, M must be large enough for original graph + 2
16 // super nodes
17 // Time: O(V^2 E), Space: O(V + E)
18 int in[N], out[N], l[M], r[M], a[M], b[M];
19 int solve(int n, int m, int s, int t){
20     flow.init(n+2, n+1, n+2); // super source = n+1, super
21     sink = n+2
22     for(int i = 0; i < m; i++){
23         in[r[i]] += a[i]; out[l[i]] += a[i];
24         flow.addEdge(l[i], r[i], b[i] - a[i]);
25         // flow from l[i] to r[i] must lie in [a[i], b[i]]
26     }
27     int nd = 0;
28     for(int i = 1; i <= n; i++){
29         if(in[i] < out[i]){
30             flow.addEdge(i, flow.t, out[i] - in[i]);
31             nd += out[i] - in[i];
32         }
33         if(out[i] < in[i])
34             flow.addEdge(flow.s, i, in[i] - out[i]);
35     }
36     flow.addEdge(t, s, INF); // original sink -> source
37     if(flow.flow() != nd) return -1; // infeasible
38     int ans = flow.G[s].back().c; // t->s edge's current flow
39     = feasible flow s->t
40     flow.G[s].back().c = flow.G[t].back().c = 0;
41     for(size_t i = 0; i < flow.G[flow.s].size(); i++){
42         Maxflow::Edge &e = flow.G[flow.s][i];
43         flow.G[flow.s][i].c = 0; flow.G[e.v][e.r].c = 0;
44     }
45     for(size_t i = 0; i < flow.G[flow.t].size(); i++){
46         Maxflow::Edge &e = flow.G[flow.t][i];
47         flow.G[flow.t][i].c = 0; flow.G[e.v][e.r].c = 0;
48     }
49     flow.addEdge(flow.s, s, INF); flow.addEdge(t, flow.t,
50     INF);
51     flow.reset(); // keeps G[] intact, only resets search
52     state
53     return ans + flow.flow();
54 }

```

9.5 MCMF

472be6

```

1 // Author: CRYPTOGRAPHER

```

```

2 // MCMF (supports negative edges without negative cycles)
3 // <!-- 1-based: vertices are numbered 1 ~ n.
4 // 1. MCMF.init(n); // n = #vertices (1 ~ n)
5 // 2. MCMF.add(u, v, cap, cost);
6 // 3. auto [max_flow, min_cost] = MCMF.flow(s, t); // s, t
   in [1, n]
7 // Time: O(F * E), Space: O(V + E)
8 typedef int Tcost;
9 const int MAXV = 20010;
10 const int INFf = 1000000;
11 const Tcost INFc = 1e9;
12 struct MCMF {
13     struct Edge {
14         int v, cap;
15         Tcost w;
16         int rev;
17         bool fw;
18         Edge() {}
19         Edge(int t2, int t3, Tcost t4, int t5, bool t6)
20             : v(t2), cap(t3), w(t4), rev(t5), fw(t6) {}
21     };
22     int V, s, t;
23     vector<Edge> G[MAXV];
24     void init(int n) {
25         V = n;
26         for(int i = 0; i <= V; i++) G[i].clear();
27     }
28     void add(int a, int b, int cap, Tcost w) {
29         G[a].push_back(Edge(b, cap, w, (int)G[b].size(), true));
30         G[b].push_back(Edge(a, 0, -w, (int)G[a].size()-1,
31 false));
32     }
33     Tcost d[MAXV];
34     int id[MAXV], mom[MAXV];
35     bool inqu[MAXV];
36     queue<int> q;
37     pair<int, Tcost> flow(int _s, int _t) {
38         s = _s, t = _t;
39         int mxf = 0; Tcost mnc = 0;
40         while(1) {
41             fill(d, d+V, INFf); // need to use type cast
42             fill(inqu, inqu+V, 0);
43             fill(mom, mom+V, -1);
44             mom[s] = s;
45             d[s] = 0;
46             q.push(s); inqu[s] = 1;
47             while(q.size()) {
48                 int u = q.front(); q.pop();
49                 inqu[u] = 0;
50                 for(int i = 0; i < (int)G[u].size(); i++) {
51                     Edge &e = G[u][i];
52                     int v = e.v;
53                     if(e.cap > 0 && d[v] > d[u]+e.w) {
54                         d[v] = d[u]+e.w;
55                         mom[v] = u;
56                         id[v] = i;
57                         if(!inqu[v]) q.push(v), inqu[v] = 1;
58                     }
59                 }
60                 if(mom[t] == -1) break;
61                 int df = INFf;
62                 for(int u = t; u != s; u = mom[u])
63                     df = min(df, G[mom[u]][id[u]].cap);
64                 for(int u = t; u != s; u = mom[u]) {
65                     Edge &e = G[mom[u]][id[u]];
66                     e.cap -= df;
67                     G[e.v][e.rev].cap += df;
68                 }
69                 mxf += df;
70                 mnc += df*d[t];
71             }
72             return make_pair(mxf, mnc);
73         }
74     };

```

9.6 Push-Relabel

fae237

```

1 // Author: Simon Lindholm (kactl)
2 // 0-based: vertices are numbered 0 ~ n-1
3 // 1. PushRelabel pr(n); // n = #vertices
4 // 2. pr.addEdge(u, v, c); // u, v in [0, n-1]
5 // 3. ll ans = pr.calc(s, t);
6 // => ans = max flow value from s to t
7 // To obtain actual flow:
8 // for (int u = 0; u < n; u++)
9 //     for (auto& e : pr.g[u])
10 //         if (e.f > 0) => (u, e.dest, e.f)
11 // Time: O(V^2 * sqrt(E)), better on dense graph
12 struct PushRelabel {

```

```

13     struct Edge { int dest, back; ll f, c; };
14     vector<vector<Edge>> g;
15     vector<ll> ec;
16     vector<Edge*> cur;
17     vector<vi> hs; vi H;
18     PushRelabel(int n) : g(n), ec(n), cur(n), hs(2*n), H(n) {}
19
20     void addEdge(int s, int t, ll cap, ll rcap=0) {
21         if (s == t) return;
22         g[s].push_back({t, sz(g[t]), 0, cap});
23         g[t].push_back({s, sz(g[s])-1, 0, rcap});
24     }
25     void addFlow(Edge& e, ll f) {
26         Edge &back = g[e.dest][e.back];
27         if (!ec[e.dest] && f) hs[H[e.dest]].push_back(e.dest);
28         e.f += f; e.c -= f; ec[e.dest] += f;
29         back.f -= f; back.c += f; ec[back.dest] -= f;
30     }
31     ll calc(int s, int t) {
32         int v = sz(g); H[s] = v; ec[t] = 1;
33         vi co(2*v); co[0] = v-1;
34         rep(i, 0, v) cur[i] = g[i].data();
35         for (Edge& e : g[s]) addFlow(e, e.c);
36
37         for (int hi = 0;;) {
38             while (hs[hi].empty()) if (!hi--) return -ec[s];
39             int u = hs[hi].back(); hs[hi].pop_back();
40             while (ec[u] > 0) // discharge u
41                 if (cur[u] == g[u].data() + sz(g[u])) {
42                     H[u] = 1e9;
43                     for (Edge& e : g[u]) if (e.c && H[u] >
44 H[e.dest]+1)
45                         H[u] = H[e.dest]+1, cur[u] = &e;
46                     if (++co[H[u]], !--co[hi] && hi < v)
47                         rep(i, 0, v) if (hi < H[i] && H[i] < v)
48                             --co[H[i]], H[i] = v + 1;
49                     hi = H[u];
50                 } else if (cur[u]->c && H[u] == H[cur[u]->dest]+1)
51                     addFlow(*cur[u], min(ec[u], cur[u]->c));
52                 else ++cur[u];
53             }
54         }
55         bool leftOfMinCut(int a) { return H[a] >= sz(g); }

```

9.7 Gomory-Hu Tree

88b014

```

1 // Author: chilli, Takanori MAEHARA (kactl)
2 // <!-- Dependency: PushRelabel.cpp
3 // Given a list of edges representing an undirected flow
   graph,
4 // returns edges of the Gomory-Hu tree.
5 // maxflow / mincut of (u, v) => min edge from u to v on
   Gomory-Hu tree
6 // Time: O(V) * O(PushRelabel)
7 typedef array<ll, 3> Edge; // (u, v, w)
8 vector<Edge> gomoryHu(int n, vector<Edge> ed) {
9     vector<Edge> tree;
10    vi par(n);
11    rep(i, 1, n) {
12        PushRelabel D(n); // Dinic also works
13        for (Edge t : ed) D.addEdge(t[0], t[1], t[2], t[2]);
14        tree.push_back({i, par[i], D.calc(i, par[i])});
15        rep(j, i+1, n)
16            if (par[j] == par[i] && D.leftOfMinCut(j)) par[j] = i;
17    }
18    return tree;
19 }

```

9.8 Global Min Cut

a040ee

```

1 // Author: ckiseki
2 // 1-based: vertices are numbered 1 ~ n
3 // 1. vector<vector<ll>> G(n+1, vector<ll>(n+1, 0));
4 // 2. add_edge(G, u, v, c); // add undirected edge u-v with
   weight c, u, v in [1, n]
5 // 3. ll ans = mincut(G, n); // n = #vertices
6 // => ans = global min cut value
7 // Time: O(V^3)
8 void add_edge(auto &w, int u, int v, int c) {
9     w[u][v] += c; w[v][u] += c; }
10 auto phase(const auto &w, int n, vector<int> id) {
11     vector<ll> g(n+1); int s = -1, t = -1;
12     while (!id.empty()) {
13         int c = -1;
14         for (int i : id) if (c == -1 || g[i] > g[c]) c = i;
15         s = t; t = c;
16         id.erase(ranges::find(id, c));
17         for (int i : id) g[i] += w[c][i];
18     } return tuple{s, t, g[t]};
19 }
20 ll mincut(auto w, int n) {

```

```

21 ll cut = numeric_limits<ll>::max();
22 vector<int> id(n); iota(all(id), 1);
23 for (int i = 0; i < n - 1; ++i) {
24     auto [s, t, gt] = phase(w, n, id);
25     id.erase(ranges::find(id, t));
26     cut = min(cut, gt);
27     for (int j = 1; j <= n; ++j)
28         w[s][j] += w[t][j], w[j][s] += w[j][t];
29 } return cut;
30 }

```

10 String

10.1 Rolling Hash

c15659

```

1// Author: ckiseki (Modified by Gino)
2// Usage: RH<Sigma, Mod> Hs(s);
3// If no modifications needed, replace BIT with prefix sum
4template <ll P = 127, ll Q = 1051762951>
5class RH {
6    int n; vector<ll> p, inv, d, bit;
7    ll add(ll a, ll b) { return a+b >= Q ? a+b-Q : a+b; }
8    ll sub(ll a, ll b) { return a-b < 0 ? a-b+Q : a-b; }
9    ll mul(ll a, ll b) { return (__int128)a * b % Q; }
10    ll pw(ll a, ll x) {
11        ll r = 1; for (; x; a = mul(a, a), x >>= 1)
12            if (x & 1) r = mul(r, a);
13        return r;
14    }
15    void bit_add(int i, ll x)
16    { for (; i <= n; i += i&-i) bit[i] = add(bit[i], x); }
17    ll bit_qry(int i)
18    { ll s = 0; for (; i; i -= i&-i) s = add(s, bit[i]);
19    return s; }
20public:
21    RH(const auto &s) : n(s.size()),
22        p(n+1, 1), inv(n+1, 1), d(n+1, bit(n+1)) {
23        ll iv = pw(P, Q - 2);
24        for (int i = 1; i <= n; i++) {
25            p[i] = mul(p[i-1], P); inv[i] = mul(inv[i-1], iv);
26            d[i] = mul(s[i-1], p[i]); bit_add(i, d[i]);
27        }
28        void update(int i, char c)
29        { ll x=mul(c, p[i]); bit_add(i, sub(x, d[i])); d[i]=x; }
30        ll query(int l, int r)
31        { return mul(sub(bit_qry(r), bit_qry(l-1)), inv[l]); }
32    };

```

10.2 KMP

376cdf

```

1// Author: Gino
2vector<int> kmp(auto s){ int n=s.size(); vector<int> f(n,0);
3    for (int i = 1, ptr = 0; i < n; i++) {
4        while (ptr && s[i] != s[ptr]) ptr = f[ptr-1];
5        if (s[i] == s[ptr]) ptr++; f[i] = ptr;
6    } return f;
7}

```

10.3 Z Value

d5b3b9

```

1// Author: std_abs
2vector<int> Z(auto s){ int n=s.size(); vector<int> Z(n);
3    for (int i = 0, l = 0, r = 0; i < n; ++i) {
4        Z[i] = max(min(Z[i-l], r-i), 0);
5        while (i+Z[i] < n && s[Z[i]] == s[i+Z[i]])
6            l = i, r = i+Z[i], Z[i]++;
7    } return Z;
8}

```

10.4 Manacher

193b08

```

1// Author: std_abs
2// return array Z (length == 2N - 1)
3// Example: s = "aaaa"
4//   a       a       a
5// Z_0 Z_1 Z_2 Z_3 Z_4 Z_5 Z_6
6// 1   2   3   4   3   2   1
7// The corresponding palindrome s[l..r]:
8// l = (i - Z[i] + 1) / 2
9// r = (i + Z[i] - 1) / 2
10vector<int> manacher(auto tmp) {
11    vector<int> s(1, -1);
12    for (auto c : tmp) s.push_back(c), s.push_back(-1);
13    int l = 0, r = 0, n = (int)s.size();
14    vector<int> Z(n);
15    for (int i = 0; i < n; ++i) {
16        Z[i] = r > i ? min(Z[2 * l - i], r - i) : 1;
17        while (i - Z[i] >= 0 && i + Z[i] < n &&
18            s[i - Z[i]] == s[i + Z[i]]) Z[i]++;
19        if (Z[i] + i > r) l = i, r = Z[i] + i;
20    }
21    for (int i = 0; i < n; ++i)
22        Z[i] = (Z[i] - (i & 1)) / 2 * 2 + (i & 1);
23    return vector<int>(Z.begin() + 1, Z.end() - 1);
24}

```

10.5 Suffix Array + LCP

c1df5b

```

1// Author: std_abs
2// Tested @yosupo, N <= 5e5, 123ms
3const int N = 5e5 + 10;
4int sa[N], tmp[2][N], c[N], rk[N], lcp[N];
5void buildSA(string s) {
6    int *x = tmp[0], *y = tmp[1], m = 256, n = s.size();
7    for (int i = 0; i < m; ++i) c[i] = 0;
8    for (int i = 0; i < n; ++i) c[x[i]] = s[i]++;
9    for (int i = 1; i < m; ++i) c[i] += c[i-1];
10   for (int i = n-1; ~i; --i) sa[--c[x[i]]] = i;
11   for (int k = 1; k < n; k <= 1) {
12       for (int i = 0; i < m; ++i) c[i] = 0;
13       for (int i = 0; i < n; ++i) c[x[i]]++;
14       for (int i = 1; i < m; ++i) c[i] += c[i-1];
15       int p = 0;
16       for (int i = n-k; i < n; ++i) y[p++] = i;
17       for (int i = 0; i < n; ++i) if (sa[i] >= k)
18           y[p++] = sa[i] - k;
19       for (int i = n-1; ~i; --i)
20           sa[--c[x[y[i]]]] = y[i];
21       y[sa[0]] = p = 0;
22       for (int i = 1; i < n; ++i) {
23           int a = sa[i], b = sa[i-1];
24           p += !(x[a]==x[b] && a+k < n && b+k < n && x[a+k]==x[b+k]);
25           y[sa[i]] = p;
26       }
27       if (n == p+1) break;
28       swap(x, y), m = p+1;
29   }
30   void buildLCP(string s) {
31       // lcp[i] = LCP(sa[i-1], sa[i])
32       // lcp(i, j) = query_lcp_min[rk[i]+1, rk[j]+1]
33       int n = s.length(), x = 0;
34       for (int i = 0; i < n; ++i) rk[sa[i]] = i;
35       for (int i = 0; i < n; ++i) {
36           if (!rk[i]) lcp[rk[i]] = 0;
37           else { if (x) x--;
38               int p = sa[rk[i]-1];
39               while (x+i < n && x+p < n && s[x+i]==s[x+p]) x++;
40               lcp[rk[i]] = x;
41           }
42       }

```

10.6 Suffix Automaton

10ef751

```

1// Author: std_abs
2// state (i.e. node) -> all substr with the same endpos
3// those substrs' length in range [len(link)+1, len]
4// state i's endpos set -> union of pos[i] over the subtree
5// of i in the suffix link tree
6// link[i] -> longest suffix with different endpos set
7// (suffix link tree edge)
8// len[i] -> length longest suffix of state i
9// pos[i] -> an example end position of state i (1-based)
10// cnt[i] -> size of endpos set of state i, built by
11// build_cnt() (tree DP)
12const int N = 5e5 + 10, C = 26;
13struct SAM {
14    int ch[2*N][C], len[2*N], link[2*N], pos[2*N], cnt[2*N], _id;
15    SAM() { reset(); }
16    void reset() { _id = 0; newnode(), link[0] = -1; }
17    int newnode() {
18        fill_n(ch[_id], C, 0);
19        len[_id] = link[_id] = pos[_id] = cnt[_id] = 0;
20        return _id++;
21    }
22    void build(string s) {
23        int last = 0; for (int i = 0; i < (int)s.size(); i++) {
24            char c = s[i]; int cur = newnode();
25            len[cur] = len[last] + 1, pos[cur] = i + 1;
26            int p = last;
27            while (~p && !ch[p][c - 'a'])
28                ch[p][c - 'a'] = cur, p = link[p];
29            if (p == -1) link[cur] = 0;
30            else { // conflict: p --> q, p --> cur
31                int q = ch[p][c - 'a'];
32                if (len[p] + 1 == len[q]) { // q is suffix of cur
33                    link[cur] = q;
34                } else { // we need auxiliary state
35                    int nxt = newnode();
36                    len[nxt] = len[p] + 1, link[nxt] = link[q];
37                    pos[nxt] = 0;
38                    for (int j = 0; j < C; j++)
39                        ch[nxt][j] = ch[q][j];
40                    while (~p && ch[p][c - 'a'] == q)
41                        ch[p][c - 'a'] = nxt, p = link[p];
42                    link[q] = link[cur] = nxt;
43                }
44            }
45            cnt[cur]++, last = cur;
46        }
47    }

```

```

43} sam;
44// void build_cnt() {
45//     vector<int> p(_id); iota(all(p), 0); sort(all(p),
46//         [&](int i, int j){ return len[i] > len[j]; });
47//     for (int i = 0; i < _id; ++i) if (link[p[i]] != -1)
48//         cnt[link[p[i]]] += cnt[p[i]];
49// }
50// bool match(string s) {
51//     int p = 0; for (auto& c : s) {
52//         if (!ch[p][c - 'a']) return false;
53//         p = ch[p][c - 'a'];
54//     } return true; }

```

10.7 Minimum Rotation

bb235f

```

1// Author: std_abs
2string rotate(auto s){ int n=s.size(), i=0, j=1;
3 string t = s + s;
4 while (i < n && j < n) {
5     int k = 0; while (k < n && t[i + k] == t[j + k]) ++k;
6     if (t[i + k] <= t[j + k]) j += k + 1; else i += k + 1;
7     if (i == j) ++j;
8 } return t.substr((i < n ? i : j), n);
9}

```

10.8 AC Automaton

285968

```

1// Author: std_abs (slightly modified by Gino)
2// Recap: fail[s] = s in trie 上 (也就是某個 pattern 的前綴
3// 的最長 proper 後綴
4// N := sum(length of all patterns) + 1
5// 1. ac.insert(pat) -> end-node id recorded in ac.pid
6// 2. ac.build_fail()
7// 3. run text: ptr = to[ptr][c-'a'] each char;
8// accumulate on your own arrays
9// - pull: rep(i ac.order_cnt-1 ~ 0) val[fail[x]] += val[x]
10// - push: rep(i 0 ~ ac.order_cnt-1) val[x] += val[fail[x]]
11// Tested @yosupo, N <= 1e6, 323ms on building AC
12const int N = 1e6 + 5, C = 26;
13struct AC {
14    int ch[N][C], to[N][C], fail[N], _id, order[N], order_cnt;
15    int np; vector<int> pid; // pattern ID on trie
16    // order[r] := which trie node has BFS order r
17    // fail link tree: (parent) fail[i] <--- i (child)
18    void reset() { _id = np = order_cnt = 0, pid.clear(),
19        newnode(); }
20    int newnode() {
21        fill_n(ch[_id], C, 0), fill_n(to[_id], C, 0);
22        fail[_id] = 0; return _id++;
23    }
24    AC() { reset(); }
25    void insert(string s) {
26        int ptr = 0; for (char c : s) {
27            if (!ch[ptr][c - 'a']) ch[ptr][c - 'a'] = newnode();
28            ptr = ch[ptr][c - 'a'];
29        } np++; pid.emplace_back(ptr);
30    }
31    void build_fail() {
32        queue<int> q; order_cnt = 0;
33        for (int i = 0; i < C; ++i) if (ch[0][i])
34            q.push(ch[0][i]), to[0][i] = ch[0][i];
35        while (!q.empty()) {
36            int u = q.front(); q.pop(); order[order_cnt++] = u;
37            for (int i = 0; i < C; ++i) {
38                if (!ch[u][i]) to[u][i] = to[fail[u]][i];
39                else { int v = ch[u][i], k = fail[u];
40                    while (k && !ch[k][i]) k = fail[k];
41                    if (ch[k][i]) k = ch[k][i];
42                    fail[v] = k, to[u][i] = v;
43                    q.push(v);
44                }
45            }
46        }
47    }
48} ac;

```

10.9 AC Automaton - Dict Links

a62cfa

```

1// Author: Gino, paste this in `struct AC {...}`
2// 3 Modifications to the original AC Automaton:
3// int np; vector<int> pid; bool is_pattern[N];
4// fail[_id] = 0, is_pattern[_id] = false; return _id++;
5// np++; pid.emplace_back(ptr); is_pattern[ptr] = true;
6int dict[N];
7void build_dict() { // call this after build_fail()!
8    for (int i = 0; i < order_cnt; ++i) {
9        int u = order[i], f = fail[u];
10        dict[u] = is_pattern[f] ? f : dict[f];
11    }
12}

```

10.10 AC Automaton - Counting Patterns

58fd32

```

1// Author: Gino, paste this in `struct AC {...}`
2ll val[N];
3void count_patterns(string& text, vector<string>& patterns){
4    for (auto& p : patterns) insert(p); build_fail();
5    ranges::fill(val, 0LL);

```

```

6    int ptr = 0; for (auto& c : text) {
7        ptr = to[ptr][c - 'a']; val[ptr]++;
8    }
9    for (int x : span(order, order_cnt) | views::reverse)
10        val[fail[x]] += val[x];
11    for (auto& i : pid) cout << val[i] << endl;
12}

```

10.11 AC Automaton - Pattern Position

輸出每個 pattern 在 text 中第一次出現的位置，若不存在則輸出 -1。
走 AC 自動機時 if (val[ptr] == -1) val[ptr] = i; 接著 pull DP
if (val[x] == -1) continue;
if (val[fail[x]] == -1) val[fail[x]] = val[x];
else val[fail[x]] = min(val[fail[x]], val[x]);

11 Geometry

11.1 Template

acaf6b

```

1using T = long long; // or double
2const double eps = 1e-8;
3int sgn(T x) { return (x > eps) - (x < -eps); }
4struct Pt {
5    T x = 0, y = 0;
6    Pt operator+(Pt a) const { return {x + a.x, y + a.y}; }
7    Pt operator-(Pt a) const { return {x - a.x, y - a.y}; }
8    Pt operator*(T k) const { return {x * k, y * k}; }
9    Pt operator/(T k) const { return {x / k, y / k}; }
10    T operator*(Pt a) const { return x * a.x + y * a.y; }
11    T operator^(Pt a) const { return x * a.y - y * a.x; }
12    bool operator<(Pt a) const
13    { return tie(x, y) < tie(a.x, a.y); }
14    bool operator==(Pt a) const
15    { return !sgn(x - a.x) && !sgn(y - a.y); }
16    friend ostream& operator<<(ostream& o, Pt a)
17    { return o << "(" << a.x << ", " << a.y << ")"; }
18};
19struct Line { Pt a, b; }; // a -> b
20struct Cir { Pt o; double r; };
21T abs2(Pt a) { return a * a; }
22double abs(Pt a) { return sqrt(abs2(a)); }
23int ori(Pt o, Pt a, Pt b) // 1: CCW, -1: CW, 0: collinear
24{ return sgn((a - o) ^ (b - o)); }
25bool onseg(Pt p, Pt a, Pt b) // p on segment ab?
26{ return !ori(p, a, b) && sgn((a - p) * (b - p)) <= 0; }

```

11.2 Basic

8507af

```

1int ud(Pt a) // 0: upper half (incl. +x axis), 1: lower
2{ return !sgn(a.y) ? sgn(a.x) < 0 : a.y < 0; }
3bool cmp(Pt a, Pt b) // polar angle in [0, 2PI)
4{ return ud(a) == ud(b) ? sgn(a ^ b) > 0 : ud(a) < ud(b); }
5bool sameVec(Pt a, Pt b, int d)//d=0: parallel, d=1: same dir
6{ return !sgn(a ^ b) && sgn(a * b) > d * 2 - 2; }
7bool sameVec(Line a, Line b, int d)
8{ return sameVec(a.b - a.a, b.b - b.a, d); }
9Pt rot90(Pt a) { return {-a.y, a.x}; } // CCW
10Pt ref(Pt a) { return ud(a) ? Pt(-a.x, -a.y) : a; }
11T dbarea(vector<Pt>& p) // doubled signed area, CCW > 0
12{ T res = 0; for (int i = 0; i < sz(p); ++i)
13    res += p[i] ^ p[(i+1) % sz(p)];
14    return res; }
15// ---- T = double ----
16const double PI = acos(-1);
17double normalize(double x) // to [0, 2pi)
18{ while (x < -eps) x += PI * 2;
19  while (x > PI * 2 + eps) x -= PI * 2;
20  return x; }
21double theta(Pt a) { return normalize(atan2(a.y, a.x)); }
22Pt unit(Pt a) { return a / abs(a); }
23Pt rot(Pt a, double o) { // CCW
24    double c = cos(o), s = sin(o);
25    return Pt(c * a.x - s * a.y, s * a.x + c * a.y); }
26Pt projVec(Pt a, Pt b, Pt c) // vector ac proj to ab
27{ return (b - a) * ((c - a) * (b - a)) / abs2(b - a); }
28Pt projPt(Pt a, Pt b, Pt c) // point c proj to ab
29{ return projVec(a, b, c) + a; }

```

11.3 Line / Segment Intersections

7e8b65

```

1// m=0: segment, m=1: ray from l.a to l.b, m=2: line
2bool banana(Line ls, int ms, Line lt, int mt, int strict) {
3    auto on = [&](Line l, int m, Pt p) {
4        if (ori(l.a, l.b, p) != 0) return false;
5        if (m && abs2(l.a - p) > abs2(l.b - p)) return true;
6        return m == 2 || sgn((p - l.a) * (p - l.b)) <= -strict;
7    };
8    if (sameVec(ls, lt, 0)) {
9        return on(ls, ms, lt.a) || on(ls, ms, lt.b) ||
10            on(lt, mt, ls.a) || on(lt, mt, ls.b);
11    }
12    auto good = [&](Line l, int m, Line o) {
13        if (m && abs((l.a - o.a) ^ (l.a - o.b)) >
14            abs((l.b - o.a) ^ (l.b - o.b))) return true;

```

```

15     return m == 2 ||
16         ori(l.a, o.a, o.b) * ori(l.b, o.a, o.b) == -1;
17 };
18 if (good(ls, ms, lt) && good(lt, mt, ls)) return 1;
19 if (!strict) {
20     if (mt != 2 && on(ls, ms, lt.a)) return 1;
21     if (mt == 0 && on(ls, ms, lt.b)) return 1;
22     if (ms != 2 && on(lt, mt, ls.a)) return 1;
23     if (ms == 0 && on(lt, mt, ls.b)) return 1;
24 }
25 return 0;
26 }

```

27 // becareful when two lines are parallel

```

28 auto bananaPoint(Line a, Line b) {
29     auto abc = (a.b - a.a) ^ (b.a - a.a);
30     auto abd = (a.b - a.a) ^ (b.b - a.a);
31     return make_pair(b.b * abc - b.a * abd, abc - abd);
32 }

```

11.4 Point-Line / Segment Distance

8b23e4

```

1 // T = double
2 double pointLineDist(Pt p, Line L)
3 { return fabs(((L.b - L.a) ^ (p - L.a)) / abs(L.b - L.a)); }
4 double pointSegDist(Pt p, Pt a, Pt b) {
5     if (a == b) return abs(p - a);
6     if (sgn((b - a) * (p - a)) >= 0 &&
7         sgn((a - b) * (p - b)) >= 0)
8         return pointLineDist(p, {a, b});
9     return min(abs(p - a), abs(p - b));
10 }

```

11.5 Sort

63db4f

```

1 // Dependency: cmp(), btwAngle()
2 // cmp in Basic: polar angle sort
3 // all points are on line ab. closer to a: front
4 bool cmpLine(Pt s, Pt t, Pt a, Pt b) {
5     Pt v = a - b;
6     if (sgn(v.x)) return sgn(s.x - t.x) == sgn(v.x);
7     return sgn(s.y - t.y) == sgn(v.y);
8 }
9 // intersect points polar angle sort, deno: positive
10 bool cmpFractionPolar(pair<Pt, ll> o,
11     pair<Pt, ll> s, pair<Pt, ll> t) {
12     Pt u = s.first * o.second - o.first * s.second;
13     Pt v = t.first * o.second - o.first * t.second;
14     return cmp(u, v);
15 }
16 struct Seg {
17     Pt a, b; // a.x < b.x
18     bool operator<(const Seg& o) const {
19         if (a == o.a) return ori(o.b, a, b) == 1;
20         if (a.x <= o.a.x) return ori(o.a, a, b) == 1;
21         return ori(a, o.a, o.b) == -1;
22     };
23 struct PolarSeg {
24     Pt a, b; // ori(Pt(0, 0), a, b) > 0
25     bool operator<(const PolarSeg& o) const {
26         if (a == o.a) return ori(o.b, a, b) == -1;
27         if (btwAngle(Pt(0, 0), a, b, o.a, o.b))
28             return ori(o.a, a, b) == -1;
29         return ori(a, o.a, o.b) == 1;
30     };
31 struct Arc {
32     // contain(a, b): circle a inside circle b
33     Cir c;
34     int id, s; // 0 -> up, 1 -> down
35     bool operator<(const Arc& b) const {
36         if (id == b.id) return s < b.s;
37         if (contain(c, b.c)) return b.s == 1;
38         if (contain(b.c, c)) return s == 0;
39         if (c.o.y == b.c.o.y) return id < b.id;
40         return c.o.y > b.c.o.y;
41     };

```

11.6 Convex Hull

37fe2b

```

1 auto convexHull(vector<Pt> pts) {
2     sort(all(pts)); vector<Pt> ans = {pts[0]};
3     for (int t = 0; t < 2; t++, reverse(all(pts))) {
4         for (int i = 1, m = sz(ans); i < sz(pts); i++) {
5             while (sz(ans) > m &&
6                 ori(ans[sz(ans) - 2], ans.back(), pts[i]) <= 0)
7                 ans.pop_back();
8             ans.pb(pts[i]); } }
9     if (sz(ans) > 1) ans.pop_back(); return ans; }

```

11.7 Triangle Centers

9c22fc

```

1 // T = double
2 Pt circenter(Pt a, Pt b, Pt c) { // r = abs(o - a)
3     b = b - a, c = c - a; double m = 2 * (b^c);
4     Pt o = {(abs2(b) * c.y - abs2(c) * b.y) / m,
5             (abs2(c) * b.x - abs2(b) * c.x) / m};

```

```

6     return o + a;
7 }
8 Pt incenter(Pt a, Pt b, Pt c) { // r = 2 * area / s
9     double x = abs(b - c), y = abs(c - a);
10    double z = abs(a - b), s = x + y + z;
11    return (a*x + b*y + c*z) / s;
12 }
13 Pt centroid(Pt a, Pt b, Pt c) { return (a + b + c) / 3; }
14 Pt orthocenter(Pt a, Pt b, Pt c) {
15     return centroid(a, b, c) * 3 - circenter(a, b, c) * 2;
16 }

```

11.8 Point Inside

109f6b

```

1 // get edge index: check (0, a), (0, b) first
2 // then after binary search, check (a, b)
3 bool inConvex(vector<Pt>& C, Pt p, bool strict = true) {
4     // only works when no three points are collinear
5     int a = 1, b = sz(C) - 1, r = !strict;
6     if (sz(C) == 0) return false;
7     if (sz(C) < 3) return r && onseg(p, C[0], C.back());
8     if (ori(C[0], C[a], C[b]) > 0) swap(a, b);
9     if (ori(C[0], C[a], p) >= r ||
10         ori(C[0], C[b], p) <= -r) return false;
11     while (abs(a - b) > 1) {
12         int c = (a + b) / 2;
13         (ori(C[0], C[c], p) > 0 ? b : a) = c;
14     }
15     return ori(C[a], C[b], p) < r;
16 }
17 // -1: out, 0: edge, 1: in
18 int inPoly(vector<Pt> poly, Pt o, int strict) {
19     int cnt = 0;
20     for (int i = 0; i < sz(poly); i++) {
21         Pt a = poly[i], b = poly[(i + 1) % sz(poly)];
22         if (onseg(o, a, b)) return !strict;
23         cnt ^= ((o.y < a.y) - (o.y < b.y)) * ori(o, a, b) > 0;
24     }
25     return cnt ? 1 : -1;
26 }
27 // relation of q with circumcircle; T = long long
28 bool inCC(array<Pt, 3> p, Pt q) {
29     __int128 det = 0;
30     for (int i = 0; i < 3; i++)
31         det += __int128(abs2(p[i]) - abs2(q)) *
32             ((p[(i + 1) % 3] - q) ^ (p[(i + 2) % 3] - q));
33     return det > 0; // in: >0, on: =0, out: <0
34 }

```

11.9 Point In Triangle

144fc0

```

1 // number of p with a < p < b and ori(p, a, b) < 0
2 int under(Pt a, Pt b) {}
3 // number of points with a < p < b and ori(p, a, b) = 0
4 int edge(Pt a, Pt b) {}
5 // check if this number is calculated
6 bool check(Pt p) {}
7 // number of points that strictly inside the triangle
8 int inTri(array<Pt, 3> arr) {
9     sort(all(arr)); auto [a, b, c] = arr; intx = ori(b, a, c);
10    if (x == 0) return 0;
11    if (x == 1) return under(a, b) + under(b, c) -
12        under(a, c) - edge(a, c);
13    return under(a, c) - under(a, b) -
14        under(b, c) - edge(a, b) - edge(b, c) - check(b);
15 }

```

11.10 Vector In Polygon

1b2dce

```

1 // ori(a, b, c) >= 0, valid: "strict" angle from a-b to a-c
2 bool btwAngle(Pt a, Pt b, Pt c, Pt p, int strict) {
3     return ori(a, b, p) >= strict &&
4         ori(a, p, c) >= strict;
5 }
6 // whether vector{cur, p} is in order prv, cur, nxt
7 bool inside(Pt prv, Pt cur, Pt nxt, Pt p, int strict) {
8     if (ori(cur, nxt, prv) >= 0)
9         return btwAngle(cur, nxt, prv, p, strict);
10    return !btwAngle(cur, prv, nxt, p, !strict);
11 }

```

11.11 Polygon Cut

c08d26

```

1 // Dependency: bananaPoint(); T = double
2 // Cut a convex polygon with line (s -> e), keep right side
3 vector<Pt> polyCut(vector<Pt> poly, Pt s, Pt e) {
4     vector<Pt> res; for (int i = 0; i < sz(poly); i++) {
5         Pt cur = poly[i], prv = i ? poly[i - 1] : poly.back();
6         bool side = ori(s, e, cur) < 0;
7         if (side != (ori(s, e, prv) < 0)) {
8             auto [p, d] = bananaPoint({s, e}, {cur, prv});
9             res.pb(p / d);
10        } if (side) res.pb(cur);
11    } return res;

```

11.12 Half-Plane Intersection c71070

```
1// Dependency: sameVec(), cmp(); T = long long
2/* Having solution, check size > 2 */
3/* --^-- Line.a --^-- Line.b --^-- */
4auto halfPlaneIntersection(vector<Line> arr) {
5    auto areaPair = [&](Line a, Line b) {
6        return make_pair((a.b - a.a) ^ (b.a - a.a),
7                          (a.b - a.a) ^ (b.b - a.a));
8    };
9    auto isin = [&](Line l0, Line l1, Line l2) {
10        // Check inter(l1, l2) strictly in l0
11        auto [a02X, a02Y] = areaPair(l0, l2);
12        auto [a12X, a12Y] = areaPair(l1, l2);
13        if (a12X - a12Y < 0) a12X *= -1, a12Y *= -1;
14        return (__int128)a02Y * a12X -
15               (__int128)a02X * a12Y > 0; // C^4
16    };
17    sort(all(arr), [&](Line a, Line b) {
18        if (sameVec(a, b, 1))
19            return ori(a.a, a.b, b.b) < 0;
20        return cmp(a.b - a.a, b.b - b.a);
21    });
22    deque<Line> dq(1, arr[0]);
23    auto popBack = [&](int t, Line p) {
24        while (sz(dq) >= t &&
25               !isin(p, dq[sz(dq) - 2], dq.back()))
26            dq.pop_back();
27    };
28    auto popFront = [&](int t, Line p) {
29        while (sz(dq) >= t && !isin(p, dq[0], dq[1]))
30            dq.pop_front();
31    };
32    for (auto p : arr) if (!sameVec(dq.back(), p, 1))
33        popBack(2, p), popFront(2, p), dq.pb(p);
34    popBack(3, dq[0]), popFront(3, dq.back());
35    return vector<Line>(all(dq));
36}
```

11.13 Cyclic Ternary Search e3165d

```
1/* bool pred(int a, int b);
2f(0) ~ f(n - 1) is a cyclic-shift U-function
3return idx s.t. pred(x, idx) is false forall x*/
4int cycTsearch(int n, auto pred) {
5    if (n == 1) return 0;
6    int l = 0, r = n; bool rv = pred(1, 0);
7    while (r - l > 1) {
8        int m = (l + r) / 2;
9        if (pred(0, m) ? rv : pred(m, (m + 1) % n)) r = m;
10       else l = m;
11    } return pred(l, r % n) ? l : r % n;
12}
```

11.14 Circle Intersections 734f65

```
1// Dependency: cycTsearch(); T = double for circles
2vector<Pt> circleLineIntersect(Cir c, Line l) {
3    Pt p = l.a + (l.b - l.a) *
4           ((c.o - l.a) * (l.b - l.a)) / abs2(l.b - l.a);
5    double s = (l.b - l.a) ^ (c.o - l.a);
6    double h2 = c.r * c.r - s * s / abs2(l.b - l.a);
7    if (sgn(h2) == -1) return {};
8    if (sgn(h2) == 0) return {p};
9    Pt h = (l.b - l.a) / abs(l.b - l.a) * sqrt(h2);
10   return {p - h, p + h};
11}
12// covered area of c1: arc from res[0] to res[1], CCW
13vector<Pt> circlesIntersect(Cir c1, Cir c2) {
14    double d2 = abs2(c1.o - c2.o), d = sqrt(d2);
15    if (d < max(c1.r, c2.r) - min(c1.r, c2.r) ||
16        d > c1.r + c2.r) return {};
17    Pt u = (c1.o + c2.o) / 2 +
18           (c1.o - c2.o) *
19           ((c2.r * c2.r - c1.r * c1.r) / (2 * d2));
20    double A = sqrt((c1.r + c2.r + d) *
21                   (c1.r - c2.r + d) * (c1.r + c2.r - d) *
22                   (-c1.r + c2.r + d));
23    Pt v = rot90(c2.o - c1.o) * A / (2 * d2);
24    if (sgn(v.x) == 0 && sgn(v.y) == 0) return {u};
25    return {u - v, u + v};
26}
27vector<pii> convexLineIntersect(vector<Pt>& C, Line la) {
28    auto dis = [&](int p) {
29        return (la.b - la.a) ^ (C[p] - la.a);
30    };
31    auto gao = [&](int s) {
32        return cycTsearch(sz(C), [&](int i, int j) {
33            return sgn(dis(i) - dis(j)) == s;
34        });
35    };
36}
```

```
36 int x = gao(1), y = gao(-1), n = sz(C);
37 if (sgn(dis(x)) < 0 || sgn(dis(y)) > 0) return {};
38 if (sgn(dis(x)) == 0 || sgn(dis(y)) == 0) {
39     int v = ((sgn(dis(x)) == 0 ? x : y) + n - 1) % n;
40     vector<pii> vec;
41     for (int i = 0; i < 3; i++, v = (v + 1) % n)
42         if (sgn(dis(v)) == 0) vec.emplace_back(v, v);
43     return vec;
44 }
45 auto get = [&](int l, int r, int s) {
46     while ((l + 1) % n != r) {
47         int m = ((l + r + (l < r ? 0 : n)) / 2) % n;
48         (sgn(dis(m)) == s ? l : r) = m;
49     }
50     if (sgn(dis(r)) == 0) return pii(r, r);
51     return pii(l, r);
52 };
53 return {get(x, y, 1), get(y, x, -1)};
54}
```

11.15 Tangents 8def22

```
1// Dependency: cycTsearch(); T = double for circle tangents
2auto circlePointTangent(Cir c, Pt p) {
3    vector<Line> res;
4    double dSq = abs2(p - c.o);
5    if (sgn(dSq - c.r * c.r) == 0) {
6        res.push_back({p, p + rot90(p - c.o)});
7    } else if (dSq > c.r * c.r) {
8        double s = dSq - c.r * c.r;
9        Pt v = p + (c.o - p) * s / dSq;
10        Pt u = rot90(c.o - p) * sqrt(s) * c.r / dSq;
11        res.push_back({p, v + u});
12        res.push_back({p, v - u});
13    }
14    return res;
15}
16auto circlesTangent(Cir c1, Cir c2, int sign1) {
17    // sign1 = 1 for outer tang, -1 for inner tang
18    vector<Line> res;
19    double dSq = abs2(c1.o - c2.o);
20    if (sgn(dSq) == 0) return res;
21    double d = sqrt(dSq);
22    Pt v = (c2.o - c1.o) / d;
23    double c = (c1.r - sign1 * c2.r) / d;
24    if (c * c > 1) return res;
25    double h = sqrt(max(0.0, 1.0 - c * c));
26    for (int sign2 = 1; sign2 >= -1; sign2 -= 2) {
27        Pt n = Pt(v.x * c - sign2 * h * v.y,
28                v.y * c + sign2 * h * v.x);
29        Pt p1 = c1.o + n * c1.r;
30        Pt p2 = c2.o + n * (c2.r * sign1);
31        if (sgn(p1.x - p2.x) == 0 &&
32            sgn(p1.y - p2.y) == 0)
33            p2 = p1 + rot90(c2.o - c1.o);
34        res.push_back({p1, p2});
35    }
36    return res;
37}
38/* The point should be strictly out of hull
39return arbitrary point on the tangent line */
40pii pointConvexTangent(vector<Pt>& C, Pt p) {
41    auto gao = [&](int s) {
42        return cycTsearch(sz(C), [&](int x, int y) {
43            return ori(p, C[x], C[y]) == s;
44        });
45    };
46    return pii(gao(1), gao(-1));
47} // return (a, b), ori(p, C[a], C[b]) >= 0
```

11.16 Bisector 5348b9

```
1Pt bisector(Pt a, Pt b, Pt c) { Pt s = b-a, t = c-a;
2    t = t * abs(s) / abs(t); return s + t; }
```

11.17 Minimum Enclosing Circle 04b498

```
1// Dependency: circenter(); T = double
2Cir minEnclosingCircle(vector<Pt> p) {
3    auto seed = chrono::steady_clock::now().
4        time_since_epoch().count();
5    shuffle(all(p), mt19937(seed));
6    double r = 0.0; Pt cent = p[0];
7    for (int i = 1; i < sz(p); i++) {
8        if (abs2(cent - p[i]) <= r) continue;
9        cent = p[i]; r = 0.0;
10       for (int j = 0; j < i; j++) {
11           if (abs2(cent - p[j]) <= r) continue;
12           cent = (p[i] + p[j]) / 2; r = abs2(p[j] - cent);
13           for (int k = 0; k < j; k++) {
14               if (abs2(cent - p[k]) <= r) continue;
15               cent = circenter(p[i], p[j], p[k]);
16               r = abs2(p[k] - cent);
17           }
18       }
19    }
```

```

17 } } }
18 return {cent, sqrt(r)};
19 }

```

11.18 Minkowski Sum

fdd915

```

1 // Dependency: convexHull()
2 auto minkowski(vector<Pt> a, vector<Pt> b) {
3     a = convexHull(a), b = convexHull(b);
4     int n = sz(a), m = sz(b);
5     vector<Pt> c = {a[0] + b[0]}, s1, s2;
6     for (int i = 0; i < n; i++) s1.pb(a[(i+1) % n] - a[i]);
7     for (int i = 0; i < m; i++) s2.pb(b[(i+1) % m] - b[i]);
8     for (int p1 = 0, p2 = 0; p1 < n || p2 < m;)
9         if (p2 == m ||
10             (p1 < n && sgn(s1[p1] ^ s2[p2]) >= 0))
11             c.pb(c.back() + s1[p1++]);
12         else
13             c.pb(c.back() + s2[p2++]);
14     return convexHull(c);
15 }

```

11.19 Convex Hull Distance

f7df29

```

1 // Dependency: minkowski(), inConvex(), pointSegDist()
2 // T = double
3 double convexHullDist(vector<Pt> A, vector<Pt> B) {
4     Pt O(0, 0); for (auto& p : B) p = O - p;
5     auto C = minkowski(A, B);
6     if (inConvex(C, O)) return 0;
7     double ans = pointSegDist(O, C.back(), C[0]);
8     for (int i = 0; i + 1 < sz(C); i++)
9         ans = min(ans, pointSegDist(O, C[i], C[i + 1]));
10    return ans;
11 }

```

11.20 Closest Point Pair

ad1bba

```

1 // returns {min squared dist, {i, j}}, n >= 2, |coord| < 1e9
2 pair<T, pair<int, int>> closestPair(vector<Pt> p) {
3     vector<int> id(sz(p)); iota(all(id), 0);
4     sort(all(id),
5          [&](int a, int b) { return p[a].y < p[b].y; });
6     set<pair<Pt, int>> s; // (point, id)
7     pair<T, pair<int, int>> best = {(T)9e18, {-1, -1}};
8     int l = 0; for (int i : id) {
9         if (!best.first) break;
10        T d = sqrtl(best.first) + is_integral_v<T>;
11        while (p[id[l]].y <= p[i].y - d)
12            s.erase({p[id[l]], id[l]}), l++;
13        auto lo = s.lower_bound({p[i] - Pt{d, 0}, 0});
14        auto hi = s.upper_bound({p[i] + Pt{d, 0}, sz(p)});
15        for (; lo != hi; lo++) {
16            auto [q, j] = *lo;
17            best = min(best,
18                      {abs2(q - p[i]), {min(i, j), max(i, j)}});
19        } s.insert({p[i], i});
20    } return best;
21 }

```

11.21 Polygon-Circle Intersection

18454b

```

1 // T = double
2 double areaSector(Pt pa, Pt pb, double r) {
3     if (abs(pa) < abs(pb)) swap(pa, pb);
4     if (abs(pb) < eps) return 0;
5     double S, h, t;
6     double a = abs(pb), b = abs(pa), c = abs(pb - pa);
7     double cosB = pb * (pb - pa) / a / c;
8     double B = acos(cosB);
9     double cosC = pa * pb / a / b, C = acos(cosC);
10    if (a > r) {
11        S = C / 2 * r * r;
12        h = a * b * sin(C) / c;
13        if (h < r && B < PI / 2)
14            S -= acos(h / r) * r * r - h * sqrt(r * r - h * h);
15    } else if (b > r) {
16        t = PI - B - asin(sin(B) / r * a);
17        S = 0.5 * a * r * sin(t) + (C - t) / 2 * r * r;
18    } else {
19        S = 0.5 * sin(C) * a * b;
20    }
21    return S;
22 }
23 double areaPolyCircle(vector<Pt> poly, Pt O, double r) {
24     double S = 0;
25     int n = sz(poly);
26     for (int i = 0; i < n; i++)
27         S += areaSector(poly[i] - O,
28                        poly[(i + 1) % n] - O, r) *
29            ori(O, poly[i], poly[(i + 1) % n]);
30    return fabs(S);
31 }

```

11.22 Union of Polygons

9d7265

```

1 // Dependency: sameVec(), bananaPoint(), cmpLine()
2 // in CCW order, use index as tiebreaker when collinear

```

```

3 auto polysBorder(vector<vector<Pt>> poly, int id) {
4     auto get = [&](auto& p, int i) {
5         return make_pair(p[i], p[(i + 1) % sz(p)]);
6     };
7     vector<pair<Pt, Pt>> seg;
8     for (int e = 0; e < sz(poly[id]); e++) {
9         auto [s, t] = get(poly[id], e);
10        vector<pair<Pt, int>> vec;
11        vec.emplace_back(s, -1 << 30);
12        vec.emplace_back(t, 1 << 30);
13        for (int i = 0; i < sz(poly); i++) {
14            int st = find_if(poly[i].begin(), poly[i].end(),
15                             [&](Pt p) { return ori(p, s, t) == 1; }) -
16                poly[i].begin();
17            if (st == sz(poly[i])) continue;
18            for (int j = st; j < st + sz(poly[i]); j++) {
19                auto [a, b] = get(poly[i], j % sz(poly[i]));
20                if (sameVec(a - b, s - t, -1)) {
21                    if (ori(a, b, s) == 0 &&
22                        sameVec(a - b, s - t, 1) && i <= id) {
23                        vec.emplace_back(a, -1);
24                        vec.emplace_back(b, 1);
25                    }
26                } else {
27                    int s1 = ori(a, s, t) == 1;
28                    int s2 = ori(b, s, t) == 1;
29                    if (s1 ^ s2) {
30                        auto [p, d] = bananaPoint({a, b}, {s, t});
31                        vec.emplace_back(p / d, s1 ? 1 : -1);
32                    }
33                }
34            }
35        }
36        sort(all(vec), [&](auto i, auto j) {
37            return cmpLine(i.first, j.first, s, t);
38        });
39        int base = 1 << 30;
40        Pt lst(0, 0);
41        for (auto [cur, val] : vec) {
42            if (!base) seg.emplace_back(lst, cur);
43            lst = cur, base += val;
44        }
45        return seg;
46    }
47    double polysUnionArea(vector<vector<Pt>> poly) {
48        double res = 0;
49        for (int i = 0; i < sz(poly); i++) {
50            auto seg = polysBorder(poly, i);
51            for (auto [l, r] : seg) res += l ^ r;
52        }
53        return res / 2;
54    }
55 }

```

11.23 Rotating Sweep Line

769b9b

```

1 // Dependency: ref()
2 struct Event {
3     Pt d; int u, v;
4     bool operator<(const Event& o) const {
5         return sgn(d ^ o.d) > 0;
6     }
7 };
8 void rotatingSweepLine(vector<Pt> pts) {
9     int n = sz(pts);
10    vector<int> ord(n), pos(n); vector<Event> e;
11    for (int i = 0; i < n; i++)
12        for (int j = i + 1; j < n; j++)
13            e.push_back({ref(pts[i] - pts[j]), i, j});
14    sort(all(e)); iota(all(ord), 0);
15    sort(all(ord), [&](int i, int j) {
16        return sgn(pts[i].y - pts[j].y) == 0 ?
17            pts[i].x < pts[j].x : pts[i].y < pts[j].y;
18    });
19    for (int i = 0; i < n; i++) pos[ord[i]] = i;
20    auto makeReverse = [](auto v) {
21        sort(all(v));
22        v.resize(unique(all(v)) - v.begin());
23        vector<pii> segs;
24        for (int i = 0, j = 0; i < sz(v); i = j) {
25            for (; j < sz(v) && v[j] - v[i] <= j - i; j++);
26            segs.emplace_back(v[i], v[j - 1] + 1 + 1);
27        }
28        return segs;
29    };
30    for (int i = 0, j = 0; i < sz(e); i = j) {
31        vector<int> tmp;
32        for (; j < sz(e) && !(e[i] < e[j]); j++)
33            tmp.pb(min(pos[e[j].u], pos[e[j].v]));
34        for (auto [l, r] : makeReverse(tmp)) {
35            reverse(ord.begin() + l, ord.begin() + r);
36            for (int t = l; t < r; t++) pos[ord[t]] = t;
37            // update value here
38        }
39    }
40 }

```

11.24 Pick's Theorem

Consider a polygon which vertices are all lattice points.
Let i = number of points inside the polygon.
Let b = number of points on the boundary of the polygon.
Then we have the following formula:

$$\text{Area} = i + b/2 - 1$$

12 Number Theory

12.1 Mod Sum

60beb8

```
1/**
2 * Author: Simon Lindholm
3 * Date: 2015-06-23
4 * License: CC0
5 * Source: own work
6 * Description: Sums of mod'ed arithmetic progressions.
7 *
8 * \texttt{modsum(to, c, k, m)} =  $\sum_{i=0}^{to-1} (ki+c) \% m$ .
9 * \texttt{divsum} is similar but for floored division.
10 * Time:  $\log(m)$ , with a large constant.
11 * Status: Tested for all  $|k|, |c|, to, m \leq 50$ , and on
12 * kattis:aladin
13 */
14 #pragma once
15 typedef unsigned long long ull;
16 ull sumsq(ull to) { return to / 2 * ((to-1) | 1); }
17 /// ^ written in a weird way to deal with overflows
18 /// correctly
19 ull divsum(ull to, ull c, ull k, ull m) {
20     ull res = k / m * sumsq(to) + c / m * to;
21     k %= m; c %= m;
22     if (!k) return res;
23     ull to2 = (to * k + c) / m;
24     return res + (to - 1) * to2 - divsum(to2, m-1 - c, m, k);
25 }
26
27 ll modsum(ull to, ll c, ll k, ll m) {
28     c = ((c % m) + m) % m;
29     k = ((k % m) + m) % m;
30     return to * c + k * sumsq(to) - m * divsum(to, c, k, m);
31 }
```

12.2 Extended Lucas Theorem

3bed10

```
1/**
2 * Author: koukanni
3 * Date: 2025
4 * License: CC0
5 * Source:
6 * Description: Computes  $C(n, m) \bmod P$  where  $P$  is not
7 * necessarily prime
8 * Functions
9 * exgcd(a, b, x, y): Extended Euclidean algorithm
10 * inv(a, p): Modular inverse of a modulo p
11 * qpow(a, b, p): Fast modular exponentiation
12 * CRT(n, a, m): Chinese Remainder Theorem
13 * calc(n, x, P): Helper function for computing factorial
14 * with prime power
15 * multilucas(n, m, x, P): Lucas theorem for prime power
16 * modulus
17 * exlucas(n, m, P): Main function - Extended Lucas theorem
18 * Usage: exlucas(n, m, P) returns  $C(n, m) \bmod P$ 
19 * Time:  $O(P \log(P))$ 
20 * Status: tested
21 */
22 typedef long long ll;
23 void exgcd(ll a, ll b, ll& x, ll& y) {
24     if (!b)
25         x = 1, y = 0;
26     else
27         exgcd(b, a % b, y, x), y -= a / b * x;
28 }
29 ll inv(ll a, ll p) {
30     ll x, y;
31     exgcd(a, p, x, y);
32     return (x + p) % p;
33 }
34 ll qpow(ll a, ll b, ll p) {
35     ll r = 1;
36     for (; b >= 1; a = a * a % p)
37         if (b & 1) r = r * a % p;
38     return r;
39 }
40 ll CRT(int n, ll* a, ll* m) {
41     ll M = 1, p = 0;
42     for (int i = 1; i <= n; i++) M = M * m[i];
43     for (int i = 1; i <= n; i++) {
```

```
41     ll w = M / m[i], x, y;
42     exgcd(w, m[i], x, y);
43     p = (p + a[i] * w * x % M) % M;
44 }
45 return (p % M + M) % M;
46 }
47 ll calc(ll n, ll x, ll P) {
48     if (!n) return 1;
49     ll s = 1;
50     for (ll i = 1; i <= P; i++)
51         if (i % x) s = s * i % P;
52     s = qpow(s, n / P, P);
53     for (ll i = n / P * P + 1; i <= n; i++)
54         if (i % x) s = i % P * s % P;
55     return s * calc(n / x, x, P) % P;
56 }
57 ll multilucas(ll n, ll m, ll x, ll P) {
58     if (n < m) return 0;
59     int cnt = 0;
60     for (ll i = n; i; i /= x) cnt += i / x;
61     for (ll i = m; i; i /= x) cnt -= i / x;
62     for (ll i = n - m; i; i /= x) cnt -= i / x;
63     return qpow(x, cnt, P) % P * calc(n, x, P) % P *
64         inv(calc(m, x, P), P) % P *
65         inv(calc(n - m, x, P), P) % P;
66 }
67 ll exlucas(ll n, ll m, ll P) {
68     int cnt = 0;
69     ll p[20], a[20];
70     for (ll i = 2; i * i <= P; i++) {
71         if (P % i == 0) {
72             p[++cnt] = 1;
73             while (P % i == 0) p[cnt] = p[cnt] * i, P /= i;
74             a[cnt] = multilucas(n, m, i, p[cnt]);
75         }
76     }
77     if (P > 1) p[++cnt] = P, a[cnt] = multilucas(n, m, P, P);
78     return CRT(cnt, a, p);
79 }
```

12.3 Prime Sieve and Defactor

e2350f

```
1// Author: Gino
2const int maxc = 1e6 + 1;
3vector<int> lpf;
4vector<int> prime;
5
6void seive() {
7     prime.clear();
8     lpf.resize(maxc, 1);
9     for (int i = 2; i < maxc; i++) {
10         if (lpf[i] == 1) {
11             lpf[i] = i;
12             prime.emplace_back(i);
13         }
14         for (auto& j : prime) {
15             if (i * j >= maxc) break;
16             lpf[i * j] = j;
17             if (j == lpf[i]) break;
18         }
19     }
20     vector<pii> fac;
21     void defactor(int u) {
22         fac.clear();
23         while (u > 1) {
24             int d = lpf[u];
25             fac.emplace_back(make_pair(d, 0));
26             while (u % d == 0) {
27                 u /= d;
28                 fac.back().second++;
29             }
30         }
31     }
```

12.4 Harmonic Series

7c56cc

```
1// Author: Gino
2//  $O(n \log n)$ 
3for (int i = 1; i <= n; i++) {
4     for (int j = i; j <= n; j += i) {
5         //  $O(1)$  code
6     }
7 }
8
9// PIE
10// given array  $a[0], a[1], \dots, a[n-1]$ 
11// calculate  $dp[x]$  = number of pairs  $(a[i], a[j])$  such that
12//  $\gcd(a[i], a[j]) = x$  // ( $i < j$ )
13//
14// idea: let  $mc(x) = \#$  of  $y$  s.t.  $x|y$ 
15//  $f(x) = \#$  of pairs s.t.  $\gcd(a[i], a[j]) \geq x$ 
16//  $f(x) = C(mc(x), 2)$ 
17//  $dp[x] = f(x) - \sum(dp[y], x < y \text{ and } x|y)$ 
18const int maxc = 1e6;
19vector<int> cnt(maxc + 1, 0), dp(maxc + 1, 0);
```

```

20 for (int i = 0; i < n; i++)
21     cnt[a[i]]++;
22
23 for (int x = maxc; x >= 1; x--) {
24     ll cnt_mul = 0; // number of multiples of x
25     for (int y = x; y <= maxc; y += x)
26         cnt_mul += cnt[y];
27
28     dp[x] = cnt_mul * (cnt_mul - 1) / 2; // number of pairs
    that are divisible by x
29     for (int y = x + x; y <= maxc; y += x)
30         dp[x] -= dp[y]; // PIE: subtract all dp[y] for y >
    x and x|y
31 }

```

12.5 Count Number of Divisors

0a5616

```

1 // Author: Gino
2 // Function: Count the number of divisors for all x <= 10^6
    using harmonic series
3 const int maxc = 1e6;
4 vector<int> facs;
5
6 void find_all_divisors() {
7     facs.clear(); facs.resize(maxc + 1, 0);
8     for (int x = 1; x <= maxc; x++) {
9         for (int y = x; y <= maxc; y += x) {
10             facs[y]++;
11         }
12     }
13 }

```

12.6 數論分塊

cd4e6b

```

1 // Author: Gino
2 /*
3 n = 17
4 i: 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17
5 n/i: 17 8 5 4 3 2 2 2 1 1 1 1 1 1 1 1 1
6
7             ^       ^
8             L(2)   R(2)
9
10 L(x) := left bound for n/i = x
11 R(x) := right bound for n/i = x
12
13 ===== FORMULA =====
14 >>> R = n / (n/L) <<<
15
16 Example: L(2) = 6
17            R(2) = 17 / (17 / 6)
18            = 17 / 2
19            = 8
20 */
21 // ===== CODE =====
22
23 for (ll l = 1, r = 1, q = n; l <= n; l = r + 1) {
24     q = n/l;
25     r = n/q;
26     // Process your code here
27 }
28 // q, l, r: 17 1 1
29 // q, l, r: 8 2 2
30 // q, l, r: 5 3 3
31 // q, l, r: 4 4 4
32 // q, l, r: 3 5 5
33 // q, l, r: 2 6 8
34 // q, l, r: 1 9 17

```

12.7 Pollard's rho

```

1 // Author: Unknown
2 // Function: Find a non-trivial factor of a big number in
    O(n^(1/4) log^2(n))
3
4 ll find_factor(ll number) {
5     __int128 x = 2;
6     for (__int128 cycle = 1; ; cycle++) {
7         __int128 y = x;
8         for (int i = 0; i < (1<<cycle); i++) {
9             x = (x * x + 1) % number;
10            __int128 factor = __gcd(x - y, number);
11            if (factor > 1)
12                return factor;
13        }
14    }
15 }
16
17 # Author: Unknown
18 # Function: Find a non-trivial factor of a big number in
    O(n^(1/4) log^2(n))
19 from itertools import count
20 from math import gcd
21 from sys import stdin
22

```

```

7 for s in stdin:
8     number, x = int(s), 2
9     brk = False
10    for cycle in count(1):
11        y = x
12        if brk:
13            break
14        for i in range(1<< cycle):
15            x = (x * x + 1) % number
16            factor = gcd(x - y, number)
17            if factor > 1:
18                print(factor)
19                brk = True
20                break

```

12.8 Miller Rabin

686187

```

1 // Author: Unknown, Modified by Gino
2 // Function: Check if a number is a prime in O(100 *
    log^2(n))
3 // miller_rabin(): return 1 if prime, 0 otherwise
4 inline ll mul(ll x, ll y, ll mod) {
5     return (__int128)(x) * y % mod;
6 }
7 ll mypow(ll a, ll b, ll mod) {
8     ll r = 1;
9     while (b > 0) {
10        if (b & 1) r = mul(r, a, mod);
11        a = mul(a, a, mod);
12        b >>= 1;
13    }
14    return r;
15 }
16 bool witness(ll a, ll n, ll u, int t){
17     ll x = mypow(a, u, n);
18     for(int i = 0; i < t; i++) {
19         ll nx = mul(x, x, n);
20         if (nx == 1 && x != 1 && x != n-1) return true;
21         x = nx;
22     }
23     return x != 1;
24 }
25 bool miller_rabin(ll n) {
26     // if n >= 3,474,749,660,383
27     // change {2, 3, 5, 7, 11, 13} to
28     // {2, 325, 9375, 28178, 450775, 9780504, 1795265022}
29     if (n < 2) return false;
30     if (!(n & 1)) return n == 2;
31     ll u = n - 1; int t = 0;
32     while (!(u & 1)) u >>= 1, t++;
33     for (ll a : {2, 3, 5, 7, 11, 13}) {
34         if (a % n == 0) continue;
35         if (witness(a, n, u, t)) return false;
36     }
37     return true;
38 }
39 // bases that make sure no pseudoprimes flee from test
40 // if WA, replace randll(n - 1) with these bases:
41 // n < 4,759,123,141          3 : 2, 7, 61
42 // n < 1,122,004,669,633     4 : 2, 13, 23, 1662803
43 // n < 3,474,749,660,383     6 : pirms <= 13
44 // n < 2^64                  7 :
45 // 2, 325, 9375, 28178, 450775, 9780504, 1795265022

```

12.9 Discrete Log

a04e88

```

1 // Author: ckiseki
2 // find x^? = y (mod M)
3 // O(sqrt(M))
4 template<typename Int>
5 Int BSGS(Int x, Int y, Int M) {
6     // x^? \equiv y (mod M)
7     Int t = 1, c = 0, g = 1;
8     for (Int M_ = M; M_ > 0; M_ >>= 1) g = g * x % M;
9     for (g = gcd(g, M); t % g != 0; ++c) {
10        if (t == y) return c;
11        t = t * x % M;
12    }
13    if (y % g != 0) return -1;
14    t /= g, y /= g, M /= g;
15    Int h = 0, gs = 1;
16    for (; h * h < M; ++h) gs = gs * x % M;
17    unordered_map<Int, Int> bs;
18    for (Int s = 0; s < h; bs[y] = ++s) y = y * x % M;
19    for (Int s = 0; s < M; s += h) {
20        t = t * gs % M;
21        if (bs.count(t)) return c + s + h - bs[t];
22    }
23    return -1;
24 }

```

12.10 Discrete Sqrt

3f16e1

```

1 // Author: ckiseki
2 // find solution for  $x^2 = n \pmod P$ 
3 //  $O(\log^2 P)$ 
4 int get_root(int n, int P) { // ensure  $0 \leq n < p$ 
5     if (P == 2 || n == 0) return n;
6     auto check = [&](ll d) {
7         return modpow(d, (P - 1) / 2, P);
8     };
9     if (check(n) != 1) return -1;
10    mt19937 rnd(7122); ll z = 1, w;
11    while (check(w = (z * z - n + P) % P) != P - 1)
12        z = rnd() % P;
13    const auto M = [P, w](auto &u, auto &v) {
14        auto [a, b] = u; auto [c, d] = v;
15        return make_pair((a * c + b * d % P * w) % P,
16                          (a * d + b * c) % P);
17    };
18    pair<ll, ll> r(1, 0), e(z, 1);
19    for (int q = (P + 1) / 2; q >= 1; e = M(e, e))
20        if (q & 1) r = M(r, e);
21    return int(r.first); // sqrt(n) mod P where P is prime

```

```

3 ll f[maxn];
4 vector<int> lpf, prime;
5 void build() {
6     lpf.clear(); lpf.resize(maxn, 1);
7     prime.clear();
8     f[1] = ...; /* mu[1] = 1, phi[1] = 1 */
9     for (int i = 2; i < maxn; i++) {
10         if (lpf[i] == 1) {
11             lpf[i] = i; prime.emplace_back(i);
12             f[i] = ...; /* mu[i] = 1, phi[i] = i-1 */
13         }
14         for (auto& j : prime) {
15             if (i * j >= maxn) break;
16             lpf[i * j] = j;
17             if (i % j == 0) f[i * j] = ...; /*  $\theta$ ,  $\phi[i] * j$  */
18             else f[i * j] = ...; /*  $-\mu[i]$ ,  $\phi[i] * \phi[j]$  */
19             if (j >= lpf[i]) break;
20         }

```

12.14 Other Formulas

- Pisano Period: 任何線性遞迴 (比如費氏數列) 模任何一個數字 M 都會循環, 找循環節 $\pi(M)$ 先質因數分解 $M = \prod p_i^{e_i}$, 然後 $\pi(M) = \text{lcm}(\pi(p_i^{e_i}))$.
- Inversion: $aa^{-1} \equiv 1 \pmod m$. a^{-1} exists iff $\gcd(a, m) = 1$.
- Linear inversion: $a^{-1} \equiv (m - \lfloor \frac{m}{a} \rfloor) \times (m \bmod a)^{-1} \pmod m$.
- Fermat's little theorem: $a^p \equiv a \pmod p$ if p is prime.
- Euler function: $\varphi(n) = n \prod_{p|n} \frac{p-1}{p}$.
- Euler theorem: $a^{\varphi(n)} \equiv 1 \pmod n$ if $\gcd(a, n) = 1$. If a, n are not coprime: 質因數分解 $n = \prod p_i^{e_i}$, 對每個 $p_i^{e_i}$ 分開看他們跟 a 是否互質 (互質: Fermat / 不互質: 夠大的指數會直接削成 0), 最後用 CRT 合併。
- Extended Euclidean algorithm: $ax + by = \gcd(a, b) = \gcd(b, a \bmod b) = \gcd(b, a - \lfloor \frac{a}{b} \rfloor b) = bx_1 + (a - \lfloor \frac{a}{b} \rfloor b)y_1 = ay_1 + b(x_1 - \lfloor \frac{a}{b} \rfloor y_1)$.
- Divisor function: $\sigma_x(n) = \sum_{d|n} d^x$. $n = \prod_{i=1}^r p_i^{a_i}$. $\sigma_x(n) = \prod_{i=1}^r \frac{p_i^{(a_i+1)x} - 1}{p_i^x - 1}$ if $x \neq 0$. $\sigma_0(n) = \prod_{i=1}^r (a_i + 1)$.
- Chinese remainder theorem (Coprime Moduli): $x \equiv a_i \pmod{m_i}$. $M = \prod m_i$. $M_i = \frac{M}{m_i}$. $t_i = M_i^{-1}$. $x = kM + \sum a_i t_i M_i, k \in \mathbb{Z}$.
- Chinese remainder theorem: $x \equiv a_1 \pmod{m_1}, x \equiv a_2 \pmod{m_2} \Rightarrow x = m_1 p + a_1 = m_2 q + a_2 \Rightarrow m_1 p - m_2 q = a_2 - a_1$. Solve for (p, q) using ExtGCD. $x \equiv m_1 p + a_1 \equiv m_2 q + a_2 \pmod{\text{lcm}(m_1, m_2)}$.
- Avoiding Overflow: $ca \bmod cb = c(a \bmod b)$.
- Dirichlet Convolution: $(f * g)(n) = \sum_{d|n} f(d)g(\frac{n}{d})$.
- Important Multiplicative Functions + Properties:
 - $\varepsilon(n) = [n = 1]$
 - $1(n) = 1$
 - $id(n) = n$
 - $\mu(n) = 0$ if n has squared prime factor
 - $\mu(n) = (-1)^k$ if $n = p_1 p_2 \dots p_k$
 - $\varepsilon = \mu * 1$
 - $\varphi = \mu * id$
 - $[n = 1] = \sum_{d|n} \mu(d)$
 - $[gcd = 1] = \sum_{d|gcd} \mu(d)$
- Möbius inversion: $f = g * 1 \Leftrightarrow g = f * \mu$

12.15 Polynomial

57318b

```

1 // Author: Gino
2 // [Usage]
3 // bezout(a, b, c):
4 //     find solution to  $ax + by = c$ 
5 //     return {-LINF, -LINF} if no solution
6 // inv(a, p):
7 //     find modulo inverse of  $a$  under  $p$ 
8 //     return -1 if not exist
9 // CRT(vector<ll>&a, vector<ll>&m)
10 //     find a solution pair (x, mod) satisfies all  $x \equiv a[i] \pmod{m[i]}$ 
11 //     return {-LINF, -LINF} if no solution
12
13 const ll LINF = 4e18;
14 typedef pair<ll, ll> pll;
15 template<typename T1, typename T2>
16 T1 chmod(T1 a, T2 m) {
17     return (a % m + m) % m;
18 }
19
20 ll GCD;
21 pll extgcd(ll a, ll b) {
22     if (b == 0) {
23         GCD = a;
24         return pll{1, 0};
25     }
26     pll ans = extgcd(b, a % b);
27     return pll{ans.second, ans.first - a/b * ans.second};
28 }
29 pll bezout(ll a, ll b, ll c) {
30     bool negx = (a < 0), negy = (b < 0);
31     pll ans = extgcd(abs(a), abs(b));
32     if (c % GCD != 0) return pll{-LINF, -LINF};
33     return pll{ans.first * c/GCD * (negx ? -1 : 1),
34               ans.second * c/GCD * (negy ? -1 : 1)};
35 }
36 ll inv(ll a, ll p) {
37     if (p == 1) return -1;
38     pll ans = bezout(a % p, -p, 1);
39     if (ans == pll{-LINF, -LINF}) return -1;
40     return chmod(ans.first, p);
41 }
42 pll CRT(vector<ll>&a, vector<ll>&m) {
43     for (int i = 0; i < (int)a.size(); i++)
44         a[i] = chmod(a[i], m[i]);
45
46     ll x = a[0], mod = m[0];
47     for (int i = 1; i < (int)a.size(); i++) {
48         pll sol = bezout(mod, m[i], a[i] - x);
49         if (sol.first == -LINF) return pll{-LINF, -LINF};
50
51         // prevent long long overflow
52         ll p = chmod(sol.first, m[i] / GCD);
53         ll lcm = mod / GCD * m[i];
54         x = chmod((__int128)p * mod + x, lcm);
55         mod = lcm;
56     }
57     return pll{x, mod};
58 }

```

12.13 Mu + Phi

ab4a91

```

1 // Author: Gino
2 const int maxn = 1e6 + 5;

```

```

13
14 const int maxk = 20;
15 const int maxn = 1<<maxk;
16

```

```

17 using u64 = unsigned long long;
18 using u128 = __uint128_t;
19
20 int g;
21 u64 MOD;
22 u64 BARRETT_IM; // [ 2^64 / MOD ]
23
24 inline void set_mod(u64 m, int _g) {
25     g = _g;
26     MOD = m;
27     BARRETT_IM = (u128(1) << 64) / m;
28 }
29 inline u64 chmod(u128 x) {
30     u64 q = (u64)((x * BARRETT_IM) >> 64);
31     u64 r = (u64)(x - (u128)q * MOD);
32     if (r >= MOD) r -= MOD;
33     return r;
34 }
35 inline u64 mmul(u64 a, u64 b) {
36     return chmod((u128)a * b);
37 }
38 ll pw(ll a, ll n) {
39     ll ret = 1;
40     while (n > 0) {
41         if (n & 1) ret = mmul(ret, a);
42         a = mmul(a, a);
43         n >>= 1;
44     }
45     return ret;
46 }
47
48 vector<ll> X, iX;
49 vector<int> rev;
50 void init_ntt() {
51     X.assign(maxn, 1); // x1 = g^((p-1)/n)
52     iX.assign(maxn, 1);
53
54     ll u = pw(g, (MOD-1)/maxn);
55     ll iu = pw(u, MOD-2);
56     for (int i = 1; i < maxn; i++) {
57         X[i] = mmul(X[i-1], u);
58         iX[i] = mmul(iX[i-1], iu);
59     }
60
61     if ((int)rev.size() == maxn) return;
62     rev.assign(maxn, 0);
63     for (int i = 1, hb = -1; i < maxn; i++) {
64         if (!(i & (i-1))) hb++;
65         rev[i] = rev[i ^ (1<<hb)] | (1<<(maxk-hb-1));
66     }
67 template<typename T>
68 void NTT(vector<T>& a, bool inv=false) {
69     int _n = (int)a.size();
70     int k = __lg(_n) + ((1<<__lg(_n)) != _n);
71     int n = 1<<k;
72     a.resize(n, 0);
73
74     short shift = maxk-k;
75     for (int i = 0; i < n; i++)
76         if (i > (rev[i]>>shift))
77             swap(a[i], a[rev[i]>>shift]);
78     for (int len = 2, half = 1, div = maxn>>1; len <= n;
79         len<<=1, half<<=1, div>>=1) {
80         for (int i = 0; i < n; i += len) {
81             for (int j = 0; j < half; j++) {
82                 T u = a[i+j];
83                 T v = mmul(a[i+j+half], (inv ? iX[j*div] :
84                     X[j*div]));
85                 a[i+j] = (u+v >= MOD ? u+v-MOD : u+v);
86                 a[i+j+half] = (u-v < 0 ? u-v+MOD : u-v);
87             }
88         }
89         if (inv) {
90             T dn = pw(n, MOD-2);
91             for (auto& x : a) {
92                 x = mmul(x, dn);
93             }
94         }
95     }
96 template<typename T>
97 inline void shrink(vector<T>& a) {
98     int cnt = (int)a.size();
99     for (; cnt > 0; cnt--) if (a[cnt-1]) break;
100     a.resize(max(cnt, 1));
101 }
102 template<typename T>
103 vector<T>& operator*=(vector<T>& a, vector<T> b) {
104     int na = (int)a.size();
105     int nb = (int)b.size();
106     a.resize(na + nb - 1, 0);
107     b.resize(na + nb - 1, 0);
108 }

```

```

104 NTT(a); NTT(b);
105 for (int i = 0; i < (int)a.size(); i++)
106     a[i] = mmul(a[i], b[i]);
107 NTT(a, true);
108
109 shrink(a);
110 return a;
111 }
112 inline ll crt(ll a0, ll a1, ll m1, ll m2, ll
113     inv_m1_mod_m2){
114     // x ≡ a0 (mod m1), x ≡ a1 (mod m2)
115     // t = (a1 - a0) * inv(m1) mod m2
116     // x = a0 + t * m1 (mod m1*m2)
117     ll t = chmod(a1 - a0);
118     if (t < 0) t += m2;
119     t = (ll)((__int128)t * inv_m1_mod_m2 % m2);
120     return a0 + (ll)((__int128)t * m1);
121 }
122 void mul_crt() {
123     // a copy to a1, a2 | b copy to b1, b2
124     ll M1 = 998244353, M2 = 1004535809;
125     g = 3; set_mod(M1); init_ntt(); a1 *= b1;
126     g = 3; set_mod(M2); init_ntt(); a2 *= b2;
127
128     ll inv_m1_mod_m2 = pw(M1, M2 - 2);
129     for (int i = 2; i <= 2 * k; i++)
130         cout << crt(a1[i], a2[i], M1, M2, inv_m1_mod_m2)
131         << ' ';
132     cout << endl;
133 }
134 }
135 /* P = r*2^k + 1
136 P
137 r k g
138 998244353 119 23 3
139 1004535809 479 21 3
140
141 P
142 r k g
143 3 1 1 2
144 5 1 2 2
145 17 1 4 3
146 97 3 5 5
147 193 3 6 5
148 257 1 8 3
149 7681 15 9 17
150 12289 3 12 11
151 40961 5 13 3
152 65537 1 16 3
153 786433 3 18 10
154 5767169 11 19 3
155 7340033 7 20 3
156 23068673 11 21 3
157 104857601 25 22 3
158 167772161 5 25 3
159 469762049 7 26 3
160 1004535809 479 21 3
161 2013265921 15 27 31
162 2281701377 17 27 3
163 3221225473 3 30 5
164 75161927681 35 31 3
165 77309411329 9 33 7
166 206158430209 3 36 22
167 2061584302081 15 37 7
168 2748779069441 5 39 3
169 6597069766657 3 41 5
170 39582418599937 9 42 5
171 79164837199873 9 43 5
172 263882790666241 15 44 7
173 1231453023109121 35 45 3
174 1337006139375617 19 46 3
175 3799912185593857 27 47 5
176 4222124650659841 15 48 19
177 7881299347898369 7 50 6
178 31525197391593473 7 52 3
179 180143985094819841 5 55 6
180 1945555039024054273 27 56 5
181 4179340454199820289 29 57 3
182 9097271247288401921 505 54 6 */

```

12.16 Counting Primes

1662d0

```

1 // prime_count - #primes in [1..n] (O(n^{2/3}) time,
2 // O(sqrt(n)) memory)
3 using u64 = unsigned long long;
4 static inline u64 prime_count(u64 n){
5     if(n<=1) return 0;
6     int v = (int)floor(sqrt((long double)n));
7     int s = (v+1)>>1, pc = 0;
8     vector<int> smalls(s), roughs(s), skip(v+1);
9     vector<long long> larges(s);

```

```

10
11 for(int i=0;i<s;++i){
12     smalls[i]=i;
13     roughs[i]=2*i+1;
14     larges[i]=(long long)((n/roughs[i]-1)>>1);
15 }
16
17 for(int p=3;p<=v;p+=2) if(!skip[p]){
18     int q = p*p;
19     if(1LL*q*q > (long long)n) break;
20     skip[p]=1;
21     for(int i=q;i<=v;i+=2*p) skip[i]=1;
22
23     int ns=0;
24     for(int k=0;k<s;++k){
25         int i = roughs[k];
26         if(skip[i]) continue;
27         u64 d = (u64)i * (u64)p;
28         long long sub = (d <= (u64)v)
29             ? larges[smalls[(int)(d>>1)] - pc]
30             : smalls[(int)((n/d - 1) >> 1)];
31         larges[ns] = larges[k] - sub + pc;
32         roughs[ns++] = i;
33     }
34     s = ns;
35     for(int i=(v-1)>>1, j=((v/p)-1)|1; j>=p; j-=2){
36         int c = smalls[j>>1] - pc;
37         for(int e=(j*p)>>1; i>=e; --i) smalls[i] -= c;
38     }
39     ++pc;
40 }
41
42 larges[0] += 1LL*(s + 2*(pc-1))*(s-1) >> 1;
43 for(int k=1;k<s;++k) larges[0] -= larges[k];
44
45 for(int l=1;l<s;++l){
46     int q = roughs[l];
47     u64 m = n / (u64)q;
48     long long t = 0;
49     int e = smalls[(int)((m/q - 1) >> 1)] - pc;
50     if(e < l+1) break;
51     for(int k=l+1;k<=e;++k) t += smalls[(int)((m/
52 (u64)roughs[k] - 1) >> 1)];
53     larges[0] += t - 1LL*(e - l)*(pc + l - 1);
54 }
55 return (u64)(larges[0] + 1);
56 }

```

12.17 Linear Sieve for Other Number Theoretic Functions

```

1// linear_sieve(n, primes, lp, phi, mu, d, sigma)
2// Outputs over the index range 0..n (n >= 1):
3// primes : all primes in [2..n], increasing.
4// lp      : lowest prime factor; lp[1]=0, lp[x] is the
5//           smallest prime dividing x.
6// phi     : Euler totient, phi[x] = |{1<=k<=x :
7//           gcd(k,x)=1}|. Multiplicative.
8// mu      : Möbius; mu[1]=1, mu[x]=0 if x has a squared
9//           prime factor, else (-1)^{#distinct primes}.
10// d       : number of divisors; if x=∏ p_i^{e_i}, then
11//           d[x]=∏(e_i+1). Multiplicative.
12// sigma   : sum of divisors; if x=∏ p_i^{e_i}, then
13//           sigma[x]=∏(1+p_i+...+p_i^{e_i}). (use ll)
14// Complexity: O(n) time, O(n) memory.
15// Notes: Arrays are resized inside; primes is cleared and
16//         reserved. sigma uses ll to avoid 32-bit overflow.
17
18 static inline void linear_sieve(
19     int n,
20     std::vector<int> &primes,
21     std::vector<int> &lp,
22     std::vector<int> &phi,
23     std::vector<int> &mu,
24     std::vector<int> &d,
25     std::vector<ll> &sigma
26 ) {
27     lp.assign(n + 1, 0); phi.assign(n + 1, 0); mu.assign(n +
28 1, 0); d.assign(n + 1, 0); sigma.assign(n + 1, 0);
29     primes.clear(); primes.reserve(n > 1 ? n / 10 : 0);
30     std::vector<int> cnt(n + 1, 0), core(n + 1, 1);
31     std::vector<ll> p_pow(n + 1, 1), sum_p(n + 1, 1);
32     phi[1] = mu[1] = d[1] = sigma[1] = 1;
33
34     for (int i = 2; i <= n; ++i) {
35         if (!lp[i]) {
36             lp[i] = i; primes.push_back(i);
37             phi[i] = i - 1; mu[i] = -1; d[i] = 2;
38             cnt[i] = 1; p_pow[i] = i; core[i] = 1;
39             sum_p[i] = 1 + (ll)i; sigma[i] = sum_p[i];
40         }

```

```

35     for (int p : primes) {
36         long long ip = 1LL * i * p;
37         if (ip > n) break;
38         lp[ip] = p;
39         if (p == lp[i]) {
40             cnt[ip] = cnt[i] + 1; p_pow[ip] = p_pow[i] * p;
41             core[ip] = core[i];
42             sum_p[ip] = sum_p[i] + p_pow[ip];
43             phi[ip] = phi[i] * p; mu[ip] = 0;
44             d[ip] = d[core[ip]] * (cnt[ip] + 1);
45             sigma[ip] = sigma[core[ip]] * sum_p[ip];
46             break; // critical for linear complexity
47         } else {
48             cnt[ip] = 1; p_pow[ip] = p; core[ip] = i;
49             sum_p[ip] = 1 + (ll)p;
50             phi[ip] = phi[i] * (p - 1); mu[ip] = -mu[i];
51             d[ip] = d[i] * 2;
52             sigma[ip] = sigma[i] * sum_p[ip];
53         }
54     }
55 }
56
57 // Optional helper: factorize x in O(log x) using lp
58 // (requires x in [2..n])
59 static inline std::vector<std::pair<int,int>>
60 factorize(int x, const std::vector<int> &lp) {
61     std::vector<std::pair<int,int>> res;
62     while (x > 1) {
63         int p = lp[x], e = 0;
64         do { x /= p; ++e; } while (x % p == 0);
65         res.push_back({p, e});
66     }
67     return res;
68 }

```

13 Numerical

13.1 Polynomials and recurrences

```

1/* Author: David Rydh, Per Austrin
2* Description: */
3#pragma once
4struct Poly {
5    vector<double> a;
6    double operator()(double x) const {
7        double val = 0;
8        for (int i = sz(a); i--;) (val *= x) += a[i];
9        return val;
10    }
11    void diff() {
12        rep(i, 1, sz(a)) a[i-1] = i*a[i];
13        a.pop_back();
14    }
15    void divroot(double x0) {
16        double b = a.back(), c; a.back() = 0;
17        for(int i=sz(a)-1; i--;) c = a[i], a[i] = a[i+1]*x0+b,
18        b=c;
19        a.pop_back();
20    };
21
22    /* Author: Per Austrin (License: CC0)
23    * Description: Finds the real roots to a polynomial.
24    * Usage: polyRoots({{2,-3,1}},-1e9,1e9) // solve x^2-3x+2 =
25    * Time: O(n^2 \log(1/epsilon)) */
26 #include "Polynomial.h"
27 vector<double> polyRoots(Poly p, double xmin, double xmax) {
28     if (sz(p.a) == 2) { return {-p.a[0]/p.a[1]}; }
29     vector<double> ret;
30     Poly der = p;
31     der.diff();
32     auto dr = polyRoots(der, xmin, xmax);
33     dr.push_back(xmin-1);
34     dr.push_back(xmax+1);
35     sort(all(dr));
36     rep(i, 0, sz(dr)-1) {
37         double l = dr[i], h = dr[i+1];
38         bool sign = p(l) > 0;
39         if (sign ^ (p(h) > 0)) {
40             rep(it, 0, 60) { // while (h - l > 1e-8)
41                 double m = (l + h) / 2, f = p(m);
42                 if ((f <= 0) ^ sign) l = m;
43                 else h = m;
44             }
45             ret.push_back((l + h) / 2);
46         }
47     }
48     return ret;
49 }

```

```

1/* Author: Simon Lindholm (License: CC0)
2* Description: Given $n$ points $(x[i], y[i])$, computes an
  $n-1$-degree polynomial $p$ that
3* passes through them: $p(x) = a[0]*x^0 + \dots +
  a[n-1]*x^{n-1}$.
4* For numerical precision, pick $x[k] = c*\cos(k/(n-1)*\pi)$,
  $k=0 \dots n-1$.
5* Time: $O(n^2)$ */
6#pragma once
7typedef vector<double> vd;
8vd interpolate(vd x, vd y, int n) {
9    vd res(n), temp(n);
10   rep(k,0,n-1) rep(i,k+1,n)
11       y[i] = (y[i] - y[k]) / (x[i] - x[k]);
12   double last = 0; temp[0] = 1;
13   rep(k,0,n) rep(i,0,n) {
14       res[i] += y[k] * temp[i];
15       swap(last, temp[i]);
16       temp[i] -= last * x[k];
17   }
18   return res;
19}

1/* Author: koukanni (License: CC0)
2* Description: Lagrange interpolation for polynomial
  evaluation at integer points.
3* Given polynomial values $f[0], f[1], \dots, f[n-1]$, computes
  $f(c)$.
4* Time: $O(n)$
5* Status: tested */
6Mint lagrange_iota(const vector<Mint> &f, const int c) {
7    const int n = int(size(f));
8    if (c < n) {
9        return f[c];
10    }
11    vector<Mint> fac(n), ifac(n);
12    fac[0] = 1;
13    for (int i = 1; i < n; i++) fac[i] = fac[i - 1] * i;
14    ifac[n - 1] = fac[n - 1].inv();
15    for (int i = n - 1; i >= 1; i--) ifac[i - 1] = ifac[i] *
  i;
16    vector<Mint> g(n);
17    for (int i = 0; i < n; i++) {
18        g[i] = f[i] * ifac[i] * ifac[n - 1 - i];
19        if ((n - 1 - i) & 1) g[i] *= -1;
20    }
21    vector<Mint> lp(n + 1), rp(n + 1);
22    lp[0] = rp[n] = 1;
23    for (int i = 0; i < n; i++) lp[i + 1] = lp[i] * Mint(c -
  i);
24    for (int i = n - 1; i >= 0; i--) rp[i] = rp[i + 1] *
  Mint(c - i);
25    Mint ans = 0;
26    for (int i = 0; i < n; i++) ans += g[i] * lp[i] * rp[i +
  1];
27    return ans;
28}

1/* Author: Lucian Bicsi (License: CC0)
2* Description: Recovers any $n$-order linear recurrence
  relation from the first
3* $2n$ terms of the recurrence.
4* Useful for guessing linear recurrences after brute-forcing
  the first terms.
5* Should work on any field, but numerical stability for
  floats is not guaranteed.
6* Output will have size $\le n$.
7* Usage: berlekampMassey({0, 1, 1, 3, 5, 11}) // {1, 2}
8* Time: $O(N^2)$, Status: brute-force-tested mod 5 for $n \le 5$
  and all $s$ */
9#include "../number-theory/ModPow.h"
10vector<ll> berlekampMassey(vector<ll> s) {
11    int n = sz(s), L = 0, m = 0;
12    vector<ll> C(n), B(n), T;
13    C[0] = B[0] = 1;
14    ll b = 1;
15    rep(i,0,n) { ++m;
16        ll d = s[i] % mod;
17        rep(j,1,L+1) d = (d + C[j] * s[i - j]) % mod;
18        if (!d) continue;
19        T = C; ll coef = d * modpow(b, mod-2) % mod;
20        rep(j,m,n) C[j] = (C[j] - coef * B[j - m]) % mod;
21        if (2 * L > i) continue;
22        L = i + 1 - L; B = T; b = d; m = 0;
23    }
24    // assert(2 * L + 30 <= n);
25    C.resize(L + 1); C.erase(C.begin());
26    for (ll& x : C) x = (mod - x) % mod;
27    return C;
28}

```

```

1/* Author: Lucian Bicsi (License: CC0)
2* Description: Generates the $k$'th term of an $n$-order
3* linear recurrence $S[i] = \sum_j S[i-j-1]tr[j]$,
4* given $S[0] \dots \ge n-1$ and $tr[0] \dots n-1$.
5* Faster than matrix multiplication.
6* Useful together with Berlekamp-Massey.
7* Usage: linearRec({0, 1}, {1, 1}, k) // $k$'th Fibonacci
  number
8* Time: $O(n^2 \log k)$
9* Status: brute-force-tested mod 5 for $n \le 5$ */
10const ll mod = 5; /** exclude-line */
11typedef vector<ll> Poly;
12ll linearRec(Poly S, Poly tr, ll k) {
13    int n = sz(tr);
14    auto combine = [&](Poly a, Poly b) {
15        Poly res(n * 2 + 1);
16        rep(i,0,n+1) rep(j,0,n+1)
17            res[i + j] = (res[i + j] + a[i] * b[j]) % mod;
18        for (int i = 2 * n; i > n; --i) rep(j,0,n)
19            res[i - 1 - j] = (res[i - 1 - j] + res[i] * tr[j]) %
  mod;
20        res.resize(n + 1);
21        return res;
22    };
23    Poly pol(n + 1), e(pol);
24    pol[0] = e[1] = 1;
25    for (++k; k; k /= 2) {
26        if (k % 2) pol = combine(pol, e);
27        e = combine(e, e);
28    }
29    ll res = 0;
30    rep(i,0,n) res = (res + pol[i + 1] * S[i]) % mod;
31    return res;
32}

```

13.2 Optimization

```

1/* Author: Ulf Lundstrom (License: CC0)
2* Description: Finds the argument minimizing the function
  $f$ in the interval $[a,b]$
3* assuming $f$ is unimodal on the interval, i.e. has only
  one local minimum and no local
4* maximum. The maximum error in the result is $eps$. Works
  equally well for maximization
5* with a small change in the code. See TernarySearch.h in
  the Various chapter for a
6* discrete version.
7* Usage: double func(double x) { return 4+x-.3*x*x; }
8* double xmin = gss(-1000,1000,func);
9* Time: $O(\log((b-a) / \epsilon))$, Status: tested */
10// It is important for $r$ to be precise, otherwise we don't
  necessarily maintain the inequality $a < x_1 < x_2 < b$.
11double gss(double a, double b, double (*f)(double)) {
12    double r = (sqrt(5)-1)/2, eps = 1e-7;
13    double x1 = b - r*(b-a), x2 = a + r*(b-a);
14    double f1 = f(x1), f2 = f(x2);
15    while (b-a > eps)
16        if (f1 < f2) { //change to > to find maximum
17            b = x2; x2 = x1; f2 = f1;
18            x1 = b - r*(b-a); f1 = f(x1);
19        } else {
20            a = x1; x1 = x2; f1 = f2;
21            x2 = a + r*(b-a); f2 = f(x2);
22        }
23    return a;
24}

1/* Author: Simon Lindholm (License: CC0)
2* Description: Poor man's optimization for unimodal
  functions.
3* Status: used with great success */
4typedef array<double, 2> P;
5template<class F> pair<double, P> hillClimb(P start, F f) {
6    pair<double, P> cur(f(start), start);
7    for (double jmp = 1e9; jmp > 1e-20; jmp /= 2) {
8        rep(j,0,100) rep(dx,-1,2) rep(dy,-1,2) {
9            P p = cur.second;
10            p[0] += dx*jmp;
11            p[1] += dy*jmp;
12            cur = min(cur, make_pair(f(p), p));
13        }
14    }
15    return cur;
16}

1/* Author: Simon Lindholm (License: CC0)
2* Description: Simple integration of a function over an
  interval using
3* Simpson's rule. The error should be proportional to $h^4$,
  although in
4* practice you will want to verify that the result is stable
  to desired

```

```

5 * precision when epsilon changes.
6 * Status: mostly untested */
7 template<class F>
8 double quad(double a, double b, F f, const int n = 1000) {
9     double h = (b - a) / 2 / n, v = f(a) + f(b);
10    rep(i, 1, n*2)
11        v += f(a + i*h) * (i&1 ? 4 : 2);
12    return v * h / 3;
13 }

1 /* Author: Simon Lindholm (License: CC0)
2 * Description: Fast integration using an adaptive Simpson's
   rule.
3 * Usage:
4 * double sphereVolume = quad(-1, 1, [](double x) {
5 *     return quad(-1, 1, [](double y) {
6 *         return quad(-1, 1, [](double z) {
7 *             return x*x + y*y + z*z < 1; });});});
8 * Status: mostly untested */
9 typedef double d;
10 #define S(a,b) (f(a) + 4*f((a+b) / 2) + f(b)) * (b-a) / 6
11 template <class F>
12 d rec(F& f, d a, d b, d eps, d S) {
13     d c = (a + b) / 2;
14     d S1 = S(a, c), S2 = S(c, b), T = S1 + S2;
15     if (abs(T - S) <= 15 * eps || b - a < 1e-10)
16         return T + (T - S) / 15;
17     return rec(f, a, c, eps / 2, S1) + rec(f, c, b, eps / 2,
18     S2);
19 }
20 template<class F>
21 d quad(d a, d b, F f, d eps = 1e-8) {
22     return rec(f, a, b, eps, S(a, b));
23 }

1 /* Author: Stanford (License: MIT)
2 * Description: Solves a general linear maximization problem:
   maximize $c^T x$ subject to $Ax \le b$, $x \ge 0$.
3 * Returns -inf if there is no solution, inf if there are
   arbitrarily good solutions, or the maximum value of $c^T x$
   otherwise.
4 * The input vector is set to an optimal $x$ (or in the
   unbounded case, an arbitrary solution fulfilling the
   constraints).
5 * Numerical stability is not guaranteed. For better
   performance, define variables such that $x = 0$ is viable.
6 * Usage:
7 * vvd A = {{1,-1}, {-1,1}, {-1,-2}};
8 * vd b = {1,1,-4}, c = {-1,-1}, x;
9 * T val = LPSolver(A, b, c).solve(x);
10 * Time: $O(NM * \#pivots)$, where a pivot may be e.g. an edge
   relaxation. $O(2^n)$ in the general case.
11 * Status: seems to work? */
12 typedef double T; // long double, Rational, double +
   mod<P>...
13 typedef vector<T> vd;
14 typedef vector<vd> vvd;
15 const T eps = 1e-8, inf = 1/.0;
16 #define MP make_pair
17 #define ltj(X) if(s == -1 || MP(X[j],N[j]) < MP(X[s],N[s]))
   s=j
18 struct LPSolver {
19     int m, n; vi N, B; vvd D;
20     LPSolver(const vvd& A, const vd& b, const vd& c) :
21         m(sz(b)), n(sz(c)), N(n+1), B(m), D(m+2, vd(n+2)) {
22         rep(i,0,m) rep(j,0,n) D[i][j] = A[i][j];
23         rep(i,0,m) { B[i] = n+i; D[i][n] = -1; D[i][n+1] =
24         b[i]; }
25         rep(j,0,n) { N[j] = j; D[m][j] = -c[j]; }
26         N[n] = -1; D[m+1][n] = 1;
27     }
28     void pivot(int r, int s) {
29         T *a = D[r].data(), inv = 1 / a[s];
30         rep(i,0,m+2) if (i != r && abs(D[i][s]) > eps) {
31             T *b = D[i].data(), inv2 = b[s] * inv;
32             rep(j,0,n+2) b[j] -= a[j] * inv2;
33             b[s] = a[s] * inv2;
34         }
35         rep(j,0,n+2) if (j != s) D[r][j] *= inv;
36         rep(i,0,m+2) if (i != r) D[i][s] *= -inv;
37         D[r][s] = inv;
38         swap(B[r], N[s]);
39     }
40     bool simplex(int phase) {
41         int x = m + phase - 1;
42         for (;;) {
43             int s = -1;
44             rep(j,0,n+1) if (N[j] != -phase) ltj(D[x]);
45             if (D[x][s] >= -eps) return true;
46             int r = -1;
47             rep(i,0,m) {

```

```

47         if (D[i][s] <= eps) continue;
48         if (r == -1 || MP(D[i][n+1] / D[i][s], B[i])
49             < MP(D[r][n+1] / D[r][s], B[r])) r = i;
50     }
51     if (r == -1) return false;
52     pivot(r, s);
53 }
54 }
55 T solve(vd &x) {
56     int r = 0;
57     rep(i,1,m) if (D[i][n+1] < D[r][n+1]) r = i;
58     if (D[r][n+1] < -eps) {
59         pivot(r, n);
60         if (!simplex(2) || D[m+1][n+1] < -eps) return -inf;
61         rep(i,0,m) if (B[i] == -1) {
62             int s = 0;
63             rep(j,1,n+1) ltj(D[i]);
64             pivot(i, s);
65         }
66     }
67     bool ok = simplex(1); x = vd(n);
68     rep(i,0,m) if (B[i] < n) x[B[i]] = D[i][n+1];
69     return ok ? D[m][n+1] : inf;
70 }
71 }

```

13.3 Matrices

```

1 /* Author: Simon Lindholm (License: CC0)
2 * Description: Calculates determinant of a matrix. Destroys
   the matrix.
3 * Time: $O(N^3)$, Status: somewhat tested */
4 double det(vector<vector<double>>& a) {
5     int n = sz(a); double res = 1;
6     rep(i,0,n) {
7         int b = i;
8         rep(j,i+1,n) if (fabs(a[j][i]) > fabs(a[b][i])) b = j;
9         if (i != b) swap(a[i], a[b]), res *= -1;
10        res *= a[i][i];
11        if (res == 0) return 0;
12        rep(j,i+1,n) {
13            double v = a[j][i] / a[i][i];
14            if (v != 0) rep(k,i+1,n) a[j][k] -= v * a[i][k];
15        }
16    }
17    return res;
18 }

1 /* Author: Unknown
2 * Description: Calculates determinant using modular
   arithmetics.
3 * Modulos can also be removed to get a pure-integer version.
4 * Time: $O(N^3)$
5 * Status: brute-force-tested for $N \le 3$, mod $\le 7$ */
6 const ll mod = 12345;
7 ll det(vector<vector<ll>>& a) {
8     int n = sz(a); ll ans = 1;
9     rep(i,0,n) {
10        rep(j,i+1,n) {
11            while (a[j][i] != 0) { // gcd step
12                ll t = a[i][i] / a[j][i];
13                if (t) rep(k,i,n)
14                    a[i][k] = (a[i][k] - a[j][k] * t) % mod;
15                swap(a[i], a[j]);
16                ans *= -1;
17            }
18        }
19        ans = ans * a[i][i] % mod;
20        if (!ans) return 0;
21    }
22    return (ans + mod) % mod;
23 }

1 /* Author: Per Austrin, Simon Lindholm (License: CC0)
2 * Description: Solves $A * x = b$. If there are multiple
   solutions, an arbitrary one is returned.
3 * Returns rank, or -1 if no solutions. Data in $A$ and $b$
   is lost.
4 * Time: $O(n^2 m)$
5 * Status: tested on kattis:equationsolver, and brute-force-
   tested mod 3 and 5 for $n, m \le 3$ */
6 typedef vector<double> vd;
7 const double eps = 1e-12;
8 int solvilinear(vector<vd>& A, vd& b, vd& x) {
9     int n = sz(A), m = sz(x), rank = 0, br, bc;
10    if (n) assert(sz(A[0]) == m);
11    vi col(m); iota(all(col), 0);
12    rep(i,0,n) {
13        double v, bv = 0;
14        rep(r,i,n) rep(c,i,m)
15            if ((v = fabs(A[r][c])) > bv)

```

```

16     br = r, bc = c, bv = v;
17     if (bv <= eps) {
18         rep(j,i,n) if (fabs(b[j]) > eps) return -1;
19         break;
20     }
21     swap(A[i], A[br]);
22     swap(b[i], b[br]);
23     swap(col[i], col[bc]);
24     rep(j,0,n) swap(A[j][i], A[j][bc]);
25     bv = 1/A[i][i];
26     rep(j,i+1,n) {
27         double fac = A[j][i] * bv;
28         b[j] -= fac * b[i];
29         rep(k,i+1,m) A[j][k] -= fac*A[i][k];
30     }
31     rank++;
32 }
33 x.assign(m, 0);
34 for (int i = rank; i--;) {
35     b[i] /= A[i][i];
36     x[col[i]] = b[i];
37     rep(j,0,i) b[j] -= A[j][i] * b[i];
38 }
39 return rank; // (multiple solutions if rank < m)
40 }

1/* Author: Simon Lindholm (License: CC0)
2* Description: To get all uniquely determined values of $x$
3back from SolveLinear, make the following changes:
4* Status: tested on kattis:equationsolverplus, stress-tested
5*/
6#include "SolveLinear.h"
7rep(j,0,n) if (j != i) // instead of rep(j,i+1,n)
8// ... then at the end:
9x.assign(m, undefined);
10rep(i,0,rank) {
11    rep(j,rank,m) if (fabs(A[i][j]) > eps) goto fail;
12    x[col[i]] = b[i] / A[i][i];
13fail;; }

1/* Author: Simon Lindholm (License: CC0)
2* Description: Solves $Ax = b$ over $\mathbb{F}_2$. If there
3are multiple solutions, one is returned arbitrarily.
4* Returns rank, or -1 if no solutions. Destroys $A$ and $b$.
5* Time: $O(n^2 m)$
6* Status: brute-force-tested for $n, m \le 4 *$
7typedef bitset<1000> bs;
8int solveLinear(vector<bs>& A, vi& b, bs& x, int m) {
9    int n = sz(A), rank = 0, br;
10    assert(m <= sz(x));
11    vi col(m); iota(all(col), 0);
12    rep(i,0,n) {
13        for (br=i; br<n; ++br) if (A[br].any()) break;
14        if (br == n) {
15            rep(j,i,n) if(b[j]) return -1;
16            break;
17        }
18        int bc = (int)A[br]._Find_next(i-1);
19        swap(A[i], A[br]);
20        swap(b[i], b[br]);
21        swap(col[i], col[bc]);
22        rep(j,0,n) if (A[j][i] != A[j][bc]) {
23            A[j].flip(i); A[j].flip(bc);
24        }
25        rep(j,i+1,n) if (A[j][i]) {
26            b[j] ^= b[i];
27            A[j] ^= A[i];
28        }
29        rank++;
30    }
31    x = bs();
32    for (int i = rank; i--;) {
33        if (!b[i]) continue;
34        x[col[i]] = 1;
35        rep(j,0,i) b[j] ^= A[j][i];
36    }
37    return rank; // (multiple solutions if rank < m)
38 }

```

```

1/* Author: Max Bennedich
2* Description: Invert matrix $A$. Returns rank; result is
3stored in $A$ unless singular (rank < n).
4* Can easily be extended to prime moduli; for prime powers,
5repeatedly
6* set $A^{-1} = A^{-1} (2I - AA^{-1}) \pmod{p^k}$
7where $A^{-1}$ starts as
8* the inverse of $A \pmod{p}$, and $k$ is doubled in each step.
9* Time: $O(n^3)$
10* Status: Slightly tested */
11int matInv(vector<vector<double>>& A) {

```

```

9    int n = sz(A); vi col(n);
10    vector<vector<double>> tmp(n, vector<double>(n));
11    rep(i,0,n) tmp[i][i] = 1, col[i] = i;
12    rep(i,0,n) {
13        int r = i, c = i;
14        rep(j,i,n) rep(k,i,n)
15            if (fabs(A[j][k]) > fabs(A[r][c]))
16                r = j, c = k;
17        if (fabs(A[r][c]) < 1e-12) return i;
18        A[i].swap(A[r]); tmp[i].swap(tmp[r]);
19        rep(j,0,n)
20            swap(A[j][i], A[j][c]), swap(tmp[j][i], tmp[j][c]);
21        swap(col[i], col[c]);
22        double v = A[i][i];
23        rep(j,i+1,n) {
24            double f = A[j][i] / v;
25            A[j][i] = 0;
26            rep(k,i+1,n) A[j][k] -= f*A[i][k];
27            rep(k,0,n) tmp[j][k] -= f*tmp[i][k];
28        }
29        rep(j,i+1,n) A[i][j] /= v;
30        rep(j,0,n) tmp[i][j] /= v;
31        A[i][i] = 1;
32    }
33    // forget A at this point, just eliminate tmp backward
34    for (int i = n-1; i > 0; --i) rep(j,0,i) {
35        double v = A[j][i];
36        rep(k,0,n) tmp[j][k] -= v*tmp[i][k];
37    }
38    rep(i,0,n) rep(j,0,n) A[col[i]][col[j]] = tmp[i][j];
39    return n;
40 }

1/* Author: Simon Lindholm
2* Description: Invert matrix $A$ modulo a prime.
3* Returns rank; result is stored in $A$ unless singular
4(rank < n).
5* For prime powers, repeatedly set $A^{-1} = A^{-1} (2I -
6AA^{-1}) \pmod{p^k}$ where $A^{-1}$ starts as
7* the inverse of $A \pmod{p}$, and $k$ is doubled in each step.
8* Time: $O(n^3)$
9* Status: Slightly tested */
10#include "../number-theory/ModPow.h"
11int matInv(vector<vector<ll>>& A) {
12    int n = sz(A); vi col(n);
13    vector<vector<ll>> tmp(n, vector<ll>(n));
14    rep(i,0,n) tmp[i][i] = 1, col[i] = i;
15    rep(i,0,n) {
16        int r = i, c = i;
17        rep(j,i,n) rep(k,i,n) if (A[j][k]) {
18            r = j; c = k; goto found;
19        }
20        found:
21        A[i].swap(A[r]); tmp[i].swap(tmp[r]);
22        rep(j,0,n)
23            swap(A[j][i], A[j][c]), swap(tmp[j][i], tmp[j][c]);
24        swap(col[i], col[c]);
25        ll v = modpow(A[i][i], mod - 2);
26        rep(j,i+1,n) {
27            ll f = A[j][i] * v % mod;
28            A[j][i] = 0;
29            rep(k,i+1,n) A[j][k] = (A[j][k] - f*A[i][k]) % mod;
30            rep(k,0,n) tmp[j][k] = (tmp[j][k] - f*tmp[i][k]) %
31mod;
32        }
33        rep(j,i+1,n) A[i][j] = A[i][j] * v % mod;
34        rep(j,0,n) tmp[i][j] = tmp[i][j] * v % mod;
35        A[i][i] = 1;
36    }
37    for (int i = n-1; i > 0; --i) rep(j,0,i) {
38        ll v = A[j][i];
39        rep(k,0,n) tmp[j][k] = (tmp[j][k] - v*tmp[i][k]) % mod;
40    }
41    rep(i,0,n) rep(j,0,n)
42        A[col[i]][col[j]] = tmp[i][j] % mod + (tmp[i][j] <
430)*mod;
44    return n;
45 }

```

```

1/* Author: Ulf Lundstrom, Simon Lindholm (License: CC0)
2* Description: Solves the tridiagonal matrix equation
3system:
4* [ b_0 ] [ d_0 p_0 0 0 ... 0 ] [ x_0 ]
5* [ b_1 ] [ q_0 d_1 p_1 0 ... 0 ] [ x_1 ]
6* [ b_2 ] [ 0 q_1 d_2 p_2 ... 0 ] [ x_2 ]
7* [ ... ] [ ... ... ... ... ] [ ... ]
8* [ b_{n-1} ] [ 0 0 ... 0 q_{n-2} d_{n-1} ] [ x_{n-1} ]
9* Application:

```

```

9 *   Solves linear recurrence systems of the form:
10 *   a_i = b_i * a_{i-1} + c_i * a_{i+1} + d_i (1 <= i <=
11 *   n)
12 *   where a_0, a_{n+1}, b_i, c_i, and d_i are given.
13 *   The solution vector a can be obtained via:
14 *   d = { 1, -1, -1, ..., -1, 1 }
15 *   p = { 0, c_1, c_2, ..., c_n }
16 *   q = { b_1, b_2, ..., b_n, 0 }
17 *   b = { a_0, d_1, d_2, ..., d_n, a_{n+1} }
18 * Numerical Stability:
19 * - Fails if the solution is not unique.
20 * - Numerically stable without pivot checks if:
21 *   1) Strictly diagonally dominant:
22 *     |d_i| > |p_i| + |q_{i-1}| for all i, OR
23 *     |d_i| > |p_{i-1}| + |q_i| for all i
24 *   2) The matrix is symmetric positive-definite.
25 * Complexity: O(N) time, O(N) space. Status: Brute-force
26 * tested mod 5 and 7, stress-tested for real matrices. */
27 typedef double T;
28 vector<T> tridiagonal(vector<T> diag, const vector<T>&
29 super,
30 const vector<T>& sub, vector<T> b) {
31     int n = sz(b); vi tr(n);
32     rep(i, 0, n-1) {
33         if (abs(diag[i]) < 1e-9 * abs(super[i])) { // diag[i] ==
34             0
35             b[i+1] -= b[i] * diag[i+1] / super[i];
36             if (i+2 < n) b[i+2] -= b[i] * sub[i+1] / super[i];
37             diag[i+1] = sub[i]; tr[i+1] = 1;
38         } else {
39             diag[i+1] -= super[i] * sub[i] / diag[i];
40             b[i+1] -= b[i] * sub[i] / diag[i];
41         }
42     }
43     for (int i = n; i--;) {
44         if (tr[i]) {
45             swap(b[i], b[i-1]);
46             diag[i-1] = diag[i];
47             b[i] /= super[i-1];
48         } else {
49             b[i] /= diag[i];
50             if (i) b[i-1] -= b[i] * super[i-1];
51         }
52     }
53     return b;
54 }

```

13.4 Fourier transforms

```

1 /**
2 * Author: chilli, Ludo Pulles, Simon Lindholm (License:
3 * CC0)
4 * Description: Higher precision FFT, can be used for
5 * convolutions modulo arbitrary integers
6 * as long as N log_2N * mod < 8.6e14 (in practice 10^16 or
7 * higher).
8 * Inputs must be in [0, mod).
9 * Time: O(N log N), where N = |A| + |B| (twice as slow as
10 * NTT or normal FFT), Status: stress-tested */
11 typedef complex<double> C;
12 typedef vector<ll> vl;
13 void fft(vector<C>& a) {
14     int n = sz(a), L = 31 - __builtin_clz(n);
15     static vector<complex<long double>> R(2, 1);
16     static vector<C> rt(2, 1);
17     for (static int k = 2; k < n; k *= 2) {
18         R.resize(n); rt.resize(n);
19         auto x = polar(1.0L, acos(-1.0L) / k);
20         rep(i, k, 2 * k) rt[i] = R[i] = i & 1 ? R[i / 2] * x :
21             R[i / 2];
22     }
23     vi rev(n);
24     rep(i, 0, n) rev[i] = (rev[i / 2] | (i & 1) << L) / 2;
25     rep(i, 0, n) if (i < rev[i]) swap(a[i], a[rev[i]]);
26     for (int k = 1; k < n; k *= 2)
27         for (int i = 0; i < n; i += 2 * k) rep(j, 0, k) {
28             auto x = (double *) &rt[j + k], y = (double *) &a[i + j
29                 + k];
30             C z(x[0] * y[0] - x[1] * y[1], x[0] * y[1] + x[1] *
31                 y[0]);
32             a[i + j + k] = a[i + j] - z;
33             a[i + j] += z;
34         }
35 }
36 template<int M> vl convMod(const vl &a, const vl &b) {
37     if (a.empty() || b.empty()) return {};
38     vl res(sz(a) + sz(b) - 1);
39     int B = 32 - __builtin_clz(sz(res)), n = 1 << B, cut =
40         int(sqrt(M));
41     vector<C> L(n), R(n), outs(n), outl(n);

```

```

35     rep(i, 0, sz(a)) L[i] = C((int)a[i] / cut, (int)a[i] %
36         cut);
37     rep(i, 0, sz(b)) R[i] = C((int)b[i] / cut, (int)b[i] %
38         cut);
39     fft(L), fft(R);
40     rep(i, 0, n) {
41         int j = -i & (n - 1);
42         outl[j] = (L[i] + conj(L[j])) * R[i] / (2.0 * n);
43         outs[j] = (L[i] - conj(L[j])) * R[i] / (2.0 * n) / 1i;
44     }
45     fft(outl), fft(outs);
46     rep(i, 0, sz(res)) {
47         ll av = ll(real(outl[i]) + .5), cv = ll(imag(outs[i])
48             + .5);
49         ll bv = ll(imag(outl[i]) + .5) + ll(real(outs[i]) + .5);
50         res[i] = ((av % M * cut + bv) % M * cut + cv) % M;
51     }
52     return res;
53 }
54
55 /* Author: Lucian Bicsi (License: GNU Free Documentation
56 License 1.2)
57 * Description: Transform to a basis with fast convolutions
58 of the form
59 * c[z] = \sum_z x \oplus y a[x] * b[y]
60 * where \oplus is one of AND, OR, XOR.
61 * The size of $a$ must be a power of 2.
62 * Time: O(N log N), Status: stress-tested */
63 void FST(vi& a, bool inv) {
64     for (int n = sz(a), step = 1; step < n; step *= 2) {
65         for (int i = 0; i < n; i += 2 * step) rep(j, i, i+step) {
66             int &u = a[j], &v = a[j + step]; tie(u, v) =
67                 inv ? pii(v - u, u) : pii(v, u + v); // AND
68             // inv ? pii(v, u - v) : pii(u + v, u); // OR ///
69             include-line
70             // pii(u + v, u - v); // XOR ///
71             include-line
72         }
73     }
74     // if (inv) for (int& x : a) x /= sz(a); // XOR only ///
75     include-line
76 }
77 vi conv(vi a, vi b) {
78     FST(a, 0); FST(b, 0);
79     rep(i, 0, sz(a)) a[i] *= b[i];
80     FST(a, 1); return a;
81 }
82 }

```

14 Combinatorics

14.1 Catalan Number

$$C_0 = 1, C_n = \sum_{i=0}^{n-1} C_i C_{n-1-i}, C_n = C_n^{2n} - C_{n-1}^{2n}$$

0	1	1	2	5
4	14	42	132	429
8	1430	4862	16796	58786
12	208012	742900	2674440	9694845

14.2 Bertrand's Ballot Theorem

- A always > B: $C(p+q, p) - 2C(p+q-1, p)$
- A always >= B: $C(p+q, p) \times \frac{p+1-q}{p+1}$

14.3 Burnside's Lemma

Let X be the original set.

Let G be the group of operations acting on X .

Let X^g be the set of x not affected by g .

Let X/G be the set of orbits. Then the following equation holds:

$$|X/G| = \frac{1}{|G|} \sum_{g \in G} |X^g|$$

15 Special Numbers

15.1 Fibonacci Series

1	1	1	2	3
5	5	8	13	21
9	34	55	89	144
13	233	377	610	987
17	1597	2584	4181	6765
21	10946	17711	28657	46368
25	75025	121393	196418	317811
29	514229	832040	1346269	2178309
33	3524578	5702887	9227465	14930352

$$f(45) \approx 10^9, f(88) \approx 10^{18}$$

15.2 Prime Numbers

- $\pi(n) \equiv \text{Number of primes } \leq n \approx \frac{n}{(\ln n)-1}$
 $\pi(100) = 25, \pi(200) = 46$
 $\pi(500) = 95, \pi(1000) = 168$
 $\pi(2000) = 303, \pi(4000) = 550$
 $\pi(10^4) = 1229, \pi(10^5) = 9592$
 $\pi(10^6) = 78498, \pi(10^7) = 664579$

15.3 Number of Divisors

- If $n = \prod p_i^{a_i}$, then $\tau(n) = \prod (a_i + 1)$
- Maximum $\tau(n)$ for $n \leq 10^k$:

k	$\max \tau(n)$	k	$\max \tau(n)$	k	$\max \tau(n)$
3	32	9	1344	15	26880
4	64	10	2304	16	41472
5	128	11	4032	17	64512
6	240	12	6720	18	103680
7	448	13	10752		
8	768	14	17280		

- Useful bounds: $n \leq 10^6 \Rightarrow \tau(n) \leq 240$
 $n \leq 10^9 \Rightarrow \tau(n) \leq 1344$
 $n \leq 10^{12} \Rightarrow \tau(n) \leq 6720$
 $n \leq 10^{15} \Rightarrow \tau(n) \leq 26880$
 $n \leq 10^{18} \Rightarrow \tau(n) \leq 103680$

15.4 Distinct Prime Factors

- Let $\omega(n)$ = number of distinct prime factors.
- Minimum number with k distinct prime factors is the product of the first k primes.
 - $2 \cdot 3 \cdot 5 \cdot 7 \cdot 11 \cdot 13 \cdot 17 \cdot 19 = 9699690$
 - $2 \cdot 3 \cdot \dots \cdot 23 = 223092870$
 - $2 \cdot 3 \cdot \dots \cdot 29 = 6469693230$
 - $n \leq 10^9 \Rightarrow \omega(n) \leq 9, n \leq 10^{18} \Rightarrow \omega(n) \leq 15$
- Number of square-free divisors = $2^{\omega(n)}$
 - $n \leq 10^9 \Rightarrow \leq 512, n \leq 10^{18} \Rightarrow \leq 32768$