



Iris, every location: error of each donor in units of the dataset mean

	Target	Repeat (other photo)	Mirror side (fellow eye)	Stranger	16 look-alikes	Same sex and age	Dataset mean
UTIRIS near-infrared						not available (no sex or age in the dataset)	
	mean iris strip (anatomy, z units)	median 0.42 x mean split-half r -0.00	median 1.19 x mean split-half r 0.60	median 1.96 x mean ~ 2 by construction	median 0.55 x mean split-half r 0.89		MSE = 1 x mean (shown: V, z units, 0 to 1.3)
UPOL visible light						not available (no sex or age in the dataset)	
	mean iris strip (anatomy, z units)	median 0.17 x mean split-half r 0.92	median 1.22 x mean split-half r 0.69	median 1.97 x mean ~ 2 by construction	median 0.67 x mean split-half r 0.65		MSE = 1 x mean (shown: V, z units, 0 to 1.1)
UTIRIS visible light						not available (no sex or age in the dataset)	
	mean iris strip (anatomy, z units)	median 0.60 x mean split-half r 0.50	median 1.29 x mean split-half r 0.16	median 1.97 x mean ~ 2 by construction	median 0.66 x mean split-half r 0.39		MSE = 1 x mean (shown: V, z units, 0 to 0.6)



One red scale 0 to 2.4 (dataset mean column: own scale): darker = larger error; 1 = dataset mean, 2 = stranger. Pupil in the centre, limbus outside; dark grey = outside the region valid in 90% of eyes (eyelids).
Masked Gaussian window sd 16/sqrt(12) px on the 64 x 256 strip, wrapped in angle; each donor's error is divided by the dataset mean's on the same pixels. frame P2 (Worldcoin open-iris segmentation): Kate accepted P2 on the trial and frame QC sheets on 7 Nov 2026 (' хорошо да берем'); the lid-shadow mask (z < -4 connected to the lid) was added after that and its final sheets are not yet re-shown to Kate