Rakuten Ichiba API
- Rakuten Ichiba Item Search API
- Rakuten Ichiba Genre Search API
- Rakuten Ichiba Attribute Search API
- Rakuten Ichiba Tag Search API
- Rakuten Ichiba Ranking API
- Rakuten Product Search API

Rakuten Books APIs
Rakuten Travel APIs
Rakuten Recipe APIs
Rakuten Kobo APIs
Rakuten GORA APIs

# API Documentation

## Rakuten Ichiba Attribute Search API (version:2026-04-01)

API Test Form →

- Endpoint
- Input Parameters
- Error
- Input Headers
- Output Parameters

The Rakuten Ichiba Attribute Search API can retrieve attribute information for items in Rakuten Ichiba. Developers can retrieve attribute information by specifying Genre ID and optionally Attribute ID.

### Endpoint (REST/JSON format)

```
https://openapi.rakuten.co.jp/ichibagt/api/IchibaAttribute/Search/2026040
```

*The JSONP format allows a JavaScript callback function to be specified as an input parameter.

The request URL below can be used to retrieve attribute information for a specific genre. (In a real use, please combine the request URL into one line.)

```
https://openapi.rakuten.co.jp/ichibagt/api/IchibaAttribute/Search/2026040
applicationId=[APPLICATION ID]&
genreId=[GENRE ID]
```

*If many accesses to an identical URL are made in a short time, the URL may be become unresponsive for a fixed period of time. Please take care during testing.

To the top of the page ↑

### Input headers

Rakuten Ichiba Attribute Search API input headers version:2026-04-01

| ID | Header name | Header | Type (maximum bytes in parentheses) | Required | Default | Comment |
|---|---|---|---|---|---|---|
| Division: Shared headers | | | | | | |
| 1 | Access key 【NEW】 | accessKey | String | ○ | - | Can be provided in either header or as query parameter<br>Required along with app ID query parameter<br>Check here |

To the top of the page ↑

### Input Parameters

Rakuten Ichiba Attribute Search API Input parameters version:2026-04-01

| ID | Item name | Parameter | Type (maximum bytes in parentheses) | Required | Default | Comment |
|---|---|---|---|---|---|---|
| Division: Shared parameters | | | | | | |
| 1 | App ID | applicationId | String | ○ | - | Required along with access key<br>Check here |
| 2 | Access Key 【NEW】 | accessKey | String | ○ | - | Can be provided in either header or as query parameter<br>Required along with app ID<br>Check here |
| 3 | Affiliate ID | affiliateId | String | - | - | Check here |
| 4 | Response format | format | String | - | json | Either JSON or XML<br>When JSON is specified the callback parameter can also be set in order to use JSONP. |
| 5 | Callback function name | callback | String | - | - | Function name to be used with the JSONP output<br>(UTF-8 URL encoded string) |

| | | | | | | |
|---|---|---|---|---|---|---|
| | | | | | | Alphanumeric characters, periods, or underscores |
| 6 | Choosing output fields | elements | String | - | - | By default, API response all of the fields. You can change response fields by this parameter. This parameter's data is separated by comma(,).<br>For example, following request will response only itemName, itemPrice and itemUrl.<br>`elements=itemName,itemPrice,itemUrl` |
| 7 | Format version | formatVersion | int | - | 1 | Response format version.<br>If `formatVersion=2` is set, the response format (JSON) will be improved.<br>In case of `formatVersion=1` :<br>Our API response will be returned in Array format as the followings.<br>You would need to use notation `items[0].item.itemName` To access `itemName` parameter.<br>`{"items": [ {"item": { "itemName": "a", "itemPrice": 10 }}, {"item": { "itemName": "b", "itemPrice": 20 }} ]}`<br>In case of `formatVersion=2` :<br>Our API response will be returned in Array format as the followings.<br>You can use notation `items[0].itemName` To access `itemName` parameter.<br>`{"items": [ { "itemName": "a", "itemPrice": 10 }, { "itemName": "b", "itemPrice": 20 } ]}` |
| Division : service specific parameters | | | | | | |
| 1 | Genre ID | genreId | string | ◯ | - | Genre ID to search attributes for |
| 2 | Attribute ID | attributeId | string | - | - | Optional: Specific attribute ID to retrieve |

To the top of the page ↑

### Output parameters

Rakuten Ichiba Attribute Search API Output Parameters version:2026-04-01

| Division : service specific parameters | | | | |
|---|---|---|---|---|
| 1 | Attribute information | Attribute information | attributes | Array of attribute information |
| 2 | | Attribute ID | attributeId | Attribute ID |
| 3 | | Attribute name | nameJa | Attribute name (Japanese) |

To the top of the page ↑

### Error

Error messages are displayed in the form of HTTP status code and its response body

| HTTP Status Code | Description | Response body example (JSON) |
|---|---|---|
| 400 | Parameter error (or required parameters were insufficient) | If *applicationId* is not set<br>`{ "error": "wrong_parameter", "error_description": "specify valid applic }`<br>If *keyword* is not valid (only 1 character given, etc.)<br>`{ "error": "wrong_parameter", "error_description": "keyword parameter is }` |
| 404 | If data not found. | `{ "error": "not_found", "error_description": "not found" }` |
| 429 | Too many requests | This error will be displayed if the number of API requests has been exceeded.<br>Please try access again after an amount of time. |

| | | |
|---|---|---|
| | | {<br>"error": "too_many_requests",<br>"error_description": "number of allowed re<br>} |
| 500 | Internal error in Rakuten Web Service | An internal system error occured. If you continue seeing this message for a long period, please give your inquiry via this link<br>{<br>"error": "system_error",<br>"error_description": "api logic error"<br>} |
| 503 | Unavailable due to maintenance or overloaded | Maintenance (the API name will be displayed in *XXX/XXX*)<br>{<br>"error": "service_unavailable",<br>"error_description": "XXX/XXX is under mai<br>} |

Response body format is display in *format*.

| format | Error output example |
|---|---|
| json | {<br>"error": "wrong_parameter",<br>"error_description": "page must be a numbe<br>} |
| xml | <?xml version="1.0" encoding="UTF-8"?><br><root><br><error>wrong_parameter</error><br><error_description>page must be a number</<br></root> |

To the top of the page ↑

API Test Form →

> How to develop



Copyright © 1997-2026 Rakuten Group. All Rights Reserved.