Rakuten Ichiba API
- Rakuten Ichiba Item Search API
- Rakuten Ichiba Genre Search API
- Rakuten Ichiba Attribute Search API
- Rakuten Ichiba Tag Search API
- Rakuten Ichiba Ranking API
- Rakuten Product Search API

Rakuten Books APIs
Rakuten Travel APIs
Rakuten Recipe APIs
Rakuten Kobo APIs
Rakuten GORA APIs

API Documentation

Rakuten Ichiba Genre Search API (version:2026-04-01)

API Test Form →

- Endpoint
- Input Parameters
- Error
- Input Headers
- Output Parameters
- Old Versions

The Rakuten Genre Search API can retrieve genre names and their structure that are used in Rakuten Ichiba. Developers can retrieve the genre information using Genre ID.

Endpoint (REST/JSON format)

```
https://openapi.rakuten.co.jp/ichibagt/api/IchibaGenre/Search/20260401?[p
```

*The JSONP format allows a JavaScript callback function to be specified as an input parameter.

The request URL below can be used, in order to retrieve the first level in a genre list. (In a real use, please combine the request URL into one line.)

```
https://openapi.rakuten.co.jp/ichibagt/api/IchibaGenre/Search/20260401?
applicationId=[APPLICATION ID]&
genreId=0
```

*If many accesses to an identical URL are made in a short time, the URL may be become unresponsive for a fixed period of time. Please take care during testing.

To the top of the page ↑

Input headers

Rakuten Ichiba Genre Search API input headers version:2026-04-01

ID	Header name	Header	Type (maximum bytes in parentheses)	Required	Default	Comment
Division: Shared headers						
1	Access key 【NEW】	accessKey	String	○	-	Can be provided in either header or as query parameter Required along with app ID query parameter Check here

To the top of the page ↑

Input Parameters

Rakuten Ichiba Genre Search API Input parameters version:2026-04-01

ID	Item name	Parameter	Type (maximum bytes in parentheses)	Required	Default	Comment
Division: Shared parameters						
1	App ID	applicationId	String	○	-	Required along with access key Check here
2	Access Key 【NEW】	accessKey	String	○	-	Can be provided in either header or as query parameter Required along with app ID Check here
3	Affiliate ID	affiliateId	String	-	-	Check here
4	Response format	format	String	-	json	Either JSON or XML When JSON is specified the callback parameter can also be set in order to use JSONP.
5	Callback function name	callback	String	-	-	Function name to be used with the JSONP output (UTF-8 URL encoded string) Alphanumeric characters, periods, or

						underscores
6	Choosing output fields	elements	String	-	-	By default, API response all of the fields. You can change response fields by this parameter. This parameter's data is separated by comma(,). For example, following request will response only itemName, itemPrice and itemUrl. `elements=itemName,itemPrice,itemUrl`

7	Format version	formatVersion	int	-	1	Response format version.
						If `formatVersion=2` is set, the response format (JSON) will be improved.
						In case of `formatVersion=1` :
						Our API response will be returned in Array format as the followings.
						You would need to use notation `items[0].item.itemName` To access `itemName` parameter.
						`{"items": [ {"item": {"itemName": "a", "itemPrice": 10 }}, {"item": {"itemName": "b", "itemPrice": 20 }} ]}`
						In case of `formatVersion=2` :
						Our API response will be returned in Array format as the followings.
						You can use notation `items[0].itemName` To access `itemName` parameter.
						`{"items": [ { "itemName": "a", "itemPrice": 10 }, { "itemName": "b", "itemPrice": 20 } ]}`

Division : service specific parameters						
1	Genre ID	genreId	string	◯	-	Use genreId=0 to search from the genre root

To the top of the page ↑

Output parameters

Rakuten Ichiba Genre Search API Output Parameters version:2026-04-01

Division : service specific parameters					
1	Genre information	Ancestor genres	Ancestor genres	ancestors	Inputted genre Id's parent genres
2			Genre ID	genreId	Genre ID
3			Genre name	jaName	Genre name (Japanese)
4			Genre level	level	Genre level , genre root has the value of 0
5		Current genre	Current genre	genre	Inputted genre ID
6			Genre ID	genreId	Genre ID
7			Genre name	jaName	Genre name (Japanese)
8			Genre level	level	Genre level
9		Sibling genres	Sibling genres	siblings	Inputted genre Id's sibling genres
10			Genre ID	genreId	Genre ID
11			Genre name	jaName	Genre name (Japanese)
12			Genre level	level	Genre level
13		Children genres	Children genres	children	Inputted genre Id's child genres
14			Genre ID	genreId	Genre ID
15			Genre name	jaName	Genre name (Japanese)
16			Genre level	level	Genre level
17	Attribute information	Attributes	Attributes	attributes	Genre attribute information
18			Attribute ID	attributeId	Attribute ID
19			Attribute name	jaName	Attribute name (Japanese)

To the top of the page ↑

Error

Error messages are displayed in the form of HTTP status code and its response body

HTTP Status Code	Description	Response body example (JSON)

400	Parameter error (or required parameters were insufficient)	If *applicationId* is not set
		`{ "error": "wrong_parameter", "error_description": "specify valid applic }`
		If *keyword* is not valid (only 1 character given, etc.)
		`{ "error": "wrong_parameter", "error_description": "keyword parameter is }`

404	If data not found.	`{ "error": "not_found", "error_description": "not found" }`
429	Too many requests	This error will be displayed if the number of API requests has been exceeded. Please try access again after an amount of time. `{ "error": "too_many_requests", "error_description": "number of allowed re }`
500	Internal error in Rakuten Web Service	An internal system error occured. If you continue seeing this message for a long period, please give your inquiry via this link `{ "error": "system_error", "error_description": "api logic error" }`
503	Unavailable due to maintenance or overloaded	Maintenance (the API name will be displayed in *XXX/XXX*) `{ "error": "service_unavailable", "error_description": "XXX/XXX is under mai }`

Response body format is display in *format*.

format	Error output example
json	`{ "error": "wrong_parameter", "error_description": "page must be a numbe }`
xml	`<?xml version="1.0" encoding="UTF-8"?> <root> <error>wrong_parameter</error> <error_description>page must be a number</ </root>`

To the top of the page ↑

Old Versions

For old versions of this API, please refer to the list below.

Version : 2017-07-11
Version : 2014-02-22
Version : 2012-07-23

To the top of the page ↑

API Test Form →

> How to develop

service

[Announcement] 02/09 Legacy version of Travel API will be shut down

Maintenance 2026-02-09

[Announcement] 02/09 Legacy version of Gora API will be shut down

Maintenance 2026-02-09

[Announcement] 02/09 Legacy version of Ichiba API will be shut down

Maintenance 2024-07-11

[Completed] [Announcement] 2024-07-18 Register New Application & Change Application Information Features Maintenance

Post

Copyright © 1997-2026 Rakuten Group. All Rights Reserved.

About Rakuten Privacy Policy Sustainability Careers