Rakuten Ichiba API
- Rakuten Ichiba Item Search API
- Rakuten Ichiba Genre Search API
- Rakuten Ichiba Attribute Search API
- Rakuten Ichiba Tag Search API
- Rakuten Ichiba Ranking API
- Rakuten Product Search API

Rakuten Books APIs
Rakuten Travel APIs
Rakuten Recipe APIs
Rakuten Kobo APIs
Rakuten GORA APIs

API Documentation

Rakuten Ichiba Item Search API (version:2026-04-01)

API Test Form →

- Endpoint
- Input Parameters
- About item-based point multipliers
- Error
- Input Headers
- Output Parameters
- About the Affiliate system
- Old Versions

The Rakuten Item Search API can retrieve data from items listed on Rakuten Ichiba. Excluded items include those co-listed, listed in auctions, listed in flea markets, or listed in customer to customer auctions (C2C). Developers can begin searching by keyword and then limit the results by shop or genre information.
This API improves on the old Rakuten Item Search API by allowing specification of output parameters, searching by item code, searching by existance of reviews, searching by whether delivery times can be specified, and other options.

Endpoint

```
https://openapi.rakuten.co.jp/ichibams/api/IchibaItem/Search/20260401?[pa
```

*The JSONP format allows a JavaScript callback function to be specified as an input parameter.

The values for the field names keyword and sort must be URL encoded in UTF-8 style.
(The whole request does not need to be encoded, only the individual value portions of it)
For example, a keyword search for "福袋" that has been ordered with the cheapest item first (sort=+itemPrice) will look like the URL below. (Don't add line breaks when actually making the request. Instead the pieces of the request should be connected together.)

```
https://openapi.rakuten.co.jp/ichibams/api/IchibaItem/Search/20260401?
applicationId=[APPLICATION ID]
&keyword=%E7%A6%8F%E8%A2%8B
&sort=%2BitemPrice
```

*If many accesses to an identical URL are made in a short time, the URL may be become unresponsive for a fixed period of time. Please take care during testing.

To the top of the page ↑

Input headers

Rakuten Ichiba Item Search API input headers version:2026-04-01

ID	Header name	Header	Type (maximum bytes in parentheses)	Required	Default	Comment
Division: Shared headers						
1	Access key 【NEW】	accessKey	String	○	-	Can be provided in either header or as query parameter Required along with app ID query parameter Check here

To the top of the page ↑

Input parameters

Rakuten Ichiba Item Search API input parameters version:2026-04-01

ID	Parameter name	Parameter	Type (maximum bytes in parentheses)	Required	Default	Comment
Division: Shared parameters						
1	App ID	applicationId	String	○	-	Required along with access key Check here
2	Access Key	accessKey	String	○	-	Can be provided in either header or as query parameter

	【NEW】					Required along with app ID Check here
3	Affiliate ID	affiliateId	String	-	-	Check here
4	Response format	format	String	-	json	Either JSON or XML When JSON is specified the callback parameter can also be set in order to use JSONP.
5	Callback function name	callback	String	-	-	Function name to be used with the JSONP output (UTF-8 URL encoded string) Alphanumeric characters, periods, or underscores
6	Choosing output fields	elements	String	-	-	By default, API response all of the fields. You can change response fields by this parameter. This parameter's data is separated by comma(,). For example, following request will response only itemName, itemPrice and itemUrl. `elements=itemName,itemPrice,itemUrl`

7	Format version	formatVersion	int	-	1	Response format version.
						If `formatVersion=2` is set, the response format (JSON) will be improved.
						In case of `formatVersion=1` :
						Our API response will be returned in Array format as the followings.
						You would need to use notation `items[0].item.itemName` To access `itemName` parameter.
						`{"items": [ {"item": {"itemName": "a", "itemPrice": 10 }}, {"item": {"itemName": "b", "itemPrice": 20 }} ]}`
						In case of `formatVersion=2` :
						Our API response will be returned in Array format as the followings.
						You can use notation `items[0].itemName`
						To access `itemName` parameter.
						`{"items": [ { "itemName": "a", "itemPrice": 10 }, { "itemName": "b", "itemPrice": 20 } ]}`

Division : service specific parameters						
1	Search keywords	keyword	String	◯ (*1)	-	UTF-8 URL encoded string • The keyword parameter can have a maximum length of 128 single byte characters • The keyword parameter is delimited with single byte space characters. This defaults to an AND operation including all the keywords. To use OR instead set the *orFlag* to *1*. • Each search keyword must be at least two single byte characters or one double byte character. • An exception is a minimum of two characters if the search keywords are using hiragana, katakana, or symbols. (*1) One of the following is required: search keyword, genre ID, item code, or shop code.
2	Shop code	shopCode	String	◯ (*1)	-	The portion of the shop URL listed as "xyz": http://www.rakuten.co.jp/[xyz] (*1) One of the following is required: search keyword, genre ID, item code, or shop code.
3	Item code	itemCode	String	◯ (*1)	-	Included in the output parameters of the Item Search, Item Ranking APIs. A value in the form of "shop:1234" (*1) A search request must contain either a keyword, a genre ID, or an item code.
4	Genre ID	genreId	long	◯ (*1)	0	ID to specify a genre in Rakuten Ichiba Please use the Rakuten Ichiba Genre Search API to look up genre names and genre relations. (*1) One of the following is required: search keyword, genre ID, item code, or shop code.
5	How many results to display on each page	hits	int	-	30	An integer between 1 and 30
6	Result page	page	int	-	1	An integer between 1 and 100

7	Sort	sort	String	-	standard	+affiliateRate： Affiliate Rate (Ascending order) -affiliateRate： Affiliate Rate (Descending order) +reviewCount： Number of reviews (Ascending order) -reviewCount： Number of reviews (Descending order) +reviewAverage： Average review rating (Ascending order) -reviewAverage： Average review rating (Descending order) +itemPrice： Price (Ascending order) -itemPrice： Price (Descending order) +updateTimestamp： Time of item update (Ascending order) -updateTimestamp： Time of item update (Descending order) standard： Rakuten standard sort *UTF-8 URL encoding is required.
8	Minimum price	minPrice	long	-	-	An integer greater than 0 and less than 999,999,999
9	Maximum price	maxPrice	long	-	-	An integer greater than 0 and less than 999,999,999 maxPrice must be larger than minPrice.
10	Availability	availability	int(1)	-	1	0: All products 1: Only available products
11	Search field	field	int(1)	-	1	0: Broad search (prefer more matches with the same keyword) 1: Restricted search (prefer fewer matches with the same keyword)
12	Platform	carrier	int(1)	-	0	Choose the target platform for type of information to return: PC, mobile, or smartphone PC: 0 mobile: 1 (*Japan only) smartphone: 2
13	Has image flag	imageFlag	int(1)	-	0	0: Search all products 1: Search only products with images
14	OR search flag	orFlag	int(1)	-	0	Choose between AND searches and OR searches when there are multiple keywords. 0: AND 1: OR *It isn't possible to use a complex search condition like "(A and B) or C".
15	Excluded keywords	NGKeyword	String	-	-	Words to exclude from search results Strings encoded with UTF-8 URL encoding Same format as *keyword*
16	Purchase type	purchaseType	int(1)	-	0	Narrow search by purchase type 0: Normal purchase 1: Periodic purchase (a service that allows customers to buy goods they choose on a cycle they specify). 2: Distribution group purchase (a service that allows the shop to choose items and also choose the number of times they are delivered).
17	Overseas shipping flag	shipOverseasFlag	int(1)	-	0	0: All products 1: Only products that can be shipped overseas
18	Overseas shipping area	shipOverseasArea	String	-	ALL	It is possible to restrict searches based on delivery areas. Check the overseas delivery area codes **shipOverseasFlag* must be *1*
19	Asuraku flag	asurakuFlag	int(1)	-	0	0: All products 1: Only items that can use the Asuraku service **From 1st July 2024 onwards, the parameter "asurakuFlag" will always be set to the value of "0".*
20	Asuraku area	asurakuArea	int	-	0	It is possible to restrict searches based on delivery areas. Check the Asuraku delivery area codes **asurakuFlag* must be *1*
21	Point multiplier flag	pointRateFlag	int(1)	-	0	0: All products 1: Only items with point multipliers
22	Point multiplier	pointRate	int	-	-	An integer from 2 to 10 (e.g. 5 means points will be multiplied by five) Read about point multipliers. **pointRateFlag* must be *1*
23	Postage flag	postageFlag	int(1)	-	0	0: All products 1: Only items with postage included/free shipping
24	Credit card flag	creditCardFlag	int(1)	-	0	0: All products 1: Only products purchaseable with credit cards

25	Giftwrap flag	giftFlag	int(1)	-	0	0: All products 1: Only products with giftwrapping available
26	Has review flag	hasReviewFlag	int(1)	-	0	0: All products 1: Only products with reviews
27	Maximum affiliate rate	maxAffiliateRate	float	-	-	A number from 1.0 to 99.9 (e.g. 5.0 for products with an affiliate rate up to 5%). Don't show if the affiliate rate is higher than specified. Up to one decimal place can be specified.
28	Minimum affiliate rate	minAffiliateRate	float	-	-	A number from 1.0 to 99.9 (e.g. 5.0 for products with an affiliate rate above 5%). Don't show if the affiliate rate is lower than specified. Up to one decimal place can be specified. Specify an affiliate rate lower than the maximum rate.
29	Has movie flag	hasMovieFlag	int(1)	-	0	0: All products 1: Only products with movies (the link to the movies will be returned)
30	Pamphlet flag	pamphletFlag	int(1)	-	0	0: All products 1: Only products with pamphlets
31	Specify delivery date flag	appointDeliveryDateFlag	int(1)	-	0	0: All products 1: Only products for which the delivery date can be specified.
32	Output elements	elements	String	-	ALL	Comma separated. When required output parameters are specified, only those parameters will be returned. (e.g elements=reviewCount,reviewAverage)
33	Genre information flag	genreInformationFlag	int(1)	-	0	0: Do not get number of item in each genre. 1: Get number of item in each genre.
34	Attribute flag	attributeFlag	int(1)	-	0	Specifies if return attribute or not. 0: Do not get attributes. 1: Get attributes. If you enable this flag, you need to set genreId (except 0)

To the top of the page ↑

Output Parameters

Rakuten Ichiba Item Search API version:2026-04-01

ID	General description	Specific description	Item name	Parameter	Comment
Division : service specific parameters					
1	Overall information		Search count	count	Total number of items in the search results
2			Page number	page	Current page number
3			First page	first	Result number to display from
4			Last page	last	Result number to display until
5			Search hits	hits	Number of results to return
6			Platform	carrier	PC: 0 mobile: 1 (*Japan only) smartphone: 2
7			Total page count	pageCount	Maximum of 100
8	Item information (Overall: ... Individual item: ...)	Item detail	Item name	itemName	To display the usual name please use *catchcopy*+*itemname*. *Depending on the setting for *carrier* the results may vary.
9			Sales message	catchcopy	
10			Item code	itemCode	
11			Item price	itemPrice	
12			Item caption	itemCaption	*Depending on the setting for *carrier* the results may vary.
13			Item URL	itemUrl	*Depending on the setting for *carrier* the results may vary. *Depending on the setting for carrier the results may vary. If you include affiliateId in the input parameter, itemUrl will be same as that of affiliateUrl. (From 2015/7/1) URL for each item, starting with https.
14			Item price basefield	itemPriceBaseField	Contains one of the following strings "item_price_min1", "item_price_min2" or "item_price_min3"

15			Item price max1	itemPriceMax1	All item price max
16			Item price max2	itemPriceMax2	Searchable item price max
17			Item price max3	itemPriceMax3	Purchasable item price max
18			Item price min1	itemPriceMin1	All item price min
19			Item price min2	itemPriceMin2	Searchable item price min
20			Item price min3	itemPriceMin3	Purchasable item price min
21			Affiliate URL	affiliateUrl	(Only when the Affiliate ID has been included as an input parameter) *Returns a URL regardless of the value of *carrier* Affiliate URL, starting with https
22			Has image flag	imageFlag	0: Items without images 1: Items with images
23			64 pixel square item image URL	smallImageUrls	Returns an array of up to three image URLs. Images size is 64 pixels square. Small Image URL (64x64), starting with https.
24			128 pixel square item image URL	mediumImageUrls	Returns an array of up to three image URLs. Images size is 128 pixels square. Medium Image URL (128x128), starting with https.
25			Availability flag	availability	0: Out of stock 1: Available
26			Tax flag	taxFlag	0: Tax included 1: Tax not included
27			Postage flag	postageFlag	0: Postage included 1: Postage not included
28			Credit card flag	creditCardFlag	0: Credit cards not accepted 1: Credit cards accepted
29			Shop of the Year flag	shopOfTheYearFlag	0: Shops that have not won Shop of the Year 1: Shops that have won Shop of the Year
30			Overseas shipping flag	shipOverseasFlag	0: Products that cannot be shipped overseas 1: Products that can be shipped overseas
31			Overseas shipping area	shipOverseasArea	Supported countries are shown, separated by slashes. (/)
32			Asuraku flag	asurakuFlag	0: No next day delivery 1: Next day delivery possible **From 1st July 2024 onwards, the parameter "asurakuFlag" will always be set to the value of "0".* *Read more about Asaraku
33			Asaraku closing time	asurakuClosingTime	Returned value takes this form: "HH:MM" *Is only returned when *asarakuFlag* is set to *1*
34			Asuraku delivery area	asurakuArea	Supported areas are shown, separated by slashes. (/) **asurakuFlag* must be *1* for this to be returned.
35			Affiliate rate	affiliateRate	
36			Sale start time	startTime	Only when a time limited sale has been set. (format is "YYYY-MM-DD HH:MM")
37			Sale end time	endTime	Only when a time limited sale has been set. (format is "YYYY-MM-DD HH:MM")
38			Review count	reviewCount	
39			Average review	reviewAverage	
40			Item point multiplier	pointRate	(e.g. 5 for a point multiplier of "5 times points." Read more about item-based point multipliers. *Only shows information for point multipliers that will not end within 24 hours.
41			Start of	pointRateStartTime	Date and time of the start of

			item point multiplier		the item-based point multiplier. *Only shows information for point multipliers that will not end within 24 hours.
42			End of item point multiplier	pointRateEndTime	Date and time of the end of the item-based point multiplier. *Only shows information for point multipliers that will not end within 24 hours.
43			Gift wrap flag	giftFlag	0: Gift wrap service unavailable 1: Gift wrap service available
44			Attribute IDs	attributeIds	Array of attribute IDs for this item.
45		Shop info	Shop name	shopName	
46			Shop code	shopCode	The portion marked "xyz" in each shop's URL: http://www.rakuten.co.jp/[xyz]
47			Shop URL	shopUrl	URL for each shop, starting with https *If you include affiliateId in the input parameter, shopUrl will be same as that of shopAffiliateUrl.(From 2015/7/1)
48			Shop Affiliate URL	shopAffiliateUrl	(Only when the Affiliate ID has been included as an input parameter) *Returns a URL regardless of the value of carrier Shop Affiliate URL, starting with https
49	Genre information	Genre information	Genre ID	genreId	
50	Attribute information	Attribute information	Attributes	attributes	
51	Number of items in each genre. （ ～	Ancestor genres	-	ancestors	Inputted genre Id's parent genres
52			Genre ID	genreId	
53			Genre name	jaName	Genre name (Japanese)
54			Genre level	level	
55		Current genre	-	genre	Genre ID from the input parameter
56			Genre ID	genreId	
57			Genre name	jaName	Genre name (Japanese)
58			Item count	itemCount	Number of item in this genre
59			Genre level	level	
60		Child genre	-	children	Inputted genre Id's child genres
61			Genre ID	genreId	
62			Genre name	jaName	Genre name (Japanese)
63			Item count	itemCount	Number of item in this genre
64			Genre level	level	
65	Attributes. （ ～	Attributes	-	attributes	Attributes array. Returned when attributeFlag=1
66			Attribute ID	attributeId	Attribute ID
67			Attribute name	jaName	Attribute name (Japanese)
68			Item Count	itemCount	Item Count

To the top of the page ↑

About Item Based Point Multipliers

With a regular purchase, 1% of the total cost will be credited as Rakuten Points. However "point multipliers" can be set for individual items for a limited period of time, multiplying the amount of Points credited with each purchase. Read more about point multipliers.

There are currently two different ways for point multipliers to be used by the shops. Item based point multipliers apply only to specially selected items in a given shop. Shop based multipliers apply to every item in a specially selected shop. Currently this API only supports item based point multipliers.

multipliers.

To the top of the page ↑

About Affiliate Commissions

Developers can use the Item Search API to make affiliate links from the returned item information. It's possible to receive affiliate commission from Rakuten Affiliate when the affiliate URL is used as the link. The steps for making the affiliate link are the same whether the carrier input parameter is PC or mobile.

When the affiliateId input parameter is included in the request the response from the API will include the affiliate URL.

To the top of the page ↑

Error

Error messages are displayed in the form of HTTP status code and its response body

HTTP Status Code	Description	Response body example (JSON)

400	Parameter error (or required parameters were insufficient)	If *applicationId* is not set
		`{ "error": "wrong_parameter", "error_description": "specify valid applic }`
		If *keyword* is not valid (only 1 character given, etc.)
		`{ "error": "wrong_parameter", "error_description": "keyword parameter is }`

404	If data not found.	`{ "error": "not_found", "error_description": "not found" }`
429	Too many requests	This error will be displayed if the number of API requests has been exceeded. Please try access again after an amount of time. `{ "error": "too_many_requests", "error_description": "number of allowed re }`
500	Internal error in Rakuten Web Service	An internal system error occured. If you continue seeing this message for a long period, please give your inquiry via this link `{ "error": "system_error", "error_description": "api logic error" }`
503	Unavailable due to maintenance or overloaded	Maintenance (the API name will be displayed in *XXX/XXX*) `{ "error": "service_unavailable", "error_description": "XXX/XXX is under mai }`

Response body format is display in *format*.

format	Error output example
json	`{ "error": "wrong_parameter", "error_description": "page must be a numbe }`
xml	`<?xml version="1.0" encoding="UTF-8"?> <root> <error>wrong_parameter</error> <error_description>page must be a number</ </root>`

To the top of the page ↑

Old Versions

For old versions of this API, please refer to the list below.

Version : 2022-06-01
Version : 2017-07-06

To the top of the page ↑

API Test Form →

How to develop

Copyright © 1997-2026 Rakuten Group. All Rights Reserved.