Rakuten Ichiba API
- Rakuten Ichiba Item Search API
- Rakuten Ichiba Genre Search API
- Rakuten Ichiba Attribute Search API
- Rakuten Ichiba Tag Search API
- Rakuten Ichiba Ranking API
- Rakuten Product Search API

Rakuten Books APIs
Rakuten Travel APIs
Rakuten Recipe APIs
Rakuten Kobo APIs
Rakuten GORA APIs

API詳細

楽天タグ検索API (version:2014-02-22)

APIテストフォーム →

- リクエストURL
- 入力ヘッダー
- 入力パラメーター
- 出力パラメーター
- エラー

楽天市場タグ検索APIは楽天市場のタグ名・タグ構造を返すAPIです。デベロッパーはタグIDを指定することでこれらの情報を得ることができます。 タグIDは、楽天市場商品検索API、楽天市場ジャンル検索APIから取得することができます。
タグに関する詳細な説明は、Q&Aや楽天ウェブサービスのブログにて記載します。

リクエストURL（REST／JSON形式の場合）

```
https://openapi.rakuten.co.jp/ichibagt/api/IchibaTag/Search/20140222?[par
```

※JSONP形式は、JSON形式で入力パラメーターにcallbackを指定することで出力されます。

たとえば、タグID「1000317」の詳細情報を取得したい場合のリクエストURLは下記になります。
（実際には改行せずに1行につなげてリクエストしてください。）

```
https://openapi.rakuten.co.jp/ichibagt/api/IchibaTag/Search/20140222?
        applicationId=[アプリID]
        &tagId=1000317
```

※短い時間の間に大量に、同一のリクエストURLへアクセスすると、一定時間利用できなくなる場合がございます。テストの際にはご注意ください。

ページの先頭へ ↑

Input headers

楽天タグ検索 API input headers version:2014-02-22

ID	Header name	Header	Type (maximum bytes in parentheses)	Required	Default	Comment
Division: Shared headers						
1	Access key 【NEW】	accessKey	String	○	-	Can be provided in either header or as query parameter Required along with app ID query parameter Check here

To the top of the page ↑

入力パラメーター

楽天タグ検索API 入力パラメータ version:2014-02-22

ID	項目名	パラメーター	型(括弧内は最大バイト数)	必須	デフォルト	備考
Division: Shared parameters						
1	App ID	applicationId	String	○	-	Required along with access key Check here
2	Access Key 【NEW】	accessKey	String	○	-	Can be provided in either header or as query parameter Required along with app ID Check here
3	Affiliate ID	affiliateId	String	-	-	Check here
4	Response format	format	String	-	json	Either JSON or XML When JSON is specified the callback parameter can also be set in order to use JSONP.

5	Callback function name	callback	String	-	-	Function name to be used with the JSONP output (UTF-8 URL encoded string) Alphanumeric characters, periods, or underscores
6	Choosing output fields	elements	String	-	-	By default, API response all of the fields. You can change response fields by this parameter. This parameter's data is separated by comma(,). For example, following request will response only itemName, itemPrice and itemUrl. `elements=itemName,itemPrice,itemUrl`

7	Format version	formatVersion	int	-	1	Response format version.
						If `formatVersion=2` is set, the response format (JSON) will be improved.
						In case of `formatVersion=1` :
						Our API response will be returned in Array format as the followings.
						You would need to use notation `items[0].item.itemName` To access `itemName` parameter.
						`{"items": [ {"item": {"itemName": "a", "itemPrice": 10 }}, {"item": {"itemName": "b", "itemPrice": 20 }} ]}`
						In case of `formatVersion=2` :
						Our API response will be returned in Array format as the followings.
						You can use notation `items[0].itemName` To access `itemName` parameter.
						`{"items": [ { "itemName": "a", "itemPrice": 10 }, { "itemName": "b", "itemPrice": 20 } ]}`

区分:サービス固有パラメーター						
1	タグID	tagId	int	◯	-	タグIDは、楽天市場商品検索API、楽天市場ジャンル検索APIから取得することができます。 0を指定することはできません。 10タグIDまでカンマ（,）区切りで指定可能

ページの先頭へ ↑

出力パラメーター

楽天タグ検索API 出力パラメーター version:2014-02-22

区分:サービス固有パラメーター					
1	タグ情報	タググループ情報	-	tagGroup	
2			タググループ名	tagGroupName	
3			タググループID	tagGroupId	
4		タグ情報	-	tags	"<tags>〜</tags>の中に複数の<tag>〜</tag>"
5			タグID	tagId	
6			タグ名	tagName	
7			親タグID	parentTagId	

ページの先頭へ ↑

Error

Error messages are displayed in the form of HTTP status code and its response body

HTTP Status Code	Description	Response body example (JSON)
400	Parameter error (or required parameters were insufficient)	If *applicationId* is not set `{ "error": "wrong_parameter", "error_description": "specify valid applic`

		`}`
		If *keyword* is not valid (only 1 character given, etc.)
		`{ "error": "wrong_parameter", "error_description": "keyword parameter is }`

404	If data not found.	`{ "error": "not_found", "error_description": "not found" }`
429	Too many requests	This error will be displayed if the number of API requests has been exceeded. Please try access again after an amount of time. `{ "error": "too_many_requests", "error_description": "number of allowed re }`
500	Internal error in Rakuten Web Service	An internal system error occured. If you continue seeing this message for a long period, please give your inquiry via this link `{ "error": "system_error", "error_description": "api logic error" }`
503	Unavailable due to maintenance or overloaded	Maintenance (the API name will be displayed in *XXX/XXX*) `{ "error": "service_unavailable", "error_description": "XXX/XXX is under mai }`

Response body format is display in *format*.

format	Error output example
json	`{ "error": "wrong_parameter", "error_description": "page must be a numbe }`
xml	`<?xml version="1.0" encoding="UTF-8"?> <root> <error>wrong_parameter</error> <error_description>page must be a number</ </root>`

To the top of the page ↑

APIテストフォーム →

開発方法

Features Maintenance

Post

Copyright © 1997-2026 Rakuten Group. All Rights Reserved.

About Rakuten Privacy Policy Sustainability Careers