

# TITLE

Konrad Cybulski

Honours Research Notes



Faculty of Information Technology  
Monash University  
Australia  
February 5, 2019

# Contents

<b>1</b>	<b>Reading List</b>	<b>2</b>
<b>2</b>	<b>Research Notes</b>	<b>4</b>
<b>3</b>	<b>Papers/Books</b>	<b>4</b>
3.1	Creating arbitrarily strong amplifiers of natural selection on graphs [1] . . . . .	4
<b>4</b>	<b>Research Ideas</b>	<b>5</b>
4.1	Generative Evolutionary Algorithms . . . . .	5
<b>5</b>	<b>Log</b>	<b>6</b>
5.1	21-28 Jan 2019 . . . . .	6

# 1 Reading List

- Ross, B. J., Ralph, W., & Zong, H. (2006, July). Evolutionary image synthesis using a model of aesthetics. In *Evolutionary Computation, 2006. CEC 2006. IEEE Congress on* (pp. 1087-1094). IEEE.  
<http://axon.cs.byu.edu/Dan/673/papers/ross.pdf>
- Machado, P., & Cardoso, A. (2000, April). NEvAr—the assessment of an evolutionary art tool. In *Proceedings of the AISB00 Symposium on Creative & Cultural Aspects and Applications of AI & Cognitive Science*, Birmingham, UK (Vol. 456).  
<https://cdv.dei.uc.pt/wp-content/uploads/2014/03/mc00.pdf>
- Cagnoni, S., Lutton, E., & Olague, G. (Eds.). (2007). *Genetic and evolutionary computation for image processing and analysis*. New York: Hindawi Publishing Corporation.  
<http://downloads.hindawi.com/books/9789774540011/art01.pdf>
- Secretan, J., Beato, N., D'Ambrosio, D. B., Rodriguez, A., Campbell, A., Folsom-Kovarik, J. T., & Stanley, K. O. (2011). Picbreeder: A case study in collaborative evolutionary exploration of design space. *Evolutionary Computation*, 19(3), 373-403.  
[https://www.mitpressjournals.org/doi/pdfplus/10.1162/EVC0\\_a\\_00030](https://www.mitpressjournals.org/doi/pdfplus/10.1162/EVC0_a_00030)
- Takagi, H. (2001). Interactive evolutionary computation: Fusion of the capabilities of EC optimization and human evaluation. *Proceedings of the IEEE*, 89(9), 1275-1296.  
<http://sclab.yonsei.ac.kr/courses/09EC/papers/IECsurvey.pdf>
- Paulinas, M., & Užinskas, A. (2007). A survey of genetic algorithms applications for image enhancement and segmentation. *Information Technology and control*, 36(3).  
<http://www.itc.ktu.lt/index.php/ITC/article/download/11886/6561>
- Romero, J. J. (2008). *The art of artificial evolution: A handbook on evolutionary art and music*. Springer Science & Business Media.  
<http://citeseerx.ist.psu.edu/viewdoc/download?doi=10.1.1.470.2312&rep=rep1&type=pdf>
- McCormack, J. (2005, March). Open problems in evolutionary music and art. In *Workshops on Applications of Evolutionary Computation* (pp. 428-436). Springer, Berlin, Heidelberg.  
<http://users.monash.edu/~jonmc/research/Papers/OpenProblemsSV.pdf>
- den Heijer, E., & Eiben, A. E. (2010, April). Comparing aesthetic measures for evolutionary art. In *European Conference on the Applications of Evolutionary Computation* (pp. 311-320). Springer, Berlin, Heidelberg.  
<http://eelcodenheijer.nl/publications/E-den-Heijer-and-AE-Eiben-Comparing-aesthetic-1.pdf>
- den Heijer, E., & Eiben, A. E. (2010, July). Using aesthetic measures to evolve art. In *Evolutionary Computation (CEC), 2010 IEEE Congress on*

(pp. 1-8). IEEE.

<http://www.eelcodenheijer.nl/publications/E-den-Heijer-and-AE-Eiben-Using-Aesthetic-M.pdf>

- den Heijer, E., & Eiben, A. E. (2011, April). Evolving art using multiple aesthetic measures. In *European Conference on the Applications of Evolutionary Computation* (pp. 234-243). Springer, Berlin, Heidelberg.  
<http://dare.ubvu.vu.nl/bitstream/handle/1871/34536/272336.pdf?sequence=1>
- Ekárt, A., Sharma, D., & Chalakov, S. (2011, April). Modelling human preference in evolutionary art. In *European Conference on the Applications of Evolutionary Computation* (pp. 303-312). Springer, Berlin, Heidelberg.  
<https://research.aston.ac.uk/portal/files/502798/ekart.pdf>
- den Heijer, E., & Eiben, A. E. (2014). Investigating aesthetic measures for unsupervised evolutionary art. *Swarm and Evolutionary Computation*, 16, 52-68.  
[https://s3.amazonaws.com/academia.edu.documents/37208620/sec2013.pdf?AWSAccessKeyId=AKIAIWOWYYGZ2Y53UL3A&Expires=1548899878&Signature=T98kzLvMluIDiePBw88y8MDxtiM%3D&response-content-disposition=inline%3B%20filename%3DInvestigating\\_aesthetic\\_measures\\_for\\_uns.pdf](https://s3.amazonaws.com/academia.edu.documents/37208620/sec2013.pdf?AWSAccessKeyId=AKIAIWOWYYGZ2Y53UL3A&Expires=1548899878&Signature=T98kzLvMluIDiePBw88y8MDxtiM%3D&response-content-disposition=inline%3B%20filename%3DInvestigating_aesthetic_measures_for_uns.pdf)
- Machado, P., Martins, T., Amaro, H., & Abreu, P. H. (2014, April). An interface for fitness function design. In *International Conference on Evolutionary and Biologically Inspired Music and Art* (pp. 13-25). Springer, Berlin, Heidelberg.  
<https://cdv.dei.uc.pt/wp-content/uploads/2014/06/mmaa14.pdf>
- den Heijer, E. (2015). Evolving symmetric and balanced art. In *Computational Intelligence* (pp. 33-47). Springer, Cham.
- den Heijer, E., & Eiben, A. E. (2012, April). Maintaining population diversity in evolutionary art. In *International Conference on Evolutionary and Biologically Inspired Music and Art* (pp. 60-71). Springer, Berlin, Heidelberg.  
[https://www.researchgate.net/profile/Eelco\\_Den\\_Heijer/publication/253650327\\_Maintaining\\_Population\\_Diversity\\_in\\_Evolutionary\\_Art/links/02e7e51fa2efb55b74000000/Maintaining-Population-Diversity-in-Evolutionary-Art.pdf](https://www.researchgate.net/profile/Eelco_Den_Heijer/publication/253650327_Maintaining_Population_Diversity_in_Evolutionary_Art/links/02e7e51fa2efb55b74000000/Maintaining-Population-Diversity-in-Evolutionary-Art.pdf)  
file:///home/konrad/Downloads/denheijer.pdf
- Machado, P., Correia, J., & Assunção, F. (2015). Graph-based evolutionary art. In *Handbook of Genetic Programming Applications* (pp. 3-36). Springer, Cham.  
<https://cdv.dei.uc.pt/wp-content/uploads/2017/11/MCA15.pdf>
- den Heijer, E., & Eiben, A. E. (2013, June). Maintaining population diversity in evolutionary art using structured populations. In *Evolutionary Computation (CEC), 2013 IEEE Congress on* (pp. 529-536). IEEE.  
<http://eelcodenheijer.nl/publications/Eelco-den-Heijer-and-Gusztai-Eiben-Maintaining-P.pdf>

- Bergen, S., & Ross, B. J. (2011). Evolutionary art using summed multi-objective ranks. In *Genetic Programming Theory and Practice VIII* (pp. 227-244). Springer, New York, NY.  
[https://link.springer.com/chapter/10.1007/978-1-4419-7747-2\\_14](https://link.springer.com/chapter/10.1007/978-1-4419-7747-2_14)

## 2 Research Notes

There exist methods for manipulating graph topologies such that the resulting evolutionary system increases the likelihood with which high fitness individuals fixate [1, 7]. This process involves numerous system factors: edge weighting, birth-death initialisation,

The main paper on which I am aiming to base my research on is that by Pavlogiannis, Tkadlec, Chatterjee & Nowak [1], which among other things, shows evidence of increasing fixation probabilities of advantageous mutants by structuring graph topologies according to a simple heuristic. This involves logically separating a directed graph topology into two parts: a hub, and branches. By doing so, and increasing weights directed towards the hub of a graph, the topology is able to maximise migration activity toward a centralised hub, and thus increase the likelihood of fixation for advantageous mutants.

## 3 Papers/Books

### 3.1 Creating arbitrarily strong amplifiers of natural selection on graphs [1]

This paper explores one of the fundamental ideas upon which a large portion of the proposed research is based. Graph topology has been shown to have a large impact on the rate of fixation for advantageous mutants [1, 7, 5]. Numerous graph structures have been found that increase the likelihood of fixation above levels expected for a well-mixed population [2, 7]; these are known as amplifiers of selection. While other topologies are known to decrease this likelihood, suppressors of selection. Properties such as distribution of edge weights, edge directionality [7], and self-loops are also shown to greatly impact fixation probabilities.

As shown by Pavlogiannis, Tkadlec, Chatterjee, & Nowak [1], not only can fixation probabilities be amplified by tuning the properties of a graph topology, but can be constructed arbitrarily. This construction process involves adjusting edge weights to create two sections: a central hub, and a series of branches. The hub is constructed such that the nodes within it are tightly coupled, thus increasing the likelihood an advantageous strategy will fixate. Then propagating through the branches, fixating on the entire graph. This amplification is however dependant on the graph having both directed edges, and self loops. Undirected edges have been shown to inherently suppress mutant fixation [7]. While self loops do not themselves amplify selection in graph topologies, they are a property required to construct an arbitrary amplifier of selection.

## 4 Research Ideas

With a method for constructing graphs that are arbitrary amplifiers of selection, my primary aim is to leverage this ability to create an evolutionary algorithm that supports generative agents with high fitness.

Use methods discussed in *Evolutionary mixed games in structured populations: Cooperation and the benefits of heterogeneity*. By randomly selecting the game in which agents partake (snow drift, prisoner’s dilemma), there is a proportional increase in population heterogeneity which increases cooperation. In terms of a generative evolutionary algorithm, by using multiple fitness functions, randomly chosen, tested against all, or a subset, to determine an individual’s overall fitness.

### 4.1 Generative Evolutionary Algorithms

- Using traditional evolutionary algorithms to generate image generation neural network weight (been done before).
- Vary fitness functions based on graph location: certain node clusters will have a given fitness function that differs from another. An issue arising from this is that we have smaller populations evolving within themselves. If an outside enters a cluster, its fitness in the new population will be, with high probability, extremely low. In the proceeding selection iteration, it will most likely be killed by an insider.

## **5 Log**

### **5.1 21-28 Jan 2019**

I met with Jon McCormack yesterday to discuss potential project ideas and where to begin with my research. Before the meeting I was able to

## References

- [1] Pavlogiannis, A., Tkadlec, J., Chatterjee, K., & Nowak, M. A. (2018). Construction of arbitrarily strong amplifiers of natural selection using evolutionary graph theory. *Communications Biology*, 1(1), 71.
- [2] Lieberman, E., Hauert, C., & Nowak, M. A. (2005). Evolutionary dynamics on graphs. *Nature*, 433(7023), 312.
- [3] Martin A. Novak, Karl Sigmund, (2005) *Evolution of indirect reciprocity*. Nature.
- [4] Amaral, M. A., Wardil, L., Perc, M., & da Silva, J. K. (2016). Evolutionary mixed games in structured populations: Cooperation and the benefits of heterogeneity. *Physical Review E*, 93(4), 042304.
- [5] Ohtsuki, H., Hauert, C., Lieberman, E., & Nowak, M. A. (2006). A simple rule for the evolution of cooperation on graphs and social networks. *Nature*, 441(7092), 502.
- [6] Fernando P. Santos, Francisco C. Santos, Jorge M. Pacheco, (2016) Social Norms of Cooperation in Small-Scale Societies. *PLOS Computational Biology*.
- [7] Hindersin, L., & Traulsen, A. (2015). Most undirected random graphs are amplifiers of selection for birth-death dynamics, but suppressors of selection for death-birth dynamics. *PLoS computational biology*, 11(11), e1004437.
- [8] Hisashi Ohtsuki, Yoh Iwasa, (2005) The leading eight: Social norms that can maintain cooperation by indirect reciprocity. *Journal of Theoretical Biology*.