

TITLE

Konrad Cybulski

Honours Research Notes



Faculty of Information Technology
Monash University
Australia
February 11, 2019

Contents

1	Reading List	2
2	Literature Summary	4
2.0.1	Interactive evolution of equations for procedural models [7]	4
2.0.2	Evolutionary image synthesis using a model of aesthetics [6]	4
2.0.3	Creating arbitrarily strong amplifiers of natural selection on graphs [1]	5
2.0.4	NEvAr—the assessment of an evolutionary art tool [8] . .	5
3	Research Ideas	7
3.1	Generative Evolutionary Algorithms	7

1 Reading List

- Cagnoni, S., Lutton, E., & Orlague, G. (Eds.). (2007). Genetic and evolutionary computation for image processing and analysis. New York: Hindawi Publishing Corporation.
<http://downloads.hindawi.com/books/9789774540011/art01.pdf>
- Secretan, J., Beato, N., D'Ambrosio, D. B., Rodriguez, A., Campbell, A., Folsom-Kovarik, J. T., & Stanley, K. O. (2011). Picbreeder: A case study in collaborative evolutionary exploration of design space. *Evolutionary Computation*, 19(3), 373-403.
https://www.mitpressjournals.org/doi/pdfplus/10.1162/EVC0_a_00030
- Takagi, H. (2001). Interactive evolutionary computation: Fusion of the capabilities of EC optimization and human evaluation. *Proceedings of the IEEE*, 89(9), 1275-1296.
<http://sclab.yonsei.ac.kr/courses/09EC/papers/IECsurvey.pdf>
- Paulinas, M., & Ušinskas, A. (2007). A survey of genetic algorithms applications for image enhancement and segmentation. *Information Technology and control*, 36(3).
<http://www.itc.ktu.lt/index.php/ITC/article/download/11886/6561>
- Romero, J. J. (2008). The art of artificial evolution: A handbook on evolutionary art and music. Springer Science & Business Media.
<http://citeseerx.ist.psu.edu/viewdoc/download?doi=10.1.1.470.2312&rep=rep1&type=pdf>
- McCormack, J. (2005, March). Open problems in evolutionary music and art. In *Workshops on Applications of Evolutionary Computation* (pp. 428-436). Springer, Berlin, Heidelberg.
<http://users.monash.edu/~jonmc/research/Papers/OpenProblemsSV.pdf>
- den Heijer, E., & Eiben, A. E. (2010, April). Comparing aesthetic measures for evolutionary art. In *European Conference on the Applications of Evolutionary Computation* (pp. 311-320). Springer, Berlin, Heidelberg.
<http://eelcodenheijer.nl/publications/E-den-Heijer-and-AE-Eiben-Comparing-aesthetic-M.pdf>
- den Heijer, E., & Eiben, A. E. (2010, July). Using aesthetic measures to evolve art. In *Evolutionary Computation (CEC), 2010 IEEE Congress on* (pp. 1-8). IEEE.
<http://www.eelcodenheijer.nl/publications/E-den-Heijer-and-AE-Eiben-Using-Aesthetic-M.pdf>
- den Heijer, E., & Eiben, A. E. (2011, April). Evolving art using multiple aesthetic measures. In *European Conference on the Applications of Evolutionary Computation* (pp. 234-243). Springer, Berlin, Heidelberg.
<http://dare.ubvu.vu.nl/bitstream/handle/1871/34536/272336.pdf?sequence=1>

- Ekárt, A., Sharma, D., & Chalakov, S. (2011, April). Modelling human preference in evolutionary art. In *European Conference on the Applications of Evolutionary Computation* (pp. 303-312). Springer, Berlin, Heidelberg.
<https://research.aston.ac.uk/portal/files/502798/ekart.pdf>
- den Heijer, E., & Eiben, A. E. (2014). Investigating aesthetic measures for unsupervised evolutionary art. *Swarm and Evolutionary Computation*, 16, 52-68.
https://s3.amazonaws.com/academia.edu.documents/37208620/sec2013.pdf?AWSAccessKeyId=AKIAIWOWYYGZ2Y53UL3A&Expires=1548899878&Signature=T98kzLvMluIDiePBw88y8MDxtiM%3D&response-content-disposition=inline%3B%20filename%3DInvestigating_aesthetic_measures_for_uns.pdf
- Machado, P., Martins, T., Amaro, H., & Abreu, P. H. (2014, April). An interface for fitness function design. In *International Conference on Evolutionary and Biologically Inspired Music and Art* (pp. 13-25). Springer, Berlin, Heidelberg.
<https://cdv.dei.uc.pt/wp-content/uploads/2014/06/mmaa14.pdf>
- den Heijer, E. (2015). Evolving symmetric and balanced art. In *Computational Intelligence* (pp. 33-47). Springer, Cham.
- den Heijer, E., & Eiben, A. E. (2012, April). Maintaining population diversity in evolutionary art. In *International Conference on Evolutionary and Biologically Inspired Music and Art* (pp. 60-71). Springer, Berlin, Heidelberg.
https://www.researchgate.net/profile/Eelco_Den_Heijer/publication/253650327_Maintaining_Population_Diversity_in_Evolutionary_Art/links/02e7e51fa2efb55b74000000/Maintaining-Population-Diversity-in-Evolutionary-Art.pdf file:///home/konrad/Downloads/denheijer.pdf
- Machado, P., Correia, J., & Assunção, F. (2015). Graph-based evolutionary art. In *Handbook of Genetic Programming Applications* (pp. 3-36). Springer, Cham.
<https://cdv.dei.uc.pt/wp-content/uploads/2017/11/MCA15.pdf>
- den Heijer, E., & Eiben, A. E. (2013, June). Maintaining population diversity in evolutionary art using structured populations. In *Evolutionary Computation (CEC), 2013 IEEE Congress on* (pp. 529-536). IEEE.
<http://eelcodenheijer.nl/publications/Eelco-den-Heijer-and-Gusztai-Eiben-Maintaining-Population-Diversity-in-Evolutionary-Art.pdf>
- Bergen, S., & Ross, B. J. (2011). Evolutionary art using summed multi-objective ranks. In *Genetic Programming Theory and Practice VIII* (pp. 227-244). Springer, New York, NY.
https://link.springer.com/chapter/10.1007/978-1-4419-7747-2_14

2 Literature Summary

2.0.1 Interactive evolution of equations for procedural models [7]

Sims introduces a method for generating images by using Lisp expressions as individual genotypes for use in an evolutionary process. This method is introduced as extremely extensible in comparison to commonly used genotype expressions: fixed length strings, parameter collections, etc. The method for mutation involves the parsing of Lisp expressions as a tree structure which then adjusted according to the following rules:

- "Any node can mutate into a new random expression."
- "If the node is a scalar value, it can be adjusted by the addition of some random amount."
- "If the node is a vector it can be adjusted by adding random amounts to each element."
- "If the node is a function, it can mutate into a different function."
- "An expression can become the argument to a new random function."
- "An argument to a function can jump out and become the new value for that node."
- "A node can become a copy of another node from the parent expression."

Sims discusses the method by which two individuals in a population mate. This involves the random swap a single node from each parent. If this process results in an invalid genotype (Lisp expression) then the crossover is performed "until a legal expression results". The method of "Genetic cross dissolves" is introduced as a smooth transitional operator of reproduction.

The genotype representation and its corresponding mating/mutation procedure is shown to produce some truly remarkable images through a user-supervised evolutionary process. This involves the user selecting "one or more of [the generated images] for mutation and/or mating to produce the next generation, and the process repeats".

2.0.2 Evolutionary image synthesis using a model of aesthetics [6]

The overarching goal of this research is to investigate the use of multiple aesthetic fitness functions for unsupervised image generation using genetic programming. Those used involved the distribution of colours in the generated images. An existing image is used to determine the frequency distribution of colours as a target which is used as the first of two objective fitness functions. The second uses knowledge that the colour gradients in fine art tends towards a normal distribution.

The mathematical model of aesthetics, as discussed here, bases its colour gradient fitness function on the hypothesis that said normal distribution of colour gradients "has been an implicit aesthetic ideal of many painters throughout history".

The method used for generating images as part of the algorithm is a slight variation of that developed by Sims [7].

This research concludes that the use of "Ralph's bell curve response model" has an aesthetically beneficial impact on the generated images. When omitting the fitness function measuring deviation from the normal distribution of colour gradients, the images produced are resultantly "chaotic or bland, artificial, mathematical, and rarely appealing". When using solely the colour gradient fitness function, without a target frequency distribution, the highest fitness individuals tended toward a "narrow bandwidth of RGB space". Resulting in images that were "not very interesting to the human eye". Target images with a colour frequency distribution that inherently have a high deviation from the normal colour gradient distribution that resulted in "creative tension" were noted as producing "the most surprising results".

2.0.3 Creating arbitrarily strong amplifiers of natural selection on graphs [1]

This paper explores one of the fundamental ideas upon which a large portion of the proposed research is based. Graph topology has been shown to have a large impact on the rate of fixation for advantageous mutants [1, 5, 4]. Numerous graph structures have been found that increase the likelihood of fixation above levels expected for a well-mixed population [2, 5]; these are known as amplifiers of selection. While other topologies are known to decrease this likelihood, suppressors of selection. Properties such as distribution of edge weights, edge directionality [5], and self-loops are also shown to greatly impact fixation probabilities.

As shown by Pavlogiannis, Tkadlec, Chatterjee, & Nowak [1], not only can fixation probabilities be amplified by tuning the properties of a graph topology, but can be constructed arbitrarily. This construction process involves adjusting edge weights to create two sections: a central hub, and a series of branches. The hub is constructed such that the nodes within it are tightly coupled, thus increasing the likelihood an advantageous strategy will fixate. Then propagating through the branches, fixating on the entire graph. This amplification is however dependant on the graph having both directed edges, and self loops. Undirected edges have been shown to inherently suppress mutant fixation [5]. While self loops do not themselves amplify selection in graph topologies, they are a property required to construct an arbitrary amplifier of selection.

2.0.4 NEvAr—the assessment of an evolutionary art tool [8]

This research was pivotal in the investigation of interactive evolutionary (IE) methods of generating images. The NEvAr program relies on the user being a key determinant of an individual's fitness. The program's basis is such that there exist multiple parallel populations. Each population is evolved through the user's direct interaction which involves the selection of individuals for crossover. Migration from one population to another can be instigated by the user, allowing for new populations to be created from a selection of high fitness individuals

rather than at random.

NEvAr puts a large focus on the end-user experience involved in the process of generating art, mentioning explicitly that the generation of 'interesting' images "is irrelevant from the artistic point of view". However it is noted that with a lack of experience, as with any tool, the results were "disappointing". As a result, the focus goes to creating a process through which the user may increase the number of "promising" images. This process follows a four stage structure: "Discovery, Exploration, Selection and Refinement".

In NEvAr, the artist is no longer responsible for the creation of the idea, she/he is responsible for the recognition of promising concepts.

Also discussed is the idea of Seeding a population with an image selected by the user. This involves the selection images with a high similarity to that chosen by the user in order to initialise a population with high relative fitness given a target outcome. The similarity metric used involves compression complexity, forgoing the standard RMSE similarity metric due to a number of shortcomings. Both JPEG and Fractal image compression complexity are used in order to mitigate the inadequacy of JPEG for images with stark colour transitions; and benefit from Fractal compression with highly self-similar images.

3 Research Ideas

With a method for constructing graphs that are arbitrary amplifiers of selection, my primary aim is to leverage this ability to create an evolutionary algorithm that supports generative agents with high fitness.

Use methods discussed in *Evolutionary mixed games in structured populations: Cooperation and the benefits of heterogeneity*. By randomly selecting the game in which agents partake (snow drift, prisoner’s dilemma), there is a proportional increase in population heterogeneity which increases cooperation. In terms of a generative evolutionary algorithm, by using multiple fitness functions, randomly chosen, tested against all, or a subset, to determine an individual’s overall fitness.

3.1 Generative Evolutionary Algorithms

- Using traditional evolutionary algorithms to generate image generation neural network weight (been done before).
- Vary fitness functions based on graph location: certain node clusters will have a given fitness function that differs from another. An issue arising from this is that we have smaller populations evolving within themselves. If an outside enters a cluster, its fitness in the new population will be, with high probability, extremely low. In the proceeding selection iteration, it will most likely be killed by an insider.
- Using a genotype definition that follows the methods introduced by [7], it may be possible to create high aesthetic fitness individuals by using RMSE/compression complexity difference from a target image. This may result in individuals with a Lisp expression genotype that generate images created in non-deterministic ways. With a collection of individuals evolved in this manner, similarly to [8], a high fitness population can be initialised for further interactive evolution.

References

- [1] Pavlogiannis, A., Tkadlec, J., Chatterjee, K., & Nowak, M. A. (2018). Construction of arbitrarily strong amplifiers of natural selection using evolutionary graph theory. *Communications Biology*, 1(1), 71.
- [2] Lieberman, E., Hauert, C., & Nowak, M. A. (2005). Evolutionary dynamics on graphs. *Nature*, 433(7023), 312.
- [3] Amaral, M. A., Wardil, L., Perc, M., & da Silva, J. K. (2016). Evolutionary mixed games in structured populations: Cooperation and the benefits of heterogeneity. *Physical Review E*, 93(4), 042304.
- [4] Ohtsuki, H., Hauert, C., Lieberman, E., & Nowak, M. A. (2006). A simple rule for the evolution of cooperation on graphs and social networks. *Nature*, 441(7092), 502.
- [5] Hindersin, L., & Traulsen, A. (2015). Most undirected random graphs are amplifiers of selection for birth-death dynamics, but suppressors of selection for death-birth dynamics. *PLoS computational biology*, 11(11), e1004437.
- [6] Ross, B. J., Ralph, W., & Zong, H. (2006, July). Evolutionary image synthesis using a model of aesthetics. In *Evolutionary Computation*, 2006. CEC 2006. IEEE Congress on (pp. 1087-1094). IEEE.
- [7] Sims, K. (1993). Interactive evolution of equations for procedural models. *The Visual Computer*, 9(8), 466-476.
- [8] Machado, P., & Cardoso, A. (2000, April). NEvAr—the assessment of an evolutionary art tool. In *Proceedings of the AISB00 Symposium on Creative & Cultural Aspects and Applications of AI & Cognitive Science*, Birmingham, UK (Vol. 456).