New Upper Bounds for Dense Max 2-SAT by Accumulating Pruning Constraints

22 October 2026
Theoretical draft

Abstract

We study exact deterministic algorithms for Max 2-SAT on n variables with running time $O^*(2^{(1-\gamma)n})$, for a fixed $\gamma > 0$, using polynomial space. Our main tool is a comparison between the two values of a branching variable. This comparison gives a hard constraint that restricts the completions worth considering in one of the branches. We show how accumulating these constraints yields an exponential saving for several classes whose clause density may grow with n. The results cover formulas with substantial relative literal bias and controlled occurrence counts, random signed clauses on arbitrary supports, and Max-Cut on regular graphs satisfying a spectral condition and on stochastic block model graphs with a fixed number of communities and sufficient random variation. The methods progress from direct accumulation to normalization and then to assignment counts that account for systematic interactions. For hidden communities, the algorithm also uses spectral preprocessing. The random-input algorithms are exact on every input; randomness qualifies their running-time guarantees.

1 Introduction

Max 2-SAT asks for a Boolean assignment satisfying the largest number of clauses of a formula with at most two literals per clause. Exhaustive search takes $O^*(2^n)$ time and polynomial space. We study conditions under which comparisons between assignments give a fixed exponential saving even when the clause density grows with the number of variables.

The space requirement is central. Williams gave an exact algorithm with running time $O^*(2^{\omega n/3})$ and exponential space, where ω is the matrix multiplication exponent [1]. Kulikov and Kutzkov obtained polynomial-space algorithms with a fixed exponential saving for every fixed clause density, using clause learning to restrict the search [2]. Degree-dependent and separator-based bounds give further improvements [3]. Our objective is a saving that stays bounded away from zero on specified families of growing density.

The basic comparison is simple. Fix all variables except v. If setting $v = 1$ is at least as good as setting $v = 0$, there is no need to retain both assignments for this completion. A pruning constraint describes exactly the completions for which the other value is strictly better. The difficulty is to make many such constraints useful together. Their neighborhoods may overlap heavily, and an assignment to a few shared variables may satisfy many of them at once.

Our analyses separate two questions. How much do the constraints require from a completion? How much can the remaining variables collectively contribute toward those requirements? The first question concerns the individual comparisons. The second concerns their overlaps and correlations. When enough requirements accumulate, the algorithm can either reject a partial assignment or enumerate only the completions of the summed constraint.

1.1 Results and progression of the method

We organize the results by the additional method needed to handle the input, rather than separating random and deterministic families. All algorithms use polynomial space.

1. **Relative literal bias.** A linear fraction of variables have an effective literal gap proportional to their degree, and a squared-occurrence bound controls the concentration of degrees. Theorem 3.2 gives a fixed exponential saving. Corollary 3.5 states the dense specialization directly for simple formulas with a linear number of linear gaps.

2. **Symmetric random signs.** Fix any set of variable pairs. On each pair, independently choose one uniformly signed clause, or independently include each of its four clauses with probability 1/4. Theorem 4.2 gives an expected and high-probability fixed exponential saving, with no density or regularity assumption on the support. Positive weights normalize the constraints before addition; fresh signs control the effects of shared variables. Additional units may be fixed independently of the draw.

3. **A common systematic interaction.** For regular-graph Max-Cut, a guessed number of ones accounts for the common part of the pair interactions. The remaining interactions satisfy a deterministic correlation bound when the nontrivial eigenvalues are small. Corollary 5.2 gives a fixed saving under a density restriction, with Paley and qualifying Ramanujan graphs as examples. The algorithm itself uses counts and comparisons.

4. **Community-dependent interactions.** In the stochastic block model, the systematic part depends on the communities of the endpoints. Theorem 6.2 gives a fixed saving when the number of communities is fixed, their edge variances are comparable, and the smallest variance times n is at least a sufficiently large multiple of $\log n$. The partition and probabilities are not supplied. Our algorithm computes approximate spectral directions and uses polynomially many projection guesses before accumulating comparisons.

The Max-Cut results also permit arbitrary additional unit clauses in their Max 2-SAT encodings. For random graphs these units may be chosen after the graph is drawn. In all random-input results, the algorithms are deterministic and return an optimum on every input. Probability statements concern the input and the resulting running time.

Section 2 establishes the common reductions and comparisons. Sections 3–6 develop the four methods in the order above. The appendices supply general forms of the estimates used in these sections, including the computational details required for hidden communities.

1.2 Relation to earlier methods

The comparison interpretation is closely related to the clause-learning approach of Kulikov and Kutzkov [2]. Our focus is on conditions under which accumulated comparisons give a density-independent saving with polynomial space. Local optimality also plays a role in exact Max 2-SAT algorithms: Hastings relates local maxima to improved bounds and obtains degree-dependent savings under additional assumptions [4]. In the count-adjusted algorithms, every optimum survives in a run with the correct aggregate information because a one-variable change cannot improve it.

The random-input and spectral estimates enter at specific points in the analysis. Scalar moment and concentration bounds suffice for the arbitrary-support random-sign theorem. Matrix estimates are used to control correlations after count adjustment. They are proof tools for regular-graph Max-Cut, whereas spectral preprocessing is an actual algorithmic step for the hidden-community result.

2 Notation, simplification, and pruning constraints

Let F be an unweighted Max 2-SAT formula on a set V of n variables. In this section and in the literal-gap theorem, the input is *simple*: no clause occurs twice, and no variable occurs twice in a clause. We write $\mathbf{v}$ for a variable and $v, \neg v$ for its two literals. The numbers $d_1^F(v)$ and $d_2^F(v)$ count the unit and binary clauses containing v, respectively. We omit the superscript when the formula is clear. Unit clauses created by simplification retain their multiplicities. The number of binary clauses is m_2, and their density is $\rho = m_2/n$. The notation O^* suppresses factors polynomial in the input size. Later sections explicitly permit additional copies of unit clauses, and Appendix B permits bounded multisets of binary clauses on a pair. The score identities below apply to individual copies as well.

A *partial assignment* α assigns values to a subset of V. A variable outside that subset is *unassigned*; a complete assignment extending α is a *completion* of α. For a complete assignment x, let $F(x)$ be its number of satisfied clauses, and let $\mathrm{OPT}(F) = \max_x F(x)$. Restricting F by α removes satisfied clauses and false literals. We record the removed satisfied clauses in a separate score s. Thus, for every completion, its original score equals s plus its score in the residual formula. An empty soft clause contributes zero and is discarded. The residual formula retains the set of unassigned input variables, including variables whose clause occurrences have all disappeared.

The input clauses are soft: an optimal assignment may leave some of them unsatisfied. A pruning constraint is an additional restriction used to reduce the search space. We write C for one such constraint and $\mathcal{C}$ for a collection of them. Our constraints have the form $\sum_i \ell_i \le b$, where every ℓ_i is a Boolean literal and repeated occurrences are counted separately.

2.1 Simplification rules and preprocessing

The first two reductions preserve the score of every assignment up to a recorded constant. This stronger property lets us reuse the same comparisons after preprocessing. Domination instead identifies a value that is at least as good for every completion.

Lemma 2.1 (Unit clause cancellation)**.** *Removing one copy of* (v) *and one copy of* $(\neg v)$ *decreases the score of every complete assignment by exactly one.*

Proof. Exactly one of the two unit clauses is satisfied by every assignment. □

Lemma 2.2 (Simplifying two clauses on the same variable pair)**.** *Let* a, b *be literals on distinct variables. Replacing* $(a \vee b), (a \vee \neg b)$ *by the unit clause* (a) *decreases the score of every complete assignment by exactly one.*

Proof. If $a = 1$, the two original clauses contribute two and the new unit contributes one. If $a = 0$, exactly one original clause is satisfied and the new unit contributes zero. In both cases the difference is one. □

Lemma 2.3 (Unit clause domination)**.** *Suppose* $d_1(\neg v) = 0$ *and* $d_1(v) \ge d_2(\neg v)$*. For every fixed assignment of the other variables, setting* $v = 1$ *satisfies at least as many clauses as setting* $v = 0$*.*

Proof. Changing v from zero to one gains all $d_1(v)$ positive units. Clauses containing v cannot lose satisfaction. The only possible losses are among the $d_2(\neg v)$ binary clauses containing $\neg v$, since there are no units $(\neg v)$. The net gain is therefore at least $d_1(v) - d_2(\neg v) \ge 0$. □

In particular, a pure literal, whose opposite has no occurrences, can be set to one. When pruning constraints are present, such an assignment must also respect them. The procedure

SIMPLIFY, defined in the next subsection, uses domination only when the literal being set to one occurs in no current constraint.

The initial procedure PREPROCESS makes no assignments. Store the clauses as an ordered list, retaining multiplicities. At each step, scan pairs of clause positions in lexicographic order and apply the first available rule: cancel opposite units or replace two binary clauses sharing one literal and opposite in the other by their shared unit. In the latter case, place the new unit at the later clause's position; otherwise retain the order of surviving clauses. Each reduction removes one constant unit of score, recorded in s. Repeat until neither rule applies and return the reduced formula and s. The order of reductions does not affect their score identities; the specified order makes the procedure deterministic.

Algorithm 1 PREPROCESS(F)

$s \leftarrow 0$; retain the clauses of F in their input order.
while an eligible pair of clauses exists **do**
  Select the first eligible pair in the order described above.
  if the pair is $(v), (\neg v)$ **then**
    Remove both clauses using Lemma 2.1.
  else
    Replace $(a \vee b), (a \vee \neg b)$ by (a) using Lemma 2.2.
  end if
  $s \leftarrow s + 1$.
end while
return (F, s).

The score identities justify PREPROCESS for every assignment, not only for an optimum. For distinct input binary clauses, after it terminates a variable pair occurs in at most two binary clauses. If there are two, their literals are complementary in both positions: otherwise the two clauses would share a literal and the loop could apply again. We call this form *canonical*. Assigning variables creates only units, so the binary clauses do not need to be preprocessed again at later nodes.

2.2 Constructing and enforcing a pruning constraint

Lemma 2.4 (Pruning constraints from comparison)**.** *In a residual formula F, let v be either literal of an unassigned variable. List the partner literals in clauses containing v as $x_1, \ldots, x_{d_2(v)}$, and those in clauses containing $\neg v$ as $y_1, \ldots, y_{d_2(\neg v)}$. Define*

$$C: \quad \sum_{i=1}^{d_2(v)} \neg x_i + \sum_{j=1}^{d_2(\neg v)} y_j \leq d_2(\neg v) - d_1(v) + d_1(\neg v) - 1. \tag{1}$$

For every complete assignment of the other variables, C holds if and only if setting $v = 0$ has strictly larger score than setting $v = 1$.

Proof. Keep all other variables fixed. A unit (v) contributes one to the gain of $v = 1$ over $v = 0$, and a unit $(\neg v)$ contributes minus one. A clause $(v \vee x_i)$ contributes $1 - x_i = \neg x_i$ to this gain. A clause $(\neg v \vee y_j)$ contributes $-(1 - y_j) = y_j - 1$. All clauses not containing the variable of v have the same score in both assignments. Their contributions cancel. The exact gain is therefore

$$d_1(v) - d_1(\neg v) - d_2(\neg v) + \sum_i \neg x_i + \sum_j y_j.$$

Setting $v = 0$ is strictly better precisely when this integer is at most -1, which is the stated constraint. □

To restrict a constraint after an assignment, remove every false literal occurrence. Remove every true literal occurrence and decrease its bound by one. Also, a complementary pair $w, \neg w$ can be removed while decreasing the bound by one, since $w + \neg w = 1$. A negative bound proves infeasibility. After cancellation, if a literal occurs more often than the bound, it must be false in every satisfying completion.

Lemma 2.5 (Infeasibility by summation)**.** *Let $\mathcal{C}$ consist of constraints $C : \sum_{i=1}^{r_C} \ell_i \leq b_C$, with literal occurrences counted separately. Add the constraints, and repeatedly remove complementary literal pairs from the sum, decreasing its bound by one per pair. If the resulting bound is negative, no assignment satisfies all constraints in $\mathcal{C}$.*

Proof. An assignment satisfying every constraint also satisfies their sum. Cancelling a pair preserves the inequality because its contribution is exactly one for every assignment. The remaining left-hand side is nonnegative, so it cannot satisfy a negative bound. □

This is a sufficient infeasibility test. Passing it does not imply that the collection has a common satisfying assignment. The summed constraint is temporary; it is not added to $\mathcal{C}$.

The procedure SIMPLIFY receives the residual formula F and current constraints $\mathcal{C}$. It records any new assignments in α and their score contribution in s, both local to this call. The instruction *assign* $v = p$ updates the formula, its unassigned variable set, and s, substitutes the value in every constraint, and records the corresponding variable value in α.

Each iteration first cancels opposite units and complementary literal pairs in the constraints, then removes constraints that are already satisfied. It checks individual constraints and their sum for infeasibility; an empty collection has sum $0 \leq 0$. If neither check rejects, it first looks for a value forced by a constraint. If none is found, it looks for a dominating literal whose assignment preserves the constraints, using the condition stated above. After either type of assignment, the procedure repeats these checks on the updated state. When neither assignment rule applies, it returns that state. All choices between eligible assignments follow fixed orders.

Algorithm 2 SIMPLIFY$(F, \mathcal{C})$

$s \leftarrow 0$; $\alpha \leftarrow \emptyset$
while true **do**
  Cancel opposite units by Lemma 2.1, adding their constant to s.
  Cancel complementary literal pairs within each $C \in \mathcal{C}$, decreasing its bound accordingly.
  Let r_C be its remaining number of occurrences; remove C if $b_C \geq r_C$.
  if some $b_C < 0$, or Lemma 2.5 proves infeasibility **then**
    return INFEASIBLE
  end if
  if some literal v occurs more than b_C times in some $C \in \mathcal{C}$ **then**
    Assign $v = 0$, updating $F, \mathcal{C}, s, \alpha$.
  else if an unassigned literal v satisfies $d_1(\neg v) = 0$, $d_1(v) \geq d_2(\neg v)$, and occurs in no $C \in \mathcal{C}$ **then**
    Assign $v = 1$, updating $F, \mathcal{C}, s, \alpha$.
  else
    return $(F, \mathcal{C}, s, \alpha)$
  end if
end while

The last assignment rule preserves feasibility of the current constraints: setting $v = 1$ cannot increase any left-hand side, because only $\neg v$ can occur there. Lemma 2.3 shows that

the soft score does not decrease. Thus this rule preserves the best score subject to the current constraints.

2.3 Preferences and enumeration of a summed constraint

We will use clause counts to choose a preferred value. For a formula H and a variable $\mathbf{v}$, define its *effective gap* by

$$g_{\mathbf{v}}(H) = d_2^H(v) - d_2^H(\neg v) + 2\big(d_1^H(v) - d_1^H(\neg v)\big). \tag{2}$$

Under a uniform assignment of the other variables, the expected score with $v = 1$ minus the score with $v = 0$ is $g_{\mathbf{v}}(H)/2$. Indeed, a unit contributes its full signed preference, whereas a binary clause contributes only when its partner literal is false, an event of probability one half. We call

$$\ell_{\mathbf{v}}(H) = \begin{cases} v, & g_{\mathbf{v}}(H) \geq 0, \\ \neg v, & g_{\mathbf{v}}(H) < 0 \end{cases} \tag{3}$$

the preferred literal; its preferred truth value is one. Equivalently, the preferred value of the underlying variable is one when the gap is nonnegative and zero otherwise. Each algorithm specifies the formula H used here. The literal-gap algorithm fixes preferences from the formula after preprocessing; the random-sign algorithm recomputes them in its current residual formula.

Several algorithms will branch on a fixed set P and then complete the remaining variables. A *prefix assignment* α specifies all variables of P; a *suffix assignment* β specifies $V \setminus P$. These names refer to the order that lists P first, not necessarily to consecutive original labels. Within each set we use the original input order. The complete assignment is $\alpha \cup \beta$.

For a collection $\mathcal{C}$ of occurrence-count constraints, its ordinary sum is

$$C_\Sigma : \qquad \sum_{C \in \mathcal{C}} \sum_{i=1}^{r_C} \ell_{C,i} \leq \sum_{C \in \mathcal{C}} b_C. \tag{4}$$

Every assignment satisfying the individual constraints satisfies this sum. The sum can also admit other assignments; we may enumerate and score them without affecting correctness. An empty collection gives $0 \leq 0$.

After substituting a prefix, collect the occurrences of each unassigned variable. If its contribution is $aw + b\neg w$, replace it by $\min(a, b) + |a - b|z$, where $z = w$ when $a \geq b$ and $z = \neg w$ otherwise. Move the constant to the right-hand side. Thus the sum has the form

$$\sum_{i=1}^{k} w_i z_i \leq B, \qquad w_i \geq 0, \quad z_i \in \{0, 1\}, \tag{5}$$

with one oriented literal z_i for each remaining variable. Include variables of coefficient zero, so every enumerated assignment is complete. For occurrence counts, this is precisely complementary cancellation from Lemma 2.5. The same operation works with nonnegative rational coefficients, which the later sections will use.

For this single inequality, the minimum left-hand side is zero: set all remaining z_i to zero. Hence a negative bound is an exact infeasibility test for the sum. This does not decide joint feasibility of the individual constraints. The distinction matters for the following enumeration bound: every retained partial assignment has a completion satisfying the sum.

Lemma 2.6 (Enumerating the summed constraint)**.** *Let $\sum_{i=1}^{k} w_i z_i \leq B$ have nonnegative rational weights and N satisfying Boolean assignments. Depth-first enumeration in a fixed order, rejecting a partial assignment as soon as its assigned contribution exceeds B, lists each satisfying assignment once and visits at most $1 + 2kN$ recursion nodes, including rejected nodes.*

Its recursion depth is at most $k+1$, and its time and space per active node are polynomial in the encoding length of the inequality and the assignment.

Consequently, suppose branching assigns a fixed set of T variables, and $N(\alpha)$ counts the suffix assignments satisfying the sum for prefix α. If constructing each summed inequality takes polynomial time and its encoding length is polynomial in the input size, the whole search uses polynomial space and time

$$O^*(2^T + W(F)), \qquad W(F) = \sum_{\alpha \in \{0,1\}^T} N(\alpha). \tag{6}$$

More precisely, the full prefix tree followed by suffix enumeration visits at most $2^{T+1} - 1 + 2kW(F)$ nodes when k variables remain after each prefix.

Proof. If $B < 0$, the root is rejected and is the only visited node. Otherwise, every retained partial assignment extends to a solution by setting all unassigned z_i to zero. At a fixed depth, distinct partial assignments have disjoint sets of completions. There are therefore at most N retained nodes at each depth. There are k depths at which children can be created. Apart from the root, every visited node is one of the at most two children of a retained node. This proves the bound $1 + 2kN$, including children that are immediately rejected. Each complete assignment follows one path, so no output is repeated.

Each recursive call assigns one variable. The depth is therefore at most $k+1$, and the algorithm stores the active path rather than all outputs. Subtraction and comparison of the rational coefficients have polynomial bit cost in the input encoding length.

The full prefix tree has $2^T - 1$ internal nodes; its leaves are the roots of the suffix enumerations. Summing their bounds gives

$$(2^T - 1) + \sum_{\alpha} (1 + 2kN(\alpha)) = 2^{T+1} - 1 + 2kW(F).$$

Constructing and processing the sums adds polynomial work per prefix and per suffix node. Process prefixes and outputs consecutively to obtain the stated space bound. □

3 The literal gap algorithm and its analysis

3.1 Intuition

Suppose a linear number of variables have a substantial difference between the frequencies of their two literals. For the initial intuition, ignore unit clauses. If one literal occurs much more often than its negation, setting it to one satisfies more clauses on average over assignments to the other variables. The opposite value can still be better for particular assignments. The pruning constraint of Lemma 2.4 describes exactly when that opposite choice is strictly better. A large gap makes this a restrictive requirement on the neighboring literals. Here a large gap means a constant fraction of the variable's degree; the degree need not be linear in n.

We fix the preferred values from the formula after preprocessing. Then we select about half the variables so that they carry at least half the total absolute gap. This selection is simple: split the variable labels into two halves and take the half with the larger total gap. Branching on all assignments to this set costs only about $2^{n/2}$ prefixes. For each prefix, add the usual pruning constraint whenever a variable takes its nonpreferred value. All comparisons use the same preprocessed formula, with the prefix substituted afterwards.

Consider a uniformly random complete assignment and its path through these prefix decisions. The algorithm itself is deterministic; the random assignment only helps us count its candidates. A variable takes its nonpreferred value with probability one half. On those paths, its constraint requires the remaining values to overcome its initial preference. For example,

a constraint $\sum_{i=1}^{r} \ell_i \le r/4$ allows only half the uniform mean $r/2$ of true literal occurrences. Each occurrence contributes zero or one; one half is its expectation.

The constraints may overlap heavily. To see how we account for this, consider one binary clause on variables $\mathbf{v}, \mathbf{w}$. It puts one occurrence of a literal of $\mathbf{w}$ in the comparison for $\mathbf{v}$, and one occurrence of a literal of $\mathbf{v}$ in the comparison for $\mathbf{w}$. Thus, across one comparison per variable, the total number of occurrences of $\mathbf{w}$ is exactly its original binary degree. This remains true when neighborhoods coincide. A shared variable can help many requirements only if it has enough occurrences to influence them. The theorem bounds the sum of the squared occurrence counts, preventing a few variables from accounting for all the requirements.

We count the complete assignments satisfying the sum of the selected constraints. The initial gaps make their combined requirement large, while the occurrence bound limits how much changing one bit can affect it. A concentration inequality then shows that only an exponentially small fraction of complete assignments satisfies the sum. Finally, Lemma 2.6 turns this counting bound into a time bound: after each prefix we enumerate only completions satisfying its summed constraint, with polynomial work per output. We do not need to track whether a variable's gap persists as earlier variables are assigned.

3.2 The algorithm

First record the input variables in their original label order and apply Preprocess, obtaining (F_0, s_0). The formula F_0 and its variable set remain fixed during the search. A complete assignment x has original score $s_0 + F_0(x)$, including variables whose occurrences have disappeared.

Compute $g_{\mathbf{v}} = g_{\mathbf{v}}(F_0)$ by (2). Set the preferred variable value $p_{\mathbf{v}}$ to one when $g_{\mathbf{v}} \ge 0$, and to zero otherwise. Equivalently, its preferred literal is $\ell_{\mathbf{v}}(F_0)$ from (3). These preferences stay fixed. Let A contain the first $\lfloor n/2 \rfloor$ variables in the recorded order, and let $A' = V \setminus A$. Choose

$$P = \begin{cases} A', & \displaystyle\sum_{\mathbf{v}\in A} |g_{\mathbf{v}}| \le \sum_{\mathbf{v}\in A'} |g_{\mathbf{v}}|, \\ A, & \text{otherwise.} \end{cases} \tag{7}$$

This deterministic choice gives

$$|P| \le \lceil n/2 \rceil, \qquad \sum_{\mathbf{v}\in P} |g_{\mathbf{v}}| \ge \frac{1}{2} \sum_{\mathbf{v}\in V} |g_{\mathbf{v}}|. \tag{8}$$

For each $\mathbf{v} \in P$, construct $C_{\mathbf{v}}$ by Lemma 2.4, using F_0 and its fixed preferred literal. This constraint says that choosing the nonpreferred value of $\mathbf{v}$ is strictly better than choosing its preferred value, with every other variable fixed.

Initialize the best original score $M = -\infty$ and its assignment $\alpha^\star = \emptyset$. Enumerate the assignments α to P by depth-first binary branching in the inherited label order. For each such prefix, take the collection

$$\mathcal{C}(\alpha) = \{C_{\mathbf{v}} : \mathbf{v} \in P,\ \alpha_{\mathbf{v}} \ne p_{\mathbf{v}}\}.$$

Form its ordinary sum (4), substitute α, and cancel complementary occurrences. A negative remaining bound rejects this prefix. Otherwise enumerate all suffix assignments satisfying the sum by Lemma 2.6. Score each complete assignment in F_0, add s_0, and update $M, \alpha^\star$ when the score improves. After all prefixes have been processed, return these best values.

The collection and its sum are local to the current prefix; only the best score and assignment persist between prefixes. A suffix may violate an individual constraint while satisfying the sum. We retain and score such candidates, and the analysis counts them too.

Algorithm 3 LiteralGap(F)

Record the original order on the n input variables V.
$(F_0, s_0) \leftarrow$ Preprocess(F).
Compute every $g_{\mathbf{v}}(F_0)$ and fix $p_{\mathbf{v}}$ as described above.
Choose the branching set P by (7).
For each $\mathbf{v} \in P$, construct $C_{\mathbf{v}}$ from F_0 and $\ell_{\mathbf{v}}(F_0)$ by Lemma 2.4.
$M \leftarrow -\infty$; $\alpha^\star \leftarrow \emptyset$.
for each assignment α to P, by depth-first branching in the fixed order **do**
  $\mathcal{C} \leftarrow \{C_{\mathbf{v}} : \mathbf{v} \in P,\ \alpha_{\mathbf{v}} \neq p_{\mathbf{v}}\}$.
  Form C_Σ by (4); substitute α and cancel complementary occurrences. *// The remaining inequality concerns exactly the suffix variables.*
  if the remaining bound is nonnegative **then**
    for each suffix β satisfying C_Σ, by Lemma 2.6 **do**
      $q \leftarrow s_0 + F_0(\alpha \cup \beta)$.
      If $q > M$, set $M \leftarrow q$ and $\alpha^\star \leftarrow \alpha \cup \beta$.
    end for
  end if
end for
return $(M, \alpha^\star)$.

The algorithm receives only F. It computes P and the preferences without knowing the set S or the real parameters in the theorem below. The stated version uses preprocessing, substitution, and cancellation; it does not make the additional assignments of Simplify during prefix generation. This keeps every prefix on the same variable set. Both the prefix loop and the suffix enumeration are streamed, so neither stores all its outputs.

3.3 Correctness

We must establish that all constraints selected by one optimum can hold simultaneously. Fixed preferences give a direct way to break ties between optima. This argument also shows why constraints can be constructed before the prefix is explored and why the order of visiting the two children is irrelevant.

Lemma 3.1 (Correctness of the literal gap algorithm)**.** *For every simple input formula,* LiteralGap *returns its optimum score and an assignment attaining that score.*

Proof. Preprocessing subtracts the same constant s_0 from every assignment's score, so it preserves the optimal assignments. Among the optimal assignments for F_0, choose x^* with the largest number of variables set to their fixed preferred values. Such an assignment exists because there are finitely many complete assignments.

Suppose $x^*_{\mathbf{v}} \neq p_{\mathbf{v}}$. Changing this one variable to $p_{\mathbf{v}}$ cannot increase the score, by optimality. It cannot leave the score unchanged either: it would then give another optimum with one more preferred value. Its score is therefore strictly smaller. By Lemma 2.4, x^* satisfies $C_{\mathbf{v}}$.

In particular, x^* satisfies every constraint in $\mathcal{C}(x^*|_P)$, and hence their sum. Substitution and complementary cancellation preserve this property. Its prefix is not rejected and its suffix is enumerated. The algorithm evaluates that complete assignment with the offset s_0, so it records the optimum original score. Every other score considered also belongs to a complete assignment of F and cannot exceed the optimum. □

3.4 Running-time guarantee

The theorem requires enough total initial gap and a bound on how strongly a few variables can influence the comparisons. Both conditions concern the formula immediately after preprocessing. The average degree may grow with n; it does not enter the saving in the exponent.

Theorem 3.2 (Relative literal bias)**.** *Fix constants $\varepsilon, \eta \in (0,1]$ and $R \geq 1$. Let F be a simple unweighted Max 2-SAT formula on a set V of n variables, and let $(F_0, s_0) = \textsc{Preprocess}(F)$. For each variable $\mathbf{v}$, define*

$$D_{\mathbf{v}} = d_2^{F_0}(v) + d_2^{F_0}(\neg v), \qquad u_{\mathbf{v}} = d_1^{F_0}(v) + d_1^{F_0}(\neg v),$$

$$g_{\mathbf{v}} = d_2^{F_0}(v) - d_2^{F_0}(\neg v) + 2\big(d_1^{F_0}(v) - d_1^{F_0}(\neg v)\big).$$

Suppose there is a set $S \subseteq V$ with $|S| \geq \eta n$ such that $|g_{\mathbf{v}}| \geq \varepsilon D_{\mathbf{v}}$ for every $\mathbf{v} \in S$. Writing $d = |S|^{-1} \sum_{\mathbf{v} \in S} D_{\mathbf{v}}$, suppose also that

$$d \geq 1, \qquad \sum_{\mathbf{v} \in V} (D_{\mathbf{v}} + u_{\mathbf{v}})^2 \leq Rnd^2. \tag{9}$$

Then an optimal assignment for F can be computed deterministically in polynomial space and time $O^*(2^{(1-\gamma)n})$, where $\gamma = \varepsilon^2\eta^2/(3000R)$.

Condition (9) allows unequal degrees and overlapping neighborhoods. It controls their squared sum rather than imposing a common degree. The proof below gives the stronger explicit search-node bound $(4+2n)\exp((\log 2 - \varepsilon^2\eta^2/(512R))n)$; we state the more conservative exponent above to keep the theorem's guarantee unchanged.

3.5 Proof of the running-time bound

The proof has two parts. First we count all complete assignments admitted by the prefix sums, including those that violate some individual cuts. Then we use Lemma 2.6 to bound the work required to list them. The next lemma provides the mean and coordinate-change bounds for this count. Its occurrence argument explains precisely how overlaps are handled. The only probabilistic tool is the bounded-differences estimate proved in Appendix A.

Throughout the proof, scores refer to F_0. Write $B_{\mathbf{v}} = D_{\mathbf{v}} + u_{\mathbf{v}}$, and let $x[\mathbf{v} \leftarrow p_{\mathbf{v}}]$ denote the assignment obtained from x by changing only $\mathbf{v}$ to its preferred value. Define

$$H_{\mathbf{v}}(x) = F_0(x[\mathbf{v} \leftarrow p_{\mathbf{v}}]) - F_0(x), \qquad L_P(x) = \sum_{\mathbf{v} \in P} H_{\mathbf{v}}(x). \tag{10}$$

Thus $H_{\mathbf{v}}(x) = 0$ when x already takes the preferred value. For the other value it measures the score gain from switching to the preferred value. The set P and all preferences are fixed before the uniform assignment x is drawn.

Lemma 3.3 (The combined comparison statistic)**.** *For any fixed set P and preferences chosen from the gaps of F_0,*

$$\mathbb{E}L_P(x) = \frac{1}{4} \sum_{\mathbf{v} \in P} |g_{\mathbf{v}}|.$$

Changing only variable $\mathbf{w}$ changes L_P by at most $B_{\mathbf{w}} + D_{\mathbf{w}} \leq 2B_{\mathbf{w}}$. If x satisfies the summed constraint associated with its prefix $x|_P$, then $L_P(x) \leq 0$.

Proof. The expectation. Fix $\mathbf{v}$ and the values of every other variable. The score gain of its preferred value over its nonpreferred value is independent of $x_{\mathbf{v}}$. Averaging over this one fair bit, $H_{\mathbf{v}}$ is zero half the time and equals that gain half the time. Averaging next over

the other variables, the expected preferred-over-nonpreferred gain is $|g_{\mathbf{v}}|/2$, by (2) and the preference rule. Hence $\mathbb{E}H_{\mathbf{v}} = |g_{\mathbf{v}}|/4$. Add these expectations; no independence between different comparisons is needed.

The effect of one variable. Let x' differ from x only at $\mathbf{w}$. In the summand $H_{\mathbf{w}}$, if it is present, the assignments with $\mathbf{w}$ reset to its preferred value coincide. Consequently

$$H_{\mathbf{w}}(x') - H_{\mathbf{w}}(x) = F_0(x) - F_0(x').$$

Only clauses containing $\mathbf{w}$ can change their satisfaction, each by at most one. The absolute value of this difference is at most $B_{\mathbf{w}}$.

For $\mathbf{v} \neq \mathbf{w}$, changing $\mathbf{w}$ does not change whether $x_{\mathbf{v}}$ is preferred. If it is preferred, both values of $H_{\mathbf{v}}$ are zero. Otherwise, the gain identity in Lemma 2.4 shows that only occurrences of literals of $\mathbf{w}$ in $C_{\mathbf{v}}$ can affect $H_{\mathbf{v}}$, by at most one per occurrence. Across the comparisons for all variables other than $\mathbf{w}$, these occurrences number exactly $D_{\mathbf{w}}$: each binary clause containing $\mathbf{w}$ contributes once, to its partner's comparison. Therefore the sum over the subset $P \setminus \{\mathbf{w}\}$ changes by at most $D_{\mathbf{w}}$. The triangle inequality gives the claimed bound. Repeated or overlapping neighborhoods require no separate assumption.

The consequence of satisfying the sum. Write $C_{\mathbf{v}}$ as $\mathrm{lhs}(C_{\mathbf{v}}, x) \leq b_{\mathbf{v}}$, and put $I_P(x) = \{\mathbf{v} \in P : x_{\mathbf{v}} \neq p_{\mathbf{v}}\}$. For every $\mathbf{v} \in I_P(x)$, the strict cut's offset of minus one gives

$$\mathrm{lhs}(C_{\mathbf{v}}, x) - b_{\mathbf{v}} = H_{\mathbf{v}}(x) + 1.$$

All other summands in L_P are zero. Adding the displayed identities yields

$$\sum_{\mathbf{v} \in I_P(x)} (\mathrm{lhs}(C_{\mathbf{v}}, x) - b_{\mathbf{v}}) = L_P(x) + |I_P(x)|. \tag{11}$$

Satisfaction of the sum makes the left-hand side nonpositive. Thus $L_P(x) \leq -|I_P(x)| \leq 0$, as required. Substitution of the prefix does not change this identity on its completions. □

The following counting statement isolates the formula properties used by the analysis. It will prove both the relative-bias theorem and the dense-gap corollary. Its count includes all candidates enumerated by the algorithm, rather than only those satisfying the individual constraints.

Lemma 3.4 (Counting candidates from the initial gaps)**.** *For the preprocessed formula F_0, put*

$$G = \sum_{\mathbf{v} \in V} |g_{\mathbf{v}}|, \qquad Q = \sum_{\mathbf{v} \in V} B_{\mathbf{v}}^2.$$

Suppose $Q > 0$, and choose P by (7). Let $W(F_0)$ be the total number of complete assignments satisfying their prefix's summed constraint. Then

$$W(F_0) \leq 2^n \exp\left(-\frac{G^2}{512Q}\right). \tag{12}$$

Proof. Let x be a uniform complete assignment. By (8) and Lemma 3.3,

$$\mu := \mathbb{E}L_P(x) \geq G/8 \geq 0.$$

Changing coordinate $\mathbf{w}$ changes L_P by at most $c_{\mathbf{w}} = 2B_{\mathbf{w}}$, so $\sum_{\mathbf{w}} c_{\mathbf{w}}^2 = 4Q > 0$. Apply Lemma A.1 with deviation $a = \mu$:

$$\mathbb{P}(L_P(x) \leq 0) \leq \exp\left(-\frac{\mu^2}{8Q}\right) \leq \exp\left(-\frac{G^2}{512Q}\right).$$

Every enumerated assignment satisfies $L_P(x) \leq 0$, by Lemma 3.3. Each complete assignment has exactly one prefix, and suffix enumeration lists it at most once. Its uniform probability is 2^{-n}. Multiplying the probability bound by 2^n therefore proves the count. □

Proof of Theorem 3.2. The algorithm is correct by Lemma 3.1. The empty variable set is trivial; assume $n \geq 1$. Put $\theta = \varepsilon\eta$. The assumptions imply

$$G \geq \sum_{\mathbf{v}\in S} |g_{\mathbf{v}}| \geq \varepsilon \sum_{\mathbf{v}\in S} D_{\mathbf{v}} = \varepsilon|S|d \geq \theta nd,$$
$$Q = \sum_{\mathbf{v}\in V} B_{\mathbf{v}}^2 \leq Rnd^2.$$

Also $Q > 0$: the positive average binary degree on the nonempty set S implies at least one positive occurrence count. Consequently

$$\frac{G^2}{512Q} \geq \frac{\theta^2 n^2 d^2}{512Rnd^2} = \frac{\theta^2 n}{512R}.$$

Lemma 3.4 gives $W(F_0) \leq 2^n e^{-\theta^2 n/(512R)}$.

Let $T = |P| \leq \lceil n/2 \rceil$. By Lemma 2.6, the number of search nodes, including rejected suffix nodes, is at most

$$\begin{aligned} 2^{T+1} - 1 + 2nW(F_0) &\leq 4 \cdot 2^{n/2} + 2n \exp\big((\log 2 - \theta^2/(512R))n\big) \\ &\leq (4 + 2n) \exp\big((\log 2 - \theta^2/(512R))n\big). \end{aligned}$$

The last inequality uses $\theta \leq 1$, $R \geq 1$, and $\theta^2/(512R) \leq 1/512 < \log 2/2$. For $\gamma = \theta^2/(3000R)$, we have $\gamma \log 2 \leq \theta^2/(512R)$. Thus the displayed bound is at most $(4 + 2n)2^{(1-\gamma)n}$, and $\gamma > 0$ gives a fixed saving.

It remains to account for arithmetic and storage. Let m_0 be the number of clauses of F_0, with multiplicity. A comparison constraint has at most m_0 occurrences and bound magnitude at most $m_0 + 1$. A sum of at most n such constraints therefore has at most nm_0 occurrences and bound magnitude at most $n(m_0+1)$. Substitution and complementary cancellation cannot increase the occurrence list. The magnitude of the resulting bound is at most its original magnitude plus twice its original occurrence count. These are polynomial-size integer data, so constructing and testing each sum takes polynomial time. Every candidate score is also computed in polynomial time.

Preprocessing, computing the gaps, and choosing P take polynomial time. The depth-first prefix and suffix traversal has at most $n + 1$ levels; its active states and the cancellation procedure use polynomial space. Only one best complete assignment is retained. Multiplying the node bound by the polynomial work per node proves the stated time bound. □

3.6 Dense gaps and the scope of the analysis

For a simple formula, linear gaps yield a direct input condition: simplicity already bounds every variable's occurrence count by $O(n)$. The next corollary uses the same counting lemma. We explain separately how preprocessing preserves the relevant quantities, since it can convert binary bias into unit clauses.

Corollary 3.5 (Linear effective gaps in a simple formula)**.** *Fix $\varepsilon, \eta \in (0, 1]$. Let F be a simple unweighted Max 2-SAT formula on n variables. Suppose at least ηn variables satisfy*

$$|d_2^F(v) - d_2^F(\neg v) + 2(d_1^F(v) - d_1^F(\neg v))| \geq \varepsilon n.$$

Then an optimal assignment for F can be computed deterministically in polynomial space and time $O^*(2^{(1-\varepsilon^2\eta^2/48000)n})$.

Proof. The case $n = 0$ is trivial. For $n \geq 1$, each variable initially has at most $4(n-1)$ binary occurrences and at most two unit occurrences. The pair reduction preserves every effective gap. At its shared literal, two signed binary occurrences are replaced by one unit with coefficient two; at its other variable, opposite signed binary occurrences cancel. Opposite-unit cancellation also preserves the gap. Neither reduction increases a variable's total number of binary and unit occurrences. Thus, in F_0,

$$B_{\mathbf{v}} \leq 4(n-1) + 2 \leq 4n, \qquad Q \leq 16n^3, \qquad G \geq \varepsilon\eta n^2 > 0.$$

In particular $Q > 0$. Lemma 3.4 gives

$$W(F_0) \leq 2^n \exp\left(-\frac{\varepsilon^2\eta^2 n}{8192}\right).$$

Combining this count with $|P| \leq \lceil n/2 \rceil$ as in the theorem's proof bounds the nodes by

$$(4 + 2n)\exp\big((\log 2 - \varepsilon^2\eta^2/8192)n\big).$$

Since $\log 2/48000 \leq 1/8192$, this implies the claimed conservative exponent. The arithmetic and space bounds are the same as above. The argument does not require a positive residual binary degree on each biased variable; bias converted to units is included in G. □

Without units, the hypothesis is exactly a gap between literal frequencies. For a simple input with units, the gap counting units and binary clauses equally differs from the effective gap by at most one. A linear gap in that convention therefore gives a linear effective gap with any fixed slightly smaller coefficient for sufficiently large n. No restriction on the degree sequence is needed for this dense corollary.

Branch order and additional reductions. The fixed preferences determine which constraints are collected, not the order in which the two values must be explored. Either order gives the same candidate set and the same bound. The proved algorithm enumerates suffixes using the single sum. Additional simplifications can be studied separately, with their compatibility and running-time accounting made explicit; they are not needed for the present result.

4 Normalized accumulation under random signs

4.1 Intuition

The literal-gap theorem uses a substantial preference for one value of many variables. Random signs usually create smaller preferences. We can nevertheless obtain a fixed saving by accumulating many of their constraints. Two ingredients are needed: put constraints of different sizes on comparable scales, and control the effect of their overlaps.

For intuition, fix any graph and place one clause on each edge, choosing the two literal signs independently and uniformly. Follow a path in the branching tree. The preferred value of the next variable is the one with larger average score over uniform assignments to the remaining variables. Whenever the path takes the other value, its pruning constraint requires the eventual completion to reverse that preference.

The numerical size of this requirement is not enough to measure how restrictive it is. Consider the two constraints

$$\sum_{i=1}^{100} z_i \leq 40, \qquad \sum_{i=1}^{400} z_i \leq 180,$$

with distinct Boolean variables in each sum. Their deficits below the uniform means are 10 and 20, but their standard deviations are 5 and 10. Each asks for a deviation of two standard deviations, so they have comparable pruning power. Adding their unscaled inequalities would nevertheless give the second a larger numerical contribution. Dividing its two sides by two puts the requirements and fluctuations on the same scale without changing either constraint's satisfying assignments.

We use this normalization before adding the constraints. In the random models considered here, the original number of neighbors gives a useful estimate of the scale: a variable of degree d receives a weight approximately $1/\sqrt{d}$. This is a fixed weight computed from the input, not an estimate of each residual constraint's exact strength. An unusually large preference still produces a stronger normalized requirement. When the graph is regular, all weights are equal and the ordinary sum already has the desired scaling.

Normalization alone does not make accumulation effective. If many constraints asked their shared variables to take the same values, one completion could satisfy their requirements together. Random signs prevent this agreement from persisting. For example, if two constraints contain y with opposite signs,

$$y + A \le b, \qquad \neg y + B \le c,$$

their sum simplifies to $A + B \le b + c - 1$. The variable y can help one constraint only by hurting the other; it has no remaining influence on the sum. Here A and B denote sums of other literal occurrences. Opposing occurrences can be useful even when the two constraints have exactly the same variable neighborhood.

On a uniform path, about half of the branching choices are nonpreferred. After linearly many steps, their normalized requirements typically have a linear total. The proof shows that an exponentially small fraction of input–assignment pairs provide enough collective compensation to satisfy the sum. It exposes fresh endpoint signs as variables are reached, rather than assuming independence of the generated constraints. This argument is what makes overlapping neighborhoods manageable.

To turn this into a time bound, the algorithm branches on the first half of a fixed variable order and then enumerates completions satisfying the summed constraint. Its enumeration procedure spends polynomial work per listed completion, including rejected partial assignments. Bounding the total number listed across all prefixes therefore bounds the running time. The algorithm itself makes no random choices.

4.2 Notation and weighted sums

We use the same residual formulas, literal counts, and pruning constraints as in Section 3. We use the prefix–suffix enumeration from Section 2.3. The additional operation here is to weight the constraints before adding them, giving the sum C_Σ in (13) below.

Let n denote the number of input variables. The algorithm separately optimizes variables occurring in no binary clause and searches on the remaining $r \le n$ variables. List these as $\mathbf{u}_1, \dots, \mathbf{u}_r$ in their original input order, inherited from the fixed input indices. This list specifies the branching order; the pruning constraints do not determine or change it. Write x_t for the Boolean value of $\mathbf{u}_t$. A *prefix assignment of length* T specifies $x_1, \dots, x_T$; a *suffix assignment* specifies the remaining $r - T$ values. These terms refer to this fixed order. As before, α denotes the current partial assignment and $\mathcal{C}$ the collection of pruning constraints. We retain the individual constraints, substituting each assigned value in them as the search proceeds.

To define C_Σ, give each constraint $C : \sum_i \ell_i \le b_C$ a positive rational weight ω_C, fixed when it is created. Multiply both sides of each constraint by its weight and add the resulting inequalities:

$$C_\Sigma : \qquad \sum_{C \in \mathcal{C}} \omega_C \sum_i \ell_i \le \sum_{C \in \mathcal{C}} \omega_C b_C. \tag{13}$$

These weights are assigned to whole constraints; they are distinct from the coefficients obtained by collecting repeated literal occurrences. When every $\omega_C = 1$, this is the ordinary sum used in Lemma 2.5, and each literal's coefficient is simply its total number of occurrences. The random-formula algorithm specifies the weights in (15). Every assignment satisfying all individual constraints satisfies this sum. The converse need not hold. In an empty collection the sum is $0 \leq 0$.

Collect complementary coefficients and move their constant contribution to the right-hand side as in Section 2.3. This gives (5), including zero-coefficient variables. Lemma 2.6 then enumerates precisely the completions satisfying this weighted sum. The weights used below have polynomial encoding length.

4.3 The algorithm

The algorithm receives only F. It constructs the graph $G_F = (V_F, E_F)$ directly from the binary clauses of F, before applying Preprocess:

$$E_F = \{\{u, v\} : F \text{ contains a binary clause on } u, v\}. \tag{14}$$

The vertices are exactly the endpoints, $V_F = \bigcup_{e \in E_F} e$, so G_F has no isolated vertices. Literal signs do not affect whether a pair is an edge, and unit clauses create no edges. This graph remains fixed throughout the search. The graph used to generate F belongs to the distributional assumptions below and is not supplied to the algorithm.

A variable outside V_F occurs only in unit clauses. Set it to the value satisfying more of its units, breaking ties by choosing zero. Let α_0 collect these assignments, let s_0 be their total score, and let F_{core} contain the clauses on the remaining variables. An optimum for F_{core}, extended by α_0, is an optimum for F, with s_0 added to its score. If V_F is empty, this already solves the instance. Otherwise write $r = |V_F|$ and search on these r variables.

List the variables of V_F in their original input order as $U = (\mathbf{u}_1, \ldots, \mathbf{u}_r)$. Set $T = \lceil r/2 \rceil$, the number of variables to be assigned by branching before switching to enumeration. This is not the number of constraints created. Next, before preprocessing, record the weights

$$\omega_t = \frac{1}{\lceil \sqrt{\deg_{G_F}(\mathbf{u}_t)} \rceil}. \tag{15}$$

A constraint created when branching on variable $\mathbf{u}_t$ receives weight ω_t. As explained in Section 4.1, this normalizes the degree-dependent scale of the random requirements and their fluctuations. The actual imbalance remains in the bound of each constraint. If G_F is regular, all weights are equal, and the weighted sum is equivalent to the ordinary sum. The weights remain fixed throughout the search.

The two procedures use the following data. Shared variables are initialized once by RandomFormula and are available to every call of RandomSearch.

Fixed shared data. $U = (\mathbf{u}_1, \ldots, \mathbf{u}_r)$ is the variable order, and $(\omega_1, \ldots, \omega_r)$ contains the constraint weights. Neither changes during the search. All variables remain in U, including variables that disappear from the residual formula.

Shared best solution. M is the largest score in F_{core} found so far, and $\alpha^\star$ assigns all variables of V_F and attains that score. The outer procedure adds s_0 and α_0 when returning the solution for the original formula. Initially $M = -\infty$ and $\alpha^\star = \emptyset$, indicating that no complete assignment has yet been evaluated. Every recursive call may update this same pair. An improvement is retained when the call returns and when the search backtracks to explore another branch.

Parameters of a recursive call. F is the residual soft formula, $\mathcal{C}$ is the collection of pruning constraints with their weights, and α is the current partial assignment. The value s is the score offset accumulated through preprocessing and assignments: for any completion β, its score in the formula F_{core} is s plus the number of clauses it satisfies in F. These four parameters belong to the current node and are copied separately for its children. The parameter T is the stopping depth; it is passed unchanged to every recursive call.

At each call, α assigns exactly the first $|\alpha|$ variables of U. In particular, M and $\alpha^\star$ are shared across branches, whereas s and α describe only the current branch. The identities used by PREPROCESS apply to copies of clauses as well. Its score guarantees therefore also apply to the bounded-multiset extension in Appendix B.

After initializing this shared data, apply PREPROCESS to F_{core} and start RANDOMSEARCH with the resulting formula and score offset, an empty assignment, and an empty constraint collection. The recursive search uses substitution, cancellation, and rejection, but does not call the full SIMPLIFY procedure or make forced assignments. Thus every call at depth $t = |\alpha|$ has assigned exactly the first t variables of U. Created constraints remain in $\mathcal{C}$ with their updated bounds, even if they have become automatically satisfied.

At each call, first form C_Σ and simplify it to (5). A negative bound rejects the current prefix. Otherwise, if $t = T$, stop creating constraints and enumerate assignments to $\mathbf{u}_{T+1}, \ldots, \mathbf{u}_r$ satisfying this sum, using Lemma 2.6. Evaluate each completion in the residual formula, add the score offset s, and update $M, \alpha^\star$ if this improves the best score. Then return. A completion may violate an individual constraint, but evaluating its actual score preserves correctness.

If $t < T$, select $\mathbf{u}_{t+1}$, compute its preferred literal from the current residual formula by (3), and construct the constraint of Lemma 2.4 with weight ω_{t+1}. Explore both values in separate copies of the state, adding this constraint only to the nonpreferred child. Substitute the chosen value in the formula and constraints and continue recursively. After the search finishes, extend the best core assignment by α_0 and add s_0 to its score.

For example, with eight core variables, the search branches on $\mathbf{u}_1, \ldots, \mathbf{u}_4$ and then enumerates completions on the last four variables for each surviving prefix. This choice gives at most 2^T prefixes while allowing a linear number of branching steps to create constraints. The proof bounds the total work of completing those prefixes.

Algorithm 4 RANDOMFORMULA(F)

Construct $G_F = (V_F, E_F)$ from F by (14), before preprocessing.
Optimize variables outside V_F, obtaining $F_{\text{core}}, s_0, \alpha_0$ as above.
if $V_F = \emptyset$ **then**
  return (s_0, α_0).
end if
Initialize shared $U = (\mathbf{u}_1, \ldots, \mathbf{u}_r)$ in the original input order, where $r = |V_F|$.
$T \leftarrow \lceil r/2 \rceil$. *// Branch on the first T variables, then enumerate completions.*
Initialize the shared weights ω_t from G_F by (15).
Initialize shared $M \leftarrow -\infty$ and $\alpha^\star \leftarrow \emptyset$.
$(F, s) \leftarrow$ PREPROCESS(F_{core}).
RANDOMSEARCH($F, \emptyset, \emptyset, s, T$).
return $(M + s_0, \alpha^\star \cup \alpha_0)$.

Algorithm 5 RandomSearch$(F, \mathcal{C}, \alpha, s, T)$

Require: Fixed shared data $U, (\omega_t)_{t=1}^{r}$ and shared best solution $M, \alpha^\star$, initialized above.

$t \leftarrow |\alpha|$. *// The variables* $\mathbf{u}_1, \ldots, \mathbf{u}_t$ *have been assigned.*
Form C_Σ by (13) and simplify it to (5).
if its bound B is negative **then**
  return
end if
if $t = T$ **then**
  for each suffix assignment β satisfying C_Σ, by Lemma 2.6 **do**
    Let q be s plus the number of clauses of F satisfied by β.
    If $q > M$, update shared $M \leftarrow q$ and $\alpha^\star \leftarrow \alpha \cup \beta$.
  end for
  return
end if
Let $\mathbf{u} \leftarrow \mathbf{u}_{t+1}$. *// The next variable in the fixed list* U.
Choose its preferred literal v from the current F by (3).
Construct C from F and v by Lemma 2.4; give it weight ω_{t+1}.
for $p \in [1, 0]$ **do**
  Make separate copies $(F_p, \mathcal{C}_p, \alpha_p, s_p)$ of the current state.
  if $p = 0$ **then**
    $\mathcal{C}_p \leftarrow \mathcal{C}_p \cup \{C\}$.
  end if
  Assign $v = p$, updating the copied formula, constraints, assignment, and score.
  RandomSearch$(F_p, \mathcal{C}_p, \alpha_p, s_p, T)$.
end for

4.4 Correctness

The comparisons are the same as in the literal-gap search. The only new point is that suffix enumeration enforces C_Σ from (13), which is weaker than enforcing every constraint separately. The next lemma shows that this still retains an optimum; its proof does not use randomness.

Lemma 4.1 (Correctness of weighted enumeration)**.** *For every formula F, including formulas with repeated clauses,* RandomFormula *returns an optimum score and an assignment attaining it.*

Proof. Variables outside V_F can be optimized independently from their units. It therefore suffices to prove that the recursive search finds an optimum for F_{core}. Preprocessing changes the score of every assignment by the same recorded constant. It therefore preserves both optimal assignments and all comparisons between the two values of a variable.

Consider the full decision tree in the fixed variable order, restoring any prefixes rejected by the algorithm. At each of the first T levels, place the preferred child first. Complete the rest of the tree in any fixed order, and choose the earliest optimal complete assignment x^*. If its path takes a nonpreferred child at variable t, changing only that value to the preferred one produces an earlier assignment. Its score must be strictly smaller: a larger score contradicts optimality, and an equal score contradicts the choice of x^*. Lemma 2.4 therefore implies that x^* satisfies the constraint added at that step.

Thus x^* satisfies every constraint created on its prefix, and hence their positively weighted sum at every earlier depth. The sum test never rejects that prefix, and enumeration at depth T visits its suffix. Every enumerated candidate is scored in F_{core}, including the preprocessing and assignment offsets. Adding the separately optimized score s_0 and extending by α_0 therefore returns an optimum for F. □

4.5 Random inputs and the running-time guarantee

The support specifies the pairs on which clauses are sampled. Fix any set E of unordered pairs of distinct input variables. Its size and degree sequence are arbitrary. In the first model, every selected pair receives exactly one of its four clauses, uniformly and independently. In the second model, each of those four clauses is included independently with probability $1/4$, and all pairs are sampled independently. The clause count on a selected pair then has distribution Binomial$(4, 1/4)$: it can be zero through four, with mean one.

The generating graph has edge set E and precisely their endpoints as vertices. It is a description of the distribution, not an input to the algorithm. In the second model, its selected pairs need not all appear in the observed graph G_F. Variables outside the observed graph have only units and are optimized separately.

Theorem 4.2 (Random clauses on arbitrary supports)**.** *There is an absolute constant $c_0 \in (0, (\ln 2)/2)$ with the following property. Fix n variables and any set E of unordered variable pairs. Generate the binary clauses by either of the following two models:*

1. *On each pair in E, choose exactly one of the four possible clauses uniformly, independently across pairs.*
2. *Include each of the four possible clauses on each pair in E independently with probability $1/4$, with all choices independent.*

Pairs outside E have no binary clauses. Additional unit clauses may be any multiset fixed independently of these draws.

An optimal assignment can be computed from the resulting formula alone by a deterministic polynomial-space algorithm with expected running time $O^*(2^n e^{-c_0 n})$. With probability at least $1 - 3e^{-c_0 n/2}$, its running time is $O^*(2^n e^{-c_0 n/2})$. The algorithm returns an optimum on every input.

The same constants work for every support, including an empty support. There is no lower bound on the clause density. A random support chosen before and independently of its clause signs is covered by conditioning on it and averaging the uniform bounds. In particular, an SBM graph decorated with these random clauses needs no additional SBM-specific analysis. Max-Cut on an SBM graph has fixed complementary signs on every edge and will require the different method of Section 6.

4.6 Proof of the running-time bound

We first condition on the observed graph G_F. Lemma B.3 shows that conditioning on a pair being present preserves the sign symmetries used by the proof. The more general pair model and supporting estimates are given in Appendix B. Thus the graph used by the algorithm can be treated as fixed for the conditional analysis, even though it was constructed from F. Write $r = |V_F|$ for the number of variables searched. We count assignments to these variables that satisfy the summed constraint at their own prefix. The enumeration lemma then turns that count into a time bound. The proof has three ingredients.

1. Along a uniform path, each nonpreferred choice adds a positive requirement measured relative to the average contribution of the remaining literals. Their weighted total is at least of order r on most paths. Lemma B.7 bounds the probability that it is much smaller.
2. The actual remaining values can help satisfy these requirements, but their effects have random signs. Lemma B.8 bounds the chance of an unusually favorable total contribution. Its proof uses the randomness of unrevealed endpoint signs, not independence of the learned constraints.

3. Combining these estimates shows that an exponentially small fraction of conditional formula–assignment pairs pass the sum. Averaging over assignments and then over the observed graph bounds the expected enumeration work; a final probability bound gives the running time for most formulas.

Appendix B proves the supporting lemmas and their elementary probability estimates.

Proof of Theorem 4.2. Both models are covered by the supporting lemmas with $m_0 = 4$ and $\kappa = 3/4$. Here m_0 bounds the number of clauses on a pair, and κ bounds below the second moment of the signed occurrence count at either endpoint. One uniformly signed clause has second moment one. For independent inclusion of four clauses with probability $1/4$, it is $4(1/4)(3/4) = 3/4$. Complementing either endpoint preserves each law. Set

$$c_1 = \frac{\sqrt{\kappa}}{2\sqrt{1 + 4m_0^4/\kappa^2}}, \qquad c_0 = \frac{c_1^2}{10816 m_0^2}.$$

These are fixed positive constants for the two stated models.

Use RandomFormula on F alone. Correctness is Lemma 4.1. Depth-first search and suffix enumeration use polynomial space. Constructing G_F and optimizing variables outside V_F take polynomial time.

Condition on $G_F = H$, where H is any possible nonempty observed graph, and write $r = |V(H)|$. By Lemma B.3, its pair laws satisfy the assumptions of Definition B.1 in Appendix B, with the same m_0, κ. Its vertex order, inherited from the input indices, and its degrees are now fixed. All probabilities in Steps 1 and 2 refer to this conditional model. The weights are rational with polynomial encoding length, and satisfy

$$\frac{1}{2\sqrt{\deg_H(\mathbf{u}_t)}} \le \omega_t \le \frac{1}{\sqrt{\deg_H(\mathbf{u}_t)}}. \tag{16}$$

Thus all arithmetic per search state has polynomial cost.

1. Express the summed requirement. Choose a uniform assignment $x \in \{0,1\}^r$, independently of the remaining random choices in F. For the analysis only, construct its first $T = \lceil r/2 \rceil$ comparisons even if an earlier sum test would have rejected its prefix. Let $\mathrm{gain}_t(x)$ be the score with $x_t = 1$ minus the score with $x_t = 0$, keeping all other values fixed. It does not depend on x_t. Let Δ_t be its average over uniform later values, with $x_1, \dots, x_{t-1}$ fixed. The preferred value of the original variable is $p_t = 1$ when $\Delta_t \ge 0$ and $p_t = 0$ otherwise. Equivalently, the algorithm's preferred literal is x_t or $\neg x_t$, respectively, by (3) applied to the current residual formula.

Put $I = \{t \le T : x_t \ne p_t\}$, the indices at which a constraint is created. Lemma 2.4 expresses each such constraint as $(2p_t - 1)\mathrm{gain}_t(x) + 1 \le 0$. Hence its weighted sum is

$$A_T + Q_T \le 0, \tag{17}$$

where

$$A_T = \sum_{t \in I} \omega_t(|\Delta_t| + 1),$$
$$Q_T = \sum_{t \in I} \omega_t(2p_t - 1)(\mathrm{gain}_t(x) - \Delta_t).$$

Here A_T records the requirements at creation, while Q_T records the deviation supplied by the subsequent values. The identity follows from $(2p_t - 1)\Delta_t = |\Delta_t|$. Preprocessing preserves each score difference, so these expressions computed from the original clauses are exactly the ones used by the search.

2. Bound the fraction that satisfies the sum. Lemma B.7 gives, for any $a, b > 0$,

$$\mathbb{P}\left(A_T < \frac{c_1 T}{26} - a - b\right) \le e^{-2a^2/(Tm_0^2)} + e^{-169b^2/(m_0^2 r)}.$$

Lemma B.8 gives, for any $c > 0$,

$$\mathbb{P}(Q_T < -c) \le e^{-2c^2/(m_0^2 T)}.$$

Take $a = b = c = c_1 T/104$. Outside these three exceptional events,

$$A_T + Q_T \ge \frac{c_1 T}{26} - 3\frac{c_1 T}{104} = \frac{c_1 T}{104} > 0.$$

Thus the summed constraint fails. The first and third exponents equal $c_1^2 T/(5408 m_0^2) \ge c_0 r$. The second is $169 c_1^2 T^2/(10816 m_0^2 r) \ge c_0 r$, since $T \ge r/2$. Consequently

$$\mathbb{P}_{F,x}(A_T + Q_T \le 0 \mid G_F = H) \le 3e^{-c_0 r}.$$

3. Convert the count to running time. For a prefix α, let $N(\alpha)$ count suffix assignments satisfying its sum, and put $W(F) = \sum_{\alpha \in \{0,1\}^T} N(\alpha)$. This definition includes prefixes rejected early, and so bounds the number of completions actually enumerated. Since x is uniform,

$$\mathbb{E}[W(F) \mid G_F = H] = 2^r \mathbb{P}_{F,x}(A_T + Q_T \le 0 \mid G_F = H) \le 3 \cdot 2^r e^{-c_0 r}.$$

If H is empty, the algorithm finishes in polynomial time; define $W(F) = 1$ in this case, so the same bound holds with $r = 0$. Since $\kappa \le m_0^2$, we have $c_0 \le 1/216320 < \ln 2$. The quantity $2^r e^{-c_0 r}$ is therefore increasing in r. Using $r \le n$ and averaging over G_F gives

$$\mathbb{E}W(F) \le 3 \cdot 2^n e^{-c_0 n}.$$

Lemma 2.6 bounds the search work by $O^*(2^T + W(F))$. Since $2^T \le 2^{\lceil n/2 \rceil}$ and $c_0 < (\ln 2)/2$, this prefix cost is absorbed by $O^*(2^n e^{-c_0 n})$, proving the expectation bound. Markov's inequality applied to the unconditional expectation also gives

$$\mathbb{P}_F\left(W(F) > 2^n e^{-c_0 n/2}\right) \le 3e^{-c_0 n/2}.$$

The prefix cost 2^T is smaller than the claimed high-probability time bound, up to a constant factor, because $c_0 < \ln 2$. This completes the proof. □

5 Assignment counts and regular-graph Max-Cut

5.1 Intuition

We now consider inputs whose interactions have a systematic common part. Max-Cut provides a natural example. Encode every graph edge $\{u, v\}$ by $(u \vee v)$ and $(\neg u \vee \neg v)$. The pair contributes $1 + [x_u \ne x_v]$, so maximizing the number of satisfied clauses maximizes the cut, up to a constant. Every variable has equal positive and negative binary occurrence counts. Random literal signs are absent.

The shared interaction can cause comparisons to agree for a reason that is unrelated to the irregular part of the graph. On a clique, for example, the cut size is $h(n - h)$, where h is the total number of ones. The identities of the selected vertices do not matter for that part of the objective. Guessing h accounts for it using only $n + 1$ runs.

For a regular graph, we use the same idea to account for the average interaction between a vertex and the others. Within a count guess, comparisons use the differences between actual

pair coefficients and this common value. A small allowance makes the adjusted comparisons sound for an optimum in the correct run.

We then accumulate the adjusted requirements. The useful graph property is that the remaining interactions cannot have too large a coordinated effect on a collection of variables. Small nontrivial eigenvalues give exactly a bound of this kind after the common interaction is removed. They are used to prove the running time; the algorithm only computes gains and counts.

The prefix is handled in two rounds. Preferences within the second round use the assigned values in the first, while preferences in a round are fixed before its values are examined. Enough interaction between the rounds produces substantial preferences on most paths. The correlation bound limits the subsequent compensation. As before, enumerating the summed inequality converts this accumulation into a running-time saving.

5.2 Notation and the count adjustment

The following coefficients record each pair's contribution to score differences. They are computed from the input formula. Expanding the truth indicator of each clause expresses the number of satisfied clauses as

$$F(x) = c + \sum_{v} a_v x_v + \sum_{u<v} J_{uv} x_u x_v, \qquad x \in \{0,1\}^n. \tag{18}$$

The matrix J is symmetric with zero diagonal. A binary clause with equal literal polarities contributes -1 to J_{uv}; one with opposite polarities contributes $+1$. Unit clauses change only the constant and linear terms. The gain from changing x_t from zero to one is therefore

$$\mathrm{gain}_t(x) = a_t + \sum_{w \neq t} J_{tw} x_w.$$

These quantities are computed by scanning clauses.

Fix a rational number β representing the common part of the pair coefficients. For a guess $h \in \{0, \ldots, n\}$ define

$$H_t^{h,\beta}(x) = \mathrm{gain}_t(x) + \beta \left(h - \sum_{w \neq t} x_w \right) = a_t + \beta h + \sum_{w \neq t} (J_{tw} - \beta) x_w. \tag{19}$$

The second expression explains the adjustment: once h is fixed, the common pair contribution β is replaced by the known constant βh. The remaining coefficients are the deviations $J_{tw} - \beta$. When $h = \sum_w x_w$ is the correct guess, $H_t^{h,\beta}(x) = \mathrm{gain}_t(x) + \beta x_t$. We account for this last term by allowing a slack of $|\beta|$ in a comparison.

5.3 The algorithm

The procedure CountComparisons receives F, the rational adjustment β, and ordered, nonempty rounds $B_1, \ldots, B_\ell$ partitioning a prefix of T variables in a fixed input order. The variables outside this prefix form the suffix. For the Max-Cut encoding of a d-regular graph, choose $\beta = -2d/(n-1)$, the average off-diagonal pair coefficient. Use $T = \lfloor n/2 \rfloor$ with two rounds of sizes $\lfloor n/4 \rfloor$ and $T - \lfloor n/4 \rfloor$. The bounded-degree alternative is described with Corollary 5.2. The comparison procedure also permits singleton rounds, as used in the supporting independent-pair analysis.

Record the original variable set and n, and initialize the best score and assignment $M, \alpha^\star$. Apply Preprocess, record its score offset s_0, and compute the coefficients a, J from the resulting formula by (18). Preprocessing changes only the constant part of the objective, so it

preserves all gains. The original variables remain in the prefix and suffix even if their clause occurrences disappear.

Process the count guesses $h = 0, \ldots, n$ consecutively. When $\beta = 0$, the comparisons do not depend on h, so use only $h = 0$. For each guess, enumerate all assignments α to the prefix. Initialize a separate sum $L(x) = 0$ for the current guess and prefix, then process its rounds in order.

For a variable t in round B_j, let $B_{<j}$ be the union of the earlier rounds. Compute the average Δ_t of $H_t^{h,\beta}$ using α on $B_{<j}$ and averaging uniformly over all other variables. In particular, the preference ignores the values of α in the current and later rounds. This average is computed exactly by substituting $1/2$ for the averaged variables in (19). Set the preferred value $p_t = 1$ if $\Delta_t \geq 0$, and $p_t = 0$ otherwise. If $\alpha_t \neq p_t$, add the comparison

$$(2p_t - 1)H_t^{h,\beta}(x) \leq |\beta|.$$

The sum L records left-hand sides minus right-hand sides of these comparisons.

After all prefix rounds have been processed, substitute α in L and enumerate suffix assignments y satisfying $L(\alpha, y) \leq 0$ by Lemma 2.6. Evaluate each candidate in the preprocessed formula and add s_0 to obtain its original score. Retain the best score and assignment across all guesses and prefixes, then return them. Enumeration does not require a candidate to have exactly h ones; each candidate is scored in the actual formula.

Algorithm 6 CountComparisons$(F, \beta, B_1, \ldots, B_\ell)$

Record the original variable set and n, retaining the supplied prefix rounds.
$M \leftarrow -\infty$; $\alpha^\star \leftarrow \emptyset$.
$(F, s_0) \leftarrow$ Preprocess(F).
Compute a, J from F by (18).
Set $\mathcal{H} \leftarrow \{0, \ldots, n\}$ if $\beta \neq 0$, and $\mathcal{H} \leftarrow \{0\}$ otherwise. *// One run suffices when the comparison does not depend on h.*
for each $h \in \mathcal{H}$ **do**
  for each prefix assignment α on $B_1 \cup \cdots \cup B_\ell$ **do**
    $L(x) \leftarrow 0$.
    for each round B_j, and each variable $t \in B_j$ **do**
      Compute the average Δ_t of $H_t^{h,\beta}$ with $x_{B_{<j}} = \alpha_{B_{<j}}$.
      Set $p_t \leftarrow 1$ if $\Delta_t \geq 0$, and $p_t \leftarrow 0$ otherwise.
      if $\alpha_t \neq p_t$ **then**
        $L(x) \leftarrow L(x) + (2p_t - 1)H_t^{h,\beta}(x) - |\beta|$.
      end if
    end for
    for each suffix y with $L(\alpha, y) \leq 0$, by Lemma 2.6 **do**
      Let $q \leftarrow s_0 + F(\alpha, y)$.
      If $q > M$, set $M \leftarrow q$ and $\alpha^\star \leftarrow \alpha \cup y$.
    end for
  end for
end for
return $(M, \alpha^\star)$.

5.4 Correctness

The count guess changes the comparisons, so we must check that a correct guess preserves an optimum. The following lemma accounts for the added slack. This argument is independent of the distribution of F and also justifies the round version used later.

Lemma 5.1 (Correctness of count comparisons)**.** *For every F, every rational β, and every ordered prefix partition,* CountComparisons *returns an optimum score and an assignment attaining it.*

Proof. Fix an optimal complete assignment x^* and its correct count $h = \sum_w x^*_w$. If $x^*_t \neq p_t$, changing just this variable to p_t cannot increase the score, so $(2p_t - 1)\mathrm{gain}_t(x^*) \leq 0$. For the correct count, (19) therefore gives

$$(2p_t - 1)H_t^{h,\beta}(x^*) = (2p_t - 1)\mathrm{gain}_t(x^*) + (2p_t - 1)\beta x^*_t \leq |\beta|.$$

Every comparison on its prefix holds, and hence so does their sum. The corresponding suffix is enumerated in this run. When $\beta = 0$, the comparisons do not depend on h, so the single run also retains x^*. Preprocessing preserves all gains and records its constant score change. Scoring candidates with that constant included proves the claim. □

5.5 Running-time guarantee

The next result makes the correlation requirement precise through the usual eigenvalues of a regular graph. The density restriction ensures that removing the common interaction leaves enough variation.

For a d-regular simple graph G, write A_G for its adjacency matrix. List its eigenvalues with $\lambda_1(A_G) = d$ and retain all multiplicities. Define $\lambda(G) = \max_{i \geq 2} |\lambda_i(A_G)|$.

Corollary 5.2 (Max-Cut on regular graphs)**.** *Fix $\lambda_0 \geq 1$ and $0 < \varepsilon \leq 1/2$. There is $c = c(\lambda_0, \varepsilon) < 2$ such that every d-regular graph satisfying*

$$d \leq (1 - \varepsilon)n, \qquad \lambda(G) \leq \lambda_0\sqrt{d}$$

admits a deterministic polynomial-space Max-Cut algorithm of time $O^*(c^n)$. The same bound holds after adding any multiset of unit clauses to the Max 2-SAT encoding with $(u \vee v)$ and $(\neg u \vee \neg v)$ on each edge.

For $d \geq 64\lambda_0^2$, use Algorithm 6 with $\beta = -2d/(n-1)$, $T = \lfloor n/2 \rfloor$, and two prefix rounds of sizes $\lfloor n/4 \rfloor$ and $T - \lfloor n/4 \rfloor$. For smaller d, branch outside a greedy independent set and optimize its vertices separately. The solver computes no spectral quantities; the eigenvalue condition is used only in the following analysis.

5.6 Proof of the running-time bound

We use a deterministic accumulation estimate for the two-round algorithm. It separates the proof into three checks: a bound on the joint influence of the remaining interactions, enough interaction between the two rounds, and a small total comparison allowance. We state the specialization needed here; Appendix C proves the underlying estimate.

For the chosen β, define $N_{uv} = J_{uv} - \beta$ when $u \neq v$ and $N_{uu} = 0$. Its average squared row size and the contribution from the first round to a vertex in the second are

$$D_N = \frac{1}{n}\sum_{u \neq v} N_{uv}^2, \qquad W_t = \sum_{w \in B_1} N_{tw}^2 \quad (t \in B_2).$$

We write $\|N\| = \sup_{z \neq 0} \|Nz\|_2/\|z\|_2$ for the operator norm, and use the same notation for other matrices. For a symmetric matrix it is the largest absolute eigenvalue. This quantity bounds the combined effect of the interactions on any vector of variable contributions. We also use the Frobenius norm $\|N\|_F = (\sum_{u,v} N_{uv}^2)^{1/2}$. The symbols $\mathbf{1}$ and I denote the all-ones vector and the identity matrix, respectively.

Lemma 5.3 (Accumulation with one guessed count)**.** *Fix $g, K > 0$. Use two prefix rounds of sizes $\lfloor n/4 \rfloor$ and $T - \lfloor n/4 \rfloor$, where $T = \lfloor n/2 \rfloor$. Suppose $D_N > 0$ and*

$$\|N\|^2 \le K D_N, \qquad \sum_{t \in B_2} \sqrt{W_t} \ge 4\sqrt{3}\, gn\sqrt{D_N}, \qquad T|\beta| \le \frac{1}{8} gn\sqrt{D_N}.$$

For sufficiently large n in terms of g, K, CountComparisons *takes polynomial space and $O^*((n+1)(2^{n/2} + 2^n e^{-cn}))$ time, for a constant $c = c(g, K) > 0$. The linear coefficients of the objective may be arbitrary.*

Proof. Apply the two-round case of Theorem C.2 with $\tau = 1/2$, $P = \beta \mathbf{1}\mathbf{1}^\mathsf{T}$, and the exact guesses $h \in \{0, \dots, n\}$. The comparison allowance there is $s_t = |\beta|$. For vertices in the first round, the earlier-round quantity W_t is zero, so the sum in that theorem's gap hypothesis is precisely the sum over B_2 displayed here. The other two displayed assumptions give its norm and allowance bounds. There are at most $n + 1$ guesses. Its enumeration and space conclusions prove the lemma. □

We now verify these conditions for the regular-graph family. The spectral assumption controls $\|N\|$. An edge-count estimate between the two rounds supplies the lower bound on $\sum \sqrt{W_t}$. The allowance is lower order on the resulting scale.

Proof of Corollary 5.2. **1. Handle bounded degree.** If $d < 64\lambda_0^2$, greedily find an independent set of size at least $n/(d+1)$, branch on its complement, and optimize its variables independently. This already gives a uniform fixed saving in this range. Assume henceforth $d \ge 64\lambda_0^2$ and n is sufficiently large in terms of the fixed parameters; finitely many smaller sizes can be absorbed in the constant.

2. Bound the remaining interactions. Apply Lemma 5.3 with two prefix rounds of sizes $\lfloor n/4 \rfloor$ and $\lfloor n/2 \rfloor - \lfloor n/4 \rfloor$ in any order, and

$$J = -2A_G, \quad P = \beta \mathbf{1}\mathbf{1}^\mathsf{T}, \quad \beta = -2d/(n-1), \quad N = -2A_G - \beta(\mathbf{1}\mathbf{1}^\mathsf{T} - I).$$

Use exact counts $0, \dots, n$, so $s_t = |\beta|$. The matrix N annihilates $\mathbf{1}$ and has other eigenvalues $-2\lambda_i(A_G) + \beta$. Since $|\beta| \le 2$,

$$\|N\| \le 3\lambda_0\sqrt{d}, \qquad D_N = 4d(1 - d/(n-1)) \ge 2\varepsilon d$$

for $n \ge 2/\varepsilon$. Here the squared Euclidean norm of each row of N is $4d(1 - d/(n-1))$, so it also equals their average D_N. Thus $K = 9\lambda_0^2/(2\varepsilon)$ suffices.

3. Obtain requirements from the first round. An edge between the two prefix rounds contributes at least ε^2 to W_t. Indeed, its coefficient has absolute value $2(1 - d/(n-1)) \ge \varepsilon$ when $n \ge 2/\varepsilon$. Write $e(B_1, B_2)$ for the number of edges between the rounds, and $\deg_{B_1}(t)$ for the number of neighbors of t in B_1. The expander mixing inequality gives, for $n \ge 80$,

$$e(B_1, B_2) \ge \frac{d|B_1||B_2|}{n} - \lambda(G)\sqrt{|B_1||B_2|} \ge \frac{dn}{32} - \frac{d}{2} \ge \frac{dn}{40}.$$

Indeed $|B_1||B_2| \ge (n/4 - 1)^2$, $\sqrt{|B_1||B_2|} \le n/4$, and $\lambda(G) \le d/8$. The mixing inequality itself follows by writing each indicator vector as its constant component plus a vector perpendicular to $\mathbf{1}$. Specifically, if $z_i = \mathbf{1}_{B_i} - (|B_i|/n)\mathbf{1}$, then

$$e(B_1, B_2) - \frac{d|B_1||B_2|}{n} = z_1^\mathsf{T} A_G z_2, \qquad |z_1^\mathsf{T} A_G z_2| \le \lambda(G)\|z_1\|_2\|z_2\|_2 \le \lambda(G)\sqrt{|B_1||B_2|}.$$

The middle inequality uses the spectral bound on the subspace perpendicular to **1** and the Cauchy–Schwarz inequality. Consequently

$$\sum_{t\in B_2}\sqrt{W_t}\ge\varepsilon\sum_{t\in B_2}\sqrt{\deg_{B_1}(t)}\ge\frac{\varepsilon e(B_1,B_2)}{\sqrt{d}}\ge\frac{\varepsilon n\sqrt{d}}{40}.$$

The middle step uses $\sqrt{a}\ge a/\sqrt{d}$ for $0\le a\le d$ and $\sum_{t\in B_2}\deg_{B_1}(t)=e(B_1,B_2)$. Since $\sqrt{D_N}\le 2\sqrt{d}$, choose $g=\varepsilon/(320\sqrt{3})$.

4. Account for the comparison allowance. Finally $\sum_{t\le T}s_t\le 2d=o(n\sqrt{d})$ uniformly for $d\le n$, so the slack condition holds for all sufficiently large n. There are $n+1$ runs and all theorem parameters are fixed. □

5.7 Concrete families and the transition to random graphs

Paley graphs on $q\equiv 1 \pmod 4$ vertices, for prime powers q, have degree $(q-1)/2$ and nontrivial eigenvalues $(-1\pm\sqrt{q})/2$ [9, Section 9.1.2]. Thus $\lambda_0=1$, $\varepsilon=1/2$ suffice for all sufficiently large q. Connected nonbipartite Ramanujan graphs satisfy $\lambda(G)\le 2\sqrt{d-1}$, so they give another family when the density restriction holds. Bipartite Ramanujan graphs have the additional eigenvalue $-d$ and do not satisfy this hypothesis at growing degree; ordinary Max-Cut on bipartite graphs is of course immediate.

These are examples of the same deterministic theorem. Their graph constructions provide the spectral condition used in its analysis.

There is a parallel interpretation for a random graph. In $G(n,p)$, each pair coefficient $J_{uv}=-2A_{uv}$ has mean $-2p$. Subtracting that mean leaves $-2(A_{uv}-p)$: present edges and absent edges have opposite deviations. When $p=1/2$, these deviations are independent signs of size one. Thus random edge presence can provide the opposing effects that random literal signs supplied in Section 4, once the common interaction has been accounted for. The next section includes $G(n,p)$ as the one-community case and extends the method to community-dependent means.

6 Community-dependent interactions

6.1 Intuition

One total count suffices when all pair interactions share the same systematic part. If the common part depends on two endpoint communities, we instead need the number of ones in each community. With a fixed number of groups, the number of count tuples is still polynomial. Once these contributions have been accounted for, the remaining interactions can accumulate requirements as in the preceding section.

The stochastic block model supplies a natural setting. Edges are sampled independently, conditional on the partition, with probabilities determined by the endpoint groups. There are two tasks: account for the systematic block probabilities, and use the variation in edge presence to control the remaining comparisons. The variance assumptions below concern this second task; they do not require that the communities be easy to identify.

In the theorem, the communities and their probabilities are hidden. Our algorithm does not recover the labels. It computes a small number of directions that account for the large systematic interactions and guesses the projections of an assignment onto them. Polynomially many guesses suffice for a fixed number of communities. Each guess gives adjusted comparisons with an explicit allowance, and at least one guess retains an optimum.

The search after this preprocessing still uses two prefix rounds and enumerates completions of the summed comparisons. Spectral computation is an additional step in this algorithm, rather than only a tool used to analyze it.

6.2 The input model

Fix a partition $V = V_1 \cup \cdots \cup V_k$ and a symmetric probability matrix $\Pi = (\pi_{ab})_{a,b \le k}$. Include each unordered pair of distinct vertices independently, with probability π_{ab} when its endpoints belong to V_a, V_b. This is the stochastic block model [10]. The partition can be arbitrary and need not be balanced. Alternatively, it can be drawn first; the result below holds uniformly conditional on it. The number k is fixed, while the probabilities may depend on n.

Define the smallest and largest edge variances by

$$v_{\min} = \min_{a,b} \pi_{ab}(1 - \pi_{ab}), \qquad v_{\max} = \max_{a,b} \pi_{ab}(1 - \pi_{ab}).$$

These conditions measure the amount of random variation, not how well the communities can be distinguished.

6.3 From one count to community counts

If the partition and rational probabilities of polynomial encoding length are given, their role has an elementary description. Guess the number h_a of vertices assigned 1 in each V_a: there are at most $(n+1)^k$ tuples. For $t \in V_a$, use the adjusted gain

$$H_t^{\boldsymbol{h}}(x) = \mathrm{gain}_t(x) - 2 \sum_{b=1}^{k} \pi_{ab} \left(h_b - \sum_{w \in V_b \setminus \{t\}} x_w \right).$$

On an assignment with these counts it equals $\mathrm{gain}_t(x) - 2\pi_{aa} x_t$, so the comparison allowance is $2\pi_{aa}$. This gives the same type of two-round comparison algorithm, with total allowance at most $2n$. The centered independent entries satisfy the required norm and cross-round mass bounds under (22); this is the proof of Lemma E.1 with the mean supplied and no approximation error. Consequently the same type of fixed exponential saving follows using only group counts and gains. The algorithm below removes the need to supply this information.

6.4 The algorithm for hidden communities

For a graph input, first form its Max-Cut encoding; additional units, if present, are retained. The following procedure takes that formula F, a fixed bound k on the number of communities, and a fixed bound $\chi \ge 1$ on the ratio of the largest to the smallest edge variance. The hidden partition and edge probabilities are not inputs. The output maximizes the formula; subtracting the number of graph edges gives the maximum cut value when no additional units are present.

Record the original variable order and n, and initialize the best score and assignment $M, \alpha^\star$. If $n < 4$, solve the instance by exhaustive search and return. Otherwise, compute the coefficients of the input objective in (18). The matrix $J = -2A_G$ records the graph edges; units affect only the constant and linear coefficients. Compute a rational approximate diagonalization of J and retain at most k directions, as specified in Appendix E. This gives

$$P = \sum_{i=1}^{r} \lambda_i v_i v_i^{\mathsf{T}}, \qquad r \le k, \qquad N = \mathrm{offdiag}(J - P),$$

where offdiag sets the diagonal entries to zero and the v_i are rational orthonormal vectors. Compute $D_N = n^{-1} \sum_{u \ne v} N_{uv}^2$. If $D_N = 0$, use exhaustive search and return before constructing any projection grids.

Next, construct the capped rational grids $\mathcal{Y}_i$ and errors δ_i specified in Appendix E. Writing $\langle v, x \rangle = \sum_t v(t) x_t$, every projection $\langle v_i, x \rangle$ of a Boolean assignment is within δ_i of some point of $\mathcal{Y}_i$. The cap keeps the number of grid tuples polynomial on arbitrary inputs for fixed k. If

no direction is retained, the product of grids contains one empty tuple and the corresponding sums are zero. Compute the comparison allowances

$$s_t = \sum_{i=1}^{r} |\lambda_i| \, |v_i(t)| \big(\delta_i + |v_i(t)|\big). \tag{20}$$

These remain fixed across all guesses.

In the recorded variable order, let B_1 contain the first $\lfloor n/4 \rfloor$ variables and B_2 the next $T - \lfloor n/4 \rfloor$, where $T = \lfloor n/2 \rfloor$. The remaining variables form the suffix. Process the projection tuples $\hat{y} \in \mathcal{Y}_1 \times \cdots \times \mathcal{Y}_r$ consecutively. For the current tuple, use the adjusted gain

$$H_t^{\hat{y}}(x) = a_t + \sum_{i=1}^{r} \lambda_i \hat{y}_i v_i(t) + \sum_{w \neq t} N_{tw} x_w. \tag{21}$$

This gain and s_t are the projection counterparts of (19) and its allowance $|\beta|$.

For each tuple, enumerate all assignments α to $B_1 \cup B_2$. Initialize a separate sum $L(x) = 0$ for this tuple and prefix, then process B_1 followed by B_2. At a variable $t \in B_j$, compute the average Δ_t of $H_t^{\hat{y}}$ using α on earlier rounds and substituting $1/2$ for all other variables. Set $p_t = 1$ if $\Delta_t \geq 0$, and $p_t = 0$ otherwise. If $\alpha_t \neq p_t$, add

$$(2p_t - 1) H_t^{\hat{y}}(x) \leq s_t.$$

As in CountComparisons, L stores the sum of left-hand sides minus right-hand sides.

After both rounds, enumerate suffixes y satisfying $L(\alpha, y) \leq 0$ using Lemma 2.6. Evaluate each complete assignment in the original formula and update $M, \alpha^\star$ if its score is larger. Retain these best values across all prefixes and tuples, and return them once all runs finish.

Algorithm 7 CommunityComparisons(F, k, χ)

Record the original variable order and n.
$M \leftarrow -\infty$; $\alpha^\star \leftarrow \emptyset$.
if $n < 4$ **then**
  return the best score and assignment found by exhaustive search.
end if
Compute a, J, c in (18).
Construct P, N by the approximate diagonalization in Appendix E. *// This polynomial computation uses J, k, χ, not the hidden partition.*
Compute $D_N = n^{-1} \sum_{u \neq v} N_{uv}^2$.
if $D_N = 0$ **then**
  return the best score and assignment found by exhaustive search.
end if
Construct the capped projection grids and allowances by Appendix E.
Fix the two prefix rounds B_1, B_2 described above.
for each projection tuple $\hat{y} \in \mathcal{Y}_1 \times \cdots \times \mathcal{Y}_r$ **do**
  for each prefix assignment α on $B_1 \cup B_2$ **do**
    $L(x) \leftarrow 0$.
    for each round B_j and each $t \in B_j$ **do**
      Compute the average Δ_t of $H_t^{\hat{y}}$ using α on earlier rounds.
      Set $p_t \leftarrow 1$ if $\Delta_t \geq 0$, and $p_t \leftarrow 0$ otherwise.
      if $\alpha_t \neq p_t$ **then**
        $L(x) \leftarrow L(x) + (2p_t - 1)H_t^{\hat{y}}(x) - s_t$.
      end if
    end for
    for each suffix y satisfying $L(\alpha, y) \leq 0$, by Lemma 2.6 **do**
      Evaluate $F(\alpha, y)$; update $M, \alpha^\star$ if this score is larger.
    end for
  end for
end for
return $(M, \alpha^\star)$.

All loops are streamed in polynomial space. The comparisons use the rational directions actually computed, so no exact-real arithmetic is assumed.

6.5 Correctness

The algorithm may consider candidates inconsistent with a guessed projection, just as the count algorithm may consider candidates with a different number of ones. Scoring them in the original formula is harmless. What matters is that one run retains an optimum.

Lemma 6.1 (Correctness with hidden communities)**.** CommunityComparisons *returns an optimum on every input, independently of whether it was generated by the stated model.*

Proof. The exhaustive-search cases are exact. Otherwise fix an optimal assignment x^* and choose a tuple $\hat{y}$ within the grid errors of its projections. For any variable t, direct subtraction of the original and adjusted gains gives

$$\mathrm{gain}_t(x^*) - H_t^{\hat{y}}(x^*) = \sum_i \lambda_i v_i(t)(\langle v_i, x^* \rangle - \hat{y}_i - v_i(t)x_t^*).$$

Its absolute value is at most s_t by (20). If the optimum takes the nonpreferred value at t, changing it to p_t cannot improve its score, so $(2p_t - 1)\mathrm{gain}_t(x^*) \leq 0$. Therefore $(2p_t - 1)H_t^{\hat{y}}(x^*) \leq$

s_t. Every comparison at its prefix, and hence their sum, is satisfied. The suffix of x^* is enumerated in this run. Every reported score is evaluated in the original formula, which proves the claim. □

6.6 Running-time guarantee

The theorem requires a fixed number of communities, comparable nonzero edge variances, and enough total variation. A binary probability matrix with singleton communities can represent any graph, but violates these assumptions. The algorithm receives only the observed graph and the fixed class parameters stated below.

Theorem 6.2 (Exact Max-Cut on the stochastic block model)**.** *Fix $k \geq 1$ and $\chi \geq 1$. There are constants $C = C(k, \chi)$ and $\gamma = \gamma(k, \chi) > 0$ such that, whenever*

$$0 < v_{\min}, \qquad v_{\max} \leq \chi v_{\min}, \qquad n v_{\min} \geq C \log n, \tag{22}$$

Max-Cut on a graph from this model can be solved by a deterministic polynomial-space exact algorithm taking $O^*(2^{(1-\gamma)n})$ time with probability $1 - o(1)$. The algorithm is given the fixed class parameters k, χ, but neither the partition nor the probabilities π_{ab}. The same statement holds with arbitrary additional unit clauses, even chosen after the graph is drawn. Exactness holds on every input; only the time bound is probabilistic.

6.7 Proof of the running-time bound

There are two estimates to establish. First, the systematic matrix of expected interactions has rank at most the number of communities. Second, independent edge variation leaves enough interaction between the two prefix rounds while keeping the norm of the centered matrix under control. The discovery lemma in Appendix E shows that computing the retained directions preserves these properties and gives projection grids with polynomially many points.

The following verification identifies its parameters explicitly. The probability event depends only on the graph, and its accumulation bound is uniform over all linear coefficients. This is why additional unit clauses may be chosen after the graph is known.

Proof of Theorem 6.2. Use the algorithm described above. Its running time follows once we verify the discovery lemma in Appendix E. In the Max 2-SAT encoding, $J_{uv} = -2A_{uv}$ for the adjacency indicators A_{uv}. Conditional on the partition, these coefficients are independent, with

$$\mathbb{E} J_{uv} = -2\pi_{ab}, \qquad \operatorname{Var} J_{uv} = 4\pi_{ab}(1 - \pi_{ab}), \qquad |J_{uv} - \mathbb{E} J_{uv}| \leq 2.$$

Let $Z_{ua} = [u \in V_a]$. The matrix $\bar{A} = -2Z\Pi Z^{\mathsf{T}}$ agrees with the means off the diagonal, has rank at most k, has diagonal entries of absolute value at most 2, and satisfies $\|\bar{A}\| \leq 2n$ by its maximum absolute row sum. In Lemma E.1, take

$$r = k, \quad \nu = 4v_{\min}, \quad B = B_0 = \mu = 2.$$

Its threshold becomes $4nv_{\min} \geq C_0(4 \log n + 8)$, which follows from (22) after increasing C. The lemma's algorithm does not use $\bar{A}$ or its probabilistic parameters. Its good event depends only on the pair coefficients and its bound is uniform over linear fields, proving the assertion about units. □

6.8 The usual within-community and between-community probabilities

When $\pi_{aa} = p$ and $\pi_{ab} = q$ for $a \neq b$, the assumptions reduce to

$$\max\{p(1-p), q(1-q)\} \leq \chi \min\{p(1-p), q(1-q)\}, \qquad n \min\{p(1-p), q(1-q)\} \geq C \log n.$$

No separation between p and q is required; in particular $p = q$ is allowed. Concrete regimes are:

- *Dense blocks:* all $\pi_{ab} \in [\delta, 1-\delta]$ for a fixed $0 < \delta \leq 1/2$. The hypotheses hold for sufficiently large n, with constants depending only on k, δ.
- *Sparse blocks:* $\pi_{ab} = c_{ab}\rho$ with fixed $0 < a \leq c_{ab} \leq b$, $\rho = o(1)$, and $n\rho \geq C' \log n$.
- *Almost complete blocks:* $\pi_{ab} = 1 - c_{ab}\rho$ with the same bounds on c_{ab} and ρ.

For the last two regimes, eventually $a\rho/2 \leq \pi_{ab}(1-\pi_{ab}) \leq b\rho$; one can take $\chi = 2b/a$ and increase C'. The saving is fixed throughout each regime.

7 Formal verification

The accompanying Lean 4 artifact formalizes the common score identities, pruning constraints, their arithmetic checker, and the literal-gap algorithm of Section 3. The paper and the formalization use the same fixed initial preferences and the same choice of the branching set. In particular, the verified algorithm enumerates completions of the sum, including completions that violate individual constraints.

The checked results include the simultaneous-optimum argument in Lemma 3.1, the expectation and influence estimates in Lemma 3.3, the candidate count in Lemma 3.4, and the concentration inequality in Appendix A. For Theorem 3.2, Lean proves correctness on the original input after preprocessing and the explicit bound $(4 + 2n)2^{(1-\gamma)n}$ on the search nodes. It also proves bounds on recursion depth and the sizes of the constraint representations. For Corollary 3.5, the formalization additionally proves that preprocessing preserves effective gaps and does not increase occurrence counts, that simplicity bounds each initial occurrence count by $4(n-1)+2$, and that these facts imply the stated candidate and search-node bounds. Simplicity identifies binary clauses whose literals are written in opposite orders; repeated units created by preprocessing are permitted in the reduced formula. The final polynomial bit-overhead and space analysis uses the ordinary implementation argument given in the proof; it is not a formal machine-cost or compiler verification.

The deterministic correctness statement in Lemma 4.1 is also formalized. The verified procedure computes its observed support, variable order, rational weights, and stopping depth from the formula alone. The proof includes independent optimization of variables occurring only in unit clauses, score offsets under substitution and preprocessing, the earliest-optimum argument with changing preferences, and exact enumeration of the weighted sum. It covers repeated clauses, empty support, and the case of zero variables.

In this formal implementation, a bit vector and a list of unassigned variables represent a partial assignment. Residual formulas are recomputed from the fixed preprocessed formula when needed; inherited constraints retain the bounds they had when created, and assigned values are substituted when the weighted sum is tested. The proved score and minimum identities justify these representations. The executable search streams the candidates and keeps a best assignment; the full decision tree and output lists used in the proofs are not constructed by it.

The artifact includes a correspondence record for every numbered result and proposed theorem, with its precise verification status and Lean declarations where available. The

probabilistic running-time guarantees for random signs and the regular-graph and stochastic-block-model results remain unverified. The proposed extension in Appendix F has neither a proof in this paper nor a Lean proof. This record distinguishes proved formal statements from future targets; it does not treat a proof of a conditional intermediate statement as a verification of its unproved hypotheses. Supporting Lean lemmas implement or justify statements and procedures retained in this paper.

8 Concluding discussion

The selected families illustrate several ways to make comparisons accumulate. Relative literal bias supplies large individual requirements. Random signs make weaker normalized requirements useful despite shared neighborhoods. Assignment counts and projection guesses account for systematic interactions before the remaining comparisons are added. In each case, a bound on collective compensation converts the accumulated requirements into a fixed exponential saving with polynomial space.

A central theoretical question is how to exploit instances whose comparisons remain strongly correlated after these adjustments. Such correlation may reveal additional structure that can be summarized by few assignment statistics, but the present results do not establish a general dichotomy. Extending the structural guarantees and identifying application-driven classes are directions for further work.

A A concentration estimate for the literal-gap analysis

The randomness in this appendix is a uniform Boolean assignment used to count candidates of a deterministic algorithm. The input formula is fixed. We give a conservative bounded-differences estimate with a short finite proof. It is the sole probability inequality used in Lemma 3.4.

Lemma A.1 (Bounded differences on uniform Boolean assignments)**.** *Let $f : \{0,1\}^n \to \mathbb{R}$, and let $c_1, \dots, c_n \geq 0$ be constants. Suppose that changing only coordinate i changes f by at most c_i. Put $V = \sum_{i=1}^n c_i^2$, and assume $V > 0$. For a uniform Boolean assignment x and every $a \geq 0$,*

$$\mathbb{P}(f(x) \leq \mathbb{E}f - a) \leq \exp(-a^2/(2V)).$$

Proof. We first prove by induction on n that, for every real t,

$$\mathbb{E}e^{t(f-\mathbb{E}f)} \leq e^{t^2V/2}. \tag{23}$$

The claim also permits $V = 0$ at this intermediate step. For $n = 0$, f is constant and both sides are one.

For the induction step, write f_0, f_1 for the restrictions obtained by fixing the first bit to zero and one. Let $\mu_b = \mathbb{E}f_b$ and $\mu = (\mu_0 + \mu_1)/2 = \mathbb{E}f$. Since $|f_0(y) - f_1(y)| \leq c_1$ for every assignment y of the remaining bits, averaging gives $|\mu_0 - \mu_1| \leq c_1$. Each restriction satisfies the same coordinate bounds $c_2, \dots, c_n$. Applying the induction hypothesis to both gives

$$\begin{aligned}
\mathbb{E}e^{t(f-\mu)} &= \frac{1}{2} \sum_{b\in\{0,1\}} e^{t(\mu_b-\mu)} \mathbb{E}e^{t(f_b-\mu_b)} \\
&\leq \exp\left(\frac{t^2}{2}\sum_{i=2}^n c_i^2\right) \frac{e^{t(\mu_0-\mu_1)/2} + e^{-t(\mu_0-\mu_1)/2}}{2} \\
&\leq \exp\left(\frac{t^2}{2}\sum_{i=2}^n c_i^2 + \frac{t^2c_1^2}{8}\right) \leq e^{t^2V/2}.
\end{aligned}$$

For the second inequality we used $(e^z + e^{-z})/2 \le e^{z^2/2}$. This follows by comparing their power series, since $(2j)! \ge 2^j j!$ for every integer $j \ge 0$. This proves (23).

Finally let $t = a/V \ge 0$. On the event $f \le \mathbb{E}f - a$, $e^{-t(f-\mathbb{E}f)} \ge e^{ta}$. Averaging this pointwise bound and applying (23) with $-t$ yields

$$\mathbb{P}(f \le \mathbb{E}f - a)e^{ta} \le \mathbb{E}e^{-t(f-\mathbb{E}f)} \le e^{t^2V/2}.$$

Divide by e^{ta} and substitute $t = a/V$ to obtain $e^{-ta+t^2V/2} = e^{-a^2/(2V)}$. The calculation includes $a = 0$. □

B Supporting estimates for symmetric random signs

The main text states the result for two familiar sampling models. For the proof, it is convenient to work with a single independent-pair condition encompassing both. The conditioning, moment, and concentration lemmas in this appendix supply the estimates used in Theorem 4.2.

Definition B.1 (Complementation-invariant random signs)**.** Fix constants $m_0 \ge 1$ and $0 < \kappa \le m_0^2$, a set of n input variables, and any set E of unordered pairs of distinct input variables. Let $V = \bigcup_{e\in E} e$ and $G = (V, E)$. For each edge $e = \{u, v\}$ draw a multiset M_e of binary clauses on u, v, independently over the edges. The binary part of F is the multiset union of these M_e; pairs outside E contribute no binary clauses. A sampled M_e may be empty, so the observed graph G_F in (14) may have fewer edges than G. Assume that

1. $|M_e| \le m_0$;
2. complementing the literal of either endpoint in every clause of M_e leaves its distribution unchanged;
3. for each endpoint u,
$$\mathbb{E}\left[\left(\sum_{c\in M_e} s_u(c)\right)^2\right] \ge \kappa,$$
where $s_u(c) = 1$ if the literal of u in c is positive and $s_u(c) = -1$ otherwise.

Add any multiset of unit clauses on the input variables, fixed independently of these draws.

The last condition requires some variation in the difference between positive and negative occurrences at an endpoint. One uniformly signed clause per edge has $m_0 = \kappa = 1$. Including each of the four clauses independently with probability $q \in (0, 1)$ has $m_0 = 4$ and $\kappa = 4q(1-q)$. In particular, $q = 1/4$ gives the independent-clause model discussed in the introduction.

Theorem B.2 (Random signs on every graph)**.** *Fix $m_0 \ge 1$ and $0 < \kappa \le m_0^2$. For a formula F on n variables drawn according to Definition B.1 with any fixed generating graph G, an optimal assignment can be computed from F alone by a deterministic polynomial-space algorithm with expected running time*

$$O^*(2^{n/2} + 2^n e^{-c_0 n}), \qquad c_0 = \frac{c_1^2}{10816 m_0^2}, \qquad c_1 = \frac{\sqrt{\kappa}}{2\sqrt{1 + 4m_0^4/\kappa^2}}.$$

With probability at least $1 - 3e^{-c_0 n/2}$, its running time is $O^*(2^n e^{-c_0 n/2})$. The algorithm returns an optimum on every input; the expectations and probabilities refer only to the random input formula.

Proof. Use the proof of Theorem 4.2 with the present values of m_0, κ, c_1, c_0. The lemmas below are stated and proved for this general model. They give the same three exceptional-event estimates and hence $\mathbb{P}(A_T + Q_T \le 0 \mid G_F = H) \le 3e^{-c_0|V(H)|}$. The enumeration count, averaging over the observed graph, and the final Markov bound are unchanged. The prefix work remains $O^*(2^{n/2})$. All pair-law assumptions used by that argument are precisely the three conditions in Definition B.1. □

The algorithm does not know which pairs were available for sampling. The next lemma justifies analyzing it after fixing the graph it actually observes. Crucially, whether a pair is empty does not distinguish between the literal polarities.

Lemma B.3 (Conditioning on the observed pairs)**.** *Suppose F is generated according to Definition B.1. Conditional on any observed graph $G_F = H$ of positive probability, the clause multisets on its edges are independent. Each has its original distribution conditioned on being nonempty, and satisfies all three conditions of that definition with the same m_0 and κ.*

Proof. The event $G_F = H$ requires $M_e \neq \emptyset$ for each edge of H and $M_e = \emptyset$ for every other edge of the generating graph. These events concern separate independent draws. Conditioning on them therefore preserves independence, and conditions each retained pair only on its own nonemptiness. The clause-count bound remains m_0.

Complementing either endpoint does not change whether a multiset is empty. Its conditional distribution is consequently still invariant under either complementation. Finally, put $Z_{u,e} = \sum_{c \in M_e} s_u(c)$ and $p_e = \mathbb{P}(M_e \neq \emptyset)$. An empty multiset contributes zero to $Z_{u,e}^2$, so for every retained edge

$$\mathbb{E}[Z_{u,e}^2 \mid M_e \neq \emptyset] = \frac{\mathbb{E}Z_{u,e}^2}{p_e} \ge \kappa.$$

The unit clauses were fixed independently of the pair draws and remain fixed under this conditioning. This proves the claim. □

For the probability estimates below, fix a nonempty observed graph $G_F = H = (V_H, E_H)$ and put $r = |V_H|$. All probabilities and expectations refer to the conditional model in Lemma B.3. We identify the variables with their positions $1, \dots, r$ in U when writing edges and neighbors.

The next lemma identifies the randomness available when a constraint is created and when a later variable is assigned. It is the reason that overlapping constraints can be analyzed without treating them as independent. We use the original sampled clauses in this analysis, since preprocessing preserves all gains.

Let b_t be the number of original units (x_t) minus the number of units $(\neg x_t)$. For an edge $\{t, v\}$, define its contribution to the gain at t by

$$G_{tv}(x_v) = \sum_{\substack{c \in M_{\{t,v\}} \\ \text{the literal on } v \text{ is false}}} s_t(c).$$

A clause contributes its sign at t exactly when its partner literal is false. Thus

$$\begin{aligned} \mathrm{gain}_t(x) &= b_t + \sum_{v \sim t} G_{tv}(x_v), \\ \Delta_t &= b_t + \sum_{\substack{v < t \\ v \sim t}} G_{tv}(x_v) + \frac{1}{2} \sum_{\substack{v > t \\ v \sim t}} \sum_{c \in M_{\{t,v\}}} s_t(c). \end{aligned}$$

Write $d_t = \deg_H(\mathbf{u}_t)$.

Lemma B.4 (Revealing the endpoint signs)**.** *The random formula and the independent uniform assignment can be exposed in variable order so that, just before the signs at variable t are revealed,*

$$\Delta_t = b_t + \sum_{v \sim t} \rho_{t,\{t,v\}} a_{tv}, \qquad Y_t = \sum_{v \sim t} a_{tv}^2 \le m_0^2 d_t.$$

The coefficients a_{tv} are already known, and the signs $\rho_{t,\{t,v\}}$ are independent fair signs. After they are revealed, x_t is still a fair bit independent of Δ_t. For each edge $\{t,v\}$ with $t < v$, the later deviation has the form

$$G_{tv}(x_v) - \frac{1}{2} \sum_{c \in M_{\{t,v\}}} s_t(c) = \rho_{t,\{t,v\}} \eta_{tv} \theta_{v,\{t,v\}}, \qquad |\eta_{tv}| \le m_0/2.$$

Here η_{tv} is known from the start. The signs $\theta_{v,\{t,v\}}$ are fresh independent fair signs when endpoint v is reached, conditional on all earlier exposed information.

Proof. For each edge e, first draw an independent base multiset K_e with the prescribed law of M_e. Write $\sigma_u(c)$ for an endpoint sign in this base multiset. Independently draw a fair sign $\rho_{u,e}$ for each endpoint of each edge. Obtain M_e by replacing its endpoint signs by $\rho_{u,e}\sigma_u(c)$. Complementation invariance implies that the result has the required distribution, independently on different edges.

Draw the uniform assignment independently and put $\theta_{u,e} = \rho_{u,e}(2x_u - 1)$. Conditional on any assignment x, the transformation from the ρ signs to the θ signs preserves their independent fair distribution. Consequently all the θ signs are mutually independent and independent of x and of the base multisets. A partner literal on v is false precisely when $\sigma_v(c)\theta_{v,e} = -1$.

Reveal all K_e first. At step t, reveal the signs $\rho_{t,e}$ on edges incident to t, followed by x_t. Let $\mathcal{H}_t$ be the information after this step. For $e = \{t,v\}$ set

$$a_{tv} = \begin{cases} \displaystyle\sum_{\substack{c \in K_e \\ \sigma_v(c)\theta_{v,e} = -1}} \sigma_t(c), & v < t, \\ \displaystyle\frac{1}{2} \sum_{c \in K_e} \sigma_t(c), & v > t. \end{cases}$$

These coefficients are determined by $\mathcal{H}_{t-1}$. Multiplying them by $\rho_{t,e}$ gives precisely the earlier-pair contributions or the average later-pair contributions to Δ_t. This proves its representation. The conditional variance of the signed sum is Y_t, because the new signs are independent and have mean zero. Also $|a_{tv}| \le m_0$, proving the upper bound on Y_t.

For $t < v$ define

$$\eta_{tv} = \sum_{\substack{c \in K_e \\ \sigma_v(c) = -1}} \sigma_t(c) - \frac{1}{2} \sum_{c \in K_e} \sigma_t(c).$$

This is half the difference of the signed sums over the two partner polarities, so $|\eta_{tv}| \le |K_e|/2 \le m_0/2$. If $\theta_{v,e} = 1$, the first sum selects the false partner literals; if $\theta_{v,e} = -1$, their complementary set is selected. Subtracting the average gives the asserted deviation with opposite signs in these two cases. The θ signs at v are jointly independent and fair conditional on $\mathcal{H}_{v-1}$, as required. □

We will apply the following probability estimate both to sequential choices and to functions of the independent edge data. Its interval form gives the constants used in Step 2 of the main proof.

Lemma B.5 (Conditional ranges and bounded differences)**.** *Let $X_1, \dots, X_k$ be exposed in order, and let $\mathcal{H}_j$ denote the information after step j. Conditional on the earlier information, suppose X_j lies in an interval of length ℓ_j, where the interval is known before X_j is revealed. If $\sum_j \ell_j^2 \le B$ on every path for a deterministic $B > 0$, then, for $a > 0$,*

$$\mathbb{P}\left(\sum_{j=1}^{k}(X_j - \mathbb{E}[X_j \mid \mathcal{H}_{j-1}]) < -a\right) \le e^{-2a^2/B}.$$

In particular, if f is a function of independent inputs and changing input j changes f by at most c_j, with $\sum_j c_j^2 > 0$, then

$$\mathbb{P}(f < \mathbb{E}f - a) \le e^{-2a^2/\sum_j c_j^2}.$$

If all c_j are zero, f is constant and this probability is zero.

Proof. A centered random variable Z supported on an interval of length ℓ satisfies $\mathbb{E}e^{\lambda Z} \le e^{\lambda^2\ell^2/8}$. To see this, let $\psi(\lambda) = \log \mathbb{E}e^{\lambda Z}$. Then $\psi(0) = \psi'(0) = 0$, and $\psi''(\lambda)$ is the variance under the distribution that reweights each outcome by $e^{\lambda Z}$. This distribution has the same support. Every random variable in an interval of length ℓ has variance at most $\ell^2/4$: subtract the midpoint, bound the second moment by $\ell^2/4$, and use that variance is no larger than this second moment. Integrating the bound on ψ'' twice proves the exponential estimate.

Apply it conditionally at each step, with either sign of λ. Successive conditional expectations and the bound on the sum of squared interval lengths give

$$\mathbb{P}\left(\sum_{j}(X_j - \mathbb{E}[X_j \mid \mathcal{H}_{j-1}]) < -a\right) \le \exp(-\lambda a + \lambda^2 B/8).$$

Taking $\lambda = 4a/B$ proves the first assertion. For the second assertion, reveal the independent inputs one at a time and consider the successive conditional expectations of f. Their increments have conditional mean zero and conditional range at most c_j. Indeed, two possible values of input j change f by at most c_j for every fixed choice of the remaining inputs, and hence also after averaging those inputs. The first assertion applies. □

An average gain may include an arbitrary unit-clause contribution. The next lemma shows that such a shift cannot remove the useful absolute fluctuations of a symmetric signed sum. Its second assertion converts a variance estimate into the average gap needed below.

Lemma B.6 (Absolute gains and second moments)**.** *Let $Z = \sum_i a_i\rho_i$ for independent fair signs ρ_i, and put $Y = \sum_i a_i^2$. For every real b and every $K > 0$,*

$$\mathbb{E}\min\{|b + Z|, K\} \ge \frac{1}{2}\left(\sqrt{Y/3} - \frac{Y}{4K}\right).$$

For any nonnegative random variable U with $\mathbb{E}U > 0$ and finite second moment,

$$\mathbb{E}\sqrt{U} \ge \frac{(\mathbb{E}U)^{3/2}}{(\mathbb{E}U^2)^{1/2}}.$$

Proof. Independence and zero means give $\mathbb{E}Z^2 = Y$ and

$$\mathbb{E}Z^4 = \sum_i a_i^4 + 6\sum_{i<j} a_i^2 a_j^2 \le 3Y^2.$$

The Hölder inequality, with exponents 3/2 and 3, gives

$$\mathbb{E}|Z|^2 = \mathbb{E}(|Z|^{2/3}|Z|^{4/3}) \le (\mathbb{E}|Z|)^{2/3}(\mathbb{E}|Z|^4)^{1/3}.$$

Rearranging yields $\mathbb{E}|Z| \ge \sqrt{Y/3}$ when $Y > 0$; the claim is immediate when $Y = 0$. Write $r_+ = \max\{r, 0\}$. Then $(z - K)_+ \le z^2/(4K)$ for $z \ge 0$, because for $z > K$ the inequality is equivalent to $(z - 2K)^2 \ge 0$. It follows that

$$\mathbb{E}\min\{|Z|, K\} \ge \sqrt{Y/3} - Y/(4K).$$

The triangle inequality gives $|b + z| + |b - z| \ge 2|z|$. After truncation this implies $\min\{|b + z|, K\} + \min\{|b - z|, K\} \ge \min\{|z|, K\}$. Symmetry of Z makes the two expectations on the left equal, proving the first assertion.

For the second assertion, apply the same Hölder inequality to $(\sqrt{U})^{2/3}U^{2/3}$:

$$\mathbb{E}U \le (\mathbb{E}\sqrt{U})^{2/3}(\mathbb{E}U^2)^{1/3}.$$

Rearranging proves the claim. □

We can now bound the accumulated requirements A_T in the main proof. There are two sources of variation: the requirement at an individual branching step, and the amount of conditional variance available across the selected variables. The two terms in the following bound account for these separately.

Lemma B.7 (Accumulated requirements)**.** *Use A_T, T, r from the proof of Theorem 4.2, with c_1 and the pair-law parameters from Theorem B.2. Then for all $a, b > 0$,*

$$\mathbb{P}\left(A_T < \frac{c_1 T}{26} - a - b\right) \le e^{-2a^2/(Tm_0^2)} + e^{-169b^2/(m_0^2 r)}.$$

Proof. Use the exposure of Lemma B.4.

1. A lower bound at each step. Put

$$\widetilde{X}_t = [t \in I]\,\omega_t \min\{|\Delta_t|, m_0\sqrt{d_t}\}.$$

Here $[t \in I]$ is one when a constraint is created at step t, and zero otherwise. Thus $0 \le \widetilde{X}_t \le m_0$ and $A_T \ge \sum_{t \le T} \widetilde{X}_t$. Conditional on $\mathcal{H}_{t-1}$, the gain is the fixed shift b_t plus a symmetric signed sum of variance Y_t. The bit x_t is independent of this gain and chooses the nonpreferred value with probability one half. Lemma B.6 gives

$$\begin{aligned}\mathbb{E}[\widetilde{X}_t \mid \mathcal{H}_{t-1}] &\ge \frac{\omega_t}{4}\left(\sqrt{Y_t/3} - \frac{Y_t}{4m_0\sqrt{d_t}}\right) \\ &\ge \frac{\omega_t\sqrt{Y_t}}{4}\left(\frac{1}{\sqrt{3}} - \frac{1}{4}\right) \ge \mu_t := \frac{\omega_t\sqrt{Y_t}}{13}.\end{aligned}$$

The middle inequality uses $Y_t \le m_0^2 d_t$. Lemma B.5, with interval lengths m_0, therefore gives

$$\mathbb{P}\left(A_T < \sum_{t \le T} \mu_t - a\right) \le e^{-2a^2/(Tm_0^2)}.$$

2. The average available variance. For an earlier neighbor $v < t$, condition on the base multiset and let q_+ and q_- be its signed sums at t over the two polarities at v. The coefficient a_{tv} takes these two values with equal probabilities. Thus

$$\mathbb{E}[a_{tv}^2 \mid K_{\{t,v\}}] = \frac{q_+^2 + q_-^2}{2} \ge \frac{(q_+ + q_-)^2}{4}.$$

Averaging and applying the model's third condition gives $\mathbb{E}a_{tv}^2 \geq \kappa/4$. For a later neighbor, a_{tv} is half the endpoint signed sum, giving the same lower bound directly. The terms of $Y_t = \sum_{v\sim t} a_{tv}^2$ depend on independent edge data, and each lies in $[0, m_0^2]$. Consequently

$$\mathbb{E}Y_t \geq \frac{\kappa d_t}{4}, \qquad \mathrm{Var}(Y_t) \leq \frac{m_0^4 d_t}{4}.$$

By Lemma B.6,

$$\begin{aligned}\mathbb{E}\sqrt{Y_t} &\geq \frac{\sqrt{\mathbb{E}Y_t}}{\sqrt{1+\mathrm{Var}(Y_t)/(\mathbb{E}Y_t)^2}} \\ &\geq \frac{\sqrt{\kappa d_t}/2}{\sqrt{1+4m_0^4/(\kappa^2 d_t)}} \geq c_1\sqrt{d_t}.\end{aligned}$$

We used $d_t \geq 1$ in the last step. The lower weight bound (16) now implies $\mathbb{E}\sum_{t\leq T}\mu_t \geq c_1 T/26$.

3. Concentration over the edge data. Regard each base multiset and its two θ signs as one independent edge input. Changing the input on $\{u, v\}$ affects only the terms μ_u, μ_v that belong to the prefix. In each affected square root, only one squared coefficient changes, with absolute coefficient in $[0, m_0]$. For $R \geq 0$ and $a, b \in [0, m_0]$, $|\sqrt{R+a^2} - \sqrt{R+b^2}| \leq |a-b| \leq m_0$. Thus an edge changes the sum by at most $m_0(\omega_u + \omega_v)/13$. The sum of squared change bounds is at most

$$\frac{m_0^2}{169}\sum_{\{u,v\}\in E_H}(\omega_u+\omega_v)^2 \leq \frac{2m_0^2}{169}\sum_v \omega_v^2 d_v \leq \frac{2m_0^2 r}{169}.$$

Lemma B.5 gives

$$\mathbb{P}\left(\sum_{t\leq T}\mu_t < c_1 T/26 - b\right) \leq e^{-169b^2/(m_0^2 r)}.$$

Combining this with the bound from the first step proves the lemma. □

The last estimate controls how much the later values can help satisfy the accumulated constraints. A shared variable may affect many constraints, but the relevant endpoint signs on its different edges are still independent when that variable is reached. This is the estimate for Q_T used in Step 2 of the main proof.

Lemma B.8 (Favorable contributions from later values)**.** *For every $c > 0$,*

$$\mathbb{P}(Q_T < -c) \leq e^{-2c^2/(m_0^2 T)}.$$

Proof. By Lemma B.4, the contribution from $\{t, v\}$, where $t \leq T$ and $t < v$, is

$$[t \in I]\,\omega_t(2p_t - 1)\rho_{t,\{t,v\}}\eta_{tv}\theta_{v,\{t,v\}}.$$

Order these terms by their later endpoint v. Their coefficients are known before step v, while the θ signs at v are conditionally independent fair signs. We may reveal these signs one at a time and then reveal x_v; the corresponding $\rho_{v,e}$ are then determined. This is equivalent to the earlier exposure and gives a conditional mean-zero increment for each displayed term.

Its conditional range has length at most $\omega_t m_0$. The sum of squared range lengths is bounded by

$$m_0^2\sum_{t\leq T}\omega_t^2|\{v > t : \{t, v\} \in E_H\}| \leq m_0^2\sum_{t\leq T}\omega_t^2 d_t \leq m_0^2 T.$$

Lemma B.5 proves the claim. This argument does not require independence between A_T and Q_T. □

C Analysis of accumulated comparisons

This appendix supplies the count and projection analysis used in Sections 5 and 6. The direct random-sign argument in Section 4 has its own estimates. It also specifies the projection comparison routine used for hidden communities. A few aggregate guesses account for systematic interactions; the remaining comparisons accumulate enough gap while a norm bound controls their combined fluctuation. The matrix formulation is proof machinery for these input families, rather than an additional class definition required of the reader.

C.1 One comparison algorithm

The comparison routine receives the objective (18), a rational representation $P = \sum_{k=1}^{r} \lambda_k v_k v_k^{\mathsf{T}}$ of polynomial encoding length, and finite rational grids $\mathcal{Y}_k$ with stated errors $\delta_k \geq 0$. Each grid must approximate every $\langle v_k, x \rangle$ to within δ_k. Fix the variable order and partition its first $T = \lfloor \tau n \rfloor$ variables into consecutive rounds $B_1, \ldots, B_\ell$, where $0 < \tau < 1$. Treat the suffix as round $\ell + 1$ and write $\rho(t)$ for the round containing t.

Compute $N = \operatorname{offdiag}(J - P)$ and the fixed allowances

$$s_t = \sum_k |\lambda_k| \, |v_k(t)|(\delta_k + |v_k(t)|), \qquad \mathcal{Y} = \prod_k \mathcal{Y}_k.$$

Initialize the best original score and assignment. Process the tuples $\hat{y} \in \mathcal{Y}$ consecutively; the grid description and each point have polynomial size, and the tuples are streamed. For the current tuple, define

$$a^{\hat{y}} = a + \sum_k \lambda_k \hat{y}_k v_k, \qquad F'_{\hat{y}}(x) = c + \langle a^{\hat{y}}, x \rangle + \sum_{u<v} N_{uv} x_u x_v.$$

For each tuple, enumerate all assignments to the prefix and process the rounds of the current prefix in order. For $t \in B_j$, compute

$$\Delta_t = a_t^{\hat{y}} + \sum_{w:\rho(w)<j} N_{tw} x_w + \frac{1}{2} \sum_{w \neq t:\rho(w)\geq j} N_{tw}.$$

Set $p_t = 1$ if $\Delta_t \geq 0$ and $p_t = 0$ otherwise. This preference uses only earlier rounds. Call t a creator when $x_t \neq p_t$, and let $\gamma_t(x)$ be the gain under $F'_{\hat{y}}$ of flipping it to p_t. Accumulate the comparisons $\gamma_t(x) \leq s_t$ for the creators of this prefix. After all prefix rounds, enumerate the suffixes satisfying

$$\sum_{t \text{ creator}} (\gamma_t(x) - s_t) \leq 0. \tag{24}$$

This is one affine inequality on the suffix, so Lemma 2.6 applies. Evaluate the original objective on every candidate. Candidates need not have projections near the guessed grid point. Retain the best score and assignment across all prefixes and tuples, and return them after all runs finish.

Lemma C.1 (Sound comparisons with approximate projections)**.** *Every optimum is enumerated in a run that approximates its projections. The algorithm is exact for every supplied representation and round partition.*

Proof. Write $y_k = \langle v_k, x \rangle$. The difference between the original $0 \to 1$ gain at t and the auxiliary gain is

$$\sum_k \lambda_k v_k(t)(y_k - \hat{y}_k - v_k(t)x_t).$$

If $|y_k - \hat{y}_k| \leq \delta_k$, its absolute value is at most s_t. Every flip at an optimum has original gain at most zero, so each creator has $\gamma_t \leq s_t$ in an approximating run. Their sum satisfies (24). Weak inequalities retain ties. □

The accumulation proof below uses only nonnegative comparison allowances, their total size, and the fact that an optimum survives in at least one run. Thus a smaller allowance may replace s_t if its validity is proved directly. The same proof allows a joint finite list of aggregate guesses, rather than a Cartesian product of independent grids. This includes the supplied-community counts and diagonal allowances in Section 6; the running bound uses the number of joint guesses.

C.2 A general accumulation theorem

Let $D_N = n^{-1}\sum_{u\neq v} N_{uv}^2 > 0$ and $W_t = \sum_{w:\rho(w)<\rho(t)} N_{tw}^2$. The shared assumptions are

$$\sum_{t\le T}\sqrt{W_t} \ge 4\sqrt{3}\,gn\sqrt{D_N}, \qquad \sum_{t\le T} s_t \le \tfrac{1}{8}gn\sqrt{D_N}. \tag{25}$$

All constants below are independent of n.

Theorem C.2 (Accumulation after projection guessing)**.** *Assume* (25)*, with* $0<\tau<1$ *and* $g, K>0$*. Either of the following conditions gives a deterministic exact algorithm in polynomial space and time*

$$O^*(|\mathcal{Y}|(2^{\tau n} + 2^n e^{-c_* n})).$$

1. ***Sequential comparisons.*** *Each prefix round is a singleton. Let* $R_{tw} = N_{tw}[w>t]$ *for* $t\le T$*, and assume* $\|R\|^2 \le KD_N$*. Set* $K_L = K$ *and* $c_* = g^2/(64\tau\alpha^2 K)$*.*

2. ***A fixed number of rounds.*** *There are* $\ell \ge 2$ *prefix rounds, with* ℓ *fixed, and* $\|N\|^2 \le KD_N$*. Set* $K_L = (\ell-1)K$ *and*

$$c_* = \min\left\{\frac{g^2}{32\tau\alpha^2 K_L}, \frac{g^2}{512\ell^2\tau K}, \frac{c_{\mathrm{HW}}g^2}{256\ell^2\tau K}, \frac{c_{\mathrm{HW}}g}{16\ell\sqrt{K}}\right\}.$$

   Here $c_{\mathrm{HW}} > 0$ *is an absolute Hanson–Wright constant.*

In both cases, $\alpha = \max(2, 9\tau\sqrt{K_L}/(4g))$ *and* $n \ge 256\pi\tau K_L/g^2$*. Linear coefficients and units are arbitrary. For polynomially many grid points this is a fixed base below two.*

Exact count guessing is a special case: for $v_k \in \{-1,0,1\}^n$, use all integer counts and $\delta_k = 0$. Then $|\mathcal{Y}| \le (2n+1)^r$ and $s_t \le \sum_k |\lambda_k|$. Empirical mean centering takes $r=1$, $v_1 = \mathbf{1}$, $\lambda_1 = \binom{n}{2}^{-1}\sum_{u<v} J_{uv}$, and only $n+1$ counts. If $P=0$, there is one run and no comparison slack.

Lemma C.3 (A common gap estimate)**.** *Let* L *be the* $T\times T$ *matrix with* $L_{tw} = N_{tw}$ *when* $\rho(w) < \rho(t)$ *and zero otherwise. Suppose* $\|L\|^2 \le K_L D_N$ *and* (25)*'s gap bound holds. With* $M = \alpha\sqrt{K_L D_N}$ *and the theorem's lower bound on* n*,*

$$\mathbb{P}\left(\sum_{t\le T}\min\{|\Delta_t|, M\} < \tfrac{3}{4}gn\sqrt{D_N}\right) \le 4e^{-g^2 n/(16\tau K_L)}.$$

The probability is over a uniform Boolean assignment, with the formula fixed.

Proof. Put $u = 2x - \mathbf{1}$ and $H_t = a_t^{\hat{y}} + \frac{1}{2}\sum_{w\neq t} N_{tw}$. Write Lu for $L(u_1,\dots,u_T)^{\mathsf{T}}$, so $\Delta_t = H_t + \frac{1}{2}(Lu)_t$. Partition the indices into $B_0 = \{t : |H_t| \le M/2\}$ and its complement B_1. Since $\|Lu\|^2 \le K_L D_N T$, clipping the gaps at M loses at most $K_L D_N T/(8M)$ from $\sum_{B_0}|\Delta_t|$; use $(a-b)_+ \le a^2/(4b)$ with $a = |(Lu)_t|/2$, $b = M/2$. For $t\in B_1$, the clipped gap is at least

$M/4$ whenever $|(Lu)_t| \le M/2$, and at most $4T/\alpha^2$ indices fail this condition. Thus, for $G(u) = \sum_{B_0} |\Delta_t|$,

$$\sum_{t \le T} \min\{|\Delta_t|, M\} \ge G(u) + \frac{M}{4}|B_1| - \frac{9T\sqrt{K_L D_N}}{8\alpha}.$$

A symmetric Rademacher sum of variance W_t has first absolute moment at least $\sqrt{W_t/3}$. Hence $\mathbb{E}|\Delta_t| \ge \frac{1}{2}\sqrt{W_t/3}$, uniformly in H_t. Also $W_t \le K_L D_N$ and $M/4 \ge \frac{1}{2}\sqrt{W_t/3}$. Consequently $\mathbb{E}G + M|B_1|/4 \ge 2gn\sqrt{D_N}$, and the displayed loss is at most $gn\sqrt{D_N}/2$. The convex function G is Lipschitz with constant at most $h = \frac{1}{2}\sqrt{TK_L D_N}$. Talagrand's inequality [7] gives

$$\mathbb{P}(G \le \mathbb{E}G - a - 8\sqrt{\pi}h) \le 4e^{-a^2/(16h^2)}.$$

The mean-to-median shift follows by integrating the median tail. The bound on n makes $8\sqrt{\pi}h \le gn\sqrt{D_N}/4$; set $a = gn\sqrt{D_N}/2$. □

Proof of Theorem C.2. Correctness is Lemma C.1. Fix a run and a uniform x, and write $u = 2x - \mathbf{1}$ and I for its creators. In the sequential case, L is the transpose of the leading square block of R, so $\|L\| \le \|R\|$. In the round case, each row block is $N_{B_j \times B_{<j}}$, whence $\|L\|^2 \le (\ell - 1)\|N\|^2$. The common gap estimate applies in both cases.

Accumulated gap. Given the earlier variables, each creator indicator is a fair coin and Δ_t is fixed; within a round all preferences were fixed before it started. For $Y_t = [t \in I] \min(|\Delta_t|, M)$, Azuma–Hoeffding gives

$$\mathbb{P}\left(\sum_t Y_t < \tfrac{1}{2}\sum_{t \le T} \min(|\Delta_t|, M) - a\right) \le e^{-2a^2/(TM^2)}.$$

Use $a = gn\sqrt{D_N}/8$. The gap lemma and the slack bound imply $S' = \sum_{t \in I}(|\Delta_t| - s_t) \ge gn\sqrt{D_N}/8$ outside these two exceptional events.

Sequential comparisons. Here the sum tested by the algorithm is

$$S' + Q, \qquad Q = -\tfrac{1}{2}\sum_w u_w \sum_{t \in I, t < w} u_t N_{tw}. \tag{26}$$

The inner coefficient is predictable, and its squared sum is at most $\|R^{\mathsf{T}}(u_t[t \in I])_{t \le T}\|^2 \le KD_N T$. The conditional cosh bound gives $\mathbb{P}(Q \le -b) \le e^{-2b^2/(KD_N T)}$. For $b = gn\sqrt{D_N}/16$, a passing assignment belongs to an exceptional event. Their total probability is at most $6e^{-c_* n}$ with the stated sequential constant (which conservatively retains the earlier bound).

Comparisons within rounds. The tested sum is $S' + Q_{\text{later}} + \sum_{j \le \ell} Q_j$, where

$$Q_{\text{later}} = -\tfrac{1}{2}\sum_w u_w \sum_{t \in I : \rho(t) < \rho(w)} u_t N_{tw}, \qquad Q_j = -\tfrac{1}{2}\sum_{t \in I \cap B_j} \sum_{w \in B_j \setminus \{t\}} u_t N_{tw} u_w.$$

For a later round the coefficients are fixed from earlier rounds. Each block of coefficients has squared norm at most $KD_N T$, and there are at most ℓ such blocks, including the suffix. Thus

$$\mathbb{P}(Q_{\text{later}} \le -b) \le e^{-2b^2/(\ell KD_N T)}.$$

Take $b = gn\sqrt{D_N}/32$.

Condition on the rounds preceding B_j. Put $c_t = 2p_t - 1$ and $\beta_t = -c_t u_t$. These are independent fair signs, and $t \in I$ precisely when $\beta_t = 1$. The matrix $M^{(j)}_{tw} = c_t c_w N_{tw}$ on B_j has zero diagonal and norm at most $\sqrt{KD_N}$. Direct expansion gives

$$Q_j = -\tfrac{1}{4}\beta^{\mathsf{T}} M^{(j)} \beta - \tfrac{1}{4}\langle M^{(j)}\mathbf{1}, \beta\rangle.$$

Both $\|M^{(j)}\mathbf{1}\|^2$ and $\|M^{(j)}\|_F^2$ are at most $|B_j|KD_N$. For $e = gn\sqrt{D_N}/(64\ell)$, the linear term is below $-e$ with probability at most $e^{-8e^2/(|B_j|KD_N)}$. Hanson–Wright [8] bounds the corresponding quadratic probability by

$$2\exp\left[-c_{\mathrm{HW}}\min\left\{\frac{16e^2}{|B_j|KD_N}, \frac{4e}{\sqrt{KD_N}}\right\}\right].$$

A union bound therefore gives $\sum_j Q_j \geq -gn\sqrt{D_N}/32$ outside these events. On the remaining assignments the tested sum is at least $(1/8 - 1/32 - 1/32)gn\sqrt{D_N} > 0$. Using $|B_j| \leq T \leq \tau n$, the total passing probability is at most $(6 + 3\ell)e^{-c_* n}$. Lemma 2.6 finishes both time bounds. Runs and candidates are streamed, so space is polynomial. □

C.3 Projection grids and discovering the low-rank part

Corollary C.4 (Polynomial projection grids)**.** *Suppose $\|v_k\|_2 \leq 1$ and use $\mathcal{Y}_k = \delta\mathbb{Z} \cap [-\|v_k\|_1 - \delta, \|v_k\|_1 + \delta]$, where $\delta > 0$ is rational. Then*

$$|\mathcal{Y}| \leq (2\sqrt{n}/\delta + 3)^r, \qquad \sum_{t \leq T} s_t \leq \sum_k |\lambda_k|(\delta\sqrt{n} + 1).$$

Thus Theorem C.2 applies whenever its norm and gap conditions hold and the last expression is at most $gn\sqrt{D_N}/8$.

Proof. The Cauchy–Schwarz inequality gives $\|v_k\|_1 = \sum_t |v_k(t)| \leq \sqrt{\sum_t 1^2}\sqrt{\sum_t v_k(t)^2} \leq \sqrt{n}$. Also $\sum_t s_t = \sum_k |\lambda_k|(\delta\|v_k\|_1 + \|v_k\|_2^2)$. □

The vectors need not be exact eigenvectors. One deterministic construction uses a rational, approximately diagonalizing orthogonal matrix, takes its r largest diagonal entries in absolute value, and uses the corresponding columns. Appendix E gives a polynomial-bit construction and a random-model guarantee. All pruning comparisons use the rational vectors actually computed, so numerical approximation affects the running bound, not exactness.

D Estimates for independent pair interactions

For this appendix, $P_{uv} = \sum_k \beta_k t_k(u) t_k(v)$ with vectors $t_k \in \{-1, 0, 1\}^n$, $N = \mathrm{offdiag}(J - P)$, $\sigma = \sum_k |\beta_k|$, $T = \lfloor \tau n \rfloor$, $R_{tw} = N_{tw}[w > t]$ for $t \leq T$, and $W_t = \sum_{j<t} N_{tj}^2$. Exact count grids have $s_t \leq \sigma$. Thus the following imply the sequential case of Theorem C.2:

$$\|R\|^2 \leq KD_N, \qquad \sum_{t \leq T} \sqrt{W_t} \geq 4\sqrt{3}\, gn\sqrt{D_N}, \qquad \sigma \leq g\sqrt{D_N}/(8\tau). \tag{27}$$

The following criterion verifies the sequential accumulation conditions for independent pair coefficients. Its random-matrix and row-mass estimates are also used in Appendix E. We write χ for the variance ratio to distinguish it from clause density. The probability event concerns J alone, which is why the linear coefficients and unit clauses can be arbitrary.

Proposition D.1 (Independent-pair membership)**.** *Fix $0 < \tau < 1$, $\chi \ge 1$, $C_0 = 10^9\chi/\tau$, and $n \ge 10^9\chi^2/\tau^2$. Suppose the coefficients J_{uv}, $u < v$, are independent, with*

$$|J_{uv} - \mathbb{E}J_{uv}| \le B, \qquad 0 < \nu \le \operatorname{Var} J_{uv} \le \chi\nu.$$

Choose either of the following decompositions:

1. *All means equal μ, and $P_{uv} = \beta$, where β is the empirical mean over pairs. Put $\sigma_0 = |\mu|$.*
2. *A fixed supplied decomposition of the form above has $P_{uv} = \mathbb{E}J_{uv}$ for $u \ne v$. Put $\sigma_0 = \sum_k |\beta_k|$. In particular, if all means vanish, take $P = 0$ and $\sigma_0 = 0$.*

If $n\nu \ge C_0(B^2 \log n + \chi\sigma_0^2)$, then with probability at least $1 - 1/n$, conditions (27) *hold with $K = 9\chi$ and $g = \tau^{3/2}/(12\sqrt{\chi})$. The lower bound on n in Theorem C.2 also holds.*

Proof. Put $X_{uv} = J_{uv} - \mathbb{E}J_{uv}$, and let $\delta = \beta - \mu$ in the first case and $\delta = 0$ in the second. Then $N_{uv} = X_{uv} - \delta$ off the diagonal. Set $\eta = 1/100$.

We use scalar Bernstein concentration [6], Talagrand's convex concentration inequality [7], and the rectangular norm estimate of Bandeira and van Handel [5, Theorem 3.1 and Corollary 3.2]. The last estimate, for independent random signs ξ_{tw} and a fixed coefficient array a, is

$$\mathbb{E}\|(\xi_{tw}a_{tw})\| \le (1+\vartheta)\left(\sigma_1 + \sigma_2 + \frac{5\max_{t,w}|a_{tw}|\sqrt{\log n}}{\sqrt{\log(1+\vartheta)}}\right), \quad 0 < \vartheta \le 1/2,$$

where σ_1, σ_2 are the largest row and column Euclidean norms. For a convex 1-Lipschitz function of independent coordinates in $[-B, B]$, we use the tail $\mathbb{P}(f > \mathbb{E}f + 8\sqrt{\pi}B + r) \le 4e^{-r^2/(16B^2)}$.

Centering and total variance. Bernstein's inequality gives, in the empirical case, $|\delta| \le \delta_0 = 6\sqrt{\chi\nu\log n}/n$ except with probability at most n^{-3}. For example, applying it to $\sum_{u<v} X_{uv}$ gives a two-sided exponent at least $4.5(1 - 1/n)\log n$. The bound on n implies $\delta_0 \le 10^{-3}\sqrt{\nu}$ and $n\delta_0 \le 10^{-3}\sqrt{n\chi\nu}$. Bernstein applied to $\sum X_{uv}^2$ also gives

$$(1-\eta)n(n-1)\nu \le \sum_{u\ne v} X_{uv}^2 \le (1+\eta)n(n-1)\chi\nu.$$

In the empirical case, $D_N = n^{-1}\sum_{u\ne v} X_{uv}^2 - (n-1)\delta^2$; in the expected case, $D_N = n^{-1}\sum_{u\ne v} X_{uv}^2$. Hence, outside another event of probability at most n^{-3},

$$(1-2\eta)(n-1)\nu \le D_N \le (1+\eta)(n-1)\chi\nu. \tag{28}$$

The operator norm. Let R_X have entries X_{tw} for $t \le T$, $w > t$, and zero otherwise. The entries in this array are independent. Symmetrize with an independent copy X' and put $\widehat{X} = X - X'$. Then $\mathbb{E}\|R_X\| \le \mathbb{E}\|R_{\widehat{X}}\|$. Condition on $\widehat{X}$ and introduce independent signs. Since its entries are symmetric, the displayed norm estimate with $\vartheta = \eta$ gives

$$\mathbb{E}\|R_X\| \le (1+\eta)(\mathbb{E}\sigma_1(\widehat{X}) + \mathbb{E}\sigma_2(\widehat{X})) + 102B\sqrt{\log n}.$$

Each squared entry is at most $4B^2$ with expectation at most $2\chi\nu$. Bernstein and a union bound show that every row-square sum is at most $2(1+\eta)n\chi\nu$, and every column-square sum at most $2(\tau+\eta)n\chi\nu$, except with probability $2ne^{-\eta^2 n\chi\nu/(5B^2)} \le n^{-3}$. Bounding each exceptional sum by $4nB^2$ gives

$$\mathbb{E}\sigma_1(\widehat{X})^2 \le 2(1+2\eta)n\chi\nu, \qquad \mathbb{E}\sigma_2(\widehat{X})^2 \le 2(\tau+2\eta)n\chi\nu.$$

Thus $\mathbb{E}\|R_X\| \le 2.89\sqrt{n\chi\nu}$, using $102/\sqrt{C_0} \le 0.004$. Convex concentration with $r = \eta\sqrt{n\chi\nu}$, together with $8\sqrt{\pi}B \le 10^{-3}\sqrt{n\chi\nu}$, now gives

$$\|R\| \le \|R_X\| + n|\delta| \le 2.902\sqrt{n\chi\nu}, \qquad \|R\|^2 \le 8.43n\chi\nu \le 9\chi D_N$$

outside an event of probability at most n^{-3}.

The earlier-neighbor mass. Put $t_0 = \lceil \tau n/10 \rceil$. For $t > t_0$, scalar Bernstein gives $V_t = \sum_{j<t} X_{tj}^2 \geq (1-\eta)(t-1)\nu$ with failure probability at most $e^{-\eta^2 \tau n \nu/(30B^2\chi)} \leq n^{-3}$. Consequently $\sqrt{W_t} \geq \sqrt{V_t} - |\delta|\sqrt{t-1} \geq 0.993\sqrt{(t-1)\nu}$. Summing and using $T \geq \tau n - 1$ yields

$$\sum_{t \leq T} \sqrt{W_t} \geq 0.635\, \tau^{3/2} n^{3/2} \sqrt{\nu} \geq 4\sqrt{3}\, gn\sqrt{D_N};$$

the last expression is at most $0.581\, \tau^{3/2} n^{3/2}\sqrt{\nu}$ by (28).

The allowed comparison slack. Equation (28) gives $g\sqrt{D_N}/(8\tau) \geq 0.0102\sqrt{\tau n \nu/\chi}$. In the expected case, $\sigma = \sigma_0 \leq \sqrt{n\nu/(C_0\chi)} \leq 10^{-4}\sqrt{\tau n\nu/\chi}$. In the empirical case, $\sigma = |\beta| \leq \sigma_0 + \delta_0 \leq 0.002\sqrt{\tau n\nu/\chi}$. This establishes the third condition.

There are at most $n+4$ failure events, each of probability at most n^{-3}, so their union has probability at most $1/n$. Finally $256\pi\tau K/g^2 = 256\pi \cdot 1296\, \chi^2/\tau^2 < 1.1 \cdot 10^6 \chi^2/\tau^2 \leq n$. □

E Spectral preprocessing for hidden communities

E.1 A discovery lemma for the stochastic block model

Lemma E.1 (Discovering a bounded-rank mean)**.** *Fix a rank bound r and variance ratio $\chi \geq 1$. Suppose the integer coefficients J_{uv} are independent over $u < v$,*

$$|J_{uv} - \mathbb{E}J_{uv}| \leq B, \quad 0 < \nu \leq \operatorname{Var} J_{uv} \leq \chi\nu,$$

where we take $B \geq 1$. Suppose their means are the off-diagonal entries of a symmetric matrix $\bar{A}$ with $\operatorname{rank}\bar{A} \leq r$, $|\bar{A}_{uu}| \leq B_0$ and $\|\bar{A}\| \leq \mu n$. For a sufficiently large $C = C(r,\chi)$, if

$$n\nu \geq C(B^2 \log n + B_0^2 + \mu^2),$$

there is a deterministic exact polynomial-space algorithm, given the fixed class parameters r, χ but not $\bar{A}$ or ν, B, B_0, μ, taking $O^*(2^{(1-\gamma)n})$ time with probability $1 - o(1)$, for a fixed $\gamma > 0$. Arbitrary units, even chosen after the binary draw, are allowed.

We give the computational detail separately so that the general theorem requires only rational comparisons, with no exact-real arithmetic oracle.

Rational approximate diagonalization. For a rational symmetric matrix J and rational $\zeta > 0$, one can compute a rational orthogonal Q and rational diagonal D with $\|J - QDQ^{\mathsf{T}}\|_F \leq \zeta$ in time polynomial in the input bit length, n, and $\log(1/\zeta)$. Here a slow Jacobi implementation suffices. For completeness, initialize $Q = I$ and $A = J$, and maintain $A = Q^{\mathsf{T}}JQ$. Let $E = \sum_{i \neq j} A_{ij}^2$. An exact plane rotation eliminating a largest entry A_{ij} reduces E by $2A_{ij}^2 \geq 2E/[n(n-1)]$. Approximate that rotation by a rational orthogonal plane rotation using

$$\cos\theta = \frac{1-t^2}{1+t^2}, \qquad \sin\theta = \frac{2t}{1+t^2}, \qquad t \in \mathbb{Q}.$$

The eliminating angle can be chosen in $[-\pi/4, \pi/4]$, so its parameter $t = \tan(\theta/2)$ is approximated on a bounded interval by elementary root approximation. With rotation error $O(\zeta^2/(n^2(1+\|J\|_F)^2))$, the error in the decrease of E is at most $\zeta^2/[2n(n-1)]$. Therefore while $E > \zeta^2$, it contracts by at least a fixed multiple of $1/n^2$ per step. After $O(n^2 \log(2 + \|J\|_F/\zeta))$ steps, set $D = \operatorname{diag}(A)$. Every rotation is exactly orthogonal and rational; products and matrix updates are performed exactly. The bit lengths grow at most polynomially in the number of rotations and their polynomial bit lengths. This proves the claimed computational bound without an eigenvalue-separation assumption.

Let P retain the r entries of D of largest absolute value and the corresponding columns of Q. It has rank at most r and a rational orthonormal representation. Since QDQ^{T} is within ζ of J, the variational characterization of singular values gives

$$\|J - P\| \le \sigma_{r+1}(J) + 2\zeta. \tag{29}$$

This is sufficient; individual eigenvectors need not be close to any particular exact eigenbasis.

Setup for the comparison search. Given the fixed class parameters r, χ, choose a positive rational g between $1/(512\sqrt{\chi})$ and $1/(256\sqrt{\chi})$. Fix the original variable order and two prefix rounds of sizes $\lfloor n/4 \rfloor$ and $\lfloor n/2 \rfloor - \lfloor n/4 \rfloor$. If $n < 4$, use exhaustive search. Otherwise, compute P by the preceding construction with $\zeta = n^{-4}$, then form $N = \operatorname{offdiag}(J - P)$ and $D_N = n^{-1} \sum_{u \neq v} N_{uv}^2$. If $D_N = 0$, use exhaustive search.

When $D_N > 0$, let $\Lambda = \sum_{k \le r} |\lambda_k|$ for the retained directions. If $\Lambda = 0$, take $P = 0$ and use one run with no projection guesses. Otherwise, choose a dyadic rational δ within a factor two below $g\sqrt{nD_N}/(64\Lambda)$ and replace it by $\max\{\delta, n^{-2}\}$. Construct the grids of Corollary C.4 with this spacing and their comparison allowances. Now execute the comparison routine of Appendix C with these grids and rounds. The lower bound on the spacing keeps the number of runs polynomial on arbitrary inputs. Each grid still covers every Boolean projection, so the routine remains exact whether or not the input satisfies the probabilistic guarantees.

Proof of Lemma E.1. We verify the running-time guarantee for this construction. Put $X = \operatorname{offdiag}(J - \bar{A})$. With $\zeta = n^{-4}$, write $E_0 = \|X\| + B_0$, so $J = \bar{A} + X - \operatorname{diag}(\bar{A})$ and $\sigma_{r+1}(J) \le E_0$. Thus

$$\|J - P\| \le E_0 + 2\zeta, \qquad \|N\| \le 2E_0 + 4\zeta, \quad N = \operatorname{offdiag}(J - P).$$

For $H = \bar{A} - P$, we have $\operatorname{rank} H \le 2r$ and $\|H\| \le 2E_0 + 2\zeta$, hence $\|H\|_F \le \sqrt{2r}(2E_0 + 2\zeta)$.

The symmetric version of the random-matrix bound of Bandeira and van Handel [5], symmetrization and convex concentration as in Appendix D, imply $\|X\| \le 3\sqrt{\chi n\nu}$ with probability $1 - o(1)$ when $n\nu \ge CB^2 \log n$ with sufficiently large C. The leading symmetrized norm constant is $2\sqrt{2} < 3$; the $O(B\sqrt{\log n})$ term is absorbed by increasing C. Bernstein's inequality and a union bound also give, on the same event,

$$.99n(n-1)\nu \le \|X\|_F^2 \le 1.01\chi n(n-1)\nu, \qquad \sum_{s \in B_1} X_{ts}^2 \ge .99|B_1|\nu \quad (t \in B_2).$$

Here $B_0^2 \le n\nu/C$, and $B \ge 1$ ensures that the numerical error ζ is negligible on this scale. Because $N = X + \operatorname{offdiag} H$, these bounds and the triangle inequality show, for fixed r, χ and sufficiently large n,

$$.9n\nu \le D_N \le 1.1\chi n\nu, \qquad \|N\|^2 \le 100\chi D_N.$$

Furthermore the correction to the sum of cross-round row norms is at most

$$\sqrt{|B_2|}\,\|H\|_F = O(n\sqrt{r\chi\nu}) = o(n^{3/2}\sqrt{\nu}).$$

The uncorrected sum is at least $|B_2|\sqrt{.99|B_1|\nu}$. Consequently the gap condition holds with the chosen $g \le 1/(256\sqrt{\chi})$, with room to spare, and $K = 100\chi$.

The retained diagonal entries are Rayleigh quotients of J, so $\Lambda \le r\|J\| \le r(\mu n + E_0)$. Increasing $C = C(r, \chi)$ and then n gives $\Lambda \le gn\sqrt{D_N}/64$. If $\Lambda = 0$, the comparison allowance is zero and only one run is needed. Otherwise, before the lower cap is applied, the chosen spacing satisfies $\delta \ge g\sqrt{nD_N}/(128\Lambda) \ge 1/(2\sqrt{n})$. Thus the cap is inactive for sufficiently large n on this event. Corollary C.4 bounds the total comparison allowance by $gn\sqrt{D_N}/32$ and gives

$$|\mathcal{Y}| \le \left(\frac{256\Lambda}{g\sqrt{D_N}} + 3\right)^r = n^{O(r)}.$$

This proves the promised bound by the round case of Theorem C.2. The constant K can be replaced by a slightly larger rational bound without affecting the conclusion.

The algorithm uses only J, the fixed class parameters r, χ, and its computed D_N, Λ. No planted mean, variance parameter, or spectral cutoff has to be supplied. □

F Proposed extension: a biased subset with bounded external influence

This appendix records a possible extension of the literal-gap analysis. The statement below is a research target: we do not provide a proof or claim Lean verification. It is not used by any result in the main text.

The global occurrence bound in Theorem 3.2 can be restrictive when a formula contains a dense part whose variables have little bias. One possible extension is to collect comparison constraints only from a linear-sized subset S of biased variables. Clauses involving no variable of S cancel in these comparisons. This suggests bounding the influence of a variable through its connections to S, rather than through all its occurrences in the formula.

For a preprocessed formula F_0, let B_v denote the total number of unit and binary occurrences of variable v, and let

$$g_v = d_2^{F_0}(v) - d_2^{F_0}(\neg v) + 2\big(d_1^{F_0}(v) - d_1^{F_0}(\neg v)\big).$$

For distinct variables v, w, let m_{vw} be the number of binary clauses containing both variables, irrespective of their signs and counting multiplicities. For $w \notin S$, write $r_S(w) = \sum_{v \in S} m_{vw}$.

Desired theorem F.1 (A biased subset attached to an arbitrary remainder)**.** Fix constants $\varepsilon, \eta \in (0, 1]$ and $C \geq 1$. Let F be a simple unweighted Max 2-SAT formula on n variables and let F_0 be its preprocessed formula. Suppose a set S and a number $d \geq 1$ satisfy

$$|S| \geq \eta n, \qquad B_v \leq d \text{ and } |g_v| \geq \varepsilon d \quad (v \in S), \qquad r_S(w) \leq Cd \quad (w \notin S).$$

Given F and such a set and scale, an optimal assignment can be computed deterministically in polynomial space and time $O^*(2^{(1-\gamma)n})$, for some $\gamma = \gamma(\varepsilon, \eta, C) > 0$.

Here S need not be a connected component, and its boundary need not be small. Variables in S may have most of their neighbors outside S. The external condition limits how many of their clause occurrences can be concentrated at a single outside variable. Clauses entirely outside S are unrestricted apart from the original simplicity assumption. In particular, that remainder may be much denser than the part incident to S. Interactions within S are also allowed.

The intended algorithm would fix the preferred values on S, choose the half of S carrying more total absolute gap, and use the same prefix branching and summed-constraint enumeration as in Section 3. The proposed analysis would count only the occurrences that can affect these selected comparisons. We leave both the proof and its formal verification to subsequent work.

The supplied set in the target separates the counting question from the question of recognizing the structure. An input-only result should also explain how to choose S in polynomial time. A concrete restricted version could take

$$S_d = \{v : B_v \leq d,\ |g_v| \geq \varepsilon d\}$$

and test its size and external occurrence bounds for candidate scales. Such tests need consider only polynomially many distinct sets, since membership changes only at the occurrence and gap thresholds. This does not establish that the tests find every set allowed by the target.

One motivation is an existing system together with a substantial set of new decisions whose pairwise soft requirements create a consistent literal bias. To obtain an application, one would still need a faithful encoding and a justification of the size, bias, and external occurrence conditions. We leave that investigation, including any extension to hard input requirements, to the later work on applications.

References

[1] R. Williams. A new algorithm for optimal 2-constraint satisfaction and its implications. *Theoretical Computer Science*, 348(2–3):357–365, 2005. Author manuscript.

[2] A. S. Kulikov and K. Kutzkov. New bounds for MAX-SAT by clause learning. *Computer Science–Theory and Applications (CSR 2007)*, LNCS 4649, pp. 194–204, 2007. Institutional publication record.

[3] A. Golovnev and K. Kutzkov. New exact algorithms for the 2-constraint satisfaction problem. *Theoretical Computer Science*, 526:18–27, 2014. Author manuscript.

[4] M. B. Hastings. Local maxima and improved exact algorithm for MAX-2-SAT. 2016. arXiv:1610.07100.

[5] A. S. Bandeira and R. van Handel. Sharp nonasymptotic bounds on the norm of random matrices with independent entries. *Annals of Probability*, 44(4):2479–2506, 2016. Author manuscript.

[6] S. Boucheron, G. Lugosi and P. Massart. *Concentration Inequalities: A Nonasymptotic Theory of Independence*. Oxford University Press, 2013.

[7] M. Talagrand. Concentration of measure and isoperimetric inequalities in product spaces. *Publications Mathématiques de l'IHÉS*, 81:73–205, 1995. Journal article.

[8] M. Rudelson and R. Vershynin. Hanson–Wright inequality and sub-gaussian concentration. *Electronic Communications in Probability*, 18(82):1–9, 2013. Author manuscript.

[9] A. E. Brouwer and W. H. Haemers. *Spectra of Graphs*. Springer, 2012. Authors' book page.

[10] E. Abbe. Community detection and stochastic block models: recent developments. *Journal of Machine Learning Research*, 18(177):1–86, 2018. Journal article.