A Learning and Coverage Dichotomy for Max 2-SAT

Two-sided comparisons, conditional dominance, and shared constraints

7 October 2026

Abstract

We investigate how overlapping learned constraints might yield a density-independent exponential saving for Max 2-SAT. Fractional packing, strengthened by conditioning on shared variables, gives a computable completion bound compatible with branching. We prove the required inheritance inequalities and construct logarithmic-width clauses with linear joint information. Two-sided comparisons lead to an entropy dichotomy: nearly implied comparisons give either immediate pruning or information already present. Joint infeasibility certificates exploit one case, including balanced variables with identical comparison profiles. Small exact experiments show both useful pruning and substantial overhead. A family with almost 2^n strict local optima identifies a remaining obstruction. A precise desired frontier theorem combines certified pruning with structural solutions; it remains unproved. No fixed-base algorithm for growing density is established.

1 What the dichotomy should accomplish

The target is a deterministic polynomial-space algorithm taking $O^*((2-\delta)^n)$ time for a fixed $\delta > 0$, independently of a growing density bound. We use the canonical unweighted $B = 1$ setting of the earlier notes unless stated otherwise. A bound on average clause density is not a bound on maximum variable degree.

The useful alternatives are not merely "large neighborhood" and "dominated variable". They are:

1. Large residual neighborhoods permit shared exposure: a small selected set of variables affects many targets, potentially creating useful gaps.

2. Smaller residual neighborhoods permit learning; accumulated learned constraints can then be exploited through their joint restrictions.

The second alternative permits learned widths tending to infinity. The Kulikov–Kutzkov learning method motivates this alternative [1]. The present note studies the accounting and exploitation of already sound constraints. It does not establish a new sound rule for learning arbitrary clauses, nor a theorem that the useful constraint families must arise.

At a node, all hard constraints must be valid for that node's search responsibility. Constraints justified only in one subtree must not be copied unconditionally into its sibling. The certificates below can ignore some valid constraints, but never introduce an unjustified one.

Exposure is available. For reference, suppose a neighborhood hypergraph has n vertices, minimum edge size s, maximum incidence degree d, and $1 \le k \le s$. There is a k-transversal of size at most

$$\min\left\{n, \frac{n}{s}(3k + 8\ln(d+1))\right\}.$$

To prove this, select each vertex with probability $p = (2k + 8\ln(d+1))/s$ if $p < 1$, and repair deficient edges by adding at most k vertices each. A Chernoff bound makes each edge deficient with probability at most $1/(d+1)$, and there are at most nd/s edges. The displayed bound follows by expectation. If $p \geq 1$, select all vertices. Thus in a d-regular graph with $d \to \infty$, $k = o(d)$ exposures per neighborhood cost $o(n)$ selected variables. This is an unsigned statement. Under uniform assignments, t exposed neighbors change one target's effective gap by a signed sum with standard deviation $\sqrt{t}$, not by t deterministically. Covering does not settle the signed analysis.

2 Exact information and two barriers

Let R be the set of r free variables and $\mathcal{P}$ the active hard constraints. Put

$$Z(\mathcal{P}) = \#\{x \in \{0,1\}^R : x \models \mathcal{P}\}, \qquad I(\mathcal{P}) = r - \log_2 Z(\mathcal{P}).$$

An inconsistent family has $I = +\infty$. Adding a constraint C to a nonempty family changes the information by

$$I(\mathcal{P} \cup \{C\}) - I(\mathcal{P}) = -\log_2 \mathbb{P}[C \mid \mathcal{P}],$$

where the conditional distribution is uniform on the satisfying assignments. The quantity is joint information, not the sum of unconditional clause contributions. Computing it exactly is generally difficult.

Proposition 1 (Residual-width barrier)**.** *For m ordinary non-tautological clauses, each on distinct variables and with residual length at least w, if $m2^{-w} < 1$, then*

$$Z \geq 2^r(1 - m2^{-w}), \qquad I \leq -\log_2(1 - m2^{-w}).$$

Proof. A length-ℓ clause is false on a $2^{-\ell}$ fraction of the Boolean cube. Apply the union bound to all clause-violation events. Overlap and literal signs do not invalidate that bound. □

Consequently, polynomially many ordinary clauses all of length $\omega(\log n)$ carry $o(1)$ bits of joint information at that state. This does not exclude savings later, once clauses become shorter, or from succinct cardinality constraints representing many ordinary clauses. It also does not exclude logarithmic or slower-growing learned widths.

Proposition 2 (Exposure alone preserves assignment mass)**.** *For a fixed ordinary clause C of length ℓ, assign any t of its variables uniformly. It remains unsatisfied with probability 2^{-t}; conditional on this, its residual length is $\ell - t$. Hence its expected remaining violation probability is $2^{-\ell}$. More generally, for any fixed hard family and variable x,*

$$Z(\mathcal{P}) = Z(\mathcal{P} \mid x = 0) + Z(\mathcal{P} \mid x = 1).$$

Shortening exposes existing restrictions and can make them easier to detect. It does not by itself create new exact information after the cost of all branches is included. A running-time proof must credit new learning, forced assignments, stronger certificates, or cheaper solution of the remaining objective. In particular, analysis must account for both the branches satisfying a learned clause and those shortening it.

3 A fractional-packing completion certificate

For each active constraint C_i, let $E_i \subseteq R$ be a support on which it depends and let

$$p_i = 2^{-|E_i|}\#\{x \in \{0,1\}^{E_i} : x \models C_i\}, \qquad c_i = -\log_2 p_i.$$

Ignore identically true constraints. An individually false constraint immediately refutes the node. For the remaining constraints, choose nonnegative weights satisfying

$$\sum_{i:v\in E_i} w_i \le 1 \quad (v \in R). \tag{1}$$

Define

$$W_w = \sum_i w_i c_i, \qquad U_w = 2^r \prod_i p_i^{w_i} = 2^{r-W_w}. \tag{2}$$

Zero weights omit their factors. A weight-one factor is allowed for an identically false constraint and makes $U = 0$.

Theorem 3 (Completion bound and inheritance)**.** *For every feasible weight vector, $Z(\mathcal{P}) \le U_w$. If a variable is branched on, retaining the same weights in the two restricted children gives*

$$U_{w,0} + U_{w,1} \le U_w. \tag{3}$$

Weights may be reoptimized in each child, provided the inherited witness remains an option. Newly learned constraints receive inherited weight zero. The same inequality then continues to hold.

Proof. Let J be the constraints containing the branching variable x. For $i \in J$, $p_i = (p_{i,0} + p_{i,1})/2$. Other probabilities are unchanged. By (1), $\sum_{i\in J} w_i \le 1$, so the weighted geometric mean $g(z) = \prod_{i\in J} z_i^{w_i}$ is concave on the nonnegative orthant. Consequently

$$\frac{1}{2}\prod_{i\in J} p_{i,0}^{w_i} + \frac{1}{2}\prod_{i\in J} p_{i,1}^{w_i} \le \prod_{i\in J}\left(\frac{p_{i,0}+p_{i,1}}{2}\right)^{w_i}.$$

Multiplying by 2^r and the unchanged factors proves (3). Feasibility persists after removing an assigned variable. Repeat the inequality to complete assignments. Every satisfying assignment has leaf bound one; other assignments have a nonnegative bound. Summing proves $Z \le U$. Further valid restrictions and minimization over candidates including the inherited one can only decrease child bounds. □

The static bound is a product-space inequality of Finner/Shearer type; it is not a new probability inequality. Read-k versions and their limitations are discussed in [2]. The point here is the explicit branching-compatible witness and its extension to conditioning below.

Computability. For an ordinary clause of residual width ℓ, $p_i = 1 - 2^{-\ell}$. For an unweighted cardinality constraint permitting at most b true literals among ℓ distinct variables,

$$p_i = 2^{-\ell} \sum_{j=0}^{\min(b,\ell)} \binom{\ell}{j},$$

with $p_i = 0$ if $b < 0$. Numerically polynomially bounded integer-weight constraints can use a knapsack dynamic program. General constraints do not automatically have efficiently computable probabilities.

For a fixed family, maximizing W_w subject to (1) is a linear program with coefficients c_i. Exact optimality is unnecessary: any rational feasible vector supplies a valid witness. Numerical LP outputs must be repaired or certified for feasibility before use.

How much ordinary packing can certify. If every variable appears in at most D active supports, $w_i = 1/D$ is feasible and gives $I \geq D^{-1} \sum_i c_i$. Here D is the incidence degree of the *learned* family; it need not equal the original graph's degree. This is a useful sufficient bound but can deteriorate with D.

There is a stronger limitation on the certificate itself. If $c_i \leq \eta |E_i|$ for every factor, then

$$W_w \leq \eta \sum_i w_i |E_i| \leq \eta r. \tag{4}$$

For ordinary clauses all of width at least w, one can take

$$\eta = \frac{-\log_2(1 - 2^{-w})}{w} = O\Big(\frac{1}{w 2^w}\Big).$$

Thus fractional packing of long ordinary clauses alone cannot certify a linear information gain, regardless of how many clauses there are. For a cardinality constraint with allowance $\beta\ell$, $\beta < 1/2$ fixed, its information can instead be $\Theta(\ell)$. The framework therefore treats ordinary clauses and strong cardinality clauses differently.

4 Conditioning on shared variables

Choose a set $H \subseteq R$, with $h = |H|$. It will be called a core; this means only a chosen set of shared variables, not a graph separator. For every assignment $a \in \{0,1\}^H$, compute the residual probabilities $p_i(a)$ and choose weights $w_i(a)$ subject to

$$\sum_{i : v \in E_i \setminus H} w_i(a) \leq 1 \qquad (v \in R \setminus H).$$

The choices may differ between core assignments. Write $W(a) = \sum_i w_i(a)(-\log_2 p_i(a))$. A locally contradicted assignment has $W(a) = +\infty$. Define

$$U_H = 2^{r-h} \sum_{a \in \{0,1\}^H} 2^{-W(a)}, \qquad I_H = r - \log_2 U_H = -\log_2 \mathbb{E}_a[2^{-W(a)}]. \tag{5}$$

Theorem 4 (Conditional certificate)**.** *We have $Z(\mathcal{P}) \leq U_H$. Store H and its assignment-indexed weight vectors as the witness. Restrict that witness in each child and retain it among the candidates. Then*

$$U_{H,0} + U_{H,1} \leq U_H.$$

For $h = O(\log n)$, polynomially many constraints with polynomial-time local counting permit polynomial-size witnesses and polynomial work per certificate evaluation, up to the numerical issue discussed below.

Proof. Apply Theorem 3 independently under each fixed core assignment and sum. Branching on $x \in H$ partitions the sum exactly. For $x \notin H$, apply (3) separately to each summand. The number of summands is 2^h. New cores and stronger weight vectors may be tried, while retaining the restricted old witness guarantees inheritance. □

Enlarging the core never worsens the best certificate: reuse each old weight vector in both extensions and apply the same concavity argument. Feasible weights can improve further because variables moved into the core no longer impose packing capacities.

Numerical implementation. Unlike the earlier integer weighted-sum certificate, U_H need not be an integer. For rigorous search, compute an upper approximation $\widetilde{U} \in [U, (1+\epsilon)U]$, with exact handling of zero factors. Use rational feasible weights and directed error bounds for logarithms, exponentials, and summation. Polynomial precision suffices when the family, weight representations, and local probability representations have polynomial size. Inheritance gives $\widetilde{U}_0 + \widetilde{U}_1 \le (1+\epsilon)\widetilde{U}$. For $\epsilon = n^{-2}$, the inflation over at most n branching levels is bounded by a constant. Cut only when the certified upper bound is less than one. The prototype below checks mathematical inequalities numerically; it does not implement directed rounding and is not a certified solver.

Rare core assignments cannot be ignored. For every a with finite $W(a)$,

$$I_H \le h + W(a). \tag{6}$$

This follows by retaining only its summand in (5). If $h = O(\log n)$, one core assignment with $W(a) = o(n)$ prevents this certificate from giving $\Omega(n)$ information. A high average of $W(a)$ is insufficient. Such surviving branches need further learning or a different structural argument. This is an explicit place where the proposed dichotomy must continue recursively.

5 Long clauses can jointly be very strong

Let $Y = \{y_1, \dots, y_q\}$ and $X = \{x_1, \dots, x_t\}$. For each $a \in \{0,1\}^q$, let $D_a(Y)$ be the ordinary clause falsified exactly by the pattern a.

Proposition 5 (A linear-size family with logarithmic width)**.** *The family*

$$\mathcal{P} = \{D_a(Y) : a \neq 0^q\} \ \cup \ \{x_i \vee y_1 \vee \cdots \vee y_q : 1 \le i \le t\} \tag{7}$$

has exactly one satisfying assignment. It has $2^q - 1 + t$ clauses of width q or $q+1$. Taking $t = 2^q$ gives $n = t + q$, $O(n)$ clauses, and every width $\Theta(\log n)$. Nevertheless its joint information is exactly n bits.

Proof. The first group forces $Y = 0^q$. The second group then forces every $x_i = 1$. Conditioning on $H = Y$ detects a false core clause on every nonzero pattern; at the zero pattern, disjoint unit factors on X have weights one. Hence the conditional certificate also gives $U_H = 1$. □

Without conditioning, all supports contain Y, so the packing weights sum to at most one. The optimal unconditioned information is only $-\log_2(1 - 2^{-q})$. This separates the conditional construction from ordinary fractional packing by a linear amount.

A second family, containing $x_i \vee D_a(Y)$ for every i, a, is equivalent to $\bigwedge_i x_i$. Its core is free, and conditioning on Y gives $U_H = 2^q$, again exactly. Both examples are abstract hard-constraint families. No claim is made that the Max 2-SAT learning rules generate them with the required frequency or cost.

Growing degree does not prevent the example. Take disjoint copies of (7), each with $t = 2^q$ targets. The learned hypergraph has maximum incidence degree $d = 2t - 1$, widths q or $q + 1 = \Theta(\log d)$, and $O(n)$ clauses. It still has a unique satisfying assignment. With $q \to \infty$ this gives examples at growing degree, not only when the degree is linear in the total number of variables. The union of all local cores has size $nq/(t+q) = O(n \log d/d) = o(n)$, while each individual core is logarithmic. The example also has many low-degree target variables; no regularity claim is intended.

Proposition 6 (Composing disjoint local certificates)**.** *Suppose valid subfamilies have pairwise disjoint variable supports B_j. For each, let U_j be a completion upper bound satisfying the inherited branching inequality, possibly obtained using its own core. Then*

$$U = 2^{r-|\bigcup_j B_j|} \prod_j U_j$$

is a completion upper bound for their conjunction and satisfies the same branching inequality. Other active constraints may be ignored or used in additional candidate certificates.

Proof. The subfamily completion counts multiply on disjoint supports. A branch in B_j changes only its factor; an uncovered-variable branch splits its free factor exactly in half. Apply the local branching inequality. □

Thus many local cores can be used without enumerating their entire union at once. In the disjoint-copy example every local bound equals one, so their product certifies the unique global assignment with polynomial work. This suggests looking for a packing of useful local cores as well as one globally shared core. It does not require the full Max 2-SAT objective to decompose: the bound concerns the selected hard constraints only.

At the other extreme, if every ordinary learned clause contains the same positive literal z, then at least 2^{r-1} assignments satisfy the whole family. Thus $I \le 1$, however many distinct clauses accumulate. Branching on z exposes a potentially constrained child and a child in which the learned family disappears. The latter child's original Max 2-SAT objective may still be arbitrary. Clause redundancy alone therefore does not establish useful structure in that objective.

6 What covering and duality provide

For ordinary learned clauses, a useful core-selection objective is to meet selected supports E_i in at least $|E_i| - b$ variables. Under any core assignment, each selected clause is either satisfied or becomes a clause of width at most b. This is a multicover problem with nonuniform demands. Signs decide which clauses survive, so a support-only objective must be followed by the conditional sum in (5).

The fractional-packing LP also supplies an exact, but quantitatively limited, covering alternative. Its dual is

$$\min \sum_{v \in R} y_v \quad \text{subject to} \quad y_v \ge 0, \quad \sum_{v \in E_i} y_v \ge c_i. \tag{8}$$

We consider nonconstant factors with $0 < p_i < 1$, so their supports are nonempty and the usual $w_i \le 1$ restrictions are redundant.

Proposition 7 (Packing or a hitting set)**.** *Suppose a selected group of factors has $|E_i| \le b$ and $c_i \ge a > 0$. Let W^* be the optimal packing value for the full family. There is a set meeting every support in the selected group, of size at most bW^*/a.*

Proof. Take an optimal dual vector and put $H = \{v : y_v \ge a/b\}$. If a selected support missed H, its at most b coordinates would sum to less than a, contradicting its dual constraint. Also $|H|a/b \le \sum_v y_v = W^*$. □

This gives a genuine packing-or-covering statement: either W^* is large, or all selected supports meet a set bounded in terms of W^*. But it hits each support only once, and for long ordinary clauses a can be about 2^{-b}. Its bound then becomes too weak. It does not establish a logarithmic core, near-complete coverage, or a small graph separator. A stronger theorem must use clause provenance, repeated shortening, or interactions between opposite literals.

Stronger factors. The factors need not be individual clauses. Any consequence with an efficiently countable satisfying set may be used. Two useful choices are:

- a conjunction of constraints whose union of supports has $O(\log n)$ variables, counted by enumeration;
- a nonnegative weighted sum of cardinality inequalities, counted by the integer dynamic program from the earlier branching note.

These can be inserted as additional factors or maintained as separate candidate certificates. Inherited witnesses are retained in either case. The approaches are complementary: two opposite cardinality inequalities may sum to a contradiction that marginal packing misses completely. Conversely, resolving sign patterns through a shared core can reveal restrictions hidden from a single weighted-sum relaxation.

7 Two-sided comparisons and conditional dominance

The question "does a fresh constraint add information?" is incomplete if it refers only to the second child. A comparison that is redundant there may exclude the corresponding part of the first child.

Proposition 8 (Partition by the better value)**.** *Write an assignment as (x, y), let $f_b(y) = f(b, y)$, and suppose the hard constraint $C(y)$ does not involve x. Define the exact comparison*

$$c_x(y) \quad \Longleftrightarrow \quad f_1(y) > f_0(y).$$

With ties assigned to $x = 0$,

$$\max_{x,y:C(y)} f(x,y) = \max\left\{ \max_{y:C(y)\wedge\neg c_x(y)} f_0(y), \quad \max_{y:C(y)\wedge c_x(y)} f_1(y) \right\}.$$

An empty maximization has value $-\infty$.

Proof. For each fixed feasible y, the displayed partition keeps exactly the better of its two extensions, with the stated tie convention. □

Consequently, $C \Rightarrow c_x$ eliminates the entire $x = 0$ child. If the implication holds only under a partial assignment α, then $C \wedge \alpha \Rightarrow c_x$ eliminates that portion of the child. When the implication is only approximate, the first child needs to search only the exceptional set $C \wedge \neg c_x$. This gives a concrete meaning to exploiting constraints that are already present.

For Max 2-SAT, $f_1 - f_0$ is an affine function of the other Boolean variables, so the exact comparison is a threshold constraint. In the earlier notes' notation, the preferred literal has flip difference $L - p$: its child keeps $L \geq p$, and its opposite child keeps $L \leq p - 1$. The asymmetric weak/strict thresholds assign every tie to the preferred literal. A learned clause may be a weaker consequence of this threshold. Merely knowing that such a necessary consequence holds does *not* prove which value is better. A sufficient improvement certificate can eliminate its certified region; an exact comparison gives the full partition (8).

Feasibility and scope are part of the rule. If genuine hard constraints involve x, put $C_b(y) = C(b, y)$. The correct two retained domains are

$$C_0(y) \wedge (\neg C_1(y) \vee f_0(y) \geq f_1(y)),$$
$$C_1(y) \wedge (\neg C_0(y) \vee f_1(y) > f_0(y)).$$

For example, $C_0 \Rightarrow C_1 \wedge c_x$ suffices to discard the first child. The implication $C \wedge (x = 1) \Rightarrow c_x$ alone does not: it can express a relation between x and its neighbors rather than a globally preferred value of x.

Optimization-preserving pruning constraints need a further distinction: they describe the node's search responsibility, not necessarily the full original feasible domain. Transferring a solution to the other value of x must respect the established search invariant, possibly because a dominating solution is covered elsewhere. The prototype below avoids a new transfer assumption: it forms the children of the existing sound two-sided search and only refutes conjunctions within those children. Likewise, a certificate available only after solving the first child does not retroactively remove the cost of solving it. Prospective comparison certificates are needed to save that work.

7.1 Disagreement mass measures both children

Let $\Omega \subseteq \{0,1\}^R$ be the nonempty current hard domain, with $r = |R|$, and let A be uniform on Ω. Let $b_x(y)$ be the comparison-preferred value of x. For a genuine hard domain it is feasibility-aware: choose 1 precisely when $C_1(y)$ holds and either $C_0(y)$ fails or $f_1(y) > f_0(y)$. Otherwise choose 0 on the projection of Ω. For a pruning domain, use a comparison whose filtering is justified by the search invariant. Define

$$\beta_x = \mathbb{P}\big[A_x \neq b_x(A_{-x})\big].$$

Filtering both children by this comparison leaves exactly $(1 - \beta_x)|\Omega|$ assignments in total. Its exact information gain is

$$g_x = -\log_2(1 - \beta_x). \tag{9}$$

Thus a comparison can be useful even when its second-child constraint adds no new information there. If C is independent of x, every feasible y has two extensions and $\beta_x = 1/2$. This does not yield one bit of gain at every later step: accumulated constraints can couple x to y, making β_x very small.

8 A proved near-implication entropy dichotomy

Let $h_2(q) = -q \log_2 q - (1 - q) \log_2(1 - q)$ denote binary entropy, with the usual endpoint convention. The following is a counting statement; it does not assume that the conditional probabilities are efficiently computable.

Theorem 9 (Nearly fixed comparisons: pruning or existing information)**.** *Let $\Omega \subseteq \{0,1\}^R$ be nonempty, A uniform on Ω, and $T \subseteq R$ nonempty. For every $x \in T$, suppose there is a constant $a_x \in \{0,1\}$ such that*

$$\mathbb{P}\big[b_x(A_{-x}) \neq a_x\big] \leq \eta.$$

For $\varepsilon > 0$, $\eta \geq 0$, and $\eta + \varepsilon < 1/2$, at least one of the following holds:

1. *Some $x \in T$ has $\beta_x \geq \varepsilon$, so its two-sided comparison removes at least an ε fraction of Ω.*
2. *The existing domain already satisfies*

$$\log_2 |\Omega| \leq r - |T|(1 - h_2(\eta + \varepsilon)). \tag{10}$$

Proof. If the first alternative fails, then for every $x \in T$,

$$\{A_x \neq a_x\} \subseteq \{A_x \neq b_x(A_{-x})\} \cup \{b_x(A_{-x}) \neq a_x\}$$

gives $\mathbb{P}[A_x \neq a_x] \leq \varepsilon + \eta$. Subadditivity of entropy and monotonicity of h_2 on $[0, 1/2]$ give

$$\log_2 |\Omega| = H(A) \leq \sum_{x \in R} H(A_x) \leq r - |T| + |T| h_2(\eta + \varepsilon).$$

□

For example, with $\eta = \varepsilon = 1/8$, either one comparison removes at least 12.5% of the current domain, or that domain already contains at least $0.18872|T|$ bits of information. If $|T| \geq \tau r$ for a fixed $\tau > 0$, the second alternative is linear in r. The theorem formalizes the proposed dichotomy when many comparison outcomes are almost constant under the old constraints. No degree gap assumption is needed for the statement.

There are two remaining gaps between this result and an algorithmic running-time bound. First, true conditional probabilities and model counts are not supplied by the theorem. An upper bound on the exception count divided by an upper bound on the total count is not, in general, an upper bound on the exception probability. Efficient certificates must justify the required implication, mass reduction, or completion bound directly. Second, small β_x need not mean that b_x is almost constant. The old constraints may already encode balanced, nonconstant response relations. That case is not covered by the theorem's hypothesis and can have very little information, as Section 10 shows.

9 Exploiting implication before opening a child

9.1 Identical comparison profiles without initial imbalance

Suppose T is an independent set of variables in the interaction graph, $Y = R \setminus T$, and all centers $x \in T$ have the same difference

$$f(x = 1, y) - f(x = 0, y) = h(y), \qquad y \in \{0, 1\}^Y.$$

The difference is independent of the other centers because there are no clauses between them. Use a common tie convention. In the unconstrained soft optimization problem, or whenever the relevant transfers are sound, the partition $h(y) > 0$ versus $h(y) \leq 0$ simultaneously determines a best value for every center. The optimum is attained with all centers equal to that common best response.

After the first center's comparison is imposed, the opposite comparison for every later center is inconsistent. For integral h, the two inequalities $h \geq 1$ and $h \leq 0$ sum to a contradiction. Thus joint constraints can force the remaining centers even if each inequality alone has no unit consequence and every initial literal gap is zero. The construction in Section 12 demonstrates this effect. This is a mechanism example, not a new general algorithm for independent sets: a large independent set is already useful structure. Its relevance is that repeated comparison information can be exploited before a large literal imbalance appears.

9.2 A checkable joint-infeasibility certificate

After assigning a candidate value and applying the existing propagation rules, write the residual child constraints as

$$\sum_j c_{ij}^{z_j} \leq k_i \quad (i = 1, \ldots, m), \qquad c_{ij}^0, c_{ij}^1 \geq 0.$$

Here c_{ij}^b is the contribution of variable j to row i when $z_j = b$; these superscripts are labels, not powers. For weights $w_i \geq 0$ define

$$M(w) = \sum_j \min_{b \in \{0,1\}} \sum_i w_i c_{ij}^b - \sum_i w_i k_i. \tag{11}$$

Proposition 10 (Joint refutation)**.** *If $M(w) > 0$, the child constraint system is infeasible.*

Proof. Every assignment has weighted left-hand side at least $\sum_j \min_b \sum_i w_i c_{ij}^b$, whereas satisfying all rows would make it at most $\sum_i w_i k_i$. □

For example, refuting $C \wedge \neg c_x$ proves $C \Rightarrow c_x$. In the implemented search we instead test the complete, correctly scoped constraint system of each proposed child. One refuted child fixes the other value; two refuted children cut the parent. The same certificate can be used under partial assignments to cover portions of an exceptional first branch. This is the zero-completion case of the weighted-sum method, used prospectively for the two-sided comparison.

The prototype first tests equal weights on all rows and on every pair of rows. If these fail, it solves the normalized linear program

$$\begin{aligned} &\text{maximize } \sum_j t_j - \sum_i w_i k_i, \\ &\text{subject to } t_j \le \sum_i w_i c_{ij}^b \quad (j,\ b \in \{0,1\}), \\ &\qquad w_i \ge 0, \qquad \sum_i w_i = 1. \end{aligned}$$

A floating-point solution only proposes multipliers. They are converted to nonnegative rationals, and (11) is verified exactly before any cut. An unverified proposal is ignored. The certificate also refutes the continuous box relaxation, so it is incomplete for Boolean infeasibility. Its use does not claim a new linear-programming duality principle. Polynomially many rows and polynomial certificate bit lengths permit polynomial verification and polynomial-size linear programs.

10 The balanced-relation obstruction

The remaining case is not just "large, balanced neighborhoods without new clauses." It can be a domain in which the comparison relations are already encoded, yet almost all of the exponential search space remains. The following example uses $B = 2$, with a complementary pair of clauses on each edge; it is not a $B = 1$ lower-bound construction.

Proposition 11 (Almost 2^r strict local optima)**.** *For even r, place the two clauses $(x_i \vee x_j)$ and $(\neg x_i \vee \neg x_j)$ on every pair $i < j$. There are exactly $\binom{r}{r/2} = \Theta(2^r/\sqrt{r})$ strict one-variable local maxima, all globally optimal. On their domain every β_x is zero and every variable has marginal $1/2$.*

Proof. If k variables are one, the number of satisfied clauses is

$$f(x) = \binom{r}{2} + k(r-k).$$

It is maximized at $k = r/2$. Flipping any one variable there decreases the objective by one. At any other cardinality, a flip toward $r/2$ increases it. Hence the strict local maxima are precisely the balanced layer. Each coordinate is balanced on that layer by complementation, and no assignment disagrees with its unconstrained best response. □

Consequently, retaining all assignments satisfying every one-variable best-response relation can leave information only $r - \log_2 \binom{r}{r/2} = \frac{1}{2}\log_2 r + O(1)$. This also gives a growing-degree example: for odd $d \to \infty$ with $d+1$ dividing r, take disjoint copies of K_{d+1} with the same

encoding. Interaction degree is d, binary clause density is d, and the number of surviving strict local maxima is

$$\binom{d+1}{(d+1)/2}^{r/(d+1)} = 2^{\,r-\Theta(r\log d/d)}.$$

Thus pure elimination of assignments that fail a one-variable local optimality test cannot by itself guarantee a fixed exponential saving for growing degree. This is not a lower bound on branching algorithms: the example is easy to optimize by the aggregate cardinality k, and its components are explicit. It explains why the desired theorem must permit structural solutions, aggregation, or additional symmetry-breaking rules. A small separator is one possible form of structure, not a necessary conclusion of redundant comparisons.

11 A concrete strategy and the desired global theorem

A possible implementation maintains the original formula, valid active learned constraints, and the best inherited completion witness. For candidate branching variables:

1. Form both children with the established learning and propagation rules, preserving their scope and tie-breaking conventions.
2. Test their joint constraints for certified infeasibility as in Section 9, before exploring either subtree.
3. Evaluate the inherited witness, weighted-sum candidates, fractional packings, and a polynomial-size list of cores of size at most $h = c\log_2 n$ for fixed c.
4. Select the variable minimizing $U_0 + U_1$, or maximizing $\log_2 U - \log_2(U_0 + U_1)$.

Candidate cores can come from high incidence, the dual weights in (8), or a greedy multicover routine aimed at short residual clauses. Greedily extending a core by trying each next variable is polynomial for fixed c, because each trial evaluates at most 2^h assignments. Searching all n^h cores would not be polynomial.

Why this is a running-time measure, not only a model count. For exact witnesses, every kept node has $U \geq 1$, and total child mass is at most parent mass. A subtree rooted at mass U has at most $O(nU)$ kept nodes under inherited certificates. Discarded children and polynomial lookahead add only polynomial work. The relative-rounding implementation changes this by a bounded multiplicative factor.

At an unconstrained root $U = 2^n$, so this observation alone gives no improved base. Let G_t be accumulated certified log-decrease under the normalized walk taking child i with probability $U_i/(U_0 + U_1)$. As proved in the earlier branching note [3], a sufficient condition is, for fixed $\alpha, \gamma, \xi > 0$,

$$\mathbb{P}\left[G_{\lfloor(1-\alpha)n\rfloor} < \gamma n\right] \leq 2^{-\xi n}.$$

It yields $O^*(2^{(1-\min\{\alpha,\gamma,\xi\})n})$ time. The conditional packing certificates can be used in that theorem just like the weighted-sum certificates. The missing condition is global availability of enough progress, not the validity of the local measure.

11.1 Desired theorem: amortized dominance or structure

The local results suggest three sources of progress: fresh comparisons remove appreciable mass; old constraints certify that the mass is already small; or balanced response relations permit a

cheaper structural solution. Theorem 9 proves a restricted counting version of the first two alternatives. Proposition 11 shows why they cannot replace the third in a universal statement.

Here is a quantitative target that accounts for all branches. It is intentionally called a *desired theorem*, rather than a conjecture already supported in its full generality. An algorithm realizing its conditions is still missing.

Desired theorem (unproved). There are constants $\alpha, \gamma \in (0,1)$, a density bound $\rho(n) \to \infty$, and a deterministic polynomial-space comparison-and-learning algorithm for canonical unweighted Max 2-SAT of density at most $\rho(n)$ with the following property. Count binary branching decisions from the root, and stop the initial search at depth $t_0 = \lfloor (1-\alpha)n \rfloor$, or earlier when a node can be discharged by a certified structural routine. The initial search uses polynomial work per node, and its boundary consists of:

1. live nodes $v \in \mathcal{F}$ with inherited completion bounds U_v that support a continuation of cost $O^*(U_v)$;
2. terminal nodes $v \in \mathcal{S}$ with valid solution routines of cost $O^*(B_v)$ and polynomial space.

The routines and certificates preserve an optimum, have polynomial-size representations, and satisfy the global frontier budget

$$\sum_{v \in \mathcal{F}} U_v + \sum_{v \in \mathcal{S}} B_v \le 2^{(1-\gamma)n}. \tag{12}$$

Polynomial factors in this budget may be absorbed into O^*. The constants are independent of n and of the allowed growing density. The initial target may restrict to $B = 1$; the stronger target allows $B = 2$, with the ultimate density range $\rho(n) = \Theta(n)$.

A refuted terminal has $B_v = 0$, and an ordinary evaluated leaf can have $B_v = 1$. A structural terminal's B_v bounds its *solution cost*, not its number of feasible assignments. This distinction is essential: the balanced clique layer has almost 2^r assignments but admits a polynomial-time solution. A demand that every terminal have a small completion count would rule out exactly the useful structural exits.

Proposition 12 (Consequence of the desired budget)**.** *If the desired theorem holds, then the algorithm runs in*

$$O^*\big(2^{(1-\kappa)n}\big) = O^*\big((2-\delta)^n\big), \qquad \kappa = \min\{\alpha, \gamma\}, \quad \delta = 2 - 2^{1-\kappa} > 0,$$

using polynomial space.

Proof. There are at most $O(2^{t_0})$ binary prefixes. Forced assignments and polynomial local processing add only a polynomial factor. The total continuation and terminal work is bounded by (12). Depth-first traversal, polynomial-size active certificates, and the assumed polynomial-space terminal routines give the space bound. □

The missing assertion is availability of this budget on states reached by a specified sound learning algorithm. No uniform one-step dichotomy for arbitrary hard constraints is claimed. A proof must exploit clause provenance and the residual objective, account for exceptional core assignments in (6), and pay for all children. The earlier normalized-walk condition is one route for the completion-bound part; it must be supplemented by structural exits when local comparisons saturate. Neither the entropy theorem nor the experiments establish these global requirements.

12 Checks and their limits

12.1 Completion certificates and shared cores

The companion experiment uses exact Boolean enumeration for reference counts, exact rational checks of packing feasibility, and floating-point certificate evaluation with tolerance 10^{-7}. It does not implement the interval-arithmetic variant described above.

- On 250 random systems of ordinary/cardinality constraints on 3–10 variables, every certificate upper-bounded the exact count. All 1,368 inherited branching checks, 250 added-constraint checks, and 223 core-extension checks passed. The largest positive numerical excess in a branching inequality was $5.7 \cdot 10^{-13}$.
- For the construction (7) with $q = 4, t = 12$, there are 16 variables and 27 clauses of width 4 or 5. The exact count is one. The certificate progresses as follows:

Core size	Completion upper bound	Certified bits
0	61,440	0.093
1	57,344	0.193
2	49,152	0.415
3	32,768	1.000
4	1	16.000

This illustrates a threshold effect: most of the benefit appears only when the entire shared core is conditioned on.

- The all-patterns construction with the same q, t has 192 width-5 clauses; conditioning on its four core variables gives the exact count 16.
- For $\sum_{j=1}^{6} x_j \leq 2$ and $\sum_{j=1}^{6}(1 - x_j) \leq 2$, unconditioned packing gives 22 completions, whereas their sum refutes the system immediately.
- We sampled 48 residual states from 12 random canonical Max 2-SAT formulas on 14 variables, with edge probability 0.85 and independent balanced signs. States had 4–10 free variables and at least two active nonvacuous pruning constraints, after domination and propagation. Conditioning on the two most frequent variables improved packing in 24 states. It beat the earlier heuristic weighted-sum certificate in 4 states; the sum certificate was better in 34 states, with 10 ties. All bounds remained above the exact intersection count.

These first experiments compare certificates, not whole-search runtime. They support keeping both certificate families, without establishing that logarithmic cores suffice in the worst case.

12.2 Two-sided search with joint refutations

Code and results are in `explore_conditional_dominance.py` and `conditional_dominance_checks.json`. The experiment compares the established two-sided branching search, with domination and propagation, against the same search with the joint-refutation test from Section 9. Both use the same variable order within each comparison. Rejected children count as leaves in *both* searches. Floating-point linear programming proposes witnesses; exact rational verification authorizes every additional cut.

Random instances. The 26 instances have 10, 12, or 14 variables (ten, ten, and six instances). Edge probabilities lie in $[0.65, 1]$, signs are independently balanced, and complementary-pair probability is 0 or 0.15, with random units. Both searches use maximum-degree branching:

Quantity	Total
Baseline leaves	433
Leaves with joint refutations	384
Additional joint cuts	29
Branch decisions reduced to one surviving child	23
Linear-program calls	270
Baseline elapsed time (seconds)	0.0129
Elapsed time with joint refutations (seconds)	0.3941

Both searches match exhaustive optima on all 26 instances. Leaves decrease by 11.3%, but the prototype is about 30 times slower: the extra pruning does not give a practical speedup here. Separately, 150 random weighted constraint systems yielded 71 multiplier refutations, all checked by exhaustive enumeration.

Identical balanced centers. For each of t independent centers x, use $(x \vee y_j)$ on the first $D/2$ common neighbors and $(\neg x \vee \neg y_j)$ on the remaining $D/2$. Add a random signed clique on the neighbors and units to reduce their unary fields. All centers have the same comparison profile and initial deficits $(D/2, D/2)$, hence zero gap. Both searches process centers first.

n	t	D	Baseline leaves	Joint-test leaves	Fixings
12	4	8	127	11	6
16	6	10	1,130	14	10
18	8	10	4,136	16	14

One center's decision forces the others in each subtree. Exhaustive optimization checks the first two instances; the baseline checks the 18-variable result. These illustrate conditional dominance, not a worst-case bound.

A negative control. For the complete-graph Max-Cut encoding on ten variables, both searches have 252 leaves; 248 linear-program calls find no new cuts. Exhaustive enumeration on 12 variables gives the predicted 924 strict local optima and only 2.1483 bits of information. As Proposition 11 indicates, saturated comparisons require collective structural progress.

Local identities, counting bounds, and certificate rules are proved; whole-search evidence is experimental. The global frontier budget and a fixed-base algorithm for growing density remain desired results. No comprehensive literature survey or general novelty claim is intended.

References

[1] A. S. Kulikov and K. Kutzkov, *New Bounds for MAX-SAT by Clause Learning*, CSR 2007, LNCS 4649, pp. 194–204. Publisher DOI; authors' presentation consulted.

[2] D. Gavinsky, S. Lovett, M. Saks and S. Srinivasan, *A Tail Bound for Read-k Families of Functions*, Random Structures & Algorithms 47(1), 2015, pp. 99–108. arXiv:1205.1478.

[3] *Exploring the Branching Frontier for Max 2-SAT*, working note, 7 October 2026, Sections 3–4. Local source: `max2sat_branching_frontier.tex`.