Max 2-SAT by Early Constraint-Guided Enumeration

A density-independent bound for random signs on almost regular graphs

8 October 2026

Abstract

We prove that the branching search can stop learning after assigning half the variables and then enumerate only completions permitted by the sum of its learned constraints. For any fixed simple graph of minimum degree $d \geq 6$ and maximum degree D, independently uniform literal signs give an exact deterministic polynomial-space algorithm with running time $O^*((2e^{-d/(1250D)})^n)$ except on a set of signings of probability at most $3e^{-nd/(1250D)}$. In particular, every regular interaction graph gives a base below 1.999, independently of its degree. The proof counts all generated completions, including exceptional prefixes. It does not require a conflict at the switching depth or a spectral hypothesis. The input guarantee is probabilistic over signs, not a worst-case bound for every signing of an almost regular graph. Constants are deliberately conservative, and no literature novelty claim is made.

1 The input model and result

Fix a simple graph G on n labeled vertices. Each edge uv contributes one clause $(\ell_u \vee \ell_v)$, whose two literal signs are independent uniform elements of $\{-1, +1\}$. All signs on distinct incidences are independent. There are no initial unit clauses. The graph and a vertex order are fixed before the signs are drawn. The graph itself can be arbitrary, including a complete graph; it need not be randomly generated.

Write $d = \min_v \deg(v)$ and $D = \max_v \deg(v)$. These denote the minimum and maximum graph degrees, not the mean squared row norm used in the explicit-class note. All logarithms without a subscript are natural.

Theorem 1 (Early enumeration)**.** *There is a deterministic algorithm that is exact on every instance in this model and uses polynomial space. If $d \geq 6$, then with probability at least $1 - 3e^{-nd/(1250D)}$ over the signs, its running time is*

$$O^*\left((2e^{-d/(1250D)})^n\right).$$

The algorithm branches in the fixed order through depth $T = \lceil n/2 \rceil$, learning the usual constraint in each nonpreferred child. It then freezes those constraints and enumerates completions of their summed inequality. No contradiction at depth T is required.

For d-regular graphs, the base is $2e^{-1/1250} \simeq 1.99840064 < 1.999$. More generally, $D/d \leq R$ for any fixed R gives a fixed base below two. Degrees may grow with n, up to $n - 1$; in the regular case the clause density is $d/2$. The expectation of the running time satisfies the stronger bound $O^*((2e^{-d/(625D)})^n)$. The algorithm does not need to recognize a typical signing or know R.

This is a precisely specified random-input result. It is not a theorem for all signings of regular graphs, and it does not supply a combinatorial membership test for the typical signings. The earlier notes already obtain density-independent bounds in this random-sign model by waiting for conflicts [3]. The point here is to justify an earlier switch to enumeration, using a different quantity in the analysis.

2 Algorithm, exactness, and cost

Use Boolean values $\sigma_v \in \{0,1\}$. At step i, let Δ_i be the number of positive occurrences minus negative occurrences of x_i in residual 2-clauses, plus twice the corresponding difference in residual unit clauses, after assigning $1,\dots,i-1$. Let D_i^+ and D_i^- be the numbers of neighbors later and earlier in the fixed order. The preferred literal is positive if $\Delta_i \geq 0$, and negative otherwise. In the nonpreferred child learn

$$L_i \leq k_i^0, \qquad k_i^0 = \frac{D_i^+ - |\Delta_i|}{2} - 1, \tag{1}$$

Here L_i counts one bad value per later neighbor: in a clause containing the preferred literal of x_i, the neighbor value is bad if its literal is false; in a clause containing the other literal of x_i, it is bad if its literal is true. This is the previous branching rule [2, 1]. The right-hand side is integral because Δ_i and D_i^+ have the same parity. Negative allowances can be cut immediately.

For clarity, the upper-bound analysis uses the *uncut process*: generate the constraints for every prefix, even if a negative allowance or an earlier test would already have killed it. Early cuts can only reduce the actual work. No new constraints are created after step T.

At a prefix $\alpha \in \{0,1\}^T$, substitute its values into every created constraint. If the remaining constraints are $L_c(y) \leq k_c$, put $K = \sum_c k_c$. For each free variable w, let m_w^b count the occurrences made true by $y_w = b$. Orient its cheaper value as $z_w = 0$ and define

$$c_w = |m_w^1 - m_w^0|, \qquad B = K - \sum_w \min\{m_w^0, m_w^1\}. \tag{2}$$

The sum of the constraints is equivalent to $\sum_w c_w z_w \leq B$. Let $N_F(\alpha)$ be its number of Boolean solutions, including zero when $B < 0$.

Generate those solutions by depth-first search, pruning whenever the current nonnegative cost exceeds B. Evaluate the original Max 2-SAT score on each generated complete assignment. Testing every individual learned constraint as well is optional: the summed condition is a necessary relaxation, and extra candidates are still valid assignments of the original soft optimization problem.

Lemma 2 (Exactness and enumeration cost)**.** *The algorithm preserves an optimum and has time*

$$O^*\left(2^T + W(F)\right), \qquad W(F) = \sum_{\alpha \in \{0,1\}^T} N_F(\alpha), \tag{3}$$

using polynomial space.

Proof. For a fixed prefix and suffix, the score of the preferred value minus that of the nonpreferred value at decision i is $L_i - (D_i^+ - |\Delta_i|)/2$. Consequently, violating (1) means that switching to the preferred value is no worse. Choose the first optimal assignment in the full search-tree order that visits preferred children first. If it violates any learned constraint on its path, flipping that decision gives an equally good assignment earlier in that order, a contradiction. Thus some optimum satisfies all its learned constraints, and hence their sum.

For a fixed prefix with $N = N_F(\alpha) > 0$, every retained generator prefix extends to a permitted completion by taking the cheaper value on every remaining variable. At each generator depth there are at most N retained nodes, and there are at most $n - T + 1$ depths. Rejected children add only a constant factor. If $N = 0$, the summed inequality has $B < 0$ and is rejected immediately. Thus each prefix costs $\mathrm{poly}(n)(N+1)$, yielding (3). Polynomial-size constraints and a depth-first traversal give polynomial space. Retaining or recomputing a polynomial number of integer counters suffices; a table over exponentially many prefixes is unnecessary. □

3 Counting completions instead of waiting for a conflict

Let $\sigma \in \{0,1\}^n$ be a uniformly random complete assignment, independent of the formula. Run its first T decisions through the uncut process, and let $\mathcal{C}_T$ denote the created constraints. For c created at i, let $L_c(\sigma)$ count all its bad values on the later neighbors, before any substitutions. Define

$$S_T = \sum_{c \in \mathcal{C}_T} \left(\frac{|\Delta_c|}{2} + 1 \right), \tag{4}$$

$$Q_T^{\text{all}} = \sum_{c \in \mathcal{C}_T} \left(L_c(\sigma) - \frac{D_c^+}{2} \right). \tag{5}$$

The superscript distinguishes this from the earlier Q_T, which counted only support variables assigned by depth T. Here all support variables are evaluated, but only constraints created by time T are used.

Lemma 3 (Candidate-mass identity)**.** *For every complete assignment in the uncut process,*

$$\sum_{c \in \mathcal{C}_T} (L_c(\sigma) - k_c^0) = S_T + Q_T^{\text{all}}.$$

Consequently,

$$\frac{\mathbb{E}_F W(F)}{2^n} = \mathbb{P}_{F,\sigma} \left[S_T + Q_T^{\text{all}} \le 0 \right]. \tag{6}$$

Proof. Substitute (1) and add. For a fixed F, the number of full assignments satisfying the summed condition belonging to their own prefix is precisely $W(F)$. Divide by 2^n and average over F. □

This identity replaces the requirement that an entire prefix be infeasible. A prefix can have many candidates and still contribute little to the total in (3). The proof averages their actual counts, so unusually expensive prefixes are included.

4 Two lower-tail estimates

Let H_i reveal the signs of vertices $1, \dots, i$ in all their incident clauses, together with $\sigma_1, \dots, \sigma_i$. Future endpoint signs are not revealed. The uncut process uses this filtration; we never condition it on surviving an earlier cut. A fixed order is important for this exposure argument.

4.1 Accumulated shortfall

At step i, let r_i be the number of earlier neighbors whose literal in their clause with i is false. This is determined by H_{i-1}. Conditional on H_{i-1}, the gap Δ_i is a sum of independent uniform signs: D_i^+ signs of weight one and r_i signs of weight two. Put $Y_i = D_i^+ + 4r_i$.

We use an elementary moment bound rather than the optimal Khintchine constant. For a Rademacher sum Z with variance v, expansion gives $\mathbb{E}Z^4 \le 3v^2$. Hölder's inequality gives $\mathbb{E}Z^2 \le (\mathbb{E}|Z|)^{2/3}(\mathbb{E}Z^4)^{1/3}$, hence

$$\mathbb{E}|Z| \ge \sqrt{v/3}.$$

The bound is also valid when $v = 0$.

Let X_i be the contribution of decision i to S_T. Given its gap, the decision is nonpreferred with probability $1/2$. Thus

$$\mathbb{E}[X_i \mid H_{i-1}] \geq \frac{\sqrt{Y_i}}{4\sqrt{3}} + \frac{1}{2} =: \mu_i,$$
$$\mathbb{E}[X_i^2 \mid H_{i-1}] \leq \frac{Y_i}{8} + \frac{\sqrt{Y_i}}{2} + \frac{1}{2} \leq \frac{D}{2} + \sqrt{D} + \frac{1}{2} \leq D,$$

where $Y_i \leq 4D$ and $D \geq 6$. For $X_i \geq 0$, the inequality $e^{-\lambda X_i} \leq 1 - \lambda X_i + \lambda^2 X_i^2/2$ implies a conditional exponential-moment bound. Multiplying its compensated versions and taking $\lambda = a/(TD)$ gives

$$\mathbb{P}\left[S_T < \sum_{i \leq T} \mu_i - a\right] \leq e^{-a^2/(2TD)}. \tag{7}$$

It remains to lower-bound the sum of the predictable means. The indicators of earlier endpoint literals being false are independent fair coins: conditional on all of σ, they use distinct independent incidence signs, and their joint distribution does not depend on σ. Thus $r_i \sim \mathrm{Bin}(D_i^-, 1/2)$, with

$$\mathbb{E}Y_i = D_i^+ + 2D_i^- \geq d, \qquad \mathrm{Var}(Y_i) = 4D_i^- \leq 2\mathbb{E}Y_i.$$

For a nonnegative random variable Y of mean $\mu > 0$,

$$\mathbb{E}\sqrt{Y} \geq \sqrt{\mu} - \frac{\mathrm{Var}(Y)}{2\mu^{3/2}}.$$

This follows by averaging the pointwise inequality $\sqrt{z} \geq 1 + (z-1)/2 - (z-1)^2/2$ for $z \geq 0$; after writing $z = t^2$, the difference factors as $t(t-1)^2(t+2)/2 \geq 0$. It follows that $\mathbb{E}\sqrt{Y_i} \geq \sqrt{D_i^+ + 2D_i^-} - 1$. The positive $1/2$ in μ_i pays for this subtraction, so

$$\mathbb{E}\sum_{i \leq T} \mu_i \geq \frac{T\sqrt{d}}{4\sqrt{3}} =: \mu_*.$$

Let e_P count edges internal to the first T vertices. Changing one of its earlier-endpoint coins changes $\sum_i \mu_i$ by at most $1/(2\sqrt{3})$. The bounded-differences inequality therefore gives

$$\mathbb{P}\left[\sum_{i \leq T} \mu_i < \mu_* - b\right] \leq e^{-24b^2/e_P} \leq e^{-48b^2/(TD)}. \tag{8}$$

If $e_P = 0$, the sum is deterministic and this failure probability is zero. Combining (7)–(8) controls S_T.

4.2 All support contributions

Reveal variables through n, but create no more constraints after T. When vertex w is revealed, its contribution to Q_T^{all} is

$$\sum_{\substack{i<w,\ i\leq T \\ i \text{ created a constraint}}} \left([\sigma_w \text{ is bad in the constraint of } i] - \frac{1}{2}\right),$$

with only adjacent i included. Conditional on H_{w-1}, the creator set is fixed. The bad values use distinct unseen signs of w and are independent fair coins. Multiplication by the common independent value of σ_w preserves their joint uniform distribution.

Let a_w count neighbors $i < w$ with $i \le T$, whether or not they created a constraint. The conditional moment generating function of the negative contribution is at most $\cosh(\lambda/2)^{a_w} \le e^{\lambda^2 a_w/8}$. If $e_\times$ counts edges from the prefix to its complement, then

$$\sum_w a_w = e_P + e_\times \le TD.$$

Multiplying the conditional bounds and optimizing λ proves

$$\mathbb{P}[Q_T^{\text{all}} < -c] \le e^{-2c^2/(e_P+e_\times)} \le e^{-2c^2/(TD)}. \tag{9}$$

No independence between S_T and Q_T^{all} is asserted or needed.

5 Completing the running-time proof

Choose

$$a = \frac{2}{25}T\sqrt{d}, \qquad b = \frac{1}{100}T\sqrt{d}, \qquad c = \frac{1}{20}T\sqrt{d}.$$

Their sum is $(7/50)T\sqrt{d}$, strictly less than $\mu_* = T\sqrt{d}/(4\sqrt{3})$. Outside the three exceptional events, $S_T + Q_T^{\text{all}} > 0$. The exponents in (7), (8), and (9) are at least, respectively,

$$\frac{2Td}{625D}, \qquad \frac{3Td}{625D}, \qquad \frac{Td}{200D}.$$

Hence Lemma 3 yields the following bound for *every* $1 \le T \le n$:

$$\mathbb{E}_F W(F) \le 3 \cdot 2^n e^{-2Td/(625D)}. \tag{10}$$

By Markov's inequality,

$$\mathbb{P}_F\left[W(F) > 2^n e^{-Td/(625D)}\right] \le 3e^{-Td/(625D)}. \tag{11}$$

For $T = \lceil n/2 \rceil$, the right-hand side is at most $3e^{-nd/(1250D)}$, and outside this exceptional set

$$W(F) \le (2e^{-d/(1250D)})^n.$$

The 2^T term in (3) is smaller up to a constant factor. This proves Theorem 1. Applying (10) directly to the cost bound proves the stated expectation bound. □

Earlier switching. For any fixed $\tau \in (0,1)$, taking $T = \lceil \tau n \rceil$ instead gives, with failure probability at most $3e^{-\tau nd/(625D)}$,

$$O^*\left(2^{\tau n} + 2^n e^{-\tau nd/(625D)}\right).$$

Thus every fixed positive switching fraction gives a fixed saving for bounded D/d. Halfway is a simple concrete choice, not a required threshold and not an optimized one.

6 Interpretation and limitations

The conflict-only analysis bounds the number of prefixes with any remaining work. This argument bounds their *total remaining work*. It pays for a prefix whose summed constraint is satisfiable but admits few assignments, and handles expensive prefixes through an expectation bound followed by Markov's inequality. No typical-prefix or median-cost assumption is substituted for that calculation.

The algorithm can deliberately do no conflict checks before T and still satisfy the theorem. Earlier checks can be added to the same fixed search without increasing its cost. Adaptive ordering during the first phase is not covered: inspecting future signs to choose a variable can invalidate the late-exposure argument. The final budget generator may use any variable order because its retained prefixes extend to solutions of the same frozen inequality. Further learning would require preserving that inherited inequality or another valid cost certificate.

The result establishes the user's proposed early-enumeration mechanism for a well-defined random-sign input model, with an elementary proof. It neither proves the general growing-density conjecture nor resolves which deterministic interaction patterns guarantee the same bound. The constants were chosen for a transparent argument, not to improve the numerical base in the previous random-sign theorem.

7 Computational checks

The companion program `explore_early_enumeration.py` checks the algorithm on small signed regular graphs, including degrees below the theorem's minimum to test exactness separately from the running-time guarantee. It compares the optimum with exhaustive search, compares budget enumeration and exact dynamic-program counts with direct counts, and verifies the identity of Lemma 3 on every complete assignment. All 44 tested instances on 6, 8, 10, and 12 variables preserved the optimum; 1,408 prefix counts and 65,024 full-assignment identities passed. Its results are recorded in `early_enumeration_checks.json`. These finite checks validate the implementation and algebra; the probabilistic running-time guarantee follows from the proof above.

References

[1] *Exploring the Branching Frontier for Max 2-SAT*, working note, 7 October 2026. Section 3: a joint measure from exact weighted-sum counts. Local source: `max2sat_branching_frontier.tex`.

[2] *A Simplified Plan for Max 2-SAT: One Search, One Count, One Key Lemma*, working note, 8 October 2026. Local source: `max2sat_plan_key_lemma.tex`.

[3] *The Key Lemma for Random Signs*, working note, 8 October 2026. Local source: `max2sat_key_lemma_proof.tex`. The shortfall and late-exposure arguments are adapted here, with an elementary fourth-moment constant and a completion-count objective.