Pre-Branching Constraints for Max 2-SAT

Sound learning, simultaneous counting, and exact enumeration

12 October 2026

Abstract

We give a common correctness invariant for constraints introduced before branching: every comparison preserves the same optimal assignment, chosen by a fixed secondary order. Single-variable comparisons yield guarded cardinality constraints, and partial improvement certificates yield ordinary clauses. Pair exchanges give a directly checkable source of binary clauses and exact exponential savings when they contain a large matching or long disjoint chains. For the random-sign model, we prove a separate counting theorem: on any fixed interaction graph, with arbitrary fixed initial unit clauses, the expected number of assignments satisfying all single-variable comparisons is at most $2^{n/2}$. The proof uses a read-two entropy inequality, not independence of the comparisons or any degree bound. This is a candidate-count bound, not an enumeration-time bound. We state the remaining Las Vegas enumeration target precisely. The local derivations are proved here; literature novelty is not claimed.

1 What is being constrained?

Let $F(x)$ be the number of satisfied soft clauses of an unweighted Max 2-SAT instance, including unit clauses. There are initially no genuine hard feasibility constraints. All assignments belong to the original optimization domain. We may also use the equivalent quadratic objective

$$F(x) = c + \sum_u h_u x_u + \sum_{u<v} J_{uv} x_u x_v, \qquad x \in \{0,1\}^n. \tag{1}$$

Units affect c, h; binary clauses determine J. The deterministic rules below also apply to rational coefficients of polynomial encoding length.

Fix a priority order on the variables and a preferred bit a_u for each variable. Rank complete assignments first by F, then lexicographically by agreement with these preferred bits. Call the resulting strict total order Φ, and let $x^\star$ be its unique maximum. Thus $x^\star$ is an optimum of the original problem. The priority and preferred bits are fixed for all constraints that will be combined.

Proposition 1 (Common representative)**.** *For any collection of maps $T : \{0,1\}^n \to \{0,1\}^n$, the constraints*

$$\Phi(x) \geq \Phi(T(x))$$

hold simultaneously at $x^\star$. Any sound consequences of these constraints can therefore be added together without losing every optimum.

Proof. No assignment has rank greater than the maximum $x^\star$. □

The maps may change one variable, exchange two values, or replace a specified pattern on a block. They may be selected adaptively or randomly. We do not need to know $x^\star$ to construct the comparisons. Randomness selects which valid tests to use; it does not guess that

an unjustified inequality holds. If the input has genuine hard constraints, a replacement must additionally be feasible, or the comparison must be guarded by its feasibility. That extension is not assumed here.

Compatibility with simplification. Strict domination for the soft objective is safe. A weak domination fixing must respect the secondary order whenever equality is possible, or have an additional compatibility proof. More generally, reductions need a reconstruction invariant preserving $x^\star$ (or an alternative joint proof). Existing path-dependent pruning constraints cannot simply be mixed with a different convention for resolving ties.

For example, take $F = (u \vee v)$ and prefer zero at both variables. The two single-variable comparisons below retain exactly 01 and 10. Ordinary weak pure-literal domination can fix $u = 1$ and then $v = 1$ while preserving an optimum of the soft objective at each step; doing so ignores the new constraints and eliminates both retained assignments. This illustrates why separate preservation of *some* optimum is insufficient. A tie-aware implementation avoids this conflict.

2 Single-variable constraints and short certificates

Write

$$D_u(y) = F(u = 1, y) - F(u = 0, y) = h_u + \sum_{v \neq u} J_{uv} y_v.$$

For readability, first take $a_u = 1$. The full pre-branching constraint is

$$C_u : \quad (u = 1 \Rightarrow D_u(y) \geq 0) \ \wedge \ (u = 0 \Rightarrow D_u(y) \leq -1). \tag{2}$$

For $a_u = 0$, use $D_u \geq 1$ on the $u = 1$ side and $D_u \leq 0$ on the $u = 0$ side. These thresholds use integer scores; strict inequalities give the corresponding rational-score formulation. The guards involving u remain present until its value is fixed.

In the occurrence notation, let

$$k = d_1(u) - d_1(\neg u), \quad r = d_2(u), \quad q = d_2(\neg u), \quad G = r + k - q.$$

Let A count true partner literals of u and B true partner literals of $\neg u$, counting occurrences. Then

$$D_u = G - A + B = L - (q - k), \qquad L = (r - A) + B. \tag{3}$$

Thus, with ties favoring $u = 1$, the two guarded inequalities are

$$\begin{aligned} &u = 1 \Rightarrow L \geq q - k, \\ &u = 0 \Rightarrow L \leq q - k - 1. \end{aligned} \tag{4}$$

The second is the usual pruning constraint. Its one-neighborhood consequence is

$$u = 0 \Rightarrow A \geq G + 1. \tag{5}$$

This uses the user's occurrence gap: unit and binary occurrences count equally. It does not change that definition to the differently weighted quantity used to select a branching orientation in some earlier notes.

The reverse upper-bound form, obtained by complementing every pruning literal, is

$$u = 1 \Rightarrow A + (q - B) \leq r + k.$$

The two full constraints allocate ties to exactly one value. Requiring strict improvement on both sides is unsound. Dropping a nonnegative term gives a valid weaker consequence; independently splitting an allowance into smaller budgets does not.

Proposition 2 (Partial certificates become clauses)**.** *Let α be a partial assignment not fixing u. If every completion of α has $D_u > 0$, or has $D_u \geq 0$ and $a_u = 1$, then the ordinary clause $\neg\alpha \vee u$ is sound under Proposition 1. The analogous negative certificate gives $\neg\alpha \vee \neg u$.*

Proof. Any assignment violating the clause improves in Φ after flipping u. □

The certificate is efficiently checkable. Substitute α into D_u, leaving $b + \sum_{v \in R} c_v y_v$. Its exact unconstrained range is

$$\left[b + \sum_{v \in R} \min(0, c_v), \quad b + \sum_{v \in R} \max(0, c_v) \right]. \tag{6}$$

This test may ignore older hard pruning constraints and is still sound. Using them to obtain a stronger certificate requires a correct joint test.

For the simple-clause case, if $p = q - k \geq 1$, any p distinct pruning literals of L that are all true certify $u = 1$ (ties favoring one). They give a clause of width $p + 1$ including u. When $r + k \geq 0$, for reverse strict improvement, $r + k + 1$ true literals in the complemented list certify $u = 0$, giving width $r + k + 2$. Such witnesses must actually exist; the threshold can exceed the list length. Nonpositive certificate thresholds are handled directly by the range test and can give a unit clause. Multiplicities or opposite literals on one variable require the occurrence-aware range test above. A full cardinality constraint can represent exponentially many such clauses.

Proposition 3 (One bit per full comparison)**.** *For every fixed formula and variable u, exactly 2^{n-1} complete assignments satisfy C_u.*

Proof. For each assignment to the other variables, exactly one value of u is preferred, with the specified tie convention. □

Consequently, a larger literal gap does not improve the unconditional one-bit saving of the *full guarded comparison*. Its importance is that the preferred value can be certified after fewer neighboring values are exposed, or by a shorter learned clause. Joint information and early detectability are different quantities.

3 A deterministic counting baseline: independent centers

Proposition 4. *Let T contain s variables with $J_{uv} = 0$ for all distinct $u, v \in T$. Exactly 2^{n-s} assignments satisfy $\bigwedge_{u \in T} C_u$. They can be generated and scored in $O^*(2^{n-s})$ time and polynomial space.*

Proof. Assign the outside variables. Each center's comparison now determines its unique preferred value independently of the other centers. Enumerate the 2^{n-s} outside assignments and compute these responses. □

The external neighborhoods may coincide completely and have linear size. Repeated information can fix different center variables. This is the familiar independent-set mechanism; balanced bipartite interaction graphs give $O^*(2^{n/2})$ time. It is a useful baseline rather than a new general algorithm. Identification of T is part of the algorithm: the proposition assumes it is supplied or efficiently found.

4 A counting theorem for arbitrary graphs with random signs

Fix any simple graph $G = (V, E)$, any initial unit clauses, and the secondary order, all before drawing the binary-clause signs. For each edge, choose one of its four literal-sign pairs uniformly and independently. Let

$$Z(F) = |\{x : \ C_u(x) \text{ holds for every } u\}| .$$

There is no restriction on minimum degree, maximum degree, regularity, or the number of fixed initial units.

Theorem 5 (Read-two count)**.** *For each vertex u, let p_u be the probability, over the clause signs, that its preferred response is one, for any fixed assignment to the other variables. This probability is independent of that assignment. Then*

$$\boxed{\mathbb{E}_F Z(F) \le \prod_u \left(\sqrt{p_u} + \sqrt{1-p_u}\right) \le 2^{n/2}.} \tag{7}$$

In particular, for every fixed $0 < \varepsilon < 1/2$,

$$\mathbb{P}_F \left[Z(F) > 2^{(1/2+\varepsilon)n} \right] \le 2^{-\varepsilon n}. \tag{8}$$

Proof. Fix a full assignment x. Write $b_u = d_1(u) - d_1(\neg u)$ and $d_u = \deg_G(u)$. The distribution of $D_u(x_{-u})$ is

$$b_u + \sum_{j=1}^{d_u} W_j, \qquad \mathbb{P}[W_j = -1] = \mathbb{P}[W_j = 1] = \tfrac{1}{4}, \quad \mathbb{P}[W_j = 0] = \tfrac{1}{2}. \tag{9}$$

Indeed, a clause contributes zero when its partner literal is true and otherwise contributes the sign of its literal on u. Independent uniform incidence signs make this distribution independent of x_{-u}. Thus $\mathbb{P}_F[C_u(x)] = p_u$ if $x_u = 1$, and $1 - p_u$ if $x_u = 0$.

The events $C_u(x)$ are not independent. However, each independent four-valued edge label is used only by the comparisons at its two endpoints. The read-two form of the generalized Hölder/Shearer inequality [1, 2] gives

$$\mathbb{P}_F \left[\bigwedge_u C_u(x) \right] \le \prod_u \mathbb{P}_F[C_u(x)]^{1/2}. \tag{10}$$

For completeness, in this finite uniform setting it follows directly from entropy. Let $\mathcal{E}$ be the set of edge-label assignments satisfying all the events, and $\mathcal{A}_u$ the allowed assignments to the d_u incident edge labels. If $\mathcal{E}$ is nonempty, apply Shearer's entropy inequality to the uniform distribution on $\mathcal{E}$. Every edge coordinate is covered twice, so

$$2 \log_2 |\mathcal{E}| \le \sum_u \log_2 |\mathcal{A}_u| = 4|E| + \sum_u \log_2 \mathbb{P}_F[C_u(x)].$$

Subtracting $4|E|$ proves (10); an empty event is trivial. Summing over x factorizes the right-hand side:

$$\mathbb{E}_F Z(F) \le \sum_x \prod_u \begin{cases} \sqrt{p_u}, & x_u = 1, \\ \sqrt{1-p_u}, & x_u = 0 \end{cases} = \prod_u (\sqrt{p_u} + \sqrt{1-p_u}).$$

Each factor is at most $\sqrt{2}$. Markov's inequality yields (8). □

The inequality of Shearer used above follows from the entropy chain rule: expand the entropy of every coordinate subset in the same global order; conditioning on only the earlier coordinates of that subset gives at least the corresponding conditional entropy given all earlier coordinates; then sum, using the fact that each coordinate occurs twice.

The marginal can be computed exactly. With ties favoring one,

$$p_u = 4^{-d_u} \sum_{\substack{-d_u \le s \le d_u \\ b_u + s \ge 0}} \binom{2d_u}{d_u + s}.$$

Replace ≥ 0 by > 0 when ties favor zero. This includes isolated variables. Their comparison fixes the preferred optimal value, so they contribute a factor one, not two. Without a tie convention, the empty formula would have 2^n weak local optima and the theorem would fail.

What the theorem establishes. For instance, take $\varepsilon = 1/4$. With probability at least $1 - 2^{-n/4}$ the entire constraint system has at most $2^{3n/4} \simeq 1.682^n$ solutions. The expectation has the stronger base $\sqrt{2}$. These are input-distribution statements on *counts*. They do not yet give these running-time bounds. The signs must be independent at clause incidences; randomly complementing the names of variables in a fixed adversarial formula does not create that model. The tie convention must also be fixed independently of the signs for the stated marginal factorization.

If comparisons are imposed only for a fixed set T, the same proof, with unrestricted local events at the other vertices, gives

$$\mathbb{E}_F \left| \{x : \bigwedge_{u \in T} C_u(x)\} \right| \le 2^{n-|T|} \prod_{u \in T} (\sqrt{p_u} + \sqrt{1 - p_u}) \le 2^{n-|T|/2}.$$

The proof requires neither spectral assumptions nor a bound on overlap. This is the principal counting result of this note. Local maxima are a classical object in exact Max 2-SAT algorithms [3]; a focused literature comparison is still needed to establish novelty of this particular formulation and bound.

5 Pair exchanges give short pre-branching clauses

Single-variable comparisons need not be the only permissible constraints. Compare the states $(x_u, x_v) = (1, 0)$ and $(0, 1)$. Their score difference is

$$E_{uv}(y) = h_u - h_v + \sum_{w \notin \{u,v\}} (J_{uw} - J_{vw}) y_w. \tag{11}$$

The internal edge uv cancels. Its exact minimum over all outside assignments is

$$\lambda_{uv} = h_u - h_v + \sum_{w \notin \{u,v\}} \min(0, J_{uw} - J_{vw}). \tag{12}$$

Proposition 6 (Unconditional exchange clause)**.** *If $\lambda_{uv} > 0$, or if $\lambda_{uv} = 0$ and the secondary order prefers state $(1, 0)$ to $(0, 1)$, then the binary clause*

$$\boxed{x_u \vee \neg x_v} \qquad (x_v \Rightarrow x_u) \tag{13}$$

can be added before branching. Any collection passing these tests with the common secondary order preserves $x^\star$.

Proof. Every violating assignment has $(x_u, x_v) = (0, 1)$. Exchanging these values increases Φ, by (11)–(12). □

Identical interaction rows outside the pair reduce the test to comparing h_u and h_v. More generally the field advantage need only compensate for the total unfavorable row discrepancy:

$$h_u - h_v \geq \sum_{w \notin \{u,v\}} \max(0, J_{vw} - J_{uw}),$$

with the stated tie condition. Hence exact twins are unnecessary. Both variables can still be individually undominated. All pair tests are computable in $O(n^3)$ arithmetic operations using a dense matrix. Variables may be complemented once before applying the test.

After exposing a partial assignment α, the same minimum test on the residual expression gives the guarded clause $\neg\alpha \vee x_u \vee \neg x_v$. This is one concrete way that branching on discrepancy coordinates creates new short constraints.

Theorem 7 (Matching and chain savings)**.** *Suppose the valid unconditional exchange clauses contain r clauses on pairwise disjoint variable pairs. They admit exactly*

$$3^r 2^{n-2r} = 2^n (3/4)^r \tag{14}$$

assignments. Enumerating these assignments solves the original soft instance in this time up to polynomial factors, with polynomial space.

More generally, suppose selected clauses form disjoint chains on $s_1, \ldots, s_q$ variables, requiring ones to precede zeros in each chain. Then the corresponding bound is

$$2^{n-\sum_i s_i} \prod_i (s_i + 1) = 2^{n-\Gamma}, \qquad \Gamma = \sum_i (s_i - \log_2(s_i + 1)). \tag{15}$$

This too is an exact polynomial-space running-time bound.

Proof. A pair has three allowed states. A chain of length s_i has $s_i + 1$ allowed cut positions. Enumerate these choices and the remaining free bits, and score every generated assignment. There is no dead-prefix overhead: every generated prefix extends to a state of this relaxation. Its domain contains $x^\star$, even if additional valid constraints are ignored during generation. □

A linear matching gives a fixed exponential saving independent of clause density. A maximum matching in the certified-pair graph can be found in polynomial time; even a greedy maximal matching loses at most a factor two in matching size. Thus this is a checkable class, not a condition involving unknown numbers of satisfying assignments. Longer chains use overlap constructively: a chain on all variables reduces the candidate set to $n + 1$ assignments.

A dense redundant example that is resolved. For even n, put $(x_u \vee x_v)$ and $(\neg x_u \vee \neg x_v)$ on every pair. If k bits are one, the score is

$$\binom{n}{2} + k(n - k).$$

All $\binom{n}{n/2}$ balanced assignments are strict single-flip local optima, so every choice of single-variable tie preferences retains them. This standard example is discussed in [3]. But its exchange differences vanish identically. Choose a priority order preferring ones; the adjacent exchange clauses impose one chain, leaving $n + 1$ assignments, and only one survives the single-variable comparisons as well. The redundant family therefore suggests an additional learning rule rather than an impossibility for the algorithmic program.

The matching rule overlaps with the existing near-twin and group-count notes [4, 5]. The contribution here is its explicit encoding as a compatible pre-branching clause, its discrepancy-versus-field test, and its integration with counting. It does not subsume the group-count solver, whose cuts allow other forms of arbitrary internal structure.

6 General block certificates and their counting effect

Fix a block S, an excluded pattern $a \in \{0,1\}^S$, and a replacement $b \in \{0,1\}^S$. Quadraticity implies

$$\begin{aligned} F(b,y) - F(a,y) &= \kappa + \sum_{w \notin S} c_w y_w, \\ \kappa &= \sum_{u \in S} h_u(b_u - a_u) + \sum_{\{u,v\} \subseteq S} J_{uv}(b_u b_v - a_u a_v), \\ c_w &= \sum_{u \in S} J_{uw}(b_u - a_u). \end{aligned} \tag{16}$$

Thus $\kappa + \sum_w \min(0, c_w)$ is an exact, polynomial-time test for unconditional domination by this *specified* replacement. Strict positivity, or zero with a favorable secondary comparison, allows the ordinary nogood clause

$$\bigvee_{u \in S} (x_u \neq a_u).$$

The comparison of the two block patterns in the secondary order is independent of the outside assignment. Searching over all blocks or all replacements is not claimed to be polynomial.

For disjoint supports of widths $w_1, \ldots, w_t$, one forbidden pattern per support leaves exactly

$$2^n \prod_{i=1}^{t} (1 - 2^{-w_i})$$

assignments and gives an enumeration algorithm of that cost. Bounded width and linearly many such clauses suffice. Growing width alone gives no comparable constant saving from this product; overlap can help, as the chain example shows, but must be analyzed jointly.

7 Enumeration and Las Vegas targets

For a supplied exposed set K, suppose polynomial-time propagation of compatible constraints fixes at least δn variables outside K on all but a $2^{-\gamma n}$ fraction of assignments to K (infeasible assignments can be discarded). Assume $|K| \leq (1-\delta)n$. Enumerating K and then the remaining free bits costs

$$O^*\left(2^{n-\delta n} + 2^{n-\gamma n}\right). \tag{17}$$

This conditional theorem pays for all exposed assignments. Its missing ingredient in a new formula class is availability of such a K and the stated propagation bound, not the final summation.

Alternatively, randomize an exact search strategy. If an independent attempt finishes within B operations with probability at least $p > 0$, abort unfinished attempts at B and restart. Returning only after a complete exact search is a Las Vegas algorithm with expected time $O(B/p)$. In particular,

$$B = O^*(2^{(1-\delta)n}), \quad p \geq 2^{-\eta n}, \quad \eta < \delta \quad \Longrightarrow \quad \mathbb{E}T = O^*(2^{(1-\delta+\eta)n}).$$

Polynomial space is retained if each attempt has polynomial space and discarded attempt data are not accumulated without a bound. Keep the secondary convention fixed when retaining constraints across attempts.

What a direct random-order analysis must bound. For a fixed constraint system and a monotone rejection test, assign variables in a uniformly random permutation. Let q_t be the probability that a uniform assignment to its first t variables passes the test. The expected number of passing depth-t prefixes is $2^t q_t$, and the expected traversal cost, up to polynomial factors, is bounded by

$$1 + \sum_{t=0}^{n} 2^t q_t.$$

At depth n, if the test evaluates the whole constraint system, $2^n q_n = Z(F)$. A candidate-count theorem controls this final term. A direct search proof also controls earlier terms; a restart proof may instead establish a sufficiently frequent set of fast attempts.

For the random-sign class, Theorem 5 settles a strong counting target for the pre-branching constraints. Obtaining a Las Vegas enumerator with a comparable base remains open here. The earlier early-enumeration note [6] proves a different, weaker-base time bound under almost regularity by enumerating a tractable summed relaxation. That theorem is not automatically upgraded to $(\sqrt{2})^n$ by the count proved above.

8 Checks and the next mathematical questions

The companion `explore_prebranch_constraints.py` uses integer scores and exact rational probabilities. Its output is `prebranch_constraint_checks.json`. All checks passed:

- 100 formulas on 4–7 variables, 37,600 exact flip identities, 6,339 one-neighborhood implications, and preservation of the canonical optimum under simultaneous single-variable and exchange constraints.
- 12,204 exchange implications; 100 independent-center counts and 100 matching counts; 5,364 block-minimum checks and 1,547 block nogoods.
- Exhaustive enumeration of 12,497 signings across eight graph/unit/tie models, including all 4^6 signings of K_4 in three settings. Every fixed-assignment read-two inequality was checked using rational arithmetic.
- Complete-cut examples on $n = 6, 8, 10, 12$ variables: single-variable counts $20, 70, 252, 924$ respectively; chain counts $7, 9, 11, 13$; their conjunction has one assignment in each case.

These finite checks are sanity checks for the stated proofs, not asymptotic evidence or a substitute for them.

The existing exploratory command `python3 explore_two_sided.py combine` also provides a concrete compatibility warning. On its 300 test instances, mixing constraints registered with a fixed root orientation and path-dependent strict branching constraints lost the optimum in 17 cases. The branching-only baseline and the variant whose branching followed the registered orientation lost none in that run. This experiment is not an implementation of the full common-order system above; it confirms that an unproved mixture of conventions is a real correctness risk.

The companion script also checks the auxiliary identity

$$\mathbb{E}_a Z(F,a) = \sum_{x \text{ a weak single-flip local optimum}} 2^{-z(x)},$$

where a is a vector of independent uniform tie preferences and $z(x)$ counts zero-gain single flips at x. Each tied coordinate imposes one independent preferred-bit condition. This identity shows exactly what random tie choices can remove, and why strict local optima need other comparisons.

The next questions are concrete:

1. For random-sign inputs, can an exposure strategy or a counted relaxation enumerate the pre-branching comparison solutions without visiting almost all dead prefixes?
2. When exchange tests initially fail, can a small exposure set make a linear matching of tests succeed on enough branches, with the cost of the other branches explicitly included?
3. Can persistent redundancy of the comparisons be converted into chains, collective block certificates, or the group-count structures of the earlier note, with a uniform bound on the total search cost?

The local soundness rules, random-sign counting theorem, and matching/chain algorithms above are proved. A general availability theorem joining these alternatives is not claimed.

References

[1] H. Finner. A generalization of Hölder's inequality and some probability inequalities. *Annals of Probability* 20(4), 1893–1901, 1992. `https://doi.org/10.1214/aop/1176989534`.

[2] D. Gavinsky, S. Lovett, M. Saks, S. Srinivasan. A tail bound for read-k families of functions. 2012 preprint. `https://arxiv.org/abs/1205.1478`.

[3] M. B. Hastings. Local maxima and improved exact algorithm for MAX-2-SAT. 2016. `https://arxiv.org/abs/1610.07100`.

[4] *Near-Twin Neighborhoods as a Structural Exit*. Working note, 8 October 2026. `max2sat_near_twin_pairs.tex`.

[5] *Useful Constraints or Compression by Group Counts*. Working note, 10 October 2026. `max2sat_redundancy_and_group_counts.tex`.

[6] *Max 2-SAT by Early Constraint-Guided Enumeration*. Working note, 8 October 2026. `max2sat_early_enumeration.tex`.