The Soft-Count Measure for Adaptive Branching

Definition, one branching step, and examples

8 October 2026

Abstract

We define a complexity measure for the adaptive branching algorithm with learned pruning constraints and final enumeration. It is a soft count of the completions that respect the learned constraints. It is exactly additive under branching, it bounds the remaining work, and a new constraint changes it by an explicit factor. A constraint has a weight that grows as the constraint tightens and becomes infinite when the constraint assigns its variables. A new constraint lowers the measure exactly when, under the current soft count, its expected number of bad values exceeds its allowance. This is a precise form of a sufficiently new constraint. We work out one branching step and three small examples, and run the search on small formulas.

1 The search and its constraints

The algorithm branches on one free variable at a time, chosen adaptively. When it branches on x with preferred literal ℓ, the child in which ℓ is false learns a constraint on the free neighbours of x. For each clause $(\ell \vee m)$ the value of the neighbour that makes m false is *bad*, and for each clause $(\neg\ell \vee m)$ the value that makes m true is bad. The constraint says that at most k neighbours take their bad value, where $k = p - 1$ and p is the deficit of ℓ. Indeed, if p or more are bad, flipping x back to ℓ is no worse. Simplification rules such as domination and propagation may be applied. At the end, the completions respecting the learned constraints are enumerated.

At a node, a learned constraint i has a *support* N_i (its free variables), a bad value $\beta_i(w)$ for each $w \in N_i$, and a current *allowance* k_i. For a completion y of the free variables, $L_i(y)$ is the number of $w \in N_i$ with $y_w = \beta_i(w)$. When a support variable is assigned it leaves N_i, and if it took its bad value, k_i drops by one. The constraint is violated when $k_i < 0$, and *vacuous* when $k_i \geq |N_i|$.

2 The measure

Definition 1 (Soft count)**.** Give each constraint a weight $\lambda_i \geq 0$. For a free variable w and a value b, let A_w^b be the sum of λ_i over the constraints in which b is the bad value of w. The soft count of the node is

$$\Phi = \sum_y \prod_i e^{\lambda_i(k_i - L_i(y))} = e^{\sum_i \lambda_i k_i} \prod_{w \text{ free}} (e^{-A_w^0} + e^{-A_w^1}),$$

where y ranges over the completions of the free variables.

The two expressions agree because $\sum_i \lambda_i L_i(y) = \sum_w A_w^{y_w}$. Each completion is discounted exponentially in how much it violates each constraint. Under the *soft distribution*, the

distribution on completions proportional to these terms, the free variables are independent, and w takes the value b with probability

$$\pi_w(b) = \frac{e^{-A_w^b}}{e^{-A_w^0} + e^{-A_w^1}}.$$

Proposition 2 (Basic properties)**.** *The soft count has three properties.*

1. Φ *is at least the number of completions that respect every learned constraint. If* $\Phi < 1$*, no completion respects them all, and the node can be cut.*
2. *At the root,* $\Phi = 2^n$*.*
3. Additivity. *If* x *is free and the weights are kept, the children* $x = 0$ *and* $x = 1$ *have soft counts* $\Phi\,\pi_x(0)$ *and* $\Phi\,\pi_x(1)$*; together they make up exactly* Φ*.*

Proof. A completion respecting all constraints has $k_i - L_i(y) \geq 0$ for every i, so its term is at least 1. At the root there are no constraints. Fixing $x = b$ keeps the completions with $y_x = b$; in the product this replaces the factor of x by $e^{-A_x^b}$, and the constraints in which b is bad lose one unit of allowance. That gives $\Phi\,\pi_x(b)$. □

3 One branching step

Branch on x, with preferred value v and other value $\bar{v}$.

- *Preferred child* $x = v$. Every constraint containing x loses x from its support, and its allowance drops by one if v is its bad value. No constraint is learned. Its soft count is $\Phi\,\pi_x(v)$.
- *Other child* $x = \bar{v}$. The same updates, plus the new constraint c on the free neighbours of x, with allowance $k_c = p - 1$. Before c is added, its soft count is $\Phi\,\pi_x(\bar{v})$.

Lemma 3 (The factor of a new constraint)**.** *Adding* c *with weight* λ *multiplies the soft count of the child by*

$$F_c(\lambda) = e^{\lambda k_c} \prod_{w \in N_c} \Big(1 - q_w(1 - e^{-\lambda})\Big), \qquad q_w = \pi_w(\beta_c(w)),$$

where q_w *is the probability, under the soft distribution of the child, that* w *takes its bad value for* c*. In particular* $F_c(0) = 1$*, and the best weight gives* $F_c \leq 1$*.*

Proof. The new constraint adds λ to $A_w^{\beta_c(w)}$ for $w \in N_c$ and λk_c to the exponent, so the factor of w becomes $\pi_w(\text{good}) + \pi_w(\text{bad})e^{-\lambda}$. □

The derivative of $\ln F_c$ at $\lambda = 0$ is $k_c - \sum_{w \in N_c} q_w$. So:

> *A new constraint lowers the measure exactly when, under the current soft count, its expected number of bad values exceeds its allowance.*

This is the precise version of a sufficiently new constraint. On a fresh variable $q_w = \frac{1}{2}$. On a variable where the earlier constraints have the *same* bad value, q_w is small, so the new constraint adds little: it is redundant there. Where they have the *opposite* bad value, q_w is large, so it adds a lot.

The *information* of the step is the decrease of $\log_2 \Phi$:

$$I_x = -\log_2\Big(\pi_x(v) + \pi_x(\bar{v})\,F_c\Big) \;\geq\; 0.$$

The adaptive rule branches on the free variable with the largest I_x. A constraint that becomes vacuous gets weight 0: its factor was at least 1, so this lowers Φ.

4 The weights

A single constraint. With r free variables and allowance $k < r/2$, on fresh variables, the best weight is

$$\lambda = \ln \frac{r-k}{k},$$

and then the constraint's factor is $2^{rH(k/r)}/2^r$, where H is the binary entropy. So the weight grows as the constraint tightens. For $k = 0$ it is infinite: the bad values get weight 0, the constraint assigns all its variables, and propagation is the limiting case.

Re-optimizing at every node. We may choose all weights afresh at every node to minimize Φ. Write Φ^* for this minimum. For the two children,

$$\Phi^*(x = 0) + \Phi^*(x = 1) \;\le\; \Phi^*(\text{parent}).$$

Evaluate both children at the parent's optimal weights, with weight 0 for the new constraint. By additivity their soft counts add up to $\Phi^*(\text{parent})$, and each child's minimum is at most this value. So re-optimized weights still give a valid measure, and constraints near assigning their variables automatically receive large weights. $\ln \Phi$ is convex in the weights, so the minimum can be computed.

5 Examples

Example 4 (One constraint, allowance zero)**.** Let x_1 have the clauses $(x_1 \vee x_2)$, $(x_1 \vee x_3)$, $(x_1 \vee \neg x_4)$ and $(\neg x_1 \vee x_5)$. Its preferred value is 1, and $p = 1$. The child $x_1 = 0$ learns

$$[x_2 = 0] + [x_3 = 0] + [x_4 = 1] + [x_5 = 1] \le 0.$$

Here $\Phi = (1 + e^{-\lambda})^4$, which is 16, 3.50, 1.66 and 1 for $\lambda = 0, 1, 2, \infty$. Exactly one completion is permitted. Branching on x_2 at $\lambda = 1$ splits 3.501 into 2.559 for $x_2 = 1$ and 0.942 for $x_2 = 0$. At $\lambda = \infty$ the child $x_2 = 0$ has soft count 0 and is cut: this is propagation.

Example 5 (Redundant and new constraints)**.** The constraint "at most one of $y_1, \ldots, y_4$ is 1" (bad value 1 everywhere, allowance 1) is present with weight $\ln 3$. Then $\Phi = 9.48$, while 5 completions are permitted, and $q_w = \frac{1}{4}$ for bad value 1. A second constraint with allowance 1 arrives on the same variables.

bad values of the new constraint	q_w	best F_c	Φ	Φ^*	permitted
$1, 1, 1, 1$ (agrees)	$\frac{1}{4}$ each	1	9.48	9.48	5
$1, 1, 0, 0$ (half)	$\frac{1}{4}, \frac{1}{4}, \frac{3}{4}, \frac{3}{4}$	0.51	4.79	4.00	2
$0, 0, 0, 0$ (disagrees)	$\frac{3}{4}$ each	0.11	1.05	0	0

The agreeing constraint is redundant and gains nothing. The disagreeing one makes the node infeasible, and the re-optimized measure Φ^* detects this.

Example 6 (A full branching step)**.** Take the formula with the nine clauses

$$(x_1 \vee x_2),\ (x_1 \vee \neg x_3),\ (\neg x_1 \vee x_4),\ (\neg x_2 \vee x_3),\ (x_2 \vee x_5),$$
$$(x_3 \vee \neg x_6),\ (x_4 \vee \neg x_5),\ (\neg x_4 \vee x_6),\ (x_5 \vee x_6).$$

At the root, x_1 has gap $+1$ over three clauses, so its preferred value is 1 and $p = 1$. The child $x_1 = 0$ learns $[x_2 = 0] + [x_3 = 1] + [x_4 = 1] \le 0$, with infinite weight, so $\Phi = 4$: the variables $x_2 = 1$, $x_3 = 0$, $x_4 = 0$ are forced and x_5, x_6 are free. The candidates in this child:

- x_2 has gap $+2$ over two free neighbours, so $p = 0$. Its other child is cut at once, and the measure splits as $4 + 0$: $I = 0$, because the constraint had already forced x_2.
- x_3 has gap 0, so its preferred value is 1, which the learned constraint forbids. The other child learns $[x_2 = 1] + [x_6 = 1] \leq 0$, which contradicts $x_2 = 1$. Both children have soft count 0: the whole node is cut, because $x_3 = 0$ is dominated whenever $x_2 = 1$.
- x_4 has gap 0; its preferred child is forbidden, and the other child learns $[x_5 = 1] + [x_6 = 1] \leq 0$. The split is $0 + 1$, so $I = 2$ bits.
- x_5 and x_6 each give the split $2 + 1$, so $I = \log_2(4/3) = 0.415$ bits.

The adaptive rule takes x_3 and cuts the node. In a fixed order starting with x_2, this step gains nothing.

6 Small searches

The search branches by the adaptive rule or in index order. A new constraint gets its best weight, vacuous constraints get weight 0, and a node is cut when a constraint is violated or $\Phi < 1$. Every search returned the optimum.

n	d	no learning	fixed order	adaptive
10	3	2047	57	21
10	5	2047	81	37
12	4	8191	65	25
12	6	8191	99	29
12	8	8191	241	81
14	6	32767	219	101
16	6	131071	623	89
16	10	131071	991	255

Here d is the expected degree of a random formula with one clause per pair and random signs, and the entries are numbers of search-tree nodes. The aligned circulant formula $C_{9,2}$ needs 429 nodes in both orders, with 42 leaves against 70 for domination alone. The information collected along a root-to-leaf path is only 0.5 to 5.2 of its 9 bits: on aligned formulas new constraints are largely redundant, and the measure shows it.

7 What comes next

The running time is bounded by the total soft count at the leaves. By additivity, this total is 2^n times the expected value of $2^{-\sum_t I_t}$ along one random root-to-leaf walk. The walk moves to a child with probability proportional to the child's soft count. With weights fixed at creation, this walk is explicit: at each step the branching variable takes value b with probability $\pi_x(b)$, and the new constraint's factor follows Lemma 3. So a bound c^n with $c < 2$ for a class of formulas reduces to the following. Along this walk, show that the information $\sum_t I_t$ is at least a constant times n, except with exponentially small probability. That is the next step.

Checks. `explore_soft_count.py`, each mode in seconds:

- `examples` gives Examples 4–6.

- `search` gives the table and checks, at every branching step, additivity and Lemma 3 (3,387 steps). At sampled nodes it compares the closed form with the sum over completions and checks the bound of Proposition 2 (358 nodes). It also checks the optimum.
- `reopt` re-optimizes all weights from scratch at 170 sampled steps and confirms $\Phi^*(x = 0) + \Phi^*(x = 1) \leq \Phi^*(\text{parent})$. It also measures that re-optimization lowers $\ln \Phi$ by 2.7 on average.
- `aligned` runs $C_{9,2}$.