Dense Max 2-SAT
Revision Plan and Exposition Standards

20 October 2026

This note records the agreed organization and writing standards for our dense Max 2-SAT paper. The immediate objective is a readable theoretical arXiv version centered on the technique and four principal results, arranged by increasing complexity of the method. Practical extensions and application studies belong to a later stage directed toward a JAIR submission. Additional theoretical material remains available in the working notes and appendices while the main exposition stabilizes. This is an editorial plan; the proposals explicitly marked for verification below are not new proved claims. The standards apply to subsequent revisions as well as the next pass.

1 Scope and organizing principle

Organize the paper around the techniques that make accumulated pruning constraints useful. Whether an input is random is a property of an application, rather than the main organizing principle. In particular, deterministic graph families and random graph families can verify similar structural conditions and should be explained together when they use the same method.

Keep the principal objective visible: a deterministic exact algorithm with a fixed exponential saving over 2^n, using polynomial space, on the specified families. State which fixed class parameters determine the saving. Do not confuse this objective with an unrestricted-space upper bound, or with an improvement whose saving tends to zero as density grows.

The four principal results should concern natural input families. General distributional or matrix conditions belong in supporting results when they are needed to prove those family statements. Do not promote every useful technical lemma or specialization to another headline theorem.

2 Publication stages and the first release

2.1 First objective is a focused theoretical arXiv paper

Disseminate the technique and selected theoretical results promptly. The four-part plan and the exposition standards remain unchanged. Limit the first release to a coherent theoretical contribution with precise statements, executable algorithm descriptions, complete proofs, and the related work needed to place the results accurately.

Natural graph families such as Paley graphs, qualifying Ramanujan graphs, and SBM are theoretical applications of the method. They remain in scope without requiring an empirical demonstration of practical relevance. A short motivation and a short concluding outlook are sufficient for the broader application ambitions.

The first release does not depend on a practical solver implementation, benchmark experiments, a survey of application domains, new application classes, or Lean formalization. Optional improvements, including unification of the sequential and two-round proofs, should

not become prerequisites for dissemination. If such a change remains unresolved, retain the existing proof route, check it for the selected statement, and present its dependencies clearly.

The release milestone is a self-contained account of the selected results: the algorithms use exactly the information stated, the proofs establish the claimed bounds and polynomial space, and the introduction, abstract, and result table accurately describe those claims. Reducing scope should make this milestone attainable sooner.

2.2 Later objective is a theory and applications paper

The longer-term aim is a JAIR submission combining the theoretical foundation with useful practical extensions and input classes arising in real applications. Identify concrete encodings, determine whether their instances satisfy the relevant assumptions or suggest useful relaxations, and evaluate the resulting algorithms where appropriate. These are later research tasks. They should not appear as established practical contributions in the first version.

Keep application ideas and solver extensions in working notes so that they remain available for this stage. Their eventual inclusion should follow the evidence and the coherence of the extended paper.

2.3 Material to defer from the current draft

Use three destinations: the main theoretical account, appendices needed to support it, and separate working material for later development. An appendix is not automatically a destination for every existing result. The following are initial scope decisions, rather than instructions to delete research material.

- Defer the extended modeling and practical-application discussion in `sec:applications`. Preserve it in working notes; retain only concise motivation in the first paper.
- Defer region comparisons, caching, and the proposed unified solver in `sec:cache` and `sec:unified`. They add mechanisms outside the four selected results.
- Reduce the extended redundancy and randomized-exploration agenda to a short outlook. Preserve the full discussion as future research material.
- Keep repeated interaction profiles, bicliques, and bounded-block compression in the working inventory initially. Include an additional theoretical result only if it materially clarifies the selected technique without creating another substantial line of exposition.
- Keep general random models, alternative analyses, and sharper constants only where they support or briefly clarify a selected result. They need not all appear in the first arXiv version.
- Keep the development record, exploratory finite checks, and formal verification priorities in author working notes. Distinguish such records from proof details required by the published statements.

All proof machinery needed by a selected theorem remains in the paper or its supporting appendices, with standard external results cited precisely. In particular, the hidden-community algorithm's spectral preprocessing and its required computational guarantees remain part of the theoretical contribution.

3 The four parts of the main presentation

3.1 Pruning constraints and relative literal bias

Present the common comparison rule, correctness, propagation, simplification, and summation. Establish the relevant enumeration fact before its first use. Use the relative literal-bias theorem as the first principal application: substantial local preferences create useful requirements in the opposite branches.

This foundation is substantially in place. Preserve it during the next revision except for necessary corrections and notation alignment. A later consistency pass should reconcile it with the reorganized sections.

Keep the actual degree and bias assumptions visible. A relative gap is proportional to a variable's degree; it need not be proportional to n. Do not describe the theorem as requiring only literal gaps if its statement also requires control of the degree spread.

3.2 Normalization and symmetric random signs

The second principal result is a fixed exponential saving for familiar random clause models on an arbitrary prescribed set of variable pairs. Lead with one uniformly signed clause per selected pair and independent inclusion of the four possible clauses with probability $1/4$. Emphasize the absence of a density or regularity requirement for these models. Keep the assumption that any additional units are fixed independently of the binary draw.

Revise the intuition around two separate tasks. Normalization puts constraints of different sizes on comparable scales before addition. Random signs prevent the effects of shared variables from remaining coordinated across all the constraints. Explain these tasks before presenting degree-dependent estimates.

Use one running example. A larger numerical gap need not mean stronger pruning when the range of typical fluctuations is also larger. Explain that the algorithm weights a constraint using the degree in the original observed graph, rather than estimating its current strength exactly.

An independently sampled support, including an SBM support subsequently decorated with independent random literal signs, is an immediate application by conditioning on that support. It does not need another algorithm or a separate extended discussion.

Place the general complementation-invariant pair law, further sampling parameters, and sharper constants in an appendix. The proof supporting the familiar main-text cases must remain complete.

3.3 Assignment counts and a common systematic interaction

Explain why some pair interactions have a common systematic contribution, and how guessing the total number of ones accounts for it. Introduce the comparison allowance needed for correctness. Then explain the structural conditions controlling the remaining correlations.

The principal application is Max-Cut on regular graphs satisfying the stated spectral and density conditions. Present Paley graphs and qualifying nonbipartite Ramanujan graphs immediately as examples of that result, retaining their qualifications. They need not receive separate theorems.

Use a supporting deterministic accumulation result to connect this application with independent random interactions having a common mean. Max-Cut on $G(n, p)$ is a useful bridge to the next part: there is one expected pair interaction, and hence one total count to consider. Include its supporting verification before treating it as an established corollary of the reorganized argument.

Proposal requiring verification. Prefer one fixed-round analysis in the main presentation if it supports all the selected applications. In particular, investigate using two prefix rounds for the independent common-mean models as well as regular-graph Max-Cut. Check the full-matrix bound, the interaction between rounds, the comparison allowance, and the resulting constants. The existing sequential proof and the round proof have different hypotheses; do not silently identify them or promise unchanged numerical bounds.

Do not force the arbitrary-support random-sign theorem through this matrix framework. Its direct exposure argument handles irregular supports and has an independent role.

3.4 Several systematic interactions and hidden communities

The fourth principal result is Max-Cut on SBM graphs with hidden communities, under the existing fixed-community and variance assumptions. The theorem's algorithm receives the graph and the stated fixed class parameters, without the generating partition or edge probabilities.

First explain the supplied-community case: guessing the number of ones in each group extends the preceding total-count idea. Use it as an intermediate explanation. Then explain how approximate spectral directions and projection guesses replace the unavailable information in the current hidden-community algorithm. Recovering the community labels is not required.

Keep the distinction between two uses of SBM explicit. Random signed clauses on an SBM support belong to the arbitrary-support result. The fixed complementary clauses encoding Max-Cut on an SBM graph belong to this fourth part. Supplied and hidden communities are different information settings for the latter distribution.

4 A consistent pattern within each part

Use the following sequence, allowing short definitions immediately before their first necessary use.

1. **Intuition for why the result is possible.** Identify the useful feature of the input, the obstacle it resolves, and the source of the search-space saving. Use a concrete example or a path in the branching tree. Do not begin with the full technical apparatus.

2. **Definitions needed by the algorithm.** Introduce only the new notation required here. Refer to the common framework for established definitions. Keep notation used only by a later extension in the section that needs it.

3. **The algorithm.** Give a short operational description followed by compact but specific pseudocode. Refer to previously stated procedures and lemmas rather than repeating their implementation.

4. **Correctness.** Explain why an optimum remains represented, including the treatment of ties, comparison allowances, simplification, and the interaction with previously added constraints. Separate this argument from the time bound.

5. **The computational result.** State a self-contained complexity theorem for the input family. Define its parameters, assumptions, probability guarantee, and space requirement. The theorem states what can be computed and at what cost; the algorithm is the tool used in its proof.

6. **A roadmap for proving the running-time bound.** Explain what must be counted and which estimates give the saving. Distinguish this roadmap from the earlier intuition about why the phenomenon occurs.

7. **The main proof.** Organize it into meaningful steps and show how they establish the stated bound. Keep the principal argument readable without repeatedly leaving it for technical derivations.

8. **Supporting lemmas and applications.** Place technical estimates after the main proof or in an appendix when that improves its flow. Introduce every lemma and theorem with a short explanation of its role, naming the argument that uses it. Facts needed to define the algorithm must already have been stated.

The section should remain coherent if the reader first follows only the intuition, algorithm, theorem, and proof roadmap. The full proof must then supply every dependency needed to justify that account.

5 Writing and notation standards

5.1 Clarity takes priority over brevity

Longer proofs are welcome when the extra explanation helps the reader. Use connected prose, meaningful intermediate steps, and consistent notation. Avoid compressing several ideas into a sentence merely to shorten a proof. Preserve the author's intended style and message when editing prose.

Use familiar mathematical language whenever it is sufficient. Say "sum of Boolean literals" when that describes the expression. Introduce general coefficients, affine forms, or matrix notation when they perform a necessary role, and explain that role at introduction.

Define every symbol, operator, and term before use. In particular, explain "unassigned variable," "preferred value," "prefix," "suffix," and any order on assignments. Do not use "free variable" or "bad value" without a definition. Prefer descriptive terms that remain meaningful from the algorithm's point of view.

Use C for one pruning constraint and $\mathcal{C}$ for the collection. Define the summed constraint C_Σ in a displayed equation and refer to that equation consistently. Distinguish coefficients arising from repeated literal occurrences from weights assigned to entire constraints. Explain multiplicity as counting appearances.

Write "by the Cauchy–Schwarz inequality" and display the particular inequality being applied. Apply the same principle to other standard tools: give the reader enough information to check the step.

5.2 Statements must describe their actual scope

Define the input model positively and precisely: simple formulas, bounded multisets, units, or graphs, as appropriate. State assumptions where they are used rather than relying on an earlier informal description. Theorem statements should define parameters such as $\varepsilon, \eta, R, k, \chi$ and explain which are fixed.

State substantive hypotheses in the theorem itself instead of making the reader reconstruct them from an equation reference. Keep technical conditions out of headline family descriptions where possible, while retaining all conditions in the formal result.

Distinguish a linear lower bound from an $O(n)$ upper bound. Distinguish degree, clause density, and the number of clauses. Define the population over which an average is taken and whether clauses or distinct neighbors are counted.

For a random-input result, specify the sampling process, the independent choices, and what is fixed first. State whether units may depend on the sample. Separate correctness on every input from an expected or high-probability running-time guarantee. Do not convert a high-probability bound into an expected bound without an argument.

Keep proved statements, proposed refinements, and open directions distinct. Do not claim novelty or completion of an independent proof audit on the basis of an exposition revision.

5.3 Intuition should explain a mechanism

A statement such as "typical assignments cannot compensate for all requirements" needs an explanation: bounded influence, opposing signs, a structural correlation bound, or another identified mechanism. Use a small example to make the mechanism visible.

When using a uniform random path, say that this is an analysis of a deterministic search tree. A literal contributes zero or one; one half is its expectation under the specified uniform assignment. Do not confuse randomness of the path with randomness of the input.

Do not assume that generated constraints are independent. Do not imply that fresh variables or disjoint neighborhoods are necessary when the argument actually controls the signs or total influence of overlaps. Explain how the proof handles exceptional paths and sums work over all prefixes.

Introduce normalization before repeated comparisons involving $\sqrt{d}$. Explain that positive scaling preserves an individual constraint but changes its contribution to the sum. Treat normalization and removal of a systematic interaction as separate operations. Avoid calling useful pruning a "disadvantage"; describe the requirement imposed on the branch or the resulting saving explicitly.

6 Algorithm presentation standards

Pseudocode should be high-level enough to follow and precise enough to execute in principle. Use the `algorithm` and `algorithmic` packages. Comments should be short explanations in a smaller font, introduced by `//`; the current convention is

```
\renewcommand{\algorithmiccomment}[1]{{\footnotesize\itshape // #1}}
```

1. **Identify the input and all state.** State parameters explicitly or define a shared-data block before the procedures. Distinguish fixed data, shared updates, and values local to a recursive call. Explain T, M, and $\alpha^\star$, where they are initialized, and which calls can change them. Define score offsets and how the returned assignment and score include them.

2. **Specify branching choices concretely.** State the variable order and how the preferred value is computed. "Increasing labels" means the original input indices if that is the intended order. Distinguish original graph degrees from residual degrees. If a theorem permits any fixed order independent of the sample, say so; do not infer adaptive-order guarantees without the appropriate proof. In round algorithms, state which earlier assignments the preferences use.

3. **Separate initial preprocessing from node operations.** Use Preprocess for the initial pair reductions and Simplify for the justified local rules and constraint propagation at search nodes. Do not repeat a reduction lemma already provided by the common framework. Apply these procedures only as permitted by the particular algorithm and its analysis: adding forced assignments to a fixed-prefix random-search analysis requires justification.

4. **Respect constraints and comparison scope.** Explain how simplification and learned constraints jointly preserve an optimum. Individual correctness of two rules does not by itself establish their compatibility. Branch exploration order is separate from the

mathematical preference and tie convention; do not impose a first-branch requirement when the correctness invariant does not need one.

5. **Use only information supplied or computed.** For the random-formula algorithm, construct the observed support from the input formula before preprocessing. The latent generating graph is not an input. For SBM, distinguish supplied structural data from hidden data and account for discovering the information actually used.

6. **Explain what a test guarantees.** Failure of the summed-constraint test certifies infeasibility, but passing it need not imply joint feasibility. Likewise, satisfying C_Σ need not satisfy every member of $\mathcal{C}$. Explain why enumerating these extra candidates preserves correctness and how their number is bounded.

Do not introduce caching as an implicit part of the core algorithm. Make the polynomial-space implementation explicit: depth-first traversal and sequential processing of guesses and candidates, rather than storing the whole search space.

7 Proof and linear algebra standards

Separate preservation of an optimum, the count of surviving assignments, enumeration time, arithmetic cost, and space. A small number of solutions to an arbitrary constraint system does not by itself yield an efficient enumerator. Invoke the proved enumeration property of the particular summed inequality when that is the argument.

For probabilistic proofs, specify what is exposed or conditioned on, why the remaining random choices have the required distribution, and which dependencies remain. When introducing a martingale, define the available information, verify conditional mean-zero increments, and justify the increment or variance bounds used by the concentration inequality. Explain transitions from probability over assignments to counts, and from joint input–assignment estimates to guarantees for most inputs.

Use supporting lemmas for technical estimates that would interrupt the main proof. Keep comments on stronger variants, adaptive choices, or possible extensions in a separate discussion unless they are needed for the stated conclusion.

Introduce linear algebra when its role becomes necessary to the presented argument. Keep the following distinctions explicit:

- Symmetric random signs on arbitrary supports use scalar moment and concentration arguments in the current proof.
- Count-adjusted independent interactions have a combinatorial algorithm but currently use matrix bounds in the analysis.
- Regular-graph Max-Cut uses its spectral hypothesis in the proof; the algorithm does not calculate eigenvectors.
- Supplied-community SBM uses counts and gains algorithmically, with matrix estimates in the proof.
- Hidden-community SBM currently performs spectral preprocessing as part of the algorithm.

Moving a proof to an appendix does not remove its mathematical dependencies. A proposed elementary replacement must be proved before claiming that the relevant technique has been eliminated.

8 Appendices and revision sequence

The first arXiv version's appendices primarily contain the complete supporting proofs for the four principal results. Include a general distributional statement, parameter refinement, or alternative analysis when it supports those results or gives a short useful clarification. The broader inventory of proved results and exploratory ideas remains available in separate working material; it need not all accompany the submission. Keep proposed extensions visibly separate from established results wherever they are retained.

The next passes should proceed as follows.

1. Revise Part 2 around normalization and the effect of random signs, using the agreed section pattern and the familiar sampling models.

2. Rebuild Part 3 around counts and the selected deterministic Max-Cut result. Verify any change of analysis before replacing an existing proof; place additional random interaction results appropriately.

3. Rebuild Part 4 from supplied community counts to the actual hidden-community algorithm, retaining its assumptions and computational steps.

4. Align the introduction, abstract, result table, transitions, and cross-references with the four-result scope. Remove superseded family descriptions and separate the deferred application and research material. Preserve author-written prose through careful, local edits.

5. Check every retained statement against its proof, algorithm, input information, and space bound; compile and inspect the manuscript. Complete the focused arXiv version before expanding the scope toward practical extensions and the later journal submission.

The existing Lean verification plan remains a separate resource. Reconcile its theorem priorities with the stable manuscript before beginning formalization, as previously agreed.

8.1 Map to the current draft

The source is `dense_max2sat_paper.tex`. Use labels rather than theorem numbers while reorganizing:

Part 1
`sec:framework`, `sec:bias`, `lem:pruning`, `lem:constraint_sum`.

Part 2
`sec:random`, `thm:weighted`, `cor:support`, `lem:observed_pairs`, `lem:enumeration`, `eq:weighted`.

Part 3
`sec:countalgorithm`, `cor:maxcut`, `thm:randomclauses`, `res:counts`, `prop:pairmembership`.

Part 4
`sec:sbm`, `thm:sbm`, `cor:planted`, `app:discovery`.

This map identifies source material for the revision; it does not freeze the final labels or require the present section boundaries to survive.