

Differentiable Neural Computers

HYBRID COMPUTING USING A NEURAL NETWORK WITH
DYNAMIC EXTERNAL MEMORY (GRAVES ET AL. 2016)

Konstantinos Kogkalidis

May 28, 2018

Logic and Computation

Overview

Differentiable Neural Computer

A recurrent neural network coupled with an external memory.

Overview

Differentiable Neural Computer

A recurrent neural network coupled with an external memory.

- Extension of NTMs

Overview

Differentiable Neural Computer

A recurrent neural network coupled with an external memory.

- Extension of NTMs
 - End-to-end differentiable

Overview

Differentiable Neural Computer

A recurrent neural network coupled with an external memory.

- Extension of NTMs
 - End-to-end differentiable
 - Auto-associative memory

Overview

Differentiable Neural Computer

A recurrent neural network coupled with an external memory.

- Extension of NTMs
 - End-to-end differentiable
 - Auto-associative memory
 - Turing complete

Overview

Differentiable Neural Computer

A recurrent neural network coupled with an external memory.

- Extension of NTMs
 - End-to-end differentiable
 - Auto-associative memory
 - Turing complete
- + Memory attention mechanisms

Overview


Differentiable Neural Computer

A recurrent neural network coupled with an external memory.

- Extension of NTMs
 - End-to-end differentiable
 - Auto-associative memory
 - Turing complete
 - + Memory attention mechanisms
- Mimic mammalian biological memory
- Employ classical concepts of computation


Introduction: Motivation

Von Neumann architecture



Introduction: Motivation

Simple Neural Net




$$y = g(h), \quad h = f(x)$$

No memory

Introduction: Motivation


Simple Neural Net



$$y = g(h), \quad h = f(x)$$

No memory

Recurrent Neural Net



$$h(t) = f([x(t); h(t-1)])$$

Finite, non-contiguous memory

Approach

Allow an RNN to act as a controller to interact with a memory matrix of N (arbitrary many) addresses.

Approach

Allow an RNN to act as a controller to interact with a memory matrix of N (arbitrary many) addresses.

1. Content Lookup

- Attention over memory defined by weightings $W \in \mathbb{R}^N$
- Compare controller output with memory objects
(auto-associative memory)
- Allow partial matches (pattern completion)

Approach

Allow an RNN to act as a controller to interact with a memory matrix of N (arbitrary many) addresses.

1. Content Lookup

- **Attention** over memory defined by weightings $W \in \mathbb{R}^N$
- Compare controller output with memory objects
(**auto-associative memory**)
- Allow partial matches (**pattern completion**)

2. Sequential Retrieval

- Fill $L \in \{0, 1\}^{2N}$ indexing **temporal transitions**
- **Shift** operations defined by LW , $L^T W$

Approach

Allow an RNN to act as a controller to interact with a memory matrix of N (arbitrary many) addresses.

1. Content Lookup

- Attention over memory defined by weightings $W \in \mathbb{R}^N$
- Compare controller output with memory objects (auto-associative memory)
- Allow partial matches (pattern completion)

2. Sequential Retrieval

- Fill $L \in \{0, 1\}^{2N}$ indexing temporal transitions
- Shift operations defined by LW , $L^T W$

3. Dynamic Allocation

- Mark memory locations with $\{0, 1\}$ to signal usage
- Manipulate signals during R/W operations to enable reallocation
- Generalization to unbounded memory

Controller

A deep long-short term memory unit receiving

$$\mathcal{X}_t = [\mathbf{x}_t; \mathbf{r}_{t-1}^1; \dots; \mathbf{r}_{t-1}^R]$$

and producing

\mathbf{a}