

Towards Representation-Independent Logic and Data

CONSTANTINE THEOCHARIS, University of St Andrews, UK

Abstract TODO

CCS Concepts: • **Theory of computation** → **Categorical semantics**; **Abstraction**; *Operational semantics*; • **Software and its engineering** → *Translator writing systems and compiler generators*.

Additional Key Words and Phrases: Representation, Algebraic Data Types, Categorical Semantics, Compilation, Low-Level Data Structures

ACM Reference Format:

Constantine Theocharis. 2024. Towards Representation-Independent Logic and Data. In *Proceedings of Make sure to enter the correct conference title from your rights confirmation email (Conference acronym 'XX)*. ACM, New York, NY, USA, 3 pages. <https://doi.org/XXXXXXX.XXXXXXX>

1 INTRODUCTION

Let \mathbb{S} and \mathbb{L} be two 2-categories. Eventually we will require additional structure to be present in these, but for now we want to consider them as context categories for two different type theories. We will consider 2-morphisms to be rewriting rules, and 1-morphisms to be terms, in the style of [CITE].

We want to view \mathbb{S} as the "high-level", nice category that we want to write our programs in. On the other hand, \mathbb{L} is the "low-level", ugly category that we actually execute our programs in. It is ugly from the point of view of the programmer, but nice from the point of view of a machine, because it closely follows the way the machine actually executes the program.

Since we have a high-level and a low-level category, we want to have a way to translate between them. We will do this by defining two functors:

- A functor $C : \mathbb{S} \rightarrow \mathbb{L}$, called the *compilation* functor. It takes a program in \mathbb{S} and compiles it to a program in \mathbb{L} .
- A functor $Q : \mathbb{L} \rightarrow \mathbb{S}$, called the *quoting* functor. it allows us to opaquely operate on program fragments from \mathbb{L} within \mathbb{S} .

Importantly, both of these functors are *lax*, meaning that they only respect functoriality up to 2-morphisms. In other words, compiling a high-level program $C(f \circ g)$ is not necessarily the same as compiling $C(f)$ and then $C(g)$ separately, but there is a 2-morphism $C(f) \circ C(g) \Rightarrow C(f \circ g)$ implying that one evaluates to the other.

The quoting functor Q is left-adjoint to the compilation functor C , in the sense that compiling a quoted program yields the same program. Commonly this adjunction is strict.

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than the author(s) must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.

Conference acronym 'XX, June 03–05, 2018, Woodstock, NY

© 2024 Copyright held by the owner/author(s). Publication rights licensed to ACM.

ACM ISBN 978-x-xxxx-xxxx-x/YY/MM

<https://doi.org/XXXXXXX.XXXXXXX>

2 FEATURES OF \mathbb{S}

Since \mathbb{S} is the site of our high-level programs, we want it to have a lot of the things that we expect from a programming language. In particular, we want it to be cartesian closed, and we want it to admit fixpoints of endofunctors.

3 FEATURES OF \mathbb{L}

We require much less convenience in the structure of \mathbb{L} , instead relying on the functor C to translate human-friendly programs into machine-friendly ones.

Commonly \mathbb{L} will not be closed, and it might be a Kleisli category with respect to some monad (probably a monad holding the state of the stack/heap/environment/etc).

We will commonly want to restrict \mathbb{L} to only be monoidal in some less-than-cartesian way, for example to model a linear logic for the tracking and preservation of resources.

4 COMPILATION

This setup of having two sites of "programming" is not a new concept. In fact, it could be argued that this is exactly how the process of standard compilation works. We have a high-level language, which is compiled into a low-level language, which is then executed on a machine.

However, the process of compilation is usually not considered to be part of the high-level program itself. Rather, it is the job of the compiler to figure out exactly what is the optimal representation of a high-level program in the low-level language. This is especially the case when the discrepancy between the levels becomes great, for example in functional languages such as Haskell or ML. In these languages, the programmer has very little control over the eventual representation of their program in the low-level language, unless they use specialised primitives which are meant to mirror the low-level capabilities of the target system.

This is what we are aiming to change with this formalism. We envision a process of compilation in which the programmer has a lot more control over the representation of their program in the low-level language, while still keeping a clear separation between that and the core logic of the high-level program itself. In a way, we are trying to create a principled and ubiquitous version of "directive annotations" in high-level languages which aim to address a particular low-level concern about a program (for example, whether to keep the field of a data type behind a pointer.)

5 TRANSLATION OF LOGIC AND DATA

In the present categorical presentation of this process, we want each program to construct its own customised compilation functor C . This functor will be constructed by the programmer, just like the rest of the high-level logic of the program.

One might remark that this sounds like a lot of work for the programmer. Imagine having to not only write a program, but also write a customised compiler for that very program, and doing that each time you want to write a program. However, we will see that this is not the case. In fact, we will see that the compilation functor can be constructed automatically based on a set of core "data type representations" that are provided by the programmer. These data type representations will be the only thing that the programmer will have to write, and they will be reusable across many different programs.

Furthermore, there will be a trade-off at play. The more custom parts of the compilation functor the programmer writes, the more control they have over the eventual representation, but the more coupling there is between the high-level program and the low-level representation. Crucially however, this coupling is never present in the high-level program itself, but rather sits alongside it.

6 ALGEBRA-COALGEBRA PAIRS AS THE PRIMITIVE OF REPRESENTATION

Consider that we have an endofunctor $F : \mathbb{S} \longrightarrow \mathbb{S}$ which admits a least fixpoint, which we will denote μF .

ACKNOWLEDGMENTS

Acknowledgments

Received 28 February 2024