EXERCISE 2 · DATA HANDLING WITH THE TIDYVERSE

Exercise 2 in R: the practical recipe

No theory. What to install, what to click, what to paste where, what you will see, and what to do with it. Written for RStudio on your own computer.

CHECK **The short version**

- You hand in **one file:** `Ex2_R_code.R`, with your answers typed into it. **No Word document**, nothing separate.
- **Code answers** (Q2, Q3, Q5, Q8) are normal R code. **Written answers** (Q1, Q4, Q6, Q7) are lines that start with `#`. R ignores those lines, so the script still runs from top to bottom.
- You add **10 things** to the script: 8 answers, 1 required fix and 1 optional extra (see the table). Everything is in section 4, ready to paste.
- Time: about 30 minutes to install everything, then about 1 hour for the exercise.

#	What you add	Find this text with Ctrl + F, paste below it	Kind
1	Q1 answer	`#Add answer Q 1 here`	words (#)
2	ungraded answer (optional)	`select(method.id, method.label)`	words (#)
3	Q2 answer	`#Add answer Q 2 here`	code + words
4	Q3 answer	`#Add answer Q 3 here`	code
5	**required fix** (a missing file)	`"dat.long.rds"))`	code (1 line)
6	Q4 answer	`#Add answer Q 4 here`	words (#)
7	Q5 answer (2 points)	`#Add the code for Q 5 here`, **1st** match	code
8	Q6 answer	`#Add the code for Q 5 here`, **2nd** match (yes, it says Q 5)	words (#)
9	Q7 answer	`#Type your answer here.`	words (#)
10	Q8 answer	`#Type your code here` (the very last line)	code

Work through section 4 from top to bottom. The written answers are complete and correct; you may want to rephrase them a little in your own words.

1. Install everything (once)

1. **Install R** from cran.r-project.org. Windows: *Download R for Windows → base → Download R-4.x.x for Windows*. Mac: *Download R for macOS*, then pick the file for your chip ("arm64" for M1/M2/M3/M4 Macs, "x86_64" for older Intel Macs). Open the downloaded file and click through the installer, keeping all default settings.
2. **Install RStudio Desktop** (free) from posit.co/download/rstudio-desktop. Install it with the default settings.

3. **Unzip** `Ex2_folders.zip` to a place you can find, e.g. `Documents/R-Exercise2`. (Windows: right-click → *Extract All*. Mac: double-click.) If a folder `__MACOSX` appears, delete it. Inside `Ex2_folders` you must see three folders: `Scripts`, `data`, `out`.
4. **Start RStudio** (not "R"; from now on you always use RStudio).
5. **Install the two packages.** Click into the **Console** (the bottom-left pane, where the `>` sign is). Type the line below, press **Enter**, and wait 2 to 10 minutes. Lots of scrolling red and black text is normal.

```
install.packages("tidyverse")
```

Then do the same with:

```
install.packages("svglite")
```

If RStudio asks...	type
"Do you want to install from sources the packages which need compilation? (Yes/no/cancel)"	`no` and press Enter
"Would you like to use a personal library instead?" (or "...create a personal library...?")	`yes` and press Enter
to choose a "CRAN mirror"	pick any one, e.g. Switzerland or "0-Cloud"

6. Test it: type `library(tidyverse)` in the console and press Enter. You should see a block starting with `── Attaching core tidyverse packages ──` and **no** line starting with `Error`. Done: you never have to install these again.

2. Every time: open the script and set the folder

Do these two steps **every time you start RStudio** to work on the exercise:

1. *File → Open File...* → go to `Ex2_folders/Scripts/` → open **`Ex2_R_code.R`**. It opens in the top-left pane.
2. *Session → Set Working Directory → To Source File Location*. The console now shows a line like `setwd("C:/Users/…/Ex2_folders/Scripts")`.

TRAP **Step 2 is the most common reason the exercise "does not work"**

The script finds its data with paths like `"../data/"`, which means "from the `Scripts` folder, go up one folder, then into `data`". That only works if R is "standing" in the `Scripts` folder. If you get `does not exist in current working directory`, repeat step 2.

TIP **The file may show an empty line between most lines**

That is only how the file was saved; it changes nothing. It also means the line numbers in RStudio are about twice as high as you might expect, which is why this guide always says **"search for this text"** instead of giving line numbers.

3. RStudio in two minutes

① Script (top left)
Your file `Ex2_R_code.R`. You paste your answers here. Nothing runs until you press Ctrl + Enter.

Environment (top right)
Lists the tables and objects R has in memory. You can ignore it.

② Console (bottom left)
Where the results (output) appear. The `>` sign means "ready".

③ Files · Plots (bottom right)
Plots: your graphs (arrows to flip through, *Zoom* to enlarge). *Files*: browse folders.

To...	do this (Mac: use Cmd instead of Ctrl)
run one line	click anywhere in the line, press **Ctrl + Enter**. If the command spans several lines, RStudio runs all of them. The cursor then jumps to the next command, so you can keep pressing Ctrl + Enter.
run several lines	select them with the mouse, press **Ctrl + Enter**
find a placeholder	**Ctrl + F** opens a search bar above the script. Type the text, press Enter (again for the next match), then **Esc**.
add an answer	click at the **end** of the placeholder line, press **Enter** for a new line, paste with **Ctrl + V**
save	**Ctrl + S**. The file name in the tab turns from red to black.
start over	*Session → Restart R*, set the working directory again (section 2), then run the script from the top
get out of a stuck console	if the console shows `+` instead of `>`, click into it and press **Esc**

Red text in the console is only a problem if the line starts with `Error`. Everything else (messages, `Rows: 36 Columns: 6`, the tidyverse start-up text) is just information.

TIP **Copying from this PDF**

You can copy the grey code boxes and paste them into RStudio. After pasting, check that the line breaks look exactly like in the PDF: every line that starts with `#` must be on its own line. If a `#` line got glued to the front of a code line, R would ignore that code. If quotes turn curly (`“ ”`), retype them as straight quotes `"`.

4. The exercise, round by round

Go through the script from top to bottom. A grey **round** means: just run the template code that is already there. A purple card means: **paste an answer** at that place, then run it. Never skip a round: later lines need the results of earlier ones.

1 Start-up

RUN — Select from `#Clean your workspace` down to `library(tidyverse)`, press **Ctrl + Enter**.

YOU SEE — `dir()` prints `"Ex2_R_code.R"`. `library(tidyverse)` prints the start-up block (a "message", not an error).

DO — Check `dir()`: if it shows `"data" "out" "Scripts"` instead, the working directory is wrong; redo section 2.

2 Read the measurement table

RUN — Select from `getwd()` down to `head(measurement)`, press **Ctrl + Enter**.

YOU SEE — a path ending in `/Scripts`, then `Rows: 36 Columns: 6` and a table of 6 rows:

```
# A tibble: 6 × 6
  measurement.id plot.id trait.id method.id timestamp  value
           <dbl>   <dbl>    <dbl>     <dbl> <chr>      <dbl>
1              1       1        1         1 2014.04.14  48.2
2              2       2        1         1 2014.04.14  49
…
```

DO — nothing. Continue with Q1.

Q1 · 1 point · written answer

1. Press **Ctrl + F**, search for `#Add answer Q 1 here`. Press **Esc**, then click at the **end** of that line and press **Enter** to get a new empty line.
2. Paste (or type) exactly this:

```
# Q1: measurement.csv has 3 comment lines (they start with "#").
# They hold metadata, i.e. information about the data: who made the file
# (A. Hund, based on data from E. Frossard), the purpose (demo of data
# handling in R) and the content (ETH excursion, 14 and 15 April 2014).
# Comment lines can document a data file (author, source, date, units,
# methods, notes). read_csv(comment = "#") skips them when reading.
```

3. Nothing to run: lines starting with `#` do nothing.

   Where the "3" comes from: open `data/measurement.csv` in a text editor (Notepad / TextEdit) and count the lines starting with `#` at the top.

3 Pipe examples

RUN — Select from `1:10 |> mean()` down to `years |> as.character() |> as.numeric()`, press **Ctrl + Enter**.

YOU SEE — `5.5`, `5.5`, then `2008 2009 2010 2011 2012` twice.

DO — nothing.

4 Read the other tables

RUN	Select from `design <- read_csv(` down to `select(method.id, method.label)`, press **Ctrl + Enter**.
YOU SEE	four short `Rows: … Columns: …` messages.
DO	nothing (optionally add the ungraded answer below).

Ungraded question · optional · written answer

1. Press **Ctrl + F**, search for `select(method.id, method.label)`. Press **Esc**, then click at the **end** of that line and press **Enter** to get a new empty line.
2. Paste (or type) exactly this:

```
# Ungraded: SPAD method (Crop Ontology CO_321:0000249, "Chl Measurement"):
# leaf chlorophyll is measured non-destructively with a hand-held meter
# (e.g. Minolta SPAD-502) via light transmittance at 650 nm (red) and
# 940 nm (infrared). It gives a relative index (0-99.9), usually measured
# on the flag leaf.
```

3. Nothing to run. (There is no placeholder for this question in the script, so this is a sensible place for it. You may also skip it: it gives 0 points.)

5 Check the keys of the entry table

RUN	Select from `entry |>` down to `filter(n > 1)`, press **Ctrl + Enter**.
YOU SEE	first a table with `Tapidor 3` and `Titlis 3`, then `# A tibble: 0 × 2`. (There are two `entry |>` blocks; run both.)
DO	nothing.

Q2 · 1 point · code + written answer

1. Press **Ctrl + F**, search for `#Add answer Q 2 here`. Press **Esc**, then click at the **end** of that line and press **Enter** to get a new empty line.
2. Paste (or type) exactly this:

```
design |>
  count(plot.id) |>
  filter(n > 1)
trait |>
  count(trait.id) |>
  filter(n > 1)
# Q2: both checks return a tibble with 0 rows, so no id occurs twice:
# plot.id is a unique key of design and trait.id is a unique key of trait.
```

3. Select the 6 code lines you pasted (from `design |>` to the second `filter(n > 1)`) and press **Ctrl + Enter**.
4. You see twice:

```
# A tibble: 0 × 2
# ℹ 2 variables: plot.id <dbl>, n <int>
# A tibble: 0 × 2
# ℹ 2 variables: trait.id <dbl>, n <int>
```

What it means: 0 rows = no duplicates = the key is unique. That is exactly what the two `#` lines of your answer say, so there is nothing more to do.

6 Join the tables

RUN	Select from `#Do a left join` down to `left_join(trait, by="trait.id")`, press **Ctrl + Enter**.
YOU SEE	nothing. Assigning with `<-` is silent.
DO	nothing. Continue with Q3.

Q3 · 1 point · code

1. Press **Ctrl + F**, search for `#Add answer Q 3 here`. Press **Esc**, then click at the **end** of that line and press **Enter** to get a new empty line.
2. Paste (or type) exactly this:

```
dat.long <- dat.long |>
  left_join(method, by = "method.id")
```

3. Click into the first pasted line and press **Ctrl + Enter** (both lines run).
4. You see nothing. To check, type `dim(dat.long)` in the console and press Enter:

```
[1] 36 15
```

Paste Q3 **exactly here**, before the next block. If you put it further down, you get the error `Can't join … due to incompatible types`.

7 Turn columns into factors

RUN — Select from `#Identify all ids` down to `str(dat.long)` (the second one), press **Ctrl + Enter**.

YOU SEE — two long `str()` listings. In the second, most columns say `Factor`, and the last one is `$ method.label` (thanks to Q3).

DO — nothing.

8 Dates

RUN — Select from `dat.long$timestamp <-` down to `str(dat.long$DOY)`, press **Ctrl + Enter**.

YOU SEE — many `15` s (week), many `2` s (quarter), then `num [1:36] 104 105 104 105 …`.

DO — nothing. Later the dates show as 2014-04-13 and 2014-04-14, one day earlier than in the file. That is a time-zone quirk and is expected (the tutorial shows the same).

9 Treatment label and save

RUN — Select from `dat.long <- dat.long |> mutate(treat` down to `write_rds(dat.long, file=paste0(outputPath, "dat.long.rds"))`, press **Ctrl + Enter**.

YOU SEE — nothing.

DO — add the fix below **right now**.

Required fix · 0 points, but without it the script crashes later

1. Press **Ctrl + F**, search for `"dat.long.rds"))`. Press **Esc**, then click at the **end** of that line and press **Enter** to get a new empty line.
2. Paste (or type) exactly this:

```
write_rds(dat.long, file = paste0(outputPath, "dat.longFull.rds"))
```

3. Click into the line and press **Ctrl + Enter**.
4. You see nothing. In the *Files* pane, open the `out` folder: it now contains `dat.long.rds` and `dat.longFull.rds`.

Why: further down, the script loads `../out/dat.longFull.rds`, a file that is missing from your zip. Without this line you get `cannot open file '../out/dat.longFull.rds': No such file or directory`.

10 Field plots

RUN — Select from `#Only the day of the year (DOY) 104` down to `plot(p3)`, press **Ctrl + Enter**.

YOU SEE — three plots in the *Plots* pane (flip with the arrows): an empty grid, coloured tiles, and tiles with labels such as `0.Tapidor`.

DO — nothing. They look slightly different from the pictures in the tutorial (axis labels 1, 2, 3 instead of 1.0, 1.5, ...). That is fine.

11 Both days side by side

RUN	Select from `#Both days together` down to `plot(p_facet)`, press **Ctrl + Enter**.
YOU SEE	the same field twice, side by side, with panels labelled 104 and 105.
DO	nothing.

12 Save the graph as PNG and SVG

RUN	Select from `p<-ggplot(dat.long, aes(row, range))` down to `ggsave(p, filename = paste0(outputPath, "rastergraph.svg"), device="svg")`, press **Ctrl + Enter**.
YOU SEE	`Saving 7 x 7 in image` twice (your numbers may differ). The `out` folder now contains `rastergraph.png` and `rastergraph.svg`.
DO	if you get `there is no package called 'svglite'`, run `install.packages("svglite")` in the console and run the `ggsave` lines again.

Q4 · 1 point · written answer

1. Press **Ctrl + F**, search for `#Add answer Q 4 here`. Press **Esc**, then click at the **end** of that line and press **Enter** to get a new empty line.
2. Paste (or type) exactly this:

```
# Q4: The PNG is a raster image: a fixed grid of pixels. When you zoom in,
# text and edges become pixelated/blurry, and single elements cannot be
# edited. The SVG is a vector image: shapes and text are stored as drawing
# instructions (readable XML text). It stays sharp at any zoom, text stays
# real text, and every element can be edited (e.g. in Inkscape).
# For further processing or scaling I would prefer the SVG.
```

3. Nothing to run.

To see it with your own eyes (optional): open both files from the `out` folder in your web browser (drag them into a browser window) and zoom in a lot with **Ctrl + mouse wheel**. The PNG gets blocky, the SVG stays sharp.

13 Line plot (prepared, but not shown)

RUN	Select from `#Prepare the panel` down to `p<-p + theme(axis.text.x = element_text(angle = 90))`, press **Ctrl + Enter**.
YOU SEE	nothing: this block only builds the plot `p`.
DO	nothing (to see it anyway, type `p` in the console). Continue with Q5.


Q5 · 2 points · code

1. Press **Ctrl + F**, search for `#Add the code for Q 5 here` (the **1st** match: press Enter in the search box until you are there). Press **Esc**, then click at the **end** of that line and press **Enter** to get a new empty line.
2. Paste (or type) exactly this:

```
p <- dat.long |>
  mutate(fertilizer = as.numeric(as.character(fertilizer))) |>
  ggplot(aes(x = fertilizer, y = value)) +
  geom_point(aes(colour = factor(block))) +
  facet_grid(date ~ variety) +
  theme(axis.text.x = element_text(angle = 90))
plot(p)
```

3. Select all 7 pasted lines and press **Ctrl + Enter**.
4. The plot appears in the *Plots* pane. Compare it with the target below: points, fertilizer 0 to 180 on the x-axis (ticks 0, 50, 100, 150), Tapidor and Titlis as columns, the two dates as rows, colours for blocks 1 to 3.

   Do not change `dat.long <- …` here. The conversion of fertilizer to numbers happens only inside this plot, which is intended: the ANOVA later needs the original version.



What Q5 should look like. Click *Zoom* in the Plots pane to see it bigger.

14 Make the wide table

RUN Select from `dat.long<-read_rds(file=paste0(outputPath, "dat.longFull.rds"))` down to `head(dat.wide)`, press **Ctrl + Enter**.

YOU SEE a table of 6 rows; the last lines mention the two new columns:

```
# A tibble: 6 × 13
  plot.id entry.id block row   range variety fertilizer trait.id method.id
…
# ℹ 4 more variables: trait.name <chr>, treat <chr>,
#   `Fl0Chl_SPAD001_2014-04-13` <dbl>, `Fl0Chl_SPAD001_2014-04-14` <dbl>
```

DO nothing. Continue with Q6 (right below `head(dat.wide)`).

Q6 · 1 point · written answer

1. Press **Ctrl + F**, search for `#Add the code for Q 5 here` (the **2nd** match: press Enter in the search box until you are there). Press **Esc**, then click at the **end** of that line and press **Enter** to get a new empty line.
2. Paste (or type) exactly this:

```
# Q6: pivot_wider() pasted the values of trait.label, method.label and
# date together (separated by "_") and used them as the NAMES of new
# columns: "Fl0Chl_SPAD001_2014-04-13" and "Fl0Chl_SPAD001_2014-04-14".
# The SPAD numbers from "value" were moved into these new columns. The
# columns trait.label, method.label, date and value no longer exist, and
# the table shrank from 36 rows (one per measurement) to 18 (one per plot).
```

3. Nothing to run.

   Yes, this placeholder says "Q 5" a second time. It is a mistake in the template; this one is for Q6.

15 Compare the two days

RUN Select from `TraitsWide<-dat.wide` down to `plot(TraitsWide)`, press **Ctrl + Enter**.

YOU SEE a simple scatter plot with 18 circles (day 1 on x, day 2 on y).

DO nothing.

16 Split the data by date

RUN Select from `test<-dat.long |> split(dat.long$date)` down to `str(test)`, press **Ctrl + Enter**.

YOU SEE a long listing that starts like this:

```
List of 2
 $ 2014-04-13: tibble [18 × 18] (S3: tbl_df/tbl/data.frame)
  ..$ plot.id       : Factor w/ 18 levels "1","2","3","4",..: 1 2 3 4 5 6 7 8 9 10
...
  …
 $ 2014-04-14: tibble [18 × 18] (S3: tbl_df/tbl/data.frame)
  …
```

DO nothing. Continue with Q7.

Q7 · 1 point · written answer

1. Press **Ctrl + F**, search for `#Type your answer here.` . Press **Esc**, then click at the **end** of that line and press **Enter** to get a new empty line.
2. Paste (or type) exactly this:

```
# Q7: split() returns a list (not a tibble) with 2 elements, one per date,
# named "2014-04-13" and "2014-04-14". Each element is a tibble with
# 18 rows (the 18 plots measured that day) and the same 18 columns as
# dat.long. Together they hold all 36 rows; the data are only divided
# into groups, nothing is lost.
```

3. Nothing to run.

17 One ANOVA per day

RUN — Select from `aov1<-dat.long |> split(dat.long$date) |>` (the first one) down to `Pr.val`, press **Ctrl + Enter**.

YOU SEE — two ANOVA printouts, a long `str()` listing, and finally the p-values:

```
$`2014-04-13`
[1] 0.2907863 0.8806472 0.1430874 0.9188675        NA

$`2014-04-14`
[1] 0.001973723 0.604497550 0.328610606 0.814910513          NA
```

DO — nothing. Continue with Q8.

Q8 · 1 point · code

1. Press **Ctrl + F**, search for `#Type your code here`. Press **Esc**, then click at the **end** of that line and press **Enter** to get a new empty line.
2. Paste (or type) exactly this:

```
F.val <- aov.tab |> map(function(x){x[[1]]$`F value`})
F.val
```

3. Select both pasted lines and press **Ctrl + Enter**.
4. You see:

```
$`2014-04-13`
[1] 1.24400422 0.12872736 2.37648907 0.08533331         NA

$`2014-04-14`
[1] 17.2390982  0.5295666  1.2464561  0.2089240         NA
```

What it means: these are the F values of variety, fertilizer, block, variety:fertilizer and the residuals for each day. The `NA` at the end is normal (residuals have no F value). Nothing more to write: Q8 only asks for the code.

5. Final check and hand-in

1. **Save** with Ctrl + S.
2. **Test the whole script in one go:** *Session → Restart R*. Then *Session → Set Working Directory → To Source File Location*. Then click the **Source** button (top right of the script pane). R runs the whole file. If it stops with a red `Error`, see section 6. If it finishes without `Error`, you are done.
3. **Check the `out` folder** (Files pane): `dat.long.rds`, `dat.longFull.rds`, `rastergraph.png`, `rastergraph.svg`.
4. **Hand in the file** `Ex2_folders/Scripts/Ex2_R_code.R`. The course says: *"Submit your exercise by selecting the file in the repository for exercise 2"* on JupyterHub. So log in to JupyterHub (via Moodle), open the exercise 2 folder, upload your finished `Ex2_R_code.R` with the **Upload** button (↑) in the file browser (replace the template if it asks), and submit it there.

TIP **Not sure which button submits?**

The tutorial itself says the submission process on JupyterHub is still being worked out. If it is not clear on Moodle, ask the teaching assistant: "Do I submit the .R file in the exercise 2 folder on JupyterHub?" Do not rename the file.

- [ ] All 8 answers (plus the fix) are in the script, each right below its placeholder.
- [ ] Every line of a written answer starts with `#`.
- [ ] Source runs the whole script without any `Error`.
- [ ] Saved, uploaded to the exercise 2 folder on JupyterHub, and submitted. No Word file needed.

6. If something goes wrong

You see…	Do this
`does not exist in current working directory`	Session → Set Working Directory → To Source File Location, then run that part again.
`could not find function "read_csv"` (or `"ggplot"`, `"week"`, `"map"`)	Run `library(tidyverse)`. You probably restarted RStudio and skipped round 1.
`there is no package called 'tidyverse'` (or `'svglite'`)	Run `install.packages("tidyverse")` (or `"svglite"`) once in the console.
`object 'dat.long' not found` (or any other object)	You skipped a round. Run the script from the top again (or use the Source button).
`cannot open file '../out/dat.longFull.rds'`	The required fix (after round 9) is missing or was not run. Add or run it.
`Can't join x$method.id with y$method.id due to incompatible types`	Q3 is in the wrong place. Move it directly below `#Add answer Q 3 here`, restart R, run from the top.
`Column method.label doesn't exist`	Q3 is missing or was not run. Add it, restart R, run from the top.
`unexpected symbol` / `unexpected ')'` / `unexpected input`	Something got mangled while pasting. Compare the line with this PDF (quotes, brackets, line breaks).
The console shows `+` and nothing happens	Click into the console, press Esc, then check the line for a missing `)` or `"`.
Q8 shows other numbers, or the ANOVA shows Df `1` for fertilizer	You changed `dat.long` somewhere (e.g. in Q5). Use the Q5 code exactly as given, restart R, run from the top.
Weird behaviour you cannot explain	Session → Restart R, set the working directory, click Source.

Every piece of code and output in this guide was tested by running the complete, finished script (R 4.3.3, tidyverse 2.0.0) on the files from Ex2_folders.zip.