


# FoodBank Spec Documentation

- [ db schema ]



- [ login page ]

## Share food, Share happy !!

image of foodhub logo  
maybe surrounded by team member photos

account:

password:

login

Copyright by FoodHub

Welcome ~ Cindy [logout](#)

## Here is what will out of expiry day in 7 days

sysuser
donatemember
donateitem
receiptitem
report

▼ expirydate	▼ item	▼ qty
2016/02/08	泡麵	5
2016/02/10	蘋果	6
2016/02/06	餅乾	9

sysuser	
# 由 foodband 內 部新增 # 承辦人員名單 # 預設帳號批次匯入使用	
PK	su_id: int
+ name: nvarchar(10)	
+ unit: nvarchar(10)	
+ phone: nvarchar(20)	
+ locate: nvarchar(10)	
+ auth: int	
+ account: nvarchar(10)	
+ pw: nvarchar(20)	
+ valid: nvarchar(5)	
+ createdate: datetime	
+ updatedate: datetime	

donate_item	
#從表單看 捐贈才有整批匯入	
FK	dn_id:int
FK	su_id: int
+ donate_serial: int (全贈字號) (allow null ?)	
+ name: nvarchar(50) v	
+ expirydate: nvarchar(10) v	
+ category: nvarchar(20) v	
+ weight: int (g) v	
+ unit: nvarchar(5) (包, 盒...) v	
+ unit_price: float v	
+ quantity: int v	
+ donatedate: nvarchar(10)	
+ memo: nvarchar(50)	
+ description: nvarchar(50)	
+ valid: nvarchar(5)	
+ createdate: datetime	
+ updatedate: datetime	

login	check <code>sysuser.account</code> and <code>sysuser.pw</code> and <code>sysuser.valid=Y</code>
get donate item out of expiry day in 7 days	get <code>donate_item.expirydate</code> , <code>donate_item.quantity</code> and <code>donate_item.name</code> where (today - <code>donate_item.expirydate</code> ) < 8
link to donate item page	link to <code>donate_item</code> update page
get user info /logout	get <code>sysuser.name</code> , <code>sysuser.su_id</code> and <code>sysuser.auth</code>  this is show on each page

- [ sysuser ]

Welcome ~ Cindy [logout](#)

sysuser	▶
donatemember	
donateitem	
receiptitem	
report	

searchadd

name, locate ▼

search

[x] del

<input type="checkbox"/>	▼ id	▼ name	▼ unit	▼ phone	▼ locate	▼ account	▼ option
<input checked="" type="checkbox"/>	A001	cindy	fruit	(02) 1234567	tp	cindy	<a href="#">update</a>
<input type="checkbox"/>	T001	erica	cookie	(02) 2345678	tp	erica	<a href="#">update</a>
<input checked="" type="checkbox"/>	K001	bryan	vegetable	(07) 1234567	ks	bryan	<a href="#">update</a>

id use T or K to represent location A is admin account, and it can add new sysuser

when press [update]. it will pop out a windows to update data

update sysuser

id: T001

name:

unit:

locate: ☒ TP ☐ KS

phone:

account:

pw:

save

cancel

pw only show on admin account using

sysuser	▶
donatemember	
donateitem	
receiptitem	
report	

searchadd

name:

unit:

phone:

locate: ☒ TP ☐ KS

account:

pw:

auth: 

1,2,3,4,5 ▼

only admin account can add sysuser

the "add" tab only show when user is admin account

admin account with auth 0, tp account with 1, ks account with 2

add new member

sysuser	
# 由 foodband 內 部新增 # 承辦人員名單 # 預設帳號批次匯入使用	
PK	su_id: int
	+ name: nvarchar(10)
	+ unit: nvarchar(10)
	+ phone: nvarchar(20)
	+ locate: nvarchar(10)
	+ auth: int
	+ account: nvarchar(10)
	+ pw: nvarchar(20)
	+ valid: nvarchar(5)
	+ createdate: datetime
	+ updatedate: datetime

add sysuser	insert data <b>sysuser.su_id</b> with a rule (T- taipei, K-kaohsiung, A-admin), <b>sysuser.valid</b> default is Y  admin account default auth from 0~5, default is 0 tp account default auth from 1~5, default is 1 ks account default auth form 2~5, default is 2  only admin user ( su_id => AXXX ) show add tab
update sysuser	update <b>sysuser.updatedate</b>  only admin user ( su_id => AXXX ) can update pw and auth
delete sysuser	update <b>sysuser.valid</b> to N  only admin user ( su_id => AXXX ) show deduce button and checkbox(exclude admin account)  single select and multi select
search sysuser by name search sysuser by location	where <b>sysuser.name</b> like % or <b>sysuser.locate</b> like % and <b>sysuser.valid=Y</b>  only admin user ( su_id => AXXX ) can get invalid data (sysuser.valid= N )

- [ donate member ]

sysuser
donatemember ▶
donateitem
receiptitem
report

searchadd

name, ic, area, cat ▼

search

[x] del

<input type="checkbox"/>	▼ id	▼ name	▼ phone	▼ address	▼ unit	▼ option
<input checked="" type="checkbox"/>	N00001	創世基金會	(02) 1234567	台北市地址	社福部	<a href="#">update</a>
<input type="checkbox"/>	N00002	馬玉山	(02) 2345789	台北市地址	行銷部	<a href="#">update</a>
<input checked="" type="checkbox"/>	S00001	捐贈人	(07) 1234567	高雄市地址	個人	<a href="#">update</a>

id use N, S, W, E to represent area, A is admin account, when import  
when press [update], it will pup out a windows to update data

update donatemember

id: N00001    name: 創世基金會    category: 團體, 個人 ▼    ic: 10250309  
phone: (02) 1234567    mobile: 0911234567    unit: 社福部    area: 北中南東 ▼  
zipcode: 10001 ▼    country: 台北市 ▼    address: 我住台北市  
people\_cnt: 0    house: 2

savecancel

sysuser
donatemember ▶
donateitem
receiptitem
report

searchadd

name: 心地    category: 個人 ▼    ic: q12345678    people\_cnt: 0    house: 0  
phone: (02) 1234567    mobile: 0911234567    unit: 社福部    area: 中 ▼  
zipcode: 64043 ▼    country: 台中市 ▼    address: 文心路180號

add new member

sysuser	
# 由 foodband 內 部新增 # 承辦人員名單 # 預設帳號批次匯入使用	
PK	su_id: int
+ name: nvarchar(10)	
+ unit: nvarchar(10)	
+ phone: nvarchar(20)	
+ locate: nvarchar(10)	
+ auth: int	
+ account: nvarchar(10)	
+ pw: nvarchar(20)	
+ valid: nvarchar(5)	
+ createdate: datetime	
+ updatedate: datetime	

donatemember	
# 由foodband 提供名單 # 目前不由網站新增 # 捐受贈者名單 # 預設帳號供批次匯入使用 # 請領次數 系統每日計算	
PK	dn_id: int
FK	su_id: id
FK	crt_id: id
+ ic: nvarchar(12)	
+ name: nvarchar(50)	
+ phone: nvarchar(10)	
+ mobile: nvarchar(10)	
+ unit: nvarchar(10)	
+ address: nvarchar(50)	
+ category: nvarchar(10) (個人 團體 )	
+ people_cnt: nvarchar(5)	
+ house: nvarchar(5) (戶 )	
+ valid: nvarchar(5)	
+ createdate: datetime	
+ updatedate: datetime	

country	
+ crt_id: int	
+ area: nvarchar(5) (北 中 南 東)	
+ country: nvarchar(10)	
+ zip: nvarchar(5)	

add donate member

insert data **donatemember.dn\_id** with a rule (N-north,S-south,W-west, E-east, A-admin), **donatemember.valid** default is Y

zip and country is related

update donate member

update **donatemember.updatedate**

delete donate member

update **donatemember.valid** to N

single select and multi select

search donate member by name  
search donate member by ic  
search donate member by area

where **donatemember.name** like % or **donatemember.ic** like % or **donatemember.area** like % and **sysuser.valid**=Y

only admin user ( su\_id => AXXX ) can get invalid data (sysuser.valid= N )

- [ donate item ]

sysuser
donatemember
donateitem ▶
receiptitem
report

searchaddimport

name, expirydate, cat ▼

search

[x] del

<input type="checkbox"/>	▼ id	▼ name	▼ expirydate	▼ category	▼ qty	▼ option
<input checked="" type="checkbox"/>	10502001	開心果	1050228	零食	5	<a href="#">update</a>
<input type="checkbox"/>	10502002	蔬菜	1050215	生鮮	7	<a href="#">update</a>
<input checked="" type="checkbox"/>	10502003	維力炸醬麵	1050203	泡麵	8	<a href="#">update</a>

check auth when login user auth > insert data user auth "update" should be disable

id autoincrease (year+month+ 0001.....etc)

update item

id: 10502001 name:  expirydate:  unit:

category:  ▼ qty:  weight:  price:  donate\_date:

memo:  description:

-----below is receipt use-----

receipter:  type:  info: ☐ pic ☐ not ☒ both

savecancel

add item id should be input text

sysuser
donatemember
donateitem ▶
receiptitem
report

searchaddimport

data example: [download sample file](#)

▼ cat	▼ name	▼ expirydate	▼ weight	▼ unit
餅乾	卡拉姆久	1020305	20	包
零食	牛奶糖	1050209	10	盒

upload

receipt without import data



sysuser	
# 由 foodband 內部新增 # 承辦人員名單 # 預設帳號批次匯入使用	
PK	su_id: int
+ name: nvarchar(10)	
+ unit: nvarchar(10)	
+ phone: nvarchar(20)	
+ locate: nvarchar(10)	
+ auth: int	
+ account: nvarchar(10)	
+ pw: nvarchar(20)	
+ valid: nvarchar(5)	
+ createdate: datetime	
+ updatedate: datetime	

donate_item	
# 從表單看 捐贈才有整批匯入	
FK	dn_id: int
FK	su_id: int
+ donate_serial: int (全贈字號) (allow null ?)	
+ name: nvarchar(50) v	
+ expirydate: nvarchar(10) v	
+ category: nvarchar(20) v	
+ weight: int (g) v	
+ unit: nvarchar(5) (包, 盒...) v	
+ unit_price: float v	
+ quantity: int v	
+ donatedate: nvarchar(10)	
+ memo: nvarchar(50)	
+ description: nvarchar(50)	
+ valid: nvarchar(5)	
+ createdate: datetime	
+ updatedate: datetime	

donatemember	
# 由 foodband 提供名單 # 目前不由網站新增 # 捐受贈者名單 # 預設帳號供批次匯入使用 # 請領次數 系統每日計算	
PK	dn_id: int
FK	su_id: id
FK	crt_id: id
+ ic: nvarchar(12)	
+ name: nvarchar(50)	
+ phone: nvarchar(10)	
+ mobile: nvarchar(10)	
+ unit: nvarchar(10)	
+ address: nvarchar(50)	
+ category: nvarchar(10) (個人 團體)	
+ people_cnt: nvarchar(5)	
+ house: nvarchar(5) (戶)	
+ valid: nvarchar(5)	
+ createdate: datetime	
+ updatedate: datetime	

add donate item

insert data [donate\\_item.donate\\_serial](#) (year + month + serial number ex: 105040001)

[donate\\_item.valid](#) default is Y

update donate item

update [donate\\_item.updatedate](#)

update data by auth, tp can update data create by ks etc....

delete donate item

update [donate\\_item.valid](#) to N

single select and multi select, update data by auth

import donate item

insert data with admin account of donate member and sysuser

download excel file with a few sample data

search donate item by name  
search donate item by expiryday  
search donate item by category

where [donate\\_item.name](#) like % or [donate\\_item.expiryday](#) like % or [donate\\_item.category](#) like %

only admin user ( su\_id => AXXX ) can get invalid data (sysuser.valid= N)

- [ receipt item ]

<div>sysuser</div> <div># 由 foodband 內部新增 # 承辦人員名單 # 預設帳號批次匯入使用</div> <div> <div>PK</div> <div>su_id: int</div> </div> <div>+ name: nvarchar(10)</div> <div>+ unit: nvarchar(10)</div> <div>+ phone: nvarchar(20)</div> <div>+ locate: nvarchar(10)</div> <div>+ auth: int</div> <div>+ account: nvarchar(10)</div> <div>+ pw: nvarchar(20)</div> <div>+ valid: nvarchar(5)</div> <div>+ createdate: datetime</div> <div>+ updatedate: datetime</div>	<div>receipt_item</div> <div># 親領跟直送單據差在親領單位</div> <div> <div>FK</div> <div>dn_id: int</div> </div> <div> <div>FK</div> <div>su_id: int</div> </div> <div>+ receipt_serial: int (全物字號)</div> <div>+ receipt_name: nvarchar(10)</div> <div>+ receipt_date: nvarchar(10)</div> <div>+ receipt_man: nvarchar(10)</div> <div>+ unit: nvarchar(5) (包, 盒...)</div> <div>+ receipt_unit: nvarchar(10)</div> <div>+ unit_price: float</div> <div>+ quantity: int</div> <div>+ type: nvarchar(10) (對象別)</div> <div>+ info: nvarchar(50) (0 收據 1 照片 2 both)</div> <div>+ valid: nvarchar(5)</div> <div>+ createdate: datetime</div> <div>+ updatedate: datetime</div>	<div>donatemember</div> <div># 由foodband 提供名單 # 目前不由網站新增 # 捐受贈者名單 # 預設帳號供批次匯入使用 # 請領次數 系統每日計算</div> <div> <div>PK</div> <div>dn_id: int</div> </div> <div> <div>FK</div> <div>su_id: id</div> </div> <div> <div>FK</div> <div>crt_id: id</div> </div> <div>+ ic: nvarchar(12)</div> <div>+ name: nvarchar(50)</div> <div>+ phone: nvarchar(10)</div> <div>+ mobile: nvarchar(10)</div> <div>+ unit: nvarchar(10)</div> <div>+ address: nvarchar(50)</div> <div>+ category: nvarchar(10) (個人 團體)</div> <div>+ people_cnt: nvarchar(5)</div> <div>+ house: nvarchar(5) (戶)</div> <div>+ valid: nvarchar(5)</div> <div>+ createdate: datetime</div> <div>+ updatedate: datetime</div>
add receipt item	insert data <b>receipt_item.donate_serial</b> (year + month + serial number ex: 105040001)  <b>receipt_item.valid</b> default is Y  <b>recepter</b> use autocomplete to get data from donate member	
update receipt item	update <b>receipt_item.updatedate</b>  <b>recepter</b> use autocomplete to get data from donate member	
delete receipt item	update <b>receipt_item.valid</b> to N  <b>single select</b> and <b>multi select</b> , update data by <b>auth</b>	
search donate item by name search donate item by catgory	where <b>receipt_item.name</b> like % or <b>receipt_item.category</b> like %	