Samsung Multifunction

SMART Multi*Xpress*

M5370LX I 4370LX

The New Way of Printing, Innovated for Smarter Business





Experience SMART printing, just like using a tablet

SMART Touch

- Intuitive usability and extendibility through the Samsung SMART UX Center, based on the Android™ OS and the first of its kind in the printing industry.
- · Pre-loaded printing apps for more convenient usability.
- Custom widgets for creating, instant one-tap access to frequently used functions.

SMART Use

- Independent functions and extensibility with direct web access through the web browser for quickly printing various web content without a PC.
- Access to more useful features and solutions by downloading them through the Samsung Partner Portal App store*.

SMART Manage

- Personalized UI for each user by arranging and managing the environment through My Page.
- Tracking of individual's usage, control accessibility and more.
- Quick custom app creation directly on the device.
- One-click instant response to different customers by customizing the UI configuration in a minute or less.



Boost productivity with ultra-fast performance

High scan rates

 Best-in-class scanning speeds of up to 35 single-sided images per minute (ipm)¹ and up to 60 double-sided ipm² using Dual-Scan ADF technology.

Faster print processing with zero fuss

- Print speeds of up to 53 pages per minute (ppm)³.
- 1 GHz dual-core CPU provides the power and capacity to swiftly print and copy jobs of virtually any size or complexity.

Sharper-quality print output

- Samsung's Rendering Engine for Clean Page (ReCP) technology for sharp text and clean images.
- 1,200 x 1,200 effective dpi resolution.



Lower TCO with cost-efficient Solutions and supplies

Resource savings with low total cost of ownership (TCO) printing

- Toner cartridges that yield up to 30,000 pages.
- Drums that yield 100,000 standard pages.

Customized, cost-efficient Samsung Business Core™ Printing Solutions (BCPS)

- · Require no dedicated server and IT resources.
- SecuThru[™] Lite 2 enhances document security and reduces costs with user authentication.
- Secure Login Manager guards valuable data and devices against unauthorized use.
- SmarThru[®] Workflow Lite increases productivity with an automated workflow solution.
- Cloud Connector scans to and prints from the Cloud with easy, secure access.
- Usage Tracker controls printing expenses by easily tracking device usage per user.



For further customization, numerous certified partner solutions are available through the Samsung XOA platform.

Samsung wireless and NFC printing option**

- User authentication enables authorized users to tap and print to a Samsung multifunction printer (MFP) from mobile devices.
- Secure printing releases documents held in a printer's memory with the BCPS and a tap on a mobile device.
- Easy wireless setup with a tap on a mobile device.
- Cloning of standard MFP functions with a tap on a mobile device.
- * The app store will be available in the Samsung Partner Portal beginning October 2014.
- ** The Samsung wireless and NFC printing option will be available beginning
 October 2014
- ¹ 55 single-sided ipm is available on the M5370 model only. 43 single-sided ipm is available on the M4370 model only.
- 2 80 double-sided ipm is available on the M5370 model only. 70 double-sided ipm is available on the M4370 model only.
- $^{\rm 3}$ 53 ppm is available on the M5370 model only. 43 ppm is available on the M4370.





Samsung Multifunction **SMART Multi**Xpress M5370LX I 4370LX

Specifications

M4370LX: 43 ppm M5370LX: 53 ppm 1 GHz Dual Core

Memory Operational Panel Interface

10.1" Color Touchscreen Panel Hi-Speed USB 2.0 Device (1EA), Host (3EA), Ethernet 10/100/1000 BaseTX, IEEE 802.11 b/g/n + NFC active (Optional)

Duty Cycle, Monthly

- M4370LX: 250,000 Images - M5370LX: 300,000 Images Dimension (WxDxH) 630 x 506 x 636 mm (24.8" x 19.9" x 25.0")

2 GB DDR3 Memory

Network Protocols

OS Compatibility

TCP / IPv4 / HTTP / HTTPS / SNMP (v1.2/v3) / LDAP / LDAPS / SMTP / SSL / TLS / IPSec / DNS / WINS / SLP / Bonjour / SSDP / DDNS / DHCP/BOOTP / IPv6 / NetBIOS over TCP / IP - Windows: XP (32 / 64 bit) / 2003 Server (32 /

64 bit) / Vista (32 / 64 bit) / 2008 Server (32 / 64

64 bit) / Vista (32 / 64 bit) / 2008 Server (32 / 64 bit) / 7 (32 / 64 bit) / 2008 Server R2 / Wink (32 / 64 bit) / 2012 (64 bit) - Linux: Red Hat Enterprise Linux 5 / 6, Fedora 11 / 12 / 13 / 14 / 15 / 16 / 17 / 18 / 19, openSUSE 11.0 / 11.1 / 11.2 / 11.3 / 11.4 / 12.7 / 12.3 , Ubuntu 10.04 / 10.10 / 11.0 / 11.10 / 12.04 / 12.10 / 13.04, SUSE Linux Enterprise Desktop 10 / 11, Debian 5.0 / 6.0 / 7.0 / 7.1, Mint 13 / 14 / 15

13/14/15 - UNIX: Sun Solaris 9 / 10 / 11 (x86 / SPARC) / HP-UNIX 11.0 / 11i v1 / 11i v2 / 11i v3 (PA-RISC / Itanium) / IBM AIX 5.1 / 5.2 / 5.3 / 5.4 / 6.1 / 7.1

Mac OS: X 10.5 - 10.9

Paper Handling

Max 3,140 Sheets @ 75 g/m² (Std 520 + MP 100 + 1 SCF 500 + 1 HCF 2,140 Sheets @75 g/m²) 500 Sheets @ 75 g/m2 Face Down

Output Capacity & Types Media Size

Media Type

Media Weight

Letter / Legal / Oficio / Folio / A4 / JIS B5 / ISO B5 / Executive / A5 / Statement / A6 / PostCard 4x6 / Envelope B5 / Envelope Monarch / Envelope COM-10 / Envelope DL / Envelope C5 / Envelope C6 / Custom [Min: 98 x 148 mm (3.85" x 5.83") / Max: 216 x 356 mm (8.5" x 14")] Plain Paper / Thin Paper / Bond / Punched / Pre-Printed / Recycled / Envelope / Label / Card Stock / Letterhead / Thick / Colored / Archive

Stock / Letterhead / Thick / Colored / Archive Supported Weight: 60 - 146 gsm (16 - 39 lb) Plain Paper: 70 - 90 gsm (18 - 24 lb) / Plain Paper (Duplex): 60 - 105 gsm (16 - 28 lb) / Thick Paper: 91 - 105 gsm (24 - 28 lb) / Thin Paper: 60 - 69 gsm (16 - 18 lb) / Bond: 105 - 120 gsm (28 - 32 lb) / Punched: 60 - 90 gsm (16 - 12 lb) / Pre-Printed: 75 - 85 gsm (20 - 23 lb) / Recycled: 60 - 85 gsm (16 - 23 lb) / Envelope: 75 - 90 gsm (20 - 24 lb) / Label: 120 - 150 gsm (32 - 40 lb) / CardStock: 90 - 163 gsm (24 - 43 lb) / Letterhead: 90 gsm cotton paper (24 lb) Width: 145 - 216 mm (5.7" - 8.5")

ADF Document Size Width: 145 - 216 mm (5.7" - 8.5") Length: 145 - 356 mm (5.7" - 14.0")

100 sheets @ 75 gsm ADF Capacity

Copy

First Copy Out Time M4370LX: 5 sec / M5370LX: 4.5 sec Up to 1,200 x 1,200 dpi 25% - 400% Resolution Zoom Rate

Up to 9,999 Duplex Copy

1→2Sided (Book / Calendar)

[DADF] - 1→1Sided

(Output: Book / Calendar)

2-1Sided (Original: Book / Calendar) 2-2Sided (Original: Book / Calendar /

Output: Book / Calendar)

Output: Book / Calendar)
Erase Edge / Margin Shift (Auto Center /
Custom Margin) / Book Center Erase / Form
Copy / Watermark Copy / Page Numbering /
Time & Date Stamp / IoB Stamp / Job Program /
Erase Background (Auto / Erase 7 Levels /
Enhance 3 Levels) / Erase Backside Image (10
Levels) / Shapness (11 Levels) / Negative
Image (On/Off) / Job Build / Mirror

Print

Copy Features

- Up to 1,200 x 600 dpi (Optical) - Up to 1,200 x 1,200 dpi Effective Output (1,200 x 600 x 2 bit)

Emulation SPLC / PCL5C / PCL6 / PS3 / PDF V1.7 Fonts - PCL: 93 Scalable Fonts / 1 Bitmap PostScript 3: 136 Scalable Fonts

Utilities

Anyweb Print / Easy Printer Manager / Easy Color Manager / Easy Document Creator / Net PC Fax / Direct Printing Utility / Easy Deployment Manager / Easy Eco Driver / Universal Printer Driver / Universal Scan Driver SyncThru Admin 6.0 / CounThru Enterprise / CounThru Pro / SmarThruWorkFlow Lite 1.0 / SecuThru Lite 1.0 / 2.0

Scanner

Solutions

- Simplex: Up to 55 ipm (@ 300 dpi) - Duplex: Up to 80 ipm (@ 300 dpi)

Compatibility TWAIN (Only for USB) - Platen / ADF: Max. 216 x 356 mm (8.5" x 14") TIFF-S / TIFF-M / JPEG / PDF / Compact PDF / Scan File Formats

- Optical: 600 x 600 dpi - Enhanced: 4,800 x 4,800 dpi

White-LED Scan Lamp Type of CCD Scan to Email / FTP / SMB / HDD / USB / Client Scan to Destination

Options

SCF: Second Cassette Feeder (SL-SCF5300)

Input Capacity 250 Sheets @ 75 g/m² 250 Sireles & 75 Jill Letter / Legal / Oficio / Folio / A4 / JIS B5 / ISO B5 / Executive / A5 / Statement/ Envelope Monarch / Envelope COM-10 / Envelope DL / Envelope C5 / Envelope C6 / Custom [Min: 98 x 152 mm (3.85" x 6") / Max: 216 x 356 mm (8.5" x 4.5") Media Size

Plain Paper / Thin Paper / Bond / Punched / Pre-Printed / Recycled / Envelope / Label / Cotton / CardStock / Letterhead / Thick / Colored / Archive

Colored / Archive
Plain Paper: 70 - 90 gsm (18 - 24 lb) / Plain
Paper (Duplex): 60 - 105 gsm (16 - 28 lb) / Thin
Paper: 60 - 69 gsm (16 - 18 lb) / Bond: 105 - 120
gsm (28 - 32 lb) / Punched: 60 - 90 gsm (16 - 24 lb)
/ Pre-Printed: 75 - 85 gsm (20 - 23 lb)
/ Recycled: 60 - 85 gsm (16 - 23 lb) / Envelope:
75 - 90 gsm (20 - 24 lb)
/ F54 x454 x 138 mm (21 8" x 17 0" x 5 4")

554 x 454 x 138 mm (21.8" x 17.9" x 5.4") Dimension (WxDxH)

HCF: High Capacity Cassette Feeder (SL-HCF001B) Media Size A5 / Statement / JIS B5 / Executive / Letter / A4

/ Folio / Oficio / Legal

Plain Paper / Thin Paper / Bond / Punched / Pre-Printed / Recycled / Cotton / CardStock / Letterhead / Thick / Colored / Archive Media Type

Letternead / Inick/ Colored / Archive Plain Paper; 70 - 90 gm (18 - 24 lb) / Plain Paper (Duplex): 60 - 105 gsm (16 - 28 lb) / Thin Paper: 60 - 69 gsm (16 - 18 lb) / Bond: 105 - 120 gsm (28 - 32 lb) / Punched: 60 - 90 gsm (16 - 24 lb) / Pre-Printed: 75 - 85 gsm (20 - 23 lb) /

Recycled: 60 - 85 gsm (16 - 23 lb) / Letterhead: 90 gsm Cotton Paper

554 x 454 x 387 mm (21.8" x 17.9" x 15.2") Dimension (WxDxH)

Media Weight

Short Stand (SL-DSK002S)

Dimension (WxDxH) 554 x 482 x 147 mm (21.8" x 19.0" x 5.8")

Cabinet Stand (SL-DSK001T) Dimension (WxDxH) 554 x 491 x 371 mm (21.8" x 19.3" x 14.6")

1-Bin Finisher (SL-FIN001M)

Capacity 500 Shee ets @ 75 g/m² Staple Cartridge Capacity 5,000 EA Stacking Finishing Tray 500 Sheets @ 75 g/m² 1 Position Stapling Positions

500 Sheets @ 75 g/m² 435 x 386 x 282 mm (17.1" x 15.2" x 11.1") Output Stacking Dimensions

10.4 kg Weight

2-Bin Finisher (SL-FIN002M)

Main tray: 500 Sheets @ 75 g/m² Top tray: 100 Sheets @ 75 g/m² Capacity

Staple Cartridge Capacity 5,000 EA Stacking Top Tray

100 Sheets @ 75 g/m² Stacking Finishing Tray 500 Sheets @ 75 g/m² Stapling Positions 1 Position 500 Sheets @ 75 g/m²

502 x 386 x 320 mm (19.8" x 15.2" x 12.6") Dimension (WxDxH)

Multi-Bin Mailbox (SL-MBT0401)

Number of Bins Capacity 400 Sheets @ 75 g/m 2 (100 Sheets / bin)

360 x 110 x 368 mm (14.2" x 4.3" x 14.5") Dimensions (WxDxH)

FDI Kit: Foreign Device Kit (SCX-KIT20F)

40 x 2 x 63 mm (1.6" x 0.1" x 2.5") Dimensions (WxDxH) Weight

0.03 kg

Fax Kit (SL-FAX1001) Compatibility

ITU-T G3 / Super G3 Modem Speed

33.6 Kbps

300 x 300 dpi (Mono) / 200 x 200 dpi (Color) Wireless + NFC (SL-NWE001X)

IEEE 802.11 b/g/n Wireless LAN NFC Type Active Type

Wireless + NFC (SL-NWE001X)

Dimensions (WxDxH) 55 x 205 x 145 mm (2.2" x 8.1" x 5.7") 0.17 kg Weight

Consumable

Black Toner Cartridge (MLT-D358S) Imaging Unit (MLT-R358) 100,000 Pages

Unsurpassed reliability and support that your business keep working

We know anything that helps business run more smoothly is priceless, especially when it comes to device management Backed by reliable performance and available whenever and wherever you're needed, we will always respond to your query.



partner@email.com



0000-000-0000 0000-000-0000



XXXXXX. XXXXXXXX XXXXX, XXXXX XXXX, XXXXX XXX XXX

Company Logo

Copyright © 2015 Samsung Electronics Co., Ltd. All rights reserved. Samsung is either trademarks or registered trademarks of Samsung Electronics Co., Ltd. Specifications and designs are subject to change without notice. Non-metric weights and measurements are approximate. All data were deemed correct at time of creation. Samsung is not liable for errors or omissions. All brand, product, service names and logos are trademarks and/or registered trademarks of their respective owners and are hereby recognized and acknowledged.

