Samsung
Monochrome Laser Printer

ML-5510 I 6510 Series

Hassle-free integration with Unlimited productivity

Unrivalled Productivity

Seamless integration for a simple business workflow solution

Delivering a business print solution that answers both simplicity and productivity needs can be a challenge, especially across today's diverse business environment. With hassle-free integration and easy-to-use functionality, the Samsung Mono Laser Printer ML-5510/6510 series delivers unlimited productivity – simply.

Configurations

- Top Cover
- Output Tray
- Control Panel
- Multi-Purpose Tray Cover
- Standard Tray
- Optional Tray
- Paper Level Indicator
- High Capacity Feeder (HCF)
- Short Stand

- Toner Cartridge
- USB Memory Port

Finisher with Stapler

4-bin Mail Box

Company Logo

SAMSUNG
BUSINESS

Samsung Monochrome Laser Printer
ML-5510 I 6510 Series

Specifications

General

Processor	Samsung 700MHz processor
Memory/Storage	256MB (Max. 768MB)
OS Compatibility	Windows 2000 / XP(32/64bits) / Vista(32/64bits) / 2003 Server(32/64bits) / 2008 Server(32/64bits) / 7(32/64bits) / 2008 Server R2(64bits)Various Linux OS: RedHat Enterprise Linux WS 4, 5 (32/64 bit) Fedora 4, 5, 6, 7, 8, 9, 10, 11, 12 (32/64 bit) SuSE Linux 10.0, 10.1 (32 bit) OpenSuSE 10.2, 10.3, 11.0, 11.1, 11.2 (32/64 bit) Mandriva 2005, 2006, 2007, 2008, 2009, 2009.1 (32/64 bit) Ubuntu 5.04, 5.10, 6.06, 6.10, 7.04, 7.10, 8.04, 8.10, 9.04, 9.10(32/64 bit) SuSE Linux Enterprise Desktop 10, 11 (32/64 bit) Debian 4.0, 5.0 (32/64 bit) Mac OS 10.3 ~ 10.6UNIX OS: Sun Solaris 9,10 (x86, SPARC) HP-UX 11.0, 11i v1, 11i v2, 11i v3 (PA-RISC, Itanium) IBM AIX 5.1, 5.2, 5.3, 5.4
Interface	Ethernet 10/100/1000 Base TX, High Speed USB 2.0, Host USB 2 Port (Rear 1 Port & Front 1 Port), IEEE 1284B Parallel connector (Option), 802.11 b,g, n wireless network (Option)
Noise Level	- ML-5510N, ML-5510ND Less than 56dBA (Printing), Background Noise Only (Less than 30dBA) (Standby) - ML-6510ND Less than 58dBA (Printing), Background Noise Only (Less than 30dBA) (Standby)
Duty Cycle, Monthly	275,000 sheets
Dimension (WxDxH)	464 x 540 x 420mm
Weight	- ML-5510N 34.2kg (Inc. Imaging Unit/Toner/WTB), 30.6kg (exc. Imaging Unit/Toner/WTB) - ML-5510ND , ML-6510ND 34.8kg (Inc. Imaging Unit/Toner/WTB), 31.2kg (exc. Imaging Unit/Toner/WTB)
Power Consumption	- ML-5510N, ML-5510ND 820W(Active)/100W(Ready)/10W(Sleep) - ML-6510ND 900W(Active)/120W(Ready)/10W(Sleep)

Print

Speed (Mono)	- ML-5510N, ML-5510ND Up to 52 ppm in A4 (55 ppm in Letter) - ML-6510ND Up to 62 ppm in A4 (65 ppm in Letter)
Resolution	Up to 1,200 x 1,200 dpi effective output
First Print Out Time (Mono)	As fast as 7.8sec
Emulation	PCL5e, PCL6, KS/KSSM, KS5895, IBM ProPrinter, EPSON, PostScript3, PDF Direct V1.7, XPS v1.0
Duplex	- ML-5510N Optional - ML-5510ND , ML-6510ND Built-in

Paper Handling

Input Capacity and Types	520-sheet Cassette, 100-sheet Multi Purpose Tray @80g/m^2, (550-sheet Cassette, 100-sheet Multi Purpose Tray @75g/m^2)
Output Capacity and Type	500-sheet Face Down
Media Size	76 x 127mm (3"" x 5"") ~ 216 x 356mm (8.5"" x 14""), (Envelope: Monarch, No10, DL, C5, C6, No9)
Media Type	Printer Default, Plain Paper, Thick Paper, Thin Paper, Bond Paper, Color Paper, CardStock, Labels, Transparency, Envelope, Preprinted, Recycled Paper, Archive, Extra Thick
Envelope Capacity	50sheets from Cassette & 50sheets from optional 1st Second Cassette, (Max. 100sheets)

Consumable

Yield	Standard: Average Cartridge Yield 10K standard pages High Yield: Average Cartridge Yield 30K standard pages (Ships with 10,000 pages Starter Toner Cartridge) Imaging Unit: Average Yield 80K standard pages Declared cartridge yield in accordance with ISO/IEC 19752.
Type	2-piece Cartridge (Toner & Imaging Unit (Drum Unit))
Model Code	Toner Cartridge: MLT-D309L, MLT-D309S, Imaging Unit: MLT-R309

Option

ML-5510N	520-sheet Cassette Tray @80g/m^2 (550-sheet Cassette Tray @75g/m^2), 2,000-sheet High Capacity Feeder @80g/m^2, Short Stand, 500-sheet Finisher with Stapler, 400-sheet 4-bin Mailbox, 160GB HDD, 512MB Memory, IEEE 1284B Parallel Connector, 802.11 b, g, n wireless network, Duplexer
ML-5510ND, ML-6510ND	520-sheet Cassette Tray @80g/m^2 (550-sheet Cassette Tray @75g/m^2), 2,000-sheet High Capacity Feeder @80g/m^2, Short Stand, 500-sheet Finisher with Stapler, 400-sheet 4-bin Mailbox, 160GB HDD, 512MB Memory, IEEE 1284B Parallel Connector, 802.11 b, g, n wireless network

* product specifications may change without notice, and product lineup may vary depending on your regions.

Unsurpassed reliability and support that your business keep working

We know anything that helps business run more smoothly is priceless, especially when it comes to device management Backed by reliable performance and available whenever and wherever you're needed, we will always respond to your query.

Email partner@email.com

Call 0000-000-0000 0000-000-0000

Write XXXXXX, XXXXXXX XXXXX, XXXXX XXXX, XXXXX XXX XXX

Company Logo

SAMSUNG BUSINESS