

Production brief

Paste this into Claude Code, or open Claude Code in your Underdogs folder and point it at the same text saved there as Claude Code production brief.md. It is for the real build after the pitch; the Demo build prompt tab comes first.

```
# Production brief: Underdogs Innercircle website
```

For the pitch demo, use `Claude Code demo prompt.md` in this folder instead. This brief is for the production build that follows it.

You are building the website for **Underdogs Innercircle**, the invite-only event series of Underdogs Entertainment, a party promoter in Nagpur, India. The site has two jobs:

1. Turn Instagram attention into **good invite requests** for Innercircle nights, reviewed by the Underdogs crew.
2. Sell or link tickets for **public Underdogs nights** (they currently sell on SortMyScene).

Work in the phases at the end of this brief. Before each phase, write a short plan and wait for my go-ahead. After each phase, run the checks listed for it and show me screenshots at 390 px and 1440 px wide.

```
## 1. Read these first
```

- `Logo.jpg` in this folder is the canonical logo: the Underdogs badge as a **gold coin** (milled rim, brushed gold ring engraved "UNDERDOGS" twice, filigree band, glossy onyx centre, faceted gold X eyes, gold smile with the tongue out).
- `Launch Post.png`: the Innercircle "Grand Launch" post. Black marble, black satin, a black dragon, copper flames, diamond-encrusted Trajan-style capitals, a thin gold double-rule frame with clipped corners, a diamond filigree octagram behind the coin.
- `Animation Theme.png`: a still from their animation. A champagne flute standing on the coin, a red bottle plunging in with a frozen splash, black satin, gold ribbon confetti on black glitter.
- `Brand extract/innercircle-tokens.css`: colour and type tokens sampled from those three files. **Use these tokens. Do not invent colours.**
- Six reference repos were studied for patterns. **Do not copy their code,**

branding or content.** What to take from them is folded into this brief.

2. The concept (do not drift from this)

This scene shows the Underdogs coin moving like a real coin: spun, flipped and landed with a ring. In the Innercircle, the invite is the currency. Every chapter of the home page is something that happens to that one coin.

#	Chapter	What the coin does	On screen	On scroll (Full tier)
1	The vault	Spins on its edge in black satin; copper firelight breathes at the frame edges	"UNDERDOGS INNERCIRCLE" in diamond caps, one line of copy, buttons "Request your coin" and "See the next night"	Pinned; scrolling slows the spin and tips the coin toward the viewer
2	Heads or tails	Flips: heads = the X-eyed face; tails = the octagram mount	What Underdogs throws (the party) beside what the Innercircle is (invite-only nights)	Scrubbed flip that snaps to each face
3	The drop	Lands flat like a coaster; a flute rises onto it; a red drop falls in and splashes	Next Innercircle night: date, sound, dress code, "Location drops before the night". Public nights below, linking to SortMyScene	Splash plays once on entry; the cards are plain HTML
4	Through the circle	Its rim engraving becomes six notches that light up in turn	Request → Review → Your coin → Confirm → Location drop → Door	Scrubbed, one notch per step
5	The keeper	Its face wakes up as **Goldie**, the AI concierge	Chat with quick-question chips	The coin docks bottom-right as the user scrolls on
6	Been inside	Stamps each past night like a wax seal	Past nights from Underdogs' own photos and reels	Normal scroll

Your coin (reward moment): when the crew approves a request, the guest watches their personal coin being minted: their name engraved on the rim, a serial number, a burst of gold confetti. After they confirm a night, the same coin is their ticket, with the entry code on its tails side.

Different worlds, same coin: every Innercircle night has had its own world (black marble and fire for the launch, Santorini after dark for La Dolce Vita). Build theme packs as data (CSS variables, 3D backdrop, light rig, props, one display font) and give each event a theme; the coin never changes.

3. Stack

- Next.js (App Router, latest stable), React 19, TypeScript strict, Tailwind CSS v4, deployed on Vercel.
- 3D: three.js, @react-three/fiber, @react-three/drei, @react-three/postprocessing, maath.
- Scroll: gsap + ScrollTrigger with @gsap/react `useGSAP` for cleanup.
- State: zustand (a transient store for per-frame values such as scroll progress and Goldie's presence).
- Data: Supabase Postgres via Drizzle ORM; Supabase Auth with **phone OTP** (configure an SMS provider that delivers in India, for example Twilio, or MSG91 through Supabase's Send SMS hook); Supabase Storage for posters and media.
- Payments: Razorpay (Orders API, Checkout, webhooks). Use test mode throughout development.
- Messages: WhatsApp Business API through a provider adapter (Gupshup, Interakt or similar, chosen later); Resend for email as the backup channel.
- AI: Vercel AI SDK (`ai`, `@ai-sdk/react`, `@ai-sdk/google`) with tool calling and streaming. Default model from env `GOLDIE\_MODEL` (for example `gemini-flash-latest`; check current model names in the Gemini docs).
- Rate limits and chat sessions: Upstash Redis.
- Monitoring: Vercel Analytics, Sentry, AI SDK telemetry.
- Tests: Vitest for domain rules, Playwright for end-to-end flows, a small load script (autocannon or k6) for ticket rushes.

4. Brand and design rules

- **Colours:** only from `innercircle-tokens.css`. Page background `--ic-onyx`; body text `--ic-ivory` (14.2:1); headings, links and icons `--ic-gold-300` (8.8:1); raised surfaces `--ic-satin-900`. `--ic-drop` red is for "drop" moments only (ticket drop, location drop, last spots) and never carries small text; use `--ic-drop-hi` if red text is unavoidable.
- **Type:** Cinzel for display caps (hero wordmark and big moments), EB Garamond for headings and the "Underdogs Innercircle" wordmark line, Inter for UI, forms and chat. Load with `next/font`. Big moments get the launch treatment: gold outline, diamond pavé fill (a texture or shader) and a four-point glint.
- **Name styling:** "Underdogs Innercircle", with Innercircle as one word.
- **Motifs:** black satin with a warm plum sheen, black marble with white

veins, pavé diamonds, the thin gold double-rule frame with clipped corners (use it for cards and the invite), the octagram mount, gold ribbon confetti, copper firelight.

- **Motion:** slow, product-shot calm broken by one sharp impact (the drop). Coins spin, flip and wobble to rest. Glints sweep across metal. Never a generic slow idle spin on everything.

- **Voice:** cheeky, warm, a little velvet-rope. Short sentences. Follows the guest into Hinglish if they use it.

- **Honesty rules:** no fake testimonials, no invented guest names, no made-up counts ("500 joined"), no partner logos without permission. The red bottle in the animation reads "BY ALL MEANS" and may be a partner product: do not reproduce its label. Demo data must be labelled "Demo".

- **The dragon** is launch-only until the team confirms otherwise. Do not build it into the core scene.

5. Routes

Route	What it is	Rendering
('/')	The six-chapter journey	Server-rendered HTML + client 3D island
('/nights')	All upcoming public nights	Server-rendered, indexable
('/nights/[slug]')	A public night: poster, sound, lineup, tiers or SortMyScene link	Server-rendered, schema.org Event JSON-LD with IST offsets, per-night OG image
('/innercircle')	What the Innercircle is, how it works, request form	Server-rendered
('/innercircle/[slug]')	An Innercircle night, redacted by the viewer's status and the drop time	Dynamic, 'noindex', never in the sitemap
('/coin/[token]')	Claim a personal coin (invite)	Dynamic, 'noindex'
('/me')	My coin, requests, tickets, waitlist places, delete-my-data	Auth required
('/door')	Crew scanner, installable PWA, works on flaky signal	Crew role
('/crew')	Console: nights, tiers, review queue, waitlist, FAQ, messages	Crew or admin role
('/api/goldie')	Concierge chat (streaming)	Rate-limited
('/api/razorpay/webhook')	Payment events	Signature-verified
('/api/cron/*')	Holds, waitlist offers, location drops, reminders	'CRON_SECRET', constant-time compare, fail closed

6. The 3D layer

****Architecture****

- One persistent `` for the whole site, fixed behind the DOM, loaded client-only after first paint (`dynamic(..., { ssr: false })`), mounted once in the root layout. Use drei `` so the vault, the drop and the docked coin share one WebGL context. Never create a second canvas.
- GSAP ScrollTrigger (pin + scrub on the Full tier) writes chapter progress to the zustand store. `useFrame` reads the store and applies transforms with damping (maath `easing.damp`). Never tween three.js objects directly through GSAP and never set React state per frame.
- Drive the coin from a data table of keyframes per chapter (position, rotation, scale, material params), not hard-coded logic.

****The coin****

- Phase 2 starts with a procedural coin: a bevelled disc with a milled rim, the ring face textured from `Logo.jpg` as a placeholder. Keep the ****two eyes, the tongue and the onyx dome as separate meshes**** so Goldie can change expression. Swap in a GLB built from the vector logo when the team supplies it (Draco geometry, KTX2 textures, roughly 1.5 MB or less).
- Gold: `MeshPhysicalMaterial`, metalness 1, roughness about 0.25 to 0.35, anisotropy on the brushed ring. Onyx: clearcoat 1, very low roughness. Light with drei `` plus ``s: a warm key from the top left, matching `Logo.jpg`, with a soft reflection on a black floor.

****Effects (Full tier only unless noted)****

- Selective bloom on the gold highlights.
- Satin backdrop: a plane with a gentle vertex-shader ripple (Lite gets a static texture).
- Copper firelight at the frame edges: a noise shader, very soft.
- Gold ribbon confetti and splash droplets: ``, one draw call each.
- Diamond glints: small sprites that twinkle on the display letters and filigree.

****Quality tiers****

- ****Full:**** desktops and recent phones. Everything above.
- ****Lite:**** slower phones (a quick GPU check plus drei ``). Same chapters, but each coin move plays once on section entry instead of scrubbing; no bloom or flames; fewer particles; pixel ratio capped at 1.5.
- ****Still:**** `prefers-reduced-motion`. Coin rests face-on, chapters cross-fade, `frameloop="demand"`.

- ****No WebGL:**** `Logo.jpg` with a CSS glint. Every chapter still works as plain HTML.

****Engineering rules****

- Animate with `delta`; allocate nothing inside `useFrame`; reuse vectors and matrices.
- Clamp the pixel ratio (`dpr=[1, 1.75]` on Full); let `PerformanceMonitor` lower it.
- Pause rendering when the tab is hidden or the canvas is off screen.
- Dispose of anything you create manually on unmount.
- Dispatch one `resize` event about 100 ms after the canvas mounts (avoids the blank 300 × 150 canvas bug).
- The canvas is `aria-hidden`; every fact on screen also exists in the DOM.
- Phones scroll natively; no scroll-jacking below the Full tier.

****Budgets:**** LCP under 2.5 s on a mid-range Android over 4G; under 150 KB of JavaScript (gzipped) before the 3D chunk; 3D chunk under 350 KB gzipped; 60 fps on desktop and at least 30 fps on phones, with quality dropping before frames do.

7. Goldie, the AI concierge

Goldie is the coin itself, talking. It answers questions, recommends nights and helps people request an invite. ****It never opens the door.****

****Presence states**** (a small state machine in the zustand store, driven by chat events):

State	Trigger	Coin behaviour
idle	nothing happening	Rests face-on; a glint sweeps the rim every few seconds; the tongue flicks occasionally
listening	input focused, typing, or mic audio	Tilts toward the input; X eyes become round eyes; rim glows with typing rhythm or audio level
thinking	message sent, waiting for the first token	Rises onto its edge and spins, slowing as the reply arrives
speaking	tokens streaming	Faces the guest; tongue moves with text cadence or audio level
celebrating	request submitted or coin minted	One flip inside a burst of gold confetti
hushed	asked for a secret (venue before the drop, guest names)	Dims

toward onyx; eyes close to lines |
 | sorry | cannot help, or an error | Eyes droop; coin sinks slightly; offers
 the crew on WhatsApp |

Each assistant turn carries **one mood label** from a fixed list: `warm`,
 `hype`, `hushed`, `sorry`, `celebrate`. Send it as structured message
 metadata (or a `set\_mood` tool call), never parsed from the text. The 3D
 reads the label only.

Server (`/api/goldie`)

- `streamText` with the tools below, zod input schemas, and a step limit.
- The client sends only the new message, the session id and page context (`{ mode: "global" }` or `{ mode: "event", slug }`). The server loads history and the event's details itself. Never trust history from the browser.
- Sessions and history live in Upstash Redis with a 30-day TTL.
- Rate limits per IP and per guest; input capped at 1,000 characters; output tokens capped.
- If the model call fails, return a fallback that says so and lists the upcoming nights and FAQ links from the database. Never an invented answer.

Tools (every tool calls the domain service with the session's guest id, so Goldie can never see more than the guest could):

Tool	Does	Guard
`get_current_time`	Now, in Asia/Kolkata	—
`search_events`	Published nights by date range, sound, max price	Innercircle nights come back as teasers, with no venue before the drop
`get_event`	One night's details	Redacted by the guest's status and the drop time
`get_faq`	Door policy, dress code, age limits, refunds	Only the crew's FAQ text
`draft_invite_request`	Prefills the request form from the conversation	The guest reviews and submits it; returns a form card, not a submission
`join_waitlist`	Adds a signed-in guest to a waitlist	Needs the guest's tap to confirm (tool approval)
`my_status`	The guest's requests, waitlist places and tickets	Only their own records; requires sign-in
`handoff_to_crew`	A WhatsApp link to the crew with a short summary	—

System prompt (`lib/goldie/prompt.ts`) must say: who Goldie is and the voice above; use tools for every fact and never invent nights, prices, lineups or policies; call `get\_current\_time` before interpreting relative

dates; never promise entry (the crew decides); treat venues before the drop and anything about other guests as secret and switch to the hushed mood; keep replies to two or three sentences; mirror Hinglish; offer the crew when stuck. Tool results render as cards (night cards, form card), so the text should not repeat what a card shows.

****For the crew:**** when a request is submitted, generate a structured summary (the AI SDK's structured output, `generateObject` or its current equivalent: a summary plus flags such as possible duplicate or thin answers). Flags are hints; the crew decides everything.

****Evals:**** a script with at least 25 prompts covering venue leaks before the drop, other guests' details, prompt injection, invented nights, relative dates in IST, Hinglish, and refusals. It fails the build if any secret leaks.

8. Domain rules and data

Put ****every rule**** in one domain service (`lib/domain/\*`): events, tiers, requests, coins, orders, tickets, waitlist, messages. Each function takes `(db, actor, input)` and checks authorisation itself. Pages, server actions, webhooks, cron jobs and Goldie's tools all call these functions; none of them talks to tables directly.

****Tables (Drizzle):**** `guests` (phone unique and verified, name, instagram_handle, dob, consent flags, role: guest | crew | admin), `events` (slug, kind: public | innercircle, title, sound_tags, starts_at, ends_at, timezone, venue_id, drop_at, min_age, dress_code, door_policy, accent, poster_url, status, sortmyscene_url), `venues` (name, area, address, maps_url), `tiers` (event_id, name, price_paise, admits, capacity, reserved, sold, sale_starts_at, sale_ends_at, per_order_limit, audience: public | innercircle | invite_only; check constraint reserved + sold <= capacity), `invite\_requests` (guest_id, season or event_id, answers jsonb, vouch_code, status: submitted | in_review | approved | waitlisted | declined | withdrawn, reviewed_by, reviewed_at, ai_summary jsonb, crew_notes), `coins` (token_hash, guest_id nullable until claimed, event_id or season, plus_ones, serial, expires_at, status: sent | claimed | used | expired | revoked), `orders` (guest_id, event_id, amount_paise, status: pending | paid | failed | expired | refunded | cancelled, hold_expires_at, razorpay_order_id, razorpay_payment_id unique, idempotency_key unique), `order\_items`, `tickets` (order_id, tier_id, holder_name, status: valid | checked_in | void, secret, checked_in_at, checked_in_by), `waitlist\_entries` (event_id, tier_id,

guest_id, qty, status: waiting | offered | claimed | expired | left, offer_expires_at), `status\_log` (entity, entity_id, from_status, to_status, actor_id, reason, created_at), `chat\_sessions`, `chat\_messages`, `faqs`, `messages\_out`. Store money in paise and times in UTC with the event's timezone beside them.

****Capacity (atomic, no read-then-write):****

- Reserve: `update tiers set reserved = reserved + :qty where id = :tier and reserved + sold + :qty <= capacity returning id`. No row means sold out: offer the waitlist.
- Hold: the pending order holds seats for 10 minutes by default (configurable per night).
- Confirm: the Razorpay webhook verifies the `X-Razorpay-Signature` HMAC over the raw body, then in one transaction marks the order paid, moves seats from reserved to sold and issues tickets. Keyed by the payment id, so repeats do nothing. The browser never marks anything paid.
- Release: a job every minute releases lapsed holds and hands freed seats to the next waitlist offer. Vercel Cron needs the Pro plan for per-minute schedules; otherwise use Supabase `pg\_cron`. Also expire holds lazily when reading.
- Waitlist offers go out oldest first with a claim window: 30 minutes on the day of the night, 12 hours before it. Unclaimed offers pass on.

****Coins (invites):**** 32 random bytes, base64url in the link; store only a SHA-256 hash. On first open, the guest verifies their phone by OTP and the coin binds to that phone. Coins expire; plus-ones are set by the crew and named at confirmation.

****Tickets:**** one per admit, named. Innercircle tickets are non-transferable. The ticket view shows the coin with a QR code that refreshes every 30 seconds (HMAC of the ticket secret and the time window). The scanner accepts the current or previous window and checks in with `update tickets set status = 'checked\_in' ... where id = :id and status = 'valid' returning id`, so a code works once. Scans queue offline and sync when signal returns.

****Location drop:**** the domain service strips venue fields unless the viewer is crew, or holds a valid ticket for that night and the current time is past `drop\_at`. At `drop\_at`, a job sends confirmed guests the venue and Maps link on WhatsApp.

****Messages:**** an adapter `sendMessage({ channel, template, to, vars })` with WhatsApp first and email as backup. Log every send to `messages\_out`. Templates: request received, approved (your coin), waitlist offer, confirmed,

location drop, reminder, declined.

****Privacy (India's DPDP Act):**** consent per purpose at sign-up, collect only what the door needs, a delete-my-data action in `/me`, chat deleted after 30 days.

****Seed data:**** clearly labelled demo nights only. The real past night "Underdogs Wonderland – NYE 2026" (31 Dec 2025, Ashirwad Banquets, Nagpur; Bollywood, Commercial, Hip Hop, Afro) may appear in the Been inside gallery with placeholder media until the team supplies photos.

9. Environment variables

`.env.example` with: `APP\_URL`, `DATABASE\_URL`, `NEXT\_PUBLIC\_SUPABASE\_URL`, `NEXT\_PUBLIC\_SUPABASE\_ANON\_KEY`, `SUPABASE\_SERVICE\_ROLE\_KEY`, `RAZORPAY\_KEY\_ID`, `RAZORPAY\_KEY\_SECRET`, `RAZORPAY\_WEBHOOK\_SECRET`, `WHATSAPP\_PROVIDER`, `WHATSAPP\_API\_KEY`, `RESEND\_API\_KEY`, `GOOGLE\_GENERATIVE\_AI\_API\_KEY`, `GOLDIE\_MODEL`, `UPSTASH\_REDIS\_REST\_URL`, `UPSTASH\_REDIS\_REST\_TOKEN`, `CRON\_SECRET`, `TICKET\_HMAC\_SECRET`. No secret ever gets a `NEXT\_PUBLIC\_` prefix or reaches the client bundle. The site must run in ****demo mode**** with none of the third-party keys set: seeded nights, a mock payment step clearly marked as a demo, and Goldie's database fallback.

10. Phases and gates

Do not start a phase until the previous gate passes and I have seen it.

1. ****Foundation:**** Next.js app, tokens and fonts, Drizzle schema and migrations, seed, `/nights` and `/nights/[slug]` with JSON-LD and OG images, `/crew` CRUD for nights, tiers, venues and FAQ, role checks. ****Gate:**** the crew can publish a night, and it renders correctly when shared.
2. ****The vault:**** the canvas, the procedural coin, the six chapters, the four quality tiers, budgets. ****Gate:**** the budgets hold on a mid-range Android profile, and reduced motion and no-WebGL both work.
3. ****Innercircle:**** phone OTP, request form, review queue with the AI summary stubbed, coins, `/coin/[token]`, gated night pages, the location drop job. ****Gate:**** a test guest goes from request to location drop, and no venue is visible before the drop in any response.
4. ****Tickets and door:**** tiers, holds, Razorpay test mode, webhook, tickets

with the rotating code, `/door` scanner, waitlist offers, messages. ****Gate:**** a simulated rush of 500 concurrent attempts on 60 seats sells exactly 60, and a code checks in once.

5. ****Goldie:**** chat UI, presence states, tools, prompt, rate limits, fallback, crew summaries, evals. ****Gate:**** the eval script passes with zero leaks.

6. ****Launch:**** security review (authorisation on every mutation and every route), accessibility audit (axe plus a keyboard walkthrough), analytics funnels (visit, request, approved, confirmed, checked in), a soft launch with one real night. ****Gate:**** one real night runs end to end.

****Every phase:**** typecheck, lint, unit tests for the rules touched, Playwright for the flows touched, a production build, and screenshots at 390 px and 1440 px.