

Problem Set 11

Question 1.

- (a) In your own words, describe what a "Greedy" algorithm is.
- (b) Give some examples of problems that a greedy algorithm would **not** be able to solve optimally.

Question 2. *Averaging down* (Levitin 9.1.4)

There are $n > 1$ identical vessels, one of them with W liters of water and the others are all empty. We can perform the following operation: Take two of the vessels, and split the total amount of water in them equally between them.

The goal is to achieve a minimum amount of water in the vessel that begins with W liters of water by a sequence of operations. Give an algorithm in pseudocode that achieves this and reason why it works.

Question 3. *Bachet's problem of weights*

Find an optimal (i.e. smallest) set of n weights $\{w_1, w_2, \dots, w_n\}$ so that it would be possible to weigh on a balance scale any integer load in the largest possible range from 1 to 13, provided



- (a) weights can be put only on the free cup of the scale,
- (b) weight can be put on both cups of the scale.
- (c) Provide pseudocode for solving the general case with for the range $1 \dots W$. Justify why your algorithm works.

Question 4.

- (a) Given a hash table with 9 slots and the hash function $h(k) = k \bmod 9$.¹

Demonstrate what happens when we insert the keys 82; 7; 18; 17; 19; 23; 21; 14; 10 into a hash table. If two values have the same hash, we say that they *collide*, put them in a **(singly) linked list**.

- (b) Operation on a hash table are:

- **Insert(k)**, insert a key, k , into the hash table.
- **Delete(k)**, delete the instance of k (if it exists) from the hash table.
- **Search(k)**, If k exists in the table, return it.

For the hash map above, explain and provide the worst-case time complexities for these operations.

- (c) It is known that in the average case these operations can be performed in $\Theta(1)$. What factors do you think are relevant for making a hash table fast?

¹That is to say, every key, k , is sent to the location with index $h(k)$, we say that $h(k)$ is the *hash of k*