

Computational Design of Woodwind Instruments

A Research Report

Integrating Open-Source Tools for Bore Profile Optimization

Instrument Designer Project
Desktop & Laptop Collaborative Team

July 2026 (ongoing)

Executive Summary

This report documents the design, development, and evaluation of a computational tool for designing woodwind instruments. The project integrates multiple open-source acoustic simulation tools (OpenWInD, chalumier, demakein) with optimization algorithms (NSGA-II, scipy.optimize) to create a platform for rapid instrument prototyping. We document what worked, what failed, what we learned from the academic literature, and where we believe the field is heading. This report is a living document that will be updated as the project progresses.

Key findings so far:

1. NSGA-II (evolutionary multi-objective) is the wrong algorithm for bore optimization — every successful instrument design tool in the literature uses gradient-based methods
2. Peak-detection-based frequency matching creates discontinuous cost functions that defeat gradient-based optimizers — Ernoult's (2020) phase-based resonance detection solves this
3. Two-phase optimization (Noreland 2013) is essential — "little success omitting Phase 1"
4. Starting from a known-good bore (Buffet R13 dimensions) dramatically improves convergence
5. 3D printing validation shows instruments can be produced that musicians cannot distinguish from originals (Yamamoto 2025)
6. The np.inf penalty in pymoo corrupts NSGA-II's crowding distance computation — a simple $1e10$ sentinel is correct

Current status: 3.11 cents RMS on clarinet Bb (borderline <3 cent target). Building scipy.gradient-based optimizer (L-BFGS-B) with two-phase workflow.

Table of Contents

1. Introduction & Motivation 2. Project Architecture 3. Acoustic Simulation: OpenWInD Integration 4. Optimization Approaches: What We Tried 5. The np.inf Bug: A Cautionary Tale 6. Bore Profile Representation 7. Frequency Target System 8. Research Literature Review 9. Software Tools Survey 10. 3D Printing & Manufacturing 11. AI-Assisted Design 12. Lessons Learned 13. Future Directions 14. References

1. Introduction & Motivation

1.1 The Problem

Designing a woodwind instrument (clarinet, flute, oboe, etc.) requires careful shaping of the bore profile (internal cross-section) so that each note plays at the correct pitch. The relationship between bore geometry and pitch is governed by acoustic wave propagation — a complex physical system that cannot be solved analytically for realistic instruments.

Traditionally, instrument design is a craft skill passed through apprenticeships. A master maker spends years learning how bore shape affects intonation, tone quality, and playability. This creates a barrier to entry and limits innovation.

1.2 Our Goal

Build a software platform that:

1. Simulates acoustic impedance of arbitrary bore profiles (using OpenWInD)
2. Optimizes bore geometry to match target frequencies (using scipy/pymoo)
3. Integrates existing tools (chalumier, demakein) rather than reimplementing them
4. Provides a usable GUI for instrument designers (Tauri desktop app)
5. Exports manufacturing-ready files (SVG, DXF, G-code)

Guiding principle: Integrate proven tools. Don't reinvent the wheel. Original work only where it genuinely improves on existing methods.


1.3 Target Accuracy

Phase	Target	Status
C1	<20 cents RMS	**Achieved** (3.11 cents)
C2	<10 cents RMS	**Achieved**
C3	<5 cents RMS	**Achieved** (3.11 cents)
C4	<3 cents RMS	Borderline — need more evals to break through cle

Reference: Noreland et al. (2013) achieved <5 cents RMS on a real clarinet prototype. Measured vs computed average deviation was 1.97 cents after correcting a ~12 cent flat offset.

2. Project Architecture

2.1 System Overview



2.2 Technology Stack

Component	Technology	Rationale
Desktop app	Tauri (Rust + React)	Native features, small binary, web UI
Backend	Python FastAPI	Rich scientific Python ecosystem
Acoustic simulation	OpenWInD	1D spectral FEM, actively maintained
Optimization	scipy.optimize / pymoo	Gradient-based / evolutionary
Cache	SQLite (mp_cache.py)	Shared across parallel workers
AI advisor	Rule-based + Ollama LLM	No dependencies for basic mode
Export	SVG, DXF	Standard manufacturing formats

2.3 Branch Strategy

Branch	Purpose
`option-a-tauri`	Main integration (stable)
`experiment/chalumier-integration`	Full chalumier UI
`experiment/staged-optimization`	Noreland 3-stage optimizer
`experiment/processpoolexecutor`	Parallel benchmark
`experiment/v2-scipy-gradient`	**NEW** — scipy.optimize replacement

3. Acoustic Simulation: OpenWInD Integration

3.1 What OpenWInD Does

OpenWInD (Open Woodwind Design) is a 1D spectral finite element method for computing the input impedance of wind instruments. It models:

- **Bore geometry:** Arbitrary cross-section profiles
- **Visco-thermal losses:** Boundary layer effects in narrow tubes
- **Tone holes:** T-junctions with series/shunt impedances
- **Cutoff frequency:** Lattice filtering behavior
- **Radiation:** Open-end radiation impedance

3.2 Our Integration

We call OpenWInD through its Python API:

```
from openwind import ImpedanceComputation

freqs = np.linspace(100, 3000, 5000)
ic = ImpedanceComputation(freqs, bore_csv, unit="m", diameter=False, temperature=20.0)

freq = np.array(ic.frequencies)
Z = np.array(ic.impedance)
mag = np.abs(Z)
```

3.3 Impedance Peak Detection

Peaks in the impedance magnitude correspond to resonances (notes the instrument can produce). We detect peaks using:

```
from scipy.signal import find_peaks

peak_height = np.max(mag) * 0.02
peaks, _ = find_peaks(mag, height=peak_height, distance=2, prominence=peak_height * 0.5)
```

With quadratic interpolation for sub-bin accuracy:

```
f_vertex = -b / (2a) # parabola vertex
```

3.4 Known Issues

1. Peak detection is discontinuous under geometry perturbation — peaks merge/disappear during optimization, creating a non-smooth cost landscape. This is the fundamental problem with peak-matching approaches (Ernault 2020).
2. Resolution matters — 800 frequency points gives ~4 Hz resolution; 5000 gives ~0.6 Hz. Quadratic

interpolation helps but cannot fix missing peaks.

3. BLAS thread oversubscription — Each OpenWInD worker spawns BLAS threads. With 6 workers $\times$ N threads, `scipy.sparse.linalg.spsolve()` deadlocks. Fix: `OMP_NUM_THREADS=1`.

4. Optimization Approaches: What We Tried

4.1 NSGA-II (Current Approach)

Implementation

We used pymoo's NSGA-II multi-objective evolutionary algorithm with:

- **3 objectives:** frequency accuracy (RMS cents), scale evenness (std of frequency ratios), projection (negative peak magnitude)
- **1 constraint:** smoothness (sum of radius jumps exceeding threshold)
- **Monotonicity repair:** Pool Adjacent Violators Algorithm (PAVA) applied after each generation
- **Parallel batch evaluation:** ProcessPoolExecutor dispatches full population to workers

Results

Configuration	RMS (cents)	Wall Time	Notes
pop=10, gen=3, serial	2.00	23s	Smoke test — passes
pop=15, gen=10, serial	3.11	~250s	Best result
pop=40, gen=50, batch	38.78	620s	FAILED — np.inf corruption

Why It Failed at Scale

The np.inf penalty (laptop's code review change) corrupted NSGA-II's crowding distance computation:

```
# pymoo's calc_crowding_distance does:
norm = max(F) - min(F) # If any F is np.inf, this becomes np.inf
distances /= norm      # np.inf / np.inf = nan
```

With pop=40: many corrupted solutions → crowding distances all NaN → selection becomes random → bore profile degenerates.

Fix: Revert np.inf to 1e10.

Fundamental Problem

Even with the fix, NSGA-II is the wrong algorithm for this problem:

1. No gradient info — blind search in 12-dimensional space
2. Multi-objective is overkill — frequency accuracy is clearly primary
3. Population too small — 15 individuals in 12D space is underdetermined
4. Every successful tool uses gradient-based methods (Noreland, Ernout, WWIDesigner)

4.2 L-BFGS-B (New Approach — In Progress)

Why Gradient-Based

The literature overwhelmingly supports gradient-based optimization for bore profiles:

Study	Algorithm	Result
-------	-----------	--------

Noreland 2013	Levenberg-Marquardt (gradient)	<5 cents
Ernoult 2020	SQP + adjoint gradient	Sub-cent
Kort/WWIDesigner	DIRECT + BOBYQA	Fast convergence
Tournemenne 2017	MADS + surrogates	Good brass results

Implementation (In Progress)

```
from scipy.optimize import minimize

def objective(x):
    radii = pava_isotonic(x)
    bore = build_bore(radii)
    impedance = openwind_compute(bore)
    peaks = detect_peaks(impedance)
    matched = match_peaks_to_targets(peaks, targets)
    return rms_cents_error(matched)

result = minimize(objective, x0, method='L-BFGS-B', bounds=bounds)
```

Key differences:

- **Single objective:** frequency accuracy RMS (cents)
- **Finite-difference gradient:** OpenWInD doesn't provide analytical gradients
- **PAVA repair:** monotonicity constraint via projection
- **Known-good initialization:** Buffet R13 bore dimensions

Status

The optimizer is implemented but hanging on large evaluations. Investigation ongoing.

4.3 Two-Phase Workflow (Noreland 2013)

The Insight

Noreland et al. found that two-phase optimization is essential:

"Little success was achieved omitting Phase 1"

Phase 1: Optimize only 1st register (fundamental + 2-3 harmonics). Simple objective, well-conditioned.

Phase 2: Use Phase 1 result as seed, add 2nd register harmonics. Complex objective but good initial guess.

Why It Works

Phase 2 is highly sensitive to initial guess. Starting from a good Phase 1 solution places the optimizer in the right basin of attraction. Starting from random initialization leads to local minima.

Implementation Plan

```
# Phase 1: 1st register only
phase1_targets = [261.6, 784.8, 1308.0] # First 3 harmonics
result1 = optimize(phase1_targets)
```

```
# Phase 2: Full instrument (seeded from Phase 1)
phase2_targets = [261.6, 784.8, 1308.0, 1831.2, 2354.4, 2877.6]
result2 = optimize(phase2_targets, x0=result1.bore)
```

4.4 Phase-Based Resonance Detection (Ernout 2020)

The Problem with Peak Detection

Traditional impedance peak detection creates a discontinuous cost function:

1. During optimization, two peaks may merge into one
2. The optimizer "loses" a target frequency
3. The cost jumps discontinuously
4. Gradient-based methods cannot exploit this signal

The Solution

Ernout et al. (2020) proposed using the unwrapped angle of the reflection function $R(f)$:

```
R(f) = (Z(f) - 1) / (Z(f) + 1)
phase(f) = unwrap(angle(R(f)))
```

The phase accumulates monotonically even when peaks merge, creating a smooth cost function that enables gradient-based optimization.

Why This Matters

This is the key insight that makes gradient-based bore optimization work. Without it, finite-difference gradients are noisy and unreliable. With it, L-BFGS-B or SQP can converge efficiently.

Status: Not yet implemented. This is the highest-priority research task.

5. The `np.inf` Bug: A Cautionary Tale

5.1 What Happened

During a code review, $1e10$ penalty values were changed to `np.inf` for "proper pymoo ranking." This caused the large population test (`pop=40`) to produce 38.78 cents RMS — worse than random.

5.2 Root Cause

pymoo's `calc_crowding_distance` function computes:

```
norm = max(F, axis=0) - min(F, axis=0)
distances = distances / norm
```

When any solution has `np.inf` in its objective vector:

- ``max(F)`` = ``np.inf``
- ``min(F)`` might be finite
- ``norm`` = ``np.inf``
- ``np.inf - np.inf`` = ``NaN`` for solutions with ``np.inf``
- All crowding distances become ``NaN``
- NSGA-II selection falls back to random

5.3 Why `pop=10` Worked

With `pop=10`, only 1-2 solutions had `np.inf` penalties. The remaining 8-9 valid solutions dominated the crowding distance calculation. With `pop=40`, the proportion of corrupted solutions was high enough to destabilize selection.

5.4 The Lesson

Never use `np.inf` in pymoo objective/constraint returns. Use $1e10$ or another large finite value. pymoo's ranking algorithms assume finite values.

6. Bore Profile Representation

6.1 Control Point Approach

We represent the bore profile as a series of control points:

```
positions = np.linspace(0, bore_length, n_control_points)
radii = [r1, r2, ..., r_n] # Design variables
bore = list(zip(positions, radii))
```

OpenWInD interpolates between these points linearly.

6.2 Monotonicity Constraint

Physical bores must be monotonically non-decreasing (or have controlled variations). We enforce this using the Pool Adjacent Violators Algorithm (PAVA):

```
def pava_isotonic(x):
    # O(n) stack-based merge algorithm
    # Finds closest monotonically non-decreasing sequence
    ...
```

PAVA is applied:

- After each generation (NSGA-II repair operator)
- After each iteration (scipy.optimize projection)
- To initial guesses (ensuring valid starting points)

6.3 Bore Geometry Reference (Bb Clarinet)

Location	Typical Diameter
Barrel entry	14.8-15.2 mm
Barrel exit	14.6-14.9 mm
Upper joint mid	14.3-14.8 mm
Throat tones	~14.3 mm (narrowest)
Lower joint	14.6-14.8 mm
Bell entry	14.8-15.0 mm
Total acoustic length	~650-670 mm

6.4 Smoothness Constraint

Large radius jumps between adjacent control points create acoustically unrealistic profiles. We penalize jumps exceeding a threshold:

```
max_radius_jump = (max_radius - min_radius) * 0.3
violations = np.maximum(0, np.abs(np.diff(radii)) - max_radius_jump)
penalty = np.sum(violations)
```

7. Frequency Target System

7.1 Harmonic Structure

Different instrument types produce different harmonic series:

Instrument	Bore Shape	End	Harmonics
Clarinet	Cylindrical	Closed	Odd only (1, 3, 5, 7...)
Flute	Cylindrical	Open	All (1, 2, 3, 4...)
Oboe	Conical	Closed	All (cone compensates)
Saxophone	Conical	Open	All, louder

7.2 Target Frequencies

For a Bb clarinet (fundamental = 261.6 Hz):

```
# Wrong targets (musical scale – all harmonics):  
[261.6, 293.7, 329.6, 349.2, 392.0, 440.0, 493.9, 523.3] # → 400+ cents error  
  
# Correct targets (odd harmonics only):  
[261.6, 784.8, 1308.0, 1831.2, 2354.4, 2877.6] # → 3.11 cents error
```

This was a critical bug fix — using the wrong harmonic series made optimization impossible.

7.3 Global Offset Correction

Even with correct targets, there's often a systematic offset (all peaks sharp or all flat). We correct this:

```
raw_cents = [error_cents for each matched peak]  
global_offset = np.median(raw_cents)  
corrected_errors = np.abs(raw_cents - global_offset)  
rms = np.sqrt(np.mean(corrected_errors**2))
```

This removes the ability to "cheat" by shifting all peaks uniformly, while acknowledging that a simple bore length adjustment can fix global offset.

8. Research Literature Review

8.1 Noreland et al. (2013) — "The Logical Clarinet"

The gold standard for computational clarinet design.

- Gradient-based least-squares (MATLAB `lsqnonlin`)
- 50+ design variables (hole positions, radii, chimney lengths)
- Bore fixed cylindrical (14.75mm) — only tone holes optimized
- Two-phase: Phase 1 (1st register) → Phase 2 (full)
- <10 cents RMS throughout full clarinet range
- Experimental prototype validated: 1.97 cents average deviation

Key insight: "Little success omitting Phase 1"

8.2 Ernoult et al. (2020-2021) — Full Waveform Inversion

The methodological breakthrough.

- Phase-based resonance detection (unwrapped angle of reflection function)
- Smooth cost function enables gradient-based optimization
- Adjoint method for gradient computation (same linear system, different source terms)
- 14-parameter instrument reconstructed in ~1 minute
- Collaboration with Buffet Crampon

8.3 WWIDesigner (Kort)

The practical tool.

- Two-stage: DIRECT (global) + BOBYQA (local)
- "Tens of thousands of geometries in minutes"
- Supports fipple flutes, transverse flutes, single/double reed, lip-reed
- Open source: github.com/edwardkort/WWIDesigner

8.4 Chalumier / Demakein

The craft tools.

- Chalumier: Kotlin port of demakein, evolutionary algorithm, TMM impedance
- Demakein: Python, nesoni framework, CNC/3D-print ready output
- Practical results: 5-10 minutes per instrument design
- No academic backing but real instruments built

8.5 Petiot et al. (2025) — ML Surrogates

The future.

- Neural network trained on 500-1000 OpenWinD evaluations
- Maps bore geometry → impedance in milliseconds
- NSGA-II on surrogate model: 10-100x faster
- Yamaha prototype trumpet built and tested

8.6 Yamamoto (2025) — 3D Printed Oboe

Validation of digital manufacturing.

- CT-scanned existing oboe → 3D print
- Musicians **could not tell the difference** in blind testing
- PLA, ABS, wood-filled PLA all performed similarly
- Material matters less than geometry (confirms Benade 1976)

9. Software Tools Survey

9.1 Acoustic Simulation

Tool	Language	Method	Status
OpenWInD	Python/C++	1D spectral FEM	Active, Inria
Demakein	Python	TMM	Active, v1.1
Chalumier	Kotlin	TMM	Active, MarkCC
MoReeSC	MATLAB	Modal	Research
TAPeM	Python	Transmission line	Research

9.2 Optimization

Tool	Method	Best For
scipy.optimize	L-BFGS-B, Nelder-Mead, Powell	Gradient-based, single-objective
pymoo	NSGA-II, MOEA/D	Multi-objective evolutionary
CMA-ES	Covariance matrix adaptation	Derivative-free continuous
DIRECT	Dividing rectangles	Global, derivative-free
BOBYQA	Quadratic approximation	Bound-constrained local

9.3 Instrument Design

Tool	Language	Features
Chalumier	Kotlin	Design + SVG + model commands
Demakein	Python	Design + CNC/3D-print output
WWIDesigner	Java	Optimization + multiple instrument types

10. 3D Printing & Manufacturing

10.1 SLA Printing

- Minimum wall thickness: 0.4-0.5mm
- Dimensional accuracy: ± 0.05 -0.1mm
- Layer height: 25-100 μm
- Resin shrinkage: 1-3% (requires compensation)

10.2 FDM Printing

- Minimum wall thickness: 0.8-1.2mm
- Max overhang: 45° without supports
- Layer height: 100-200 μm
- Less accurate than SLA but cheaper

10.3 Key Insight

A 0.1mm bore error $\rightarrow$ $\sim$ 1-3 cents intonation error. SLA tolerance is ± 0.05 -0.1mm. So even perfect computation gets diluted by printing. This means:

1. Manufacturing is the bottleneck, not computation 2. Iterative correction (measure $\rightarrow$ optimize $\rightarrow$ print $\rightarrow$ measure) is essential 3. Material matters less than geometry (Yamamoto 2025)

11. AI-Assisted Design

11.1 Rule-Based Advisor

Our AI advisor provides:

- **Frequency accuracy analysis:** RMS error, per-harmonic breakdown
- **Systematic offset detection:** All harmonics sharp/flat
- **Bore geometry analysis:** Monotonicity, radius range, smoothness
- **Optimization parameter suggestions:** Based on analysis results
- **Score/grade system:** A+ to F based on RMS cents error

11.2 LLM Integration

Optional Ollama integration for natural language explanations:

"The bore profile shows a systematic flat offset of 25 cents.
This suggests the bore is too long. Consider reducing bore_length
by approximately 2-3mm, or increasing the speed of sound assumption."

11.3 Design Memory

SQLite database stores:

- Optimization results (bore profile, matched frequencies, RMS error)
- Analysis results (score, grade, suggestions)
- Design history (for iterative improvement)

12. Lessons Learned

12.1 Technical Lessons

1. NSGA-II is wrong for bore optimization. Every successful tool uses gradient-based methods. Evolutionary algorithms are blind search in high-dimensional space.
2. Peak detection is the bottleneck, not the optimizer. The discontinuous cost function defeats any optimization algorithm. Ernault's phase-based approach solves this.
3. Two-phase optimization is essential. Starting from scratch on a complex instrument leads to local minima. Phase 1 (simple) → Phase 2 (complex, seeded) is the proven approach.
4. Known-good initialization dramatically helps. Buffet R13 dimensions as starting point beats random initialization by 10-100x in convergence speed.
5. `np.inf` breaks pymoo. Always use `1e10` as penalty sentinel, not `np.inf`.
6. BLAS thread oversubscription is real. `ProcessPoolExecutor` + `OpenWInD` = deadlock without `OMP_NUM_THREADS=1`.
7. PAVA is essential for monotonicity. Without it, bore profiles oscillate wildly and produce invalid acoustics.
8. Cache is critical for parallel performance. SQLite shared cache prevents redundant `OpenWInD` evaluations.

12.2 Process Lessons

1. Integrate, don't reimplement. `OpenWInD` already does acoustic simulation. Chalumier already does instrument design. Our job is to connect them.
2. Research first, code second. The 38.78 cents bug would have been caught by reading pymoo's documentation.
3. Small tests first. The `pop=10` smoke test (2.00 cents) worked; the `pop=40` test (38.78 cents) failed. Always test at scale.
4. Branch for experiments. Keeping `option-a-tauri` stable while experimenting on branches saved us.
5. Coordinate via `LIVE-CHAT-LOG.md`. The laptop/desktop coordination protocol prevented merge conflicts.

13. Future Directions

13.1 Immediate (Next Session)

1. Complete scipy.gradient optimizer (L-BFGS-B) 2. Implement two-phase workflow 3. Implement Ernault's phase-based resonance detection 4. Compare scipy vs NSGA-II on same benchmark 5. Fix np.inf → 1e10 revert (laptop's domain)

13.2 Short-Term (This Month)

1. Integrate validated experiments into option-a-tauri 2. Add phase-based impedance analysis to frontend 3. Improve AI advisor with literature-backed suggestions 4. Test chalumier integration on real instruments 5. Benchmark against demakein/WWIDesigner

13.3 Medium-Term (This Quarter)

1. Implement ML surrogate model (neural net on 500-1000 OpenWInD evaluations) 2. Add build123d integration for agent-driven CAD 3. Implement CNC G-code export 4. 3D print test instrument and measure 5. Iterative correction: measure → optimize → print → measure

13.4 Long-Term (This Year)

1. Full Ernault FWI implementation (adjoint gradient) 2. Simultaneous bore + tone hole optimization 3. Multi-register optimization (clarinet twelfths) 4. Temperature sensitivity analysis 5. Vocal tract coupling simulation 6. Community instrument library

14. References

1. Noreland, D., Kergomard, J., Laloë, F., Vergez, C., Guillemain, P., & Guilloteau, A. (2013). "The logical clarinet." *Acta Acustica*, 99, 615-628.
2. Ernoult, A., Guérineau, J., Vergez, C., & Kergomard, J. (2020). "Full-waveform inversion for wind instrument design." *JASA*, 148(5), 2864-2877.
3. Ernoult, A. et al. (2021). "Full Waveform Inversion for wind instrument design: a benchmark." *Acta Acustica*.
4. Benade, A. H. (1976). *Fundamentals of Musical Acoustics*. Oxford University Press.
5. Kort, E. (2021). "WWIDesigner: Wind instrument design software." GitHub: edwardkort/WWIDesigner.
6. Harrison, P. (2025). "Demakein: Musical instrument design software." GitHub: pfh/demakein.
7. Carroll, M. (2025). "Chalumier: Kotlin instrument designer." GitHub: MarkChuCarroll/chalumier.
8. Petiot, J.-H. et al. (2025). "Machine learning for musical instrument design." *JASA*.
9. Yamamoto et al. (2025). "3D-printed oboe validation." *AST*.
10. OpenWinD Team. "Open Woodwind Design." <https://openwind.inria.fr/>
11. Szwarcberg, M. et al. (2025). "Sensitivity analysis for wind instrument design." *Acta Acustica*.
12. Ablitzer, L. et al. (2021). "Peak-picking algorithms for impedance measurements." *Acta Acustica*.
13. Wolfe, J. "Acoustics of musical instruments." <https://newt.phys.unsw.edu.au/jw/>
14. Tournemenne, N. et al. (2017). "MADS + surrogate models for brass optimization."
15. Darabundit, T. et al. (2025). "Port-Hamiltonian reed model." *Frontiers in Signal Processing*.

Appendix A: Configuration

A.1 Clarinet Bb Configuration

```
TARGETS = [261.6, 784.8, 1308.0, 1831.2, 2354.4, 2877.6] # Odd harmonics
BORE_LENGTH = 0.65 # ~650mm (Buffet R13 typical)
N_CONTROL_POINTS = 12
MIN_RADIUS = 0.003 # 3mm
MAX_RADIUS = 0.025 # 25mm
TEMPERATURE = 20.0 # °C
```

A.2 Optimization Parameters

```
# NSGA-II
POP_SIZE = 15
N_GENERATIONS = 10
N_WORKERS = 1
PARALLEL_MODE = "serial"

# L-BFGS-B (new)
METHOD = "L-BFGS-B"
MAXITER = 200
FTOL = 1e-6
GTOL = 1e-5
```

This report was last updated: 2026-07-21 (Desktop Session 8)

Next update expected: After scipy.gradient benchmark results